INDEXES TO THE JOURNAL

compiled by the

American Ceramic Society

VOL. 52, NO. 12 DECEMBER 21, 1969

AUTHOR INDEX TO THE JOURNAL

The reference number in parentheses refers to the *monthly* issue of *The Journal;* the numbers following are the *page* numbers.

Ainsworth, J. H., and Moore, R. E. Fracture behavior of thermally shocked aluminum oxide, (11) 628–29.
Albers, F. C. See Olsen, D. A.
Alderton, J. R. See Perry, G. S.
Allen, M. D. See Lindemer, T. B.
Almassy, M. Y. See Holt, J. B.
Altug, Inci. See Hair, M. L.
Anderson, Scott; Tandon, Dinesh; Kohlenberger, L. B.; and Blair, F. G. Strength of adhesion of dried clay slurries to window glass as a function of slurry pH, (9) 521.
Ansell, G. S. See Bradt, R. C.
Arase, Masahiko. See Okamoto, Shoichi.
Arend, H., and Kihlborg, L. Phase composition of reduced and reoxidized barium titanate, (2) 63–65.
Arndt, Jörg. Effect of impurities on densification of silica glass, (5) 285–86.
Ayer, J. E., and Soppet, F. E. Vibratory compaction: III, Rate of entry, (8) 414–16.

Babcock, C. L. Substructure classification of silicate glasses, (3) 151–53.
Baird, D. H. See Natansohn, S.
Bannister, M. J. Surface enthalpy of thoria gel, (12) 675–76.
Bartholomew, R. F., and Holland, H. J. Vitreous nature of some new inorganic glasses as shown by X-ray diffraction, (7) 402–403.
Basch, C. See Pearce, M. L.
Baskin, Y. Preparation and properties of ThP and ThP-UP solid solutions, (1) 54–55.
Baskin, Y., and Shalek, P. D. Melting point studies of the system UP-US, (6) 341–42.
Beall, G. H. See MacDowell, J. F.
Beals, R. J., Handwerk, J. H., and Wrona, B. J. Behavior of urania–rare-earth oxides at high temperatures, (11) 578–81.
Beals, R. J., and Kern, R. S. Irradiation testing (pulse conditions) of the ternary fuel system for the power burst facility, (7) 355–58.
Berard, M. F. See Wirkus, C. D.
Berard, M. F., and Wilder, D. R. Cation self-diffusion in polycrystalline Y_2O_3 and Er_2O_3, (2) 85–88.
Bergeron, C. G. See De Luca, J. P.
Bergman, J. G., Jr. See Crane, G. R.
Berkes, J. S., and White, W. B. Calculation of volume free energy of nucleation of crystalline phase from a multicomponent regular solution, (4) 231–32; Phase relations in the system Li_2O-B_2O_3-B_2O_3-NiO, (9) 481–84.
Bhatt, S. J., and Merchant, H. D. Influence of stoichiometry on lattice parameter in Fe_3O_4, NiO, and Ni-Fe ferrite, (8) 452–53.
Bigelow, W. C. See Tien, T. Y.
Biggar, G. M. The system CaO-NiO-SiO_2, (6) 316–17.
Biggar, G. M., and O'Hara, M. J. Monticellite and forsterite crystalline solutions, (5) 249–52.
Bieler, B. H. Further discussion of "Technique for estimating thickness of a thin section," (12) 678.
Birle, J. D., and Ehlers, E. G. High pressure phase of Al_2GeO_5, (5) 287–88.
Bishay, A. M., and Makar, L. Role of iron in calcium phosphate glasses, (11) 605–609.
Bittel, J. T., Sjodahl, L. H., and White, J. F. Steam oxidation kinetics and oxygen diffusion in UO_2 at high temperatures, (8) 446–51.
Blair, F. G. See Anderson, Scott.
Blank, S. L., and Pask, J. A. Solubility limits in the MgO-Fe_2O_3 system as determined by diffusion, (8) 460–61; Diffusion of iron and nickel in magnesium oxide single crystals, (12) 669–75.
Blickensderfer, Robert. See Henry, J. L.
Bradley, F. N. $Pb_2Ti_2O_5F_2$, a new pyrochlore, (2) 114.
Bradt, R. C., and Ansell, G. S. Aging in tetragonal ferroelectric barium titanate, (4) 192–99.
Bratton, R. J. Defect structure of Y_2O_3-ZrO_2 solid solutions, (4) 213; Initial sintering kinetics of $MgAl_2O_4$, (8) 417–19.
Bright, N. F. H. See Reeve, D. A.
Brindley, G. W. See Staley, W. G., Jr.
Brinen, J. S. See Williams, E. F.
Brook, R. J. Pore-grain boundary interactions and grain growth, (1) 56–57; Pores and grain growth kinetics, (6) 339–40.
Burggraaf, A. J., and Van Velzen, H. C. Glasses resistant to sodium vapor at temperatures to 700°C, (5) 238–42.
Burns, G. See Giess, E. A.

Cahn, J. W. The metastable liquidus and its effect on the crystallization of glass, (3) 118–21.
Cantin, M. R., Clauer, A. H., Seltzer, M. S., and Wilcox, B. A. Techniques for transmission electron microscopy and etch pitting of CoO single crystals, (2) 112–13.
Carlson, R. V. See Kerr, J. M.
Carnahan, R. D., Janowski, K. R., and Rossi, R. C. Elastic behavior of arc-cast zirconium carbide-graphite alloys, (9) 475–77.
Carter, R. E. See Lay, K. W.
Caslavska, V., Strickler, D. W., and Roy, Rustum. Optimization of properties of photoconductive oxide glasses, (3) 154–57.
Chaklader, A. C. D. See Sunderland, P. W.
Chang, L. L. Y., and Phillips, Bert. Phase relations in refractory metal-oxygen systems, (10) 527–33.
Charles, R. J. Effect of uniaxial stress on glass resistivity, (6) 350.
Chui, G. K., and Gardon, Robert. Interaction of radiation and conduction in glass, (10) 548–53.
Chyung, C. K. Secondary grain growth of Li_2O-Al_2O_3-SiO_2-TiO_2 glass-ceramics, (5) 242–45.
Clauer, A. H. See Cantin, M. R.
Clougherty, E. V. See Kalish, David.
Coble, R. L. See Jones, T. P.
Compton, D. M. J., and Firle, T. E. Reduction of TiO_2 powders and rutile single crystals, (9) 515–16.
Cooper, A. R. See Krohn, D. A.
Cooper, A. R., and Krohn, D. A. Strengthening of glass fibers: II, Ion exchange, (12) 665–69.
Crane, G. R., Bergman, J. G., Jr., and Glass, A. M. Ammonium iodate—a potentially useful nonlinear optical material, (12) 655–57.
Cutler, I. B. Effect of water vapor on the sintering of glass powder compacts, (1) 11–13; Sintering of glass powders during constant rates of heating, (1) 14–17; see also McAllister, P. V.

Daimon, Masaki. See Kondo, Renichi.
Day, D. E. See Shelby, J. E., Jr.
Day, D. E., and Steinkamp, W. E. Mechanical damping spectrum for mixed-alkali R_2O-Al_2O_3-$6SiO_2$ glasses, (11) 571–74.
Day, R. B., and Johnston, W. A. Mechanical behavior of lithium fluoride at high temperatures, (11) 595–99.
DeHoff, R. T. See Gokularathnam, C. V.
De Luca, J. P., and Bergeron, C. G. Diffusion of lead in a lead borate glass, (11) 629–30.
De Luca, J. P., Eagan, R. J., and Bergeron, C. G. Crystallization of PbO-$2B_2O_3$ from its supercooled melt, (6) 322–26.
DePoorter, G. L. Evaluation of a statistical thermodynamic method for calculating the composition dependence of chemical potentials in nonstoichiometric zirconium carbide, (6) 311–15.
DeVries, R. C., and Roth, W. L. Critical evaluation of the literature data on beta alumina and related phases: I, Phase equilibria and characterization of beta alumina phases, (7) 364–69.
de Waal, H. Influence of proton exchange on internal friction in alkali silicate glasses, (3) 165–66.
Dick, Egon, and Peter, Klaus. Generation of deep cracks in glass, (6) 338–39.
Dolloff, R. T. See Mazdiyasni, K. S.
Dorrian, J. F. See Malone, J. A.
Duffy, J. A., and Ingram, M. D. Formation of acetate glasses, (4) 224–25.
Duncan, J. F., MacKenzie, K. J. D., and Foster, P. K. Kinetics and mechanism of high-temperature reactions of kaolinite minerals, (2) 74–77.

Eagan, R. J. See De Luca, J. P.
Edelson, D., Jaeger, R. E., and Williams, J. C. Transient effects of nuclear radiation on the dielectric properties of refractory low-loss ceramics at microwave frequencies, (7) 359–63.
Ehlers, E. G. Discussion of "Technique for estimating thickness of a thin section," (8) 451; see also Birle, J. D.
Ejiri, Koichi. See Setaka, Nobuo.
Eppler, R. A. Crystallization and phase transformation in TiO_2-opacified porcelain enamels: I, Theory, (2) 89–94; II, Comparison of theory with experiment, (2) 94–99.
Eppler, R. A., and Spencer-Strong, G. H. Role of P_2O_5 in TiO_2-opacified porcelain enamels, (5) 263–66.
Ernsberger, F. M. Reply to comment by Martin Goldstein, (5) 292; see also, Dick, Egon, and Peter, Klaus, (6) 339; Levengood, W. C., (7) 404.
Everhart, J. O. See Schorr, J. R.

Falckenberg, H. R. See Grabmaier, J. G.
Fine, M. E. See Woods, K. N.
Firle, T. E. See Compton, D. M. J.
Fischer, G. R. See Ostertag, W.
Fix, W., Heymann, H., and Heinke, R. Subsolidus relations in the system $2CaO$-SiO_2-$3CaO$-P_2O_5, (6) 346–47.
Foster, P. K. See Duncan, J. F.
Foster, W. R. Discussion of "Silica transformations in the system PbO-SiO_2," (6) 345–46; see also Semler, C. E.
Freiman, S. W. See Gokularathnam, C. V.
Freiman, S. W., and Hench, L. L. Further analysis of glass crystallization kinetics, (2) 111–12.
French, D. N. X-ray stress analysis of WC-Co cermets: I, Procedures, (5) 267–71; II, Temperature stresses, (5) 271–75.
Friedberg, A. L. See Tummala, R. R.
Frischat, G. H. Evidence for calcium and aluminum diffusion in SiO_2 glass, (11) 625.
Fujino, Takeo, and Naito, Keiji. Solubility of KUO_3 in $BaUO_3$, (11) 574–77.
Fulrath, R. M. See Moon, R. L.

Gardon, Robert. See Chui, G. K.; Narayanaswamy, O. S.
Gejyo, Tetsuo. See Minagawa, Shigekazu.
Giess, E. A., Scott, B. A., Burns, G., O'Kane, D. F., and Segmüller, A. Alkali strontium-barium-lead niobate systems with a tungsten bronze structure: crystallographic properties and Curie points, (5) 276–81.

Glass, A. M. See Crane, G. R.
Gokhale, K. V. G. K. See Ramani, S. V.
Gokularathnam, C. V., Freiman, S. W., DeHoff, R. T., and Hench, L. L. Thickness error in quantitative transmission microscopy of ceramics, (6) 327–31.
Goldstein, Martin. Comments on "Role of densification in deformation of glasses under point loading," (5) 291.
Gordon, R. S. See Terwilliger, G. R.
Grabmaier, J. G., and Falckenberg, H. R. Strength of flame-fusion-grown magnesium-aluminum spinel, (12) 648–50.
Greene, C. H., and Platts, D. R. Behavior of bubbles of oxygen and sulfur dioxide in soda-lime glass, (2) 106–109.
Greskovich, C. See Stubican, V. S.
Grossman, D. G., and Isard, J. O. Lead titanate glass-ceramics, (4) 230–31.
Groves, G. W. See Shockey, D. A.
Gulden, T. D. Mechanical properties of polycrystalline β-SiC, (11) 585–90.
Gupta, T. K. Comments on "Sintering kinetics based on geometric models," (3) 166–67.
Gurganus, T. B. See Manning, C. R., Jr.

Hadden, J. C., Rogers, E. A., and Williams, D. J. Absorption spectra of first row transition metal ions in phosphate glasses, (1) 52.
Haggerty, J. S. See Lee, D. W.
Hair, M. L. The structure of alkali glass, (12) 677–78.
Hair, M. L., and Altug, Inci. Ion-selective properties of a polished porous glass, (2) 65–68.
Handwerk, J. H. See Beals, R. J.
Hansen, E. E., Munir, Z. A., and Mitchell, M. J. Sublimation pressure and sublimation coefficient of single-crystal lead selenide, (11) 610–12.
Hasselman, D. P. H. Micromechanical thermal stresses and thermal stress resistance of porous brittle ceramics, (4) 215–16; Griffith criterion and thermal shock resistance of single-phase versus multiphase brittle ceramics, (5) 288–89; Griffith flaws and the effect of porosity on tensile strength of brittle ceramics, (8) 457; Analysis of the strain at fracture of brittle solids with high densities of microcracks, (8) 458–59; Crack growth and creep in brittle ceramics, (9) 517–18; Unified theory of thermal shock fracture initiation and crack propagation in brittle ceramics, (11) 600–604.
Hayakawa, Shigeru. See Matsuo, Yoshihiro.
Heinke, R. See Fix, W.
Held, P. C., and Wilder, D. R. High-temperature hemispherical spectral emittance of uranium oxides at 0.65 and 0.70 μm, (4) 182–86.
Hench, L. L. See Freiman, S. W.; Gokularathnam, C. V.; Kinser, D. L.
Henry, J. L., and Blickensderfer, Robert. The quaternary system U-C-O-N at 1700°C, (10) 534–39.
Heuer, A. H. Transgranular and intergranular fracture in polycrystalline alumina, (9) 510–11.
Heuer, A. H., Sellers, D. J., and Rhodes, W. H. Hot-working of aluminum oxide: I, Primary recrystallization and texture, (9) 468–74.
Heymann, H. See Fix, W.
Hirai, Toshio, and Yamasaki, Nakamichi. Tentative method for crystallite size determination of beryllium oxide, (6) 343.
Hoar, E. A. See Ostertag, W.
Hodgson, W. G. See Williams, E. F.
Hoenig, C. L. See Stout, N. D.
Holland, H. J. See Bartholomew, R. F.
Holt, J. B., and Almassy, M. Y. Nitrogen diffusion in uranium nitride as measured by alpha particle activation of ^{15}N, (12) 631–35.
Holt, J. B., Sockel, H. G., and Schmalzried, H. Mobility of cation vacancies in the solid solution KCl–RbCl, (7) 375–78.
Horton, R. M. Oxidation kinetics of powdered silicon nitride, (3) 121–24.
Hummel, F. A. See Nath, D. K.
Hunter, O., Jr. See Manning, W. R.

Ingram, M. D. See Duffy, J. A.
Inoue, Zenzaburo. See Setaka, Nobuo.
Isard, J. O. See Grossman, D. G.

Jaeger, R. E. See Edelson, D.
Janowski, K. R. See Carnahan, R. D.
Johnson, D. L. Discussion of "Time and length corrections in the analysis of the initial stages of diffusion-controlled sintering," (10) 562–63.
Johnson, H. B., and Kessler, Frank. Kaolinite dehydroxylation kinetics, (4) 199–204.
Johnson, Irving. See Sharma, R. A.
Johnson, R. E. See Olsen, D. A.
Johnston, W. A. See Day, R. B.
Jones, N. W. Discussion of "Subsolidus equilibria in the system MgO-GeO$_2$-MgF$_2$," (4) 220–21.
Jones, T. P., Coble, R. L., and Mogab, C. J. Defect diffusion in single crystal aluminum oxide, (6) 331–34.
Kalish, David, and Clougherty, E. V. Densification mechanisms in high-pressure hot-pressing of HfB_2, (1) 26–30.
Kalish, David, Clougherty, E. V., and Kreder, Konstantine. Strength, fracture mode, and thermal stress resistance of HfB_2 and ZrB_2, (1) 30–36.
Kanamaru, Fumikazu. See Matsuo, Yoshihiro.
Kawamoto, Yoji, and Tsuchihashi, Shoji. Glass-forming regions and structure of glasses in the system Ge-S, (11) 626–27.
Kay, H. F. See Reed, J. S.
Kern, R. S. See Beals, R. J.
Kerr, J. M., Carlson, R. V., and Shield, W. A. Alpha autoradiography of (U,Pu)O$_2$ microspheres, (8) 461–62.
Kessler, Frank. See Johnson, H. B.
Kihlborg, L. See Arend, H.
Kinser, D. L., and Hench, L. L. Electrode polarization in alkali silicate glasses, (12) 638–41.
Kirchner, H. P. Thermal expansion anisotropy of oxides and oxide solid solution, (7) 379–86.
Kivel, Joseph. See Olsen, D. A.
Kohlenberger, L. B. See Anderson, Scott.
Koizumi, Mitsue. See Matsuo, Yoshihiro.
Kondo, Renichi, and Daimon, Masaki. Early hydration of tricalcium silicate: A solid reaction with induction and acceleration periods, (9) 503–508.
Korda, E. J., Pruden, L. H., and Williams, J. P. Three-dimensional and stereo observations in glass and ceramic systems, (1) 46–51.
Kotera, Yoshihide, and Yonemura, Michiko. Role of catalysts in the transformation of germanium dioxide, (4) 210–13.
Koyama, Karl. Thermal conductivity of magnesium fluoride between 25° and 900°C, (4) 222–23.
Kreder, Konstantine. See Kalish, David.
Kreidl, N. J., and Maklad, M. S. Effect of water content on phase separation in soda-silica glasses, (9) 508–509.
Krohn, D. A. See Cooper, A. R.
Krohn, D. A., and Cooper, A. R. Strengthening of glass fibers: I, Cladding, (12) 661–64.

Lay, K. W., and Carter, R. E. Time and length corrections in the analysis of the initial stages of diffusion-controlled sintering, (4) 189–91.
Lee, D. W., and Haggerty, J. S. Plasticity and creep in single crystals of zirconium carbide, (12) 641–47.
Leitnaker, J. M. See Lindemer, T. B.; Spear, K. E.
Levengood, W. C. Dislocations and surface flaws on glass, (7) 403–404.
Levin, E. M. X-ray determination of the thermal expansion of silver nitrate, (1) 53–54.
Li, C. T. See Weaver, E. A.
Lindemer, T. B., Allen, M. D., and Leitnaker, J. M. Kinetics of the graphite-uranium dioxide reaction from 1400° to 1756°C, (5) 233–37.
Low, M. J. D., Ramasubramanian, N., and Ramamurthy, P. Reaction of HF with porous glass, (3) 124–27.
Lu, W-K. See Tyrolerova, P.
Lundy, T. S. See Reimann, D. K.

Maass, Klaus-Eckart. Properties of Ba_3P_2 and other barium phosphides, (10) 566–67.
McAllister, P. V., and Cutler, I. B. Evaluation of thermal grooving data, (6) 348–49.
McCarthy, G. J., White, W. B., and Roy, Rustum. Phase equilibria in the 1375°C isotherm of the system Sr-Ti-O, (9) 463–67.
McCormick, G. R. Reply to "Discussion of 'Subsolidus equilibria in the system MgO-GeO$_2$-MgF$_2$'," (4) 221.
McDaniel, C. L. See Schneider, S. J.
MacDowell, J. F., and Beall, G. H. Immiscibility and crystallization in Al$_2$O$_3$-SiO$_2$ glasses, (1) 17–25.
MacEwan, J. R., and Stoute, R. L. Annealing of irradiation-induced thermal conductivity changes in ThO$_2$-1.3 wt% UO$_2$, (3) 160–65.
McGee, T. D. See Smiser, L. W.; Vojnovich, T.
McHargue, C. J. See Yust, C. S.
MacKenzie, K. J. D. Infrared kinetic study of high-temperature reactions of synthetic kaolinite, (12) 635–37; see also Duncan, J. F.
McKinstry, H. A. See Stubican, V. S.
McNamara, V. M. See Weston, T. B.
Makar, L. See Bishay, A. M.
Maklad, M. S. See Kreidl, N. J.
Malone, J. A., Dorrian, J. F., Muller, O., and Newnham, R. E. Crystal structure of Lu_2TeO_6, (10) 570.
Manghnani, M. H. See Sokolowski, T. J.
Manning, C. R., Jr., and Gurganus, T. B. Wetting of binary aluminum alloys in contact with Be, B_4C, and graphite, (3) 115–18.
Manning, W. R., and Hunter, O., Jr. Elastic properties of polycrystalline yttrium oxide, holmium oxide, and erbium oxide: High-temperature measurements, (9) 492–96.
Manning, W. R., Hunter, O., Jr., and Powell, B. R., Jr. Elastic properties of polycrystalline yttrium oxide, dysprosium oxide, holmium oxide, and erbium oxide: Room temperature measurements, (8) 436–42.
Masaki, Daimon. See Kondo, Renichi.
Matsuo, Yoshihiro; Sasaki, Hiromu; Hayakawa, Shigeru; Kanamaru, Fumikazu; and Koizumi, Mitsue. High-pressure synthesis of perovskite-type Pb(Zn$_{1/3}$Nb$_{2/3}$)O$_3$, (9) 516–17.
Mazdiyasni, K. S., Dolloff, R. T., and Smith, J. S., II. Preparation of high-purity submicron barium titanate powders, (10) 523–26.
Mehta, P. K. Morphology of calcium sulfoaluminate hydrates, (9) 521–22.
Mendelson, M. I. Average grain size in polycrystalline ceramics, (8) 443–46.
Merchant, H. D. See Bhatt, S. J.; Weaver, E. A.
Mills, J. J. High shear rate rheology of liquid glass, (12) 680.
Minagawa, Shigekazu, and Gejyo, Tetsuo. X-ray microtopographs of alpha alumina whiskers, (5) 282–84.
Mitchell, M. J. See Hansen, E. E.
Mogab, C. J. See Jones, T. P.
Montgomery, T. S. Lattice spacings of periclase-chromite solid solutions, (1) 59–60; Optical reflectance spectra of Cr^{3+} in MgO solid solutions, (9) 478–81.
Moon, R. L., and Fulrath, R. M. Vaporization and surface phases in the lead zirconate-lead titanate system, (10) 565–66.
Moore, R. E. See Ainsworth, J. H.
Morgan, A. M. See Sewell, P. A.
Morgan, C. S. Activation energy in sintering, (8) 453–54.
Moss, H. I. See Stollar, W. P.
Muller, O. See Malone, J. A.
Munir, Z. A. See Hansen, E. E.

Nadeau, J. S. Dependence of flow stress on nonstoichiometry in oxygen-rich uranium dioxide at high temperatures, (1) 1–7; Reply to Yust and McHargue comments, (10) 569–70.
Naito, Keiji. See Fujino, Takeo.
Narayanaswamy, O. S., and Gardon, Robert. Calculation of residual stresses in glass, (10) 554–58.
Nassau, K., and Shiever, J. W. Cupric oxide-molybdenum oxide phase diagram in air and in oxygen, (1) 36–40.
Natansohn, S., and Baird, D. H. Effect of synthesis parameters on the magnetic properties of manganese zinc ferrites, (3) 127–32.
Nath, D. K., and Hummel, F. A. Synthesis of vanadate and arsenate spodiosites and interpretation of optical spectra of manganese-doped Sr_2VO_4Cl, (1) 8–10.
Nelson, J. A. See Stuvgis, D. H.
Neumann, H., and Wijn, H. P. J. Correction: Polycrystalline hexagonal Fe_2W with varying ferrous content, (2) 109.
Newnham, R. E. See Malone, J. A.
Nicholson, P. S. Technique for estimating thickness of a thin section, (4) 221–22.
Noguchi, Tetsuo; Ōkubo, Tsutomu; and Yonemochi, Osamu. Reactions in the system ZrO$_2$-SrO, (4) 178–81.
Nordine, P. C. See Stout, N. D.

O'Hara, M. J. See Biggar, G. M.
Ohring, Milton, and Tai, King Lien. Gas-filled bubbles in ionic solids, (10) 559–62.
Okamoto, Shoichi; Arase, Masahiko; and Okamoto, Shoko. Reactive hot-pressing of $Ni_{1-3}Fe_{2/3}$ oxyhydroxides, (2) 110–11.
Okamoto, Shoko. See Okamoto, Shoichi.
O'Kane, D. F. See Giess, E. A.
Ōkubo, Tsutomu. See Noguchi, Tetsuo.
Olsen, D. A., Johnson, R. E., Kivel, Joseph, and Albers, F. C. Kinetics of leaching of lead glass by ethylenediaminetetraacetic acid, (6) 318–22.
Ostertag, Werner. Magnetic susceptibility of uranium(IV) glasses, (1) 61–62.
Ostertag, W., Hoar, E. A., and Fischer, G. R. Stereographic projection of crystal structures: Example, β-spodumene, (4) 224.

Pask, J. A. See Blank, S. L.
Paterson, M. S. See Weaver, C. W.
Paul, A., and Rusin, J. M. Ultraviolet absorption of pentavalent vanadium in binary alkali borate glasses, (12) 657–60.
Pearce, M. L., and Basch, C. Oxidation kinetics of single crystal titanium nitride by optical measurements, (9) 496–98.
Perry, G. S., and Alderton, J. R. Dielectric properties of titanate-alumina ceramics, (6) 348.
Peter, Klaus. See Dick, Egon.
Phillips, Bert. See Chang, L. L. Y.
Platts, D. R. See Greene, C. H.
Pointon, A. J., and Saull, R. C. Solid state reactions in lithium ferrite, (3) 157–60.
Poplawsky, R. P. See Weaver, E. A.
Powell, B. R., Jr. See Manning, W. R.
Prunaris, A. L. Coaxing effect during the dynamic fatigue of glass, (6) 340–41.

Prentice, J. L. Scanning electron microscopy of BeO whiskers formed on the surface of burning beryllium droplets, (10) 564–65.
Progelhof, R. C., and Throne, J. L. Effect of surface porosity on emittance of an opaque substance, (4) 227–28.
Pruden, L. H. See Korda, E. J.

Radosevich, L. G., and Williams, W. S. Low-temperature thermal conductivity of uranium nitride, (9) 514.
Ramamurthy, P. See Low, M. J. D.
Ramani, S. V., Subbarao, E. C., and Gokhale, K. V. G. K. Kinetics of zircon synthesis, (11) 619–23.
Ramasubramanian, N. See Low, M. J. D.
Ramsey, T. H., and Rice, S. B. Effects of heat treatment on electron-gun-deposited SiO_2 films, (4) 225–26.
Rase, D. E. Comments on "Silica transformations in the system PbO-SiO_2," (6) 345.
Reed, J. S., and Kay, H. F. Optical spectra of 3*d* transition metal ions in MgO·$3.5Al_2O_3$ spinel, (6) 307–11.
Reeve, D. A., and Bright, N. F. H. Phase relations in the system CaO-Ta_2O_5-SiO_2, (8) 405–409.
Reimann, D. K., and Lundy, T. S. Diffusion of ^{235}U in UO_2, (9) 511–12.
Rhodes, W. H. See Heuer, A. H.
Rice, R. W. CaO: I, Fabrication and characterization, (8) 420–27; II, Properties, (8) 428–36.
Rice, S. B. See Ramsey, T. H.
Riewald, P. G., and Van Vlack, L. H. Slip behavior and hardness indentations in MnSe and MnSe-MnS solid solutions, (7) 370–75.
Robinson, H. A. Physical properties and structure of silicate glasses: I, Additive relations in alkali binary glasses, (7) 392–99.
Rogers, E. A. See Haddon, J. C.
Rosen, J. J. See Tien, T. Y.
Rossi, R. C. Thermal expansion of BeO-SiC composites, (5) 290–91; see also Carnahan, R. D.
Roth, W. L. See DeVries, R. C.
Roy, Rustum. Gel route to homogeneous glass preparation, (6) 344; see also Cáslavská, V.; McCarthy, G. J.; Sargeant, P. T.
Roy, S. K. Characterization of porosity in porcelain-bonded porous almuina ceramics, (10) 543–48.
Rusin, J. M. See Paul, A.

Sakka, Sumio. Phototropy of alkaline earth tungstates doped with bismuth, (2) 69–73.
Sanvordenker, V. See Tien, T. Y.
Sarjeant, P. T., and Roy, Rustum. Ti^{4+} coordination in glasses in RO-TiO_2 systems, (1) 57–58.
Sasaki, Hiromu. See Matsuo, Yoshihiro.
Satava, Vladimir, and Skvara, Frantisek. Mechanism and kinetics of the decomposition of solids by a thermogravimetric method, (11) 591–95.
Saull, R. C. See Pointon, A. J.
Schmalzried, H. See Holt, J. B.
Schneider, S. J., and McDaniel, C. L. The BaO-Pt system in air, (9) 518–19.
Schoenlaub, R. A. Oxidation of pyrite, (1) 40–43.
Schorr, J. R., and Everhart, J. O. Thermal behavior of pyrite and its relation to carbon and sulfur oxidation in clays, (7) 351–54.
Scott, B. A. See Giess, E. A.
Scott, W. D. Impurity deposits on alumina crystals, (8) 454–55.
Segmüller, A. See Giess, E. A.
Sellers, D. J. See Heuer, A. H.
Seltzer, M. S. See Cantin, M. R.
Semler, C. E., and Foster, W. R. Studies in the ternary system BaO-Al_2O_3-SiO_2: IV, The system celsian-alumina and the join celsian-mullite, (12) 679–80.
Seo, Hirokichi. See Takamori, Takeshi.
Setaka, Nobuo, and Ejiri, Koichi. Influence of oxygen on growth of 2H-SiC whiskers, (1) 60–61; Evidence for 2H-SiC whisker growth by a screw dislocation process, (7) 400.
Setaka, Nobuo, and Inoue, Zenzaburo. Beta silicon carbide whiskers prepared on a molybdenum substrate, (11) 624.
Sewell, P. A., and Morgan, A. M. Methanol vapor adsorption on silica and soda-lime-silica glass, (3) 136–38.
Shaffer, P. T. B. Comments regarding the structure of beta SiC whiskers, (1) 51.
Shalek, P. D. See Baskin, Y.
Sharma, R. A., and Johnson, Irving. Phase diagrams for the systems $MgCl_2$-MgF_2, $CaCl_2$-MgF_2, and NaCl-MgF_2, (11) 612–15.
Shelby, J. E., Jr., and Day, D. E. Mechanical relaxations in mixed-alkali silicate glasses: I, Results, (4) 169–74.
Shield, W. A. See Kerr, J. M.
Shiever, J. W. See Nassau, K.
Shiraishi, Takashi. See Yamaguchi, Takashi.
Shockey, D. A., and Groves, G. W. Origin of water-induced toughening in MgO crystals, (2) 82–85.
Shore, R. G., and Wanklyn, B. M. The systems PbF_2-AlF_3 and CaF_2-AlF_3, (2) 79–81.
Sjodahl, L. H. X-ray measurement of strain in TaC due to composition gradients, (4) 216–17; see also Bittel, J. T.
Skvara, Frantisek. See Satava, Vladimir.
Smiser, L. W., and McGee, T. D. Transmission electron microscopy of sodium chloride, (12) 681–82.
Smith, D. E., Tien, T. Y., and Van Vlack, L. H. The system NiO-CaO, (8) 459–60.
Smith, J. S., II. See Mazdiyasni, K. S.
Sockel, H. G. See Holt, J. B.
Soga, Naohiro. Elastic constants of polycrystalline BeO as a function of pressure and temperature, (5) 246–49.
Sokolowski, T. J., and Manghnani, M. H. Adiabatic elastic moduli of vitreous calcium aluminates to 3.5 kilobars, (10) 539–42.
Soppet, F. E. See Ayer, J. E.
Spear, K. E., and Leitnaker, J. M. Formation of active carbon in twin-crucible studies of vanadium carbonitride solutions, (5) 257–62.
Spencer-Strong, G. H. See Eppler, R. A.
Staley, W. G., Jr., and Brindley, G. W. Development of noncrystalline material in subsolidus reactions between silica and alumina, (11) 616–19.
Steinkamp, W. E. See Day, D. E.
Steverding, B. Brittleness and impact resistance, (3) 133–36.
Stoller, W. P., and Moss, H. I. Pressure sintering of gallium arsenide, (4) 204–10.
Stout, N. D., Hoenig, C. L., and Nordine, P. C. Knudsen cell studies of the vaporization of samarium dicarbide, (3) 145–51.
Stoute, R. L. See MacEwan, J. R.
Strickler, D. W. See Caslavska, V.
Stubican, V. S., Greskovich, C., and McKinstry, H. A. Kinetics of precipitation and measurements of strain in the system MgO-Al_2O_3-Cr_2O_3, (4) 174–77.
Sturgis, D. H., and Nelson, J. A. Effects of gaseous adsorbates on the compaction of ultrafine active alumina powder, (5) 286–87.
Subbarao, E. C. See Ramani, S. V.
Sunderland, P. W., and Chaklader, A. C. D. Creep during dehydroxylation of magnesium hydroxide, (8) 410–14.

Tai, King Lien. See Ohring, Milton.
Takamori, Takeshi; Seo, Hirokichi; and Tashiro, Minoru. Polarization effects in semiconducting oxide glasses containing Na_2O, (9) 513–14; Electrical resistivity of titanium-containing glasses, (11) 582–85.
Tandon, Dinesh. See Anderson, Scott.
Tashiro, Minoru. See Takamori, Takeshi.
Terwilliger, G. R., and Gordon, R. S. Correlations between models for time-dependent creep with concurrent grain growth, (4) 218–19.
Throne, J. L. See Progelhof, R. C.
Tien, T. Y. See Smith, D. E.
Tien, T. Y., Rosen, J. J., Bigelow, W. C., and Sanvordenker, V. Microhardness of TiO_2-Nb_2O_5 solid solutions, (9) 520.
Tischer, R. E. Heat of annealing in simple alkali silicate glasses, (9) 499–503.
Tokar, Michael. Microstructure and magnetic properties of lead ferrite, (6) 302–306.
Tsuchihashi, Shoji. See Kawamoto, Yoji.
Tummala, R. R., and Friedberg, A. L. Strength of glass-crystal composites, (4) 228–29.
Tyrolerova, P., and Lu, W-K. Volume change on freezing of Al_2O_3, (2) 77–79; Volume change of mullite on solidification, (5) 292.

Van Velzen, H. C. See Burggraaf, A. J.
Van Vlack, L. H. See Riewald, P. G.; Smith, D. E.
Vijh, A. K. Electrochemical oxidation of semiconducting ceramic barium titanate, (4) 219.
Vojnovich, T., and McGee, T. D. Determination of donor gradients within surface barriers formed on dense Gd-doped barium titanates, (7) 386–92; correction, (10) 567.

Wagstaff, F. E. Crystallization and melting kinetics of cristobalite, (12) 650–54.
Wanklyn, B. M. See Shore, R. G.
Weaver, C. W., and Paterson, M. S. Deformation of cube-oriented MgO crystals under pressure, (6) 293–302.
Weaver, E. A., and Li, C. T. Growth of complex oxide single crystals from fluoride melts, (6) 335–38.
Weaver, E. A., Merchant, H. D., and Poplawsky, R. P. Growth of Fe-Ni oxide spinel single-crystals by arc image techniques, (4) 214–15.
Webster, A. H. See Weston, T. B.
Weston, T. B., Webster, A. H., and McNamara, V. M. Lead zirconate-lead titanate piezoelectric ceramics with iron oxide additions, (5) 253–57.
White, J. F. See Bittel, J. T.
White, W. B. See Berkes, J. S.; McCarthy, G. J.
Wiederhorn, S. M. Fracture surface energy of glass, (2) 99–105; Fracture of sapphire, (9) 485–91.
Wijn, H. P. J. See Neumann, H.
Wilcox, B. A. See Cantin, M. R.
Wilder, D. R. See Berard, M. F.; Held, P. C.; Wirkus, C. D.
Williams, D. J. See Haddon, J. C.
Williams, E. F., Hodgson, W. G., and Brinen, J. S. Synthetic photochromic sodalite, (3) 139–45.
Williams, J. C. See Edelson, D.
Williams, J. P. See Korda, E. J.
Williams, W. S. See Radosevich, L. G.
Wirkus, C. D., Berard, M. F., and Wilder, D. R. Oxygen diffusion in Gd_2O_3, (8) 456.
Woods, K. N., and Fine, M. E. Nucleation and growth of magnesioferrite in MgO containing 0.9% Fe^{2+}, (4) 186–88.
Wrona, B. J. See Beals, R. J.

Yamaguchi, Takashi, and Shiraishi, Takashi. Eutectoid decomposition of $CuFe_2O_4$-Fe_3O_4 spinel solid solution including $CuFe_3O_5$, (7) 401.
Yamasaki, Nakamichi. See Hirai, Toshio.
Yonemochi, Osamu. See Noguchi, Tetsuo.
Yonemura, Michiko. See Kotera, Yoshihide.
Young, J. F. Influence of tricalcium aluminate on the hydration of calicum silicates, (1) 44–46.
Yust, C. S., and McHargue, C. J. Comments on "Dependence of flow stress on nonstoichiometry in oxygen-rich uranium dioxide at high temperature," (10) 568–69.

SUBJECT INDEX TO THE JOURNAL

Volume 52, 1969

The reference number in parentheses refers to the *monthly* issue of *The Journal;* the number following is the *page* number.

Abrasives. See *Aluminum, oxide; Polishing; Silicon, carbide.*
Absorption, ultraviolet, of pentavalent vanadium in binary alkali borate glasses, (12) 657.
Acid, ethylenediaminetetraacetic, kinetics of leaching of lead glass by, (6) 318.
Activation, α-particle, of ^{13}N, use to measure nitrogen diffusion in UN, (12) 631.
Adhesion, strength of, of dried clay slurries to window glass as function of slurry pH, (9) 521.
Adsorption, of gases, effects on compaction of ultrafine active alumina powder, (5) 286.
of methanol vapor on silica and soda-lime-silica glass, (3) 136.
Aging, in tetragonal ferroelectric barium titanate, (4) 192.
Alites, hydration of, (1) 44.
Alloys, ZrC-graphite, arc-cast, elastic behavior, (9) 475.
binary aluminum, wetting in contact with Be, B_4C, and graphite, (3) 115.
Alumina. See *Aluminum, oxide.*
Aluminates, tricalcium, influence on hydration of Ca silicates, (1) 44.
Aluminum, Al_2GeO_5, high-pressure phase, (5) 287.
diffusion in SiO_2 glass, evidence for, (11) 625.
oxide. See also *Corundum; Refractories.*
α-, whiskers, X-ray microtopography, (5) 282.
β-, and related phases, critical evaluation of literature data: I, phase equilibria and characterization of β-alumina phases, (7) 364.
ceramics, porcelain-bonded porous, characterization of porosity in, (10) 543.
crystals, impurity deposits on, (8) 454.
polycrystalline, hot-working: I, primary recrystallization and texture, (9) 468.
polycrystalline, transgranular and intergranular fracture in, (9) 510.
polycrystalline, transient effects of nuclear radiation on dielectric properties of, at microwave frequencies, (7) 359.
single crystal, defect diffusion coefficient, (6) 331.
subsolidus reactions with silica, development of noncrystalline material in, (11) 616.
thermally shocked, fracture behavior, (11) 628.
ultrafine active powder, effects of gaseous adsorbates on compaction, (5) 286.
volume change on freezing, (2) 77.
systems. See *Systems.*
Ammonium, iodate, potentially useful optical material, (12) 655.
Analysis. See also *Microscopy; Particles; Thermal analysis; Thermogravimetry; X rays.*
of initial stages of diffusion-controlled sintering, time and length corrections, (4) 189; discussion, (10) 562.
technique for estimating thickness of a thin section, (4) 221; reply, (8) 451; discussion, (12) 678.
Anatase. See also *Titanium, dioxide.*
concentration in TiO_2-opacified porcelain enamels: I, (2) 89; II, (2) 94.
Anions. See *Ions.*
Anisotropy, of strength in UO_2, (1) 1; comments, (10) 568; reply, (10) 569.
thermal expansion, of oxides and oxide solid solutions, (7) 379.
Annealing, effect on strength of flame-fusion-grown Mg-Al spinel, (12) 648.
heat of, in simple alkali silicate glasses, (9) 499.
of irradiation-induced thermal conductivity changes in ThO_2–1.3 wt% UO_2, (3) 160.
strain, in growth of single crystals in hot-worked Al_2O_3, (9) 468.
surface, of hot-pressed CaO, (8) 420.
Arc image, techniques for growing Fe-Ni oxide single crystals, (4) 214.
Argon, -filled bubbles, in ionic solids, (10) 559.
Arsenates, spodiosites, synthesis of, (1) 8.

Barium, $Ba_3MgTa_2O_9$, single crystal, growth from fluoride melt, (6) 335.
Ba_3P_2 and other phosphides, properties, (10) 566.
$BaUO_3$, solubility of KUO_3 in, (11) 574.
ferrite, polycrystalline hexagonal with the *W*-structure type with varying ferrous content: correction, (2) 109.
oxide, doping, effect on adiabatic elastic moduli of vitreous calcium aluminates, (10) 539; correction, (11) 630.
Barium *(continued)*
systems. See *Systems.*
titanate, Gd-doped, donor gradients within surface barriers formed on, (7) 386; correction, (10) 567.
powders, high-purity submicron, preparation, (10) 523.
reduced and reoxidized, phase composition, (2) 63.
semiconducting ceramic, electrochemical oxidation, (4) 219.
tetragonal ferroelectric, aging, (4) 192.
tungstate with Bi, phototropy of, (2) 69.
Beryllium, oxide, crystallite size determination of, methods, (6) 343.
polycrystalline, pressure and temperature derivatives of elastic constants, (5) 246.
-silicon carbide composites, thermal expansion, (5) 290.
transient effects of nuclear radiation on dielectric properties of, at microwave frequencies, (7) 359.
whiskers, formed on surface of burning Be, scanning electron microscopy of, (10) 564.
systems. See *Systems.*
wetting of binary aluminum alloys by, (3) 115.
Bismuth, oxide, effect on magnetic properties of lead ferrite, (6) 302.
phototropy of alkaline earth tungstates doped with, (2) 69.
systems. See *Systems.*
Boron, carbide, wetting of binary aluminum alloys by, (3) 115.
nitride, transient effects of nuclear radiation on dielectric properties of, at microwave frequencies, (7) 359.
oxide, effect on magnetic properties of lead ferrite, (6) 302.
systems. See *Systems.*
Brittle materials, ceramics, crack growth and creep in, (9) 517.
Griffith flaws and effect of porosity on tensile strength of, (8) 457.
porous, micromechanical thermal stresses and thermal stress resistance, (4) 215.
unified theory of thermal shock fracture initiation and crack propagation in, (11) 600.
single-phase and multiphase ceramics, thermal shock resistance, (5) 288.
with high densities of microcracks, analysis of strain at fracture, (8) 458.
Brittleness, and impact resistance, (3) 133.
Bubbles, gas-filled, in ionic solids, (10) 559.

Calcium, aluminates, vitreous, adiabatic elastic moduli to 3.5 kbars, (10) 539; correction, (11) 630.
$CaNb_2O_6$, single crystal, growth from fluoride melt, (6) 335.
$CaTiO_3$-Al_2O_3 ceramics, dielectric properties, (6) 348.
diffusion in SiO_2 glass, evidence for, (11) 625.
oxide: I, fabrication and characterization, (8) 420; II, properties, (8) 428.
silicates, hydration of, influence of tricalcium aluminate, (1) 44.
sulfoaluminate hydrates, morphology of, (9) 521.
systems. See *Systems.*
tri-, silicate, early hydration of: a solid reaction with induction and acceleration periods, (9) 503.
tungstate with Bi, phototropy of, (2) 69.
Carbon. See also *Graphite.*
active, formation in twin-crucible studies of vanadium carbonitride solutions, (5) 257.
dioxide-filled bubbles, in ionic solids, (10) 559.
oxidation, and sulfur, in clays, and relation to thermal behavior of pyrite, (7) 351.
Catalysts, role in transformation of germanium dioxide, (4) 210.
Ceramic materials, polycrystalline, average grain size, (8) 443.
Ceramics, quantitative transmission microscopy of, thickness error, (6) 327.
titanate-alumina, dielectric properties, (6) 348.
Cermets, WC-Co, X-ray stress analysis: I, procedures, (5) 267; II, temperature stresses, (5) 271.
Chemistry. See also *Analysis; Thermodynamics.*
crystal, of Sr_2VO_4Cl and Sr_2AsO_4Cl, (1) 8.
Chlorine, -filled bubbles, in ionic solids, (10) 559.
Chrome. See *Chromium.*
Chromia. See *Chromium.*
Chromite, solid solution with periclase, (1) 58.
Chromium, absorption spectrum of, in phosphate glasses, (1) 52.
Cr^{3+}, optical reflectance spectra in MgO solid solution, (9) 478.
systems. See *Systems.*
Cladding, for strengthening of glass fibers, (12) 661.
Clays. See also *Kaolinite.*
carbon and sulfur oxidation in, and relation to thermal behavior of pyrite, (7) 351.
dried slurries, strength of adhesion of, to window glass, as function of slurry pH, (9) 521.
Coaxing effect, during dynamic fatigue of glass, (6) 340.
Cobalt, absorption spectrum of, in phosphate glasses, (1) 52.
content, effect on temperature stress in WC-Co cermets, (5) 271.
oxide single crystals, transmission electron microscopy and etch pitting of, (2) 112.
systems. See *Systems.*
Colloids, gels, for homogeneous glass preparation, (6) 344.
gel, thoria, surface enthalpy, (12) 675.
Compaction. See also *Pressing.*
of ultrafine active alumina powder, effects of gaseous adsorbates on, (5) 286.
vibratory: III, rate of entry, (8) 414.
Composites, BeO-SiC, thermal expansion, (5) 290.
glass-crystal, strength, (4) 228.
Conductivity, electrical, in alkali silicate glasses, (12) 638.
of aluminate glasses attacked by sodium vapor, (5) 238.
of pure and doped KCl-RbCl, (7) 375.
Conductivity, thermal. See also *Heat.*
irradiation-induced changes, annealing in ThO_2–1.3 wt% UO_2, (3) 160.
of glass, interaction with radiation, (10) 548.
of MgF_2 between 25° and 900°C, (4) 222.
of UN, polycrystalline, low-temperature, (9) 514.
Copper, absorption spectrum of, in phosphate glasses, (1) 52.
$CuFe_2O_4$-Fe_3O_4 spinel solid solution, including $CuFe_2O_4$, eutectoid decomposition, (7) 401.
systems. See *Systems.*
Corrosion, of aluminate glasses by sodium vapor, (5) 238.
Cracks, deep, in glass, generation, (6) 338; reply, (6) 339.
growth and creep in brittle ceramics, (9) 517.
micro-, brittle solids with high densities of, analysis of strain at fracture, (8) 458.
propagation and thermal shock fracture initiation, in brittle ceramics, unified theory, (11) 600.
Creep, and crack growth in brittle ceramics, (9) 517.
and plasticity in single crystals of ZrC, (12) 641.
Nabarro-Herring model, application to densification of HfB_2 in high-pressure hot-pressing, (1) 26.
of MgO, during dehydroxylation, (8) 410.
time-dependent with concurrent grain growth, models, (4) 218.
Cristobalite. See also *Silicon, dioxide.*
crystallization and melting kinetics, (12) 650.
Crystal growth, at interfaces and in glass-crystal systems, electron microscopy of, (1) 46.
of ionic solids containing gas-filled bubbles, (10) 559.
Crystal lattice, MgO, effect of Cr^{3+} on electronic transitions in, (9) 478.
Crystalline materials, non-, development of, in subsolidus reactions between silica and alumina, (11) 616.
Crystallites, size determination in BeO, method, (6) 343.
Crystallization, in Al_2O_3-SiO_2 glasses, (1) 17.
in TiO_2-opacified porcelain enamels: I, (2) 89; II, (2) 94.
kinetics of glass, (2) 111.
of cristobalite, kinetics, (12) 650.
of glass, effect of metastable liquidus, (3) 118.
of PbO-$2B_2O_3$ from supercooled melt, (6) 322.
re-, primary, of hot-worked Al_2O_3, (9) 468.
Crystallography, properties of alkali strontium-barium-lead niobate systems with tungsten bronze structure, (5) 276.
space group of NH_4IO_3, (12) 655.
Crystals. See also specific kinds.
Al_2O_3, impurity deposits on, (8) 454.
CaO, single, properties, (8) 428.

Crystals *(continued)*
lattice parameter, influence of stoichiometry on, in Fe_3O_4, NiO, and Ni-Fe ferrite, (8) 452.
oxide, complex single, growth from fluoride melts, (6) 335.
single, Fe-Ni oxide spinel, growth by arc image techniques, (4) 214.
MgO, diffusion of Fe and Ni in, (12) 669.
rutile, reduction of, (9) 515.
TiN, oxidation kinetics by optical measurements, (9) 496.
ZrC, plasticity and creep in, (12) 641.
structure of Lu_2TeO_5, (10) 570.
structures, stereographic projection: example, β-spodumene, (4) 224.

Decomposition, eutectoid, of $CuFe_2O_4$-Fe_3O_4 spinel solid solution including $CuFe_2O_4$, (7) 401.
of metal alkoxides, for synthesis of $BaTiO_3$ powders, (10) 523.
of solids, mechanism and kinetics by a thermogravimetric method, (11) 591.
Defects. See also *Crystals; Glass; Structure.*
diffusion coefficient in single crystal Al_2O_3, (6) 331.
Griffith flaws in brittle ceramics, (8) 457.
Deformation, in LiF at high temperatures, (11) 595.
of glasses under point loading, role of densification in, comments, (5) 291; reply, (5) 292.
of hot-worked Al_2O_3, (9) 468.
plastic, of cube-oriented MgO crystals under pressure, (6) 293.
Dehydroxylation, creep of MgO during, (8) 410
kinetics of kaolinite, (4) 199.
Densification, mechanisms, in high-pressure hot-pressing of HfB_2, (1) 26.
mechanisms, in hot-pressed CaO, (8) 420.
of gallium arsenide by pressure sintering, (4) 204.
of silica glass, effect of impurities on, (5) 285.
role in deformation of glasses under point loading, comments, (5) 291; reply, (5) 292.
Dielectrics. See also *Ferrites; Glass; Titanates.*
properties, of refractory low-loss ceramics at microwave frequencies, transient effects of nuclear radiation on, (7) 359.
properties, of titanate-alumina ceramics, (6) 348.
Differential thermal analysis. See *Thermal analysis.*
Diffractometers. See *X rays.*
Diffusion, coefficient, defect, in single crystal Al_2O_3, (6) 331.
control of kinetics of ion exchange with glass, (12) 665.
determination of solubility limits in MgO-Fe_2O_3 system by, (8) 460.
of Ca and Al in SiO_2 glass, evidence for, (11) 625.
of Fe and Ni in MgO single crystals, (12) 669.
of lead in lead borate glass, (11) 629.
of nitrogen in UN, measured by α-particle activation of ^{15}N, (12) 631.
of ^{233}U in UO_2, (9) 511.
oxygen, in Gd_2O_3, (8) 456.
oxygen, in UO_2 at high temperatures, (8) 446.
self-, of cations in polycrystalline Y_2O_3 and Er_2O_3, (2) 85.
volume, determines initial sintering kinetics of $MgAl_2O_4$, (8) 417.
Dislocations, and surface flaws, on glass, (7) 403; reply by F. M. Ernsberger, (7) 404.
bands, in cube-oriented MgO deformed under pressure, (6) 293.
screw, evidence for growth of 2H-SiC whiskers by, (7) 400.
Doping, of solid solutions, as method for determining cation vacancy mobility, (7) 375.
Dysprosium, oxide, polycrystalline, elastic properties, (8) 436.

Elasticity, behavior, of arc-cast ZrC-graphite alloys, (9) 475.
constants, of polycrystalline BeO, pressure and temperature derivatives, (5) 246.
moduli, adiabatic, of vitreous calcium aluminates to 3.5 kbars, (10) 539; correction, (11) 630.
moduli, of porcelain-bonded porous alumina ceramics, (10) 543.
modulus, of CaO, single and polycrystalline, (8) 428.
of WC-Co cermets, (5) 267.
relation to fracture surface energy in glass, (2) 99.
properties, of polycrystalline Y_2O_3, Ho_2O_3, Er_2O_3, and Dy_2O_3, (8) 436.
properties, of polycrystalline Y_2O_3, Ho_2O_3, and Er_2O_3: high-temperature measurements, (9) 492.
Young's modulus of polycrystalline β-SiC, (11) 585.
Electrical conductivity. See *Conductivity, electrical.*
Electrical resistivity. See *Resistivity, electrical.*
Emittance, high-temperature hemispherical spectral, of uranium oxides at 0.65 and 0.70 μm, (4) 182.
of an opaque substance, effect of surface porosity, (4) 227.
Enamels, porcelain, opacified with TiO_2, crystallization and phase transformation in: I, (2) 89; II, (2) 94.

Enamels *(continued)*
TiO_2-opacified porcelain, role of P_2O_5, (5) 263.
Energy, activation, for conversion of synthetic kaolinite to mullite, (12) 635.
activation, in sintering, (8) 453.
functions, for nonstoichiometric zirconium carbide, (6) 311.
fracture surface, of sapphire, (9) 485.
surface, in fracture of glass, (2) 99.
volume free, of nucleation of crystalline phase from multicomponent regular solution, calculation, (4) 231.
Enthalpy. See *Heat, content.*
Equilibrium studies. See also *Systems; Phase diagrams.*
β-alumina and related phases, and critical evaluation of literature data on, (7) 364.
in system Li_2O-B_2O_3-B_2O_3-NiO, (9) 481.
in system Sr-Ti-O, in 1375°C isotherm, (9) 463.
of system BaO-Al_2O_3-SiO_2: system celsian-alumina and join celsian-mullite, (12) 679.
phase relations in system CaO-Ta_2O_5-SiO_2, (8) 405.
subsolidus, in system MgO-GeO_2-MgF_2, discussion, (4) 220; reply, (4) 221.
Erbium, oxide, cation self-diffusion in, (2) 85.
polycrystalline, elastic properties, (8) 436.
polycrystalline, elastic properties at high temperatures, (9) 492.
systems. See *Systems.*
Etching, of specimens for stereo electron microscopy, (1) 46.
pitting of CoO single crystals, (2) 112.
Expansion, thermal, anisotropy, of oxides and oxide solid solutions, (7) 379.
of BeO-SiC composites, (5) 290.
of CaO, single and polycrystalline, (8) 428.
X-ray determination of for $AgNO_3$, (1) 53.

Fatigue, dynamic, of glass, coaxing effect, (6) 340.
Ferrites. See also specific types.
lead, microstructure and magnetic properties, (6) 302.
lithium, solid state reactions, (3) 157.
magnesio-, nucleation and growth in MgO containing 0.9% Fe^{3+}, (4) 186.
manganese zinc, effect of synthesis parameters on properties, (3) 127.
Ni-Fe, lattice parameter, influence of stoichiometry on, (8) 452.
Ferroelectrics, tetragonal barium titanate, aging, (4) 192.
Fibers, glass, strengthening: I, cladding, (12) 661; II, ion exchange, (12) 665.
Films, SiO_2, electron-gun-deposited, effects of heat treatment, (4) 225.
Firing. See also *Sintering.*
commercial, action of pyrite in, (1) 40.
Fluoride, melts, for growth of complex oxide single crystals, (6) 335.
Forging, press-, of Al_2O_3: I, primary recrystallization and texture, (9) 468.
Forsterite, crystalline solutions, (5) 249.
Fractionation. See *Separation.*
Fracture, behavior of thermally shocked Al_2O_3, (11) 625.
initiation, thermal shock, and crack propagation in brittle ceramics, unified theory, (11) 600.
mode, for HfB_2 and ZrB_2, (1) 30.
of brittle solids with high densities of microcracks, analysis of strain at, (8) 458.
of CaO, single and polycrystalline, (8) 428.
of sapphire, (9) 485.
strength and mode, of polycrystalline β-SiC, (11) 585.
surface energy of, in glass, (2) 99.
transgranular and intergranular, in polycrystalline Al_2O_3, (9) 510.
Freezing, effect on volume of Al_2O_3, (2) 77.
Friction, internal, in alkali silicate glasses, influence of proton exchange, (3) 165.
of mixed-alkali R_2O-Al_2O_3-$6SiO_2$ glasses, (11) 571.
in mixed-alkali silicate glasses, (4) 169.
Fuels, system, for power burst facility, irradiation testing (pulse conditions), (7) 355.

Gadolinium, -doped barium titanates, donor gradients within surface barriers on, (7) 386; correction, (10) 567.
oxide, diffusion of oxygen in, (8) 456.
systems. See *Systems.*
Gallium, arsenide, pressure sintering, (4) 204.
systems. See *Systems.*
Gases, effect on TGA of pyrite, (1) 40.
effects of adsorption of, on compaction of ultrafine active alumina powder, (5) 286.
Gels. See *Colloids.*
Germanium, dioxide, role of catalysts in transformation, (4) 210.
systems. See *Systems.*
Glasses, acetate, formation, (4) 224.
alkali borate, binary, uv absorption of pentavalent vanadium in, (12) 657.
alkali silicate, electrode polarization in, (12) 638.
influence of proton exchange on internal friction, (3) 165.
simple, heat of annealing in, (9) 499.
structure, (12) 677.
Al_2O_3-SiO_2, immiscibility and crystallization in, (1) 17.
aluminate, sodium vapor resistant, (5) 238.

Glasses *(continued)*
borosilicate, cladding with silica glass, (12) 661.
breaks. See *Fracture.*
calcium phosphate, role of iron in, (11) 605.
-ceramics, lead titanate, (4) 230.
-ceramics, Li_2O-Al_2O_3-SiO_2-TiO_2, secondary grain growth in, (5) 242.
crystalline. See *Glass-ceramics.*
crystallization, effect of metastable liquidus, (3) 118.
crystallization kinetics, (2) 111.
deep cracks in, generation, (6) 338; reply, (6) 339.
deformation of, under point loading, role of densification, comments, (5) 291; reply, (5) 292.
dislocations and surface flaws on, (7) 403; reply by F. M. Ernsberger, (7) 404.
dynamic fatigue of, coaxing effect, (6) 340.
fibers. See *Fibers, glass.*
-forming regions and structure of glasses in system Ge-S, (11) 626.
fracture surface energy, (2) 99.
heat transfer in, effect of interaction of radiation and conduction, (10) 548.
homogeneous, preparation from gels, (6) 344.
in RO-TiO_2 systems, coordination of Ti^{4+} in, (1) 57.
in system Ge-S, structure, (11) 626.
lead borate, diffusion of lead in, (11) 629.
lead, leaching by EDTA, kinetics, (6) 318.
liquid, high shear rate rheology, (12) 680.
mixed-alkali R_2O-Al_2O_3-$6SiO_2$, mechanical damping spectrum, (11) 571.
mixed-alkali silicate, mechanical relaxations, (4) 169.
new inorganic, vitreous nature shown by X-ray diffraction, (7) 402.
optical properties. See *Optical properties.*
oxide, optimization of photoconductive properties, (3) 154.
phosphate, absorption spectra of first row transition metal ions in, (1) 52.
polished porous, ion-selective properties, (2) 65.
polishing. See *Polishing.*
porous, reaction with HF, (3) 124.
powder compacts, effect of water vapor on sintering, (1) 11.
powders, sintering during constant rates of heating, (1) 14.
resistivity of, effect of uniaxial stress, (6) 350.
semiconducting oxide, containing Na_2O, polarization effects in, (9) 513.
silica, cladding borosilicate glass with, (12) 661.
silica, effect of impurities on densification, (5) 285.
SiO_2, evidence for Ca and Al diffusion in, (11) 625.
silicate, physical properties and structure: I, additive relations in alkali binary glasses, (7) 392.
silicate, substructure classification, (3) 151.
soda-alumina-silica, fibers, strengthening by ion exchange, (12) 665.
soda-lime, behavior of bubbles of oxygen and sulfur dioxide in, (2) 106.
effect of water vapor on sintering of powder compacts of, (1) 11.
sintering of powders, at constant rates of heating, (1) 14.
soda-lime-silica, adsorption of methanol vapor, (3) 136.
soda-silica, effect of water content on phase separation in, (9) 508.
systems, three-dimensional, and stereo observations of, (1) 46.
tempered, calculation of residual stresses in, (10) 554.
thorium, magnetic data for, (1) 61.
titanium-containing, electrical resistivity, (11) 582.
uranium(IV), magnetic permeability of, (1) 61.
vitreous calcium aluminates, adiabatic elastic moduli to 3.5 kbars, (10) 539; correction, (11) 630.
window, strength of adhesion of dried clay slurries to, as function of slurry pH, (9) 521.
Grain boundaries, interactions with pores, (1) 56.
Grain growth, pore-grain boundary interactions, (1) 56.
kinetics, effect of pores, (6) 339.
secondary, kinetics of, in Li_2O-Al_2O_3-SiO_2-TiO_2 glass-ceramics, (5) 242.
Grains. See *Particles.*
Graphite. See also *Carbon.*
-uranium dioxide reaction from 1400° to 1756°C, kinetics, (5) 233.
wetting of binary aluminum alloys by, (3) 115.
-ZrC alloys, arc-cast, elastic behavior, (9) 475.
Griffith criterion, and thermal shock resistance of single-phase vs multiphase brittle ceramics, (5) 288.
Growth, of complex oxide single crystals from fluoride melts, (6) 335.
rate, of PbO-$2B_2O_3$ crystals, (6) 322.

Hafnium, diboride, densification mechanisms in high-pressure hot-pressing of, (1) 26.
diboride, strength, fracture mode, and thermal stress resistance of, (1) 30.
systems. See *Systems.*

Halloysite, kinetics and mechanism of high-temperature reactions, (2) 74.
Hardness, indentations and slip behavior in MnSe and MnSe-MnS solid solutions, (7) 370.
micro-, of TiO_2-Nb_2O_5 solid solutions, (9) 520.
Heat. See also *Conductivity, thermal; Temperature.*
content, surface, of thoria gel, (12) 675.
of annealing in simple alkali silicate glasses, (9) 499.
of sublimation of PbSe, (11) 610.
transfer, in glass, effect of interaction of radiation and conduction, (10) 548.
treatment, effects on electron-gun-deposited SiO_2 films, (4) 225.
Heat conductivity. See *Conductivity, thermal.*
Holmium, oxide, polycrystalline, elastic properties, (8) 436.
oxide, polycrystalline, elastic properties at high temperatures, (9) 492.
Hydration, early, of tricalcium silicate: a solid reaction with induction and acceleration periods, (9) 503.
of CaO, single and polycrystalline, (8) 428.
of Ca silicates, influence of tricalcium aluminate, (1) 44.
Hydrolysis, of metal alkoxides, for synthesis of $BaTiO_3$ powders, (10) 526.
Hydrogen, fluoride, reaction with porous glass, (3) 124.

Immiscibility, in Al_2O_3-SiO_2 glasses, (1) 17.
Impact resistance, and brittleness, (3) 133.
Impurities, and residual additives, of hot-pressed CaO, (8) 420.
deposits, on alumina crystals, (8) 454.
effect on densification of silica glass, (5) 285.
Infrared, frequency shift method for study of high-temperature reaction kinetics of synthetic kaolinite, (12) 635.
absorption. See *Absorption.*
radiation. See *Radiation.*
spectra See *Spectra.*
Interferometry, optical, for measurement of oxidation kinetics of single crystal TiN, (9) 496.
ultrasonic, for measurement of adiabatic elastic moduli of vitreous calcium aluminates to 3.5 kbars, (10) 539; correction, (11) 630.
Ion, cation vacancies, mobility, in solid solution KCl-RbCl, (7) 375.
exchange, for strengthening of glass fibers, (12) 665.
ferrous, in polycrystalline hexagonal barium ferrite of the *W*-structure type: correction, (2) 109.
first row transition metal, absorption spectra of in phosphate glasses, (1) 51.
ionic parameters of alkali binary silicate glasses; additive relations of physical properties and structure, (7) 392.
selective response to, of polished porous glass, (2) 65.
3*d* transition metal, optical spectra in MgO·3.5 Al_2O_3 spinel, (6) 307.
Iron, absorption spectrum of, in phosphate glasses, (1) 52.
diffusion in MgO single crystals, (12) 669.
Fe_3O_4, lattice parameter, influence of stoichiometry on, (8) 452.
in calcium phosphate glasses, role, (11) 605.
-nickel oxide spinel single crystals, growth by arc image techniques, (4) 214.
oxide additions to lead zirconate-titanate piezoelectric ceramics, (5) 253.
Irradiation. See *Radiation;* specific types.

Kaolinite, dehydroxylation kinetics, (4) 199.
kinetics and mechanism of high-temperature reactions, (2) 74.
synthetic, infrared kinetic study of high-temperature reactions, (12) 635.
Kinetics. See also *Thermodynamics.*
and mechanism of decomposition of solids by a thermogravimetric method, (11) 591.
crystallization, of cristobalite, (12) 650.
dehydroxylation, of kaolinite, (4) 199.
grain growth, and pores, (6) 339.
of densification of HfB_2 in high-pressure hot-pressing, (1) 26.
of glass crystallization, (2) 111.
of graphite-uranium dioxide reaction from 1400° to 1756°C, (5) 233.
of high-temperature reactions of kaolinite minerals, (2) 74.
of leaching of lead glass by EDTA, (6) 318.
of precipitation in system MgO-Al_2O_3-Cr_2O_3, (4) 174.
of secondary grain growth in Li_2O-Al_2O_3-SiO_2-TiO_2 glass-ceramics, (5) 242.
of zircon synthesis, (11) 619.
oxidation, of powdered silicon nitride, (3) 121.
oxidation, of single crystal TiN by optical measurements, (9) 496.
sintering, based on geometric models, comments, (3) 166.
sintering, initial, of $MgAl_2O_4$, (8) 417.
steam oxidation, in UO_2 at high temperatures, (8) 446.
study, infrared, of high-temperature reactions of synthetic kaolinite, (12) 635.
Lanthanons. See *Rare earths.*
Leaching, lead glass by EDTA, kinetics, (6) 318.
Lead, diborate, crystallization from supercooled melt, (6) 322.
diffusion, in lead borate glass, (11) 629.
Lead *(continued)*
ferrite, microstructure and magnetic properties, (6) 302.
$PbTa_4O_{11}$, single crystal, growth from fluoride melt, (6) 335.
$Pb(Zn_{1/3}Nb_{2/3})O_3$, perovskite-type, high-pressure synthesis, (9) 516.
selenide, single-crystal, sublimation pressure and coefficient, (11) 610.
systems. See *Systems.*
titanate glass-ceramics, (4) 230.
-titanium pyrochlore, (2) 114.
zirconate-titanate piezoelectric ceramics with Fe_2O_3 additions, (5) 253.
Lithium, ferrite, solid state reactions, (3) 157.
fluoride, mechanical behavior at high temperatures, (11) 595.
systems. See *Systems.*
Lutetium, Lu_2TeO_6, crystal structure, (10) 570.

Magnesia. See *Magnesium, oxide.*
Magnesium, aluminate spinel, initial sintering kinetics, (8) 417.
fluoride, thermal conductivity between 25° and 900°C, (4) 222.
hydroxide, creep during dehydroxylation of, (8) 410.
oxide, crystals, cube-oriented, deformation under pressure, (6) 293.
in solid solution, retardant of primary recrystallization of hot-worked Al_2O_3, (9) 468.
single crystals, diffusion of Fe and Ni in, (12) 669.
solid solutions, optical reflectance spectra of Cr^{3+} in, (9) 478.
thermal grooving data, evaluation, (6) 348.
transient effects of nuclear radiation on dielectric properties of, at microwave frequencies, (7) 359.
water-induced toughening of, (2) 82.
systems. See *Systems.*
Magnetic permeability, of uranium(IV) glasses, (1) 61.
Magnetic properties, of lead ferrite, (6) 302.
of manganese zinc ferrites, effect of synthesis parameters, (3) 127.
Magnetic susceptibility. See *Magnetic permeability*
Manganese, absorption spectrum of, in phosphate glasses, (1) 52.
effect of doping with, on optical spectra of Sr_2VO_4Cl, (1) 8.
selenide and MnSe-MnS solid solutions, slip behavior and hardness indentations in, (7) 370.
systems. See *Systems.*
Mechanical properties, behavior of LiF at high temperatures, (11) 595.
brittleness and impact resistance, (3) 133.
of polycrystalline β-SiC, (11) 585.
relaxations in mixed-alkali silicate glasses, (4) 169.
Melting, in system CuO-MoO_3, (1) 36.
of cristobalite, kinetics, (12) 650.
points, in system UP-US, (6) 341.
Melts, fluoride, for growth of complex oxide single crystals, (6) 335.
supercooled, crystallization of PbO·$2B_2O_3$ from, (6) 322.
Membrane potential, of polished porous glass, (2) 65.
Metals. See also *Rare earths.*
alkoxide, decomposition for synthesis of $BaTiO_3$ powders, (10) 523.
systems. See *Systems.*
transition, 3*d* ions, optical spectra in MgO·3.5-Al_2O_3 spinel, (6) 307.
Methanol, vapor adsorption on silica and soda-lime-silica glass, (3) 136.
Microhardness. See *Hardness.*
Microscopy, electron, three-dimensional and stereo, application to glass and ceramic systems, (1) 46.
quantitative transmission, of ceramics, thickness error, (6) 327.
scanning electron, of BeO whiskers formed on surface of burning Be droplets, (10) 564.
technique for estimating thickness of thin section, (4) 221; reply, (8) 451; discussion, (12) 678.
transmission electron, of CoO single crystals, (2) 112.
transmission electron, of NaCl, (12) 681.
Microstructure. See *Structure.*
Model, for grain structure in polycrystalline ceramics, (8) 443.
for time-dependent creep with concurrent grain growth, (4) 218.
geometric, for sintering kinetics, comments, (3) 166.
quasi-chemical, for nonstoichiometric zirconium carbide, (6) 311.
Modulus of elasticity. See *Elasticity.*
Moisture. See *Water.*
Molybdenum, as substrate for growing SiC whiskers, (1) 60.
substrate, preparation of β-SiC whiskers on, (11) 624.
systems. See *Systems.*
Monticellite, crystalline solutions, (5) 249.
Morphology, of calcium sulfoaluminate hydrates, (9) 521.
Mullite, crystallization from high-alumina-dispersed glass phase in Al_2O_3-SiO_2 glasses, (1) 17.
Mullite *(continued)*
kinetics of growth from kaolinite minerals, (2) 74.
volume change on solidification, (5) 292.

Nickel, absorption spectrum of, in phosphate glasses, (1) 52.
diffusion in MgO single crystals, (12) 669.
$2NiO$-B_2O_3, new compound in system Li_2O-B_2O_3-B_2O_3-NiO, (9) 481.
oxide, and Ni-Fe ferrite, lattice parameter, influence of stoichiometry on, (8) 452.
systems. See *Systems.*
Niobate, systems, alkali strontium-barium-lead, with tungsten bronze structure: crystallographic properties and Curie points, (5) 276.
Nitrogen, diffusion in UN measured by α-particle activation of ^{15}N, (12) 631.
-filled bubbles, in ionic solids, (10) 559.
systems. See *Systems.*
Nucleation, and growth of magnesioferrite in MgO containing 0.9% Fe^{3+}, (4) 186.
at interfaces and in glass-crystal systems, electron microscopy of, (1) 46.
mechanisms, in Al_2O_3-SiO_2 glass melts, (1) 17.
of crystalline phase from multicomponent regular solution, calculation of volume free energy, (4) 231.

Optical materials, NH_4IO_3, potentially useful, (12) 655.
Optical properties, of CaO, single and polycrystalline, (8) 428.
Organic materials, dielectrics, transient effects of nuclear radiation on dielectric properties of, at microwave frequencies, (7) 359.
Oxidation, electrochemical, of semiconducting ceramic barium titanate, (4) 219.
kinetics, of powdered silicon nitride, (3) 121.
kinetics of single crystal TiN by optical measurements, (9) 496.
of carbon and sulfur in clays, and relation to thermal behavior of pyrite, (7) 351.
of pyrite, (1) 40.
steam, kinetics, and oxygen diffusion, in UO_2 at high temperatures, (8) 446.
Oxides. See also *Rare earths;* specific types.
alkali and alkaline earth, effect on crystallization and emulsion formation in Al_2O_3-SiO_2 glasses, (1) 17.
and oxide solid solutions, thermal expansion anisotropy, (7) 379.
single crystals, complex, growth from fluoride melts, (6) 335.
Oxygen, bubbles of, behavior in soda-lime glass, (2) 106.
diffusion, in Gd_2O_3, (8) 456.
diffusion, in UO_2 at high temperatures, (8) 446.
influence on growth of 2H-SiC whiskers, (1) 60.
systems. See *Systems.*
Oxyhydroxides, $Ni_{1-x}Fe_{2+x}$-, reactive hot-pressing of, (2) 110.

Particles. See also *Colloids.*
grain size, average, in polycrystalline ceramics, (8) 443.
rate at which fine can be vibratorily infiltrated into column matrix of packed coarser particles, (8) 414.
size, of hot-pressed CaO, (8) 420.
Peierls barrier, surmounting of, as deformation mechanism in UO_2, (1) 1; comments, (10) 568; reply, (10) 569.
Periclase, solid solution with chromite, (1) 59.
Phase, separation, in soda-silica glasses, effect of water content, (9) 508.
Phase diagrams. See also *Equilibrium studies.*
BaO-Pt, in air, (9) 519.
Ba-P, (10) 567.
B_2O_3-NiO, (9) 482.
BaO-TiO_2, (1) 58.
$CaCl_2$-MgF_2, (11) 614.
CaO-NiO-SiO_2, provisional, (6) 317.
$2CaO$·SiO_2-$3CaO$·P_2O_5, (6) 347.
CaO-Ta_2O_5, (8) 405.
celsian-corundum, (12) 679.
celsian-mullite join, (12) 679.
CuO-MoO_3, in air and oxygen, (1) 38.
KUO_3-$BaUO_3$, (11) 575.
Li_2O-B_2O_3-B_2O_3-NiO, estimated ternary, (9) 484.
Li_2O-B_2O_3-NiO, (9) 483.
$2Li_2O$-$3B_2O_3$-NiO section through Li_2O-B_2O_3-NiO system, (9) 483.
$4Li_2O$-$5B_2O_3$-NiO section through Li_2O-B_2O_3-NiO system, (9) 484.
$MgCl_2$-MgF_2, (11) 613.
Mo-O system, (10) 530.
NaCl-MgF_2, (11) 615.
Na_2O-Al_2O_3, (7) 366.
Na_2O-Al_2O_3-Al_2O_3, (7) 367.
Nb-O system, (10) 532.
NiO-CaO, (8) 460.
partial, of CuO-MoO_3 under oxygen pressure, (1) 40.
PbF_2-AlF_3, (2) 80.
schematic, of UO_{2+x}, (1) 1; comments, (10) 568; reply, (10) 569.

Phase Diagrams *(continued)*
section through Li_2O-B_2O_3-NiO system at $Li_2O \cdot 2B_2O_3$-NiO, (9) 483.
showing metastable liquidus, (3) 120.
Sr-Ti-O, 1375°C, 30-70 at.% O_2, (9) 465.
Ta_2O_5-SiO_2, (8) 407.
U-C-N system at 1700°C, (10) 537.
U-C-O-N system at 1700°C, (10) 537.
UO_2-$GdO_{1.5}$, (11) 580.
U-O-N system at 1700°C, (10) 536.
W-O system, (10) 528.
ZrO_2-SrO, tentative, (4) 181.
Phase rule. See *Equilibrium studies.*
Phases, surface, and vaporization in lead zirconate-lead titanate system, (10) 565.
Phosphorus, pentoxide, role in TiO_2-opacified porcelain enamels, (5) 263.
systems. See *Systems.*
Photochromism, of synthetic sodalite, (3) 139.
Photoconductivity, optimization of properties in oxide glasses, (3) 154.
Phototropy, of alkaline earth tungstates doped with Bi, (2) 69.
Physical properties, and structure, of silicate glasses: I, additive relations in alkali binary glasses, (7) 392.
Piezoelectricity, of NH_4IO_3, (12) 655.
properties of lead zirconate-titanate ceramics with iron oxide additions, (5) 253.
Poisson's ratio, of WC-Co cermets, (5) 267.
Plasticity, and creep, in single crystals of ZrC, (12) 641.
Polarization, effects in semiconducting oxide glasses containing Na_2O, (9) 513.
electrode, in alkali silicate glasses, (12) 638.
Polishing, effect on membrane potential of porous glass, (2) 65.
Pores, in glass, electron microscopy of, (1) 46.
interactions with grain boundaries, (1) 56.
relation to grain growth kinetics, (6) 339.
size of, influence on membrane potential of porous glass, (2) 65.
Porosimeter, water-removal, (10) 543.
Porosity. See also *Pores.*
effect of, on tensile strength of brittle ceramics, (8) 457.
inner, of Al_2O_3, determination by volume change on freezing, (2) 77.
in porcelain-bonded porous alumina ceramics, characterization, (10) 543.
surface, effect on emittance of an opaque substance, (4) 227.
Potassium, chloride melt, introduction of insoluble gases into, (10) 559.
chloride-RbCl solid solutions, mobility of cation vacancies in, (7) 375.
$K_2Ge_4O_9$, single crystal, growth from fluoride melt, (6) 335.
KUO_3, solubility in $BaUO_3$, (11) 574.
nitrate, strengthening of glass fibers by ion exchange with, (12) 665.
systems. See *Systems.*
Powders, high-purity submicron $BaTiO_3$, preparation, (10) 523.
TiO_2, reduction of, (9) 515.
Precipitation, kinetics and strain in system MgO-Al_2O_3-Cr_2O_3, (4) 174.
of magnesioferrite from MgO containing 0.9% Fe^{3+}, (4) 186.
pre-, as cause of strengthening of flame-fusion-grown Mg-Al spinel, (12) 648.
Pressing, hot-, high-pressure, of HfB_2, densification mechanisms, (1) 26.
hot-, of CaO, (8) 420.
reactive hot-, of $Ni_{1/3}Fe_{2/3}$ oxyhydroxides, (2) 110.
Pressure, deformation of cube-oriented MgO crystals, (6) 293.
high-, synthesis of perovskite-type $Pb(Zn_{1/3}Nb_{2/3})O_3$, (9) 516.
sublimation, of single-crystal PbSe, (11) 610.
Proton, exchange, influence on internal friction of alkali silicate glasses, (3) 165.
Pyrite, oxidation and decomposition, (1) 40.
thermal behavior, and relation to carbon and sulfur oxidation in clays, (7) 351.
Pyrochlore, lead-titanium, (2) 114.
Pyrrhotite, DTA of, (1) 40.

Radiation. See also specific types.
interaction with conduction in glass, (10) 548.
ir-, testing (pulse conditions) of ternary fuel system for power burst facility, (7) 355.
nuclear, transient effect of, on dielectric properties of refractory low-loss ceramics at microwave frequencies, (7) 359.
radiography, α-, of $(U,Pu)O_2$ microspheres, (8) 461.
Rare earths. See also specific types.
oxides, role and effect as additives on stabilization of urania at high temperatures, (11) 578.
systems. See *Systems.*
Reaction mechanism, high-temperature, of kaolinite minerals, (2) 74.
Reactions, subsolidus, between silica and alumina, development of noncrystalline material in, (11) 616.
Reactors, nuclear (power burst facility), irradiation testing (pulse conditions) of ternary fuel system for, (7) 355.
Reduction, of TiO_2 powders and rutile single crystals, (9) 515.
Refractories. See also specific types.
low-loss ceramics, dielectric properties, transient effects of nuclear radiation on, at microwave frequencies, (7) 359.
metal-oxygen systems, phase relations, review, (10) 527.
Relaxation, mechanical, in mixed-alkali silicate glasses, (4) 169.
Resistivity, electrical, of titanium-containing glasses, (11) 582.
of glass, effect of uniaxial stress, (6) 350.
Resonance, sonic, technique, for determination of elastic properties of Y_2O_3, Dy_2O_3, Ho_2O_3, and Er_2O_3, (8) 436.
Retarder, lignosulfate, effect on hydration behavior of calcium silicates with addition of tricalcium aluminate, (1) 44.
Rheology, high shear rate, of liquid glass, (12) 680.
Rutile. See also *Titanium, dioxide.*
concentration in TiO_2-opacified porcelain enamels: I, (2) 89; II, (2) 94.
single crystals, reduction of, (9) 515.

Samarium, dicarbide vaporization, Knudsen cell studies, (3) 145.
systems. See *Systems.*
Sapphire, fracture of, (9) 485.
Semiconductors, donor gradients within surface barriers formed on dense Gd-doped barium titanates, (7) 386; correction, (10) 567.
oxide glasses containing Na_2O, polarization effects in, (9) 513.
Separation, phase, in glass, electron microscopy of, (1) 46.
phase, in soda-silica glasses, effect of water content, (9) 508.
Shock, resistance, thermal, and Griffith criterion, of single-phase vs multiphase brittle ceramics, (5) 288.
Shrinkage, of glass powders during sintering at constant rates of heating, (1) 14.
of powder compacts of soda-lime glasses, effect of water vapor, (1) 11.
Silica. See *Silicon, dioxide.*
Silicon, carbide, β-, mechanical properties, (11) 585.
β-, whiskers, prepared on Mo substrate, (11) 624.
β-, whiskers, structure of, (1) 51.
2H-, whiskers, evidence for growth by screw dislocation, (7) 400.
influence of oxygen on growth of 2H whiskers, (1) 60.
dioxide. See also *Cristobalite.*
dioxide, clear and opaque fused, transient effects of nuclear radiation on dielectric properties of, at microwave frequencies, (7) 359.
doping, effect on adiabatic elastic moduli of vitreous calcium aluminates, (10) 539; correction, (11) 630.
effect on magnetic properties of lead ferrite, (6) 302.
films, electron-gun-deposited, effects of heat treatment, (4) 225.
rutile (stishovite), thermal expansion properties, (7) 379.
subsolidus reactions with alumina, development of noncrystalline material in, (11) 616.
transformations, in system PbO-SiO_2, comments and discussion, (6) 345.
vitreous, adsorption of methanol vapor, (3) 136.
nitride, powdered, kinetics of oxidation, (3) 121.
Silver, nitrate, thermal expansion of, (1) 53.
systems. See *Systems.*
Sintering, activation energy in, (8) 453.
diffusion-controlled, time and length corrections in analysis, (4) 189; discussion, (10) 562.
kinetics based on geometric models, comments, (3) 166.
kinetics, initial, of $MgAl_2O_4$, (8) 417.
of glass powder compacts, effect of water vapor on, (1) 11.
of glass powders during constant rates of heating, (1) 14.
pressure, of gallium arsenide, (4) 204.
Slip. See also *Deformation.*
behavior and hardness indentations in MnSe and MnSe-MnS solid solutions, (7) 370.
Sodalite, synthetic photochromic, (3) 139.
Sodium, chloride, transmission electron microscopy of, (12) 681.
systems. See *Systems.*
vapor, glasses resistant to, (5) 238.
Solidification, of mullite, volume change, (5) 292.
Solids, decomposition, mechanism and kinetics by a thermogravimetric method, (11) 591.
ionic, gas-filled bubbles in, (10) 559.
reaction with induction and acceleration periods: early hydration of tricalcium silicate, (9) 503.
Solid solutions. See *Solutions, solid.*
Solid state, reactions of lithium ferrite, (3) 157.
Sols. See *Colloids.*
Solubility, limits in MgO-Fe_2O_3 system as determined by diffusion, (8) 460.
Solutions, solid, $CuFe_2O_4$-Fe_3O_4 spinel, including $CuFe_2O_4$, eutectoid decomposition, (7) 401.
KCl-RbCl, mobility of cation vacancies in, (7) 375.
KUO_3 in $BaUO_3$, (11) 574.
Solutions, solid *(continued)*
MgO, optical reflectance spectra of Cr^{3+} in, (9) 478.
MnSe-MnS, slip behavior and hardness indentations in, (7) 370.
monticellite and forsterite, (5) 249.
of Cr and V spodiosites, (1) 8.
of periclase and chromite, (1) 59.
of ThP and UP, (1) 54.
of tungsten bronze-type niobates, (5) 276.
of Y_2O_3-ZrO_2, defect structure, (4) 213.
oxide, thermal expansion anisotropy, (7) 379.
$SrTiO_3$, diffuse reflectance spectra of, (9) 463.
TiO_2-Nb_2O_5, microhardness, (9) 520.
urania–rare-earth oxide, lattice parameters and theoretical densities, (11) 580.
Sound, velocities of polycrystalline BeO, (5) 246.
Spectra, absorption, of first row transition metal ions in phosphate glasses, (1) 52.
diffuse reflectance, of $SrTiO_3$(*ss*), (9) 463.
infrared, in study of reaction of HF with porous glass, (3) 124.
mechanical damping, for mixed-alkali R_2O-$Al_2O_3 \cdot 6SiO_2$ glasses, (11) 571.
optical, interpretation for Mn-doped Sr_2VO_4Cl, (1) 8.
optical, of 3*d* transition metal ions in MgO-3.5-Al_2O_3 spinel, (6) 307.
optical reflectance, of Cr^{3+} in MgO solid solutions, (9) 478.
Spheres, micro-, $(U,Pu)O_2$, α-autoradiography of, (8) 461.
Spinel. See also specific types.
$CuFe_2O_4$-Fe_3O_4 solid solution, including Cu-Fe_2O_3, eutectoid decomposition, (7) 401.
Fe-Ni oxide single crystals, growth by arc image techniques, (4) 214.
magnesium aluminate, initial sintering kinetics, (8) 417.
Mg-Al, flame-fusion-grown, strength, (12) 648.
MgO-3.5Al_2O_3, optical spectra of 3*d* transition metal ions in, (6) 307.
Spodiosites, vanadate and arsenate, synthesis of, (1) 8.
Spodumene, β-, stereographic projection of crystal structures, (4) 224.
Steam. See also *Water.*
oxidation kinetics and oxygen diffusion in UO_2 at high temperatures, (8) 446.
Stereology, of glass and ceramic systems, (1) 46.
parameters, errors, in quantitative transmission microscopy of ceramics, (6) 327.
projection of crystal structures: example, β-spodumene, (4) 224.
Stoichiometry, dependence of strength of UO_{2+x} on, at high temperatures, (1) 1; comments, (10) 568; reply (10) 569.
influence on lattice parameter in Fe_3O_4, NiO, and Ni-Fe ferrite, (8) 452.
Strains, and strain rates in hot-worked Al_2O_3, (9) 468.
at fracture of brittle solids with high densities of microcracks, analysis, (8) 458.
in TaC due to composition gradients, X-ray measurement, (4) 216.
precipitation, measurements in system MgO-Al_2O_3-Cr_2O_3, (4) 174.
Strength, of CaO, single and polycrystalline, (8) 428.
of flame-fusion-grown Mg-Al spinel, (12) 648.
of glass fibers, increasing by: I, cladding, (12) 661; II, ion exchange, (12) 665.
of HfB_2 and ZrB_2, (1) 30.
of sapphire, (9) 485.
of UO_{2+x} polycrystals, dependence on temperature and stoichiometry, (1) 1; comments, (10) 568; reply, (10) 569.
tensile, high-temperature, of LiF, (11) 595.
tensile, of brittle ceramics, Griffith flaws and effect of porosity on, (8) 457.
Stress, flow, dependence on nonstoichiometry in oxygen-rich uranium dioxide at high temperatures, (1) 1; comments, (10) 568; reply, (10) 569.
micromechanical thermal, and resistance, of porous brittle ceramics, (4) 215.
residual, in tempered glass, calculation, (10) 554.
-strain behavior of cube-oriented MgO crystals, (6) 293.
-strain curves, for polycrystalline β-SiC, (11) 585.
thermal, resistance to, of HfB_2 and ZrB_2, (1) 30.
uniaxial, effect on glass resistivity, (6) 350.
X-ray analysis of, in WC-Co cermets: I, procedures, (5) 267; II, temperature stresses, (5) 271.
Strontium, $SrTiO_3$-Al_2O_3 ceramics, dielectric properties, (6) 348.
tungstate with Bi, phototropy of, (2) 69.
Structure, and physical properties of silicate glasses: I, additive relations in alkali binary glasses, (7) 392.
defect, of Y_2O_3-ZrO_2 solid solution, (4) 213.
of alkali silicate glass, (12) 677.
micro-, of arc-cast ZrC-graphite alloys, relation to elastic behavior, (9) 475.
micro-, of lead ferrite, (6) 302.
of glasses in system Ge-S, (11) 626.
Sublimation, coefficient and pressure, of single-crystal PbSe, (11) 610.

Sulfur, dioxide, bubbles of, behavior in soda-lime glass, (2) 106.
oxidation, and carbon, in clays, and relation to thermal behavior of pyrite, (7) 351.
systems. See *Systems.*
Surface, flaws and dislocations, on glass, (7) 403; reply by F. M. Ernsberger, (7) 404.
Swelling. See *Expansion.*
Synthesis, high-pressure, of perovskite-type Pb-$(Zn_{1/3}Nb_{2/3})O_3$, (9) 516.
of vanadate and arsenate spodiosites, (1) 8.
zircon, kinetics of, (11) 619.
Systems. See also *Equilibrium studies; Phase diagrams*
alkali strontium-barium-lead niobate, with tungsten bronze structure: crystallographic properties and Curie points, (5) 276.
$BaO-Al_2O_3-SiO_2$, studies in system celsian-alumina and join celsian-mullite, (12) 679.
Ba-P, (10) 566.
BaO-Pt, in air, (9) 518.
CaF_2-AlF_3, (2) 79.
$CaO-NiO-SiO_2$, (6) 316.
$2CaO{\cdot}SiO_2-3CaO{\cdot}P_2O_5$, subsolidus relations in, (6) 346.
$CaO-Ta_2O_5-SiO_2$, phase relations, (8) 405.
celsian-alumina, (12) 679.
Ge-S, glass-forming regions and structure of glasses, (11) 626.
lead zirconate-lead titanate, vaporization and surface phases in, (10) 565.
$Li_2O{\cdot}B_2O_3-B_2O_3-NiO$, phase relations, (9) 481.
metal-oxygen, refractory, phase relations in, review, (10) 527.
$MgO-Al_2O_3-Cr_2O_3$, kinetics of precipitation and measurements of strain, (4) 174.
$MgO-Fe_2O_3$, solubility limits as determined by diffusion, (8) 460.
$MgO-GeO_2-MgF_2$, subsolidus equilibria, discussion, (4) 220; reply, (4) 221.
Mo-O, phase relations in, review, (10) 527.
$Na_2O-Al_2O_3$, (7) 364.
Nb-O, phase relations in, review, (10) 527.
NiO-CaO, (8) 459.
$PbO-SiO_2$, silica transformations in, comments and discussion, (6) 345.
RO-TiO_2, (1) 57.
Sr-Ti-O, phase equilibria in 1375°C isotherm, (9) 463.
Ta-O, phase relations in, review, (10) 527.
U-C-O-N, quaternary, at 1700°C, (10) 534.
UO_2-ZrO_2-CaO, as fuel system for nuclear reactor (power burst facility), (7) 355.
UP-US, melting point studies, (6) 341.
W-O, phase relations in, review, (10) 527.
ZrO_2-SrO, reactions, (4) 178.

Tantalum, carbide, X-ray measurement of strain due to composition gradients, (4) 216.
systems. See *Systems.*
Temperature, Curie, of alkali strontium-barium-lead niobate systems with tungsten bronze structure, (5) 276.
distributions and heat fluxes, in glass, effect of interaction of radiation and conduction, (10) 548.
Testing. See *Analysis* and specific types.
Texture, recrystallization, of hot-worked Al_2O_3, (9) 468.
Thermal analysis, differential, of clays, (7) 351.
of hydrated silicate pastes, (1) 44.
of pyrite and pyrrhotite, (1) 40.
of ThP, (1) 54.
Thermal conductivity. See *Conductivity, thermal.*
Thermal decomposition. See *Decomposition.*
Thermal expansion. See *Expansion.*
Thermal properties, grooving, evaluation of data, (6) 348.
Thermochemistry. See *Thermodynamics.*
Thermodynamics, statistical method for calculating composition dependence of chemical potentials in nonstoichiometric zirconium carbide, evaluation, (6) 311.
Thermogravimetry, for determination of mechanism and kinetics of decomposition of solids, (11) 591.
of pyrite, (1) 40.
of ThP, (1) 54.
Thickness, error, in quantitative transmission microscopy of ceramics, (6) 327.
Thoria. See *Thorium, oxide.*

Thorium, dioxide-1.3 wt% UO_2, annealing of irradiation-induced changes in, (3) 160.
glasses, magnetic data for, (1) 61.
oxide, surface enthalpy, (12) 675.
phosphide, preparation and properties, (1) 54.
systems. See *Systems.*
Titanates See also specific types.
-alumina ceramics, dielectric properties, (6) 348.
Titania. See *Titanium, dioxide.*
Titanium, -containing glasses, electrical resistivity, (11) 582.
dioxide, in porcelain enamels, effect of P_2O_5 on, (5) 263.
-Nb_2O_5 solid solutions, microhardness, (9) 520.
porcelain enamels opacified with, crystallization and phase transformation in: I, (2) 89; II, (2) 94.
powders, reduction of, (9) 515.
ion, 4+, coordination in glasses in the RO-TiO_2 systems, (1) 67.
nitride, single crystal, oxidation kinetics by optical measurements, (9) 496.
systems. See *Systems.*
Ti^{3+}, use to measure defect diffusion in Al_2O_3, (6) 331.
Toughening, water-induced, in MgO crystals, (2) 82.
Transformation, of germanium dioxide, role of catalysts, (4) 210.
phase, of silica in system $PbO-SiO_2$, comments and discussion, (6) 345.
phase, in TiO_2-opacified porcelain enamels: I, (2) 89; II, (2) 94.
Tungstates. See also specific types.
alkaline-earth, doped with Bi, phototropy of, (2) 69.
Tungsten, bronze structure, alkali strontium-barium-lead niobate systems with: crystallographic properties and Curie points, (5) 276.
carbide-cobalt cermets, X-ray stress analysis: I, procedures, (5) 267; II, temperature stresses, (5) 271.
systems. See *Systems.*

Urania. See *Uranium, dioxide.*
Uranium, dioxide, behavior at high temperatures, and effect of rare-earth oxide additives on stabilization, (11) 578.
graphite reaction from 1400° to 1756°C, kinetics, (5) 233.
oxygen-rich, dependence of flow stress on nonstoichiometry in, at high temperatures, (1) 1; comments, (10) 568; reply, (10) 569.
steam oxidation kinetics and oxygen diffusion in, at high temperatures, (8) 446.
(IV) glasses, magnetic permeability of, (1) 61.
nitride, nitrogen diffusion in, measured by α-particle activation of ^{15}N, (12) 631.
nitride, polycrystalline, thermal conductivity, low-temperature, (9) 514.
oxides, high-temperature hemispherical spectral emittance at 0.65 and 0.70 μm, (4) 182.
phosphide, solid solution with ThP, (1) 54.
systems. See *Systems.*
^{235}U, diffusion in UO_2, (9) 511.
$(U,Pu)O_2$ microspheres, α-radiography of, (8) 461.

Vanadates. See also specific types.
spodiosites, synthesis of, (1) 8.
Vanadium, absorption spectrum of, in phosphate glasses, (1) 52.
carbonitride solutions, formation of active carbon in twin-crucible studies of, (5) 257.
dioxide, tetragonal, thermal expansion properties, (7) 379.
pentavalent, uv absorption of, in binary alkali borate glasses, (12) 657.
systems. See *Systems.*
Vaporization, and surface phases in lead zirconate-lead titanate system, (10) 565.
of samarium dicarbide, Knudsen cell studies, (3) 145.
Viscosity, of lead diborate melt, (6) 322.
of sintered glass powder compacts, effect of water vapor on, (1) 11.
Volume, change of mullite on solidification, (5) 292.
change of, on freezing of Al_2O_3, (2) 77.
Water See also *Steam.*
content, effect on phase separation in soda-silica glasses, (9) 508.
toughening effect on MgO crystals, (2) 82.
vapor, effect on sintering of glass powder compacts, (1) 11.
Wave, micro-, frequencies, transient effects of nuclear radiation on dielectric properties of refractory low-loss ceramics at, (7) 359.
Wetting, of binary aluminum alloys in contact with Be, B_4C, and graphite, (3) 115.
Whiskers. See also *Crystals;* specific types.
α-Al_2O_3, X-ray microtopography, (5) 282.
BeO, formed on surface of burning Be, scanning electron microscopy of, (10) 564.
β-SiC, prepared on Mo substrate, (11) 624.
β-SiC, structure of, (1) 51.
2H-SiC evidence for growth by screw dislocation, (7) 400.
2H-SiC, influence of oxygen on growth of, (1) 60.

X-ray, analysis of β-SiC structures, (1) 51.
analysis of kinetics of high-temperature reactions of kaolinite minerals, (2) 74.
data for $BaTiO_3$, (2) 63.
data for compounds in system $CuO-MoO_3$, (1) 36.
data for Lu_2TeO_6, (10) 570.
data for $Pb_2Al_2F_{12}$, (2) 79.
data for $Pb_2Ti_2O_5F_2$, (2) 114.
data for Sr_2VO_4Cl and Sr_2AsO_4Cl, (1) 8.
determination of thermal expansion of $AgNO_3$, (1) 53.
diffractometry, method for crystallite size determination of BeO, (6) 343.
diffraction patterns of oxidation of pyrite, (7) 351.
diffraction, shows vitreous nature of new inorganic glasses, (7) 402.
diffraction spectra of devitrified iron-containing calcium phosphate glasses, (11) 605.
diffraction stress analysis, "two-exposure," of WC-Co cermets: I, procedures, (5) 267; II, temperature stresses, (5) 271.
measurement of strain in TaC due to composition gradients, (4) 216.
microtopography of α-Al_2O_3 whiskers, (5) 282.
powder patterns for $Ba_3MgTa_2O_9$, $Pb_3Ta_4O_{12}$, and $K_2Ge_4O_9$, (6) 335.

Young's modulus. See *Elasticity.*
Yttria. See *Yttrium, oxide.*
Yttrium, oxide, cation self-diffusion in, (2) 85.
polycrystalline, elastic properties, (8) 436.
polycrystalline, elastic properties at high temperatures, (9) 492.
-zirconium oxide solid solution, defect structure, (4) 213.
systems. See *Systems.*

Zinc, oxide (zincite), thermal expansion properties, (7) 379.
systems See *Systems.*
Zirconium, carbide-graphite alloys, arc-cast, elastic behavior, (9) 475.
nonstoichiometric, composition dependence of chemical potentials, evaluation of statistical thermodynamic method for calculating, (6) 311.
single crystals, plasticity and creep in, (12) 641.
diboride, strength, fracture mode, and thermal stress resistance of, (1) 30.
systems. See *Systems.*
Zircon, synthesis, kinetics, (11) 619.

JOURNAL

of the

American Ceramic Society

A MONTHLY PUBLICATION DEVOTED TO THE ARTS AND SCIENCES RELATED TO CERAMICS

VOLUME 52, 1969

F. P. Reid, *Publisher and Executive Director*
Herbert Insley, *Editor*
Margie K. Reser, *Technical Editor*
M. Geraldine Smith, *Associate Editor*
Nancy L. Reed, *Assistant Editor*
Olive Scott, *Senior Editorial Assistant*
Martha Bell, *Editorial Assistant*

Committee on Publications: W. J. Smothers, *Chairman;*
Seymour L. Blum, E. F. Osborn, J. P. Poole;
ex officio members: F. P. Reid, Herbert Insley, Floyd A. Hummel

Executive, Editorial, and Advertising Offices:
4055 North High Street, Columbus, Ohio 43214

Officers of the American Ceramic Society, 1969-70

Society Officers

President: ARTHUR J. BLUME
American Olean Tile Co., Lewisport, Ky. 42351
President-Elect: J. EARL FRAZIER
Frazier-Simplex, Inc., Box 493, Washington, Pa. 15301
Vice Presidents:
WILLIAM W. COFFEEN, Clemson University
Dept. of Ceramic Engineering, Clemson, S. C. 29631
SCROOP W. ENLOE, JR., 504 Rogers Lane
Spruce Pine, N. C. 28777 (Harris Mining Co.)
J. O. EVERHART, Ohio State University
Department of Ceramic Engineering
2041 N. College Rd., Columbus, Ohio 43210
Treasurer: WILLIAM J. SMOTHERS, Bethlehem Steel Corp.
Homer Research Labs., Bethlehem, Pa. 18016

Division Officers

Basic Science Division

Trustee: JOHN B. WACHTMAN, JR., (1972)
National Bureau of Standards, Materials Bldg.
Room B306, Washington, D. C. 20234
Chairman: ORSON L. ANDERSON, Lamont Geological
Observatory, Columbia University
Palisades, N. Y. 10964
Chairman-Elect: RALPH E. CARTER
General Electric Research & Development Center
Box 1088, Schenectady, N. Y. 12301
Vice Chairman: ROBERT L. COBLE
Massachusetts Institute of Technology, Ceramics Div.
Rm. 13-4062, Cambridge, Mass. 02139
Secretary: RICHARD M. SPRIGGS, Lehigh University
Materials Research Center, Bethlehem, Pa. 18015

Ceramic-Metal Systems Division

Trustee: EUGENE E. BRYANT (1970) Ferro Corp.
4150 E. 56th St., Cleveland, Ohio 44105
Chairman: LYNN E. FUSSELL, 435 Crestover Circle
Richardson, Texas 75080 (Texas Instruments, Inc.)
Vice Chairman: ROBERT J. MCWILLIAMS, Pfaudler Co.
Div. of Sybron Corp., 1000 West Ave.
Rochester, N. Y. 14603
Secretary: JAMES D. SULLIVAN, Haveg Industries, Inc.
Glascote Div. 20900 E. St. Clair Ave., Cleveland, O. 44117
Counselor: CLIFTON G. BERGERON, University of Illinois
203 Ceramics Bldg., Urbana, Ill. 61801
Counselor: JACK E. BURROUGHS, SR., 2005 Milam St.,
Fort Worth, Texas 76112

Design Division

Trustee: MARVIN G. YUTZEY, (1971) Fostoria Glass Co.
1200 First St., Moundsville, W. Va. 26041
Chairman: CHARLES R. DIBBLE, 848 Livingston Ave.
Syracuse, N. Y. 13210 (Syracuse University)
Secretary: VINCENT BROOMHALL
Homer Laughlin China Co., Newell, W. Va. 26050

Electronics Division

Trustee: SEYMOUR L. BLUM (1972)
IIT Research Institute, 10 W. 35th St.
Chicago, Ill. 60616
Chairman: MERLE D. RIGTERINK, Bell Telephone Labs.,
Inc., Mountain Ave., Murray Hill, N. J. 07974
Chairman-Elect: BERNARD SCHWARTZ, IBM Corp.
Box 390, B003-2, D709, Hopewell Junction, N. Y. 12533
Vice Chairman: RICHARD D. DILLENDER, 411 Fern Trail
Signal Mountain, Tenn. 37377 (American Lava Corp.)
Secretary: JAMES R. FLOYD, Reynolds Metal Co.
Ten Presidential Blvd., N., Philadelphia, Pa. 19101

Glass Division

Trustee: WILLIAM R. PRINDLE (1971) Ferro Corp.
4150 E. 56th St., Cleveland, Ohio 44105
Chairman: JOHN R. HUTCHINS III, Corning Glass Works
Sullivan Park, Corning, N. Y. 14830
First Vice Chairman: RICHARD E. MOULD
American Glass Research, Inc.
Box 149, Butler, Pa. 16001
Second Vice Chairman: CHARLES R. KURKJIAN
Bell Telephone Labs., Inc., Murray Hill, N. J. 07974
Secretary: JOSEPH J. HAMMEL, PPG Industries, Inc. Glass
Research Center, Box 11472, Pittsburgh, Pa. 15238

Materials & Equipment Division

Trustee: LYLE A. HOLMES (1972)
International Minerals & Chemical Corp.
Industrial Minerals Div., 5401 Old Orchard Rd.
Skokie, Ill. 60076
Chairman: RICHARD O. HOMMEL, 5 Grandview Ave.
Apt. 803, Pittsburgh, Pa. 15211 (The O. Hommel Co.)
Chairman-Elect: WILLIAM C. MOHR
Electro Refractories & Abrasives Div., Ferro Corp.
Box 151, Crooksville, Ohio 43731
Vice Chairman: CARL W. GARTNER,
General Color & Chemical Co.
Box 7, Minerva, Ohio 44657
Secretary: RICHARD C. HANNON, 1310 E. Tenth St.,
Salem, Ohio 44460 (R. T. Vanderbilt Co., Inc.)

Nuclear Division

Trustee: STEPHEN D. STODDARD (1970) 203 Chamisa Ave.
Los Alamos, N. M. 87544 (Los Alamos Scientific Lab.)
Chairman: STEPHEN C. CARNIGLIA, Rocketdyne Div.
North American Rockwell Corp., 6633 Canoga Ave.
Canoga Park, Calif. 91304
Vice Chairman: J. LAMBERT BATES, Battelle/Northwest
Box 999, Richland, Wash. 99352
Secretary: OWEN L. KRUGER, 2745 Northwest Blvd.
Columbus, Ohio 43221 (Battelle Memorial Institute)

Refractories Division

Trustee: KENNETH A. BAAB (1970)
Bethlehem Steel Corp., Homer Research Labs.
Bethlehem, Pa. 18016
Chairman: WILLIAM D. FITZPATRICK, 412 E. Promenade
Mexico, Mo. 65265 (A. P. Green Refractories Co.)
Vice Chairman: CHARLES A. MCFADDEN
Bickley Furnaces, Inc., 550 State Rd.
Philadelphia, Pa. 19114
Secretary: DAVID H. HUBBLE
82 Sequoia Dr., R.R.3, Export, Pa. 15632
(United States Steel Corp.)

Structural Clay Products Division

Trustee: ARTHUR J. JABBUSCH (1972)
Pomona Pipe Products Co., Pomona Sta.
Greensboro, N. C. 27400
Chairman: ROBERT W. RICHARDS, Richards Brick Co.
Box 407, 234 Springer, Edwardsville, Ill. 62025
Chairman-Elect: SHERWOOD E. PATEK
Midland Brick & Tile Co., Chillicothe, Mo. 64601
Vice Chairman: ROGER C. STOEN, Can-Tex Industries
Div. of Harsco Corp., Fourth and Washington St.
Cannelton, Ind. 47520
Secretary: JOHN H. VAN RAVESTEIN
J. C. Steele & Sons, Inc., Box 951, Statesville, N.C. 28677

White Wares Division

Trustee: WALTER W. PERKINS (1971) 871 Jacoby Rd.
Copley, Ohio 44321 (Norton Chemical Process Products
Div.)
Chairman: WILLIAM B. CAMPBELL, 1892 Inchcliff Rd.
Columbus, Ohio 43221 (Ohio State University)
Chairman-Elect: DONALD L. HEATH, Coors Porcelain Co.
600 Ninth St., Golden, Colo. 80401
Vice Chairman: ERNEST L. KASTENBEIN
375 Washington Ave., Rutherford, N. J. 07070
(Rutgers University)
Secretary: ROBERT B. OBERST
Industrial Ceramic Products, Inc.
965 W. Fifth Ave., Columbus, Ohio 43212

Ceramic Educational Council

Trustee: DAVID R. WILDER (1971) Iowa State University
Dept. of Ceramic Engineering, Ames, Iowa 50010
President: WILLIS G. LAWRENCE, State University of
New York, College of Ceramics at Alfred University
Alfred, N. Y. 14802
President-Elect: ROBERT E. MOORE
University of Missouri—Rolla
School of Mines & Metallurgy, Rolla, Mo. 65401
Vice President: MALCOLM G. MCLAREN
Rutgers University, School of Ceramics
New Brunswick, N. J. 08903
Secretary: W. C. HACKLER
Virginia Polytechnic Institute
Dept. of Metals & Ceramic Engineering
Blacksburg, Va. 24061

National Institute of Ceramic Engineers

Trustee: WINSTON DUCKWORTH (1971)
Battelle Memorial Institute
505 King Ave., Columbus, Ohio 43201
President: MURRAY C. GAUTSCH,
540 Golfview Dr., Vero Beach, Fla. 32960
President-Elect: HAROLD D. PRIOR
Chas. Taylor Sons Co.
Box 44040, Cincinnati, Ohio 45244
Vice President: J. R. TINKLEPAUGH, State University of
New York, College of Ceramics at Alfred University
Alfred, N. Y. 14802
Secretary-Treasurer: E. P. MCNAMARA
106 Fir Trail, Marshall, Tex. 75670
(Marshall Tiles, Inc.)

TABLE OF CONTENTS

VOLUME 52, 1969

January [No. 1], pp. 1–62

1. J. S. Nadeau: Dependence of Flow Stress on Nonstoichiometry in Oxygen-Rich Uranium Dioxide at High Temperatures 1
2. D. K. Nath and F. A. Hummel: Synthesis of Vanadate and Arsenate Spodiosites and Interpretation of Optical Spectra of Manganese-Doped Sr_2VO_4Cl 8
3. Ivan B. Cutler: Effect of Water Vapor on the Sintering of Glass Powder Compacts 11
4. Ivan B. Cutler: Sintering of Glass Powders During Constant Rates of Heating 14
5. J. F. MacDowell and G. H. Beall: Immiscibility and Crystallization in Al_2O_3-SiO_2 Glasses 17
6. David Kalish and Edward V. Clougherty: Densification Mechanisms in High-Pressure Hot-Pressing of HfB_2 26
7. David Kalish, Edward V. Clougherty, and Konstantine Kreder: Strength, Fracture Mode, and Thermal Stress Resistance of HfB_2 and ZrB_2 30
8. K. Nassau and J. W. Shiever: Cupric Oxide-Molybdenum Oxide Phase Diagram in Air and in Oxygen 36
9. Robert A. Schoenlaub: Oxidation of Pyrite 40
10. J. F. Young: Influence of Tricalcium Aluminate on the Hydration of Calcium Silicates 44
11. E. J. Korda, L. H. Pruden, and J. P. Williams: Three-Dimensional and Stereo Observations in Glass and Ceramic Systems 46

Discussions and Notes

P. T. B. Shaffer: Comments Regarding the Structure of Beta SiC Whiskers 51
J. C. Haddon, E. A. Rogers, and D. J. Williams: Absorption Spectra of First Row Transition Metal Ions in Phosphate Glasses 52
Ernest M. Levin: X-Ray Determination of the Thermal Expansion of Silver Nitrate 53
Y. Baskin: Preparation and Properties of ThP and ThP-UP Solid Solutions 54
R. J. Brook: Pore-Grain Boundary Interactions and Grain Growth 56
P. T. Sarjeant and Rustum Roy: Ti^{4+} Coordination in Glasses in RO-TiO_2 Systems 57
Thomas S. Montgomery: Lattice Spacings of Periclase-Chromite Solid Solutions 59
Nobuo Setaka and Koichi Ejiri: Influence of Oxygen on Growth of 2H-SiC Whiskers 60
Werner Ostertag: Magnetic Susceptibility of Uranium(IV) Glasses 61

February [No. 2], pp. 63–114

12. H. Arend and L. Kihlborg: Phase Composition of Reduced and Reoxidized Barium Titanate 63
13. Michael L. Hair and Inci Altug: Ion-Selective Properties of a Polished Porous Glass 65
14. Sumio Sakka: Phototropy of Alkaline Earth Tungstates Doped with Bismuth 69
15. J. F. Duncan, K. J. D. MacKenzie, and P. K. Foster: Kinetics and Mechanism of High-Temperature Reactions of Kaolinite Minerals 74
16. P. Tyrolerova and W-K. Lu: Volume Change on Freezing of Al_2O_3 77
17. R. G. Shore and Barbara M. Wanklyn: The Systems PbF_2-AlF_3 and CaF_2-AlF_3 79
18. D. A. Shockey and G. W. Groves: Origin of Water-Induced Toughening in MgO Crystals 82
19. M. F. Berard and D. R. Wilder: Cation Self-Diffusion in Polycrystalline Y_2O_3 and Er_2O_3 85
20. R. A. Eppler: Crystallization and Phase Transformation in TiO_2-Opacified Porcelain Enamels: I, Theory 89
21. R. A. Eppler: Crystallization and Phase Transformation in TiO_2-Opacified Porcelain Enamels: II, Comparison of Theory with Experiment 94
22. S. M. Wiederhorn: Fracture Surface Energy of Glass 99
23. C. H. Greene and D. R. Platts: Behavior of Bubbles of Oxygen and Sulfur Dioxide in Soda-Lime Glass 106

H. Neumann and H. P. J. Wijn: Correction: Polycrystalline Hexagonal Fe_2W with Varying Ferrous Content 109

Discussions and Notes

Shoichi Okamoto, Masahiko Arase, and Shoko Okamoto: Reactive Hot-Pressing of $Ni_{1.4}Fe_{2.6}$ Oxyhydroxides 110
S. W. Freiman and L. L. Hench: Further Analysis of Glass Crystallization Kinetics 111
Marjorie R. Cantin, Allan H. Clauer, Martin S. Seltzer, and Ben A. Wilcox: Techniques for Transmission Electron Microscopy and Etch Pitting of CoO Single Crystals 112
Fennimore N. Bradley: $Pb_2Ti_2O_6F_2$, A New Pyrochlore 114

March [No. 3], pp. 115–68

24. Charles R. Manning, Jr., and T. B. Gurganus: Wetting of Binary Aluminum Alloys in Contact with Be, B_4C, and Graphite 115
25. John W. Cahn: The Metastable Liquidus and Its Effect on the Crystallization of Glass 118
26. Ralph M. Horton: Oxidation Kinetics of Powdered Silicon Nitride 121
27. M. J. D. Low, N. Ramasubramanian, and P. Ramamurthy: Reaction of HF with Porous Glass 124
28. S. Natansohn and D. H. Baird: Effect of Synthesis Parameters on the Magnetic Properties of Manganese Zinc Ferrites 127
29. B. Steverding: Brittleness and Impact Resistance 133
30. P. A. Sewell and A. M. Morgan: Methanol Vapor Adsorption on Silica and Soda-Lime-Silica Glass 136
31. E. F. Williams, W. G. Hodgson, and J. S. Brinen: Synthetic Photochromic Sodalite 139
32. Norman D. Stout, Clarence L. Hoenig, and Paul C. Nordine: Knudsen Cell Studies of the Vaporization of Samarium Dicarbide 145
33. C. L. Babcock: Substructure Classification of Silicate Glasses 151
34. V. Čáslavská, D. W. Strickler, and Rustum Roy: Optimization of Properties of Photoconductive Oxide Glasses 154
35. A. J. Pointon and R. C. Saull: Solid State Reactions in Lithium Ferrite 157
36. J. R. MacEwan and R. L. Stoute: Annealing of Irradiation-Induced Thermal Conductivity Changes in ThO_2-1.3 wt% UO_2 160

Discussions and Notes

H. de Waal: Influence of Proton Exchange on Internal Friction in Alkali Silicate Glasses 165
Tapan K. Gupta: Comments on "Sintering Kinetics Based on Geometric Models" 166

April [No. 4], pp. 169–232

37. James E. Shelby, Jr., and Delbert E. Day: Mechanical Relaxations in Mixed-Alkali Silicate Glasses: I, Results 169

38. V. S. Stubican, C. Greskovich, and H. A. McKinstry: Kinetics of Precipitation and Measurements of Strain in the System $MgO-Al_2O_3-Cr_2O_3$ 174
39. Tetsuo Noguchi, Tsutomu Ōkubo, and Osamu Yonemuchi: Reactions in the System ZrO_2-SrO 178
40. Peter C. Held and D. R. Wilder: High-Temperature Hemispherical Spectral Emittance of Uranium Oxides at 0.65 and 0.70 μm 182
41. K. N. Woods and M. E. Fine: Nucleation and Growth of Magnesioferrite in MgO Containing 0.9% Fe^{3+} 186
42. K. W. Lay and R. E. Carter: Time and Length Corrections in the Analysis of the Initial Stages of Diffusion-Controlled Sintering 189
43. R. C. Bradt and G. S. Ansell: Aging in Tetragonal Ferroelectric Barium Titanate 192
44. Howard B. Johnson and Frank Kessler: Kaolinite Dehydroxylation Kinetics 199
45. W. P. Stollar and H. I. Moss: Pressure Sintering of Gallium Arsenide 204
46. Yoshihide Kotera and Michiko Yonemura: Role of Catalysts in the Transformation of Germanium Dioxide 210

Discussions and Notes

R. J. Bratton: Defect Structure of Y_2O_3-ZrO_2 Solid Solutions 213
E. A. Weaver, H. D. Merchant, and R. P. Poplawsky: Growth of Fe-Ni Oxide Spinel Single Crystals by Arc Image Techniques 214
D. P. H. Hasselman: Micromechanical Thermal Stresses and Thermal Stress Resistance of Porous Brittle Ceramics 215
L. H. Sjodahl: X-Ray Measurement of Strain in TaC Due to Composition Gradients 216
G. R. Terwilliger and R. S. Gordon: Correlations Between Models for Time-Dependent Creep with Concurrent Grain Growth 218
Ashok K. Vijh: Electrochemical Oxidation of Semiconducting Ceramic Barium Titanate 219
Norris W. Jones: Discussion of "Subsolidus Equilibria in the System MgO-GeO_2-MgF_2" 220
George Robert McCormick: Reply to "Discussion of 'Subsolidus Equilibria in the System MgO-GeO_2-MgF_2'" 221
Patrick S. Nicholson: Technique for Estimating Thickness of a Thin Section 221
Karl Koyama: Thermal Conductivity of Magnesium Fluoride Between 25° and 900°C 222
W. Ostertag, E. A. Hoar, and G. R. Fischer: Stereographic Projection of Crystal Structures: Example, β-Spodumene 224
J. A. Duffy and M. D. Ingram: Formation of Acetate Glasses 224
T. H. Ramsey and Stanley B. Rice: Effects of Heat Treatment on Electron-Gun-Deposited SiO_2 Films 225
R. C. Progelhof and J. L. Throne: Effect of Surface Porosity on Emittance of an Opaque Substance 227
R. R. Tummala and A. L. Friedberg: Strength of Glass-Crystal Composites 228
D. G. Grossman and J. O. Isard: Lead Titanate Glass-Ceramics 230
John S. Berkes and William B. White: Calculation of Volume Free Energy of Nucleation of a Crystalline Phase from a Multicomponent Regular Solution 231

May [No. 5], pp. 233–92

47. T. B. Lindemer, M. D. Allen, and J. M. Leitnaker: Kinetics of the Graphite-Uranium Dioxide Reaction from 1400° to 1756°C 233
48. A. J. Burggraaf and H. C. Van Velzen: Glasses Resistant to Sodium Vapor at Temperatures to 700°C 238
49. C. K. Chyung: Secondary Grain Growth of $Li_2O-Al_2O_3-SiO_2-TiO_2$ Glass-Ceramics 242
50. Naohiro Soga: Elastic Constants of Polycrystalline BeO as a Function of Pressure and Temperature 246
51. G. M. Biggar and M. J. O'Hara: Monticellite and Forsterite Crystalline Solutions 249
52. T. B. Weston, A. H. Webster, and V. M. McNamara: Lead Zirconate-Lead Titanate Piezoelectric Ceramics with Iron Oxide Additions 253
53. Karl E. Spear and James M. Leitnaker: Formation of Active Carbon in Twin-Crucible Studies of Vanadium Carbonitride Solutions 257
54. R. A. Eppler and G. H. Spencer-Strong: Role of P_2O_5 in TiO_2-Opacified Porcelain Enamels 263
55. David N. French: X-Ray Stress Analysis of WC-Co Cermets: I, Procedures 267
56. David N. French: X-Ray Stress Analysis of WC-Co Cermets: II, Temperature Stresses 271
57. E. A. Giess, B. A. Scott, G. Burns, D. F. O'Kane, and A. Segmüller: Alkali Strontium-Barium-Lead Niobate Systems with a Tungsten Bronze Structure: Crystallographic Properties and Curie Points 276
58. Shigekazu Minagawa and Tetsuo Gejyo: X-Ray Microtopographs of Alpha Alumina Whiskers 282

Discussions and Notes

Jörg Arndt: Effect of Impurities on Densification of Silica Glass 285
D. H. Sturgis and J. A. Nelson: Effects of Gaseous Adsorbates on the Compaction of Ultrafine Active Alumina Powder 286
J. D. Birle and E. G. Ehlers: High Pressure Phase of Al_2GeO_5 287
D. P. H. Hasselman: Griffith Criterion and Thermal Shock Resistance of Single-Phase Versus Multiphase Brittle Ceramics 288
R. C. Rossi: Thermal Expansion of BeO-SiC Composites 290
Martin Goldstein: Comments on "Role of Densification in Deformation of Glasses Under Point Loading" 291
F. M. Ernsberger: Reply 292
P. Tyrolerova and W-K. Lu: Volume Change of Mullite on Solidification 292

June [No. 6], pp. 293–350

59. C. W. Weaver and M. S. Paterson: Deformation of Cube-Oriented MgO Crystals Under Pressure 293
60. Michael Tokar: Microstructure and Magnetic Properties of Lead Ferrite 302
61. J. S. Reed and H. F. Kay: Optical Spectra of 3*d* Transition Metal Ions in $MgO \cdot 3.5Al_2O_3$ Spinel 307
62. Gerald L. DePoorter: Evaluation of a Statistical Thermodynamic Method for Calculating the Composition Dependence of Chemical Potentials in Nonstoichiometric Zirconium Carbide 311
63. G. M. Biggar: The System CaO-NiO-SiO_2 316
64. Douglas A. Olsen, Richard E. Johnson, Joseph Kivel, and Frank C. Albers: Kinetics of Leaching of Lead Glass by Ethylenediaminetetraacetic Acid 318
65. J. P. De Luca, R. J. Eagan, and C. G. Bergeron: Crystallization of $PbO \cdot 2B_2O_3$ from Its Supercooled Melt 322
66. C. V. Gokularathnam, S. W. Freiman, R. T. DeHoff, and L. L. Hench: Thickness Error in Quantitative Transmission Microscopy of Ceramics 327
67. T. P. Jones, R. L. Coble, and C. J. Mogab: Defect Diffusion in Single Crystal Aluminum Oxide 331
68. E. A. Weaver and C. T. Li: Growth of Complex Oxide Single Crystals from Fluoride Melts 335

Discussions and Notes

Egon Dick and Klaus Peter: Generation of Deep Cracks in Glass 338
F. M. Ernsberger: Reply 339
R. J. Brook: Pores and Grain Growth Kinetics 339
A. L. Pranatis: Coaxing Effect During the Dynamic Fatigue of Glass 340
Y. Baskin and P. D. Shalek: Melting Point Studies of the System UP-US 341

Toshio Hirai and Nakamichi Yamasaki: Tentative Method for Crystallite Size Determination of Beryllium Oxide .. 343
Rustum Roy: Gel Route to Homogeneous Glass Preparation 344
Daniel E. Rase: Comments on "Silica Transformations in the System PbO-SiO_2" 345
W. R. Foster: Discussion of "Silica Transformations in the System PbO-SiO_2" 345
W. Fix, H. Heymann, and R. Heinke: Subsolidus Relations in the System $2CaO \cdot SiO_2$-$3CaO \cdot P_2O_5$ 346
G. S. Perry and J. R. Alderton: Dielectric Properties of Titanate-Alumina Ceramics 348
P. V. McAllister and I. B. Cutler: Evaluation of Thermal Grooving Data 348
R. J. Charles: Effect of Uniaxial Stress on Glass Resistivity 350

July [No. 7], pp. 351–404

69. J. R. Schorr and J. O. Everhart: Thermal Behavior of Pyrite and Its Relation to Carbon and Sulfur Oxidation in Clays 351
70. R. J. Beals and R. S. Kern: Irradiation Testing (Pulse Conditions) of the Ternary Fuel System for the Power Burst Facility 355
71. D. Edelson, R. E. Jaeger, and J. C. Williams: Transient Effects of Nuclear Radiation on the Dielectric Properties of Refractory Low-Loss Ceramics at Microwave Frequencies 359
72. R. C. DeVries and W. L. Roth: Critical Evaluation of the Literature Data on Beta Alumina and Related Phases: I, Phase Equilibria and Characterization of Beta Alumina Phases 364
73. Paul G. Riewald and Lawrence H. Van Vlack: Slip Behavior and Hardness Indentations in MnSe and MnSe-MnS Solid Solutions 370
74. J. B. Holt, H. G. Sockel, and H. Schmalzried: Mobility of Cation Vacancies in the Solid Solution KCl-RbCl 375
75. Henry P. Kirchner: Thermal Expansion Anisotropy of Oxides and Oxide Solid Solutions 379
76. T. Vojnovich and T. D. McGee: Determination of Donor Gradients Within Surface Barriers Formed on Dense Gd-Doped Barium Titanates 386
77. Howard A. Robinson: Physical Properties and Structure of Silicate Glasses: I, Additive Relations in Alkali Binary Glasses 392

Discussions and Notes

Nobuo Setaka and Koichi Ejiri: Evidence for 2H-SiC Whisker Growth by a Screw Dislocation Process 400
Takashi Yamaguchi and Takashi Shiraishi: Eutectoid Decomposition of $CuFe_2O_4$-Fe_3O_4 Spinel Solid Solution Including $CuFe_2O_3$ 401
R. F. Bartholomew and H. J. Holland: Vitreous Nature of Some New Inorganic Glasses as Shown by X-Ray Diffraction 402
W. C. Levengood: Dislocations and Surface Flaws on Glass 403
F. M. Ernsberger: Reply 404

August [No. 8], pp. 405–62

78. D. A. Reeve and Norman F. H. Bright: Phase Relations in the System CaO-Ta_2O_5-SiO_2 405
79. P. W. Sunderland and A. C. D. Chaklader: Creep During Dehydroxylation of Magnesium Hydroxide 410
80. J. E. Ayer and F. E. Soppet: Vibratory Compaction: III, Rate of Entry 414
81. R. J. Bratton: Initial Sintering Kinetics of $MgAl_2O_4$ 417
82. Roy W. Rice: CaO: I, Fabrication and Characterization 420
83. Roy W. Rice: CaO: II, Properties 428
84. W. R. Manning, O. Hunter, Jr., and B. R. Powell, Jr.: Elastic Properties of Polycrystalline Yttrium Oxide, Dysprosium Oxide, Holmium Oxide, and Erbium Oxide: Room Temperature Measurements 436
85. Mel I. Mendelson: Average Grain Size in Polycrystalline Ceramics 443
86. J. T. Bittel, L. H. Sjodahl, and J. F. White: Steam Oxidation Kinetics and Oxygen Diffusion in UO_2 at High Temperatures 446

Discussions and Notes

Ernest G. Ehlers: Discussion of "Technique for Estimating Thickness of a Thin Section" 451
S. J. Bhatt and H. D. Merchant: Influence on Stoichiometry of Lattice Parameter in Fe_3O_4, NiO, and Ni-Fe Ferrite 452
C. S. Morgan: Activation Energy in Sintering 453
William D. Scott: Impurity Deposits on Alumina Crystals 454
C. D. Wirkus, M. F. Berard, and D. R. Wilder: Oxygen Diffusion in Gd_2O_3 456
D. P. H. Hasselman: Griffith Flaws and the Effect of Porosity on Tensile Strength of Brittle Ceramics 457
D. P. H. Hasselman: Analysis of the Strain at Fracture of Brittle Solids with High Densities of Microcracks 458
D. E. Smith, T. Y. Tien, and L. H. Van Vlack: The System NiO-CaO 459
Stuart L. Blank and Joseph A. Pask: Solubility Limits in the MgO-Fe_2O_3 System as Determined by Diffusion 460
J. M. Kerr, R. V. Carlson, and W. A. Shield: Alpha Autoradiography of $(U,Pu)O_2$ Microspheres 461

September [No. 9], pp. 463–522

87. Gregory J. McCarthy, William B. White, and Rustum Roy: Phase Equilibria in the 1375°C Isotherm of the System Sr-Ti-O 463
88. A. H. Heuer, D. J. Sellers, and W. H. Rhodes: Hot-Working of Aluminum Oxide: I, Primary Recrystallization and Texture 468
89. R. D. Carnahan, K. R. Janowski, and R. C. Rossi: Elastic Behavior of Arc-Cast Zirconium Carbide-Graphite Alloys . 475
90. Thomas S. Montgomery: Optical Reflectance Spectra of Cr^{3+} in MgO Solid Solutions 478
91. John S. Berkes and William B. White: Phase Relations in the System $Li_2O \cdot B_2O_3$-B_2O_3-NiO 481
92. S. M. Wiederhorn: Fracture of Sapphire 485
93. W. R. Manning and O. Hunter, Jr.: Elastic Properties of Polycrystalline Yttrium Oxide, Holmium Oxide, and Erbium Oxide: High-Temperature Measurements 492
94. M. L. Pearce and C. Basch: Oxidation Kinetics of Single Crystal Titanium Nitride by Optical Measurements 496
95. R. E. Tischer: Heat of Annealing in Simple Alkali Silicate Glasses 499
96. Renichi Kondo and Masaki Daimon: Early Hydration of Tricalcium Silicate: A Solid Reaction with Induction and Acceleration Periods 503

Discussions and Notes

N. J. Kreidl and M. S. Maklad: Effect of Water Content on Phase Separation in Soda-Silica Glasses 508
A. H. Heuer: Transgranular and Intergranular Fracture in Polycrystalline Alumina 510
D. K. Reimann and T. S. Lundy: Diffusion of ^{233}U in UO_2 511
Takeshi Takamori, Hirokichi Seo, and Minoru Tashiro: Polarization Effects in Semiconducting Oxide Glasses Containing Na_2O 513
Lee G. Radosevich and Wendell S. Williams: Low-Temperature Thermal Conductivity of Uranium Nitride 514
D. M. J. Compton and T. E. Firle: Reduction of TiO_2 Powders and Rutile Single Crystals 515
Yoshihiro Matsuo, Hiromu Sasaki, Shigeru Hayakawa, Fumikazu Kanamaru, and Mitsue Koizumi: High-Pressure Synthesis of Perovskite-Type $Pb(Zn_{1/3}Nb_{2/3})O_3$ 516

D. P. H. Hasselman: Crack Growth and Creep in Brittle Ceramics 517
S. J. Schneider and C. L. McDaniel: The BaO-Pt System in Air 518
T. Y. Tien, J. J. Rosen, W. C. Bigelow, and V. Sanvordenker: Microhardness of TiO_2-Nb_2O_5 Solid Solutions 520
Scott Anderson, Dinesh Tandon, L. B. Kohlenberger, and F. G. Blair: Strength of Adhesion of Dried Clay Slurries to Window Glass as a Function of Slurry pH 521
P. K. Mehta: Morphology of Calcium Sulfoaluminate Hydrates 521

October [No. 10], pp. 523–70

97. K. S. Mazdiyasni, R. T. Dolloff, and J. S. Smith II: Preparation of High-Purity Submicron Barium Titanate Powders . 523
98. Luke L. Y. Chang and Bert Phillips: Phase Relations in Refractory Metal-Oxygen Systems 527
99. Jack L. Henry and Robert Blickensderfer: The Quaternary System U-C-O-N at 1700°C 534
100. T. J. Sokolowski and M. H. Manghnani: Adiabatic Elastic Moduli of Vitreous Calcium Aluminates to 3.5 Kilobars 539
101. Salil K. Roy: Characterization of Porosity in Porcelain-Bonded Porous Alumina Ceramics 543
102. Granger K. Chui and Robert Gardon: Interaction of Radiation and Conduction in Glass 548
103. O. S. Narayanaswamy and Robert Gardon: Calculation of Residual Stresses in Glass 554
104. Milton Ohring and King Lien Tai: Gas-Filled Bubbles in Ionic Solids 559

Discussions and Notes

D. Lynn Johnson: Discussion of "Time and Length Corrections in the Analysis of the Initial Stages of Diffusion-Controlled Sintering" 562
Jack L. Prentice: Scanning Electron Microscopy of BeO Whiskers Formed on the Surface of Burning Beryllium Droplets 564
R. L. Moon and R. M. Fulrath: Vaporization and Surface Phases in the Lead Zirconate-Lead Titanate System 565
Klaus-Eckart Maass: Properties of Ba_3P_2 and Other Barium Phosphides 566
T. Vojnovich and T. D. McGee: Correction: Determination of Donor Gradients Within Surface Barriers Formed on Dense Gd-Doped Barium Titanates 567
C. S. Yust and C. J. McHargue: Comments on "Dependence of Flow Stress on Nonstoichiometry in Oxygen-Rich Uranium Dioxide at High Temperatures" 568
J. S. Nadeau: A Reply 569
J. A. Malone, J. F. Dorrian, O. Muller, and R. E. Newnham: Crystal Structure of Lu_2TeO_6 570

November [No. 11], pp. 571–630

105. Delbert E. Day and W. E. Steinkamp: Mechanical Damping Spectrum for Mixed-Alkali R_2O-Al_2O_3-$6SiO_2$ Glasses 571
106. Takeo Fujino and Keiji Naito: Solubility of KUO_3 in $BaUO_3$ 574
107. R. J. Beals, J. H. Handwerk, and B. J. Wrona: Behavior of Urania–Rare-Earth Oxides at High Temperatures 578
108. Takeshi Takamori, Hirokichi Seo, and Minoru Tashiro: Electrical Resistivity of Titanium-Containing Glasses 582
109. T. D. Gulden: Mechanical Properties of Polycrystalline β-SiC 585
110. Vladimír Šatava and František Škvára: Mechanism and Kinetics of the Decomposition of Solids by a Thermogravimetric Method 591
111. R. B. Day and W. A. Johnston: Mechanical Behavior of Lithium Fluoride at High Temperatures 595
112. D. P. H. Hasselman: Unified Theory of Thermal Shock Fracture Initiation and Crack Propagation in Brittle Ceramics 600
113. A. M. Bishay and L. Makar: Role of Iron in Calcium Phosphate Glasses 605
114. Edward E. Hansen, Zuhair A. Munir, and Martha J. Mitchell: Sublimation Pressure and Sublimation Coefficient of Single-Crystal Lead Selenide 610
115. Ram A. Sharma and Irving Johnson: Phase Diagrams for the Systems $MgCl_2$-MgF_2, $CaCl_2$-MgF_2, and NaCl-MgF_2 612
116. W. G. Staley, Jr., and G. W. Brindley: Development of Noncrystalline Material in Subsolidus Reactions Between Silica and Alumina 616
117. S. V. Ramani, E. C. Subbarao, and K. V. G. K. Gokhale: Kinetics of Zircon Synthesis 619

Discussions and Notes

Nobuo Setaka and Zenzaburo Inoue: Beta Silicon Carbide Whiskers Prepared on a Molybdenum Substrate 624
G. H. Frischat: Evidence for Calcium and Aluminum Diffusion in SiO_2 Glass 625
Yoji Kawamoto and Shoji Tsuchihashi: Glass-Forming Regions and Structure of Glasses in the System Ge-S 626
John H. Ainsworth and Robert E. Moore: Fracture Behavior of Thermally Shocked Aluminum Oxide 628
John P. De Luca and C. G. Bergeron: Diffusion of Lead in a Lead Borate Glass 629
T. J. Sokolowski and M. H. Manghnani: Correction: Adiabatic Elastic Moduli of Vitreous Calcium Aluminates to 3.5 Kilobars 630

December [No. 12], pp. 631–692

118. J. B. Holt and Marcia Y. Almassy: Nitrogen Diffusion in Uranium Nitride as Measured by Alpha Particle Activation of ^{15}N 631
119. K. J. D. MacKenzie: Infrared Kinetic Study of High-Temperature Reactions of Synthetic Kaolinite 635
120. D. L. Kinser and L. L. Hench: Electrode Polarization in Alkali Silicate Glasses 638
121. D. W. Lee and J. S. Haggerty: Plasticity and Creep in Single Crystals of Zirconium Carbide 641
122. J. G. Grabmaier and H. R. Falckenberg: Strength of Flame-Fusion-Grown Magnesium Aluminum Spinel 648
123. F. E. Wagstaff: Crystallization and Melting Kinetics of Cristobalite 650
124. G. R. Crane, J. G. Bergman, Jr., and A. M. Glass: Ammonium Iodate—A Potentially Useful Nonlinear Optical Material 655
125. A. Paul and J. M. Rusin: Ultraviolet Absorption of Pentavalent Vanadium in Binary Alkali Borate Glasses 657
126. D. A. Krohn and A. R. Cooper: Strengthening of Glass Fibers: I, Cladding 661
127. A. R. Cooper and D. A. Krohn: Strengthening of Glass Fibers: II, Ion Exchange 665
128. Stuart L. Blank and Joseph A. Pask: Diffusion of Iron and Nickel in Magnesium Oxide Single Crystals 669

Discussion and Notes

M. J. Bannister: Surface Enthalpy of Thoria Gel 675
Michael L. Hair: The Structure of Alkali Silicate Glass 677
Barrie H. Bieler: Further Discussion of "Technique for Estimating Thickness of a Thin Section" 678
C. E. Semler and W. R. Foster: Studies in the System BaO-Al_2O_3-SiO_2: IV, The System Celsian-Alumina and the Join Celsian-Mullite 679
J. J. Mills: High Shear Rate Rheology of Liquid Glass 680
L. M. Smiser and Thomas D. McGee: Transmission Electron Microscopy of Sodium Chloride 681
Author Index to The Journal 683
Subject Index to The Journal 686

CERAMIC ABSTRACTS

December 1969 *SECTION*

Compiled by the American Ceramic Society

AUTHOR INDEX FOR 1969

The reference number in parentheses refers to the monthly issue of *Ceramic Abstracts;* the number following is the page number. The letter B or P preceding the reference number indicates an abstract of (B) a book, bulletin, or separate publication or (P) a patent. The italic letter following the page number indicates the position of the abstract on the page.

Aas, H. G. Monocrystalline directional sonic transducer, P (5) 184*i*.

Abdrashitova, E. I., and Petrovskii, G. T. Electron paramagnetic resonance of ions of the iron transition group in fluoroberyllate glasses, (8) 276*f*.

Abe, Heiji. See Okada, Yoshiji.

Abe, Hisashi. See Kubo, Takeji.

Abeles, T. P., and Bos, W. G. Dimensional analysis of magnetic susceptibility calculations, (10) 343*i*.

Abernethy, I. A. See Feichter, H. R.

Aboaf, J. A. Deposition and properties of aluminum oxide obtained by pyrolytic decomposition of an aluminum alkoxide, (4) 131*d*.

Abolina, V., and Lukes, R. M. Asbestos-phosphoric acid molding composition, P (1) 13*g*.

Abowitz, G., Arnold, E., and Ladell, J. Symmetry of interface charge distribution in thermally oxidized silicon, (4) 158*i*.

Abraham, D. See Lehmann, H.

Abraham, M. M. See Boatner, L. A.

Abraham, M. M., Clark, G. W., Finch, C. B., Reynolds, R. W., and Zeldes, H. Ground-state splitting of trivalent Gd and Cm in $ZrSiO_4$, $HfSiO_4$, and $ThSiO_4$ determined by SER, (11) 385*c*.

Abraham, M. M., Weeks, R. A., Clark, G. W., and Finch, C. B. Electron spin resonance of rare-earth ions in CeO_2:Yb^{3+} and Er^{3+}, (2) 76*g*.

Abraham, R. C. See Heller, H. B.

Abraham, R. P. See Ramsey, T. H., Jr.

Abrahams, S. C. See Jamieson, P. B.; Nassau, K.

Abrahams, S. C., Bernstein, J. L., and Jamieson, P. B. Crystal structure of the transition-metal molybdates and tungstates (IV) paramagnetic $CuMoO_4$, (4) 130*e*.

Abrahams, S. C., Jamieson, P. B., and Bernstein, J. L. Crystal structure of piezoelectric bismuth germanium oxide, $Bi_{12}GeO_{20}$, (4) 130*c*.

Abramowitz, S., and Levin, I. W. Vibrational analysis of SeF_5 and WF_5, (4) 163*f*.

Abrams, L., and Low, M. J. D. Thermal decomposition of fibrillar synthetic boehmite, (7) 262*b*.

Abramson, I. G. Use of neutrons for moisture control in the furnace, (1) 3*e*. See Kichkina, E. S.

Abramyan, A. V., Aramyan, V. G., and Melkonyan, M. T. Rovenskie basalts as raw materials for pressed stoneware ceramics, (6) 219*d*.

Abrasive Products, Inc. Butt joint for flexible abrasive sheet material, P (1) 1*g*.

Abrol, Y. P. See Srivastava, R. C.

AB Tetra Pak. Method of applying preferably band-shaped metal parts with good mechanical adhesion to a metal frame coated with insulating, preferably ceramic, material, P (5) 183*j*.

Abukov, A. A., Zhukov, O. A., Podvigalkina, G. Ya., and Beketov, Yu. E. Apparatus for testing glass specimens at various temperatures and in vacuo, (2) 46*f*.

Acara, N. A. Zeolite N and process for preparing same, P (4) 126*b*.

Accary, A. See Bazin, J.; Boncoeur, M.; Dogu, A.; Magnier, P.

Accary, A., Magnier, P., and Marchal, M. Method of extruding metallic carbides and in particular uranium monocarbide, P (6) 217*g*.

Acciarri, J. A., Ziegenhain, W. C., and Ziegler, D. L. Process for producing alpha alumina monohydrate, P (4) 125*j*.

Accountius, O. E. Process for making graphitic-type fibers, P (4) 279*j*.

ACF Industries, Inc. Outlet structure for unloading bulk materials either by gravity or pneumatically, P (2) 74*h*.

Achar, B. N. N. See Brindley, G. W.

Acheson, R. J. See Jones, K. A.

Achhammer, J. See Jacobi, R.

Ackerman, S. C. Manufacture of coiled lamp filaments, P (11) 371*c*.

Ackermann, C., and Hennicke, H. W. Problem of dust measurement in the ceramic industry, (6) 227*a*.

Ackermann, R. J., Faircloth, R. L., and Rand, M. H. Thermodynamic study of the vaporization behavior of the substoichiometric plutonium dioxide phase, (4) 161*e*.

Acquaviva, S. J., and Bortz, S. A. (editors). Structural Ceramics and Testing of Brittle Materials, B (11) 390*i*.

Adachi, Akira; Ogino, Kazumi; and Hara, Shigeta. Rate and mechanism of silica reduction, (9) 309*a*.

Adachi, Gin-ya; Kato, Iwao; Shiokawa, Jiro; and Ishino, Toshio. Preparation of yttrium hydroxide and its thermal decomposition in nitrogen stream, (8) 296*e*.

Adachi, Shozo. See Tanemura, Fumikazu.

Adachi, Yuko. See Tokuyama, Takashi.

Adair, R. B., and Browning, J. S. Flotation of muscovite from Alabama graphitic-mica schist ore, (10) 348*g*.

Adami, A., and Ridge, M. J. Observations on calcium sulfate dihydrate formed in media rich in phosphoric acid (I) precipitation of calcium sulfate dihydrate; (II) derived calcium sulfate hemihydrate, (9) 326*j*.

Adami, L. H., and Joe, C. J. Heats of formation of four anhydrous sodium borates, (1) 30*c*.

Adams, C. E. See Quan, J. T.

Adams, C. E., and Quan, J. T. Vapor pressure measurements and a structural interpretation in the liquid system rubidium monoxide-boron oxide, (4) 163*f*.

Adams, G. E., Broszkiewicz, R. B., and Michael, B. D. Pulse radiolysis studies on stable and transient complexes of platinum, (9) 328*a*.

Adams, P. B. See Campbell, D. E.

Adamski, J. A. See Lipson, H. G.

Adamski, J. A., Powell, R. C., and Sampson, J. L. Growth of uncommon verneuil crystals and their characterization by light scattering, (9) 322*b*.

Adamski, M., Jr. See Johnson, B. A.

Adamson, A. W. Adsorption model for contact angle and spreading, P (5) 191*i*.

Addamiano, A. Stabilization of cubic silicon carbide, P (2) 59*g*.

Addison, C. C., Barker, M. G., and Pulham, R. J. Reactions of liquid sodium with transition-metal oxides (I) dioxides of molybdenum, tungsten, and uranium, (1) 35*i*.

Addiss, R. R., Jr., Ghosh, A. K., and Wakim, F. G. Thermally stimulated currents and luminescence in rutile (TiO_2), (6) 239*g*.

Adler, D. Antiferromagnetism in Ti_2O_3, (2) 74*j*.

Adler, R. P. I., McCandless, L. C., Heffelfinger, R. E., and Lanstrom, D. K. Metallographic structure of continuous vapor deposited SiC filaments, (4) 110*g*.

Admiral Corp. Cermet resistance module, P (7) 256*a*. Color tube with mask interior peripheral shield of treated steel foil for improved heat radiation, P (2) 64*i*.

Ado, Kazuaki. See Nobuoka, Soichiro.

Aerofall Mills, Ltd. Slow magnetic drum ore separator control device, P (6) 230*d*.

Aerojet-General Corp. Glass fiber compositions, P (2) 52*h*. Lightweight armor with laminated base member resistant to delamination, P (8) 280*f*. Lightweight protective armor plate, P (7) 252*a*. Method of testing transparent materials, P (4) 100*a*.

Aeronca, Inc. Method and material for making joints between refractory panels, P (6) 218*a*.

Aerovox Corp. Process for manufacturing a multilayer ceramic capacitor, P (10) 345*g*.

Afonin, V. P. See Losev, N. F.

Afonina, N. S. See Ryabov, V. A.

Afonskii, N. S., and Neiman, M. Study of the phase composition of the system La_2O_3-Ta_2O_5, (10) 361*e*.

Aftandilian, V. D. Process for the production of titanium dioxide, P (10) 349*d*.

Agabal'yants, E. G. See Ovcharenko, F. D.

Agar, G. E. See Somasundaran, P.

Agar, J. Vibrating spool fluid density meter, (11) 381*d*.

Agarwal, M. K. See Patel, A. R.

Agency of Industrial Science and Technology. Producing method of carbon or carbonaceous material, P (5) 179*c*.

Agetti, A. H., Carini, R. V., and Alverson, R. F. Glass sheet feeder for cutting and processing machines, P (1) 10*f*.

Aggarwal, P. S., Bishui, B. M., and Sen, S. K. Dehydroxylation of tricalcium aluminate hexahydrate, (2) 44*c*.

Agranovskaya, A. I. See Vinnik, M. A.

Agrios, J. P., and Freiberger, E. Reciprocal microwave ferrite phase shifter, P (6) 223*a*.

Agthe, R. Apparatus for analyzing fresh concrete, P (4) 121*d*.

Agusta, B., and Hess, M. S. Low resistivity semiconductor underpass connector and fabrication method therefor, P (8) 282*c*.

Ahl, D. See Bromer, H.

Ahlert, R. H. See Milch, A.

Ahmad, F. U. See Majumdar, N. C.

Ahmad, L. I. Lattice structure of the (100) free surface of barium titanate, (6) 234*j*.

Ahmed, S. J., and Taylor, H. F. W. Crystal structures of the lamellar calcium aluminum hydrates, (4) 130*e*.

Ahn, K. Y., and McGuire, T. R. Magnetic and magneto-optic properties of Eu_2O films doped with trivalent rare-earth oxide, (7) 255*d*.

Ahrens, T. J., Gust, W. H., and Royce, E. B. Material strength effect in shock compression of alumina, (6) 234*i*.

Ahrland, S. Thermodynamics of complex formation between hard and soft acceptors and donors, B (6) 242*i*.

Ahrons, R. W. Cryoelectric memories, P (9) 312*d*.

Aia, M. A. Hydrothermal studies of the system NiO-H_2O, (2) 78*c*. Structure and luminescence of the phosphate-vanadates of yttrium, gadolinium, lutetium, and lanthanum, (4) 156*h*.

Aia, M. A., and Lublin, P. Blue luminescence in calcium chlorovanadates, (2) 75*a*.

Ainscough, J. B., and Walker, M. J. High temperature thermal conductivity of sintered uranium dioxide. (2) 56*b*.

Air Liquide, Soc. Anon. pour l'Etude et l'Exploitation des Procedes Georges Calude. Production of crystalline mordenite, P (7) 263*b*.

Air Products & Chemicals, Inc. Contact masses containing zeolite, P (9) 317*c*. Cryogenic refrigeration for crystal X-ray diffraction studies, P (4) 121*j*. Method of treating fluidizable particles, P (9) 317*h*.

Air Reduction Co., Inc. Composition resistor, P (4) 112*i*. Electrode connecting pin and assembly, P (4) 106*e*. Extruded graphite matrix containing coated particles, P (4)

106*f*. Lime fines briqueting, P (4) 92*i*. Method of making electrical resistor by recrystallization, P (8) 283*a*. Method of making film resistor, P (2) 65*g*. Method of stabilizing friction coefficient of carbonaceous base materials and the products thereof, P (5) 179*g*. Production of ultrapure titanium nitride refractory articles, P (9) 309*d*. Welding electrode and composition, P (10) 337*d*.

Airola, E. J. Inorganic glass coating and method for making, P (11) 369*a*.

Aisanich, D. J. Antishock control devices for electrically heated glass panels or the like, P (9) 307*j*.

Aitcin, P. C., Garnier, G., and Carles-Gibergues, A. Powder density measurement by hydrostatic weighing, (8) 285*i*.

Aitken, E. A., Edwards, J. A., and Joseph, R. A. Thermodynamic study of solid solutions of uranium oxide (I) uranium oxide-thorium oxide, (4) 161*b*.

Aitken, E. A., and Joseph, R. A. Thermodynamic study of solid solutions of uranium oxide (II) uranium oxide-yttrium oxide, (4) 161*d*.

Akanuma, Masanobu. See Takamori, Takeshi.

Akashi, Nobuya. Occupational fatigue factors affecting quality and production control of firebrick, (4) 104*i*.

Akashi, Tsuneo; Takahashi, Masao; Tsubouchi, Norio; Ohno, Tomeji; and Yamauchi, Fumio. Piezoelectric ceramic composition, P (11) 378*d*.

Akhtar, S., and Cable, M. Effects of atmosphere and minor constituents on the surface tension of glass melts, (4) 95*e*.

Akimoto, Okikazu, and Hasegawa, Hiroshi. Interband optical transitions in extremely anisotropic semiconductors (II) coexistence of exciton and the Landau levels, (5) 195*f*.

Akimoto, Shunichi, and Syono, Yasuhiko. High-pressure decomposition of some titanate spinels, (4) 138*j*.

Akimoto, Syun-iti. See Katsura, Takashi; Morimoto, Nobuo; Sugawara, Fuyuhiko.

Akin, G. A. See Larkins, T. H., Jr.

Akisue, Osamu. See Mannami, Michi-hiko.

Akita, K., and Kase, M. Relationship between the DTA peak and the maximum reaction rate, (5) 199*b*.

Akluli, M. E. Method of fabricating semiconductor devices, P (11) 377*i*.

Akmenkalns, I. G., Gamblin, R. L., and Lord, P. A. Ferriresonant memory system, P (11) 376*f*.

Akmenkalns, I. G., Wilfinger, R. J., and Wilson, A. D. Four terminal electrooptical logic device, P (4) 113*f*.

Akopjan, S. C. See Arija, S. M.

Akopov, E. K., and Bergman, A. G. System $Li,Na,K\|Cl$, (7) 269*j*.

Akopov, F. A., and Poluboyarinov, D. N. Thermodynamic analysis of equilibrium in the CeO_2-Ce_2O_3 system, (4) 161*g*.

Aksel'rod, E. I. See Sukharevsky, B. Ya.

Aksenov, V. S. See Sidorov, T. A.

Aktiebolaget Atomenergi. Neutron detector having a radioactive vanadium emitter, P (1) 18*g*.

Akutsu, Hidezo. See Mizuno, Hideo.

Alam, A. S. M. M., and Di Bartolo, B. Thermal dependence of fluorescence and lifetimes of Sm^{3+} in several host lattices, (4) 160*d*.

Alapin, B. G. See Sukharevsky, B. Ya.

Albee, A. L. Minor element content of coexistent Al_2SiO_5 polymorphs, (9) 324*h*.

Albers, F. C. See Olsen, D. A.

Albert, J. Clays for Brickmaking and Their Application in the Ceramic Industry, B (1) 41*e*.

Albert, P. Stability of anatase in titania enamels, (7) 246*i*. See Gosse, G.

Albinak, M. J., and Turner, W. H. Photoluminescent glass systems, P (7) 249*b*.

Albrecht, R. Clay preparation plant in a fine-ceramics plant, (1) 15*e*.

Albrecht, W. L. Method of making silica sols containing large particle size silica, P (7) 262*j*.

Albright, R. A. See Bielecki, E. J.

Alchem, Ltd. Refractory coating compositions, P (6) 218*c*.

Alco Standard Corp. Burner tube assembly for heat-treating furnace, P (5) 189*g*. Hearth for a heat-treating furnace, P (5) 189*b*.

Alcock, A. J., DeMichelis, C., Korobkin, V. V., and Richardson, M. C. Preliminary evidence for self-focusing in gas breakdown produced by picosecond laser pulses, (9) 311*h*.

Alcock, C. B. See Hawkins, R. J.; Jeffes, J. H. E.

Alcock, C. B., and Iyengar, G. N. K. Study of the oxidation-reduction equilibria of dilute magnesiowustites, (5) 200*b*.

Alcock, C. B., Javed, N. A., and Steele, B. C. H. Thermodynamics of the solution of oxygen and nitrogen in uranium monocarbide, (5) 202*b*.

Alcock, C. B., Zador, S., and Steele, B. C. H. Thermodynamic study of dilute solutions of defects in the rutile structure TiO_{2-x}, Nb_xO_{2-x}, and $Ti_{0.5}Nb_{0.5}O_{2+x}$, (5) 201*h*.

Alderoft, D., Bye, G. C., Robinson, J. G., and Sing, K. S. W. Surface chemistry of the calcination of gelatinous and crystalline aluminum hydroxides, (9) 330*g*.

Alden, T. H., and Livingston, J. D. Type II superconductors containing magnetic particles, P (9) 314*d*.

Alderton, J. R. See Perry, G. S.

Aldinger, R. Composition of enamel batches, (1) 4*e*. Evolution of sheet steel ware for enameled utensils, (6) 207*g*.

Alekseev, O. L. See Polyakov, V. E.

Alekseev, V. N. See Oblival'nvi, F. A.

Alekseeva, Z. D. System Cs_2O-SiO_2, (7) 269*h*.

Aleonard, S. See Vicat, J.

Aleonard, S., and Pouzet, C. Crystallographic studies of complex rare-earth fluorides, (9) 319*j*.

Aleonard, S., and Vicat, J. Borates of dolomite structure, (1) 25*b*

Aleshin, B. N., Ryabov, V. A., and Fedoseev, D. V. Strength of glass foil, (2) 51*h*.

Aleskovskii, V. B. See Kol'tsov, S. I.; Smirnova, M. F.

Alexander, E. M. See Searight, C. E.

Alexander, F. C. Method and means for casting syphon-jet type toilet bowls, P (11) 376*a*.

Alexander, J. A., and Shaver, R. G. High-strength whisker-reinforced metallic monofilament, P (10) 342*e*.

Alexander, J. H. See Drake, C. F.

Alexander, J. M. See Johnson, A. L.

Alexander, R. E. See Reissmueller, K. H.

Alexander, R. W., Jr. See Sievers, A. J.

Alexandropoulos, N. G. Variation of Compton scattering with changes in structure of quartz (SiO_2). (4) 163*j*. See Brumberger, H.

Alexinschi, T. See Moldovan, T.; Veiser, I.

Alford, H. E., and Veatch, F. Microsphere glass agglomerates and method for making them, P (11) 371*i*.

Alford, W. J. See Fay, H.

Algrain, A., and Fabry, G. Multipane glazing unit, P (11) 372*a*.

Ali, A. Nucleation and crystallization behavior of two glass compositions in the system Li_2O-Al_2O_3-SiO_2, (10) 338*d*.

Ali, M. A. See Rasul, S. H.

Ali, M. K. See Qaiser, M. A.

Ali, S. A., and Weiss, M. P. Fluorescent dye penetrant technique for displaying obscure structures in limestone, (1) 21*j*.

Allam, D. S., Watkins, J., and Pitt, K. E. G. Structure of continuously evaporated cermet resistors, (8) 281*g*.

Allbutt, M., Junkison, A. R., and Carney, R. F. Preparation and fabrication of uranium mononitride, phosphide, and sulfide, (4) 150*a*.

Allegheny Ludlum Steel Corp. Laboratory apparatus, P (2) 58*i*.

Allegrini, A. P. See Hecklau, F. L.

Allen, A. C. Alumina, (2) 59*i*. Appliance enameler gets ready for self-cleaning ovens, (2) 45*h*. Canada builds first float glass plant, (2) 47*c*. Cercom protects combat troops, (2) 59*j*. Crane produces 300,000 pieces of sanitary ware annually, (2) 59*j*. Fiber producer adapts European techniques, (2) 49*e*. First glass shingle line success in California, (2) 49*f*. 40% saved with electrostatic spraying, (2) 67*g*. Foundry control improves dry process enameling, (2) 45*i*. Metlox hand decorates 360,000 pieces per month, (2) 60*i*. New plant specializes in plasma sprayed ceramics, (2) 46*a*. One thousand pounds of ferrite a day, (2) 63*a*. One of the world's largest glass tanks on stream, (2) 50*j*. Quality assurance supports job shop concept, (2) 85*b*. Rainbow of colors from fast decorating line, (2) 50*f*. Smooth flow pattern speeds sanitary ware production, (2) 60*f*. Syracuse fills Canadian hotelware vacuum, (2) 60*h*. Titanates lead to other electronic ceramics, (2) 64*b*.

Allen, A. S. See Vanderheiden, D. B.

Allen, C. A. See Mannion, W. A.

Allen, D. R. See Vanderheiden, D. B.

Allen, F. G. See Buck, T. M.

Allen, George E., and Allen, Glenn E. Beneficiation of fluorspar ores, P (6) 229*c*.

Allen, Glenn E. See Allen, George E.

Allen, J. W., Shyam, M., and Pearson, G. L. Indium arsenide Gunn oscillator, P (2) 65*d*.

Allen, L. R. Apparatus for evaporation of low temperature semiconductor material by electron beam impingement on the material and comprising means for draining electric charge from the material, P (4) 112*b*. Codeposition of boron containing coatings, P (11) 369*c*. Method of making a niobium stannide coated niobium wire, P (2) 65*h*.

Allen, M. D. See Lindemer, T. B.

Allen, R. C., Gavish, E., Friedman, G. M., and Sanders, J. E. Aragonite-cemented sandstone from Outer Continental Shelf off Delaware Bay—submarine lithification mechanism yields product resembling beachrock, (8) 286*g*.

Allen, R. D. Electron beam technique for measuring thermal conductivity, (8) 285*b*.

Allen, R. E. Method of conditioning forming rollers to form glass-ceramic, P (9) 307*j*. Method of improving roll forming properties of molten materials, P (7) 249*f*.

Allen, W. C., and Taebel, W. A. Dense refractory zirconium boride bodies, P (6) 217*j*.

Allen, W. R. Combined crushing [gyratory] and attrition apparatus and method, P (10) 349*c*.

Allender, J. T. See Tipsword, R. F.

Allendorf, H. D. See Rosner, D. E.

Alliancewall Corp. Heat-resistant [refractory core] wall, P (10) 342*e*.

Allied Chemical Corp. Beneficiation of fluorspar ores, P (6) 229*c*. Manufacture of chromium spinels, P (7) 256*i*. Method for preparing superdense sodium carbonate from Wyoming trona and the product thereof, P (5) 191*c*. Process for the production of phosphoric acid and cement material, P (7) 245*f*.

Alliegro, R. A. Method [pressure sinter] of preparing plates of boron carbide powder, P (7) 252*i*.

Allis-Chalmers Mfg. Co. Anisotropic superconductor, P (2) 64*d*. Capacitance measuring means for indicating clearance in gyratory crusher and having means to compensate for stray capacitance, P (7) 262*e*. Gyratory crusher, P (4) 124*b*. Gyratory crusher clearance measuring means having resonant coupling circuits, P (7) 262*i*. Method and apparatus for preheating particulate feed material for a rotary kiln [counterflow], P (7) 261*e*. Method of preparing tetraborosilicide (B_4Si), P (5) 179*f*. Voltage graded electrical insulator, P (9) 310*a*.

Allison, D. F. Method for making field effect transistor, P (5) 183*f*.

Allmanna Svenska Elektriska Aktiebolaget. Semiconductor device comprising two parallel-connected semiconductor systems in pressure contact, P (8) 283*e*. Semiconductor device with increased reverse and forward blocking voltages, P (2) 66*e*. Thyristor with positively bevelled junctions, P (7) 258*c*.

Allnatt, A. R., and Chadwick, A. V. Thermal diffusion of strontium ions in sodium chloride crystals, (4) 160*e*.

Allnatt, A. R., and Pantelis, P. Isothermal diffusion of strontium and cobalt ions in pure NaCl crystals and reconsiderations of the Soret effect, (10) 356*e*.

Allred, W. See Spitzer, W. G.

Almaula, B. C. See Genco, J. I.

Almenningen, A., Gundersen, G., and Haaland, A. Molecular structure of aluminum borohydride, $Al(BH_4)_3$, (8) 295*i*.

Alper, A. M. Metallurgical furnace, P (6) 217*e*. See Doman, R. C.

Alper, A. M., and McNally, R. N. MgO-ZrO_2 fused cast refractory, P (4) 107*h*.

Alpha Portland Cement Co. Steam cured cement and process, P (9) 304*e*.

Alten, E. H. See Dubble, R. D.

Althaus, E. Experimental determination of the stability range of disthene (cyanite), (6) 232*f*. Experimental evidence for the kyanite-sillimanite reaction being bivariant, (7) 265*h*.

Altman, M. See Hopfinger, E. J.

Altug, I. See Hair, M. L.

Altug, I., and Hair, M. L. Ion-selective properties of sintered porous glass membranes, (5) 173*b*. Porous glass as an ionic membrane, (5) 173*i*.

Aluminum Co. of America. Process for producing kappa alumina, P (8) 288*e*. Production of ceramic bodies, P (6) 220*b*. Refractory composition, P (7) 253*b*.

Alverson, R. F. See Agett, A. H.

Alwitt, R. S. See Vijh, A. K.

Alyamovskii, S. I., Shveikin, G. P., Gel'd, P. V., and Volkova, N. M. Orthorhombic β' phases of the carbides of niobium and vanadium, (9) 326*h*.

Amato, I. Preparation of alumina and zirconia coated particle nuclear fuels, (5) 178*b*.

Amato, I., and Ardizzone, L. Preparation of UO_2-MO and UO_3-W cermets fuel by metal vapor deposition in fluidized bed and hot-pressing, (1) 12*g*.

Amato, I., Ardizzone, L., Crisa, V., and Dusi, G. Phenomenological aspects of cosintering UO_2-W cermets, (5) 177*i*.

Amato, I., and Colombo, R. L. Occurrence of exaggerated grain growth in sintered bodies, (9) 326*c*.

Amberger, E., Druminski, M., and Dietze, W. Pyrolytic preparation of borocarbides, (8) 297*a*.

Amberger, E., and Ploog, K. Formation of a tetragonal modification of boron, (8) 292*j*.

Ambler, E., Colwell, J. H., Hosler, W. R., and Schooley, J. F. Magnetization and critical fields of superconducting $SrTiO_3$, (2) 80*g*.

Amelin, E. S., and Patrushev, D. A. Apparatus for kinetic studies in high-temperature processes accompanied by changes in weight, (2) 68*j*.

Amelinckx, S. See Van Landuyt, J.

American Abrasive Co. Method of treating alumina abrasive grains with iron nitrate and products made thereby, P (5) 169*h*.

American Cast Iron Pipe Co. Ladle for use in treatment of molten metal, P (4) 106*c*.

American Colloid Co. Method and apparatus for blending pulverulent materials, P (2) 68*b*.

American Cyanamid Co. Apparatus for making titanium dioxide pigment, P (5) 190*e*. Caustic leach treatment of alumina particles to improve strength properties, P (1) 382*i*. Compact ampoule sealer, P (7) 248*d*. Electroluminescence from cooled homogeneous gallium sulfide crystal, P (8) 282*f*. Method for preparing reduced tungsten oxide, P (2) 74*e*. Novel quaternary semiconducting compositions of matter, P (5) 184*c*. Novel ternary semiconducting materials, P (10)

345*d*. Novel zinc manganese arsenide semiconducting materials, P (5) 184*c*. Preparation of an alumina catalyst support, P (1) 24*c*. Process for preparing a crystalline zeolite catalyst composite, P (1) 24*a*, P (6) 230*a*. Rare earth metal compounds and their process of preparation, P (1) 19*f*. Silica-alumina catalyst support, P (1) 24*f*. Synthesis of finely divided oxide powders, P (9) 317*g*.

American Electronic Laboratories, Inc. Tester for determining the semiconductor material type of transistors, P (11) 379*b*.

American Enka Corp. [Conical] mixing apparatus, P (5) 186*e*. Process for preparing amorphous germanium dioxide, P (10) 349*b*.

American Hoist & Derrick Co. Rotary dryer for aggregate, P (2) 72*g*.

American Metal Climax, Inc. Molybdenum powder for use in spray coating, P (2) 46*e*.

American Optical Corp. Fiber laser structures and the like, P (10) 344*j*. Fiber-optical image-conducting devices embodying varying controlled stray light absorbing means, P (7) 248*f* Fiber-optical image-enhancing devices, systems, and the like, P (9) 307*d*. Fluorescent lanthanide chelates of dibenzylamine, P (5) 183*c*. Glass laserable material, P (5) 174*h*. Laser amplifier construction, P (4) 99*j*. Laser systems and the like employing solid laser components and light-absorbing claddings, P (8) 282*a*. Materials and structures for optical Faraday rotation devices, P (5) 175*h*. Method of making laser components, P (10) 339*b*. Method of making lens molds, P (11) 371*h*. Method of making optical couplers, P (10) 339*b*. Method for treating molten glass with a laser beam, P (4) 100*b*. Plural fiber optic laser construction, P (4) 100*g*. Radiation modulator, P (4) 101*a*.

American Plate & Window Glass Distributors. Glass transporting rack, P (5) 175*a*.

American Potash & Chemical Corp. Process for preparing improved titanium dioxide pigment composition, P (9) 317*c*. Process for producing borax decahydrate crystals, P (1) 24*b*. Process for producing boric oxide, P (9) 317*d*. Process for rejuvenating spent glass polishing agents [by flocculation], P (7) 249*d*.

American Saint Gobain Corp. Glass case [sheet container], P (9) 307*f*. Glass sheet feeder for cutting and processing machines, P (1) 10*f*. Strengthening glass sheets by ion exchange, P (4) 101*b*.

American Standard, Inc. Apparatus for casting ceramic articles including separate closed loop conveyors for molds and cores, P (9) 309*j*. Automatic apparatus with continuously moving conveyors for casting ceramic articles, P (4) 109*b*. Ceramic fixture casting apparatus with molds forming separate sections of said fixture and means mating said sections, P (9) 310*a*. Method for producing an enamelware article having a patterned surface, P (10) 337*c*. Silicon coated graphite, P (6) 218*g*.

American Zinc Co. Zinc oxide, P (6) 230*e*.

Amero, J. J. Method for making impregnated sintered bauxite grains and the product thereof, P (10) 335*g*. Sintered alpha-alumina and zirconia abrasive product and process, P (10) 335*h*.

Amick, J. A. See Fisher, A. W.; Tietjen, J. J.

Amick, J. A., and Fisher, A. W. Isolation techniques for fabricating integrated circuits (I) laminate substrates, (8) 281*j*.

Amin, R. B. See Wilicox, O. B.

Amlinger, P. R. MOS field-effect transistor with a 1 μm vertical channel, P (4) 115*a*.

Ammerman, F. E., and Schindehette, D. J. Electrolytic preparation of semiconductor compounds, P (4) 112*g*.

Ammermann, D. Isostatic pressing of ceramic bodies, (11) 379*d*.

Amosov, N. L. Spontaneous cracking of hardened glass, (2) 51*g*.

AMP, Inc. Ceramic insulator in cable connections, P (7) 255*j*. Dielectric constant measurement means and method utilizing frequency sweep and fixed probe, P (1) 18*d*.

Amsterdam, M. F., Shaikh, M. S., and Tarneja, K. S. Method of making [photovoltaic] solar cell, P (7) 257*g*. Solar cell panels from nonuniform dendrites, P (4) 117*a*.

Amsterdam, M. F., and Whigham, D. M. Heterojunction solar cell with shorted substrate, P (10) 345*a*.

Anaconda Co. Ore grinding control, P (4) 125*d*. Recovery of pure crystals of $AlCl_3$-$6H_2O$ and production of aluminum oxide product therefrom, P (2) 74*f*.

Anaconda Wire & Cable Co. High-temperature magnet wire, P (8) 275*d*. High-temperature magnet wire and apparatus and enamel composition for the insulation thereof, P (8) 275*d*. Method of making high-temperature encapsulated apparatus, P (5) 172*c*.

Anandan, N. S. See Moorthy, V. K.

Ananich, N. I., Botvinkin, O. K., Bogdanova, G. S., and Orlova, E. M. Initial crystallization phases for glasses of the system SiO_2-Al_2O_3-BaO-TiO_2 by optical anisotropy, (10) 337*i*.

Ananthanarayan, A. See Bhide, G. K.

Anastasakis, E., Isasa, S., and Burstein, E. Electric-field-induced infrared absorption in diamond, (2) 76*h*.

Anayama, Takeshi. See Saito, Yukinori.

Anazawa, Shinzo. See Ikeda, Koichi; Tsuji, Shigeru; Yawata, Keisuke.

Anbar, M., and Pecht, I. Oxygen isotope effects in the oxidation of water by transition metal ions, (9) 326*a*.

Ance, C. See Nguyen Van Mau, A.

Anchor Hocking Glass Corp. Article transferring means, P (4) 98*h*. Glass container coated with a lubricating film comprising carnauba wax and polyvinyl alcohol, P (8) 277*a*. Glass furnace with two separate throat passages, P (5) 174*g*. Glassware forming apparatus with blowhead control, P (1) 10*h*. Method and means for vapor coating, P (7) 249*h*. Production of decorated polytetrafluoroethylene coated glass cooking vessel, P (8) 278*b*. Stencil screen, P (5) 176*b*.

Andersen, D. G. Apparatus for producing small holes, P (7) 248*j*.

Andersen, J. W. Glass fabric structure and method of making the same, P (8) 277*a*.

Anderson, A. R., Carlson, R. C., Jr., Higgins, C. W., and Smith, N. F. Apparatus for making slab cuts in resistor films, P (4) 112*c*.

Anderson, D. H. Nuclear magnetic resonance of ^{57}Fe in single-crystal hematite, (4) 147*a*.

Anderson, D. M. Interface between ice and silicate surfaces, (1) 31*e*.

Anderson, E. L. Zone refining, P (6) 228*a*.

Anderson, H. L. See Kessler, D.

Anderson, J. A., Feldman, A., and Williams, M. M. D. Early fading of thermoluminescence induced by radiation in lithium fluoride, (4) 132*e*.

Anderson, J. C. See Fisher, J. H.; Morley, A. R.; Poh, K. J.

Anderson, J. H., and Parks, G. A. Electrical conductivity of silica gel in the presence of adsorbed water, (10) 352*e*.

Anderson, N. G., and Stevens, R. H. Flame ionization detector, P (4) 121*g*.

Anderson, P. A. M., and Kleppa, O. J. Thermochemistry of the kyanite-sillimanite equilibrium, (7) 270*a*.

Anderson, P. J. See Brett, N. H.; Webster, R. K.

Anderson, R. M., and Demchock, L. A., Jr. Method of heat-sealing flash lamps containing combustible gas mixtures, P (2) 53*d*.

Anderson, R. V. See Economy, J.

Anderson, S. Paramagnetic resonance of iron in glass, (10) 338*f*.

Anderson, S., Tandon, D., Kohlenberger, L. B., and Blair, F. G. Strength of adhesion of dried clay slurries to window glass as a function of slurry pH, (11) 370*d*.

Anderson, S. B., and Haraldson, H. C. Cement-rock possibilities in Paleozoic rocks of eastern North Dakota, (9) 316*g*.

Anderson, W. W. See Girton, D. G.

Anderson, W. W., and Mitchell, J. T. Phosphorus-ion-implanted CdS, (4) 149*e*.

Andersson, K. O. I. Neutron detector having a radioactive vanadium emitter, P (1) 18*g*.

Andersson, L. O. Nuclear magnetic resonance measurements of distortion effects around substitutional monovalent ions in alkali halide crystals, (8) 295*g*.

Andersson, L. O., and Ödberg, L. NMR measurements of field gradients at Br nuclei surrounding a substantial Cl ion in a KBr crystal, (4) 146*f*.

Andersson, N. E. Semiconductor device comprising two parallel-connected semiconductor systems in pressure contact, P (8) 283*e*.

Andersson, S. See Jahnberg, L.

Andersson, S., and Lundstrom, T. Crystal structure of CrB_4, (10) 351*i*.

Ando, Jumpei, and Matsuno, Seiichi. $Ca_3(PO_4)_2$-$CaNaPO_4$ system, (4) 127*d*.

Ando, K. J., Kuendig, W., Constabaris, G., and Lundquist, R. H. Moessbauer studies of nickel oxide—bulk material and ultrafine particles, (10) 357*i*.

Ando, Yoshio; Fujimura, Tadato; Tanaka, Tadayoshi; and Inoue, Yoshihiko. Brazing composition for carbonaceous materials, P (7) 252*e*. Method of brazing carbonaceous materials and brazing carbonaceous materials with metal and brazing material thereof, P (7) 252*e*.

Andrae, K. H. Continuous muller, P (6) 225*a*.

Andre, E., and LeDuc, J. M. Gallium arsenide doped with chromium obtained by epitaxy in the liquid phase, (10) 354*g*.

Andre, J. See Fripiat, J. J.

Andreeva, A. B., and Keler, E. K. Reaction of oxides of lanthanum and neodymium with the oxides of elements of the second group in the periodic system, (8) 297*g*.

Andreeva, G. T., and Keler, E. K. Synthesis of $4BaO·Nb_2O_5$ in the solid phase, (10) 362*b*.

Andres, F. H., and Gentile, A. L. Potassium tantalate niobate crystal growth from a melt, P (6) 223*f*.

Andres, K. See Robin, M. B.

Andresen, A. F. Neutron diffraction investigation of $FeSe_2$, (9) 325*c*.

Andrew, B. M., and Blumenberg, K. E. Titanium pigment manufacture, P (11) 383*a*.

Andrew, K. F. See Gulbransen, E. A.

Andrews, P. B. B. Annual sales forecast, (6) 240*c*.

Andrews, R. C., and Bedford, A. H. Microscope cover glass and method, P (5) 176*a*.

Andrews, R. E. See Landes, B. D.

Andrews, R. W. J., Kenward, J. R., and Dewhurst, J. R. Control of gas flame characteristics, P (2) 72*f*.

Andrysick, C. A. Vertical index press for press forming glass articles, P (7) 249*g*.

Andryushchenko, Yu. I. See Bergman, A. G.

Angell, C. A., and Gruen, D. M. Short-range order in fused salts (I) coordination states of nickel; (II) in molten zinc chloride-potassium chloride mixtures, (4) 154*i*.

Angell, C. A., Pollard, L. J., and Strauss, W. Transport in molten salts under pressure (I) glass-forming nitrate melts, (10) 338*c*.

Angell, C. A., and Sare, E. J. Liquid-liquid immiscibility in common aqueous salt solutions at low temperatures, (10) 356*i*.

Angelova, S. M. See Samygin, V. D.

Angino, E. E. Far infrared absorption spectra of plagioclase feldspars, (9) 321*c*.

Angstadt, R. L. See Edelson, M. R.; Edwards, G. C.; Hurley, F. R.; Keenum, J. C., Jr.

Angstadt, R. L., and Hurley, F. R. Accelerator for portland cement, P (5) 170*j*.

Angstadt, R. L., Hurley, F. R., and Miller, C. F. Set retarded portland cement, P (2) 45*f*.

Ankerst, H. Multicolor enameling, (6) 207*j*.

Annunziata, C., and Lee, R. H. Method and material for hard-surfacing, P (5) 172*a*.

Ansell, G. S. See Bradt, R. C.; Natesh, R.

Antell, G. R. Light emitting junction device using silicon as a dopant, P (5) 183*h*.

Antes Componenti Elettronici S.p.A. Method of making *pn* alloy junctions, P (5) 183*g*.

Anthony, A. M. See Faucher, M.

Anthony, B. F. See Charman, W. M., Jr.

Anthony, G. H. See LaLonde, R. E.

Anthony, R. G., Stitt, D. M., and Welch, B. J. Corrosion of recrystallized alumina by some fluoride melts, (5) 176*i*.

Antill, J. E., and Warburton, J. B. Oxidation of nickel by carbon dioxide, (4) 148*g*.

Antonenko, V. M., Gogotsi, G. A., and Lankin, Yu. N. Apparatus for programed thermal stability tests of brittle materials, (2) 68*f*.

Antoniou, A. A., and Litvan, G. G. Calorimeter for simultaneous measurement of thermal properties and dimensional changes, (9) 314*j*.

Antonov, A. V. See Melamed, Sh. G.

Antonova, E. A. See Popov, N. N.

Antonova, E. A., Kuznetsova, L. A., Vsesvyatskaya, L. M., and Borovkov, G. N. Data on the resistance of cermet coatings to abrasion, B (5) 204*i*.

Antonova, N. I. See Yastrebova, L. S.

Aoki, Masaharu. See Sudo, Toshio.

Aoki, Minoru. See Futaki, Hisao.

Aoki, Toshio. See Wakatsuki, Masao.

Aoyagi, Kiyoshi; Kajiura, Masako; and Uesugi, Mitsuo. Magnetic circular dichroism in ruby, (8) 294*j*.

Aoyama, Kaneichi. Detrick construction, (5) 177*a*.

Apel, J. R., Poehler, T. O., and Westgate, C. R. Quantum effects in electron cyclotron resonance in InSb, (11) 386*j*.

Apostolov, A. See Bertaut, E. F.

Apostolov, A., and Pataud, P. Crystallographic and magnetic study of the series Mn_xFe_{1-x}-HoO_2, (10) 351*f*.

Appel, J. Superconductivity in pseudoferroelectrics, (2) 83*d*.

Appen, A. A. See Krivtsov, V. A.; Popov, N. N.

Appen, A. A., Kayalova, S. S., and Baikova, G. V. Shock-resistant cermet coatings on steel, B (5) 204*h*.

Apple, E. F. See Sarver, J. F.

Appolloni, J. See Richards, E. A.

ARA, Inc. Apparatus for and method of measuring thermal stress by nuclear resonance, P (1) 22*i*.

Arai, Yuzo; Ida, Ichiro; and Fukuda, Mitsutoshi. Dressing of a metal-bonded diamond wheel in grinding ceramics for circuit component, (4) 109*j*.

Arai, Yuzo; Ida, Ichiro; Fukuda, Mitsutoshi; and Suzuki, Makoto. Peculiarities in diamond grinding of ceramics for circuit components, (4) 110*i*.

Arai, Yuzo; Ida, Ichiro; and Furumoto, Shunichi. Production lapping of lead zirconate-titanate ceramics, (1) 17*h*.

Arakawa, E. T., and Williams, M. W. Optical properties of aluminum oxide in the vacuum ultraviolet, (9) 326*e*.

Arakawa, Masafumi. Particle size and packing property of fine powders, (4) 148*h*.

Arakelyan, O. I. See Sazhin, V. S.

Aramaki, S., and Roy, R. Single-crystal growth of VO_2 by isothermal flux-evaporation, (9) 329*f*.

Aramendia, M. M., and Armant, D. L. Method for producing titanium dioxide concentrate from massive ilmenite ores, P (10) 349*d*.

Aramyan, V. G. See Abramyan, A. V.

Arase, Masahiko. See Okamoto, Shoichi.

Arashi, Haruo. See Sakurai, Takemaro.

Aravamuthan, V., and Viswanathan, S. Ionic melts—their properties and applications, (1) 31*a*.

Arbuzov, M. P., and Khaenko, B. V. Use of X rays to study the atomic scattering factors of the components of titanium carbide and the defect concentration of its structure, (1) 40*c*. X-ray study of electron density distribution in titanium carbide, (6) 240*b*.

Archer, A. I. Photodetector, P (10) 345*e*.
Archer, R. J. See Atalla, M. M.
Ardco, Inc. Antishock control devices for electrically heated glass panels or the like, P (9) 307*j*.
Ardizzone, L. See Amato, I.
Arend, H. See Veprek, S.
Arend, H., and Kihlborg, L. Phase composition of reduced and reoxidized barium titanate, (4) 111*a*.
Arens, R. P. See Peake, J. S.
Argall, F., and Jonscher, A. K. Dielectric properties of thin films of aluminum oxide and silicon oxide, (8) 281*a*.
Argauer, R. J. Crystalline galliosilicates, P (6) 229*e*.
Argiro, T. J. Method of reducing friction on coated abrasive cloth and abrasive product, P (4) 90*a*.
Argon, A. S. Delayed elasticity in inorganic glasses, (4) 95*g*.
Argyle, L. C., and Bublitz, A. T. Automatic control means, P (2) 52*b*.
Ariga, Shozo. Results of service tests on ladle spout bricks of various types, (7) 251*c*.
Arija, S. M., Akopjan, S. C., and Wintruff, W. Paramagnetic electron spin resonance spectra of higher vanadium oxides, (6) 235*d*.
Aristov, B. G., Bosacek, V., and Kiselev, A. V. Dependence of adsorption of krypton and xenon by crystals of zeolite LiX and NaX on pressure and temperature, (4) 131*c*.
Arizumi, Tetsuya; Umeno, Masayoshi; and Horiba, Yasutaka. Effect of magnetic field on density distribution of injected plasma in semiconductor rods, (5) 180*f*.
Arjona, A. M., and Fripiat, J. J. Proton mobility in solids (II) dielectric and diffusion measurements in boehmite, (8) 296*j*.
Arkhipov, S. M. See Mikheeva, V. I.
Arlett, R. H., and Robbins, M. Pressure sintering of $CuCr_2Se_{4-x}Br_x$ spinels, (1) 17*h*.
Arlt, U. See Zagar, L.
Armant, D. L. See Aramendia, M. M.
Armington, A. F., and O'Connor, J. J. Some factors influencing the growth of crystals in gel by the complex dilution method, (9) 329*a*.
Armisi, I. See Bernardini, F.
Armour & Co. Coated abrasive products, P (1) 1*g*. Method of reducing friction on coated abrasive cloth and abrasive product, P (4) 90*a*.
Armstrong, A. M. See Chaklader, A. C. D.
Armstrong, A. T. See Maria, H. J.
Armstrong, J. A. Ultrafast optical coincidence detector which utilizes the (1, −1, 0) surface or its crystallographic equivalent in [GaAs] crystals of the 42*m* or 43*m* class for mixing two orthogonally polarized pulses, P (8) 284*c*. See Young, M. R.
Armstrong, L. D. See Kim, C.
Armstrong, W. J., Healy, A. M., and Duffy, M. C. Integrated semiconductor devices and fabrication methods therefor, P (4) 113*f*.
Armstrong Cork Co. Glass surfaces coated with decorative organic coatings, P (7) 248*i*. Glassware inspection device, P (4) 99*d*.
Arnal, T. Spectrographic analysis of impurities in $(U\text{-}Pu)O_2$, (8) 285*e*.
Arndt, H. H., and Schadel, J. Method and apparatus for thermally bonding semiconductor components to carriers, P (7) 256*j*.
Arndt, J. Effect of impurities on densification of silica glass, (7) 247*f*. See Stoeffler, D.
Arndt, J., and Stoeffler, D. Anomalous changes in some properties of silica glass densified at very high pressures, (11) 369*e*.
Arnold, A. J., McKeough, E. L., Ripple, W. M., Schoeffler, P. W., and Smith, Herbert J. Ceramic fixture casting apparatus with molds forming separate sections of said fixture and means uniting said sections, P (9) 310*a*.
Arnold, A. J., Van Dyke, B., Van Dyke, D., and Porter, D. D. Apparatus for casting ceramic articles including separate closed loop conveyors for molds and cores, P (9) 309*j*.
Arnold, D. J., and Mires, R. W. Magnetic susceptibilities of metallic V_2O_3 single crystals, (4) 143*i*.
Arnold, E. See Abowitz, G.
Arnold, G. P. See Rabideau, S. W.
Arnold, M. See Schrader, R.
Arnold, S. R., Edwards, R., and Pritchett, R. L. Low resistance contact to diffused junction germanium transistor, P (2) 65*i*.
Arntz, F., and Yacoby, Y. Electroabsorption in rutile (TiO_2), (2) 76*b*.
Aronson, S. See Auskern, A. B.
Aronson, S., and Auskern, A. B. Magnetic susceptibility of thorium carbides, nitrides, and carbonitrides, (4) 143*a*. Vapor pressure measurements on thorium nitrides, (4) 163*g*.
Aronson, S., and Ingraham, A. Characteristic temperatures and entropies of some refractory thorium compounds, (4) 128*i*.
Arrance, F. C., and Soltis, D. G. Method of making membranes, P (5) 179*b*.
Arrhenius, G. Monolithic ceramic electrical interconnecting structure, P (5) 184*j*.
Artamonov, A. Ya., and Bovkun, G. A. Materials for the protection of surfaces against abrasive wear. (1) 1*g*.
Arthur, E. P. Glass standard for fluorescence, P (4) 99*e*.
Arthur, G. See Brown, D. J.
Artman, J. O. See Sharma, K. K.
Artyukhin, P. I., Gil'bert, E. N., Pronin, V. A., and Sil'vanovich, Yu. A. Activation analysis of silicon and arsenic, (2) 68*d*.
Aryanin, B. V. See Belitskii, M. E.
Asada, Chiaki. Test results on electric furnace tapping spout constructed by ramming, (7) 251*j*.
Asada, Eiichi. See Takiguchi, Toshimichi.
Asaff, A. G. Method of sealing aluminum oxide bodies to metals, P (1) 18*e*.
Asahi Glass Co., Ltd. Apparatus for automatically cutting a glass sheet, P (7) 248*h*.
Asal, K. W. See Feder, R.
Asaki, Z. See Yamazaki, S.
Asamaki, Tatsuo. See Oda, Zenjiro.
Asamura, Hitoshi; Tanaka, Tsukasa; and Tanaka, Takeshi. High density compacting of powders by Dynapak method, (4) 119*h*.
Asano, Kiyoshi. See Kawamura, Sukizo.
Ascast Corp. Graphite continuous casting mold, P (11) 374*j*.
Ascoli, A., Barbesino, F., and Ferrario, A. First internatl. conference on material science (II) ceramic science and technology, (10) 353*d*.
A/S Dansk Lecabeton. Insulating structural sheets, P (7) 252*j*.
Asell, J. F., and Nicol, M. Raman spectrum of α-quartz at high pressures, (10) 359*g*.
Ash, F., and Aurandt, H. K. Welding flux compositions, P (2) 46*d*.
Ash, J. M. Welding flux compositions, P (2) 46*d*.
Ashbee, K. H. G. See May, C. A.
Ashburn, L. L., and Starbuck, C. L. Vapor coating employing degassing of coating metal, P (2) 67*a*.
Asher, J. W., Martin, F. W., and Tarcza, W. H. Method of enclosing an electrical device, P (2) 65*j*.
Asher, R. C., Goodman, J. F., and Gregg, S. J. Absorption of water vapor by some inorganic oxides, (1) 24*i*.
Asher, R. C., and Kirstein, T. B. A. Inhibiting effect of chlorine or carbon tetrachloride on graphite oxidation, (9) 323*b*.
Ashida, Toshio; Sawamoto, Kenichi; and Toyoda, Hiroo. Integrated ultrasonic delay line made of $BaTiO_3$ ceramics, (4) 110*a*.
Ashkin, A. See Bergman, J. G.
Ashland Oil & Refining Co. Process for preparing sand cores, P (6) 218*a*.
Ashley, E. J. See Bennett, H. E.
Ashpole, R. S., and Davidson, T. W. Glass fabric reinforced mica tape and process for production thereof, P (6) 212*c*.
Ashpole, R. S., and Wells, S. T. Method of coating metallic wire or strip with glass, P (9) 304*i*.
Ashton, R. L. Solid state drive system at Ford's float glass plant, (10) 338*h*.
Ashworth, R. H. Cost reduction through design of components using porcelain enamel on steel, (8) 274*j*.
Aslanov, S. M. See Zakharchenko, M. A.
Asmus, E., and Lunkwitz, H. D. 1,2-Dimorpholinylethane as a reagent in quantitative analysis (VII) gravimetric determination of arsenic and silicon, (4) 120*b*.
Aspinall, A., Slater, D. N., and Mayes, P. Neutron activation analysis of medieval ceramics, (4) 120*f*.
Asquiedge, M. See Guillou, M.
Asquiedge, M., Busson, N., Guillou, M., Jacquin, M., Lecante, A., Millet, J., Palous, S., and Pithon, M. Physicochemical properties of solid binary electrolytes (ZrO_2) (CeO_2), (9) 327*e*.
Assaad, F. F. See Helmy, A. K.
Assabghy, F. Y. I. See Robson, D.
A/S Skarrehage Molervaerk. Nonabsorbent hydrophobic mineral powder, P (7) 252*j*.
Associated Electrical Industries, Ltd. Refractory crucibles, P (7) 253*c*.
Astbury, N. F. Deformation and fracture, (6) 214*i*. Model for connected porosity in ceramic bodies, (2) 70*f*. Some problems of the mechanics of ceramic materials, (2) 85*c*.
Aston, J. G. See Bernard, H. W.
Astrom, A. Vapor pressure studies on the thermal decomposition of NbO_2F, (4) 163*i*.
Asumman, S. K. Method for initiating and controlling crystallization of glass, P (8) 277*i*.
Asztalos, I., and Gado, P. Grading of powder specimens in respect to dispersion and compactness by means of diffracted intensity, (9) 315*f*.
Atalla, M. M., Archer, R. J., Hall, R. D., and Engelman, R. W. H. Semiconductor bulk oscillators, P (5) 185*g*.
Ataman, G. Geochemistry of boron and gallium in clay minerals, (1) 30*h*.
Ateo Ceramics Corp. Tile setter loading device, P (4) 109*c*.
Ateliers Heuze, Malevez et Simon Reunis Societe Anonyme. Apparatus for the horizontal stacking of [glass] sheets of rigid material. P (4) 98*d*. Device for handling [glass] sheet materials, P (4) 98*b*.
Ateliers Reunis Broyeurs Forplex S. A. Dynamical selector device for crushers, P (5) 190*h*.
Athanassiadis, E. G. See Olmstead, J.
Atkeson, F. V. Method and apparatus for the manufacture of float glass on a bilevel support bath, P (11) 371*e*.
Atkins, F. B. Pyroxenes of the Bushveld intrusion, South Africa, (11) 386*j*.
Atkins, P. W. Magnetic hyperfine interactions in the electronic spectra of diatomic molecules (II) magnetic interactions in Hund's case (c) and the spectrum of BiO, (1) 32*e*.
Atkins, P. W., and Barron, L. D. Quantum field theory of optical birefringence phenomena (I) linear and nonlinear optical rotation, (1) 35*f*.
Atkinson, C. R. Techniques in modern brickmaking—quarrying and clay preparation, (10) 340*d*.
Atkinson, R. H., and Sell, H. G. Refractory-oxide incandescent lamp with preheater, P (4) 116*g*.
Atlantic Richfield Co. Metal contaminant removal from solid carbonaceous materials, P (10) 342*h*.
Atlas, J. Atomized powders in the isostatic pressing, (4) 108*c*.
Atlas, L. M. Statistical model of partially ordered defects in a hypostoichiometric metal oxide, (10) 360*f*. Statistical model of partially ordered defects in UO_{2+x}, (9) 330*f*.
Atluri, S. R., and Duffy, W. B. Digital control of dry material blending, (4) 91*g*.
Atoji, Masao. Neutron diffraction study of UC_2 at 300°−5°K, (4) 146*a*.
Atomic Energy of Canada, Ltd. Nuclear reactor fuel, P (11) 375*e*.
Atwater, H. A. See Vrabel, M. J.
Atwood, G. E., Bourne, D. J., and Lamb, F. E. Method of producing ammonium sulfate, potassium sulfate, and magnesium oxide from langbeinite, P (7) 263*b*.
Aubuchon, K. G. See Perkins, C. W.
Audesse, E. G. See Palermo, J. J.
Augustin, E. H. See Greenler, R. J.
Augustithus, A. S. Phenomenology and geochemistry of differential leaching and element agglutination processes, (1) 34*j*.
Augustus, P. D. See Fochs, P. D.
Auld, J. R. Magnesium surface for cooling TiO_2, P (8) 287*i*.
Ault, C. H., and Webb, W. M. Locations of clay and shale operations in Indiana, (4) 123*g*.
Ault, N. N., and Wheildon, W. M., Jr. Protective coated article, P (4) 94*d*.
Aumento, F. Space group of prehnite, (1) 37*h*.
Aurandt, H. K. See Ash, F.
Auskern, A. B. See Aronson, S.
Auskern, A. B., and Aronson, S. Electrical properties of thorium borides, (6) 232*b*. Electrical properties of (Th,U)C (thorium carbide-uranium carbide) solid solutions, (10) 341*e*.
Austerman, S. B. See Chikawa, Junichi.
Austerman, S. B., and Newkirk, J. B. Experimental procedures in X-ray diffraction topography, B (1) 40*h*.
Austin, G. A. See Parham, W. E.
Austin, I. G. See Smith, B. A.
Austin, L. M. Apparatus for producing glass rod and tubing, P (4) 98*f*. See Best, W. V.
Auth, D. C., Mayer, W. G., and Thaler, W. J. Detection of photon-photon scattering in KD_2PO_4, (10) 351*i*.
Authier, A. Contrast of dislocation images in X-ray transmission topography, B (1) 40*h*. See Willaime, C.
Automatic Electric Laboratories, Inc. Method and apparatus for making dimpled reed capsules, P (7) 249*b*.
Automation Industries, Inc. Material tester, P (6) 227*i*. Nondestructive tester, P (6) 228*a*.
Avarbe, R. G. See Vil'k, Yu. N.
Avco Corp. Flame spray metalizing, P (11) 379*f*. High temperature probe, P (10) 347*i*. Spray coating, P (7) 246*h*.
Avella, F. J. Cathodoluminescence of terbium activated indium orthoborate, (2) 75*b*. Orthovanadate phosphors with zircon structure, (1) 33*i*.
Avella, F. J., Sovers, O. J., and Wiggins, C. S. Rare earth cathodoluminescence in $InBO_3$ and related orthoborates, (4) 152*e*.
Aven, M., Hall, R. B., and Prener, J. S. Growth of ZnSe-ZnTe solid solutions in Te_2 atmosphere, (10) 354*d*.
Averbach, B. L. See Renninger, A.
Averbach-Pouchot, M. T., and Durif, A. Crystallographic data for two varieties of $ZnNH_4PO_4$, (2) 75*i*.
Avery, F. J. Vitrifiable photosensitive emulsion, P (2) 61*a*.
Aver'yanova, L. N. See Belyaev, I. N.
Aveston, J. Hydrolysis of sodium silicate: Ultracentrifugation in chloride solutions, (1) 30*h*.
Avgustinik, A. I. (editor). Studies of the Chemistry of Silicates and Oxides, Academy of Sciences of the USSR—Collection of Papers, B (4) 168*h*. See Vil'k, Yu. N.; Zhuravlev, G. I.
Avgustinik, A. I., Sintsova, I. T., and Milyukov, E. M. Structure and phase composition of glass-porcelain bodies, (6) 211*j*.
Avogadro, A. See Wurm, J. G.
Avram, C., Tocu, P., Grigore, N., and Ianache, P. Qualitative improvement of fluxed sinter, (10) 336*b*.
Avramov, A. See Hr, E.
Ayer, J. E., and Soppet, F. E. Vibratory compaction (III) rate of entry, (10) 346*h*.
Ayers, O. See Binkley, M. E.
Aylos, D., and Bradfield, W. S. Effects of electrostatic force, relative humidity, heating surface temperature, and size and shape on droplet evaporation rate, (6) 224*f*.
Ayyar, T. S. R. See Narain, J.
Azinger, K. H. See Heiman, F. P.
Azuma, Kiyoshi. See Kametani, Hiroshi.
Azzam, A. M. See Hassanein, M.

Baak, N. T. E. A. Glass compositions, method, and articles, P (11) 371*h*.

Baak, N. T. E. A., and Rapp, C. F. Sealed glass article of manufacture, P (4) 101*d*.
Babaeva, E. P. See Bukhalova, G. A.
Babaeva, E. P., and Bukhalova, G. A. Interaction of scandium fluoride with the fluorides of the alkali metals, (7) 267*e*. System $Li^+,Cs^+,Sc^{3+}||F^-$, (4) 159*a*.
Babayan, S. A. See Toropov, N. A.
Babb, S. E., Jr. See Rein, R. G., Jr.
Babcock, C. L. Substructure classification of silicate glasses, (6) 211*d*.
Babcock, E. W. Apparatus for producing multiple sheet glazing units, P (7) 248*j*.
Babcock, H. N. See Small, A. B.
Babcock, K. See Brixner, L. H.
Babcock & Wilcox Co. Burner throat, P (10) 342*b*. Furnace roof hangers for refractory brick, P (1) 14*b*. Hot drawing tubes, P (1) 10*i*. Method and apparatus for descaling billets, P (4) 94*c*. Two fuel burner arrangement, P (4) 123*c*.
Babel, D. Structural chemistry of octrahedral fluorocomplexes of the transition elements, B (6) 242*d*.
Babich, V. I., Pankova, N. A., and Shcherbak, B. I. Problem of boil of molten glass in tank furnaces, (1) 8*j*.
Babl, A., and Geng, H. Preparation of hexagonal boron nitride, P (4) 107*a*.
Babonas, G., Krivaite, E., Raudonis, A., and Silelka, A. Effect of high electric field on the absorption spectra of CdTe, (5) 193*h*.
Babu, V. H., and Bansigir, K. G. Dissolution kinetics at dislocation sites in sodium chloride crystals, (6) 231*h*.
Babunovic, M. See Stapf, V. M.
Backer, W. R. Higher wheel speeds "make" cylindrical abrasive machining, (11) 367*g*.
Backsen, H. See Schmidt-Holthausen, H. J.
Bacmann, J. J. Reply to comment on "Dorn method in the study of initial phase of uranium dioxide sintering," (1) 26*g*.
Bacon, F. R. Chemical durability of silicate glass (I,II), (1) 5*j*; (III), (2) 47*e*.
Bacon, F. T. Fuel cells—past, present, and future, (10) 344*d*.
Bacon, G. E. Ordered magnetic arrangements, (4) 147*e*.
Baczewski, A., and Bracco, D. J. Electroluminescent cell matrix material of improved stability, P (7) 256*f*.
Badami, D. V., Joiner, J. C., and Jones, G. A. Microstructure of high strength, high modulus carbon fibers, (4) 144*c*.
Bader, R. F. W., and Bandrauk, A. D. Molecular charged distributions and chemical binding (III) isoelectronic series N_2, CO, BF, and C_2, BeO, LiF, (8) 295*i*.
Badger, A. E. See Lehr, G. J.
Badische Anilin- & Soda-Fabrik Akt.-Ges. Continuous wet grinding of solid materials in tube mills, P (7) 259*e*.
Baer, C. E., Jr., Evans, W., and Malinowski, E. Colloidal silica compositions containing set indicator, P (7) 252*h*.
Baertsch, R. D. Cryogenic avalanche photodiode of InSb with negative resistance characteristic at potential greater than reverse breakdown, P (9) 312*e*.
Baes, C. F., Jr. See Mathews, A. L.
Bagdade, W., and Stolen, R. Far infrared absorption in fused quartz and soft glass, (9) 305*e*.
Baggaley, B. J., Malin, A. S., and McCartney, E. R. Microstructural changes during the sintering of pure alumina, (5) 177*g*.
Bagnall, K. W., Brown, D., and Easey, J. F. Neptunium(V) and (VI) oxyfluorides, (5) 197*a*.
Bagotskii, V. S. See Ezerskii, M. L.
Bagrov, A. A. Dependence of plasticity of the clay-water system on the dispersed phase concentration, (7) 253*i*.
Bahl, O. P., Evans, E. L., and Thomas, J. M. Identification and some properties of point defects and nonbasal dislocations in molybdenite surfaces, (5) 195*i*.
Bahnson Co. Apparatus and method for removing concentration of particles in liquids, P (10) 349*a*.
Baier, E., Deeg, E., and Constabel, H. G. Radiochemical studies of the adsorption or orthophosphate on two ternary borate glasses (IV), (5) 173*j*.
Baikova, G. V. See Appen, A. A.
Bailey, A. C., and Yates, B. Low temperature thermal expansion and related thermodynamic properties of alkali halides with a cesium chloride structure, (2) 79*e*.
Bailey, D. K. Stability of acmite in the presence of water, (9) 329*i*.
Bailey, F. Furnace tooling design for heavy loading, (8) 275*b*.
Bailey, J. T., and Russell, R., Jr. Sintered spinel ceramics, (1) 13*e*.
Bailey, L. G. Electrical isolation of circuit components of monolithic integrated circuits, P (2) 64*a*.
Bailly, H., Francois, B., and Meny, L. Nuclear fuel element, P (2) 59*a*.
Baily, D. F., and Norris, A. W. Isostatic pressing of clay-containing bodies, (4) 108*g*.
Bainbridge, D. W. Elastic strain measurement in the interior of crystalline materials by means of X-ray diffraction, (9) 315*e*.
Baird, D. H. See Natansohn, S.
Baird, D. H., and Natansohn, S. Cadmium-substituted ferrite materials, P (7) 255*g*.
Bakalar, D. See Navon, D. H.
Bakanin, V. V. See Mill, B. V.
Baker, A. A. Fatigue of fiber-reinforced aluminum, (1) 4*b*. See Cratchley, D.
Baker, A. G., and Dale, B. Method of producing an array of semiconductor elements, P (10) 345*j*. Method of producing semiconductor devices, P (5) 184*d*.
Baker, A. G., and Ingraham, R. C. Method [etching] of forming leads on semiconductor devices, P (5) 183*c*. Method of producing semiconductor devices having connecting leads attached thereto, P (5) 184*e*.
Baker, C. G. J., and Buckle, E. R. Double layer relaxation in liquid electrolytes (I) theory of the space charge polarization, (9) 320*g*.
Baker, E. M. See Mellen, E. J., Jr.
Baker, H. W. Method and apparatus for toughening sheets of glass, P (6) 213*a*.
Baker, L. R., Bertoya, H. C. M., Mann, J. R., and Whyte, J. N. Apparatus for and methods of testing lenses, P (7) 248*i*.
Baker, M. A., and Laurenson, L. Quartz crystal microbalance holder for low temperature use in vacuum, (1) 21*h*
Baker, P. E. Petrology of Mt. Misery Volcano, St. Kitts, West Indies, (8) 296*d*.
Baker, P. M., and Farrant, B. R. Determination of the total silicon content of water, (6) 225*j*.
Bakker, W. T. General Refractories research project reveals high grade domestic bauxite, (6) 215*b*.
Bakos, J. See Balint, P.
Bakunov, V. S., Lukin, E. S., and Poluboyarinov, D. N. Vaporization and creep of sintered oxide ceramics, (4) 163*i*.
Balakir, E. A., Krylov, Yu. I., Kuz'minskaya, L. N., and Moiseitseva, Z. K. Compatibility of magnesium oxide with titanium monoxide, (8) 289*a*.
Balakrishna, S. Experimental study of fracture mechanism in sandstones, B (6) 241*d*.
Balasubramanian, T. M. See Rangaswamy, N. S.
Balberg, I., and Many, A. Frequency shifts during growth of amplified acoustic flux in CdS, (8) 292*c*.
Balcar, O. Forming ceramic bodies with a pressure shock wave, (5) 186*b*.
Balcar, O., Kralove, H., and Vavrina, K. Method and arrangement for shaping objects from ceramic raw material, P (10) 346*j*.
Balcar, O., and Schwarzbach, J. Effect of high forming pressures on the properties of ceramics with high permittivity, (7) 254*j*.
Balcar, O., and Vavrina, K. Forming ceramics by pressure shock-wave caused by electric discharge, (2) 67*f*.
Balch, C. W. Creative process, (1) 40*g*.
Balde, J. W. Integrated circuit containing multilayer tantalum compounds, P (2) 65*e*.
Baldrian, J. See Satava, V.
Balducci, G. See De Maria, G.
Balducci, G., Capalbi, A., De Maria, G., and Guido, M. Thermodynamics of rare-earth–carbon systems (I) cerium-carbon system, (11) 388*d*.
Baldwin, H. Indication of particle shape by measuring the capillary rise, (6) 226*a*.
Balentine, J. W. See Iannicelli, J.
Balentine, J. W., Iannicelli, J., and Whitley, J. B. Chemically treated clays, P (8) 287*f*.
Baleshta, T. M. See Keys, J. D.
Balian, K. S., and Shekhawat, V. S. Selective masking for metal contacts on silicon planar devices, (4) 111*h*.
Balian, K. S., Singh, A., and Saha, R. Experimental *n-p-n* planar silicon power transistor, (4) 110*g*.
Balint, P. Drying of hollow ceramic building units, (2) 54*i*.
Balint, P., and Bakos, J. Thermal conductivity of hollow bricks determined by electrical modeling, (2) 71*c*.
Balk, A. C. Method of making laminated glass products, P (9) 308*b*.
Balkanski, M., Petroff, Y., and Trivich, D. Optical properties of cuprous oxide in the ultraviolet, (4) 147*a*.
Balkevich, V. L. Oxide refractories in industry, (2) 56*f*.
Balkwill, J. T. See Sowers, H. L.
Ball, F. C. Making off-center shapes on the potter's wheel, (6) 206*f*. Throwing a square vase, (7) 244*e*.
Ball, M. C. Phase-equilibrium relationships in the systems CuO-P_2O_5 and Cu_3O-P_2O_5, (5) (5) 198*i*.
Ball Brothers Co., Inc. Glass having dual protective coatings thereon and a method for forming such coatings, P (5) 174*g*. Method for manufacturing hollow plastic articles, P (2) 53*g*. Sectional mold mounts, P (1) 11*d*.
Ball Brothers Research Corp. Apparatus for determining wall thickness utilizing radiation absorption, P (5) 174*g*.
Ballard, D. B. See Gugeler, A. L.
Ballard, H. D., Jr., Mool, J., and Rogers, E. S. Method of crystallizing aluminosilicates, P (5) 191*a*.
Ballard, K. H., and Hoffman, L. C. Noble metal metalizing compositions, P (9) 313*j*.
Ballard, L. H., and Satterley, B. L. Gauze catalyst support, P (5) 178*g*.
Ballard, S. S., and Browder, J. S. Thermal expansion and other physical properties of the newer infrared-transmitting materials, (1) 39*c*.
Ballentyne, D. W. G. See Lou, F. H.
Ballman, A. A. See Bergman, J. G.; Lenzo, P. V.
Ballman, A. A., and Brown, H. Growth and properties of strontium barium metaniobate, $Sr_{1-x}Ba_xNb_2O_6$, a tungsten bronze ferroelectric, (6) 233*c*.
Ballman, A. A., and Van Uitert, L. G. Optical devices utilizing substantially tetragonal ferroelectric tungsten-bronzes, P (5) 184*d*.
Balloomal, L. S. See Wadia, W.
Bally, A. O. Filter and method and apparatus for its production, P (5) 174*d*.
Balthis, J. H., Jr. Preparation of ferromagnetic chromium dioxide, P (5) 184*i*. Preparation of MCr_2O_5, where M is an alkali metal, from CrO_3, Cr_2O_3, and MCr_2O_7, P (9) 317*c*. Process for preparing chromium dioxide and product thereof, P (9) 317*c*.
Balzers Patent-und Lizenz-Anstalt. Electrically conductive solderable metallic coatings on nonmetallic bases, P (5) 182*h*.
Balzhiser, R. E. See Craig, J. A.
Bambauer, H. U., Brunner, G. O., and Laves, F. Light scattering of heat-treated quartz in relation to hydrogen-containing defects, (11) 385*c*.
Ban, V. S. See Knox, B. E.
Ban, Z., and Sikirica, M. Uranium-transition metal silicides of the UM_2Si_3 composition, (5) 202*e*.
Bancroft, G. M., Burns, R. G., and Howie, R. A. Determination of cation distribution in the orthopyroxene series by the Moessbauer effect, (4) 119*a*.
Bancroft, G. M., Burns, R. G., and Maddock, A. G. Determination of cation distribution in the cummingtonite-grunerite series by Moessbauer spectra, (4) 131*e*.
Bandemer, M. K. See Jaselskis, B.
Bando, Yoshichika. Effect of impurities on the densification of oxides, (4) 132*i*. See Yasuoka, Hiroshi.
Bandrauk, A. D. See Bader, R. F. W.
Bandyopadhyay, T., and Saha, P. Growth of alumina crystal by flux-fusion method, (10) 346*f*. Hydrothermal growth of quartz (III) effects of constraints, (4) 139*g*.
Banerjee, A. K., and Thakur, R. L. Barium titanate from glasses, (5) 172*f*.
Banerjee, J. C., Banerjee, S. P., and Sircar, N. R. High-temperature thermal expansion of magnesite and chrome-magnesite bricks, (1) 12*e*. Preparation and properties of magnesite and chrome-magnesite bricks from Indian magnesites, (5) 190*g*.
Banerjee, J. C., and Sircar, N. R. Distribution and characteristics of Indian magnesites, (2) 55*b*. Petrography and microstructure of Indian magnesites calcined up to 2000°, (2) 73*h*. Petrography and X-ray analysis of Indian magnesites, (2) 73*j*. X-ray analysis of Indian magnesites on sintering, (2) 73*i*.
Banerjee, S. C., and Chakravorty, R. N. Use of DTA in the spontaneous combustion of coal, (4) 122*f*.
Banerjee, S. P. See Banerjee, J. C.
Bang, C. A. M. Developing and application methods of ceramic coating, P (1) 5*e*.
Bangasser, R. L. See Hyzer, W. G.
Banin, A. See Lahav, N.
Banin, A., and Lahav, N. Optical study of particle size of montmorillonite with various adsorbed cations, (9) 326*f*.
Banks, E. See Gasnurov, G.
Banks, E., and Goldstein, A. Solution of lithium in hexagonal potassium tungsten bronze, (11) 387*e*.
Banks, E., Greenblatt, M., and Holt, S. 80°K crystal spectrum of $Ca_2(CrO_4,PO_4)Cl$, (8) 290*b*.
Banks, E., Greenblatt, M., and McGarvey, B. R. ESR and optical spectrography of CrO_4^{3-} in chlorospodiosite, Ca_2PO_4Cl, (4) 135*j*.
Banks, E., Greenblatt, M., and Schwartz, R. W. New analogs of spodiosite, Ca_2VO_4Cl and Ca_2AsO_4Cl, (11) 386*i*.
Banky, J. Problems in standardization of refractories, (1) 12*i*.
Banner, J. G., and Murphy, N. A. Method of and apparatus for the manufacture of flat glass on a molten metal bath, P (2) 53*i*.
Bannister, G. H. See Cornell, R. M.
Bannister, M. J. Storage behavior of uranium dioxide powders, (8) 298*i*.
Bansagi, T. See Solymosi, F.
Bansigir, K. G. Strain polarizability constant—a measure of ion overlap in crystals of the sodium chloride structure, (6) 237*j*. See Babu, V. H.
Banus, M. D. Quenchable effects of high pressures and temperatures on the cubic monoxide of titanium, (2) 82*h*.
Banus, M. S. See Strauss, A. J.
Ban-Ya, Shiro. See Iguchi, Yasutaka.
Baptista, J. L., Newton, G. W. A., and Robinson, V. J. Valence distribution of radiophosphorus in potassium chloride single crystals (I) initial distribution; (II) effect of thermal annealing, (9) 332*g*.
Barag, D. Unpublished Achemenid cut glass bowl from Nippur, (4) 91*a*.
Baran, R. J. See Morris, W. C.
Barbaras, G. D. Isostatic hot-pressing of refractory bodies, P (10) 342*f*.
Barber, D. J., and Tighe, N. J. Neutron damage in single crystal aluminum oxide, (1) 33*a*.

Barber-Greene Co. Clamping and release means for [gyratory] crusher bowls, P (11) 382*i*.
Barbesino, F. See Ascoli, A.
Barbier, J. C. See Plumat, E.
Barbulescu, E. See Szabo, A.
Barbulescu, E., Szabo, A., and Mogosanu, E. Improving the quality of metallurgical dolomite by sintering with mill scale, (1) 12*h*.
Barclay, L. M., and Thompson, D. W. Electron microscopy of sodium montmorillonite, (10) 352*j*.
Barcus, S. W., Jr. See Cornelison, B.
Bardi, G. See Piacente, U.
Barditch, I. F. See Gallagher, R. C.
Bardonnet, P. See Levillain, J.
Bardsley, W., and Jones, O. Crystal growth of optical quality proustite and pyrargyrite, (9) 319*c*. Synthesis of optical quality proustite and pyrargyrite, (8) 299*g*.
Bareau, J. See Carteret, Y.
Barfield, J. R. See Gazza, G. E.
Barford, J. See Day, R. V.
Barger, C. H. See Crouch, R. T.
Bargero, C. Cylindrical mill for grinding cement, P (7) 245*d*.
Barinov, Yu. D. See Savin, L. S.
Barkauskas, V. I. See Meshkauskas, Yu. I.
Barker, A. Fast nuclear reactor cooled by supercritical steam, P (2) 58*e*.
Barker, A. S., Jr., Verleur, H. W., and Guggenheim, H. J. Infrared optical properties of vanadium dioxide above and below the transition temperature, (2) 79*b*.
Barker, D. B. See Sickafus, E. N.
Barker, J. E. Waste pickle liquor (what to do?), (8) 275*g*.
Barker, J. E., and Robinson, J. H. Process for producing fluosilicates, P (11) 382*i*.
Barker, J. S. Protecting and insulating covering for furnace support members, P (9) 309*d*.
Barker, M. G. See Addison, C. C.
Barker, P. D., and Torok, E. J. Sharp thin ferromagnetic film, P (6) 223*j*.
Barkowitz-Mattuck, J. Influence of stress on the disintegration of molybdenum disilicide by oxidation at intermediate temperatures, (1) 31*b*.
Barlow, I. C. See Oron, M.
Barlow, R. See Oron, M.
Barlow, T. E. Method of improving the operation of a cupola, P (4) 106*i*.
Barnard, J. K. See Pisano, A. M.
Barnes, R. G. See Uhrich, D. L.; Will, J. D.
Barnes Engineering Co. Method of producing immersed bolometers, P (5) 175*f*. Pyroelectric radiation detector providing compensation for environmental temperature changes, P (10) 345*h*. Scanning densitometer for thermal profile analysis, P (2) 72*a*. 72*a*.
Barnett, A. M., and Jensen, H. A. Observation of current filaments in semi-insulating GaAs, (4) 147*e*.
Barnett, C. W. H. Ceramic [piezoelectric] memory device, P (9) 312*c*.
Barnett, H. J. Apparatus for grinding multifocal lens, P (5) 174*h*.
Barns, R. L. Crystallographic data and thermal expansion coefficients of $Ba_{4+x}Na_{2-2x}Nb_{10}O_{30}$, (11) 383*c*.
Baro, G. See Gleiter, H.
Barr, H. N. See Frank, L.
Barr, L. W. See Dawson, D. K.
Barr, L. W., and Dawson, D. K. Exchange reactions between potassium bromide and bromine vapor, (1) 29*c*.
Barrer, R. M. Surface flow of adsorbed gases and vapors, (1) 38*i*.
Barrer, R. M., Cole, J. F., and Sticher, H. Chemistry of soil minerals (V) low temperature hydrothermal transformations of kaolinite, (8) 289*i*.
Barrer, R. M., and Dicks, L. W. R. Chemistry of soil minerals (III) synthetic micas with substitutions of NH_4 for K, Ga for Al, and Ge for Si, (1) 26*a*; (IV) synthetic alkylammonium montmorillonites and hectorites, (4) 128*e*.
Barrer, R. M., and Marshall, D. J. Chemistry of soil minerals (I) hydrothermal crystallization of some alkaline Al_2O_3-SiO_2-P_2O_5 compositions; (II) reactions of phosphates with kaolin and faujasite, (1) 26*a*.
Barrer, R. M., and Millington, A. D. Sorption and intracrystalline porosity in organo-clays, (1) 37*f*.
Barrer, R. M., and Vaughan, D. E. W. Solution and diffusion of helium and neon in tridymite and cristobalite, (5) 200*a*.
Barrett, D. I. Evaluation of trace impurities in the preparation of high-purity silicon carbide, (2) 77*a*.
Barrett, L. R. See Lee, H. M.
Barron, L. D. See Atkins, P. W.
Barron, S. Thermocouple cements for nuclear rocket engine nozzles, (10) 342*a*.
Barron, S., and Rautio, W. S. Thermistor theory and special applications (I), (2) 63*i*.
Barrow, R. F. See Cheetham, C. J.
Barrow, R. F., Gissane, W. J. M., and Richards, D. Magnetic hyperfine interactions in the electronic spectra of diatomic molecules (I) rotational structure of absorption bands of gaseous BiO, (1) 32*e*.
Barry, R. J. Semiconductor device employing punchthrough, P (11) 378*c*.
Barry, T. I., Bayliss, R. K., and Lay, L. A. Mixed oxides prepared with an induction plasma torch (I) chromia/alumina; (II) chromia-titania, (9) 325*d*.
Barry, T. I., and Lay, L. A. Selective exchange of cation sites in zeolites observed by electron spin resonance of manganese(II) ions (II) Linde Y, (9) 329*d*.
Barry, T. L. Equilibria and Eu^{2+} luminescence of subsolidus phases bounded by $Ba_2MgSi_2O_7$, $Sr_2MgSi_2O_7$, and $Ca_2MgSi_2O_7$, (10) 353*g*. Fluorescence of Eu^{2+}-activated phases in binary alkaline earth orthosilicate systems, (10) 353*f*.
Barry-Wehmiller Co. Light transparent container inspecting apparatus, P (10) 339*h*.
Barsegov, D. G. See Il'yasov, I. I.
Barsell, A. W. Thermal diffusion flux equation for zirconium hydride at high hydrogen contents, (2) 84*g*.
Barshad, I. See Kishk, F. M.
Barshad, I., and Kishk, F. M. Oxidation of ferrous iron in vermiculite and biotite alters fixation and replaceability of potassium, (5) 198*c*.
Barshchevskaya, S. V. See Kruglitskii, N. N.
Barsis, E., Lilley, E., and Taylor, A. Ionic conductivity of MgF_2-doped LiF crystals, (8) 293*j*.
Barsis, E., and Taylor, A. F^- vacancy conductivity in BaF_2 crystals, (5) 194*a*. Interstitial conduction in BaF_2 crystals, (5) 195*g*.
Barsky, L. A. See Samygin, V. D.
Barsom, J. M. See Curtze, E. W.
Barson, F., and Lehman, H. S. Semiconductor devices with cup-shaped regions, P (11) 378*d*.
Barson, F., and Sturm, J. Method and apparatus for reverse sputtering selected electrically exposed areas of a cathodically biased workpiece, P (4) 114*g*.
Barta, S. See Marino, D.
Bartenev, G. M., and Sidorov, A. B. Statistical theory of the strength of glass fibers, (4) 97*g*.
Bartenev, G. M., and Voskoboinikov, G. I. Strength of enameled glass, (1) 9*e*.
Bartholomew, R. F., and Holland, H. J. Vitreous nature of some new inorganic glasses as shown by X-ray diffraction, (9) 307*i*.
Bartlett, A. F. See Eyre, B. L.
Bartlett, E. S. See Bradley, E. F.
Bartlett, H. E., and Johnson, K. E. Cathode processes in molten nitrates and nitrites, (4) 127*g*. Electrochemical studies in molten Li_2CO_3-Na_2CO_3, (4) 134*g*.
Bartlett, N., and Jha, N. K. Preparation and some physical properties of osmium oxide pentafluoride, $OsOF_5$, (5) 198*j*.
Bartlett, N., and Trotter, J. Structure of the orthorhombic phase of osmium oxide pentafluoride, $OsOF_5$, (5) 200*j*.
Bartlett, P. G. Ceramic ferroelectric memory device, P (11) 376*i*.
Bartlett, P. G., and Meschi, J. E. Ceramic memory having a piezoelectric drive member, P (1) 18*a*.
Bartlett, R. W. Platinum oxidation kinetics with convective diffusion and surface reaction, (4) 150*a*.
Barlett, R. W., Nelson, W. E., and Halden, F. A. Influence of carbon transport kinetics on solution growth of β-silicon carbide crystals, (4) 139*g*
Bartnitskaya, T. S. See Lyutaya, M. D.
Barto, J., Durham, J. L., Baston, V. F., and Wade, W. H. Gas phase autophobicity of alcohols adsorbed on alumina, (1) 30*f*.
Barton, A. F. M., Cleaver, B., and Hills, G. J. High-pressure studies on fused salt systems—activation volumes for electrical conductance of fused alkali-metal nitrates, (8) 293*b*.
Barton, F. L., Jr., and Kaiser, L. F. Method and apparatus for bedding glass plates for grinding and polishing, P (4) 99*c*.
Barton, G. W., Jr. See Newbury, R. S.
Barton, J. L. Thermodynamic aspects of ion exchange between glass and molten salt, (5) 173*i*.
Barton, R. D. See Kessler, D.
Bartram, R. H. See Fournier, J. T.
Bartram, S. F. See Turner, P. P.
Bartrug, N. G. See Kolek, R. L.
Bartuska, M. Problems of stabilizing and sintering zirconia (I), (4) 105*f*.
Barzac, G., and Fuseau, M. Comparison of spraying dried bodies of vitrified ceramic tiles, (6) 219*c*.
Basavanna, B. M. See Reddy, A. S.
Basch, C. See Pearce, M. L.
Basch, H., and Gray, H. B. Molecular orbital method for inorganic molecules—application to transition metal oxides, (4) 145*i*.
Bascom, W. D., and Romans, J. B. Microvoids in glass-resin composites, (1) 7*j*.
Bascomb, C. L. New apparatus for recording particle size distribution, (1) 21*e*.
Bash, S. M., Tumanov, A. D., and Rakhimbaev, Sh. M. Plugging cement from phosphorus slag, (1) 3*h*.
Bashirov, I. G. See Tobolov, P. N.
Basic, Inc. Electric resistance heater and method of making, P (2) 58*b*. Process for recovery of magnesium compounds from magnesium carbonate and calcium carbonate bearing materials, P (1) 24*c*. Selective flotation of dolomite away from magnesite, P (4) 125*j*.
Basit, M. A. See Chalmers, R. A.
Baskin, Y. Preparation and properties of ThP and ThP-UP solid solutions, (4) 150*h*. Solid-solubility relationships and atomic size in NaCl-type uranium compounds, (1) 37*f*.
Baskin, Y., and Shalek, P. D. Melting point studies of the system UP-US, (8) 295*b*.
Bass, M., and Woodward, D. Observation of picosecond pulses from an Nd:YAG laser, (4) 147*d*.
Bass, S. J., and Oliver, P. E. Pulling of gallium phosphide crystals by liquid encapsulation, (7) 255*a*.
Bass, S. J., Oliver, P. E., and Birbeck, F. E. Pulled crystals of gallium phosphide by the liquid encapsulation method, (5) 187*i*.
Bassa, G., and Remenyi, K. Furnace slag crust heat conductivity measurements, (5) 189*a*.
Basset, J. Apparatus for producing very high pressures, P (11) 379*e*.
Basset, M. J. Equipment for isostatic pressing and its use, (4) 108*f*.
Bassett, D. R., Boucher, E. A., and Zettlemoyer, A. C. Adsorption studies on hydrated and dehydrated silicas, (5) 191*j*.
Bastiaanssen, J. W. See van Langen, J. O. M.
Baston, V. F. See Barto, J.
Batchelor, C. S., and Jensen, W. R. Flame spray metalizing, P (11) 379*f*.
Batchelor, E. A. Sanitary ware for Europe? (4) 108*j*.
Batchelor, R. W. Firing earthenware bodies, (7) 253*h*.
Bate, G., Judge, J. S., Morrison, J. R., and Speliotis, D. E. Wear resistant magnetic recording member, P (11) 379*b*.
Bates, H. E. See Weinstein, M.
Bates, H. E., Wald, F., and Weinstein, M. Controlled solidification of metal matrix composites utilizing monovariant eutectic reactions, (7) 250*i*.
Bates, H. E., and Weinstein, M. Solidification of Bi_2Te_3 and its solid solutions with Bi_2Se_3 and Sb_2Te_3 under the influence of ultrasonic agitation, (4) 155*e*.
Bates, R. G. See Staples, B. R.
Bates, T. R. See Waterfield, C. G.
Bathellier, L. R. M. Operational safety mold cam bypass, P (4) 100*f*.
Bathelt, R. R., and Panis, C. J. W. Color television display tube with ferromagnetic screening member, P (5) 182*a*.
Batt, J. A., Douglas, F. C., and Galasso, F. S. Optical properties of unidirectionally solidified NaF-NaCl eutectic, (8) 276*f*.
Battelle Development Corp. High pressure furnace, P (5) 189*d*.
Battista, O. A. Modified colloidal chrysotile and method of preparing same, P (11) 382*f*. Opening up asbestos with dimethylsulfoxide, P (4) 118*g*.
Battista, O. A., and Karasinski, F. J. Low melting metallic articles reinforced with modified chrysotile, P (6) 217*c*.
Battista, O. A., and Robertson, J. A. Method of preparing carbonized shaped cellulose crystallite aggregates, P (1) 14*i*.
Battle, J. H. See Shanefield, D. J.
Battles, J. E., Gundersen, G. E., and Edwards, R. K. Mass spectrometric study of the rhenium-oxygen system, (10) 356*j*.
Batyrev, V. A., and Shatunova, A. V. Effect of chemical bonds on the fine structure of X-ray emission spectra in microvolumes of a material, (4) 132*i*.
Bauer, D. J. See Levy, R. M.
Bauer, D. J., and Lindstrom, R. E. Process for fractionating lanthanide mixtures containing cerium, P (5) 191*f*.
Bauer, G. Conversion to liquid-gas firing, (6) 228*d*.
Bauer, H., and Ploetscher, G. Lead diborate, PbO-B_2O_3, (6) 234*b*.
Bauer, R. W. Providing low viscosities for aged siliceous slurries, P (1) 24*e*.
Bauer, W. See Schier, K. H.; Sosin, A.
Bauerle, J. E. See Ruka, R. J.
Bauerlein, R., and Raithel, K. Method of making a *pnpn* thyristor [indiffusing], P (8) 283*b*.
Baughan, E. C. Ionization potentials, electron affinities, and screening constants (VII) comparison with Hartree-Fock calculations, (9) 323*g*.
Baugher, J. F., and Bray, P. J. Magnetic resonance studies of thallium borate glasses, (11) 370*i*.
Baughman, R. J., and Corill, J. A. Apparatus for vapor phase preparation of mixed compounds, (1) 20*j*.
Baughman, R. J., and Lefever, R. A. Czochralski growth of lithium metagallate, (6) 231*b*.
Bauhaus, R. H., Harrington, H. W., and Poulter, H. C. Method for spectroscopically analyzing a sample by detecting radiation field change as a function of the radiation power density in the sample, P (7) 261*b*.
Baukal, W. Fuel battery with stabilized zirconium oxide electrolyte, P (6) 217*j*.
Baukal, W., and Scheidegger, R. Lattice constants of the cubic solid solutions ZrO_2-CaO and ZrO_2-Y_2O_3, (6) 234*f*.
Baukus, J. See Blumenthal, R. N.
Bauleke, M. P. See Hardy, R. G.; Hladik, W. B.; Huh, J. M.
Bauleke, M. P., and Edmonds, C. S. Thermal expansion of siliceous Kansas clays (Dakota formation) (4) 160*f*.
Bauleke, M. P., and Hornbaker, A. L. Attrition scrubbing and flotation beneficiation of Cheyenne sandstone (Lower Cretaceous—Kansas), (9) 316*e*.

Bauleke, M. P., and Huh, J. M. Absorbent clay granules from Kansas under clays, (9) 316*e*. Thermal expansion of Kansas volcanic ash, (9) 317*b*.
Baum, G. A., Beno, R. L., and Van Vorous, T. Apparatus for vacuum deposition on a negatively biased substrate, P (6) 220*h*.
Baum, R. L. See Fordyce, J. S.
Baun, W. L. See Fischer, D. W.
Baun, W. L., and White, E. W. Clinochlore—versatile new analyzing crystal for the X-ray region 5–27 Å, (8) 284*j*.
Baurmann, K. W. See Schulten, R.
Bausch & Lomb, Inc. Lens surfacing machine for forming both surfaces of a lens simultaneously, P (8) 277*e*. Method for forming ceramic metallic bonds, P (6) 208*d*. Method for forming strong metallic bonds to lead-containing glass, P (5) 175*d*. Method of making infrared transmitting element, P (6) 213*c*. Optical fiber bundle coupling system, P (10) 339*g*.
Bavrilov, V. A., and Majumdar, N. S. Refractory lining for blast furnaces, (1) 17*b*.
Bawa, M. S., Connally, L. O., and Truitt, J. K. Cermet material and method of making same, P (5) 178*d*.
Baxter, J. C. See Ullman, W. L.
Baxter, R. D. See Reid, F. J.
Bayer, G. Process for preparing indium and scandium antimonates, P (9) 317*d*.
Bayer, P. D., and Cooper, R. E. Tensile strength of sapphire whiskers at elevated temperatures, (10) 362*g*.
Bayer, R. O. Inorganic fibers containing positively charged silica and fibrous potassium titanate, (11) 375*a*.
Bayliss, R. K. See Barry, T. I.
Bazhenova, L. N., Ivanko, A. A., Samsonov, G. V., and Slyshankova, V. A. Microhardness of oxides of certain elements, (7) 267*c*.
Bazin, J., and Accary, A. Contribution to the study of the U-C-O system, (5) 193*d*. Equilibrium pressure of CO above uranium oxycarbides in the presence of UO_2, (1) 29*h*.
Bazinet, W. P., Jr. Method of making laser components, P (10) 339*b*. See Snitzer, E.
Beagley, B., Cruickshank, D. W. J., Hewitt, T. G., and Haaland, A. Molecular structures of P_4O_{10} and P_4O_6, (4) 145*a*.
Beale, J. R. A., and Beer, A. F. IGFET with interdigital source and drain and gate with limited overlap, P (9) 312*b*.
Beale, J. R. A., Beer, A. F., and Newman, P. C. Opto-*pn* junction semiconductor having greater recombination in *p*-type region, P (4) 115*d*.
Beall, G. H. See MacDowell, J. F.
Beals, R. J. See White, D. E.
Beals, R. J., and Kern, R. S. Irradiation testing (pulse conditions) of the ternary fuel system for the power burst facility, (9) 308*i*.
Beals, R. S. See Reardon, D. E.
Bean, C. M., and Oliver, R. H. Methods and apparatus for differential thermal analysis, P (4) 122*b*.
Bean, K. E., and Gleim, P. S. Some properties of vapor deposited SiC, (4) 155*a*. Structure and method for preventing spurious growths during epitaxial deposition of semiconductor material, P (5) 185*c*.
Bean, K. E., Gleim, P. S., and Yeakley, R. L. Some properties of vapor deposited silicon nitride films using the SiH_4-NH_3-H_2 system, (4) 155*b*.
Bearce, W. E. Dryer, P (1) 20*d*.
Beard, D. W., and Proctor, E. M. Method of liquid analyses providing increased sensitivity for light elements, B (1) 41*a*.
Beard, R., Dinnie, A., and Richards, R. Movement of brickwork, (10) 340*d*.
Beasley, A. E., Jr. See Cowan, J. C.
Beasley, W. C. Shredded carbonaceous fiber compactions and method of making the same, P (2) 59*f*.
Beattie, W. R. See Charman, W. M., Jr.
Beaumont, D. H., and Friedman, A. I. Lamp phosphor adherence, P (5) 183*g*.
Beaver, E. R., Jr. Incased graphite segmented thermoelement, P (6) 221*g*.
Becherescu, D., and Cipau, R. Reaction between ZrO_2 and Cr_2O_3 in argon plasma, (6) 237*e*.
Becherescu, D., and Winter, F. Interaction between zirconium oxide and iron oxide at high temperatures, (9) 323*c*.
Beck, F. H. See Herrnstein, W. H., III.
Beck, J. H. Conditioned atmosphere furnace muffle, P (4) 122*j*.
Beck, K. See Hou, S. L.
Becker, D. L. See Doyle, C. F.
Becker, H. Effect of flow on the homogenization of glass in flat glass tanks—a contribution to the problem of layering using a sheet glass tank as an example, (6) 209*a*.
Becker, J. H. See Keezer, R. C.
Beckett, R. S. See Galwey, A. K.
Beckman, L., and Jansson, R. Measurements on insulator-surface breakdown in vacuum under dc voltage, (2) 63*f*.
Beckman, P. Thermal probe, P (6) 228*a*.
Beckman Instruments, Inc. Cermet resistors, their composition and method of manufacture, P (4) 112*h*. Glass electrodes and method for producing the same, P (4) 99*a*. Glass standard for fluorescence, P (4) 99*c*. Sample transport system, P (4) 122*a*. Wavelength programed monochromator device with adjustable entrance and exit cam operated slit means for providing a variable proportionality factor between their widths, P (11) 381*e*.
Becton Dickinson & Co. Packaging method [laboratory tubes], P (10) 339*i*.
Bedford, A. H. See Andrews, R. C.
Bednyakov, F. I. See Kichkina, E. S.
Beebe, R. A., and Frankel, S. A. Surface hydroxyl population in bone mineral, (4) 158*b*.
Beech, D. G. See West, H. W. H.
Beegle, L. C. See Haacke, G.
Beekenkamp, P., and Stevels, J. M. Color centers in borate glasses, (6) 208*h*.
Beeman, D. E., Fink, H. J., and Shaltiel, D. Magnetostatic modes in the canted antiferromagnetic $MnCO_3$, (1) 32*f*.
Beeman, G. E. Programing switch and kiln unloader control, P (7) 261*g*.
Beer, A. F. Insulated-gate field-effect transistor with plural overlapped gates, P (7) 256*e*. See Beale, J. R. A.
Beer, L. N. See Hoganson, D. K.
Beer, S. Z. Synthesis and solution growth of aluminum phosphide (I), (2) 83*e*.
Beerntsen, D. J. See Revolinsky, E.
Beese, N. C. High-pressure electric discharge lamp having magnetically actuable arc ignition means, and apparatus for starting such a lamp, P (9) 312*b*.
Beevers, C. J. See Edmonds, D. V.; Stapley, A. J.
Beggs, D. Furnace hearth, P (10) 342*d*.
Behmenburg, H. Pore size distribution in earthenware bodies, (1) 15*b*.
Behrends, K., and Kiel, G. Pentafluosilicic acid, (6) 235*f*.
Behrens, M. D. See Leak, R. J.
Behrens, R. Calcium family glazes for cone 10, (6) 205*i*. Changing the fusion level of glazes (I), (7) 244*d*. Glazes for cone 6, (7) 244*b*. Glazes of the Ming dynasty, (10) 335*i*. Majolica ware at low temperatures, (6) 206*e*. Stoneware-type bodies and glazes at the cone 04–4 range, (6) 206*d*.
Behruzi, M., and Hahn, Th. Crystallization and polymorphism of high-form eucryptite ($LiAlSiO_4$), (6) 231*j*.
Beketov, Yu. E. See Abukov, A. A.
Belen'kaya, I. M., Dubinin, M. M., and Krishtofori, I. I. Formation and properties of hydrogen form mordenite (I) preparation of synthetic hydrogen form mordenite, dealuminizing process, and ion-exchange properties of zeolite, (7) 266*a*.
Belentepe, Y. C., and Carmi, A. Cooling arrangement for glass forming equipment, P (2) 52*e*.
Beley, M. Percusaion drill bit for shattering hard formations, P (2) 74*a*.
Belfield, R. E. See Pall, D. B.
Belfield, R. E., and Vogel, A. C. Equipment for use in laying down glass fiber blanket, P (8) 277*i*.
Belik, F. A. See Ovcharenko, F. D.
Belinskaya, G. V. See Krotikov, V. A.
Belitskaya, A. A. See Sorokin, I. P.
Belitskii, M. E., Ivanov, B. G., and Aryanin, B. V. Stand tests of cermet packing material UMB-4S, (6) 216*i*.
Bell, P. M. See Richardson, S. W.
Bell, P. M., and Davis, B. T. C. Melting relations in the system jadeite-diopside at 30 and 40 kbars, (9) 324*d*.
Bell, R. J., and Dean, P. Configurational entropy of vitreous silica in the random network theory, (4) 129*d*.
Bell, R. L., Graeme-Barber, C., and Langdon, T. G. Contribution of grain boundary sliding to the overall strain of a polycrystal, (1) 26*b*.
Bell, R. L., and Uebbing, J. J. Photoemission from InP-Cs-O, (1) 34*a*.
Bell, R. O. Study of the perovskites Pb(Nb-Fe)$_{1/2}$O$_3$ and Sr(TaFe)$_{1/2}$O$_3$ with the Moessbauer effect, (10) 361*b*.
Bell, S. A. See Kolpack, R. L.
Bell Telephone Laboratories, Inc. Aluminum-gold contact to silicon and germanium, P (1) 17*h*. Camera tube target including *n*-type semiconductor having higher concentration of deep donors than shallow donors, P (1) 17*i*. Cathodic sputtering of films of stoichiometric zinc oxide, P (5) 182*i*. Cathodic sputtering from a cathodically biased target electrode having an rf potential superimposed on the cathodic bias, P (11) 376*h*. Devices utilizing crystals of $Pb_2MgNb_2O_9$, P (10) 344*f*. Electroluminescent cell comprising zinc-doped gallium arsenide on one surface of a silicon nitride layer and spaced chromium-gold electrodes on the other surface, P (5) 182*i*. Electroluminescent junction device including a bismuth doped group III (a)-V(a) composition, P (4) 112*g*. Electroluminescent material and device, P (11) 376*d*. Electron beam charge storage device employing diode array and establishing an impurity gradient to reduce the surface recombination velocity in a region of electron-hole pair production, P (11) 376*d*. Electrostatic control of electron movement in cathode sputtering, P (4) 112*j*. [Epoxy] bonding transducers to delay lines, P (2) 64*e*. Fabrication of solid thin film capacitor, P (7) 256*g*. Ferrimagnetic light transmission garnets, P (9) 312*h*. Fluorescent garnet compositions and optical maser devices utilizing such compositions, P (2) 64*g*. Garnet compositions, P (8) 282*h*. Generation of second harmonic optical wave energy, P (2) 65*a*. Glass bonding medium for ultrasonic devices, P (4) 98*h*. Growth of *a*-domain barium titanate, P (11) 376*i*. Growth of lithium niobate crystals, P (8) 282*i*. Hydrothermal growth of potassium tantalate-potassium niobate mixed crystals and material so produced, P (7) 256*b*. Infrared modulators and detectors employing single crystal Te or Se, P (4) 113*d*. Lapping machine, P (11) 371*b*. Light sensitive storage device including diode array, P (4) 113*h*. Lithium metaniobate crystalline growth from melt containing magnesium oxide, P (4) 113*i*. Low resistance contact to diffused junction germanium transistor, P (2) 65*i*. Magnetic memory element comprising Ni-Fe and Zr and composition comprising Ni-Fe-Zr, P (5) 183*h*. Method for alignment of microcircuit devices on substrate, P (11) 377*g*. Method of fabricating integrated circuits by controlled process, P (7) 257*b*. Method of fabricating semiconductor contacts, P (8) 282*h*. Method for making closely spaced conductive layers, P (11) 377*b*. Nd and Yb doped borate laser glass, P (11) 372*b*. Negative resistance microwave device, P (5) 184*b*. Nontranslating variable output coupler for optical masers, P (9) 313*j*. Optical devices utilizing substantially tetragonal ferroelectric tungsten-bronzes, P (5) 184*d*. Optical $LiNbO_3$ modulator, P (8) 283*g*. Optical modulator, P (11) 378*b*. Oriented $LiTaO_3$ crystal and devices using same, P (11) 378*b*. Preparation of metal-coated powders and cathode structures, P (2) 66*g*. Process for introduction of oxygen vacancies in perovskite ferroelectric crystals, P (5) 185*a*. Process for preparation of stabilized metal film resistors, P (10) 345*g*. Sealed reed switch with adjustable reed, P (5) 185*f*. Second harmonic semiconductor modulators for coherent radiation, P (10) 345*j*. Second overtone DT-cut quartz resonator, P (2) 66*a*. Semiconducting niobate tantalate compositions, P (4) 116*a*. Semiconductive device including beam leads, P (5) 185*h*. Semiconductor amplifier using field-effect modulation of tunneling, P (11) 378*b*. Semiconductor integrated circuitry with improved isolation between active and passive elements, P (4) 116*c*. Silicon oxide tunnel diode structure and method of making same, P (5) 185*j*. Solution growth of nitrogen doped gallium phosphide, P (11) 379*b*. Surface-barrier diode transducer using high dielectric semiconductor material, P (8) 283*i*. Technique for fabrication of printed circuit resistors, P (5) 185*d*. Techniques for charting and removing defects in thin film capacitors, P (2) 66*i*. Temperature measuring apparatus using semiconductor junction, P (5) 188*h*. Thin film distributed RC network, P (8) 284*b*. Tunable crystal diodes, P (9) 314*c*. Tunable Raman laser, P (6) 224*b*. ZnTe:O electroluminescent device, P (4) 117*d*.
Bellaire, M. Brush and sgraffito decoration, (7) 244*b*. Printing with plastic foam, (7) 244*d*. Reverse motif, (6) 206*b*.
Belloc, P. A. M. Ferroelectric ceramics, P (7) 256*h*. Method of manufacturing ferroelectric ceramics, P (5) 183*j*.
Beloivan, A. F., Isakhanov, G. V., Radomyssel'skii, I. D., and Shcherban, N. I. Mechanical properties of sintered metal-glass materials, (1) 4*g*.
Belokrinitskii, N. S. See Broude, V. L.
Belopol'skii, M. S. Preparation of ceramic molding powder in spray dryers, (11) 375*h*.
Belostotskaya, N. S., and Sheinin, E. I. Hydrostatic pressing of sanitary ware, (11) 375*f*.
Belov, K. P., Talalaeva, E. V., and Yarkho, G. A. Magnetic properties of lanthanide ferrite garnets near the Curie point, (2) 80*c*.
Belova, A. N. See Shteinberg, Yu. G.
Belova, M. A. See Gal'perin, E. L.
Belt, R. F. Lang X-ray topographic studies of ruby grown by different methods, B (1) 40*i*.
Belyaev, E. K. See Safiullin, N. Sh.
Belyaev, I. N., Aver'yanova, L. N., and Belyaeva, I. I. Solid phase reactions of the titanates of bivalent metals, (7) 268*h*.
Belyaev, I. N., and Revina, O. Ya. System MeF-MnF_2(Me=Li,Na,K,Rb,Cs), (7) 269*j*. Ternary systems of the fluorides of the alkali metals and manganese, (7) 270*d*.
Belyaeva, I. I. See Belyaev, I. N.
Belyaevskaya, L. V. See Kunev, D. K.
Belyakov, I. M. See Tananaev, I. V.
Belyakova, E. P., Goroshchenko, Ya. G., Dvernyakova, A. A., and Shirokova, G. A. Water extraction of decomposition products of modified ilmenite treated with sulfuric acid, (7) 262*c*.
Belyavskaya, V. V., and Kupriyanova, L. A. Phase analysis of compounds in the system CaO-ZrO_2-SiO_2, (2) 70*b*.
Belyi, L. I. See Kharchenko, N. F.
Benard, E. J. J., and de Leeuw, G. Method and device for the production of glass footed stemware, P (10) 339*a*.
Benassi, R. Moistening apparatus particularly for use in mixing argillaceous products, P (1) 20*f*.
Benbow, J. J. See Ovenston, A.
Bendeliani, N. A., Popova, S. V., and Vereshchagin, L. F. New modifications of ZrO_2 and HfO_2 produced under high pressures, (4) 146*g*.

Bendix Corp. BaO-Nb_2O_5-SiO_2 glass compositions for use in fiber optics, P (11) 371*a*. Copper base friction material with dispersed spinels, P (6) 229*d*. Method of manufacturing semiconductor devices, P (8) 283*d*. Method of mounting semiconductor devices on thick film circuits, P (11) 377*f*. Multiemitter semiconductor device, P (11) 377*j*. Negative resistance semiconductor device, P (11) 378*a*.

Ben-Dor, L. See Jungreis, E.

Bendoraitis, J. G., and Salomon, R. E. Optical energy gaps in the monoclinic oxides of hafnium and zirconium and their solid solutions, (1) 33*h*.

Benedek, G., and Nardelli, G. F. Lattice dynamics of imperfect alkali halides, (6) 234*j*.

Benedict, T. S., and Norman, H. W. [Growth of] single crystal silicon rods, P (9) 312*a*.

Bennema, P. Analysis of crystal growth models for slightly supersaturated solutions, (5) 192*d*. Interpretation of the relation between the rate of crystal growth from solution and the relative supersaturation at low supersaturation, (6) 233*i*.

Bennema, P., and Haneveld, H. B. K. Error analysis of a technique to determine the rate of crystal growth from solution at low super saturations, (5) 194*e*. Least-square method to determine a theoretical rate of growth versus relative supersaturation curve from accurate data, (5) 196*a*.

Bennett, C. E. G. See McKinnon, N. A.

Bennett, C. E. G., McKinnon, N. A., and Williams, L. S. Sintering in gas discharges, (9) 329*g*.

Bennett, G. A. Seeded growth of garnet from molten salts, (7) 259*b*.

Bennett, H., and Reed, R. A. Method for the determination of silica by coagulation (for high-silica, aluminosilicate, and aluminous materials), (10) 347*i*.

Bennett, H. E. Instrument for measuring absolute reflectance and transmittance at cryogenic temperatures, P (1) 22*c*.

Bennett, H. E., Bennett, J. M., and Ashley, E. J. Measuring thin film thickness using interferometric-capacitance technique, P (5) 183*i*.

Bennett, H. S. Electric fields produced by a charge density in ionic crystals, (4) 134*c*. Electrostatic potentials and their spatial derivatives about point defects in ionic crystals, (4) 135*c*.

Bennett, J. M. See Bennett, H. E.; Speakman, K.

Bennett, J. M., and Smith, J. V. Positions of cations and molecules in zeolites with the faujasite-type framework (I) dehydrated Ca-exchanged faujasite, (2) 81*i*; (II) dehydrated La-exchanged faujasite; (III) hydrated Ca-exchanged faujasite, (8) 296*a*; (IV) dehydrated La-exchanged faujasite at 420°C, (10) 359*c*.

Bennett, R. W., and Sprague, L. G. Metallic members for insertion into glass, P (4) 99*b*.

Bennion, R. B. See Woriton, T. G.

Beno, R. L. See Baum, G. A.

Benson, G. C., and Claxton, T. A. Application of a shell model to the calculation of surface distortion in alkali halide crystals, (4) 126*i*.

Benson, G. E. Apparatus for bulking yarn, P (1) 10*c*. Method and apparatus for handling strand, P (2) 53*h*.

Benson, J. E. See Huang, Yun-Yang.

Benton, E. J., and Kalousek, G. L. Sulfate-bearing phases in steam-cured cement pastes, (6) 206*j*.

Bentz, G., Provost, G., and Urban, C. Plasma-gun spraying of borides and nitrides (II) properties of resulting products, (5) 177*j*. Spraying of borides and nitrides with the plasma torch, (2) 58*a*.

Ben-Yair, M. See Heller, L.

Benz, M. G. Superconducting performance of diffusion-processed Nb_3Sn (Cb_3Sn) doped with ZrO_2 particles, (4) 157*i*. See Martin, D. L.

Benz, R. Thorium-thorium monoarsenide phase equilibria, (5) 202*g*.

Benz, R., and Tinkle, M. C. Uranium-uranium monoarsenide phase diagram, (4) 163*b*.

Berard, M. F. See Crick, R. F.; Wirkus, C. D.

Berard, M. F., and Wilder, D. R. Cation self-diffusion in polycrystalline Y_2O_3 and Er_2O_3, (4) 128*d*.

Berard, M. F., Wirkus, C. D., and Wilder, D. R. Diffusion of oxygen in selected monocrystalline rare earth oxides, (1) 27*b*.

Bereczky, E. Studies to stabilize and to increase formation velocity of tricalcium silicate, (8) 298*f*.

Berens, L. W., and Hoppe, H. J. Flow properties of calcium hydrate pastes, (11) 367*j*.

Berenshtein, P. I., and Ermolaeva, A. I. Developing production parameters for wall tiles once-fired in roller kilns, (6) 219*d*.

Berenshtein, P. I., Krasnousova, A. S., and Rokhvarger, E. L. Rapid firing of face plates in roller kilns, (11) 372*e*.

Beretka, J., and Ridge, M. J. Dehydration products of aluminum hydroxides, (4) 130*h*. Formation of zinc ferrite at low temperatures, (7) 266*c*. Reaction between iron(III) oxide and barium carbonate in vacuo, (8) 297*e*.

Berezhnoi, A. I., and Polukhin, Yu. M. Study of the formation of crystallization centers in light-sensitive glasses, (2) 51*b*.

Berezin, G. I., and Kiselev, A. V. Dependence of heat capacity of adsorbate on surface coverage on the basis of BET theory assumptions, (1) 26*i*.

Berezovskii, V. I. Phase transitions during firing of phosphogypsum and strength of phosphoanhydrite cement, (8) 274*e*.

Berg, L. G., Malkova, T. I., and Pavlova, A. K. System PbTe-PbI_2, (9) 331*e*.

Berg, M. See Schwartzwalder, K.

Berg, W. T. Specific heat of Corning 7560 glass between 4.5° and 20°K, (1) 8*j*.

Bergenback, R. E. See Williams, E. G.

Berger, C., and Strier, M. P. Zirconium phosphate membranes for intermediate temperature fuel cells, (4) 164*c*.

Berger, G. See Keller, W.

Berger, M., and Sienko, M. J. Magnetic susceptibility of uranium trifluoride in the range 2°–300°K, (4) 143*b*.

Berger, S. Electrophoresis and its industrial applications, (6) 220*g*.

Bergeron, C. G. Electrical properties of vitreous coatings, (7) 245*j*. See De Luca, J. P.

Berges, M. D., and Domine, D. Production of crystalline mordenite, P (7) 263*b*.

Berggren, M. J. See Wong, J. Y.

Bergh, S., Sandberg, H., and Stahl, N. Continuous measurement of lining wear in steel furnaces with radioisotopes, (7) 250*h*.

Berghezan, A. I. Polycrystalline oxide bodies, P (8) 274*e*. Solid solution cement, P (8) 274*f*.

Berghout, C. W., Hokkeling, P., and Lutelin, A. I. Method of manufacturing solid bodies containing Nb_3Sn, P (5) 184*a*.

Berglund, C. N. Electroluminescent cell comprising zinc-doped gallium arsenide on one surface of a silicon nitride layer and spaced chromium-gold electrodes on the other surface, P (5) 182*i*.

Berglund, C. N., and Kahng, D. Semiconductor amplifier using field-effect modulation of tunneling, P (11) 378*b*.

Bergman, A. G. See Akopov, E. K.; Il'yasov, I. I.

Bergman, A. G., and Andryushchenko, Yu. I. Some properties of the systems of the bromides of lithium, calcium, and lead, (9) 329*c*.

Bergman, J. G., Ashkin, A., Ballman, A. A., Dziedzic, J. M., Levinstein, H. J., and Smith, Richard G. Curie temperature, birefringence, and phase-matching temperature variations in $LiNbO_3$ as a function of melt stoichiometry, (1) 26*e*.

Bergman, R. M. See Wilhelm, H. A.

Bergmann, O. R. Cermets of aluminum with titanium carbide and titanium and zirconium borides, P (11) 374*g*.

Bergna, H. E. Metallic [boride] refractory compositions, P (10) 342*i*.

Bergquist, H. R. See Ross, C. S.

Bergseth, H. Phosphate combination with and release from clay minerals through anion exchange treatment with ^{32}P, (4) 149*a*.

Bergstein, A. Compensated tetragonal deformation and oxygen nonstoichiometry in spinels $Cu_{0.5}Mn_2Fe_{2.5-\delta}O_{4+\gamma}$, (7) 264*j*. Formation of the spinel $Cu_{0.5}Fe_{2.5}O_4$ from $CuFe_2O_4$ and α-Fe_2O_3, (8) 292*j*.

Bergstoel, S. See Christie, O. H. J.

Bergstrom, J. W., and Sutherland, G. E. Method of fabricating ferrite bodies, P (5) 183*d*.

Bergwerksverband, G.m.b.H. Method and apparatus for successively metering identical quantities of particulate material, P (4) 118*f*.

Bering, B. P., Zhukovskaya, E. G., Rakhmukov, B. Kh., and Serpinskii, V. V. Adsorption in micropores (I) theoretical representations, (7) 263*h*.

Berkes, J. S., and White, W. B. Calculation of volume free energy of nucleation of a crystalline phase from a multicomponent regular solution, (6) 230*f*. Phase relations in the system Li_2O-B_2O_3-B_2O_3-NiO, (11) 386*e*.

Berkowitz-Mattuck, J. B. High-temperature oxidation (III) zirconium and hafnium diborides, (2) 78*g*; (IV) zirconium and hafnium carbides, (4) 138*e*. See Buechler, A.

Berl, K. Texture and pattern on metal bases(I), (8) 273*j*; (II), (10) 335*i*.

Berman, I. See Ryan, C. E.

Berman, M., and Ergun, S. Angular positions of X-ray emission lines of the elements for common analyzing crystals, (9) 318*b*.

Bernard, H. W., and Aston, J. G. Susceptibilities of copper acetylacetonate adsorbed on anatase and silica gel and diphenylpicrylhydrasyl adsorbed on silica gel from 1°–4°K, (5) 200*h*.

Bernard, N. G. S. See Deschamps, A.

Bernardini, F., and Collepardi, M. Pore distribution in solids from sorption isotherms of nitrogen at −195.8°C, (2) 70*d*.

Bernardini, F., Collepardi, M., and Armisi, I. Pore distribution in solids from sorption isotherms of nitrogen at −195.8°C (II), (4) 120*d*.

Berne, B. J., Pechukas, P., and Harp, G. D. Molecular reorientation in liquids and gases, (9) 325*b*.

Bernert, J. Installations and methods for the reduction of emissions from commercial installations as well as methods for the determination of their effectiveness, (10) 363*j*.

Berning, P. H., and Small, E. A., Jr. Transparent articles coated with gold, chromium, and germanium alloy film, P (1) 11*e*.

Bernolak, B. Experimental data on spectrographic qualitative analysis of materials used in the silicate industry, (8) 285*b*.

Bernstein, F., and Mattson, R. A. Quantitative X-ray emission analysis of magnesium through fluorine with X-ray and electron excitation, B (1) 40*j*.

Bernstein, H. J. See Rolfe, J.

Bernstein, J. L. See Abrahams, S. C.; Jamieson, P. B.

Berolo, O. See Wooley, J. C.

Berry, J. S., Jr. See Richards, N. E.

Berry, L. G. See Mason, B.; Radcliffe, D.

Berry, W. B., and Jayadevaiah, T. S. Mobility studies on vacuum deposited PbTe thin films, (8) 281*b*.

Berryhill, J. R. Capacitor and method of making same, P (5) 182*g*.

Bershov, L. V. See Morfunin, A. S.

Bertaut, E. F., Chappert, J., Apostolov, A., and Semenov, V. Moessbauer effect and neutron diffraction study of monocalcium ferrite, Fe_2O_3-CaO, (1) 33*b*.

Bertaut, E. F., Mareschal, J., and DeVries, G. F. Neutron diffraction study of the magnetic structure of terbium chromite, (10) 357*f*.

Bertens, J. A. A. See Bril, A.

Berth, M., and Jean, B. L. P. Method of manufacturing a target plate for use in a camera tube, P (10) 345*j*.

Bertorelli, O. L. See Mays, R. K.

Bertoti, I., Lendvay, E., Farkas-Jahnke, M., Harsy, M., and Kovacs, P. Dendritic growth of ZnS crystals, (6) 231*e*.

Bertoya, H. C. M. See Baker, L. R.

Bertozzi, G., and Soldani, G. Surface tension of liquid cadmium chloride-alkali chloride systems, (5) 200*g*.

Bertrand, L., and McCarthy, H. E. Fluid energy milling process, P (11) 379*f*.

Bertsch, W. See Englehardt, W. V.

Bertulis, K. See Tolutis, V.

Berube, Y. G., and DeBruyn, P. L. Adsorption at the rutile-solution interface (I) thermodynamic and experimental study, (5) 191*i*.

Berul, S. I., and Nikonova, I. N. Interaction of boric anhydride with the fluorides of barium and lithium, (4) 140*b*.

Berul, S. I., and Voskresenskaya, N. K. Reaction of ferric oxide with sodium metaphosphate, (8) 297*e*.

Beryllium Corp. Production of beryllium fluoride, P (4) 125*e*.

Besenbruch, G., Kana'an, A. S., and Margrave, J. L. Knudsen and Langmuir measurements of the sublimation pressure of cadmium(II) fluoride, (1) 31*g*.

Besselere, J. P., and Le Duc, J. M. Crystallization of gallium phosphide from a stoichiometric melt in a gallium solution, (8) 290*f*.

Bessent, R. G. Paramagnetic resonance of an *N* center in calcium oxide, (11) 386*c*.

Bessent, R. G., Cavenett, B. C., and Hunter, I. C. Faraday rotation studies of *F* centers in alkaline earth oxides, (10) 353*b*.

Bessey, G. E. Current developments affecting the design and use of mortars for building purposes, (2) 44*b*.

Besson, J. See Souquet, J. L.

Bessonov, A. F. See Ust'yantsev, V. M.

Bessonov, A. F., Shalaginov, V. N., and Taksis, G. A. Complex study of processes during the heating of a mixture of zirconium dioxide and calcium carbonate, (7) 264*a*.

Best, H. S., and Bowser, R. E. Resistor tailoring machine, P (5) 185*f*. [Vibratory] process for joining transistor chip to printed circuit, P (2) 67*a*.

Best, W. V., and Hughes, R. L. Apparatus and method for producing silica and other oxides, P (5) 190*f*. Preparation of luminescent silica glass modified with a rare earth metal, P (11) 372*c*. Process of producing oxides of metals and metalloids, P (4) 125*j*.

Best, W. V., Hughes, R. L., and Austin, L. M. Art of producing metal salt impregnated silica-coated substrates, P (7) 248*a*.

Bethell, K. D., Shaw, J. T., and Thomas, A. C. Improved form of solid oxidizer for the conversion of nitric acid to nitrogen dioxide, (2) 72*b*.

Bethlehem Steel Corp. Composite refractory lining for basic oxygen furnace, P (4) 106*b*. Graphite bearing high MgO mortar, P (8) 279*b*. Rotary crusher feeding aid, P (8) 288*d*.

Bettinali, C., Ferraresso, G., and Manconi, J. W. Thermoluminescence of ZrO_2, (11) 388*e*.

Bettinali, C., Gottardi, V., and Ferraresso, G. Application of thermoluminescence in glass study, (6) 208*f*.

Beucher, M. Crystallographic data for CaP_4O_{11}, (10) 351*f*.

Beucher, M., and Grenier, J. C. Crystallographic data for tetrametaphosphates of the type $M_2^{II}P_4O_{12}$(M^{II}=Ni, Mg, Zn, Cu, Co, Mn), (2) 75*h*.

Beumel, O. F., Jr., Smith, W. N., Jr. and Harris, R. F. Method for making lithium borohydride, P (11) 382*d*.

Bever, M. B. See Reti, A. M.

Beyard, R. M., and Horai, J. C. Artificially colored mineral granules, P (5) 180*d*.

Beyersdorfer, P. Knowledge about oxygen in silicates, (11) 385*a*.

Bezborodov, V. G. Technological properties of slips for hot casting glass articles under pressure, (6) 211*e*.
Bezdekova, A. See Budesinsky, B.
Bezouska, V., Skvor, J., Paljisek, F., Zavazal, Z., and Pokorny, O. Semiconductor assembly with semiconductor element in area contact under pressure with conductive terminal elements, P (6) 223*d*.
Bezpalov, K. M. Automation of machines for vertical drawing of glass, (1) 5*i*. Influence of change in height of molten glass on thickness and taper of glass sheet, (2) 49*j*.
Bhadra, A. K., Mandal, S. S., and Roy, S. B. Effect of stains and inclusions on the electrical properties of mica, (5) 190*d*.
Bhandari, R. C. See Chaudhary, D. R.
Bhat, R. See Moorthy, V. K.
Bhatt, S. J., and Merchant, H. D. Influence of stoichiometry on lattice parameter in Fe_2O_4, NiO, and Ni-Fe ferrite, (10) 344*g*.
Bhattacharya, D. S. Quartz fabric studies in the rocks of the Sonapet Valley, Singhbhum District, Bihar State, (4) 123*h*.
Bhattacharyya, B. N., Bhusan, B., and Sen, S. Zircon sand from Kerala beach, its mineralogy, metamictization and suitability as a raw material for glaze opacification, (10) 348*i*.
Bhatty, M. I., Rasheed, A. Z., and Qureshi, A. A. Beneficiation of low grade lead ore, (6) 228*j*.
Bhide, G. K., Verma, R. L., Ananthanarayan, A., Rangarajan, L. M., Valdya, M. D., and Kelkar, G. N. Development of cathode ray oscilloscope tubes, (4) 109*h*.
Bhide, V. G., and Multani, M. S. Moessbauer effect for ^{57}Fe in ferroelectric $BaTiO_3$: Vacancy-impurity associated state, (5) 197*g*.
Bhusan, B. See Bhattacharyya, B. N.
Bianchini, A. See Gottardi, V.
Biard, J. R. Semiconductor optical radiation device, P (10) 346*d*.
Biard, J. R., Bonin, E. L., Kilby, J. S., and Pittman, G. E. Electrooptical transistor switching device, P (4) 112*i*.
Bibenina, G. A., and Smirnov, M. P. System PbS-Na_2S-CuS, (8) 299*g*.
Bichara, M. R. E. Absorption coefficient of GaAs at microwave and millimeter wave frequencies, (1) 24*g*.
Bickley, R. I., and Gregg, S. J. Nitridation of magnesium in the temperature range 400°–650°, (1) 33*d*.
Bicknell, J. A., and Lipson, H. Methods for interpretation of electron diffraction patterns of thin alloy films, (4) 144*j*.
Biczok, E. Air permeability of granular materials, (5) 183*h*.
Biddy, O. D., Jr. See Hampikian, A. K.
Bidwell, L. R. Free energy of formation of cupric oxide, (4) 136*e*. See Rizzo, F. E.
Biegler, H., Neugebauer, W., and Kempers, H. Apparatus for the production of finely divided amorphous silica, P (5) 189*f*.
Bielecki, E. J., and Albright, R. A. Purification of niobium and tantalum pentoxides, P (7) 263*c*.
Bieler, B. H. See Bunting, J. A.
Bieling, C. A. See Egerton, L.
Biemann, F. Dominik Biemann's dealings with the dealer Steigerwald in Frankfurt am Main, (4) 90*g*.
Bienert, W. B., and Gillen, F. M. Process of making Mn_4Si_7 thermoelectric element and product of the process, P (2) 66*h*.
Bienstock, D. See Feldmann, H. F.
Bier, M. See Moulik, S. P.
Biermann, M. Rheology, (4) 118*b*.
Biermann, W. See Kunert, H.
Bierstedt, P. E. See Bither, T. A.
Bigelow, W. C. See Tien, T. Y.
Biggar, G. M. System CaO-NiO-SiO_2, (8) 299*c*. See O'Hara, M. J.
Biggar, G. M., and O'Hara, M. J. Monticellite and forsterite crystalline solutions, (7) 267*e*.
Bikova, A. V. See Perrault, G.
Bilaine, J. Silicon carbide refractories, (1) 13*e*.
Bilbe, W. G. Sintering method, P (8) 280*a*.
Bildstein, H., Stolba, G., and Knotik, K. Method for the extraction of materials embedded in a graphite body, P (5) 178*j*.
Bil'kevich, I. N. See Rudnev, N. A.
Bill, H., Sierro, J., and Lacroix, R. Origin of coloration in some fluorites, (4) 147*g*.
Bilous, O. See Pecoraro, R. P.
Binkley, M. E., and Ayers, O. Effect of cryolite on calcium silicate compositions, P (9) 304*b*.
Binnie, W. P. See Redman, M. J.
Binnix, W. B. Pneumatic separator and classifier apparatus and method, P (5) 191*e*.
Binns, D. B., George, W., and Popper, P. Factors affecting the surface resistivity of alumina ceramics, (2) 62*b*.
Binns, D. B., and Popper, P. Mechanical properties of some commercial alumina ceramics, (2) 56*c*.
Bintzek, G. See Richter, H.
Bippus, J. R., and Johnson, A. F., Jr. Methods and apparatus for separating articles initially in a compact array, and composite assemblies so formed, P (9) 313*e*.
Birbeck, F. E. See Bass, S. J.
Birch, J. A. See White, G. K.
Birchler, R. O., and Williams, E. R., Jr. Semiconductor devices and process for embedding same in plastic, P (7) 258*c*.
Birgeneau, R. J. Mechanisms of energy transport in ruby, (11) 386*a*.
Birkle, A. J. See Grenawalt, J. J.
Birkner, F. B. See Black, A. P.
Birle, J. D., and Ehlers, E. G. High pressure phase of Al_2GeO_5, (7) 266*d*.
Birle, J. D., Gibbs, G. V., Moore, P. B., and Smith, Joseph V. Crystal structures of natural olivines, (8) 290*c*.
Bisaz, S. See Fleisch, H.
Bischoff, J. L. Catalysis, inhibition, and the calcite-aragonite problem (II) the vaterite-aragonite transformation, (6) 230*h*. Temperature controls on aragonite-calcite transformation in aqueous solution, (11) 387*i*.
Bischoff, J. L., and Fyfe, W. S. Catalysis, inhibition, and the calcite-aragonite problem (I) the aragonite-calcite transformation, (6) 230*g*.
Bishay, A., and Gomaa, I. Gamma-induced absorption in silicate glasses containing titanium, (6) 209*c*.
Bishay, A., and Maghrabi, C. Properties of bismuth glasses in relation to structure, (7) 247*j*.
Bishop, B. A., and Hogarth, C. A. Thermal oxidation of silicon using wet oxygen, (1) 17*f*.
Bishop, F. L. Cathode-ray tube envelopes, P (2) 52*c*. Composite lamp article with glass-ceramic lamp envelope, P (9) 307*b*. Method of sealing copper in silica body, P (8) 278*b*.
Bishop, L. H. Air conveyor and unloader for granular materials and unloading process therefor, P (10) 346*j*.
Bishop, S. G. See Kriz, H. M.
Bishop, S. G., and Bray, P. J. NMR studies of diffusion in glassy and crystalline lithium borates, (1) 8*a*.
Bishui, B. M. See Aggarwal, P. S.
Bishui, B. M., and Ghosh, D. K. Mineralogical studies of clays of chain-like structure, (10) 357*g*.
Bissada, K. K., Johns, W. D., and Cheng, F. S. Cation-dipole interactions in clay organic complexes, (7) 264*c*.
Bistline, W. A. Optimum batch moisture and unique furnace feeding pays off for Kerr glass, (7) 247*i*.
Biswas, D. K. See Poddar, S. N.
Biswas, S. R., and Mukerji, J. Solubility of ruthenium in silicate and phosphate glasses, (10) 338*i*.
Bither, T. A., Prewitt, C. T., Gillson, J. L., Bierstedt, P. E., Flippen, R. B., and Young, H. S. New transition metal dichalcogenides formed at high pressure, (4) 146*a*.
Bittel, J. T., Sjodahl, L. H., and White, J. F. Steam oxidation kinetics and oxygen diffusion in UO_2 at high temperatures, (10) 361*b*.
Bitterlich, G. M. Burners, P (5) 189*g*.
Bixby, P. H. Talc beneficiation method, P (4) 126*a*.
Bizouard, M., Cerisier, P., and Scandellari, B. Temperature regulation of a laboratory furnace to 800°C with an accuracy of ±0.02°C, (1) 22*j*.
Bjerkelund, E., and Kjekshus, A. High-pressure induced transformations in $NbTe_4$ and $TaTe_4$, (10) 354*h*.
Bjorkholm, J. E. Relative signs of the optical nonlinear coefficients d_{31} and d_{33} in $LiNbO_3$, (8) 297*i*.
Bjornson, G. High temperature zirconia coated thermocouple, P (11) 381*f*.
Bkhargava, Kh. D., Kovba, L. M., Martynenko, L. I., and Spitsyn, V. I. Interaction of barium oxide with oxides of the rare-earth elements, (7) 267*d*.
Black, A. P., Birkner, F. B., and Morgan, J. J. Effect of polymer adsorption on the electrokinetic stability of dilute clay suspensions, (1) 28*b*.
Blackburn, A. R. See Emmel, D. R.
Blackburn, P. E., and Buechler, A. Thermodynamics of vaporization in the beryllium oxide-boron oxide system, (2) 84*h*.
Blackburn, P. E., Buechler, A., and Stauffer, J. L. Thermodynamics of vaporization in the aluminum oxide-boron oxide system, (4) 162*d*.
Blackburn, W. H., and Dennen, W. H. Grinding apparatus for the accurate removal of thin layers from rock slabs, (11) 380*f*.
Blackburn, W. S. Criterion for crack nucleation from a dislocation pileup, (2) 75*g*.
Blackman, L. C. F., and Harrop, R. Hydrophilation of glass surfaces (I) investigation of possible promoters of filmwise condensation; (II) reaction of quaternary ammonium compounds with surface hydroxyl groups; (III) synthesis of novel quaternary ammonium compounds tested as possible promoters of filmwise condensation, (9) 305*h*.
Blackman, S. N. Mercury glass clinical thermometer with maximum temperature recording trap and method of making the trap, P (11) 371*d*.
Blackwelder, B. W. See Pilkey, O. H.
Blaha, E. Method of making ceramic shapes, P (5) 180*c*.
Blair, F. G. See Anderson, S.
Blair, G. R. Inorganic thermal control pigment, P (6) 208*b*.
Blair, J. C. See Hartman, T. E.
Blair, R. C., and Munir, Z. A. Vapor pressure and heats of sublimation of calcium nitride, (8) 300*e*.
Blake, W. E., Bryant, M. W. R., and Waters, A. Flame photometric determination of calcium in solutions of high sodium content, (7) 260*d*.
Blakeslee, A. E. Effects of substrate misorientation in epitaxial GaAs, (9) 320*d*.
Blank, B. A. H., and Searcy, A. W. Rate of sublimation of magnesium nitride from effusion cells and from free surfaces in vacuo and in argon and nitrogen gases, (5) 199*i*.
Blank, J. M., and Potter, R. M. SiC *pn* junction electroluminescent diode with a donor concentration diminishing from the junction to one surface and an acceptor concentration increasing in the same region, P (11) 378*i*.
Blank, S. L., and Pask, J. A. Solubility limits in the MgO-Fe_2O_3 system as determined by diffusion, (10) 360*j*.
Blank, Z., and Brenner, W. Growth of single crystals of cuprous oxide in silica gel at near ambient temperatures, (10) 354*j*.
Blank, Z., Brenner, W., and Okamoto, Yoshiyuki. Growth of single crystals of lead sulfide in silica gels at ambient temperatures—preliminary characterization and effect of various organic compounds as sulfide ion donors, (7) 266*j*.
Blank, Z., Speyer, D. M., Brenner, W., and Okamoto, Y. Growth of single crystals of silver halides in silica gels at near ambient temperatures, (7) 266*j*.
Blankenburg, H. Liquid-gas equipment in a porcelain factory, (6) 219*h*.
Blankenburg, J. See Bostroem, K.
Blass, R. See Schafer, W.
Blasse, G. Concentration quenching of characteristic broad-band fluorescence, (10) 350*i*. Fluorescence of uranium-activated compounds with rock salt lattice, (10) 353*g*. Influence of crystal structure on luminescence, (8) 293*a*. Properties of magnetic compounds in connection with their crystal chemistry, B (7) 272*b*. See Bril, A.
Blasse, G., and Bril, A. Fluorescence of Eu(II) activated alkaline earth aluminates, (9) 321*f*. Fluorescence of Eu^{3+}-activated garnets containing pentavalent vanadium, (4) 136*b*. Fluorescence of Eu^{3+}-activated sodium lanthanide titanates ($NaLn_{1-x}Eu_xTiO_4$), (5) 194*h*. Fluorescence of rhodium-activated aluminum oxide, (4) 110*g*. Investigations on Bi^{3+}-activated phosphors, (2) 79*h*. Luminescence phosphors based on host lattices ABO_4 (A=Sc,In; B=P,V,Nb), (11) 385*g*. Phosphors based on Ln_2SO_5, (10) 358*e*.
Blasse, G., Bril, A., and de Vries, J. Fluorescence of Eu^{3+}-activated barium octaborate, (10) 353*f*.
Blasse, G., Wanmaker, W. L., and ter Vrugt, J. W. Some new classes of efficient Eu^{3+}-activated phosphors, (5) 200*c*.
Blasse, G., Wanmaker, W. L., ter Vrugt, J. W., and Bril, A. Fluorescence of Eu(II) activated silicates (9) 321*e*.
Blasum, H. A., and Claus, D. Combating dust in the ceramic industry, (6) 224*g*.
Blau, F. R. Glass union, P (5) 175*a*.
Blauer, J. A. See Ko, H. C.
Blauer, J. A., Greenbaum, M. A., and Farber, M. Thermodynamic and physical properties of beryllium compounds (IX) free energy of formation of beryllium hydroxide(*g*), (4) 161*h*.
Blaw-Knox Co. Centrifugal casting apparatus with smooth refractory nonhydrocarbon mold coating, P (7) 252*e*. Mold coating composition, particularly for centrifugal molds, P (9) 309*a*.
Blazer, R. See Peisl, H.
Blazey, K. W. Ferromagnetic exchange coupling in the spinel lattice, (4) 136*e*.
Bleckmann, H. Measurement of expansion at high temperature by X-ray diffraction, (11) 380*g*.
Blezard, R. G. See Fifield, J. A.
Blicher, A. Insulated-gate field-effect transistor with critical bulk characteristics for use as an oscillator component, P (7) 256*d*.
Blicher, A., and Czorny, B. R. High voltage semiconductor transistor, P (5) 183*f*.
Blickensderfer, R. See Henry, J. L.
Blin, C., and Guerga, M. Drying ceramic products by means of dielectric losses—an industrial microwave dryer, (11) 381*g*.
Blinc, R., Dimic, V., Kolar, D., Lahajnar, G., Stepisnik, J., Zumer, S., and Vene, N. High-temperature phase transition in KH_2PO_4, (10) 355*b*.
Blinc, R., and Sentjure, M. Effect of applied electric field on the electron paramagnetic resonance spectra of doped ferroelectric Rochelle salt, (4) 132*h*.
Blinc, R., and Svetina, S. Cluster approximations for order-disorder type hydrogen-bonded ferroelectrics (I) small clusters; (II) application to KH_2PO_4, (1) 26*d*.
Blinov, B. S. See Sorokin, I. P.
Bliss, E. W., Co. Ceramic ferroelectric memory device, P (11) 376*i*. Ceramic memory having a piezoelectric drive member, P (1) 18*a*.
Bliznakov, G. See Peshev, P.
Bloch, J. See Lesueur, D.
Block, A., and Simms, B. B. Desorption and exchange of adsorbed octadecylamine and stearic acid on steel and glass, (1) 27*c*.
Block, M. L., and Mones, A. H. Indium oxide resistor composition, method, and article, P (4) 113*c*.
Block, S. See Weir, C. E.

Bloemen, J. L. H. H. Quantitative analysis in the ceramic industry with X-ray fluorescence, (11) 380*e*.
Blokhin, M. A. See Shuvaev, A. T.
Blomqvist, C. E. See Peisson, A.
Blomqvist, P. O. See Hedvall, J. A.
Blood, A. E. See Hagemeyer, H. J., Jr.
Bloom, M. S. See Foster, E. G.
Bloss, F. D. Indexing powder patterns for cubic materials, (11) 385*g*.
Blossey, R. G., and Pehlke, R. D. Nitrogen solubility in liquid Fe-Cr-Ni alloys, (6) 235*i*.
Bloxam, T. W. Rapid method for determination of fluoride in silicate rocks, (4) 121*b*.
Bludov, B. F. See Ved, E. I.
Blue, M. D. Solid state junction device for ultraviolet detection, P (4) 117*b*.
Bluhm, J. I. Effect of nonlinear Hertzian deformations and gage length on the measurement of elastic energy release rate, (5) 193*i*.
Blum, J. F., Fournier, R. G., and Kesten, P. N. Spark plug and seal therefor, P (2) 66*h*.
Blum, J. M., and Genser, M. Connection arrangement for three-element component to a microelectronics circuit, P (4) 112*b*.
Blum, P. See Poncelet, J.
Blum, R. T., and Zak, T. J. Lens surfacing machine for forming both surfaces of a lens simultaneously, P (8) 277*e*.
Blum, S. E. See Plaskett, T. S.
Blum, S. E., and Chicotka, R. J. Growth of large single crystals of gallium phosphide from a stoichiometric melt, (4) 137*i*.
Blum, S. E., Chicotka, R. J., and Bischoff, B. K. Gallium phosphide—its preparation in bulk ingot form, (4) 123*j*.
Blumberg, R. H., Caswell, H. L., and Chiou, C. Process control of indium sheet film memories, P (1) 19*c*.
Blume, A. J. Influence of design in the ceramic tile industry, (6) 206*d*.
Blumenberg, K. E. See Andrew, B. M.
Blumenfeld, J. F. Glassmaking apparatus, P (4) 99*d*.
Blumenfeld, J. F., and Hanks, G. F. Electrode holder for glass furnaces or the like, P (4) 98*c*.
Blumenfeld, J. F., and Merdian, J. T. Liquid cooling device for glass furnace electrode, P (1) 10*j*.
Blumenthal, R. N., Baukus, J., and Hirthe, W. M. Studies of the defect structure of nonstoichiometric rutile, TiO_{2-x}, (4) 156*g*.
Blythe, G. K. E. See Temperley, H. N. V.
Blyumkin, L. M. See Ivanovskii, G. F.
Boatner, L. A., Reynolds, R. W., and Abraham, M. M. Electron spin resonance spectra of Er^{3+} and Yb^{3+} in single crystals of $SrCl_2$, (6) 232*c*.
Boaz, P. T. See Thompson, R. J.
Bobb, J. S. S. See Weldes, H. H.
Bobo, J. C. Use of magnetism in structural determination of inorganic compounds, (1) 22*h*.
Bobrov, B. S., Epel'baum, M. B., and Pogorelov, N. M. Hydration of clinker minerals, their mixtures, and cements during initial periods, (1) 2*h*.
Bobrov, V. S., Kalmykova, L. P., and Shul'ts, M. M. Determination of the coordination state of boron by the electrode behavior of lithium borosilicate glasses, (2) 48*d*.
Bochirol, L. See Poncelet, J.
Bochkareva, I. V. See Shteinberg, Yu. G.
Bock, R., and Langrock, P. Investigation on the quantitative precipitation of germanium sulfide, (6) 233*j*.
Bockris, J. O'M. See Solomons, C.
Bocquillon, G., Susse, C., and Vodar, B. Allotropy of hafnium oxide under high pressure, (9) 318*a*.
Boczar, W. J., and Davis, W. C. Heat conductive mounting base for a semiconductor device, P (6) 221*e*.
Boddey, R. F. Method of forming a casting mold, P (11) 375*c*.
Boddy, P. J., and Frova, A. F. Optical modulator, P (11) 378*b*.
Bodenheimer, W., and Heiler, L. Sorption of α-amino acids by copper montmorillonite, (7) 269*e*.
Bodin, D. J. Dual-wheel lapping key to pump quality, (8) 273*f*.
Bodine, A. G., Jr. Apparatus for crushing rock material and the like utilizing complex sonic wave action, P (4) 124*h*. Sonic method and apparatus for grinding rock material and the like to powder, P (6) 230*d*.
Bodor, E. See Copeland, L. E.
Bodor, E. E. See Brunauer, S.; Mikhail, R. Sh.
Boehler, P. See Dionisotti, J.
Boehm, F. See Gokhale, B. G.
Boehm, H. P. Surface chemistry of solids, (6) 238*d*. See Hofmann, U.
Boehme, H. J. See Schwiete, H. E.
Boehni, H. See Dignam, M. J.
Boeing Co. Alloy for metalizing ceramics, P (2) 64*c*. Bonded article comprising two metallic members joined by an intermediate layer, P (1) 5*e*. Emissive coating, P (2) 58*d*. Polarization pyrometer, P (11) 381*a*.
Boell, G. R. See Ridge, M. J.
Boelsterli, H. U., and Hulliger, F. Preparation of Th and U oxychalcogenides, (9) 328*c*.
Boer, K. W., and Nalesnik, W. J. Semiconductivity of CdS as a function of S-vapor pressure during heat treatment between 500° and 700°C, (10) 360*g*.
Boes, D. J. Solid lubricant composites, P (5) 191*f*.
Boesenberg, W. A., Flatley, D., and Wallmark, J. T. MOS field-effect transistor drivers for laminated-ferrite memories, (8) 281*b*.
Boettcher, A. Fuel or fertile element for nuclear reactions, P (4) 106*h*.
Boettcher, A. L. See Wyllie, P. J.
Boettcher, A. L., and Wyllie, P. J. Melting of granite with excess water to 30 kbars pressure, (4) 144*b*. System CaO-SiO_2-CO_2-H_2O (III) second critical end point on the melting curve, (11) 387*c*.
Boettner, G. B. Flow control of molten material in a glass furnace, P (10) 338*i*. Glass-melting furnace, P (5) 174*i*.
Bogar, J. H. See Couper, W. D.
Bogart, B. S. Glass container coated with a lubricating film comprising carnauba wax and polyvinyl alcohol, P (8) 277*a*.
Bogdanova, G. S. See Ananich, N. I.
Bogdanova, G. S., Litvinov, P. I., and Kudryakova, M. L. Frequency and temperature dependence of ε and $tg\delta$ of sitalls containing compounds of cerium, bismuth, and lead, (2) 77*i*.
Boggs, S., Jr. Experimental study of rock fragments, (6) 228*j*.
Boggs, W. E., Kachik, R. H., and Pellissier, G. E. Effects of crystallographic orientation and oxygen pressure on the oxidation of iron, (4) 133*e*.
Boginskii, L. S., Dorozhkin, N. N., and Kabel'skii, I. M. Automatic press tool for calibrating cermet bushings and rings, (2) 68*i*.
Bognar, L. L. Apparatus [tongs] for suspending sheet glass, P (10) 338*h*.
Bogren, E. C. See Patterson, J. W.
Boguslavskii, A. I. State and future development of consumer goods (pottery and glassware) production, (6) 206*c*.
Boguslavskii, I. A., Markelova, M. Ya., and Tykachinskii, I. D. Possibilities of strengthening vitreous crystalline materials, (2) 50*b*.
Bohandy, J. See Murphy, J. C.
Bohm, J. Integrated parametric amplifier consisting of a material with both semiconductive and piezoelectric properties, P (4) 113*f*.
Bohn, E. See Stober, W.
Bohn, T. See Schulten, R.
Bohor, B. F., and Ehrlinger, H. P., III. Beneficiation of kaolinite clay from silica sand washings, (9) 316*f*.
Bohor, B. F., and Khandelwal, S. New use for Illinois clay materials in pesticide formulation, (9) 316*i*.
Bohun, A., and Dolejsi, J. Absorption and emission phenomena in NaCl crystals with a high concentration of copper, (6) 230*f*.
Boicey, J. H., and Livingston, R. L. Laminated transparent panel incorporating electrical heating wires and method of producing same, P (2) 53*d*.
Boiko, D. Ya., and Shul'man, I. G. Capacity and economic efficiency of tunnel kilns for porcelain, (6) 228*d*.
Boikova, A. I., Toropov, N. A., Piryutko, M. M., and Grum-Grzhimailo, S. V. Effect of chromium oxide on the structural changes in tricalcium silicate, (6) 231*j*.
Boikova, A. I., Toropov, N. A., and Vavilonova, V. T. Solid solutions between tricalcium silicate and tricalcium germanate, (8) 297*g*.
Boirat, R. Application of X-ray fluorescence analysis to the determination of calcium and iron, (2) 68*f*.
Boisot, M. P. Stereographic projection for monoclinic zirconia, (7) 269*i*.
Boivent, M. Method of melting glass, P (8) 277*j*.
Bok, A. B. See Fontyn, L. A.
Bokros, J. C., Chin, J., and Schwartz, A. S. Deposition of massive pyrolytic carbon, P (1) 13*h*.
Boksha, S. S. Equipment for the growth of crystals at very high gas pressures, (7) 254*h*.
Boldyrev, A. I., and Povarennykh, A. S. Infrared absorption spectra of the most important oxides, (4) 140*e*.
Bolef, D. I. See Leisure, R. G.; Miller, J. G.
Bolgar, A. S., Fesenko, V. V., and Gordienko, S. P. Study of the evaporation and thermodynamic properties of chromium carbides, (1) 38*c*.
Bolgiano, N. C. Glass surfaces coated with decorative organic coatings, P (7) 248*i*.
Boling, E. A. Gas burner for atomic absorption spectroscopy, P (6) 227*h*.
Bolkcom, W. T., and Knapp, W. E. Silicon carbide furnaces and plants, P (6) 218*f*.
Bolt, G. H. See Laudelout, H.
Bolton, A. P. See Lanewala, M. A.
Bolton, H. C., and McIntyre, P. N. Electric field in crystals (III) refractivity of α-quartz, (4) 134*a*.
Bon, C. K. See Piegols, N. L.
Bonazoli, R. P. See Palermo, J. J.
Boncoeur, M. Sintering of oxides sprayed with an oxyacetylene torch, (2) 57*g*.
Boncoeur, M., and Accary, A. Uranium monocarboxides deficient in metalloid—composition and lattice parameters, (5) 202*d*.
Boncoeur, M., Magnier, P., and Accary, A. Influence of oxygen on the existence domains of U C phases, (10) 355*e*.
Bondarenko, V. S. See Chkalova, V. V.
Bondarev, K. T., Grimal'skii, N. P., Knigin, G. E., and Gnedashevskaya, E. S. Determining batch moisture content by an electrical conductivity method, (6) 226*d*.
Bondarevskaya, E. A. See Lapteva, A. S.
Bondi, A. Physical Properties of Molecular Crystals, Liquids, and Glasses, B (6) 241*i*.
Bondley, R. J. Thermionic cathode, P (6) 224*d*.
Bones, R. J. See Markin, T. L.
Bonham, R. D. Claude Conover, (8) 273*i*. Jane Parshall and Denis Chasek, (7) 244*b*.
Bonin, E. L. See Biard, J. R.
Bonin, E. L., Pittman, G. E., and Reed, B. S. Semiconductor junction device for generating optical radiation, P (2) 66*f*.
Bonin, G. E. Pressure chuck, P (10) 339*i*.
Bonis, L. J., Duga, J. J., and Gilman, J. J. (editors). Fundamental Phenomena in the Materials Sciences (Vol. 4) Fracture of Metals, Polymers, and Glasses — Proceedings of the Fourth Symposium, Boston, January 1966, B (1) 41*d*.
Bonis, L. J., and Grierson, R. Method for the production of composite materials and articles produced thereby, P (11) 377*g*.
Bonn, R., Wegdam, G. H., and van der Elsken, J. Infrared absorption band forms of molten alkali-metal nitrates, (11) 385*h*.
Bonner, W. A. See Van Uitert, L. G.
Bonner, W. A., Geusic, J. E., and Van Uitert, L. G. Devices utilizing crystals of $Pb_2MgNb_2O_9$, P (10) 344*f*.
Bonner, W. A., and Van Uitert, L. G. Semiconducting niobate tantalate compositions, P (4) 116*a*.
Bonnier, E. See Balignat, N.; Recasens, J.
Bonsall, P. C., Dollimore, D., and Dollimore, J. Selective effect of adsorption on the strength of compacts of various oxides and salts, (2) 82*h*.
Bonse, U. K., Hart, M., and Newkirk, J. B. X-ray diffraction topography, B (1) 40*h*.
Booker, G. R., Shaw, A. M. B., Whelan, M. J., and Hirsch, P. B. Comments on the interpretation of the "Kikuchi-like reflection patterns" observed by scanning electron microscopy, (2) 75*d*.
Booker, J., and Stonehouse, A. J. Chemical conversion coatings retard corrosion of beryllium, (5) 171*c*.
Boon, G. C. Roman figure-cut vessel from Caerleon, (4) 90*f*.
Boone, J. S. See Richmond, J. F.
Booster, P., van Laar, K., Visser, R., and Waasdorp, A. High temperature cross bending and compressive strengths as criteria of the suitability of refractory materials, (4) 104*d*.
Borch, E. A. Role of abrasive analysis in keeping blast cleaning variables under control, (5) 169*h*.
Borchardt, H. J. Single crystals, P (7) 258*f*. Thoria/europium fluoride luminophors, P (2) 66*j*. Thoria/terbium fluoride luminophors, P (2) 66*j*.
Borchert, W. See Kroll, J. M.
Borcsik, M. See Gammon, J. R.
Borg, I. Y., and Smith, D. K. Calculated powder patterns (II) six potassium feldspars and barium feldspar, (10) 350*h*.
Borghese, C. Cation distributions in multisublattice ionic crystals and applications to solid solutions of ferrimagnetic garnets and spinels, (10) 350*c*. Temperature dependence of the cation distribution in ferrimagnetic spinels, (11) 387*j*.
Borgwardt, R. H. See Harrington, R. E.
Borg-Warner Corp. Materials having high corrosive resistance to attack by fluorine at cryogenic temperatures and method of preparing them, P (6) 217*d*.
Borisenko, A. I. Highly refractory anticorrosion coatings, (2) 45*j*.
Borisova, I. I., and Botvinkin, O. K. Physicochemical bases of the formation of a cobalt oxide coating on glass, (2) 50*a*.
Borns, J. Experiences with shrink foil packaging of brick veneer, (10) 340*c*.
Borodulenko, G. P. See Korshunov, B. G.
Borovkov, G. N. See Antonova, E. A.
Borrelli, N. F. Infrared spectra of SiO_2-GeO_2 glass, (8) 276*b*.
Borrello, S. R. See Cronin, G. R.
Borremee-Gautier, C., Giessen, B. C., and Grant, N. J. Metastable phases in the Pb-Sb and Pb-Bi systems, (4) 144*h*.
Borsook, P. A. See Liass, A. M.
Bortaud, P. See Recasens, J.
Bortz, S. A. See Acquaviva, S. J.
Borus, S., and Rev, E. Reliability of the determination of the plasticity index, (5) 187*j*.
Bos, W. G. See Abeles, T. P.
Bos, W. G., and Gutowsky, H. S. Magnetic properties and electronic structure of lanthanum hydrides, (4) 143*g*.
Bosacek, V. See Aristov, B. G.
Bosch, F. S. Spanish ceramic industry, (6) 240*d*.
Bosch, G. Photoconduction of *n*-type SiC, (9) 327*d*.
Bosch, Robert, G.m.b.H. Mercury vapor tube with special discharge chamber means separating mercury electrodes, P (2) 53*e*.
Boskovic, S. B., Gasic, M. C., Nilosic, V. S., and Ristic, M. M. Electroceramics having the cordierite structure, (2) 62*h*. Structural changes of the talc during heating, (2) 63*f*.

Boss, B. D., and Stejskal, E. O. Restricted anisotropic diffusion and anisotropic nuclear spin relaxation of protons in hydrated vermiculite crystals, (5) 199*c*.
Bossetti, A. Continuous tunnel kilns having a rotary roller sole for firing ceramic materials, P (10) 348*d*.
Boston, C. R., James, D. W., and Smith, G. P. Ultraviolet spectrum of the nitrate ion in molten mixtures of alkali metal nitrates, (5) 202*c*.
Bostroem, K., Frazer, J., and Blankenburg, J. Subsolidus phase relations and lattice constants in the system $BaSO_4$-$SrSO_4$-$PbSO_4$, (10) 361*e*.
Boswarva, I. M. Energy of formation of Schottky defects in cesium halides, (1) 29*f*.
Boswarva, I. M., and Lidiard, A. B. Energy of formation of Schottky defects in ionic crystals, (1) 29*g*.
Botha, J. C. See Henning, C. A. O.
Bott, G. S. Compact ampoule sealer, P (7) 248*d*.
Botterill, J. S. M. Progress in fluidization, (1) 20*g*.
Bottger, G. L., and Geddes, A. L. Infrared absorption spectrum of CdTe, (4) 140*g*.
Botvinkin, O. K. See Ananich, N. I.; Borisova, I. I.
Botvinkin, O. K., and Yaroker, Kh. G. Dependence on composition of certain properties of glasses in the system Na_2O-MgO-SiO_2 (I) glass formation; (II) density and index of refraction; (III) refraction of oxygen ion; (IV) electrical properties; (V) microhardness, (2) 47*a*.
Bouchard, G. H., Jr., Perlstein, J., and Sienko, M. J. Solid-state studies of potassium molybdenum bronzes, (11) 387*e*.
Bouchard, G. H., Jr., and Sienko, M. J. Magnetic susceptibility of barium molybdate(IV) and strontium molybdate(IV) in the range 2°–300°K, (11) 385*h*.
Bouchard, J. G. F. Transistors and method of manufacturing the same, P (5) 185*h*.
Bouchard, R. J. Preparation of pyrite solid solutions of the type $Fe_xCo_{1-x}S_2$, $Co_xNi_{1-x}S_2$, and $Cu_xNi_{1-x}S_2$, (7) 268*d*. Preparation of single crystals of FeS_2, CoS_2, and NiS_2 pyrites by chlorine transport, (6) 236*e*.
Bouchard, R. J., and Gillson, J. L. Hexagonal indium tungsten bronze, (11) 385*d*.
Boucher, E. A. See Bassett, D. R.
Boucraut, M., and Toth, I. Process and apparatus for pneumatically classifying pulverulent material, P (8) 288*d*.
Boudart, M. See Huang, Yun-Yang.
Bough, M. O., Jr. See Zappia, A. T.
Bougnot, G. See Nguyen Van Mau, A.
Bouillon, B. See d'Albis, A.
Boulet, P., and Polledri, J. Tunnel diode manufacturing apparatus, P (11) 379*b*.
Boundy, W. S. See Gray, N. B.
Bourbon, M. Simultaneous measurements of the viscosity and electrical resistivity of glass at temperatures in the melting and working range, (5) 173*b*.
Bourdeau, R. G. Metallic carbides and a process of producing the same, P (1) 14*f*.
Bourgeaux, M. See de Lajarte, S. D.; Peyches, P. I.
Bourggraff, R., and Hainke, G. Apparatus for manufacture of flat wire glass, P (10) 338*g*.
Bourne, D. J. See Atwood, G. E.
Bourns, Inc. Method of making a piezoelectric device, P (11) 377*e*.
Bouska, V. Original rock source of tektites, (5) 198*b*.
Boutin, H., and Yip, S. Molecular Spectroscopy with Neutrons, B (10) 364*j*.
Boux, J. F. Mississauga plant pioneers new fly ash process, (7) 244*a*.
Bovenkerk, H. P. Process for growing diamond on a diamond seed crystal, P (5) 186*f*.
Bovkun, G. A. See Artamonov, A. Ya.
Bowden, F. P., Brunton, J. H., Field, J. E., and Heyes, A. D. Controlled fracture of brittle solids and interruption of electrical current, (5) 180*f*.
Bowden, F. P., Fox, P. G., and Soria-Ruiz, J. Direct observation of thermal decomposition produced by fracture in brittle crystalline solids, (9) 320*c*.
Bowden, F. P., Greenwood, J. H., and Imai, M. Lubrication at high temperature of refractory solids, (1) 32*a*.
Bowen, G. Glass laminate and interlayer, P (7) 248*h*.
Bowen, J. D., Jr. Unusual structural material, P (9) 309*f*.
Bowen, R. M. Thermochemistry of reacting materials, (8) 300*g*.
Bowen, V. T. See Thompson, G.
Bowles, A. G. Automatically operating air vent for isostatic molding press [wet bag], P (9) 314*h*. Method [cutting] for the manufacture of brick and tile, P (11) 372*g*.
Bowling, K. McG., and Water, P. L. Fuel processing in fluidized beds, (1) 20*b*.
Bowman, A. L. See Helms, S. B.; Rabideau, S. W.
Bowman, D. See Kamath, G. S.
Bowman, D. L. See Keezer, R. C.
Bowman, M. G. See Hausner, H. H.
Bowman, R. A., and Pilloton, R. L. Method for preparing metal oxide microspheres, P (5) 179*e*.
Bowser, R. E. See Best, H. S.
Boyarskaya, Yu. S., and Val'kovskaya, M. I. Impression and scratching tests for the hardness anisotropy of crystals, (2) 70*a*.
Boyce, W. A. Lamp monogram and monogram ink, P (8) 277*d*.
Boyd, D. R. See Sihvonen, Y. T.
Boyer, A. J. G., Fray, D. J., and Meadowcroft, T. R. Surface tensions and molar volumes of the binary phosphates of sodium, lithium, calcium, and zinc, (4) 158*g*.
Boyer, C. B., and Orcutt, F. D. High pressure furnace, P (5) 189*d*.
Boyer, J. L. Compression bonded semiconductor device, P (4) 112*a*. Pressure assembled semiconductor device using massive flexibly mounted terminals, P (9) 313*c*.
Boyle, F. A. See Weldes, H. H.
Boyle, W. S., and Verleur, H. W. Radiant self-stabilization of temperature, (1) 35*f*.
Bozhevol'nov, E. A. Luminescent Analysis of Inorganic Substances, B (5) 203*j*.
BPB Industries, Ltd. Gypsum articles resistant to erosion by water and a method for their protection, P (4) 92*g*. Production of plaster of Paris, P (5) 170*f*.
Bracco, D. J. See Baczewski, A.
Bracken, A. T., Luhrs, M. E., and Green, C. F. Glass tank coolers, P (11) 371*j*.
Bracken, R. C. See Haberecht, R. R.
Bracken, R. C., Stroup, R. F., and Wakefield, G. F. Formation of carbide compounds by vapor deposition on graphite bodies, P (11) 374*i*.
Braddy, J. E., and Wiens, B. E. Method for surface treatment of glass articles, P (6) 213*f*.
Bradfield, W. S. See Aylos, D.
Bradford, A. P., Hass, G., McFarland, M., and Ritter, E. Effect of ultraviolet radiation on the optical properties of silicon oxide films, (1) 28*e*.
Bradhurst, D. H., and de Bruin, H. J. Self-diffusion of oxygen in beryllium oxide by proton activation of oxygen-18, (10) 360*e*.
Bradley, E. F., Bartlett, E. S., Ogden, H. R., and Jaffee, R. I. Method of forming Ti-modified silicide coatings on Nb-base substrates and resulting articles, P (8) 275*f*.
Bradley, F. N. Densification of ferric oxide and ferrites containing Bi_2O_3 additions, (10) 343*j*. $PbTi_2O_3F_2$, a new pyrochlore, (4) 148*j*.
Bradley, J. N., and Greene, P. D. Kinetics of solid-state reactions between iodides of silver, potassium, and rubidium, (4) 142*f*. Relation of structure and ionic mobility in solid MAg_4I_5, (5) 199*b*.
Bradley, R. See Wilks, R. S.
Bradley, W. F. See Towe, K. M.
Bradt, R. C., and Ansell, G. S. Aging in tetragonal ferroelectric barium titanate, (6) 220*e*.
Brady, E. R. See Goosey, M. H.
Brady, J. G. Ceramics in a changing world (I) glass, clay products, and ceramic-metal systems, (1) 40*e*.
Brady, L. E., Castle, J. W., and Hamilton, J. F. Epitaxial silver halide films, (8) 292*c*.
Braecher, L. Formation and prevention of efflorescence [on bricks and brickwork], (4) 101*j*.
Brafman, O., Chang, I. F., Lengyel, G., Mitra, S. S., and Carnall, E., Jr. Optical phonons in ZnS_xSe_{1-x} mixed crystals, (4) 147*j*.
Bragg, L. X-ray crystallography, (4) 121*a*.
Brailovskaya, R. V. Method of calculating the temperature-frequency change of the dielectric constant of simple silicate glasses, (2) 50*e*.
Brailsford, J. R., Morton, J. R., and Vannotti, L. E. Paramagnetic resonance spectra of O^- trapped in alkali iodide crystals, (8) 296*b*.
Braithwaite, E. R. W. Techniques in modern brickmaking—machinery, (10) 340*d*.
Brame, E. G., Jr. (editor). Applied Spectroscopy Reviews (Vol. 1), B (4) 165*a*.
Bramman, J. I. See Yates, G.
Bramman, J. I., Sharpe, R. M., Thom, D., and Yates, G. Metallic fission product inclusions in irradiated oxide fuels, (5) 197*b*.
Brammer, A. J. See Drabble, J. R.
Branca, F. P. New high-sensitivity quartz thermometer, (9) 315*a*.
Brandenburg, J. T. See Leak, R. J.
Brandmayr, R. J. Method of making a barium titanate body, P (6) 222*e*. Method of processing ferroelectric powders, P (10) 345*j*.
Brandmayr, R. J., and DiVita, S. Method of treating monolithic ceramic capacitors, P (5) 184*f*.
Brandt, B. G., and Skapski, A. C. Refinement of the crystal structure of molybdenum dioxide, (4) 153*f*.
Brandt, M. P. See Strasheim, A.
Bransky, I., and Tallan, N. M. High-temperature defect structure and electrical properties of NiO, (8) 293*c*.
Branson, D. L. Effect of particle size on the reaction rate constants in the formation of zinc aluminate spinel, (4) 133*d*.
Braslau, N. Semiconductor bulk effect microwave oscillator, P (6) 223*e*.
Brassart, F. A. See Gulbransen, E. A.
Brates, N., and Cloacs, E. Quick method of determining silicon in cast iron, steels, slags, and ferrosilicon, (1) 21*h*.
Bratton, R. J. Coprecipitates yielding $MgAl_2O_4$ spinel powders, (10) 340*j*. Defect structure of Y_2O_3-ZrO_2 solid solutions, (6) 231*d*. Initial sintering kinetics of $MgAl_2O_4$, (10) 355*h*.
Brauer, H., Fenner, E., and Kuschke, R. Ceramic bodies of ferroelectric material with perovskite structure which is partially *p*-conducting and partially *n*-conducting, P (7) 255*i*.
Braun, C., Delmas, R., and Francois, B. Method of making sintered nuclear fuel pellets in particular consisting of uranium dioxide, P (2) 59*c*.
Braun, L. O. See Collins, R. J.
Braunstein, J. Nonideality and association in binary mixtures of molten salts, (9) 325*h*.
Braunstein, M. See Zuleeg, R.
Bray, G., & Co., Ltd. Postaerated gas jets, P (7) 261*f*.
Bray, J. See Leger, L.
Bray, P. J. See Baugher, J. F.; Bishop, S. G.; Griscom, D. L.; Kim, Y. M.; Kline, D.; Kriz, H. M.; Marino, R. A.; Weeks, R. A.
Bray, R. See Spears, D. L.
Brazdziunas, P. See Kudaba, V.
Bre, M. M. See Deribere-Desgardes, M. L.
Brebner, J. L. See Mooser, E.
Brebrick, R. F. Si-Te system—partial pressures of Te_2 and SiTe and thermodynamic properties from optical density of the vapor phase, (8) 297*f*.
Brecher, C., Samelson, H., Riley, R., and Lempicki, A. Polarized spectra and crystal-field parameters of Eu^{3+} in YPO_4, (9) 327*i*.
Bred, L. See Preaux, L.
Bredsdorff, P., Poulsen, E., and Spohr, H. Experiments on mortar bars prepared with a representative sample of Danish aggregates, (4) 91*d*.
Breiter, M. W., and Vedder, W. Nature of anodic films on cadmium in alkaline electrolytes, (4) 145*g*.
Breitling, G., and Richter, H. Structure of amorphous arsenic and selenium according to the intensity curves, (10) 361*e*.
Brekhunets, A. G., Mank, V. V., Matiash, I. V., Ovcharenko, F. D., and Tarasevich, Yu. I. Proton magnetic resonance in a vermiculite single crystal, (6) 236*b*.
Bremner, P. R. See Porter, B.
Brenholz, G. See Maricic, A.
Brenner, S. S., and McVeagh, W. J. Field ion microscopy study of the formation of oxide particles on tungsten, (10) 353*c*.
Brenner, W. See Blank, Z.
Breske, C. D. Apparatus for inspecting a reflective surface which includes a projector of a pattern of lines having different thicknesses, P (7) 260*g*.
Bressat, R., De Calmes, A., Claudel, B., and Trambouze, Y. Mixed oxide of thorium and uranium monophased oxidation catalyst, P (11) 382*f*.
Brett, N. H. See Qureshi, M. H.
Brett, N. H., and Anderson, P. J. Mechanism of decomposition of brucite, (4) 143*h*.
Breuer, H., and Rehage, G. Thermodynamics of the glassy state, (4) 97*h*.
Brevetti C.E.A. S.p.A. Apparatus for checking of impurities, P (11) 370*i*.
Brewer, H. W. General relation of heat flow factors to the unit weight of concrete, (1) 2*e*.
Brewin, J. D. Method of bending sheet glass with gas pressure cushions, P (10) 339*j*.
Brezny, B. See Woermann, E.
Brice, J. C. Analysis of the temperature distribution in pulled crystals, (7) 263*i*. Kinetics of growth from solution, (5) 196*e*.
Brichard, E. Melting furnace for manufacturing flat glass, P (1) 11*b*. Process for homogenizing glass by gas injection, P (4) 100*h*.
Bridenbaugh, P. M. See Peterson, G. E.
Bridger, N. J. See Dell, R. M.
Brienza, M. J. See Clobes, A. R.
Bright, N. F. H. See Iwasaki, H.; Reeve, D. A.
Bril, A. See Blasse, G.; Wanmaker, W. L.
Bril, A., Blasse, G., and Bertens, J. A. A. Measurement of quantum efficiencies of Eu^{3+}-activated phosphors using excitation to selected Eu^{3+} levels, (5) 196*i*.
Bril, A., Wanmaker, W. L., and ter Vrugt, J. W. $Sr_2(PO_4)_2$-Tb, a bluish-white emitting cathode-ray phosphor with a long decay time, (5) 200*e*.
Brill, O. L., Weil, C. G., and Schmidt, P. W. Determination of particle-diameter distributions in silica and gold suspensions, (5) 193*b*.
Brinckmann, P. C. Sodium activated cesium iodide scintillator, P (8) 283*g*.
Brindle, J. H. See Eastwood, F.
Brindley, G. W. See Thompson, T. D.
Brindley, G. W., Achar, B. N. N., and Sharp, J. H. Kinetics and mechanism of dehydroxylation processes (II) temperature and vapor pressure dependence of dehydroxylation of serpentine, (4) 142*g*.
Brindley, G. W., and Gibbon, D. L. Kaolinite layer structure—relaxation by dehydroxylation, (5) 196*b*.
Brinen, J. S. See Hodgson, W. G.; Williams, E. F.
Briske, C., and Hartshorne, N. H. Linear rate of the polymorphic transformations of sulfur, (4) 142*i*.

Brisse, F., and Knop, O. Pyrochlores (III) X-ray, neutron, infrared, and dielectric studies of $A_2Sn_2O_7$ stannates, (2) 82*f*.
Bristol Siddeley Engines, Ltd. Method of producing refractory metal articles, P (8) 275*g*.
Bristow, T. J., Packer, M. E., and Gane, N. Surface layer fracture of brittle material by giant laser pulses, (10) 361*i*.
British Cast Iron Research Assn. Apparatus for milling foundry sand, P (5) 178*a*.
British Titan Products Co., Ltd. Oxides, P (7) 263*b*. Process and apparatus for milling, P (4) 125*h*. Process for producing metal oxide particles of reduced particle size, P (6) 230*d*. Production of pigmentary size titanium dioxide, P (6) 230*b*. Purification of pigments, P (8) 288*c*. [Sand] milling apparatus and process, P (10) 347*b*.
Brittain, J. O. See Buch, J. D.; Lautenschlager, E. P.
Brittan, K. W. Laminated transparent panels incorporating heating wires, P (7) 248*j*.
Brivati, J. A., Symons, M. C. R., Tinling, D. J. A., Wardale, H. W., and Williams, D. O. Electron spin resonance studies of the hydroxyl radical in γ-irradiated ice, (5) 194*d*.
Brixner, L. H. Fluorescence and cathodoluminescence of Eu^{3+} in some alkali and alkaline earths—yttrates and gadolinates as hosts, (4) 136*a*. Luminescent properties of some $CaMoO_4/LnVO_4$ systems, (1) 32*c*. Segregation coefficients of the rare earth niobates in $CaMoO_4$, (4) 154*c*. Rare earth silicate phosphor composition, P (1) 19*g*. Segregation coefficients of some rare earth niobates in $SrMoO_4$, (1) 36*j*.
Brixner, L. H., and Babcock, K. Inorganic single crystals from reactions in fused salts, (8) 293*d*.
Briyak, E., and Lesnyak, K. Methods of molding and sintering carbides, (2) 56*e*.
Brizes, W. F. Diffusion of carbon in tantalum carbides, (8) 290*g*.
Broadbent, D., Dollimore, D., and Dollimore, J. Thermal decomposition of oxalates (V) thermal decomposition of nickel oxalate dihydrate, (1) 39*a*; (IX) thermal decomposition of the oxalate complexes of iron, (4) 160*j*.
Broch, N. C. See Christensen, A. N.
Brockman, F. G. Method of controlling the atmosphere in preparing ferrites, P (4) 114*i*.
Brockway Glass Co., Inc. Rotary screen decorating machine, P (5) 176*a*.
Broder, J. See Mandelkorn, J.
Brodkina, E. R. See Fedorov, N. F.
Brodskii, Yu. A., and Pruslin, G. Sh. Influence of diamond wheel characteristics on spherical grinding of glass and sitall shapes, (2) 49*c*.
Broers, A. N. Holder for highly reactive cathodes of rare-earth borides such as lanthanum hexaboride, the holder provided with a cooling means opposite the emissive end of the cathode to reduce tendency of holder deterioration, P (11) 376*j*.
Broker, D. Bent glass—design and decoration, (2) 46*i*.
Brolde, K. See Genahr, R.
Bromer, H., and Meinert, N. Optical crown glasses, P (9) 308*d*.
Bromer, H., Meinert, N., and Ahl, D. Optical flint glasses, P (8) 278*d*.
Bron, V. A., and Diesperova, M. I. Kinetics of isothermal sintering of low-fired magnesium oxide obtained from crystalline magnesium carbonate, (5) 196*f*.
Bron, W. E. Pseudolocalized vibrations of M^{2+}-vacancy complex and thermal conductivity of alkali halides, (4) 151*d*.
Bronisz, S. E. See Douglass, D. L.
Bronnes, R. L., Hughes, R. C., and Sweet, R. C. Fusion bonding to nonmetals, P (4) 113*g*.
Bronnes, R. L., Sweet, R. C., and Hughes, R. C. Fluorine-resistant electrical terminal, P (4) 113*e*. Method of joining a semiconductor to a base, P (6) 222*c*.
Brook, R. J. Pore-grain boundary interactions and grain growth, (4) 150*e*. Pores and grain growth kinetics, (8) 296*a*.
Brooks, A. M. Coprecipitated $CaHPO_4{\cdot}2H_2O$ and $CaSO_4{\cdot}2H_2O$ pigment and method of preparation, P (8) 287*h*.
Brooks, C. S., DeCrescente, M. A., and Scola, D. A. Wetting of silicon carbide surfaces, (5) 203*e*.
Brooks, R. L. Growth and spectral characteristics of silver azide crystals, (5) 194*f*.
Brooks, W. V. F., Costain, C. C., and Porter, R. F. Microwave spectrum, molecular structure, and dipole moment of cyclic $H_3B_3O_3$, (4) 144*f*.
Broquet, C. See Vidal, J. P.
Broszkiewicz, R. B. See Adams, G. E.
Bretzmann, K. See Knueppel, H.
Broude, V. L., Soskin, M. S., Prokopyuk, N. F., Kravchenko, V. I., Belokrinitskii, N. S., and Manuil'skii, A. D. Shape and internal structure of the luminescence band of neodymium in solid bodies, (4) 154*g*.
Broutman, L. J., and Krock, R. H. (editors). Modern Composite Materials, B (7) 272*e*.
Browder, J. S. See Ballard, S. S.
Brower, W. S., and Fang, P. H. Dielectric constants of $PbMoO_4$ and $CaMoO_4$, (4) 131*a*.
Brown, A. R. Nonglare sealed beam headlights, P (6) 213*g*.
Brown, A. S., Joyce, B. A., Neave, J. H., and Stirland, D. J. Epitaxy of silicon on quartz, (9) 310*d*.
Brown, C. A. See Brown, R. A.
Brown, C. E. New talc deposit in St. Lawrence County, N. Y., (8) 286*h*.
Brown, D. Halides of the Lanthanides and Actinides, B (11) 389*e*. See Bagnall, K. W.
Brown, D., and Douglas, R. W. "Carbon-Sulfur" amber glass—correction, (11) 369*i*.
Brown, D. J., Sly, F. A. W., and Arthur, G. Effect of oxide impurities on the electrical resistivity of La-doped $BaTiO_3$, (2) 62*d*.
Brown, D. M. Protection means for surface semiconductor devices having thin oxide films therein, P (11) 378*a*.
Brown, D. M., Engeler, W. E., Garfinkel, M., and Gray, P. V. Self-registered molybdenum-gate MOSFET, (5) 182*b*.
Brown, D. M., Gray, P. V., Heumann, F. K., Philipp, H. R., and Taft, E. A. Properties of $Si_xO_yN_z$ films on Si, (4) 151*h*.
Brown, G. See Gastuche, M. C.
Brown, G., and Gastuche, M. C. Mixed magnesium-aluminum hydroxides (II) structure and structural chemistry of synthetic hydroxycarbonates and related minerals and compounds, (9) 325*b*.
Brown, G. A., Robinette, W. C., Jr., and Carlson, H. G. Electrical characteristics of silicon nitride films prepared by silane-ammonia reaction, (5) 180*j*.
Brown, H. See Ballman, A. A.
Brown, H. J. See Gutzeit, C. L.
Brown, J. J. Manganese-activated luminescence in the $MgO\text{-}Al_2O_3\text{-}Ga_2O_3$ system, (4) 143*c*. See Herbert, W. C.
Brown, J. J., Jr. Fluorescent manganese activated magnesium digallate phosphor composition, P (2) 64*g*. Fluorescent manganese activated magnesium gallate phosphor and lamp, P (2) 64*h*. See Haynes, J. W.
Brown, L. H., Stigger, E. K., and Watson, D. D. Alkaline refractory mixtures containing formaldehyde-furylethylenealdehyde resins and gunning therewith, P (2) 58*j*.
Brown, M. G. Preparation of calcium sulfate alpha-hemihydrate slurries for casting in molds, P (6) 207*c*.
Brown, M. L., and Remington, W. J. Polyurea bonded sand foundry cores, P (10) 343*a*.
Brown, R. A. Particle size and morphology of zinc sulfide (I) influence of precipitating conditions, (4) 148*f*.
Brown, R. A., and Brown, C. A. Method of making investment shell molds for the high integrity precision casting of reactive and refractory metals, P (5) 179*a*.
Brown, W. B. See Lonadier, F. D.
Brown, W. E. See Moreno, E. C.
Brown, Boveri & Cie Akt.-Ges. Controllable semiconductor element, P (6) 221*f*, P (7) 256*c*. Fuel battery with stabilized zirconium oxide electrolyte, P (6) 217*j*. Induction crucible furnace comprising a rammed crucible, P (10) 348*e*. Process [diffusion] for making a semiconductor element, P (9) 313*d*. S.C.R. with emitter electrode spaced from semiconductor edge equal to 10 times base thickness, P (9) 313*g*. Semiconductor elements with disturbed crystalline surface structure in a junction area, P (8) 283*f*. Semiconductor rectifier structure having semiconductor element assembly screwed into place on support base, P (10) 346*d*.
Brown Boveri/Krupp Reaktorbau G.m.b.H. Sorting apparatus for spherical bodies, P (7) 253*a*.
Brownell, G. L. See Fitzgerald, J. J.
Browning, J. S. See Adair, R. B.
Brownmiller, L. T. See Hersey, A. T.
Broyde, B. Lanthanum and yttrium tungsten bronzes, (11) 385*c*.
Broyles, J. E., and Olsen, C. W. Finishing ball tracks—a complete abrasive process, (5) 169*g*.
Bruce, B. D., and Thompsen, R. S. Determining effective coverage of protective coatings, (7) 245*h*.
Bruce, D., and Hancock, P. Influence of mechanical properties of surface oxide films on oxidation mechanisms (I) vibrational technique to study the nature and growth of thermally formed [iron and nickel] oxide films on metals; (II) mechanical properties and adhesion of surface oxide films in iron and nickel measured during growth, (10) 355*a*.
Bruce, S. K., Jr. Automating the decorating operation, (1) 5*i*.
Bruch, C. A. Problems in die-pressing submicron size alumina powder, (4) 118*a*.
Brueckner, R. Basic mechanism of interfacial convection leading to erosion of model substances and refractory materials, (9) 305*a*. Peculiarities of accelerated vertical corrosion ("upward drilling"), (9) 306*d*. See Dietzel, A.
Bruegger, W., and Hitz, E. Induction crucible furnace comprising a rammed crucible, P (10) 348*e*.
Bruel, N. See Jorgensen, M. H.
Brueschke, E. E. Scanning densitometer for thermal profile analysis, P (2) 72*a*.
Bruet, M. See Kingery, W. D.
Brugger, R. M. See Worlton, T. G.
Brukl, C. E. See Rudy, E.
Brumage, W. H., and Mahoney, J. P. Magnetic susceptibilities of trivalent europium in yttrium gallium garnet, (6) 234*h*.
Brumberger, H., and Alexandropoulos, N. G. High-temperature sample cell for the Kratky small-angle X-ray camera, (9) 315*g*.
Brumley, C. H., and Ferris, J. T. Optical fiber bundle coupling system, P (10) 339*g*.
Brumm, G. Gas-filled overvoltage arrester for telecommunication installations, P (9) 307*e*.
Brunauer, S. See Mikhail, R. Sh.
Brunauer, S., Mikhail, R. Sh., and Bodor, E. E. Pore structure analysis without a pore shape model, (1) 35*c*.
Brune, D., and Jirlow, K. Determination of oxygen in aluminum by means of 14 MeV neutrons with an account of flux attenuation in the sample, (6) 225*h*.
Brunie, S., and Chevreton, M. Structural study of Ti_2Te_3, (5) 200*h*.
Brunner, G. O. See Bambauer, H. U.
Brunner, H. R., Emmenegger, F. P., Robinson, M. L. A., and Roetschi, H. Growth and properties of Nb_2O_5 thin film capacitors, (5) 181*f*.
Bruns, R., Smith, Don, and Devlin, J. P. Photo-induced reactions in solid carbon suboxide, (4) 149*h*.
Brunswick Corp. Resistor unit and method of making same, P (7) 257*i*.
Brunton, J. H. See Bowden, F. P.
Bruss, H. G., Jr., Schlientz, W. J., and Wiens, B. E. Abrasion resistant glass article and method for producing same, P (8) 277*d*. Method of rendering glass surfaces abrasive-resistant and article produced, P (4) 100*g*.
Brustik, J. Mechanical polishing of glass by PVC polishers, (10) 338*b*.
Brutskus, T. K. See Segalova, E. E.
Bryant, C. R. Prefabricated masonry fireplace [fireplace], P (11) 375*a*.
Bryant, M. W. R. See Blake, W. E.
Bryantsev, B. A. Apparatus for measuring the melting point of silicates in inert atmospheres, (2) 68*j*.
Brydon, J. E., and Singh, S. S. Nature of the synthetic crystalline basic aluminum sulfates as compared with basaluminite, (9) 316*h*.
Bryon, J. F. Yield and flow of single crystals of uranium dioxide, (9) 333*a*.
Brzozowski, W., Mikos, M., and Niewiadomski, J. Method of and means for heat-treating refractory materials at high temperatures, P (9) 314*h*.
BTU Engineering Corp. Conditioned atmosphere furnace muffle, P (4) 122*j*.
Bubar, S. F., and Vermilyea, D. A. Deformation of anodic oxide films, (2) 75*c*.
Bubik, I. Electronic ceramic materials, (1) 16*d*. See Moldvai, R.
Bublitz, A. T. See Argyle, L. C.
Bucci, C., Fieschi, R., and Guidi, G. Ionic thermocurrents in dielectrics, (2) 79*h*.
Bucci, F. See Tasca, A.
Buch, J. D., Carnahan, R. D., and Brittain, J. O. Improved internal friction apparatus, (9) 315*h*.
Buchanan, B. L. See Dolan, R. P., Jr.
Buchner, E. See Fitzer, E.
Buchowiecki, J., and Cherry, R. D. Thorium, radium, and potassium in Mn nodules, (4) 124*d*.
Buchsbaum, S. J., McFee, J. H., and Tien, P. K. Second harmonic semiconductor modulators for coherent radiation, P (10) 345*j*.
Buck, R. H. See Martin, A. J.
Buck, R. H., Jr. Process for making permanently backed shell molds, P (8) 279*j*.
Buck, T. M., Allen, F. G., Dalton, J. V., and Struthers, J. D. Studies of sodium in SiO_2 films by neutron activation and radiotracer techniques, (4) 157*b*.
Buck, T. M., and Dalton, J. V. Electron beam charge storage device employing diode array and establishing an impurity gradient to reduce the surface recombination velocity in a region of electron-hole pair production, P (11) 376*d*.
Buckle, E. R. See Baker, C. G. J.
Buckley, E. A. See Loukes, D. G.
Buckley, J. D. Static oxidation and compatibility of boron nitride and boron nitride composite to 2000°C, (8) 279*h*.
Bucko, E. P. Crate for shipping glass [panels] and like frangible materials, P (2) 52*e*.
Buckup, H. Problem of works medicine relating to the combating of dust, (6) 224*j*.
Budd, S. M. Process for strengthening glass containers, P (9) 308*c*.
Budesinsky, B., Vrzalova, D., and Bezdekova, A. Spectrophotometric determination of barium and strontium by means of dimethylsulfonazo-III and related compounds, (5) 188*g*.
Bud'ko, I. A. See Kukui, A. L.
Budnikov, P. P., and Ginstling, A. M. Principles of Solid State Chemistry, B (11) 390*f*.
Budnikov, P. P., and Kerbe, F. Thermodynamics of thermal decomposition of aluminum sulfate, (4) 162*b*.
Budnikov, P. P., Kerbe, F., and Kostyukov, N. S. Influence of thermal neutron radiation on certain electrical properties of pure alumina ceramics, (2) 63*a*.
Budnikov, P. P., and Kharitonov, F. Ya. Production of compact shapes from pure oxides by hot-pressing and their properties, (2) 67*j*. Production of complicated shapes by hot-pressing of alumina, (11) 379*h*.
Budnikov, P. P., and Krolchuk, L. A. Materials for hydrothermal hardening of cements, (2) 44*g*.

Budnikov, P. P., Matveev, M. A., Yanovskii, V. K., and Kharitonov, F. Ya. Sintering of highly pure magnesium oxide with additives, (8) 297*e*.

Budnikov, P. P., and Nekhoroshev, A. V. Solid-phase reactions with the participation of "carriers" in the transfer of volatile compounds of the starting compounds, (8) 297*g*.

Budnikov, P. P., Shishkov, N. V., and Shubina, N. V. Development of composite materials based on oxides and metals, (2) 55*a*.

Budnikov, P. P., Shubin, V. I., and Lepeshova, V. I. Nature of adhesion between basic refractories and portland cement clinker, (1) 12*d*.

Budnikov, P. P., Zlochevskaya, K. M., and Matveev, M. A. Study of phase transformations in firing of spinel-mullite mixtures and charges of cordierite and sapphirine, (6) 238*f*.

Budova, G. P., and Voskresenskava, N. K. Solubility of niobium pentoxide in melts of the fluoride salts of lithium, sodium, and potassium, (7) 269*b*.

Budworth, D. W. Comments on "Observations on 'pressure sintering of NaCl and other ionic materials'," (1) 26*h*. See Haroun, N. A.

Budzich, T. Material pulverization, P (6) 229*g*.

Buechler, A. See Blackburn, P. E.

Buechler, A., and Berkowitz-Mattuck, J. B. Gaseous ternary compounds of the alkali metals, B (4) 165*d*.

Buehler, W. J. See Goldstein, D.

Buenzen, K. Water solubility of porcelain enameled ware, (10) 337*c*.

Buessem, W. R. Electroceramics move ahead, (1) 16*c*. See Chung, D. H.; Goswami, A. K.

Buettner, K., Richter, H., and Voeller, H. Method and apparatus for compacting magnetic powder, P (1) 18*a*.

Buettner, K. H. See Richter, H.

Bugenis, C. K. See Toothacker, W. S.

Bugosh, J., and Hoffman, L. C. Composite vitreous enamels and their preparation, P (8) 275*c*.

Builders Equipment Co. Brick stacking machine, P (2) 54*e*.

Bulst, D. S., Highfield, A., and Pressley, H. Modulus of rupture as an index of potential refractory performance in service, (10) 341*e*.

Bujor, I. See Rosu, D. P.

Bukhalova, G. A. See Babaeva, E. P.; Litvinova, G. N.; Mateiko, Z. A.; Sementsova, D. V.

Bukhalova, G. A., and Babaeva, E. P. System Li,Cs,Sr‖Cl, (8) 299*e*. System $Li^+,K^+,Sr^{2+}‖Y^{3+}‖F^-$, (4) 159*d*.

Bukhalova, G. A., and Burinkova, V. M. System Li,Cs,Sr‖Cl, (8) 299*e*. System $Li^+,K^+,Sr^{2+}‖Cl^-$, (4) 159*b*.

Bukhalova, G. A., and Mal'tsev, V. T. Volumetric relations in binary systems made up of fusible salts of the type Me_3AlF_6, (4) 163*i*.

Bukhalova, G. A., and Mardirosova, I. V. Phase diagrams of the binary systems of the fluorides and metaphosphates of sodium and potassium, (4) 149*c*. System $Na^+,K^+‖PO_3^-,F^-$, (4) 159*c*.

Bukhalova, G. A., and Sementsova, D. V. System $Na^+,K^+,Ca^{2+}‖F^-$, (9) 331*d*.

Bulavin, I. A. New methods of forming ceramic objects, (2) 60*i*.

Bull & Roberts, Inc. Compact radiation detector with superimposed filter, phosphor, glass, and photosensitive layers, P (5) 182*a*.

Bullock, C. L. Tongs, P (10) 340*a*.

Bullough, R. See Eyre, B. L.

Bulthuis, K. Effect of high uniaxial pressure along the main crystallographic axes of Si and C, (9) 320*h*.

Bumm, H., Thuemmler, F., and Weimar, P. Isostatic hot-pressing, a new densification method in powder metallurgy, (4) 117*g*.

Bunce, J. L. See Lapage, R.

Bunchuk, L. B. See Ni, L. P.

Bundy, A. J., and Williams, J. L. Glass case [sheet container], P (9) 307*f*.

Bunge, K. See Vinzelberg, B.

Bunker-Ramo Corp. Method of making a thin film circuit having a resistor-conductor pattern, P (5) 183*i*. Thin film capacitor and method of adjusting the capacitance thereof, P (1) 19*g*. Thin-film resistor adjustment, P (11) 379*a*.

Bunting, J. A., and Bieler, B. H. Batch-free time versus crucible volume in glass melting, (10) 337*g*.

Bur, T. R. Transformations of the elastic constants for anisotropic media by successive simple rotations, (8) 286*a*.

Burd, J. W. Multiwafer growth system for the epitaxial deposition of GaAs and $GaAs_{1-x}P_x$, (9) 311*b*. See Rossi, J. A.

Burewicz, A. See Wolski, W.

Burge, R. W. See Thomas, P. M.

Burgess, C. A. Method of preparing a cermet nuclear fuel, P (2) 59*f*.

Burgess, N. S., Jr., and de Lisse, C. W. Temperature sensor probe, P (9) 316*a*.

Burggraaf, A. J., and Van Velzen, H. C. Glasses resistant to sodium vapor at temperatures to 700°C, (7) 247*c*.

Burgiel, J. C., Chen, Y. S., Vratny, F., and Smolinsky, G. Refractive indices of ZnO, ZnS, and several thin-film insulators, (10) 359*h*.

Burgman, J. A., and Margason, L. L. Method and apparatus for producing an intermittently hollow glass filament, P (5) 175*b*.

Burke, J. E. (editor). Progress in Ceramic Science (Vol. IV), B (7) 272*g*.

Burke, J. J., Reed, N. L., and Weiss, V. (editors). Surfaces and Interfaces (Vol. I) Chemical and Physical Characteristics; (Vol. II) Physical and Mechanical Properties, B (10) 366*d*.

Burke, M. F., Moreland, A. K., and Rogers, L. B. Surface area studies in pretreated silica gels, (10) 361*h*.

Burke, W. E., and Hinds, L. S. X-ray spectrography sample holder containing an adjustably mounted internal reference standard, P (11) 381*e*.

Burkhardt, P. J. Tracer evaluation of hydrogen in steam-grown SiO_2 films, (4) 162*a*.

Burlakova, V. M. See Bukhalova, G. A.

Burley, R. A. Infrared spectrum and structure of selenium dioxide, (2) 79*c*.

Burlington Industries, Inc. Process for dulling glass fibers with oxalic acid including pretreatment with calcium salts, P (2) 54*a*. Process for treating glass fabric, P (5) 176*e*.

Burmeister, R. A., Jr., Pighini, G. P., and Greene, P. E. Large area epitaxial growth of $GaAs_{1-x}P_x$ for display applications, (9) 310*g*.

Burmeister, R. A., Jr., and Regehr, R. W. Epitaxial growth of $GaAs_{1-x}P_x$ on germanium substrates, (9) 310*b*.

Burmeister, R. A., Jr., and Stevenson, D. A. Phase equilibria in the Cd-Se system, (4) 149*d*.

Burnham, D. A., and Eyring, L. Phase transformations in the praseodymium oxide-oxygen system—high-temperature X-ray diffraction studies, (10) 358*d*.

Burnham, D. A., Eyring, L., and Kordis, J. High-temperature X-ray diffraction studies of the terbium oxide-oxygen and mixed cerium terbium oxide-oxygen systems, (10) 355*d*.

Burns, G. See Giess, E. A.; O'Kane, D. F.; Scott, B. A.

Burns, R. E., Phillips, J. F., and Schulz, W. W. Method of dissolving aluminum-clad thoria target elements, P (2) 59*a*.

Burns, R. G. See Bancroft, G. M.

Burroughs Corp. Method for adjusting thin film resistors, P (6) 222*b*.

Burrus, H. L., and Paulusz, A. G. Luminescence of Eu^{3+} activated thorium, alkali metal vanadates, (10) 356*d*.

Burstein, E. See Anastassakis, E.

Burstein, E., and Lundqvist, S. (editors). Tunneling Phenomena in Solids—Lectures Presented at the 1967 NATO Advanced Study Institute at Riso, Denmark, B (11) 390*d*.

Burton, J. Glass: Hand-Blown, Sculptured, Colored——Philosophy and Method, B (6) 241*b*.

Burykina, A. L. Zirconium carbide and niobium carbide coatings on niobium, tantalum, molybdenum, and tungsten, B (5) 204*f*.

Busby, T. S., and Carter, M. Effect of temperature cycling, in oxidizing and reducing atmospheres, on the structure of basic bricks, (6) 215*f*.

Buschmann, H. See Golde, K. H.

Busdiecker, R. A. Method for sealing glass to metal and seal produced thereby, P (2) 66*b*. Solder glass compositions and method of sealing metal therewith, P (10) 340*b*.

Busen, K. M. See Tsang, Wei K.

Busen, K. M., Lindmayer, J., Schneider, W. C., and Tsang, Wei K. *Lh* junction lateral transistor, P (8) 282*b*.

Busker, L. H. Microwave moisture measurement, (5) 187*d*.

Busiaev, F. P. See Yarosh, P. Ya.

Busson, N. See Asquiedge, M.; Guillou, M.

Butcher, J. W., and Samuel, R. L. Hot-pressing of metal powders having inert solid surface films by adding activator elements, P (2) 68*b*.

Butler, G. P. Modern evaporite deposition and geochemistry of coexisting brines, The Sabkha, Trucial Coast, Arabian Gulf, (8) 286*h*.

Butler, J. F., and Harman, T. C. Long-wavelength infrared $Pb_{1-x}Sn_xTe$ diode lasers, (4) 142*j*.

Butler, J. M. See Nielsen, M. L.

Butler, M. B. N. See Sandbank, C. P.

Butler, P., Jr. Mineral compositions and equilibria in the metamorphosed iron formation of the Gagnon Region, Quebec, Canada, (7) 262*f*.

Butt, Yu. M., and Timashev, V. V. Effect of additives on the crystallization of alite and belite in portland cement clinkers, (1) 2*g*. High-strength cements—their production and properties, (2) 44*d*.

Butt, Yu. M., Timashev, V. V., and Paramonova, V. A. Influence of reducing medium on stability and hydration activity of calcium aluminoferrites, (1) 3*a*.

Butterworth, B. Ceramic building materials, (6) 213*j*. (9) 308*g*.

Buttgereit, C. See Routschka, G.

Buttress, G. D., and Hughes, M. A. Thermal decomposition of uranium(IV) and uranyl(VI) formates, (5) 201*d*. Thermal decomposition of uranyl(VI) oxalate, (5) 201*e*.

Buttyan, J. See Cochardt, A. W.

Butyleva, E. S. Production of sanitary ware with low porosity, (11) 375*i*.

Buyers, W. J. L., and Smith, T. X-ray study of lattice dynamics of sodium chloride, (4) 164*b*.

Buykx, W. J. See Reeve, K. D.

Bye, G. C. See Aldcroft, D.

Bye, G. C., Robinson, J. G., and Sing, K. S. W. Characterization of aluminum hydroxide gels by nitrogen adsorption, (8) 289*d*.

Byer, N. E., and Sack, H. S. Symmetry of paraelectric defects in alkali halides, (2) 83*d*.

Byers, G. L. Cement market—how will the pendulum swing? (7) 244*h*.

Bynum, S. A. Photoconductive layer separated from reactive opaque pattern by transparent conductive layer, P (4) 115*e*.

Byrd, T. E. Semiconductor controlled rectifier device, P (6) 223*f*.

Byron, J. F. Yield and flow of polycrystalline uranium dioxide, (10) 363*g*.

Byrup, J. Denmark—a leader in brick panels, (6) 214*a*.

Bystrikov, A. S. See Tumanov, S. G.

Bystrikov, A. S., and Grum-Grzhimailo, O. S. Complex study of mineral composition of clays, (11) 379*j*.

Bystrikov, A. S., and Petrov, Yu. F. Synthesis of chromium garnet-type pigments, (6) 219*f*.

Bystrova, O. N. See Denisova, N. D.

Cable, M. See Akhtar, S.

Cable, M., Clarke, A. R., and Haroon, M. A. Effect of arsenic on the composition of the gas in seed during the refining of glass, (7) 247*d*. Influence of size of melt on the refining of a glass, (2) 49*f*.

Cable, S. J. See Feichter, H. R.

Cabot Corp. Method of producing extremely finely divided oxides, P (2) 74*f*. Process for halogenating molten metals, P (1) 24*a*. Process for the production of titanium dioxide, P (10) 349*d*.

Cabrera, J. G. See Smalley, I. J.

Cabri, L. J. Density determinations—accuracy and application to sphalerite stoichiometry, (10) 347*c*. See Keys, J. D.

Cadenhead, D. A., and Everett, D. H. Sintering of porous glass—benzene adsorption by heat-treated porous glasses, (5) 173*c*.

Cadoret, R., and Monier, J. C. Growth of noncentrosymmetric crystals in a polar direction—role of superficial polarization, (4) 138*a*.

Cady, P. D. See Larson, T. D.

Cady, W. G. Piezoelectric transducer, P (7) 257*f*.

Cafferata, G. W. Gypsum articles resistant to erosion by water and a method for their production, P (4) 92*g*. Production of plaster of Paris, P (5) 170*j*.

Caffyn, J. E., Goodfellow, T. L., and Hamdani, A. J. Experiments on deformation and charge flow in KCl, (8) 292*e*.

Cagnina, S. F., and Snow, E. H. Properties of gold doped MOS structures, (4) 151*f*.

Cahen, R., and Driffort, J. P. Method of sealing frustoconical lead-through elements, P (4) 100*i*.

Cahen, R. R. See de France, H.

Cahn, J. W. Metastable liquidus and its effect on the crystallization of glass, (6) 210*c*. Spinodal decomposition, (1) 37*h*.

Caillat, R. See Paidossi, J.

Caillet, M., Deportes, C., Robert, G., Vallier, G., and Vitter, G. High-temperature structure and electrical conductivity in the ZrO_2-Y_2O_3-Ta_2O_5 system, (5) 195*g*.

Caillet, M., Deportes, C., Robert, G., and Vitter, G. Structural study of the system HfO_2-Y_2O_3, (1) 38*e*.

Cain, O. J. Plastic substrates for thin film electronic devices, (8) 281*d*.

Cairns, R. E. Adhered windshield with concealed adherent, P (5) 174*e*.

Caldwell, C. W., and Liebler, C. F. Universal motion device for use in ultrahigh vacuum, (2) 71*j*.

Caldwell, V. E. See Vassamillet, L. F.

Callen, E. Magnetic properties of magnetite, (4) 143*h*.

Caloric Corp. Radiant burner, P (7) 261*g*.

Calow, C. A. Processes for producing fiber-reinforced materials, P (9) 309*c*.

Calvert, S. E. See Ernst, W. G.

Calvo, C. Crystallographic character of the $Sr_{2-x}Mg_xP_2O$ system, (10) 351*f*. See Datars, W. R.

Calvo, C., Leung, K. Y., and Stager, C. V. Electron spin resonance of Mn^{2+} in α-$Sr_2P_2O_7$, (9) 321*i*.

Camerman, C. See Corneanu, A.; Dragoman, I.

Cameron, A. See Giles, C. H.

Cameron, E. M., and Horton, R. E. Analysis of rocks using a multichannel emission spectrometer, (1) 20*i*.

Cameron, N. M. Effect of environment and temperature on the strength of E-glass fibers (II) heating and aging, (4) 95*c*.

Cameron, N. M., and Neely, H. E. Effect of batch carbon on the strength of E-glass fibers, (11) 369*e*.

Camilbel, I. See Wemple, S. H.

Camm, W. T. Rotary dryer for aggregate, P (2) 72*g*.

Camozzo, G., Coenen, F., Francesconi, A., Goossens, W., Pierini, G., Schmets, J. J., and Stynen, A. Method of processing nuclear fuel by selective ClF fluorination [illegible] separation of UF_6 and PuF_4, P (6) 218*g*.

Camozzo, G., Coenen, F., Francesconi, A., Pierini, G., Schmets, J. J., and Stynen, A. Method of fluorinating nuclear fuels and recovery of plutonium tetrafluoride and uranium hexafluoride, P (6) 217*g*.

Camp, F. E. See Hirayama, C.

Camp, P. R. Method for producing predetermined crystal structures, P (10) 347*a*.

Campbell, D. E., and Adams, P. B. Evaluation of the problem of the chemical analysis of trace coloring oxides in optical glasses, (8) 276*g*.

Campbell, D. R., Fallos, G., and Zine, A. R., Jr. [Glass] pipe coupling, P (4) 99*b*.
Campbell, D. S. See Harrop, P. J.; Morley, A. R.; Ridge, C. J.
Campbell, F., Jr. Composite refractory lining for basic oxygen furnace, P (4) 106*b*.
Campbell, F. E., and Roeder, P. Stability of olivine and pyroxene in the Ni-Mg-Si-O system, (7) 269*f*.
Campbell, I. E., and Sherwood, E. M. (editors). High-Temperature Materials and Technology, B (1) 41*h*.
Campbell, J. H., and Kershaw, D. D. Low pressure electric discharge lamp electrode, P (9) 312*f*.
Campbell, J. K., and Clark, H. A. Aminoalkyl silicone glass [fiber] lubricant, P (11) 370*h*.
Campbell, R. B., and Chu, T. L. Epitaxial growth of silicon carbide by the thermal reduction technique, (1) 29*h*.
Campbell, W. B. Method for controlling the feed of nuclei in the production of crystals by vapor deposition, P (4) 114*a*.
Campbell, W. B., and Kingery, W. D. Preparation of alumina crystals from a vapor phase reaction by monitoring the spectral scattering of light, P (9) 317*a*.
Campbell, W. B., and Schaffer, P. S. Epitaxially coating ruby with doped alumina, P (9) 312*g*.
Campbell, W. W., and Leatham, E. Process for the production of caustic calcined magnesia, P (6) 230*a*.
Canadian Patents & Development, Ltd. Production of amorphous ferric oxide, P (4) 125*d*. Recovery of high purity magnesium oxide and calcium oxide from magnesite and calcite ores, P (4) 125*h*.
Candela, G. A. See Frederikse, H. P. R.
Canfield, S. A. Method and means for strand dispersal, P (4) 100*c*.
Cannon, R. W. Proportioning fly ash concrete mixes for strength and economy, (2) 45*d*.
Canrad Precision Industries, Inc. Zinc sulfide phosphor, P (7) 258*f*.
Cansa, G. See Cavalern, A.
Cantor, S. See Moynihan, C. T.
Cantor, S., Ward, W. T., and Moynihan, C. T. Viscosity and density in molten BeF_2-LiF solutions, (10) 338*d*.
Capalbi, A. See Balducci, G.; De Maria, G.
Cape, A. T. Method of spray coating gas seals of gas turbines and the like, P (7) 246*h*. Powder spray torch, P (7) 246*h*.
Capek, R. G. See Melkeraaen, T. O.
Capella, L. See Heyraud, J. C.
Capes, C. E. See Coleman, R. D.
Canio, C. D. See Levinstein, H. J.
Capita, E. R. Vapor plating apparatus including rotatable substrate support, P (2) 67*a*.
Capitonova, T. A. See Perrault, G.
Caplan, F. Nomograph gives radiant coefficient of heat transfer, (6) 228*d*.
Caplan, P. J. See Theissing, H. H.
Caporaso, A. J. See Kolb, E. D.
Capotosto, A. See Petrocelli, A. W.
Capp, A. C. See Taylor, S. R.
Carbajal, H. Contact microradiography with filtered X-ray spectra, (5) 187*c*.
Carborundum Co. Abrasive belts and method of making same, P (6) 205*g*. Abrasive cut-off wheels, P (4) 89*g*. Barrel finishing media, P (6) 205*h*. Boron nitride fiber manufacture, P (6) 217*h*. Electric furnace having replaceable liner tube sections, P (5) 189*a*. Method of stabilizing resistance in semiconductor manufacture, P (8) 283*e*. Nozzle having interior guide, P (4) 100*d*. Process for producing reinforced carbon and graphite bodies, P (11) 375*b*. Process for producing silicon carbide articles employing pyromellitic dianhydride-limonene dioxide mixture, P (11) 375*b*. Rocking electric tube furnace, P (4) 123*b*. Vibratory molding apparatus, P (11) 375*d*.
Cardone, V. P. Glare reduced light ray screen, P (1) 10*c*.
Cardwell, J. G., Jr. Filament mount structure for electric lamps [fused SiO_2] and manufacture thereof, P (7) 248*g*. Filament support for incandescent electric lamps, P (7) 248*g*. Single-ended electric incandescent lamp filament support, P (1) 19*i*.
Caresara, S. See Federighi, T.
Carini, G. F. See Davies, B.
Carini, R. V. See Agett, A. H.
Carl, D. G. Banding machine, P (10) 338*h*.
Carl Zeiss-Stiftung (trading as Carl Zeiss). Lightweight optical mirror for astronomical equipment, P (10) 339*h*.
Carles-Gibergues, A. See Aitcin, P. C.
Carlson, E. H. Growth of HgS and $Hg_3S_2Cl_2$ single crystals by a vapor phase method, (5) 194*e*.
Carlson, H. G. See Brown, G. A.
Carlson, K. D., and Claydon, C. R. Electronic structure of molecules of high temperature interest, B (4) 165*f*.
Carlson, O. N., and Paulson, W. M. Yttrium-carbon system, (4) 164*b*.
Carlson, R. C., Jr. See Anderson, A. R.
Carlson, R. J., and Simons, C. C. Electric resistance heater and method of making, P (2) 58*b*.
Carlson, R. V. See Kerr, J. M.
Carlson, W. J. Cathode sputtering apparatus for producing plural coatings in a confined high frequency generated discharge, P (5) 182*h*.
Carlson Tool & Machine Co. Abrasive device for finishing paint brushes, P (4) 89*h*.
Carman, C. J., and Kroenke, W. J. Electron spin resonance of α-chromia-alumina solid solutions, (8) 291*h*.
Carmi, A. See Belentepe, Y. C.
Carmichael, R. S. Remanent and transitory effects of elastic deformation of magnetite crystals, (4) 153*j*.
Carmichael, R. S., and Fuller, M. D. Effect of compression on the magnetic behavior of magnetite in thermal cycles across the magnetocrystalline isotropic point, (7) 265*i*.
Carnahan, R. D. See Buch, J. D.
Carnahan, R. D., Janowski, K. R., and Rossi, R. C. Elastic behavior of arc-cast zirconium carbide-graphite alloys, (11) 384*h*.
Carnall, E., Jr. Lanthanum fluoride infrared transmitting optical elements, P (7) 249*a*. See Brafman, O.
Carnall, E., Jr., and Hatch, S. E. Process of hot-pressing magnesium oxide infrared transmitting optical elements, P (1) 11*c*.
Carnall, E., Jr., Hatch, S. E., Parsons, W. F., and Weagley, R. J. Hot-pressed polycrystalline laser material, P (10) 339*g*.
Carnall, E., Jr., and Roy, D. W. Method of forming zinc oxide infrared transmitting optical element, P (4) 99*i*.
Carnes, R. A., and Taylor, D. W. Encapsulated semiconductor device including a ceramic substrate, P (7) 256*g*.
Carney, R. F. See Allbutt, M.
Carniol, B., and Styblo, R. Circuit arrangement for temperature measurement, P (1) 22*a*.
Caron, A. P., Huettner, D. J., Ragle, J. L., Sherk, L., and Stengle, T. R. Ion motion in tetrafluoroborate salts (I) NH_4BF_4 and ND_4BF_4, (4) 141*c*.
Carpay, F. M. A. Vanadium, chalcogenides and the NiAs structure, (9) 332*h*.
Carpenter, J. H. See Kirkorian, O. H.
Carpenter, S. H. Recovery of strain amplitude independent dislocation damping in single crystal LiF, (1) 35*j*.
Carpenter, W. E. Mechanically based rear loading panel lamp, P (1) 11*b*.
Carpenter, W. E., and Varick, L. Lamp lead wire terminal, P (5) 175*c*.
Carpentier, S., Delarue, R., Francois, H., Grand-Clement, A. M., Portal, G., and Soudain, G. Phosphate glass for X-ray, gamma-ray, and thermal neutron dosimeters, P (9) 308*f*.
Carr, R. Glass coach, (9) 303*f*.
Carr, R. G. See Szekely, J.
Carr, R. M. Problem of quartz-corundum stability, (10) 359*c*.
Carr, T. T. Technique for plant composition control—simplified low-temperature viscosity measurements, (10) 338*a*.
Carr-Brion, K. G. X-ray methods for on-stream analysis, (4) 121*b*.
Carr-Brion, K. G., and Jenkinson, D. A. Continuous X-ray fluorescent analysis of the solid component of a slurry, P (8) 286*c*.
Carroll, J. W. Effect of alkaline cleaner composition on the removal of drawing and stamping compounds from steel, (8) 274*j*.
Carruthers, J. D., and Sing, K. S. W. Glow phenomenon of chromium oxide, (4) 137*f*. Surface properties of calcined chromium oxide gel, (4) 158*d*.
Carruthers, J. R. Radial solute segregation in Czochralski growth, (4) 151*i*. Temperature oscillations in Czochralski crystal growth, (4) 159*g*. Thermal convection in horizontal crystal growth, (6) 239*b*.
Carruthers, T. G., and Scott, B. Reactive hot-pressing of kaolinites, (4) 153*a*.
Carter, G. See Konjevic, R.
Carter, G. H. Tiled roofs, P (6) 214*g*.
Carter, J., Cuniberti, M., and Scott, J. E. Apparatus for supporting and glazing glass articles, P (4) 98*f*.
Carter, J. R. See Redman, M. J.
Carter, L. S. See Slabaugh, W. H.
Carter, M. See Busby, T. S.
Carter, M. B. See Kellar, A. A.
Carter, N. I. See Heard, H. C.
Carter, N. W. Glass electrodes and method for producing the same, P (4) 99*a*.
Carter, R. E. Glower lamp and process, P (6) 221*b*. See Lay, K. W.
Carteret, Y., Bareau, J., and Elston, J. Kinetics of the escape of helium from BeO compacts during irradiation, (4) 142*b*.
Cary, H. B. Arc welding with ac power and cored electrode, P (6) 207*j*.
Cary, K. H., Nagamatsu, H. T., Sheer, R. E., Jr., and Graber, B. C. Compensating means for a [slotted] piezoelectric sensing element, P (1) 18*c*.
Casey, H. C., Jr., and Panish, M. B. Reproducible diffusion of zinc into GaAs—application of the ternary phase diagram and the diffusion and solubility analyses, (2) 82*d*.
Casey, J. J. See Lindmayer, J.
Cashion, J. D., Cooke, A. H., Leask, M. J. M., Thorp, T. L., and Wells, M. R. Crystal growth and magnetic susceptibility of some rare-earth compounds (II) magnetic susceptibility measurements on a number of rare-earth compounds, (8) 289*j*.
Casko, R. E. Method of making lens molds, P (11) 371*h*.
Caslavska, V., Strickler, D. W., Gibbon, D., and Roy, R. Two-liquid phase structure of photoconducting oxide glasses, (2) 52*d*.
Caslavska, V., Strickler, D. W., and Roy, R. Optimization of properties of photoconductive oxide glasses, (6) 210*d*.
Cass, L. A. See Dropkin, D.
Cass, T. R., and Washburn, J. Dislocation configurations in deformed magnesium oxide, (2) 75*f*.
Casselman, T. N. See Zook, J. D.
Castaing, R., and Slodzian, G. Ionic microanalyzer wherein secondary ions are emitted from a sample surface upon bombardment by neutral atoms, P (4) 121*j*.
Castellion, G. A. Novel quaternary semiconducting compositions of matter, P (5) 184*c*. Novel ternary semiconducting materials, P (10) 345*d*. Novel zinc manganese arsenide semiconducting materials, P (5) 184*c*.
Castellucci, N. T., and Krouskop, N. C. New low density ceramic material for packing fractional distillation columns (I,II), (9) 309*i*.
Caster, A. D. Municipalities' handling of industrial waste, (1) 4*i*.
Castle, J. G., Jr. See Hirayama, C.
Castle, J. W. See Brady, L. E.
Castles, J. R. See Watanabe, D.
Castrucci, P. P., and Pecoraro, R. P. Palladium ohmic contact to silicon semiconductor, P (6) 223*c*.
Caswell, H. L. See Blumberg, R. H.
Caswell, H. L., and Stern, E. Sputtering processes for depositing thin films of controlled thickness, P (1) 19*b*.
Catana, V. See Corneanu, A.
Catana, V., Szabo, A., Petri, I., and Deica, N. Tests of aluminosilica refractory mortars, (4) 105*f*.
Cataphote Corp. High index of refraction glass compositions, P (4) 99*h*.
Cater, E. D., Rauh, E. G., and Thorn, R. J. Thermochemistry of UOS; evaporation of US–UO_2 mixtures; on the attainment of equilibrium in Knudsen cells, (10) 362*i*.
Caterpillar Tractor Co. Friction welding ceramic to metal, P (4) 118*d*.
Cathcart, J. V., and Petersen, G. F. Structural characteristics of the oxide on the (111) of copper, (8) 298*b*.
Cathey, L. See Smith, P. K.
Cauge, T. P. See Swann, R. C. G.
Cauwenberg, W. J. See Roberts, G. L.
Cavalern, A., Cansa, G., and Iosifescu, B. Desorption of ionically pumped argon from clean and metalized glass surfaces, (9) 305*i*.
Cave, E. F. See Czorny, B. R.
Cavenett, B. C. See Bessent, R. G.
Caveney, R. J. Chemical bonding and structure of the semiconductor compounds, (4) 128*b*. Epitaxial growth of II–VI compounds, (7) 265*e*. Reciprocal lattice spikes in type Ia diamonds, (4) 153*e*.
Cawthon, W. C., and Ulrich, R. J. Method for producing an enamelware article having a patterned surface, P (10) 337*c*.
Cecil, O. B. Aluminum oxide humidity sensor, P (7) 260*f*. Electron beam techniques in integrated circuits, P (10) 344*g*.
Cecil, P. S. Cylinder flow test controls vitreous bonds, (4) 89*h*.
Celanese Corp. Direct production of graphite fibers, P (9) 309*e*.
Central Glass Co., Ltd. Process for preparing sodium metaphosphate, P (11) 382*h*.
Central Mfg. District. Method of fabricating panels of expanded perlite, P (4) 102*g*.
Centre Electronique Horloger S. A. Semiconducting resistance and a method for its manufacture, P (10) 346*a*. Silicon planar transistor, P (5) 185*a*.
Centre National de Recherches Metallurgiques. Measuring temperatures, P (1) 22*e*.
Centre National de la Recherche Scientifique. Manufacture of ferrite monocrystals, P (4) 114*b*. Solid solutions of the transition metal nitrides and oxynitrides and methods of preparation thereof, P (4) 107*j*.
Centre National de la Recherche Scientifique and CSF — Compagnie Generale de Telegraphie Sans Fil. Ionic microanalyzer wherein secondary ions are emitted from a sample surface upon bombardment by neutral atoms, P (4) 121*j*.
Ceramco Industrial Corp. [Tapered hollow] dowels for fireable ceramic dies and method for their use, P (10) 343*g*.
Cerberus Akt.-Ges. Gas-filled overvoltage arrester for telecommunication installations, P (9) 307*e*.
Cerisier, P. See Bizouard, M.
Cernichiari, O. See Pastor, R. C.
Cerny, V. Method for preparing thin sections from porous materials containing components of various hardness, (2) 70*e*.
Certain-Teed Fiber Glass Corp. Apparatus for production of glass fibers, P (6) 212*g*.
Certain-Teed Products Corp. Method of curing hydraulic cement, P (6) 207*e*.
Certain-Teed Saint Gobain Insulation Corp. Equipment for use in laying down glass fiber blanket, P (8) 277*i*. Method and apparatus for forming tubular fibrous insulating articles, P (8) 277*g*.
Cerulli, N. F. Method of removing carbon from mixtures of tungsten powder and thoria and insuring a uniform dispersion of thoria, P (9) 317*g*.

Ceskoslovenska Akademie Ved. Method and arrangement for shaping objects from ceramic raw material, P (10) 346*j*.
Cessna, L. C., Jr., and Sternstein, S. S. Viscoelasticity and plasticity considerations in the fracture of glasslike high polymers, B (1) 41*g*.
Cevales, G. Devitrification studies with X rays, (6) 208*g*. Phase equilibrium diagram of Al_2O_3-ZrO_2 and examination of a new phase of $99Al_2O_3$-$1ZrO_2$ (ε-Al_2O_3), (2) 81*b*.
Cevales, M. Research on direct enameling, (4) 93*h*, (6) 207*g*.
Ceve, P., Modesto, M., and Schara, M. Growth of the ferroelectric crystals $NaH_3(SeO_3)_2$ and $NaD_3(SeO_3)_2$, (4) 137*i*.
CFT—Compagnie Francaise de Television. Making of multicolor luminescent screens, P (6) 222*a*.
Chabaglian, H. F. Apparatus for thermal treatment of minerals, P (4) 122*g*.
Chabal, J. See Junge, A. E.
Chabra, K. C., and Kuma, J. Avalanche breakdown in diffused junction, (1) 16*b*.
Chabria, J. R. How to grow king size single crystal YIG, (2) 62*i*.
Chadderton, L. T. See Morgan, D. V.
Chadenson, P., and Lepeuve, A. Apparatus for continuous weighing of powdered or granular materials with weight regulation of the flow, P (2) 67*f*.
Chadwick, A. V. See Allnatt, A. R.
Chaille, C. E., and King, B. W., Jr. Effect of water vapor in the furnace atmosphere on a one-coat white porcelain enamel, (8) 274*i*.
Chaklader, A. C. D. Flow behavior of hydroxides during decomposition, (10) 353*d*. See Sunderland, P. W.
Chaklader, A. C. D., Armstrong, A. M., and Misra, S. K. Interface reactions between metals and ceramics (IV) wetting of sapphire by liquid copper-oxygen alloys, (1) 31*g*.
Chakraborty, S. K. See Narain, J.
Chakravorty, R. N. See Banerjee, S. C.
Chalifour, H. R. See Moroney, W. J.
Chalmers, R. A., and Basit, M. A. Microanalysis of silicate rocks (V) spectrophotometric determination of alumina, (4) 120*b*.
Chaloupka, J. See Spicak, K.
Chalupa, B. See Zelenka, J.
Chamberlain Mfg. Corp. Means for and method of applying mosaic to curvate surfaces, P (4) 109*e*.
Chamberland, B. L. See Sleight, A. W.
Chambers, G. P. C. Colloidal and surface properties of clay minerals, (4) 128*h*.
Chamis, C. C., and Sendeckyj, G. P. Critique on theories predicting thermoelastic properties of fibrous composites, (2) 47*g*.
Champion, J. A. Electrical conductivity of sapphire and ruby crystals, (10) 352*c*. Morphology of alumina crystals, (10) 357*b*.
Champion, J. A., Keene, B. J., and Sillwood, J. M. Wetting of aluminum oxide by molten aluminum and other metals, (10) 363*b*.
Champion Spark Plug Co. Method of accurately producing an abrasive surface of revolution, P (7) 243*i*. Method for making an insulator, P (8) 280*c*.
Champlin, K. S., and Glover, G. H. Temperature dependence of the microwave dielectric constant of the GaAs lattice, (4) 159*b*.
Champness, P. E., and Gay, P. Oxidation of olivines, (9) 326*j*.
Chance, D. A. Process for etching silicon monoxide and etchant solutions therefor, P (6) 223*h*.
Chance Brothers, Ltd. Microscope cover glass and method, P (5) 176*a*.
Chandler Evans, Inc. Rocket nozzle, P (6) 218*e*.
Chandler, H. H., Jr., Morrell, H. P., and Sayers, P. G. Ceramic filled plastic system, P (11) 369*b*.
Chandler, L. See Ono, K.
Chandler, M. Ceramics in the Modern World—Man's First Technology Comes of Age, B (2) 85*e*.
Chandley, G. D. Method and apparatus for improving grain structures and soundness of castings, P (7) 252*c*.
Chang, C. C. See Wang, S.
Chang, Chuan C. LEED studies of the (0001) face of α-alumina, (7) 267*i*.
Chang, H. L., and Custard, H. C. Ion exchange of montmorillonite at high pressures, (10) 356*d*.
Chang, Hsu, and Genovese, E. R. Memory element having two orthogonally disposed magnetic films, P (11) 377*e*.
Chang, I. F. See Brafman, O.
Chang, L. L., and Esaki, L. Insulated-gate field-effect transistor with nonplanar gate electrode structure for optimizing transconductance, P (9) 312*c*.
Chang, L. L. Y. See Hill, V. G.
Chang, Nien-Chih. See Lefever, R. A.
Chang, R. Schottky defect formation and the kinetics of dissolution of precipitates containing divalent cation impurities in the alkali halides, (8) 297*c*.
Chang, R., and Graham, L. J. Third order elastic constants of polycrystalline media and their relationships to the single crystal constants, (2) 84*j*.
Chang, R. K., Lacina, B., and Pershan, P. S. Raman scattering from mixed crystals $(Ca_xSr_{1-x})F_2$ and $(Sr_xBa_{1-x})F_2$, (2) 82*a*.
Chang, T. N. See Copeland, L. E.
Chang, Tetse, and Yang, G. C. Temperature dependence of paramagnetic relaxation of Mo^{5+} in TiO_2, (4) 159*c*.
Chang, Y. A. Thermal properties of tantalum monocarbide and tungsten monocarbide, (5) 201*f*.
Chang, Y. G. Integrated complementary transistor structure with equivalent performance characteristics, P (5) 183*f*.
Chanowitz, H. Apparatus for making pressurized reed switches, P (5) 174*h*.
Chapman, G. C. Apparatus for controlling glass tube and rod dimensions, P (1) 10*c*.
Chapman, J. H. See Lyons, S. C.
Chappert, J. See Bertaut, E. F.
Chappert, J., and Frankel, R. B. Moessbauer study of ferrimagnetic ordering in nickel ferrite and chromium substituted nickel ferrite, (4) 145*h*.
Charbnau, H. P. See Feder, R.
Charbonnages de France. Installation and method for the treatment at high temperature and cooling of granular or divided solid products utilizing a fluidized layer, P (5) 186*a*.
Charbonnier, W. P. See Steimke, F.
Charette, G. G., and Flengas, S. N. Thermodynamic properties of the oxides of Fe, Ni, Pb, Cu, and Mn by emf measurements, (10) 362*j*.
Charles, R. J. Effect of uniaxial stress on glass resistivity, (8) 276*f*.
Charleston, R. J. George Ravenscroft—new light on the development of his "christalline" glasses, (4) 90*h*.
Charman, W. M., Jr., and Anthony, B. F. Hot top structure, P (4) 106*j*.
Charman, W. M., Jr., and Beattie, W. R. Apparatus for lining a hot top, P (6) 217*f*.
Charnell, J. F. See Olson, D. H.
Charnock, H. Method of and apparatus for the manufacture of flat glass on a molten metal bath, P (5) 175*a*.
Chartier, G., and Laval, R. Polarization of the light emitted by a neodymium-glass laser, (8) 296*j*.
Chase, J. D. See Van Ruyven, L. J.
Chase, V. A., and Copeland, R. L. Fiber reinforcement strengthens ceramic parts, (1) 4*c*.
Chatterjee, H. P. Quality control of concrete and its economics for paving projects, (4) 92*c*.
Chatterjee, M. K. See Chaudhuri, S. P.
Chatterjee, M. R. See Ghosh, R. K.
Chatterji, S., and Jeffery, J. W. Strength development in calcareous cements, (4) 92*h*.
Chattopadhyay, B., and Measor, J. C. Thin films of cobalt oxide, (5) 182*d*.
Chattopadhyaya, S. K. Measurement of four-pole parameters of transistors, (4) 110*f*.
Chaudhary, D. R., and Bhandari, R. C. Thermal conductivity of two-phase porous materials—dry soils, (9) 315*d*.
Chaudhuri, S. P., and Chatterjee, M. K. Studies on thermal-shock resistance of aluminosilicate refractories in relation to strength, thermal expansion, and modulus of elasticity, (2) 58*c*.
Chaumet, C. Norman clays from the Pays de Bray, (4) 123*h*.
Chaumont, H. J. Grinding and polishing apparatus, P (1) 10*i*. Method for the surface treatment of glass, P (6) 213*e*. See Nedelec, M.
Chaurskii, N. I. See Il'yasov, I. I.
Chauvin, B. Apparatus for sealing off glass vessels, P (6) 212*h*.
Chauvy, D., Guye, R., and Huebner, K. Silicon planar transistor, P (5) 185*a*.
Chayes, F. Locating field boundaries in simple phase diagrams by means of discriminant functions, (8) 294*g*.
Cheatham, J. F. See Cheatham, R. G.
Cheatham, R. G., and Cheatham, J. F. Composite structural material incorporating metallic filaments in a matrix and method of manufacture, P (5) 178*e*.
Chebotarev, V. L. See Kichkina, E. S.
Chebukov, M. F., and Ignat'eva, L. P. Gypsum waste products from boric acid production as additives in grinding of clinker, (1) 2*f*.
Cheetham, C. J., and Barrow, R. F. Spectroscopy of diatomic transition element molecules, B (4) 165*d*.
Chekunov, A. V. See Kurdyumov, G. M.
Chemische Werke Albert. Process for the manufacture of metal fluorophosphates, P (1) 24*d*.
Chemla, M. See Mecta, O. P.
Chen, D. H. See Kevan, L.
Chen, F. S., Guggenheim, H. J., Levinstein, H. J., and Singh, S. Magnetooptical properties of transparent $RbFeF_3$, (4) 143*c*.
Chen, G. K. C. Semiconductor device with integral electrodes, constituting a unitary vitreous structure, P (10) 346*b*.
Chen, R. See Halperin, A.
Chen, W. K., and Jackson, R. A. Diffusion of oxygen in near stoichiometric α-Nb_2O_5, (4) 131*e*.
Chen, Y. See Sibley, W. A.
Chen, Y., Sibley, W. A., Srygley, F. D., Weeks, R. A., Hensley, E. B., and Kroes, R. L. Negative ion vacancies in irradiated MgO, (9) 325*b*.
Chen, Y. S. See Burgiel, J. C.
Cheng, Chin J. Friction welding ceramic to metal, P (4) 118*d*.
Cheng, F. S. See Bissada, K. K.
Chenot, C. F. Europium activated barium and strontium haloaluminate phosphors, P (9) 312*g*. Europium activated strontium fluoroborate phosphor, P (6) 221*i*. Europium activated strontium haloborate phosphor, P (6) 221*j*.
Cherdron, E. See Rueter, H.
Chernoch, J. P. Disk laser having pumping means in direct optical communication with disk end faces, P (5) 174*c*.
Chernoch, J. P., and Koenig, H. R. Disk laser having pumping means in direct optical combination with the disk end faces, P (5) 174*b*. Disk laser having pumping means in indirect optical communication with the disk end faces, P (5) 174*c*.
Chernov, A. A., and Khadzhi, V. E. Trapping of colloidal inclusions in the growth of quartz crystals, (10) 363*b*.
Chernov, N. I. See Menkovskii, M. A.
Chernow, F., Eldridge, G., Ruse, G., and Wahlin, L. High-conductivity *p*-type CdS, (4) 138*i*.
Chernyi, L. N. See Kashkurov, K. F.; Kleshchev, G. V.
Chernyshev, E. M. See Fedin, A. A.
Chernyshev, K. S. See Gal'perin, E. L.
Chernyshov, I. P. See Mazurov, D. J.
Cheroff, G., and Hochberg, F. Method for fabricating insulated-gate field-effect transistors having controlled operating characteristics, P (8) 282*g*.
Cherry, R. D. See Buchowiecki, J.
Chervinsky, A. A. See Telyatnikov, G. V.
Chesler, R. B. See Gokhale, B. G.
Chesswas, M. See Cockayne, B.
Chevallier, J., Derse, P., and Spitz, J. Study of the uranium-hydrogen system at high pressures, (4) 157*d*.
Chevreton, M. See Brunie, S.
Chevron Research Co. Hydrocracking of hydrocarbons with a catalyst composite comprising nickel and tin associated with a porous acidic inorganic oxide carrier, P (1) 23*i*. Process for producing ferrimagnetic materials, P (5) 185*d*.
Chiang, Ping-Wang, and Gluck, J. V. Sb-Tl-Te system—phase relations and transport properties in the tellurium-rich region, (4) 153*h*.
Chiang, Ping-Wang, O'Kane, D. F., and Mason, D. R. Phase diagram of the pseudobinary system Ag_2Te-In_2Te_3 and semiconducting properties of $AgIn_5Te_{14}$, (4) 149*b*.
Chiang, Y. S. See Ing, S. W., Jr.
Chiba, Kozo. See Tanaka, Shigezo.
Chicago Fire Brick Co. Carbon composition and process, P (8) 279*j*.
Chickerur, N. S. See Singh, R. P.
Chickerur, N. S., and Narasaraju, T. S. B. Quantitative separation of calcium, strontium, and phosphate, (1) 21*g*.
Chicotka, R. J. See Blum, S. E.
Chikan, J. Material transport and homogenization in the cement industry, (2) 44*f*.
Chikanov, N. D., and Il'ginova, V. T. System $TaCl_5$-$NbCl_5$-KCl-$MgCl_2$, (7) 270*c*. Systems KTaCl₆-KMgCl₃-KCl-NaCl and KNbCl₆-KMgCl₃-KCl-NaCl, (8) 299*j*.
Chikawa, Junichi. X-ray diffraction contrast from impurity precipitates in CdS single crystals, B (1) 40*i*.
Chikawa, Junichi, and Austerman, S. B. X-ray diffraction contrast of inversion twin boundaries in beryllium oxide crystals, (10) 363*d*.
Chikinev, N. M. Connector for high temperature electrical heating element, P (2) 72*e*.
Child, F. S. Two faces of emerging Suriname, (1) 9*h*.
Childs, B. G. See Rezek, J.
Chilingarian, G. V., and Rieke, H. H., III. Data on consolidation of fine-grained sediments, (1) 26*g*.
Chin, D. A., and Hollingshead, E. A. Liquidus curves for aluminum cell electrolyte (IV) systems Na_3AlF_6 and Na_3AlF_6-Al_2O_3 with MgF_2, Li_3AlF_6, and K_3AlF_6, (1) 31*h*.
Chin, J. See Bc&ros, J. C.
Chinnor, G. A., Smith, Joseph V., and Knowles, C. R. Transition metal content of Al_2SiO_5 polymorphs, (9) 332*c*.
Chiotti, P., Korbitz, F. W., and Dooley, G. J. Electrical resistivity and phase relations for the thorium-carbon system, (4) 134*e*.
Chiotti, P., and White, R. W. Miscibility gap in the Th-ThC system from high-temperature X-ray data, (4) 144*h*.
Chiou, C. See Blumberg, R. H.
Chira, I. See Rosu, D. P.
Chisaka, Haruo; Morita, Eiichi; Takeda, Shigeru; and Masuda, Masayoshi. Effects of oxidation on surface-barrier detectors, (5) 180*g*.
Chiu, Wen-Chau. See Yamaguchi, Goro.
Chkalova, V. V., Kalabukhova, V. F., Bondarenko, V. S., Freidenfel'd, E. Zh., and Milberg, Z. P. Investigation of the properties of some ferroelectric crystallized glasses, (2) 49*h*.
Chloupek, F. J. Disproportionation of alkyl aromatics with a crystalline aluminosilicate and oxygen, P (7) 262*g*.
Chojnicka, G. See Tuszynski, W.
Choi, G. See Konig, U.
Cholger, H. W. See Thompson, R. J.
Chope, H. R. Measuring ablation shield thickness, P (7) 261*a*.
Chorkey, W. J. Shock absorbers in industry, (2) 51*b*.
Chorne, J. See Jakas, R. P.
Chrenko, R. M. See Slack, G. A.
Christe, K. O., and Pavlath, A. E. Silicon tetrafluoride as a fluorinating agent (II), (1) 36*d*.
Christensen, A. N. See Larsen, F. K.
Christensen, A. N., and Broch, N. C. Hydro-

thermal investigation of the systems In_2O_3-H_2O-Na_2O and In_2O_3-D_2O-Na_2O — crystal structure of rhombohedral In_2O_3 and of $In(OH)_3$, (4) 139*i*.
Christensen, A. N., and Fregerslev, S. Hydrothermal preparation of hematite from amorphous iron(III) hydroxide, (8) 293*f*.
Christensen, A. N., and Hazell, R. G. Crystal structure of $NaIn(SiO_3)_2$, (4) 130*h*.
Christensen, D. I. Laminated safety glass, P (1) 10*j*.
Christensen, F. L. Diamond milling or planer cutters, P (1) 1*h*. Rounding and polishing apparatus for crystalline carbon bodies, P (7) 243*j*.
Christensen, H. V. Laminated glass assembly with tapered inner layer, P (7) 248*j*.
Christensen Diamond Products Co. Diamond milling or planer cutters, P (1) 1*h*. Rounding and polishing apparatus for crystalline carbon bodies, P (7) 243*j*.
Christiansen, R. L. See Lipman, P. W.
Christie, O. H. J. Spinodal precipitation in silicates (I) introductory application to exsolution in feldspar, (8) 298*h*.
Christie, O. H. J., and Bergstoel, S. Calibration of intensity data for X-ray fluorescence silicate rock analysis, (8) 289*a*.
Chromy, S. Photoelectric apparatus for refractive index determination by the immersion method, (10) 347*b*.
Chrysler Corp. Electrolytic preparation of semiconductor compounds, P (4) 112*g*.
Chu, T. L. See Campbell, R. B.
Chu, T. L., Lee, C. H., and Gruber, G. A. Preparation and properties of amorphous silicon nitride films, (4) 150*e*.
Chu, T. L., Szedon, J. R., and Lee, C. H. Films of silicon nitride-silicon dioxide mixtures, (4) 136*g*.
Chubb, W. Ternary peritectics between tungsten and molybdenum, and uranium monocarbide, (4) 159*i*.
Chujo, Nobuyoshi. See Suzuki, Hisashi.
Chukhlantsev, V. G., and Galkin, Yu. M. Preparation and some properties of barium zirconium silicates, (5) 199*a*.
Chung, D. H. Elastic constants of a cubic crystal subjected to moderately high hydrostatic pressure, (9) 320*g*.
Chung, D. H., and Buessem, W. R. Voigt-Reuss-Hill (VRH) approximation and the elastic moduli of polycrystalline ZnO, TiO_2 (rutile), and α-Al_2O_3, (5) 203*d*.
Chung, D. H., and Simmons, G. Pressure and temperature dependencies of the isotropic elastic moduli of polycrystalline alumina, (7) 268*e*.
Chung, P. L. See Gerstein, B. C.
Churaev, N. V. See Zorin, Z. M.
Churbakov, V. F. See Menkovskii, M. A.
Churbakova, T. I. See Menkovskii, M. A.
Churikov, V. D. See Shabanov, A. G.
Chuss, J. T. Metallization of selected regions of surfaces and products so formed, P (4) 114*d*.
Chvatal, T. See Fitzer, E.
Chyapas, A. F. See Lautsyus, A. S.
Chyung, C. K. Secondary grain growth of Li_2O-Al_2O_3-SiO_2-TiO_2 glass-ceramics, (7) 248*c*.
Ciba, Ltd. Process for the preparation of finely divided nonpyrophoric nitrides of zirconium, hafnium, niobium, and tantalum, P (6) 218*a*. Process for the preparation of mixed oxides, P (4) 94*c*.
Cicotte, L. J. See Toth, R. S.
Ciments Lafarge. Method of manufacture of superwhite cement, P (5) 170*g*.
Cini, L. Corrosion of a mullite refractory with 70–72% alumina by the ash of a fuel oil, (4) 103*b*.
Cioaca, E. See Brates, N.
Cipau, R. See Becherescu, D.
Cirie, J. Lithium-containing crystalline aluminosilicate, P (4) 124*d*.
Cismaru, D., and Dobroghiu, E. Oxidation of zirconium at high temperatures — oxidation kinetics of zirconium powder in O_2 and CO_2 atmospheres, (10) 358*f*.
Cities Service Oil Co. X-ray spectrography sample holder containing an adjustably mounted internal reference standard, P (11) 381*e*.
CKD Praha, Oborovy Podnik. Semiconductor assembly with semiconductor element in area contact under pressure with conductive terminal elements, P (6) 223*d*.
Claessens, F. D., and Hein, T. F. Method of drying a molded ceramic article on a form, P (7) 259*c*.
Clapham, C. H., Jr. Self-luminous light-emitting units, P (2) 66*c*.
Clare, C. P., & Co. Apparatus for making pressurized reed switches, P (5) 174*h*.
Clare, T. E. Effect of water vapor on the sintering of beryllia, (5) 177*f*.
Clark, C. A. See Drum, C. M.
Clark, C. C. See Marsh, A.
Clark, G. W. See Abraham, M. M.; Finch, C. B.; Kopp, O. C.
Clark, H. A. See Campbell, J. K.
Clark, J. B. See Pistorius, C. W. F. T.
Clark, J. H., Van Tassel, J. H., Larrabee, G. B., and Haefling, J. F. Ohmic contact to semiconductor devices, P (4) 115*d*.
Clark, K., Rajac, T. J., Santillo, G. R., Jr., and Schuelke, W. J. Vacuum operated chip placement head, P (10) 346*c*.
Clark, L., and Woods, J. Growth of single crystals of cadmium sulfide, (10) 354*j*.
Clark, L. M. Packaging method [laboratory tubes], P (10) 339*i*.
Clark, M. W., and Freeman, A. G. Kinetics and mechanism of dehydroxylation of crocidolite, (4) 142*f*.
Clark, R. C. See Kohn, E. J.
Clark, T. J., and Ettinger, B. L. Deposition of pyrolytic material, P (11) 379*e*.
Clark, W. C., and Mason, G. Tensile strength of wet granular materials, (7) 270*d*.
Clarke, A. R. See Cable, M.
Clarke, F. J. P. See Miles, G. D.
Clarke, F. J. P., Tattersall, H. G., and Tappin, G. Toughness of ceramics and their work of fracture, (2) 85*b*.
Clarke, J. H. R. See Solomons, C.
Claude Paz et Visseaux. Process for filling an electric discharge lamp having an ionizable atmosphere, P (5) 176*d*.
Claudel, B. See Bressat, R.
Clauer, A. H. See Contin, M. R.; Wilcox, B. A.
Clauer, A. H., and Hirth, J. P. Climb forces on dislocations, (10) 350*f*.
Claus, D. See Blasum, H. A.
Claus, H. Preparation of brown glasses with pyrites, (11) 370*b*.
Clausmeyer, H., and Peppler, P. Material technique, (4) 164*j*.
Claussen, N. Deformation behavior of ceramic materials, (6) 231*d*. Isothermal elastic modulus of UO_2 and UO_2-Mo cermets, (1) 12*j*.
Claxton, T. A. See Benson, G. C.
Clay, R. A. See Cockayne, B.
Claydon, C. R. See Carlson, K. D.
Claypoole, S. A., and Mertsoc, M. M. Method of attaching leads to electrical components, P (7) 257*a*.
Clayton, W. A., Gunderson, J. M., and Sargent, J. C. Emissive coating, P (2) 58*d*.
Clearfield, A. See Stynes, J. A.
Cleary, J. G. See Johansen, H. A.
Cleaver, B. See Barton, A. F. M.
Cleaver, D. Oxides, P (7) 263*b*. See Evans, A. W.; Weinberg, F. J.
Clements, J. F. Fracture strains of technical refractories, (2) 55*g*. See Padgett, G. C.
Clements, J. F., and Vyse, J. Comparison of methods of measuring pore-size distribution in refractories, (2) 69*a*.
Clendenning, T. G., Kellam, B., and MacInnis, C. Hydrogen evolution from ferrophosphorus aggregate in portland cement concrete, (4) 91*h*.
Clevite Corp. Piezoelectric materials, P (2) 66*c*. Piezoelectric resonators, P (1) 18*j*, P (5) 184*h*.
Clinard, F. W., Jr., and Kempter, C. P. Low-temperature electrical properties of some transition metals and transition-metal carbides, (8) 294*h*.
Cline, C. F., and Newkirk, H. W. Electrical transport processes in beryllium oxide, (9) 321*e*.
Clobes, A. R., and Brienza, M. J. Passive mode locking of a pulsed Nd:YAG laser, (10) 344*j*.
Clock, G. S. Coated glass article and process for making same, P (4) 98*i*.
Cloete, F. L. D., Ortega, R. F., and White, E. A. D. Detection of trace impurities in stoichiometric spinel crystals by instrumental neutron activation analysis, (7) 254*h*.
Clough, R. Nuclear reactor fuel elements, P (2) 59*b*.
Clougherty, E. V. See Kalish, D.; Kaufman, L. P.
Clougherty, E. V., Pober, R. L., and Kaufman, L. Synthesis of oxidation resistant metal diboride composites, (1) 13*h*.
Clow Corp. See Dickey, W. S., Clay Mfg. Co.
Clowers, C. C., Jr., and Guyon, J. C. Spectrophotometric determination of hafnium as reduced molybdosulfatohafnic acid, (10) 347*h*.
Clunie, J. S., Goodman, J. F., and Tate, J. R. Adsorption of inorganic ions in black foam films, (9) 317*j*.
Coast Metals, Inc. Adapter for converting torch to powder spray work, P (7) 246*d*. Method of spray coating gas seals of gas turbines and the like, P (7) 246*h*. Powder spray torch, P (7) 246*h*. Powder spray torch with explosion-proof hopper construction, P (4) 94*a*. Powder supply construction for spray torch, P (4) 94*a*.
Coast Mfg. & Supply Co. Method for manufacturing glass fiber reinforced resin impregnated mats, P (2) 53*g*.
Coastal Dynamics Corp. Twin filament lamp, P (4) 101*e*.
Cobaugh, G. D., Stock, D. F., and Wishon, B. E. Furnace construction, P (1) 14*a*.
Coberly, C. J., and Kogut, V. Fuel nozzles for high temperature furnace and method of operating, P (11) 381*i*.
Coble, R. L. See Jones, T. P.
Coblenz, A. G. Semiconductor wafer forming a plurality of rectifiers, P (11) 378*h*.
Coblentz, R. C. See Goodwin, G. I.
Cochardt, A. Method for making ferrite magnets, P (4) 115*b*.
Cochardt, A. W., and Buttyan, J. Apparatus and process for forming or molding magnetic substances, P (9) 312*a*.
Cochran, A. A. See Donaldson, J. G.
Cockayne, B. Developments in melt-grown oxide crystals, (7) 254*j*.
Cockayne, B., Chesswas, M., and Gasson, D. B. Growth of strain-free $Y_3Al_5O_{12}$ single crystals, (7) 266*a*.
Cockayne, B., Gasson, D. B., Findlay, D., Goodwin, D. W., and Clay, R. A. Growth and laser characteristics of yttrium-gadolinium-aluminum garnet single crystals, (9) 322*e*.
Cockbain, A. G. High-quality ceramic dielectrics sintered in reducing atmospheres, (2) 62*g*.
Cockram, D. R., Halder, Z., and Roberts, G. J. Diffusion of "water" in soda-lime glass within and near the transformation range, (7) 247*b*.
Cockshott, C. P. Semiconductor devices, P (4) 116*e*.
Coenen, F. See Camozzo, G.
Coenen, M. Density of glasses as a function of thermal history, (9) 305*f*.
Coes, L., Jr. Grinding apparatus, P (6) 205*f*.
Coetzee, C. J., and Rohwer, E. F. C. H. Determination of sodium and potassium after separation from each other and from other ions by means of ammonium phosphomolybdate and other ion exchanges, (7) 259*j*.
Coey, J. M. D. See Sawatzky, G. A.
Coffey, R. B. See Edwards, J. W.
Coffman, R. E., Lyle, D. L., and Mattison, D. R. Small tunneling effect in the electron paramagnetic resonance spectrum of Cu^{2+}-CaO at 1.2°K, (5) 199*g*.
Cogliati, G., De Leone, R., Mezi, E., Scibona, G., and Lanz, R. Process for producing dense particles of oxides of actinides usable as fuels for nuclear reactors, P (1) 14*e*.
Coglaiti, J. S., Jr., and Masterson, D. J. Increasing the bulk density of soda ash by adding calcium and magnesium ions prior to precipitation, P (11) 382*b*.
Cohen, F. Semiconductor device having increased resistance to second breakdown, P (9) 313*i*.
Cohen, G. Monolithic semiconductor microcircuits with improved means for connecting points of common potential, P (5) 184*a*.
Cohen, M. See Ramasubramanian, N.
Cohn, E. See Cosneanu, C.
Cohz, S. N. Process for treating glass cathode-ray tube envelopes, P (4) 100*j*.
Coiffu, P. Method and arrangement for producing white cement, P (9) 304*c*.
Coker, E. H., and Hofer, D. E. Infrared spectra of borohydride ions in alkali halide single crystals, (4) 140*g*.
Coker, J. E. See Zanowick, R. L.
Colbow, K., and Nyberg, D. W. Recombination kinetics in cadmium sulfide, (9) 328*f*.
Colby, J. W., Wise, W. N., and Conley, D. K. Quantitative microprobe analysis by means of target current measurements, B (1) 40*j*.
Coldrey, J. M., and Purton, M. J. Application of thermal analysis in investigations on calcium silicate bricks, (9) 303*i*.
Cole, A. E. See Fletcher, K. E.
Cole, J. F. See Barrer, R. M.
Cole, K. J. Potential of ceramics, (6) 240*e*.
Cole, W. C., Paul, F. B., and Wood, C. E. Thermocouple head, P (11) 381*d*.
Coleburn, N. L., and Forbes, J. W. Irreversible transformation of hexagonal boron nitride by shock compression, (2) 79*i*.
Coleman, D. S. See Spencer, D. R. F.
Coleman, R. D., Sutherland, J. P., and Capes, C. E. Reduction of the calcite content of ground shale by liquid-liquid particle transfer, (8) 287*g*.
Coleman, W. L., and Manning, J. P. Decorative fiber glass product [woven sheet] and process for making same, P (11) 371*d*.
Coleman Instruments Corp. Optical prism unit and manufacture thereof, P (9) 308*e*.
Coless, T. L. Method of making bonded welding flux, P (6) 208*b*.
Coless, T. L., and Rimer, K. W. Low silica welding composition, P (5) 172*a*.
Colgan, J. D., and Ostroff, N. Preparation of an alumina catalyst support, P (1) 24*c*.
Colgan, J. D., and Sanborn, W. E. Silica-alumina catalyst support, P (1) 24*f*.
Colgate Research & Development Co. Nondestructive measurement of material strength, P (1) 22*g*.
Colgate, S. A. Nondestructive measurement of material strength, P (1) 22*g*.
Colin, F. Contribution to the study of phases obtained during the reduction of some *n*-Al_2O_3-MO oxides, (9) 318*h*. See Collongues, R.
Collepardi, M. See Bernardini, F.
Colley, H., and Davies, P. J. Ferroan and nonferroan calcite cements in Pleistocene-Recent carbonates from the New Hebrides, (11) 384*j*.
Collie, W. D. Lime fines briqueting, P (4) 92*i*.
Colling, P. M. See Woskow, M. Z.
Collins, D. R. Effect of gold on the properties of the Si-SiO_2 system, (4) 132*h*.
Collins, D. S. See Villaume, H. F.
Collins, F. C. See Nakayama, Takashi.
Collins, F. C., and Schrager, M. Cationic migration in silicon dioxide films on silicon, (4) 128*d*.
Collins, F. M. Method of making film resistor, P (2) 65*g*.
Collins, J. D., and Corwin, J. F. Cementitious compositions, P (4) 92*f*.
Collins, J. F., and Ferguson, I. F. Lattice parameter variations in mixed oxides with the monoclinic zirconia structure: Systems ZrO_2-Fe_2O_3, ZrO_2-SnO_2, and ZrO_2-Cr_2O_3, (5) 196*j*.
Collins, J. H., Rubino, N., Zapp, H. R., Mee, J. E., Pizzarello, F. A., Pulliam, G. R., and Hamilton, T. N. Shear wave generation at microwave frequencies utilizing epitaxial YIG films on YAG, (4) 111*i*.
Collins, J. H., and Wilson, D. A. Optical probing of magnetostatic modes in YIG delay lines, (4) 147*j*.
Collins, J. O., Jr. Thermal insulation of fibrous brucite, P (6) 218*h*.
Collins, R. J., Braun, L. O., and Dean, D. R.

New method of giant pulsing ruby lasers, (4) 110*h*.
Collins, S. A., Jr. See Toth, L.
Collins Radio Co. Selective sputtering rate circuit forming process, P (7) 258*a*.
Collongues, R., Colin, F., Thery, J., Michel, D., and Perez y Jorba, M. Reduction and nitridation reactions in alumina-based ceramics, (1) 13*a*.
Colombo, M. See Lampani, A.
Colombo, R. L. See Amato, I.
Colombo, U., Fagherazzi, G., Gazzarrini, F., Lanzavecchia, G., and Sironi, G. Mechanism of low-temperature oxidation of magnetites, (9) 324*d*.
Colson, F. A. Throwing tips, (8) 273*j*.
Colton, E. See Matkovich, V. I.
Columbian Carbon Co. Apparatus for forming aggregates of powdered materials, P (2) 67*f*.
Colville, A. A., and Ribbe, P. H. Crystal structure of an adularia and a refinement of the structure of orthoclase, (5) 193*i*.
Colwell, J. H. See Ambler, E.
Combe, E. C., and Smith, D. C. Effects of some organic acids and salts on the setting of gypsum plaster (III) citrates, (2) 44*j*. Studies on the preparation of calcium sulfate hemihydrate by an autoclave process, (9) 304*e*.
Combustion Research Corp. Low intensity radiant heater system and burner therefor, P (1) 23*b*.
Comfort, E. H. See Dropkin, D.
Comins, J. D., and Wedepohl, P. T. Temperature dependence of the *F*-center production in KCl, (4) 159*a*.
Comins, L. B. Modeling from a solid block of clay, (10) 335*j*.
Comitato Nazionale per l'Energia Nucleare. Process for producing dense particles of oxides of actinides usable as fuels for nuclear reactors, P (1) 14*e*.
Commissariat a l'Energie Atomique. Composite electrode for magnetohydrodynamic generator, P (6) 221*c*. Composite electrode for MHD conversion duct, P (6) 221*d*. Composite structure electrode and process for manufacturing such electrode, P (4) 106*c*. Device for polishing specimens, P (7) 260*h*. Electrode and method of fabrication, P (5) 182*i*. Fluid fuel burner, P (5) 189*c*. Method of extruding metallic carbides and in particular uranium monocarbide, P (6) 217*g*. Method of making sintered nuclear fuel pellets, in particular consisting of uranium dioxide, P (2) 59*c*. Method for the obtainment of uranium fluoride, P (2) 59*e*. Mixed oxide of thorium and uranium monophased oxidation catalyst, P (11) 382*f*. Nuclear fuel element, P (2) 59*a*. Phosphate glass for X-ray, gamma-ray, and thermal neutron dosimeters, P (9) 308*f*.
Commonwealth Aluminium Corp., Ltd. Extraction of alumina from bauxite, P (1) 23*h*.
Commonwealth Scientific & Industrial Research Organization. Plasma sintering, P (6) 225*d*.
Compagnie belgo-luxembourgeoise du Commerce exterieur—Cobelcomex. Process and installation for glass tempering and cooling, P (2) 54*b*.
Compagnie Francaise de Television. Method of sealing frustoconical lead-through elements, P (4) 100*i*.
Compagnie Generale d'Electricite. Laser deflector having a nonuniform field applied to an electrooptic crystal, P (11) 377*b*. Tunnel diode manufacturing apparatus, P (11) 379*b*.
Compagnie Generale d'Electro-Ceramique. Ceramic capacitor, P (4) 112*f*.
Compagnie Generale de Telegraphie Sans Fil. Garnet compositions, P (4) 113*h*. Gas-filled discharge tube and electrical energy generators using the same, P (11) 376*h*. Semiconductor device having dielectric and metal protectors, P (7) 258*b*. See Centre National de la Recherche Scientifique.
Compagnie de Saint-Gobain. Apparatus for detecting and recording the locations of defects in sheet material in two dimensions, P (4) 98*c*. Apparatus for manufacture of flat wire glass, P (10) 338*g*. Apparatus for production of armored sheet glass, P (11) 370*j*. Glass sheet forming apparatus with coated silica core roller and roller, P (2) 52*i*. Glassworking apparatus with liquid seal, P (4) 99*e*. Grinding and polishing apparatus, P (1) 10*i*. Manufacture of flat glass on a molten metal bath, P (5) 175*g*. Manufacture of sheets or wicks from fibers of thermoplastic material such as glass fibers, P (8) 277*f*. Method and apparatus for manufacture of flat glass, P (2) 53*h*. Method of and apparatus for the manufacture of flat glass on a molten metal bath, P (4) 99*e*. Method of and apparatus for the shaping of plastic sheets, P (11) 371*e*. Method and apparatus for supporting sheets on a gaseous bed, P (9) 307*i*. Method of melting glass, P (8) 277*j*. Method for the surface treatment of glass, P (6) 213*e*. Method for surface working glass, P (8) 278*c*. Mounts for objects such as glassware, particularly for transportation and display, P (4) 100*d*. Operational safety mold cam bypass, P (4) 100*f*. Polychrome striped screens for color television receiver comprising filaments of homogeneous glass, P (1) 18*j*. Process and apparatus for supporting a sheet of glass on a gas and liquid support bed, P (7) 249*c*. Safety glass, P (6) 213*d*. Sheet handling apparatus and method, P (4) 101*f*.
Comperatore, J. Method and apparatus for [downward] bending glass sheets, P (2) 53*f*.
Compton, D. M. J., and Firle, T. E. Reduction of TiO_2 powders and rutile single crystals, (11) 387*b*.
Compton, J. B., and Zieber, F. L. Unipolar transistor, P (10) 346*b*.
Comstock, D. F., Jr., and Richardson, D. L. Pyrometric device, P (7) 261*a*.
Comsules, D., and Ungureanu, G. Spectral analysis of standard electrocorundum, (1) 22*d*.
Conaway, H. L. See Toland, D. A.
Conaway, W. A., Johnson, A. J., and Smisko, J. Process of preparing barium carbonate by carbonation of aqueous barium sulfide, P (5) 191*g*.
Condit, R. H., and Holt, J. B. Determination of self-diffusion of oxygen in ceramics by nuclear activation, (6) 231*e*.
Conley, D. K. See Colby, J. W.
Conley, R. F. Magnetic materials and methods of making the same, P (1) 24*a*.
Conley, R. F., and Lloyd, M. K. Potentiometric control of bleaching of kaolin clays, P (1) 24*b*.
Conn, W. M. See Noguchi, Tetsuo.
Connally, L. O. See Bawa, M. S.
Connan, G. B. Artificial ceramic tooth, P (9) 309*j*.
Conner, W. V. Recovery of plutonium from refractory siliceous materials, P (4) 125*i*.
Connor, G. J. See Kurpisz, Z. J.
Conrac Corp. Semiconductive pressure transducer, P (4) 116*b*.
Conrad, E. E. Method of selectively removing powdered glass, P (4) 115*i*.
Conrad, R. W. See Cronin, G. R.
Conrad, R. W., and Cox, R. H. Method for making graded composition mixed compound semiconductor materials, P (7) 257*f*.
Conrad, R. W., Haisty, R. W., and Hoyt, P. L. Method of making high resistivity group III-V compounds and alloys doped with iron from an iron-arsenide source, P (5) 183*f*.
Conrad, R. W., Hoyt, P. L., and Martin, D. D. Preparation and epitaxial $Ga_nIn_{1-n}As$, (4) 150*j*.
Conradi, V. R. Inside the diamond wheel (I, II), (5) 169*g*.
Conroy, A. R. See Manring, W. H.
Conroy, L. E., and Podolsky, G. Preparation of tungsten bronzes from metal halides, (11) 376*d*.
Considine, D. P. See Ryan, C. E.
Consogno, G. Method and device for the protection of refractory masonries, P (8) 279*f*.
Consortium fuer Elektrochemische Industrie G.m.b.H. Apparatus for manufacturing flawless stress-free boron rods, P (6) 217*g*.
Constabaris, G. See Ando, K. J.
Constabel, H. G. See Baier, E.
Contin, M. R., Clauer, A. H., Seltzer, M. S., and Wilcox, B. A. Techniques for transmission electron microscopy and etch pitting of CoO single crystals, (4) 121*j*.
Continental Can Co., Inc. Increasing the strength of glass by overglazing, P (6) 212*h*. Method of dressing grinding wheels, P (5) 169*h*.
Continental Oil Co. Process [and catalyst] for reducing the pour point of crude oil and the like, P (1) 24*f*. Process for producing alpha alumina monohydrate, P (4) 125*j*. Subterranean consolidation silicate cement, P (9) 304*f*. X-ray spectrometer sample cell having an adjustable secondary X-radiation radiator and taut X-ray transparent window, P (2) 72*a*.
Control Data Corp. Cathode sputtering apparatus for producing plural coatings in a confined high frequency generated discharge, P (5) 182*h*.
Conway, J. C. Structural evaluation of a ceramic underwater vehicle, (1) 9*h*.
Conway, J. G. See McLaughlin, R.
Conwell, E. M. See Zemon, S.
Conzinc Riotinto of Australia, Ltd. Continuous production of alpha plaster, P (7) 245*c*.
Coobs, J. H. See Wymer, R. G.
Cook, A. M. Method and apparatus for heating formed products, P (4) 123*a*.
Cook, A. R., and Matarrese, L. M. Zero-field EPR of Fe^{3+} in quartz, (11) 388*f*.
Cook, B. C., Jr., and Rovnyak, R. M. Method and apparatus for making dimpled reed capsules, P (7) 249*b*.
Cook, C. F., Jr. New technique for high magnification calibration of an electron microscope, (9) 315*a*.
Cook, D. O. Calibration of the University of Southern California automatically recording settling tube, (11) 379*i*.
Cook, E. G. Method and apparatus for resonating small piezoelectric crystals at low frequencies, P (6) 222*b*.
Cook, H. E. Electrode connecting pin and assembly, P (4) 106*e*.
Cook, J. E. Apparatus for forming glass articles with [air] treating means, P (8) 277*f*. See Stone, L. R.
Cook, R. L. See Harris, N. H.
Cooke, A. H. See Cashion, J. D.
Cooley, J. A. Method of producing a ceramic gapped ceramet tape head, P (5) 184*c*.
Cooper, A. R. See Haggerty, J. S.
Cooper, C. F. Surface of silica melts, (1) 38*j*.
Cooper, D. E. Hydrocarbon separation process employing crystalline aluminosilicates, P (11) 382*a*.
Cooper, F. C. See Moulik, S. P.
Cooper, G. A. See Crivelli-Visconti, I.
Cooper, R. E. See Bayer, P. D.
Cooper, W. D., and Parfitt, G. D. Comparison of particle size distributions of "monodisperse" particles from 0.8 to 3.5 μm in diameter using a Coulter Counter and electron microscopy, (4) 119*c*.
Coors Porcelain Co. Liner [lifter bar] for grinding mills, P (11) 375*j*. Means for indicating wear of ball mill lining bricks and the like, P (6) 225*b*. Method for making curved ceramic plates, P (8) 280*c*.
Cope, G. R. Refractories for continuous casting, (1) 13*b*.
Cope, G. R., Smoot, T. W., and Renkey, A. L. Tar impregnated fused silica stopper head, P (6) 218*g*.
Copeland, B. H. Braze grounded lead header, P (7) 255*g*.
Copeland, L. E., Bodor, E., Chang, T. N., and Weise, C. H. Reactions of tobermorite gel with aluminates, ferrites, and sulfates, (4) 152*i*.
Copeland, R. L. See Chase, V. A.
Copeland, W. D., and Swalin, R. A. Studies on the defect structure of strontium oxide, (9) 330*d*.
Copley, G. J. Electrical polarization during internal friction measurements in alkali silicate glass, (1) 6*i*. Internal friction of sheet glass under high stress, (8) 276*d*.
Copley, G. J., and Oakley, D. R. Internal friction studies of the stabilization of sheet glass, (4) 96*h*.
Copley, J. R., Cuming, W. R., and Rowe, P. E. Closed-cell ceramic article and method, P (5) 180*a*.
Coppen, P. J. High-frequency field-effect transistor, P (7) 256*a*. See Heynes, M. S. R.
Coppens, P. See Drowart, J.
Coppens, P., Smoes, S., and Drowart, J. Mass spectrometric determination of the dissociation energy of the molecule BO, (9) 324*i*.
Coquin, G. A. See Warner, A. W.
Corak, W. S. See Gallagher, R. C.
Corbach, R., and Scholze, H. Surface energy of glasses below the transformation temperature, (11) 370*e*.
Corbin, P. L. See Naumann, E. C.
Corhart Refractories Co. MgO-ZrO_2 fused cast refractory, P (4) 107*h*.
Corll, J. A. See Baughman, R. J.
Corman, G. A. Method and apparatus for measuring the thickness of an insulating layer by variation of the dielectric of a condenser using a contacting electrode, P (5) 183*i*.
Cormis, R. L. Method of forming carbon resistor films, P (4) 114*e*.
Corneanu, A. See Mircea, S.
Corneanu, A., Catana, V., Szabo, A., and Camerman, C. Technological study of the Anina refractory clays, (4) 124*a*.
Cornelison, B., Jones, M. E., Lineback, J. T., Wolff, E. A., Jr., Barcus, S. W., Jr., Horak, F. A., and Ince, N. S. Gold alloy for attaching a lead to a semiconductor body, P (6) 221*c*.
Cornell, R. M., and Bannister, G. H. Migration of krypton bubbles in uranium dioxide, (4) 144*f*.
Cornely, K. W. See Keith, C. D.
Corning Glass Works. Alkali metal salt separation, P (4) 124*f*. Alpha- and beta-cristobalite glass-ceramic articles and methods, P (8) 277*e*. Apparatus for pressing articles of thermoplastic material, P (6) 212*f*. Apparatus [tongs] for suspending sheet glass, P (10) 338*h*. Automatic control means, P (2) 52*b*. Centrifugal forming mold, P (11) 371*b*. Ceramic seals and bearing members, P (2) 58*a*. Constant force internal [refractory] support for glass overflow wedge, P (7) 248*d*. Cooking surfaces, P (2) 52*d*. Cooling arrangement for glass forming equipment, P (2) 52*e*. Crystalline glazed ceramic containing lead titanate crystals and method, P (2) 52*f*. Device for scoring glass articles, P (2) 52*g*. Double ion exchange method for making glass article, P (4) 98*b*. Electric flame generator, P (8) 286*d*. Electric lamp and method of production, P (1) 10*b*. Fibers of submicroscopic beta silicon carbide crystals with sheath of silica, P (2) 58*f*. Filter and method and apparatus for its production, P (5) 174*d*. Flexible shaping [flange] tool, P (9) 307*d*. Flow control of molten material in a glass furnace, P (10) 338*i*. Glass article having a birefringence pattern and method of production, P (5) 174*d*. Glass electrode composition, P (4) 98*j*. Glassmelting furnace, P (5) 174*i*. [Glass] pipe coupling, P (4) 99*b*. Glass rod and tube forming with controlled dimensional uniformity, P (4) 99*b*. Heat transfer members and method of fabrication thereof, P (4) 99*g*. High density alumina and method for producing it, P (11) 382*a*. High strength resistor, P (7) 256*a*. Infrared absorptive sealing glass, P (8) 277*c*. Internal ridging tool, P (2) 53*c*. Kovar sealing glass, P (5) 175*b*. Low thermal expansion glasses, P (2) 53*e*. Manufacture of silicon carbide fibers, P (9) 309*f*. Metalized semiconductor device with fired-on glaze con-

sisting of 25–35% PbO, 10–15% B_2O_3, 5–10% Al_2O_3, and the remainder SiO_2, P (11) 377*f*. Metallic members for insertion into glass, P (4) 99*b*. Metallurgical furnace, P (6) 217*e*. Method of attaching leads to electrical components, P (7) 257*a*. Method of conditioning forming rollers to form glass-ceramic, P (9) 307*j*. Method of connecting together a plurality of transducer segments, P (10) 345*e*. Method for cutting glass tubing, P (2) 53*c*. Method of differential chemical tempering glass and article, P (8) 277*i*. Method of drawing glass articles, P (5) 175*c*. Method of enclosing an electrical device, P (2) 65*j*. Method of improving roll forming properties of molten materials, P (7) 249*f*. Method for improving the visible and infrared transmission hot-pressed magnesium fluoride, P (2) 53*e*. Method of making an electrical component, P (10) 345*h*. Method of making electric heating units, P (7) 249*f*. Method for making fibers of titanium carbide and of titanium dioxide, P (7) 252*f*. Method of making filamentary metal structures, P (2) 65*f*. Method for making hollow glass particle having a metallic copper coating, P (5) 175*e*. Method of making synthetic marble, P (4) 109*a*. Method of measuring potassium ion and glass electrode therefor, P (11) 381*f*. Method of producing a photochromic glass and resulting article, P (4) 100*d*. Method of sealing and resilient seal for elements having different coefficients of expansion, P (5) 175*g*. Method of selective stressing and birefringent article, P (9) 308*c*. Method of treating glass, P (5) 175*j*. Method of treating a porous high silica content glass, P (11) 371*j*. Method of treating strengthened glass surface to increase acid durability, P (9) 308*d*. Miniature pressure transducer, P (7) 257*e*. Photochromic glass image display and storage system, P (6) 213*i*. Photochromic glass making, P (9) 308*a*. Pressure chuck, P (10) 339*i*. Process for producing seals, P (4) 100*i*. Radiation filters, P (4) 107*f*. Red stained soda lime glass, P (6) 213*c*. Resistor tailoring machine, P (5) 185*f*. Sheet glass edge control device, P (9) 308*c*. Sheet glass forming apparatus with means to transform vertical flows into a horizontal flow, P (6) 213*e*. Stressed hermetic seal and method of making said seal, P (7) 249*f*. System for measuring temperature, P (6) 228*c*. Temperature change measuring device, P (10) 348*b*. Transparent glass-ceramic articles and method for producing, P (9) 308*d*. Vertical index press for press forming glass articles, P (7) 249*g*. [Vibratory] process for joining transistor chip to printed circuit, P (2) 67*a*.

Cornu, R. Mounts for objects such as glassware, particularly for transportation and display, P (4) 100*d*.

Cornuault, P. See Gillot, J.

Corrigan, T. E., Dean, M. J., and Denton, D. Feeding pneumatic conveyors, (8) 284*d*.

Corsi, G. See Luciani, L.

Corsi, R. J. See Reese, T. J.

Corth, R. Method for producing tantalum carbide and tantalum-alloy carbide filaments, P (4) 107*b*.

Corwin, J. F. See Collins, J. D.

Cosgrove, J. F. See Persiani, C.

Cosgrove, J. J. Method of making a laminated ferrite memory, P (1) 18*b*.

Cosneanu, C., Cohn, E., and Petrescu, V. Fluidization mechanism of molding-coring sands, (10) 341*i*. New molding-coring sands for mechanical engineering applications, (10) 341*g*.

Cost, J. R., Janowski, K. R., and Rossi, R. C. Elastic properties of isotropic graphite, (2) 76*g*.

Costain, C. C. See Brooks, W. V. F.

Couch, P., and Pytel, R. N. Transferring sheets, P (4) 101*d*.

Coughlin, R. W. Carbon as adsorbent and catalyst, (7) 261*j*.

Coulter, J. S. See Schenk, G. H.

Coulter, W. H., and Hogg, W. R. Particle analyzing apparatus and method utilizing multiple apertures, P (8) 286*b*.

Coulter Electronics, Inc. Particle analyzing apparatus and method utilizing multiple apertures, P (8) 286*b*. Particle length measuring apparatus, P (7) 261*a*.

Council of Scientific and Industrial Research. Improvements in or relating to the manufacture of high alumina refractories, P (4) 106*a*. Process for the preparation of daylight and pink light emitting electroluminescent phosphors, P (1) 19*f*.

Counsell, J. F., and Martin, J. F. Entropy of tetragonal germanium dioxide, (4) 135*b*.

Couper, W. D., and Bogar, J. H. Dielectric constant measurement means and method utilizing frequency sweep and fixed probe, P (1) 18*d*.

Couquelet, D. M. Apparatus for controlled heat softening of glass tubing, P (11) 370*i*. Machine for the manufacture of glass hollow ware, P (5) 175*g*.

Court, G. R. Value of adding preheat section to conventional furnace, (8) 275*f*.

Courtney, T. H. See Rauch, G. C.

Cousseins, J. C. Solid-state study of some ternary fluorides; synthesis, identification, relationships, and miscibility, (1) 37*g*.

Cowan, G. R., Dunnington, B. W., and Holtzman, A. H. Process for sythesizing diamond, P (1) 20*f*.

Cowan, J. C., Beasley, A. E., Jr., and Gainey, H. G. Foundry core and molding sand composition, P (1) 14*a*.

Cowgill, M. G., and Smeltzer, W. W. Oxidation properties of a zirconium-2.7 wt% niobium alloy in the temperature range 300°–500°C, (4) 148*h*.

Cowgill, U. M., and Hutchinson, G. E. Chemical and mineralogical examination of the ceramic sequence from Tikal, in Peten, Guatemala, (9) 303*h*.

Cowles, R. J. Method of manufacturing cylindrical ceramic capacitors, P (7) 257*j*.

Cox, B. Porosimeter for determining the sizes of flaws in zirconia or other insulating films in situ, (2) 70*e*.

Cox, B., and Pemsler, J. P. Diffusion of oxygen in growing zirconia films, (10) 352*g*.

Cox, D. E. See Gonzalo, J. A.

Cox, D. L., and Savoie, J. E. Method for blocking and deblocking lenses, P (2) 53*c*.

Cox, J. A. See Padgett, G. C.

Cox, J. T., and Quinn, C. M. Conductivity measurements on cobalt and nickel oxides in highly enriched oxygen atmospheres, (10) 351*c*. Some aspects of the role of the cation vacancy density in the phase transition from monoxide to spinel in the lithium-cobalt-oxygen system, (10) 360*b*.

Cox, N. L., and Hicks, W. T. Preparation of ferromagnetic CrO_2 by heating CrO_3 in the presence of O_3 and Cr_2O_3, P (9) 317*b*.

Cox, R. H. See Conrad, R. W.

Cox, S. M. Electrical insulating bodies, P (2) 64*j*.

Coyle, H. F. Innovations in furnace atmosphere controls, (2) 70*b*.

Craft, W. L., and Slutsky, L. J. Ultrasonic and infrared studies of the lambda transition in $NaNO_3$, (6) 239*d*.

Cragg, D. G., Dicker, R. J., Harrison, J. D. L., Isaacs, J. W., McLaren, J. R., and Roberts, W. G. Reaction of oxygen and water vapor on UN, UC, and $(UPu)C_{1-x}O_x$, (1) 12*i*.

Craig, G. B. See Mills, D.

Craig, J. A., Balzhiser, R. E., and Ragone, D. V. Study of the free energies of formation of uranium monocarbide and uranium dicarbide, (4) 157*h*.

Cramer, H. R. Evaporites—a selected bibliography, (9) 316*j*.

Cramer, W. H., and Garfinkel, H. M. Method of producing a photochromic glass and resulting article, P (4) 100*d*.

Crane, G. R. See Kiel, A.

Cratchley, D., Baker, P. A., and Jackson, P. W. Ceramic fiber reinforced metal composites provide high strength with light weight, (1) 4*d*.

Crawford, J. H., Jr. See Hirata, Masako.

Cree, R. F., and Gatti, A. Catalyst for growth of boron carbide crystal whiskers, P (5) 178*d*.

Cremer, G. New tunnel kiln for firing large diameter clay pipe in Germany, (6) 214*f*.

Cremers, A., and Thomas, H. C. Self-diffusion in suspensions. Sodium in montmorillonite at equilibrium, (4) 154*e*.

Crest Ultrasonics Corp. Method and apparatus for resonating small piezoelectric crystals at low frequencies, P (6) 222*b*.

Creyke, W. E. C. Delayed fracture of glazed porcelain, (2) 59*j*. See Duncan, J. H.

Cribb, J. L. Shrinkage and thermal expansion of a two phase material, (4) 121*g*.

Cricchi, J. R., White, M. H., and McLouski, R. M. Integrated complementary MOS type transistor structure and method of making same, P (8) 282*a*.

Crick, R. F., Berard, M. F., and Wilder, D. R. Structural stabilization of Sm_2O_3, Gd_2O_3, and Nb_2O_5 with WO_3, (8) 298*c*.

Crile, E. E. See Thomas, P. M.

Crisa, V. See Amato, I.

Crisler, D. F. Piezoelectric semiconductor [ZnO] acoustic wave signal device, P (6) 223*e*.

Criss, G. H. Lightweight refractory brick and aggregate, P (7) 252*b*. Refractory coated composite oxygen lance, P (6) 208*b*.

Crivelli-Visconti, I., and Cooper, G. A. Mechanical properties of a new carbon fiber material, (6) 216*c*.

Crocker, B. S., Fulmor, T. G., Holderreed, F. L., Lucy, W., and Mahoney, J. F. Ore grinding control, P (4) 125*d*.

Croft, W. J., and Kestigian, M. Crystallographic phase transformation of ferric fluoride, (9) 319*j*. Crystallography of Na_3FeF_6, (7) 264*j*. Optical phenomenon in $LiNbO_3$ single crystals, (2) 81*e*.

Cronin, G. R., and Borrello, S. R. Epitaxial InAs on InAs substrates, (4) 110*f*.

Cronin, G. R., Conrad, R. W., and Borrello, S. R. Epitaxial InAs on semi-insulating GaAs substrates, (2) 77*a*.

Cronin, J. See Rodriguez, A. R.

Crook, D. N. Zircon as a pigment base, (5) 180*b*.

Crooks, D. D. See Kelsey, R. W.

Crooks, D. D., Kelsey, R. W., and Sumsion, H. T. Brazing method, P (5) 178*c*.

Crookston, J. A., and Gritton, W. R. Basic refractory for oxygen converters, P (8) 279*i*. Coke bonded [tar impregnated] basic refractory, P (7) 252*h*.

Cropp, D. I., Jordan, C. C., and Lingo, R. W. Work holder for aligning and sealing a beaded wire element into a glass tube, P (4) 101*e*.

Cropper, D. R., and Langdon, T. G. Creep of polycrystalline lithium fluoride, (9) 319*a*.

Cropper, D. R., and Pask, J. A. Effect of plastic instability on compressive deformation, (6) 226*f*.

Crosier, C. M., and Hardy, R. G. Cellular concrete of Kansas pozzolanic materials, (2) 43*j*.

Cross, L. E. See Goswami, A. K.; Tien, T. Y.

Cross, L. E., and Gooner, C. F. Dielectric measurements on flux-grown crystals of rutile (TiO_2) without contacting electrodes, (9) 310*g*.

Cross, L. E., and Smith, J. W. Dielectric and mechanical loss in the system $Pb_3MgNb_2O_9$-$Pb_3NiNb_2O_9$, (5) 180*g*.

Crouch, R. T., and Barger, C. H. Nonporous asbestos-reinforced plastic pipe, P (11) 375*d*.

Crowe, K. R., and Leiter, H. A. Cylinder with internal photosensitive coating and prism on outer surface for admitting light at an angle to be totally internally reflected, P (8) 282*d*.

Crowe-Gulde Cement Co. Apparatus for making concrete facing bricks with varied color and texture, P (5) 170*d*.

Crowell, C. R., and Rideout, V. L. Thermionic-field resistance maxima in metal-semiconductor (Schottky) barriers, (9) 311*e*.

Crowell, M. H., Dalton, J. V., Gordon, E. I., and Labuda, E. F. Light sensitive storage device including diode array, P (4) 113*h*.

Crowley, M. S. Influence of particle size on erosion resistance of refractory concretes, (8) 279*b*.

Cruickshank, D. W. J. See Beagley, B.

Cruz, C. R. Apparatus for measuring creep of concrete at high temperatures, (5) 170*d*.

CSF. See Compagnie Generale de Telegraphie Sans Fil.

Csillag, L., Janossy, M., and Kantor, K. Experimental investigation of the spatial coherence of an He-Ne laser, (5) 181*d*.

Cubicciotti, D. Thermodynamic properties of bismuth trifluoride, (10) 362*i*. See Keneshea, F. J.

Cubicciotti, D., and Withers, G. L. Enthalpy of formation and the dissociation energy of thallium monofluoride, (2) 76*i*.

Cuenat, P., and Mozzo, G. Measurement of the diameter of a glass filament by determination of its mechanical resistance, (7) 247*g*.

Culbertson, J. R., and Lamprey, H. Process for preparing chromates, P (2) 74*c*.

Culfeather, W. R. See Wigginton, R. J.

Cull, N. L. See Mertzweiller, J. K.

Cullen, G. W. See Wang, C. C.

Cullis, R. Semiconductor process including reduction of the substrate thickness, P (6) 223*j*. Semiconductor switching device, P (4) 116*j*.

Culp, J. D., Grimm, T. C., Fitzpatrick, T. H., and Patterson, R. D. Refractory metal coating, P (4) 94*e*.

Culver, R. V. See Gray, N. B.

Cuming, W. R. See Copley, J. R.

Cummings, C. D. Abrasive cutting systems, (11) 367*f*.

Cummings, H. B. Ceramic casting techniques, P (6) 220*d*. [Pulsed] pug mill apparatus, P (9) 314*h*.

Cummings, H. B., and Gibson, R. Process of manufacturing ceramic articles and the products of such process, P (1) 16*a*.

Cummings, J. L., Sr. Lining material for oxygen blowing basic steel making vessels, P (4) 106*d*.

Cummins, H. Z. See O'Shea, D. C.; Shapiro, S. M.

Cundy, E. K. Processing of clay, P (9) 317*f*.

Cuniberti, M. See Carter, J.

Cunningham, M. B., and Dunlap, C. K., Jr. Forming tube for glass fibers, P (9) 307*e*; P (10) 338*j*.

Cunningham, R. S., and Geankoplis, C. J. Effects of different structures of porous solids on diffusion of gases in the transition region, (4) 133*g*.

Cuomo, J. J., and Gambino, R. J. Synthesis and epitaxial growth of GaP by fused salt electrolysis, (10) 362*a*.

Curcio, E. N. Apparatus and method of growing a crystal from a vapor, P (4) 112*c*.

Curl, G. A. Twin filament lamp, P (4) 101*e*.

Curn, F. Diamond tool, P (7) 243*i*.

Curran, D. R., Gerber, W. J., and Williams, A. L. W. Piezoelectric resonator, P (5) 184*h*.

Curran, D. R., and Koneval, D. J. Piezoelectric resonators, P (1) 18*j*.

Currie, T. E. Detection of organic films on metal surfaces, (1) 4*f*.

Currier, E. W. See Shanefield, D. J.

Currin, C. G. Large volume semiconductor coating reactor, P (11) 377*b*.

Curry, D., Hodson, F., and West, I. M., with Gilkes, R. J. Eocene succession in the Fawley Transmission Tunnel (Southampton Water, England), (4) 135*b*.

Curtis, J. P. See Kurpisz, Z. J.

Curtis, M. G. Lining ring assembly for rock crushers, P (2) 74*b*.

Curtis, S. R. Grooved brick construction and composite thereof, P (6) 214*d*.

Curtze, E. W., Huffman, C. O., and Mikus, C. A. Automatically sizing and severing glass sheets, P (5) 174*i*.

Curtze, E. W., Wehner, G. O., and Barsom, J.

M. Apparatus for severing glass sheets, P (1) 10*i*. Method and apparatus for severing glass sheets, P (10) 339*i*.
Cusano, D. A. See Potter, R. M.
Custard, H. C. See Chang, H. L.
Cuthbert, J., Faircloth, R. L., Flowers, R. H., and Pummery, F. C. W. Vaporization of alkaline-earth and rare-earth metal dicarbides, (5) 202*i*.
Cuthbert, J. D., Hopfield, J. J., and Thomas, D. G. ZnTe:O electroluminescent device, P (4) 117*d*.
Cuthbert, J. D., and Thomas, D. G. Electroluminescent material and device, P (11) 376*d*.
Cutler, I. B. Effect of water vapor on the sintering of glass powder compacts, (4) 117*g*. Sintering of glass powders during constant rates of heating, (4) 118*c*. See McAllister, P. V.; Whitworth, C. R.
Cyr, D. Combination pot, (7) 244*e*.
Czanderna, A. W. Reduction of $CuO_{0.67}$ in hydrogen, (1) 36*b*.
Czaplinski, W. J. See West, R. R.
Czerlinsky, E. R., and Gianino, P. D. Method of eliminating magnetocrystalline anisotropy effect on spin resonance of ferrimagnetic materials, P (2) 65*i*.
Czorny, B. R. See Blicher, A.
Czorny, B. R., and Cave, E. F. *Pn* junction semiconductor with polycrystalline layer on one region, P (8) 283*i*.
Czysz, P., and Dixon, W. P. Thermographic heat transfer measurement, (2) 63*j*.

Dachille, F., Simons, P. Y., and Roy, R. Pressure-temperature studies of anatase, brookite, rutile, and TiO_2-II, (10) 359*b*.
Dachs, H., and Weitzel, H. Magnetic structure of manganese tungstate $MnWO_4$ at 4.2°K, (4) 143*h*.
Dadape, V. V. See Rao, D. B.
Daendliker, G. Process for the preparation of mixed oxides, P (4) 94*c*.
Dagley, J. F. See Van Sickler, R. H.
Dahl, E. Crystal structure of Pt_2P_3, (4) 130*d*.
Dahl, T., and Hassel, O. Crystal chemistry of binary systems of donor and acceptor molecules, (7) 264*e*.
Dahlberg, R. Controllable electrical resistance, P (4) 112*b*. Controllable tunnel diode, P (11) 376*b*. Electrical structural element having closely neighboring terminal contacts and method of making it, P (4) 112*f*.
Dahowski, E. L. See Feagin, R. C.
Daikin Kogyo Co., Ltd. Process for the manufacture of a bearing surface on a steel article including a single sintered layer of bronze particles and a layer of polytetrafluoroethylene, P (4) 94*a*.
Daikoku, Kazuhiro, and Mizushima, Yoshihiko. Breakdown characteristics of germanium [silver] bonded diode and its microwave oscillation, (4) 109*g*.
Daimon, Masaki. See Kondo, Renichi.
Daines, W. L., and Pehlke, R. D. Kinetics of manganese oxide reduction from basic slags by silicon dissolved in liquid iron, (2) 79*j*.
D'Albis, A., Yerouchalmi, D., and Bouillon, B. Electrode and method of fabrication, P (5) 182*i*.
Dale, B. Four-layer semiconductor switching devices in integrated circuitry, P (9) 312*a*. See Baker, A. G.
Dale, R. D. Elastic insulating bodies of inorganic fiber material [asbestos] and method of producing such bodies, P (11) 374*h*.
Dale Electronics, Inc. Capacitor and method of making same, P (5) 182*g*.
D'Alessandro, W. J. Abrasive wheels comprising a novolak resin and a thermoplastic polyhydroxyether, P (2) 43*g*.
Dalton, J. T. See Harper, E. A.
Dalton, J. V. See Buck, T. M.; Crowell, M. H.
Dalton, J. V., and Drobek, J. Structure and sodium migration in silicon nitride films, (10) 361*g*.
Dalton, R. H. Infrared absorptive sealing glass, P (8) 277*c*.
Daluja, K. L., and Srivastava, S. N. Stability of hydrosol of arsenic trisulfide in the light of Deriaguin-Landau-Verwey-Overbeek theory, (4) 155*j*.
Daly, J. H., Sommer, J. G., and Meyer, D. A. Elastomeric composition containing chromic oxide for use as rocket insulation, P (5) 178*f*.
Daly, R. A. Valve lever [pneumatic] and latch mounting mechanisms for glassware forming machine, P (11) 372*c*.
Damen, T. C. See Porto, S. P. S.
Damm, D. A., and Powell, D. E. Apparatus for applying [resin] bonding material between implosion band and glass for cathode ray tubes, P (2) 52*i*.
Dampier, F. W. See Janz, G. J.
Daneyrolle, C. See May, P.
D'Anglejan, B. F. See MacIntyre, I. G.
Daniels, B. K. Twist boundaries and rotational slip in ZnS, (9) 332*e*.
Daniels, H. P. C., and Rademakers, F. M. A. Ultrasonic welding method and apparatus, P (10) 340*b*.
Danjo, Hiroyuki. See Hayashi, Takeshi.
Danko, G. K. See Stone, M. L.
Dapkus, P. D. See Rossi, J. A.
Dapolito, J. J., and te Grootenhuis, W. D. Method of fabricating a color cathode ray tube screen, P (7) 257*a*.
Darinskii, B. M. See Postnikov, V. S.
Darling, A. H., and Weightman, H. L. Process for making structural gypsum board for neutron shielding, P (10) 336*c*.
Darnell, A. J., and McCollum, W. A. Phase diagrams of the bismuth trihalides at high pressure, (5) 198*g*.
Darnley, A. Glass fiber mold for industrialized building, (1) 7*e*.
Darr, D. E., Leiser, R. S., Lochr, C. E., and Richardson, K. W. Scraped removal of metal oxide deposit by a ceramic edge, P (5) 191*e*.
D'Artemare, E. See Palmer, D. W.
Darvoid, T. I. See Popova, M. A.
Das, C. R. Study of the equilibrium pH of some commercial and experimental glasses and their relation with chemical durability, (2) 51*a*.
Das, C. R., and Katrekar, S. A. Measurement of specific surface of silicate materials, (10) 347*h*.
Das, K. See Majumdar, N. C.
Das, P. See Wang, Wen-Chung.
Das, S. R. See Guha, S. K.
Da Silva, A. P. See Giles, C. H.
Data Products Corp. Apparatus for inspecting a reflective surface which includes a projector of a pattern of lines having different thicknesses, P (7) 260*g*.
Datars, W. R., and Calvo, C. Electron spin resonance of thortveitite, (4) 135*b*.
Datta, R. K. Bismuth in yttrium vanadate and yttrium europium vanadate phosphors, (4) 109*f*. Luminescent behavior of bismuth in rare-earth oxides, (4) 110*d*. See Mitra, N. K.; Ragone, S. E.
Datta, R. K., and Roy, R. Order-disorder in $MgAl_2O_4$ — the systems $MgAl_2O_4$-$LiAl_5O_8$, $MgAl_2O_4$-$NiCr_2O_4$, $MgAl_2O_4$-$NiAl_2O_4$, and Ni-Al_2O_4-$ZnAl_2O_4$, (10) 358*e*.
Datta, S. K. See Saalfeld, H.
Davenport, S. T. E. See West, H. W. H.
Davenport, T. Prolific potter, (4) 90*e*.
Davey, J. E., and Pankey, T. Polymorphism in vacuum-deposited GaP films, (1) 35*a*.
Davidge, R. W. Irradiation damage and irradiation hardening in single crystal MgO after low neutron doses $<10^{18}$ *nvt* (>1 MeV), (5) 196*a*. Work hardening and latent hardening in NaCl, (2) 84*f*.
Davidge, R. W., and Green, T. J. Strength of two-phase ceramic-glass materials, (4) 97*h*.
Davidge, R. W., and Tappin, G. Effective surface energy of brittle materials, (6) 232*h*. Internal strain energy and the strength of brittle materials, (8) 293*f*.
Davidse, P. D., and Maissel, L. I. Low power density sputtering on semiconductors, P (6) 221*j*.
Davidson, I. A., Hantusch, G. H., and May, G. A. Method of making large scale integrated circuit, P (5) 183*g*.
Davidson, K. V. See Riley, R. E.
Davidson, T. W. See Ashpole, R. S.
Davies, B., and Carini, G. F. Phosphate-impregnated magnesite brick, P (9) 309*b*.
Davies, L. M. Effect of heat treatment on the tensile strength of sapphire, (2) 76*a*. Residual strain in sapphire rods and boules, (2) 82*d*. See Harrison, J. W.
Davies, M. W. See Ignatowicz, S.
Davies, P. J. See Colley, H.
Davies, R. L. Conductive electrode for reducing the electric field in the region of the junction of a junction semiconductor device, P (4) 112*a*.
Davis, B. T. C. See Bell, P. M.
Davis, C. M. Semiconductor devices, P (6) 223*h*.
Davis, D. K., Hendrix, W. P., and Orr, C., Jr. Particle classifier, P (7) 261*b*.
Davis, E. A. See Drews, R. E.
Davis, E. M., Jr., McNutt, R. D., and Mones, A. H. Connections for microminiature functional components, P (10) 344*d*.
Davis, E. S. See Navon, D. H.
Davis, H. F., Jr. Barrel finishing media, P (6) 205*h*.
Davis, H. T., and McDonald, J. Conformal solution theory of certain molten salts, (4) 129*e*.
Davis, J. H., Doble, J. D., and Flockhart, M. G. Radiant gas burner, P (7) 261*g*.
Davis, J. S. See Wells, P. E.
Davis, N. S. Combined waste treatment and cement-making method and means, P (8) 274*a*.
Davis, R. E. Economics and application of day tanks, (2) 48*j*. Empty bottle inspection method and apparatus utilizing both water soluble and oil soluble fluorescent dyes, P (4) 98*d*. See Ullman, W. L.
Davis, R. J. Oxide growth and capacitance on preirradiated Zircaloy-2 and zirconium, (4) 148*i*.
Davis, T. A. See Vedam, K.
Davis, W. C. See Boczar, W. J.
Davis, W. R. Measurement of the elastic constants of ceramics by resonant frequency methods, (6) 226*b*. See King, J. F., Jr.
Davit, J. Mechanism for laser surface damage of glasses, (9) 306*e*.
Daviyan, I. A., Kelier, E. K., and Glushkova, V. B. Influence of additions of germanium dioxide and yttrium and neodymium germanates on the polymorphism of zirconium dioxide, (7) 267*b*.
Davydov, V. Ya., and Kiselev, A. V. Reaction of hydroxyl groups on a silica surface with water and alcohol molecules, (6) 237*d*.
Dawihl, W., and Frisch, B. Wear properties of tungsten carbide and aluminum oxide sintered materials, (1) 13*e*.
Dawihl, W., Frisch, B., and Kollmar, H. J. Boundary surfaces of α-Al_2O_3 (I) arrangement of adsorbed monocarboxylic molecules on α-Al_2O_3 surfaces, (2) 75*a*; (II) sedimentation activity of organic acids in Al_2O_3 suspensions, (4) 140*j*.
Dawihl, W., and Klingler, E. Effect of cold-welding between metals and sintered alumina on their wear resistance, (4) 89*h*. Mechanical and thermal properties of welded joints between alumina and metals, (7) 246*b*.
Dawson, B., and Sanger, P. L. X-ray studies of covalent bonding in diamond and silicon, (5) 203*b*.
Dawson, D. K. See Barr, L. W.
Dawson, D. K., and Barr, L. W. Entropies and enthalpies for self-diffusion in potassium bromide, (4) 135*a*. Measurement of anionic diffusion in KBr by means of isotopic exchange, (8) 294*g*.
Dawson, R. H., Ditrick, N. H., and Mitchell, M. M. Method of fabricating insulated-gate field-effect devices, P (10 345*f*.
Day, C. E., Jr. How we specify fuels for our plants, (9) 316*d*.
Day, D. E. See Shelby, J. E., Jr.
Day, F., and Froberg, M. L. Wall construction for melting tanks, P (7) 249*g*.
Day, F., Froberg, M. L., and Holschlag, J. B. Method and apparatus for processing filament-forming mineral materials, P (2) 53*j*.
Day, R. K. Assignment in Iran, (1) 5*j*.
Day, R. V., and Barford, J. Particle coarsening in the solid state, (9) 326*d*.
De, P. L. Resin concrete, (4) 92*e*.
De, P. L., and Hajela, P. B. Special bricks, (4) 105*j*.
Deal, B. E. Method of making stable semiconductor devices, P (5) 183*i*.
De Alarcao, J. Bowl with gold base discovered at Farrobo, Portugal, (4) 90*b*.
Dean, C. B. Kiln liner block supporting structure, P (4) 106*c*.
Dean, D. R. See Collins, R. J.
Dean, M. J. See Corrigan, T. E.
Dean, P. See Bell, R. J.
Dean, P. J. Survey of radiative and nonradiative recombination mechanisms in the III–V compound semiconductors, (2) 83*d*.
Dean, P. J., and Faulkner, R. A. Nitrogen isoelectronic trap in phosphorus-rich gallium arsenide phosphide, (9) 311*d*.
Dear, W. N. See Wigginton, R. J.
Dearborn, E. F. See Van Uitert, L. G.
Deb, S. K. Physical properties of a transition metal oxide—optical and photoelectric properties of single crystal and thin film molybdenum trioxide, (1) 34*b*.
De Bard, Y. See Perieres, R.
De Batist, R. See Socino, G.
De Beauchamp, R. L. Preparation of anhydrous aluminum chloride, (10) 348*g*.
De Bell & Richardson, Inc. Glass-resin composite structure, P (5) 174*j*.
De Bock, E. J. Method for refining glass baths, P (8) 278*a*.
De Boer, J. H. Changes in pore systems associated with sintering, (1) 25*e*.
Debrabant, P. Geochemical study of metamorphic marbles of French Massif Central, (1) 30*g*.
Debras-Guedon, J. Analysis by atomic absorption spectrophotometry—applications to the study of silicates, (5) 186*i*.
De Bruin, H. J. See Bradhurst, D. H.
DeBruyn, P. L. See Berube, Y. G.
DeBucs, E. S., Oesterhelt, G., and Pietsch, D. Fused junction between a germanium-silicon semiconductor member and a junction element and method of producing the same, P (7) 256*i*.
Debuisser, J. P. See Fleck, J. P.
De Calmes, A. See Bressat, R.
DeCarli, P. S. See Linde, R. K.
Decius, J. C. Dipolar coupling and molecular vibration in crystals (I) general theory, (8) 290*i*.
Decker, E. L. Industry ball milling procedures, (8) 275*b*.
Decker, R. L. See McCleary, R. E.
Decker, T. G. See Gaudin, A. M.
DeCrescente, M. A. See Brooks, C. S.; Vozzella, P. A.
De Diemar, R. B. Clamping and release means for [gyratory] crusher bowls, P (11) 382*i*.
Deeg, E. Cause of dependence of light transmission of struck glasses on intensity of illumination, (9) 305*d*. See Baier, E.
Deeley, G. G., and Herbert, J. M. Silicon nitride, P (10) 343*b*.
Deery, A. R. See Deery, E. D.
Deery, E. D., and Deery, A. R. Apparatus for forming a helically shaped glass tube, P (5) 174*g*.
De France, H., and Cahen, R. R. Making of multicolor luminescent screens, P (6) 222*a*.
De Gasperi, F. E. See Ligon, E. R.
Degen, K. See Suckow, A.
Degen, M. G. See Toropov, N. A.
De Gier, J. Cathode-ray tube having a non-

discoloring X-ray absorptive display window, P (5) 182*h*.
Degtyareva, E. V., and Kainarskii, I. S. Polycrystalline transparent materials, their properties and application, (2) 56*h*.
Dehn, J. T., Newnham, R. E., and Mulay, L. N. Mixed magnetic ordering—magnetic susceptibility and Moessbauer studies on iron(III) tellurate (Fe_2TeO_6), (9) 325*d*.
DeHoff, R. T. Reformulation of Fick's first law for solid-state diffusion, (2) 82*a*. See Gokularathnam, C. V.
Deica, N. See Catana, V.
Deica, N., Sorocopud, L., Guriuc, V., and Naumescu, V. Improvement of the quality of refractory brick for steel ladles, (1) 12*g*.
Deichelmann, H. Experimental investigations concerning stress in enamels for thick plate steel, (10) 336*i*.
De Jong, J. See Spit, B. J.
De Jong, J. G. M., Stein, H. N., and Stevels, J. M. Hydration of tricalcium silicate, (8) 286*h*. Influence of aluminum hydroxide and lime on the hydration of tricalcium silicate, (9) 323*a*. Influence of amorphous $Al(OH)_3$ on the hydration of tricalcium aluminate, (9) 323*d*.
DeKeyser, W. Disordered structures and network defects, B (4) 168*i*.
De Kimpe, C. R. Hydrothermal aging of synthetic aluminosilicate gels, (7) 266*j*.
De Kimpe, C. R., and Fripiat, J. J. Kaolinite crystallization from H-exchanged zeolites, (6) 234*c*.
Dekker, A., and Middlehoek, A. Anodic oxidation of Al, (10) 350*c*.
Dekker, P. Corrosion of enameled surfaces (I) enamels for sanitary ware, (10) 336*f*.
De Klerk, J. *C* axis flipping for multilayer piezoelectric thin-film transducers, (4) 109*h*.
Deksnys, A. See Tolutis, V.
De la Breteque, P. Process for purifying solutions containing aluminates, P (10) 349*e*.
De la Fuente, I. Studies of Philippine manganese oxides, (1) 23*d*.
De Lajarte, S. D. Glassworking apparatus with liquid seal, P (4) 99*e*. Manufacture of flat glass on a molten metal bath, P (5) 175*g*. Method and apparatus for manufacture of flat glass, P (2) 53*h*.
De Lajarte, S. D., and Bourgeaux, M. Method of and apparatus for the manufacture of flat glass on a molten metal bath, P (4) 99*e*.
Delaney, R. A., and Kaiser, H. D. Polycrystalline zinc oxide dielectrics, (4) 111*a*.
Delaney, R. A., and Williams, J. J., Jr. Thermistor and method of fabrication, P (8) 283*j*.
Delange, M., Huet, H., and Vertes, P. Method for the obtainment of uranium fluoride, P (2) 59*e*.
De Lange, M. H. Conversion to natural gas in the glass industry, (9) 305*f*.
Delarue, R. See Carpentier, S.
De Lau, J. G. M. High-frequency and microwave properties of hot-pressed fine-grained ferrites, (2) 62*e*. New methods for preparation of powdered ceramic compositions, (11) 379*f*.
Delchar, T. A., and Tompkins, F. C. Surface potential study of the chemisorption of hydrogen on nickel films, (9) 330*i*.
De Leeuw, G. See Benard, E. J. J.
De Leone, R. See Cogliati, G.
De Lisse, C. W. See Burgess, N. S., Jr.
Delivorias, P. Complementary MOS transistor integrated circuits with inversion layer formed by ionic discharge bombardment, P (11) 376*j*. Development of *p*-channel enhancement MOS triodes, (8) 280*j*.
Dell, R. M., Wheeler, V. J., and Bridger, N. J. Hydrolysis of uranium mononitride, (4) 139*a*.
Delmas, R. See Braun, C.
De Loach, B. C., Jr. Tunable crystal diodes, P (9) 314*c*.
De Loach, B. C., Jr., Gummel, H. K., and Scharfetter, D. L. Negative resistance microwave device, P (5) 184*b*.
Delrieux, J., Grollier-Baron, T., and Penez, A. Impurities and gases in fusion cast refractories, (9) 308*i*.
Delroy, W. See Thompson, S. P.
De Luca, J. P., Eagan, R. J., and Bergeron, C. G. Crystallization of $PbO{\cdot}2B_2O_3$ from its supercooled melt, (8) 276*d*.
Demarest, H. M., Jr. Load-bearing member for curved ceramic segments subjected to high compressive loads, P (9) 307*h*.
Demarest, P. C., and Karlson, K. Light bulb with a plurality of independently connected filaments for indicating graphic symbols, P (2) 65*h*.
De Maria, G. See Balducci, G.
De Maria, G., Balducci, G., Capalbi, A., and Guido, M. High-temperature mass spectrometric study of the system neodymium-carbon, (5) 195*e*.
Demas, N. P. Method for gettering completed gas filled lamps and the product resulting therefrom, P (7) 249*e*.
Dembinski, K. See Faucher, M.
Dembovsky, S. A. Elastic constants, softening temperature, and structure of chalcogenide glasses, (8) 276*f*.
Demchock, L. A., Jr. See Anderson, R. M.
Demekhin, V. F., and Sachenko, V. P. Relative intensities of $K\alpha$ satellites and the chemical bond, (4) 153*h*.
Dement'eva, S. D. See Sazhin, V. S.
DeMichelis, C. See Alcock, A. J.
Demichev, S. A. See Lipchanskaya, R. V.
Demonis, I. M. See Ezerskii, M. L.
Dempsey, E. See Kerr, G. T.
Dem'yanov, V. V., and Solov'ev, S. P. Investigation of dynamic polarization of ferroelectric materials, (2) 79*g*.
Denayer, M. See Nagels, P.
Denchick, F. A. See Warshaw, S.
Denes, P. A. Method of making a miniature magnetic core memory array, P (7) 257*f*.
Denisov, Yu. V., Dzhurinskii, B. V., and Kizel, V. A. Study of glasses in the system Na_2O-B_2O_3, activated by oxides of samarium, terbium, and dysprosium, (2) 51*d*.
Denisova, N. D. See Pustil'nik, A. I.
Denisova, N. D., Safronov, E. K., and Bystrova, O. N. System $ZrCl_4$-Al_2Cl_6, (8) 299*h*. Vapor pressures and heats of sublimation of the tetrachlorides of zirconium and hafnium, (8) 300*f*.
Denker, S. P. Cohesion in cubic refractory monocarbides, mononitrides, and monoxides, (5) 192*j*.
Denki Kagaku Kogyo Kabushiki Kaisha. Method of producing boron carbide, P (1) 14*j*.
Denman, R. R. Strengthened crystalline article and method of making the same, P (6) 213*f*.
Dennen, W. H. See Blackburn, W. H.
Dennert, H. Method and apparatus for heat-treating granulated expansible materials, P (7) 250*c*.
Dennert, H. V. Production of expanded clay pellets using the fluid bed process, (10) 348*g*.
Dennis, J., and Henisch, H. K. Nucleation and growth of crystals in gels, (4) 147*b*.
De Novion, C. H., and Lorenzelli, R. Electronic properties of neptunium monocarbide and mononitride, (10) 353*a*.
Dentists' Supply Co. of New York. Artificial ceramic tooth, P (9) 309*j*. Composite artificial tooth, P (5) 180*b*. Porcelain and resin tooth with silicon bonding agent, P (5) 180*d*. Tooth structure including means for chemically bonding diverse materials together, P (5) 180*d*.
Denton, D. See Corrigan, T. E.
Denton, I. E. Ceramic fuel materials, P (8) 279*a*.
Deo, P. G., and Kumar, S. Observation of dislocations in melt grown potassium chloride crystals using thermal etching, (10) 357*i*.
De Pape, R. See Portier, J.
De Pape, R., Tressaud, A., and Portier, J. Fluorine bronzes of composition M_xFeF_3 (M= Na,Rb,Tl), (2) 77*e*.
DePoorter, G. L. Evaluation of a statistical thermodynamic method for calculating the composition dependence of chemical potentials in nonstoichiometric zirconium carbide, (8) 292*d*.
Deportes, C. See Caillet, M.; Duclot, M.; Souquet, J. L.
Depoutot, R. See Flaks, S.
De Rango, C., Tsoucaris, G., Zelwer, C., and Devaux, J. Comparison of two refinements of the structure of kyanite, (1) 26*h*.
Deren, J., Novotny, J., and Zilokowski, J. Surface and bulk electronic properties of lithium-doped nickel oxide, (4) 111*c*.
Derevyankin, V. A. See Koryukov, V. N.
Derham, L. J., and Marriott, J. Production of zinc oxide, P (4) 125*f*.
Deri, M. Role of purposely produced alterations of crystal structure in the manufacture of ceramic products, (6) 220*j*.
Deribere-Desgardes, M. L., and Bre, M. M. Knowledge of the state of the surface of glass, (5) 204*i*.
Derjaguin, B. V., Fedoseev, D. V., Lukyanovich, V. M., Spitzin, B. V., Ryabov, V. A., and Lavrentyev, A. V. Filamentary diamond crystals, (7) 265*i*.
Derror, F. L. Method and apparatus for dusting mold cores, P (2) 60*j*. Method [casting] of making ceramic shapes, P (2) 61*a*.
Derse, P. See Chevallier, J.
Dersin, H. See Lochner, H. P.
Dersin, H., and Fruechte, E. Process of epitaxial growth wherein the distance between the carrier and the transfer material is adjusted to effect either material removal from the carrier surface or deposition thereon, P (5) 185*b*.
De Ruiter, J. W., and Willemstein, A. Methods [gas discharge] and arrangements for melting material which melts only with difficulty, P (7) 261*e*.
Desai, C. C. See Patel, A. R.
De Santis, P. Evidence of longitudinal magnetoelastic waves in YIG rods, (6) 232*e*.
Descamps, C. Radioisotopes for tagging foundry refractories, (2) 57*g*.
Deschamps, A., and Bernard, N. G. S. Ferromagnetic materials and processes for their manufacture, P (10) 344*i*.
Descurieux, S. See Mayaux, P.
De Sigoyer, Bruno de B. See Kingery, W. D.
De Silva, A. R. T. Theoretical analysis of creep in fiber-reinforced composites, (11) 368*j*.
Desmond, T. J., Greenberg, L. S., and Weisberg, H. High speed controlled rectifiers with deep level dopants, P (8) 282*j*.
De Sorbo, W. Magnetooptic glass body and electric circuit element in readout apparatus including the same, P (4) 99*a*. Superconductor quaternary alloys with high current capacities and high critical field values, P (4) 117*c*.
Desport, J. A. See Wilks, R. S.
Dess, H. M. See Fay, H.
DeSwardt, M. C. See Radmacher, H. W.
Detorre, R. P. See Insolio, T. A.
Detrick, R. S., and Gillespie, G. J. Method of resin impregnating a spool of fiber glass roving, P (9) 308*c*.
Dettingmeijer, J. H., and Meinders, B. Tungsten-oxygen-iodine system (I) tungsten dioxide (*s*) +iodine (*g*) = tungsten dioxide diiodide (*g*) equilibrium, (5) 202*b*.
Dettmann, L. See Thiele, K. H.
Deussner, H., and Schmitz, H. Apparatus for classifying particulate material, P (8) 284*d*.
D'Eustachio, D. See Johnson, H. E.
D'Eustachio, D., and Johnson, H. E. Arcuately shaped cellular glass article and method of making the same, P (11) 370*j*. Process for making cellular materials, P (7) 249*c*.
Deutsche Edelstahlwerke Akt.-Ges. Apparatus for compacting permanent magnet powders into pressings, P (4) 112*a*. Method and apparatus for compacting magnetic powder, P (1) 18*a*. Sintered [titanium] carbide hard alloy, P (9) 309*e*.
Deutsche Fafelglas Akt.-Ges. Detag. Method for sealing spacing members in a double or multiple glass pane assembly to the margins of the glass panes, P (1) 11*a*.
Deutsche Gold- und Silber-Scheideanstalt vorm. Roessler. Apparatus for the production of finely divided amorphous silica, P (5) 189*f*. Colloidal solutions of extremely finely divided oxides which are stable on storage and process for the production thereof, P (10) 349*b*. Noble metal alloy adapted to receive porcelain cladding, artificial dental constructions, and method of preparing the same, P (4) 109*b*. Process for producing finely divided precipitated silica, P (6) 230*c*. Process for producing sodium aluminum silicate pigments, P (5) 191*a*. Process for the production of extremely finely divided inorganic mixtures, particularly those containing silicon dioxide, P (6) 230*b*. Process for treating silicic acids and silicates, P (5) 191*a*. Production of boron nitride, P (4) 107*d*.
Devaux, J. See de Rango, C.
Devereux, O. F. Structure of reaction-formed alumina-silicon cermets, (4) 156*c*.
DeVilbiss Co. Self-cleaning tip for airless spray guns, P (4) 118*i*.
De Villiers, J. M., and Van Rooyen, T. H. Solid solution formation of lepidocrocite-boehmite and its occurrence in soil, (7) 268*f*.
Devlin, J. P. See Bruns, R.; Williamson, K.
Devreese, J. T. See Kartheuser, E.
Devreese, J. T., and Evrard, R. P. Investigation of the quadratic approximation in the theory of slow electrons in ionic crystals, (10) 356*b*.
DeVries, G. F. See Bertaut, E. F.
De Vries, J. See Blasse, G.
DeVries, R. C., and Roth, W. L. Critical evaluation of the literature data on beta alumina and related phases (I) phase equilibria and characterization of beta alumina phases, (9) 319*a*.
De Waal, H. Boric oxide anomaly in Nabal glasses, (11) 369*h*. Influence of proton exchange on internal friction in alkali silicate glasses, (6) 209*e*. Internal friction of sodium disilicate glass after ion exchange, (11) 370*f*.
Dewey, J. L. Vitrified products, P (7) 250*a*.
Dewhurst, J. R. See Andrews, R. W. J.
De Wijn, H. W., and de Wildt, J. L. Temperature dependence of nuclear quadrupole resonance in cuprous oxide, (4) 159*b*.
De Wijn, H. W., and Schrama, A. H. M. Spin Hamiltonian of $^{51}V^{2+}$ in MgO, as derived from electron nuclear double resonance, (9) 329*g*.
De Wildt, J. L. See de Wijn, H. W.
De Witt, D. See Napier, J.
De Witte, S. See Okaya, Akira.
Dews, J. N., and Schmersahl, G. W. Laboratory aerosol device, (5) 188*g*.
Dexco Corp. Abrading wheel structure, P (2) 43*g*.
Dexter, A. H. See Goosey, M. H.
Dey, S. K. Magnetic interactions in the system $(La,Gd)_2CoMnO_6$, (2) 80*b*.
Dgebuadze, T. P., and Mazurin, O. V. Use of dielectric loss method in the study of chemical inhomogeneities in sodium borosilicate glasses, (10) 338*c*.
Dhargupta, K. K., and Mukerji, J. Solubility dependence of ruthenium volatilization from glass, (10) 338*h*.
D'Heurle, F. M., Esaki, L., and Seki, Hajime. Schottky-barrier diode formed by sputter-deposition processes, P (9) 313*f*.
Dhillon, H. S. See Packter, A.
D'Huart, G. Method for surface working glass, P (8) 278*c*.
Diamond, S., and Kinter, E. B. Adsorption of calcium hydroxide by montmorillonite and kaolinite, (1) 24*g*.
Diamond Shamrock Corp. Inhibiting thermal decomposition of alkali metal silicates, P (4) 124*c*. Process for the production of calcium carbonate, P (8) 288*b*.
Diamond Tool Engineering Co. Method of sealing aluminum oxide bodies to metals, P (1) 18*e*.
Diatron Pacific. Process for manufacturing welding devices for semiconductors, P (11) 378*i*.
Di Bartolo, B. See Alam, A. S. M. M.
Dibdin, G. H. ESR of γ-irradiated single crystals of ice at 77°K—identification of the

hydroxyl radical and its trapping site, (5) 194*f*.

DiBenedetto, A. See Wambach, A.

Di Benedetto, B. A., and Mlavsky, A. I. Method of growing [piezoelectric] crystals, P (6) 225*c*.

Dibrov, G. D., Kuprii, Yu. M., Ostrikov, M. S., and Mirsoyanov, V. N. Change in strength of porous disperse bodies as a function of water content, (5) 192*i*.

Dick, E. See Peter, K.

Dick, E., and Peter, K. Generation of deep cracks in glass, (8) 276*a*.

Dickens, P. G., Heckingbottom, R., and Linnett, J. W. Calculation of the heats of formation of point defects in some transition metal oxides, (9) 318*j*.

Dickens, P. G., and Hurditch, R. J. X-ray and neutron diffraction study of a tetragonal hydrogen bronze H_xWO_3, (4) 164*e*.

Dickens, P. G., and Neild, D. J. Some electronic properties of the molybdenum bronzes, (8) 298*b*.

Dickens, P. G., Quilliam, R. M. P., and Whittingham, M. S. Reflectance spectra of the tungsten bronzes, (9) 328*i*.

Dicker, R. J. See Cragg, D. G.

Dickey, W. S., Clay Mfg. Co. and Clow Corp. Ceramic molding apparatus, P (10) 340*e*.

Dickinson, G. A., and Griffith, C. F. Composite tweel with internal suspension system, P (8) 277*h*.

Dickinson, G. A., Morgan, J. H., Thomas, J. E. C., and Oxley, B. W. Apparatus and method for manufacture of float glass with restricted lateral spread, P (6) 212*d*.

Dickinson, G. A., and Preston, A. Apparatus for manufacturing flat glass, P (6) 212*c*.

Dickinson, T. R. Method of patching ceramic lined equipment and patch therefor, P (4) 94*d*.

Dicks, L. W. R. See Barrer, R. M.

Dickson, E. J. Furnace roof hangers for refractory brick, P (1) 14*b*.

Dickson Electronics Corp. Irradiated temperature compensated Zener diode device, P (1) 18*i*.

Di Curcio, R. A. Process for making and testing semiconductive devices, P (11) 378*i*.

DiDomenico, M., Jr. See Wemple, S. H.

DiDomenico, M., Jr., Porto, S. P. S., and Wemple, S. H. Evidence from Raman scattering for an overdamped soft optic mode in $BaTiO_3$, (4) 135*j*.

DiDomenico, M., Jr., and Wemple, S. H. Calculation of the nonlinear optical tensor coefficients in oxygen-octahedra ferroelectrics, (4) 127*j*.

Didyk, W. See Sobel, I. J.

Diebold, E. J. High voltage diode for low pressure applications, P (2) 65*a*. High-voltage semiconductor device with electrical gradient-reducing groove, P (4) 113*b*.

Diefendorf, R. J. Metal boride-metal carbide-graphite deposition, P (11) 377*f*. Process for construction of high temperature capacitor, P (6) 223*g*.

Diehl, D. S. Semiconductor with trilayered metal contact, P (2) 66*f*.

Dielectric Systems, Inc. Monolithic ceramic electrical interconnecting structure, P (5) 184*j*.

Dieman, W. R., Lambden, R. L., and Pickles, A. Flexible shaping [flange] tool, P (9) 307*d*.

Diemer, G. *Pn* junction injection laser using a refractive index gradient to confine the laser beam, P (10) 345*e*.

Diemer, G., and van der Maesen, F. Insulated-gate field-effect transistor with widening current path between source and drain, P (7) 256*e*. Tapered insulated gate field-effect transistor, P (7) 258*b*.

Diesperova, M. I. See Bron, V. A.

Dietert, H. W. Method of and apparatus for premixing granular material additives, P (10) 346*i*. Volumetric measuring unit for materials, P (1) 20*g*.

Dietert, Harry W., Co. Method of and apparatus for premixing granular material additives, P (10) 346*i*. Volumetric measuring unit for materials, P (1) 20*g*.

Dietrich, R. V. Behavior of zirconium in certain artificial magmas under diverse *P-T* conditions, (4) 127*e*.

Dietrick, M. I. See Hood, R. T.

Dietsch, H. E., Gow, J., III, and Surty, R. J. Method of continuously curing resistor elements, P (11) 377*h*.

Dietz, A. See Wilson, W. L.

Dietz, A. G. H. (editor). Composite Engineering Laminates, B (11) 388*f*.

Dietze, W. See Amberger, E.

Dietzel, A. Effect of cobalt and nickel in ground coat and direct-on white enamels, (10) 336*g*. Mechanism of adherence for single layer, direct-on enameling, (10) 336*e*. Relation between phase diagrams, reaction kinetics, and structure of melts, (9) 307*a*. See Upadhyaya, V. G.

Dietzel, A., and Brueckner, R. Calculation of the viscosity-temperature curve of glass from fixed points, (4) 94*h*.

Dietzel, A., and Oel, H. J. Improvement of acid and alkali resistant enamels for the chemical processing industry by the use of oxides of the transition elements, (10) 336*j*.

Dietzsch, H. J. Apparatus for manufacturing ceramic elements having a honeycomb structure, P (2) 67*g*.

Diez, H. Proper media and compounds make mass finishing, (4) 89*f*.

Diez-Vilches, A. See Vian-Ortuno, A.

Dignam, M. J., and Fawcett, W. R. Kinetics and mechanism of oxidation of superpurity aluminum in dry oxygen (II) growth of crystallites of γ-alumina, (1) 31*e*.

Dignam, M. J., Fawcett, W. R., and Boehni, H. Kinetics and mechanism of oxidation of superpurity aluminum in dry oxygen (I) apparatus description and the growth of "amorphous" oxide, (1) 31*e*.

Dill, H. G. Field effect transistor having interdigitated source and drain and overlying insulated gate, P (4) 113*c*. Gate cooling structure for field-effect transistors, P (10) 344*j*. See Perkins, C. W.

Dillard, J. G., and Kiser, R. W. Ionization and dissociation of ruthenium and osmium tetroxides, (2) 79*i*.

Dillard, P. D. See Mills, W. H.

Dillman, N. G. Photosensitive semiconductor device for obtaining light source position data, P (8) 283*h*.

Dilloway, K. P. See Schenk, G. H.

Dilts, R. L. See Tien, Pei-Lin.

Dimarova, E. N., and Poplavko, Yu. M. Effect of a constant electric field on the thermal conductivity of ceramic samples ($BaTiO_3$-based solid solution) and of triglycine sulfate single crystals in the phase transformation region, (4) 132*j*.

Dimic, V. See Blinc, R.

Dimmock, J. O. See Donnelly, J. P.; Stillman, G. E.

Dimmock, J. O., Hurwitz, C. E., and Reed, T. B. Infrared transmission, magnetic birefringence, and Faraday rotation in EuO, (10) 355*h*.

Dingwall, A. G. F. Method of fabricating semiconductor devices, P (7) 257*b*. Thermoelectric device with graphite elements, P (9) 314*b*.

Dingwall, A. G. F., and Wilde, D. K. Thermoelectric device having a graphite member between thermoelement and refractory hot strap, P (8) 284*a*.

Dinner, H. See Filippi, L.

Dinnie, A. See Beard, R.

Dinsdale, A. See Webster, A. V.

Dinsdale, A., and Wilkinson, W. T. Strength of whiteware bodies, (2) 60*f*.

Diogenov, G. G., and Ermachkov, V. I. Systems Li,K,Cs‖Br and Li,K,Rb‖Br, (9) 331*g*. Systems Li,Na,Cs‖Br and Na,K,Rb‖Br, (9) 331*g*.

Dionis'ev, S. D. See Il'yasov, I. I.

Dionisotti, J., and Boehler, P. Cooling and suction device of an installation comprising a [rotary] furnace having at one side a burner producing a flow of hot gases and at the other side a distributor of material to be boiled, P (8) 286*f*.

Dionne, G. F., and Paul, P. J. Magnetic anisotropy and magnetostriction of $Y_2Mn_{0.1}Fe_{4.9}O_{12}$ at 300°K, (10) 356*f*.

Discry, H. Apparatus for the production of ribbed glass sheets, P (11) 370*j*.

Distillers Co., Ltd. Two stage heat treatment of cobalt molybdate catalysts, P (4) 126*a*.

Distler, G. I., Kobzareva, S. A., and Gerasimov, Y. M. Decoration of NaCl single crystal cleavage surface, covered by an amorphous carbon layer, by vacuum condensation of PbS, (6) 231*c*.

Distler, G. I., and Shenyaskaya, L. A. Polarization structure of interfacial amorphous films, (6) 220*i*.

Dithmar, K., and Koblischek, P. Colloidal solutions of extremely finely divided oxides which are stable on storage and process for the production thereof, P (10) 349*b*.

Ditrick, N. H. See Dawson, R. H.

Dittrich, F. J. Composite carbide flame spray material, P (4) 93*j*.

Dittrich, V. Methods for handling waste water and slimes, (10) 363*j*.

Ditz, J. See Neumann, J.

Divecha, A. P., Hahn, H., and Lare, P. J. Preparation of fiber-reinforced metal alloy composites by compaction in the semimolten phase, P (7) 253*a*.

DiVita, S. See Brandmayr, R. J.

Dixit, M. S. See Kessler, D.

Dixon, A. F., and Valdes, L. B. Controlled breakdown voltage diode, P (4) 112*c*.

Dixon, E. O. See Koester, C. J.

Dixon, J. K., LaMer, V. K., Li, C., Messinger, S., and Linford, H. B. Effect of the structure of cationic polymers on the flocculation and the electrophoretic mobility of crystalline silica, (1) 28*d*.

Dixon, J. R. See Schoolar, R. B.

Dixon, M. See Willis, J. B.

Dixon, S., Jr. Microwave power limiter comprising abutting semiconductor and ferrite elements, P (5) 184*i*.

Dixon, W. P. See Czyzz, P.

Dmitrevskii, G. E. See Sorokin, I. P.

Dobie, J. D. See Davis, J. H.

Dobo, I. Reliability of soil density measurements using nuclear methods for different soils, (5) 188*a*.

Dobos, G., Nemecz, E., Solymar, K., and Elek, S. Phase transformation in the complex processing of red mud, (6) 216*j*.

Dobretsov, N. L. Paragenetic types and compositions of metamorphic pyroxenes, (4) 148*d*.

Dobroghiu, E. See Cismaru, D.

Dobroklonskaya, N. S. See Krokhina, A. I.

Dobrovol'skii, A. G., and Nazarchuk, N. V. Slip casting of molybdenum disilicide, (2) 57*h*.

Dockerty, S. M. Glass rod and tube forming with controlled dimensional uniformity, P (4) 99*b*. Sheet glass forming apparatus with means to transform vertical flows into a horizontal flow, P (6) 213*e*.

Dodge, F. C. W., Papike, J. J., and Mays, R. E. Hornblendes from granitic rocks of the central Sierra Nevada batholith, California, (4) 138*h*.

Dodge, F. C. W., Smith, V. C., and Mays, R. E. Biotites from granitic rocks of the central Sierra Nevada batholith, California, (11) 383*c*.

Dodson, V. H., and Serafin, F. G. Mineral grinding aids, P (8) 288*c*.

Doerbecker, K., and Oel, H. J. Optical properties of ceramic glazes (II) experiments with polarized light, (6) 219*j*.

Doering, W. E., and Kegg, R. R. Method of fabricating transparent reinforced glass pipe, P (10) 339*a*.

Dogu, A., Val, C., and Accary, A. Application of a quantitative method of differential thermal analysis to the determination of formation enthalpies of U_3P_4 and UP_2, (10) 350*g*.

Doherty, C. J. See Wagner, R. S.

Doi, Akira. See Kato, Chuzo.

Doi, K. Atomic structure of amorphous ZrO_2, (1) 25*i*.

Doihara, Takeo. See Hayashi, Takeshi.

Doihara, Yoshio. See Hayashi, Takeshi.

Dojiva, C. See Vranka, L.

Dokukina, N. V., and Shamrai, F. I. Oxidation resistance of alloys based on tungsten and niobium silicides, (6) 216*h*.

Dolan, R. P., Jr., Buchanan, B. L., and Roosild, S. A. Process for implanting grids in semiconductor devices, P (6) 223*i*.

Dolan, R. P., Jr., and Roosild, S. A. Process for implanting buried layers in semiconductor devices, P (11) 378*h*.

Dolejs, V. See Kvapil, J.

Dolejsi, J. See Bohun, A.

Dolezsai, K., and Revay, M. Stability and stabilization possibility of products formed from the calcium aluminates of high-alumina cements by hydration, (2) 45*a*.

Dollimore, D. See Bonsall, P. C.; Broadbent, D.

Dollimore, D., Dollimore, J., and Perry, P. D. Thermal decomposition of the oxalates (VIII) thermogravimetric and X-ray analysis study of the decomposition of aluminum oxalate, (4) 160*j*.

Dollimore, D., and Nicholson, D. Thermal decomposition of oxalates (VI) decomposition and surface properties of ferric oxalate; (VII) effect of prior dehydration conditions upon the subsequent decomposition of cobalt oxalate, (1) 39*b*.

Dollimore, J. See Bonsall, P. C.; Broadbent, D.; Dollimore, D.

Dollish, F. R. See Hall, W. K.

Dolomite Franchi S.p.A. Refractory lining for arc furnaces adapted to facilitate dismembering on completion of a campaign, P (11) 375*c*.

Dolomitwerke G.m.b.H. Burner projecting into a rotary kiln, P (10) 348*c*. Manufacture of shaped refractories from dolomite, P (7) 252*b*.

Doman, R. C., Alper, A. M., and McNally, R. N. Periclase solid solutions containing Li^{1+} and R^{3+} ions, (9) 326*d*.

Domenico, R. J., and Lloyd, R. H. F. Thin film decoupling capacitor incorporated in an integrated circuit chip and process for making same, P (11) 379*c*.

Domine, D. See Berges, M. D.

Dominey, D. A. Reaction of boron carbide with oxygen and the effect of preirradiation in a nuclear reactor, (5) 199*j*.

Dompkowski, A. G. Apparatus for shaping and tempering glass sheets with means to transport the sheets therebetween, P (10) 338*g*.

Domtar, Ltd. Retarded gypsum plaster compositions, P (9) 304*d*.

Donaldson, E. M. Groves' method for determining ferrous oxide in refractory silicates, (8) 285*c*.

Donaldson, J. G., Stephenson, J. B., and Cochran, A. A. Boron and boron carbide by vapor deposition, (1) 4*b*.

Donaldson Co., Inc. Particle classification device and method, P (7) 259*e*.

Donati, E., Ferraresi, M., and Vantini, N. Conductometric determination of slag basicity, (2) 54*j*.

Donati, G., and Missiroli, A. Quantitative control of the chromatic behavior of enameled ceramic tiles of Italian manufacture (I, II), (9) 309*j*.

Donets, I. G. See Tresvyatskii, S. G.

Donnay, J. D. H. See Kennard, O.

Donne, W. Fluorescence radiation device radiating at 280 nm wavelength and method of making same, P (5) 188*f*.

Donnelly, J. P., Foyt, A. G., Hinkley, E. D., Lindley, W. T., and Dimmock, J. O. Type conversion and *pn* junctions in *n*-CdTe produced by ion implantation, (4) 163*a*.

Donner, E. B. Glass bottle handling apparatus, P (5) 174*e*.

Doo, V. Y. Monolithic silicon device containing

dielectrically isolating film of silicon carbide, P (1) 18*f*.
Doo, V. Y., Kerr, D. R., and Nichols, D. R. Property changes in pyrolytic silicon nitride with reactant composition changes, (4) 151*c*.
Doo, V. Y., Nichols, D. R., and Silvey, G. A. Preparation and properties of pyrolytic silicon nitride, (2) 82*d*.
Dooley, G. J. See Chiotti, P.
Dooley, P. C., Jr. Abrasive cutoff wheels, P (4) 89*g*.
Dooling, J. S. See Fresh, D. L.
D'Orazio, L. A., and Wood, R. H. Thermodynamics of the higher oxides (I) heats of formation and lattice energies of the superoxides of potassium, rubidium, and cesium, (1) 39*f*.
Doremus, R. H. Electrical conductivity and electrolysis of alkali ions in silica glass, (7) 247*g*. Electrical potentials of glass electrodes in molten salts, (5) 172*j*. Exchange and diffusion of sodium and silver ions in Pyrex glass, (2) 49*c*. Ion exchange with a two-phase glass, (5) 173*a*. Ionic transport in amorphous oxides, (4) 96*j*. Membrane potentials of Pyrex glass electrodes, (5) 173*e*.
See Laska, H. M.
Dorendorf, H., Ruechardt, H., and Rebstock, H. Semiconductor device with interelectrode capacitance compensation, P (1) 19*i*.
Dormer, G. Coated refractory metals beat heat and oxidation, (1) 4*d*.
Dornfeld, J. E., and Greenberg, J. Stacked mica capacitor having a multiple value mica film, P (1) 19*b*.
Doroszkowski, A., and Lambourne, R. Viscometric technique for determining the layer thickness of polymer adsorbed on titanium dioxide, (5) 188*c*.
Dorozhkin, N. N. See Boginskii, L. S.
Dorrian, J. F., and Newnham, R. E. Refinement of the structure of Li_2TiO_3, (10) 359*g*.
Dorr-Oliver, Inc. Filtration process with scraping and blowback cake removal, P (2) 74*a*. Wash arrangement for screen centrifuges, P (5) 191*g*.
Dorschu, K. E., and Rolnick, J. M. Welding electrode and composition, P (10) 337*d*.
Dorsey, J. J. See Pomerantz, D. I.
Dorst, M. Isostatic pressing in industry, (4) 108*i*.
Doser, M. See Gielisse, P. J.
Douglas, A. G. Tensile strength of granular materials, (4) 159*h*.
Douglas, E., and Walsh, T. Dry separation of mixtures of solid materials, P (8) 287*i*.
Douglas, F. C. See Batt, J. A.
Douglas, R. W. See Brown, D.; Moriya, Yoshiro.
Douglas, R. W., Duke, P. J., and Mazurin, O. V. Network contribution to the anelasticity of glasses, (6) 210*a*.
Douglas, T. B. See Krause, R. F., Jr.
Douglass, D. L., and Bronisz, S. E. Cavities in evaporated thin films of NpO_2, (8) 280*g*.
Douglass, D. L., and Wagner, C. Oxidation of oxygen-deficient zirconia and its relation to the oxidation of zirconium, (1) 34*b*.
Douma, G. H. Specific surface of heavy clays—measuring methods and significance, (11) 380*i*.
Douta, Kikuo; Matumaru, Haruo; and Nishimura, Takeo. Method of manufacturing integrated circuits, P (6) 222*c*.
Dove, V. See Ganley, W. P.
Dow Chemical Co. Coated glass article and process for making same, P (4) 98*i*. Foamable granule product with method of preparation and molding, P (11) 371*f*. Hyperconductive graphite structures, P (2) 58*g*. Method for making porous structures, P (7) 252*f*. Method of preparation of compressed vermicular graphite, P (9) 309*g*. Method for preparing compressed vermicular graphite structures, P (7) 252*h*. Method of preparing manganese dioxide, P (7) 263*a*. Method of preparing magnesium hydroxide, P (9) 317*e*. Method for producing carbon-bonded graphite structures, P (8) 279*h*. Method for producing low density graphite structures, P (4) 107*a*. Method of separating magnesium and calcium values from calcium and magnesium carbonates, P (4) 125*b*. Perlite composition, porous low density perlite structure, and method of making same, P (8) 278*i*. Process for preparing compounds containing silicon and fluorine, P (10) 349*b*. Process for preparing resilient graphite structures, P (5) 179*b*. Process for producing structures containing shaped voids, P (6) 218*b*. Process for removing polyvalent metal impurities from lithium aluminate, P (9) 317*e*. Production of low density rigid shapes, P (5) 176*g*. Removal of halide ions from crude lithium aluminate, P (9) 317*f*. Vitrified products, P (7) 250*a*.
Dow Corning Corp. Aminoalkyl silicone glass [fiber] lubricant, P (11) 370*h*. Coating of objects with tetraboron silicide, P (10) 344*d*. Coating with silicon carbide by immersion reaction, P (10) 342*c*. Large volume semiconductor coating reactor, P (11) 377*b*. Manufacture of silicon carbide ribbons, P (8) 279*e*. Method of growing thin film semiconductors using an electron beam, P (4) 114*j*. Treatment of glass with silsesquioxanes to improve durability of subsequent silicone treatments to washing, P (8) 278*c*.
Dowd, J. See Loewenstein, K. L.
Dowley, A. See Meadows, F. W.
Dowling, J. H. School complex uses 100 tile combinations, (4) 102*g*.
Downie, P. M. See Smith, D. L.
Downs, A., and Maclean, C. Welding thermocouples, P (5) 188*i*.
Doyle, C. F., and Becker, D. L. Fluid energy mill, P (5) 186*f*.
Doyle, G. A. See Woulbroun, J. M.
Doyle, N. J. See Taylor, A.
Doyle, W. F. Weld backing member and method of forming welded joints in metallic members or between metallic members, P (6) 208*c*.
Drabble, J. R., and Brammer, A. J. Third order elastic constants of gallium arsenide, (4) 162*i*.
Drabble, J. R., and Palmer, A. W. Method of growing a crystal or crystalline layer by means of a direct current arc discharge, P (8) 282*j*.
Draghici, I. See Spinulescu-Carnaru, I.
Dragoman, I., and Camerman, C. Behavior of refractory products in CO atmosphere, (10) 340*f*.
Drahovzalova, M. See Litomisky, J.
Drake, C. F., Scanlan, I. F., and Alexander, J. H. Glassy bistable electrical switching and memory device, P (7) 256*j*.
Drake, E. G., and Frechette, M. Method and apparatus for treating particulate material in a fluidized bed, P (7) 259*b*.
Drake, L. C. Conversion of ammonium aluminosilicate to hydrogen aluminosilicate, P (4) 124*j*.
Draley, J. E. See Levitan, J.
Dransfeld, K. See Salzmann, E.
Dravo Corp. Percussion drill bit for shattering hard formations, P (2) 74*a*. Process for pickling of steel strip and regeneration of the contact acid, P (8) 275*h*.
Dreeben, A. Direct observation of precipitate phenomena and dislocations in annealed CdS:Cu and CdS:Au single crystals, (4) 131*i*. Effects of growth conditions on microstructures in CdS:Cu single crystals, (2) 76*g*.
Dresher, W. H. See Naumann, A. W.; Woolery, R. G.
Dresher, W. H., and Naumann, A. W. Chrysotile asbestos fiber dispersion including monocarboxylic acid, P (2) 74*a*.
Dresner, J. Photoconductive device having a target including a selenium blocking layer, P (2) 66*c*.
Dresser Industries, Inc. Aluminosilicate refractory brick, P (5) 178*j*. Carbon baking furnaces, P (9) 309*e*. Checkerbrick and checkerwork construction for regenerators, P (7) 252*f*. Continuous casting of steel, P (4) 93*j*. Dome-shaped electric furnace roof construction, P (9) 309*e*. Electric furnace having refractory brick of specific composition in the critical wear areas, P (1) 13*j*. Elements for the support of refractory anchors, P (4) 106*f*. Flotation process, P (5) 190*i*. Furnace construction, P (1) 14*a*. Furnace roof construction [contour controlled], P (10) 342*d*. Inclined kiln, P (7) 261*c*. Induction furnace, P (1) 14*c*. Induction furnace construction, P (6) 217*c*. Induction furnace having a composite lining composed of refractory brick, P (1) 14*d*. Insulating refractories, P (4) 106*b*. Lightweight refractory brick and aggregate, P (7) 252*b*. Method of slip casting basic refractory materials, P (4) 107*f*, P (9) 309*a*. Monolithic refractory, P (6) 218*e*. Phosphate-impregnated magnesite brick, P (9) 309*b*. Precision casting, P (1) 14*b*. Preformed refractory block for strip heating furnaces, P (1) 14*c*. Process for the production of caustic calcined magnesia, P (6) 230*a*. Production of magnesium hydroxide from aqueous solutions containing magnesium and boron values, P (5) 191*c*. Recovery of clay and sand from an ore, P (5) 191*c*. Refractory coated composite oxygen lance, P (6) 208*b*. Refractory shapes coated with organic material, P (10) 343*b*. Rotary kiln construction, P (5) 189*f*. Tar impregnated fused silica stopper head, P (6) 218*g*. Waterless molding sand, P (6) 218*i*.
Dressler, P. d'Huc. Recuperation—the key to 40–80% fuel savings, (8) 286*d*.
Drever, J. I. Separation of clay minerals by continuous particle electrophoresis, (11) 380*g*.
Drews, R. E., Davis, E. A., and Leiga, A. G. Reflectivity spectra of $Cd_{1-x}Zn_xS$ single crystals, (4) 153*g*.
Dreyfus, B. A. Electrical film resistors, P (7) 256*e*. Preparation of tin oxide resistances, P (1) 19*b*.
Drickamer, H. G. Effect of interionic distance on the ligand field in NiO, (4) 132*j*. See Lewis, G. K., Jr.; Vaughan, R. W.
Driessens, F. C. M., and Rieck, G. D. Phase equilibria in the system Cu-Mn-O, (6) 235*j*.
Driffort, J. P. See Cahen, R.
Driscoll, J. L., and Evans, P. E. Solid state preparation of uranium monophosphide, (8) 279*d*.
Driver Southall, Ltd. Automatic weigher with rapping means to aid discharge of materials, P (1) 20*d*.
Drobek, J. See Dalton, J. V.; Schmidt, P. F.
Drobot, D. V. See Korshunov, B. G.
Dropkin, D., O'Connor, T. J., Cass, L. A., and Comfort, E. H. High temperature probe, P (10) 347*i*.
Drossbach, P., and Hoff, H. Oxygen overvoltage on graphite electrodes in fused salts, (6) 216*i*.
Drost, W. Desiccant bodies, P (8) 287*i*.
Drowart, J. See Coppens, P.; Pattoret, A.
Drowart, J., Coppens, P., and Smoes, S. Dissociation energy of the molecule TiO(*g*) and the thermodynamics of the system titanium-oxygen, (11) 383*i*.
Drowart, J., Pattoret, A., and Smoes, S. Mass spectrometric studies of the vaporization of refractory compounds, (5) 196*j*.
Drozdova, L. N. See Mordovin, O. A.
Drum, C. M., and Clark, C. A. Geometrical stability of shallow surface depressions during growth of (111) and (100) epitaxial silicon, (9) 322*a*.
Druminski, M. See Amberger, E.
Drummond, E. L., and Drummond, M. E. Microhematocrit tube sealer, P (4) 100*d*.
Drummond, M. E. See Drummond, E. L.
Drummond Scientific Co. Microhematocrit tube sealer, P (4) 100*d*.
Dryden, H. L. Ceramic-to-metal seal and method of making same, P (4) 93*e*.
Dryon, J. M. C. Apparatus for the horizontal stacking of [glass] sheets of rigid material, P (4) 98*d*. Device for handling [glass] sheet materials, P (4) 98*b*.
Dubble, R. D., and Alten, E. H. Method and means for vapor coating, P (7) 249*h*.
Dubinin, M. M. See Belen'kaya, I. M.
Dubinina, E. M. See Spivak, G. V.
DuBois, D. F. See Picus, G. S.
Dubois, M. See Jegou-Vilnat, J.
Dubovik, A. S. Photographic Recording of High-Speed Processes, B (4) 167*f*.
Dubovik, T. V. See Pechentkovskaya, L. E.
Dubovik, T. V., and Struk, L. I. Electric insulation tube of boron carbonitride for protection of metal thermocouples, (6) 215*g*.
Duc, T. Q. See Durif, A.
Ducarroir, M. Reactions occurring on solar bot front and their use for pyrocarbon production, (5) 178*c*.
Du Chaffaut, F. See Gillot, J.
Duclot, M., Vitter, G., and Deportes, C. Mercury pycnometer for the precise determination of apparent specific gravity of oxide refractory samples, (7) 260*h*.
Ducommun, Inc. Anisotropic continuous casting mold, P (7) 252*c*. Anisotropic [pyrolytic graphite] mold liner for continuous casting of metals, P (5) 178*j*. [Graphite] liner for smoking pipe, P (5) 178*g*.
Dudareva, A. G. See Fedorov, P. I.
Dudnik, E. M. See Samsonov, G. V.
Dudnik, E. M., and Oganesyan, V. Kh. Thermal expansion of some sulfides of the transition metals, (1) 39*d*.
Dudzik, C. J., and Perkins, G. E. Glass yarn having controlled torsional forces, P (6) 212*f*.
Duemecke, G., and Gersoene, H. Experiences with the direct spectrochemical analyzer DSA 24 for the quantitative spectral analysis of silicates, (10) 347*g*.
Duff, E. J. Magnetic interactions in the olivine structure, (5) 196*b*. System magnesium oxide-silica, (8) 299*e*.
Duffy, J. A. Spectroscopic study of molybdenum(V) in a bisulfate melt and glass, (6) 211*f*. See Ingram, M. D.
Duffy, J. A., and Ingram, M. D. Formation of acetate glasses, (6) 209*b*.
Duffy, M. C. See Armstrong, W. J.
Duffy, W. B. See Atluri, S. R.
Duga, J. J. See Bonis, L. J.
Dugge, R. H. See Stine, C. K.
Duggin, M. J. Tetragonal and hexagonal iron-manganese carbides, (7) 270*f*. Thermally induced phase transformations in iron carbides, (4) 161*d*.
Duke, M. B. See Finkelman, R. B.
Duke, P. J. See Douglas, R. W.
Dulin, F. H. See Rea, R. F.
Duma, G., and Lengyel, I. Demonstration of the presence of blood in the ceramic body of antique pottery, (6) 205*j*, (9) 303*f*.
Dumanchin, R. Laser deflector having a nonuniform field applied to an electrooptic crystal, P (11) 377*b*.
Dumas, J. P. See Lerner, P.
Dumbaugh, W. H., Jr. Low thermal expansion glasses, P (2) 53*e*.
Dumesnil, M. E. Low melting oxide glass, P (2) 53*d*. See Pilling, D. J.
Dumin, D. J. Epitaxial growth of germanium on single crystal spinel, (4) 135*c*. See Robinson, P. H.
Dumitrescu, M. See Huber-Panu, I.
Dumler, J. T. See Vanderheiden, D. B.
Duncan, J. F., MacKenzie, K. J. D., and Foster, P. K. Kinetics and mechanism of high-temperature reactions of kaolinite minerals, (4) 142*e*.
Duncan, J. F., and Stewart, D. J. Kinetics and mechanism of formation of zinc ferrite, (4) 142*c*.
Duncan, J. H., and Creyke, W. E. C. Formation and stability of β-Al_2O_3 in α-Al_2O_3 ceramics, (10) 354*d*.
Duncan, R. F. Economics of one-way glass beverage containers, (10) 337*h*.
Dundee Cement Co. Process for forming special cements, P (7) 245*d*.

Dunham, A. C. See Kaye, M. J.

Dunicz, B. L. Cage structure for polyborate ions, (4) 127*g*.

Dunkle, R. B. Metalization of silicon semiconductor devices for making ohmic connections thereto, P (10) 345*e*.

Dunlap, C. K., Jr. See Cunningham, M. B.

Dunlevy, B. O., and Harper, L. E., Jr. Liner for crucibles, P (1) 14*e*.

Dunn, W. W., McLellan, R. B., and Oates, W. A. Solubility of carbon in cobalt and nickel, (4) 155*f*.

Dunne, B. B. Shock wave optically pumped laser, P (9) 314*b*.

Dunning, W. J. Structure of crystal surfaces, (1) 38*h*.

Dunnington, B. W. Process for sintering diamond particles, P (1) 1*j*. See Cowan, G. R.

Dupart, E. See Marchand, A.

Dupin, J. L. See Portier, J.

Du Pont de Nemours, E. I., & Co. Acid-reacting ceramic grade anatase (TiO_2) pigment, P (11) 382*g*. Alumina-spinel composite material, P (7) 243*h*. Capacitor dielectric compositions and capacitors made therefrom, P (7) 255*h*. Cermets of aluminum with titanium carbide and titanium and zirconium borides, P (11) 374*g*. Cobalt-bonded tungsten carbide, P (10) 335*h*. Composite vitreous enamels and their preparation, P (8) 275*c*. Compositions, P (4) 112*j*. Copper/vanadium oxide compositions, noble metal metalizing compositions containing vanadium oxide additives, and electrical conductor elements made therewith, P (7) 256*d*. Dense products of vanadium or zirconium nitride with iron, nickel, or cobalt, P (2) 58*b*. Fluid energy milling process, P (11) 379*f*. Glass laminate, P (6) 212*d*. Glass laminate and interlayer, P (7) 248*h*. Glass-polyurethane-polyvinyl butyral-polyurethane-glass laminate, P (11) 371*i*. Hot-pressing process, P (4) 118*e*. Inorganic blue to green pigments, P (9) 317*d*. Isostatic hot-pressing of refractory bodies, P (10) 342*f*. Low pressure synthesis of electrically conductive platinum cobalt oxide from a platinum halide and an oxide containing cobalt, P (4) 113*j*. Magnesium surface for cooling TiO_2, P (8) 287*i*. Metal bonded silicon nitride, P (2) 58*j*. Metalizing compositions containing critical proportions of metal (Pt-Au or Pd-Au) and a specific high density frit, P (7) 256*j*. Metallic [boride] refractory compositions, P (10) 342*i*. Nitride-refractory metal compositions, P (2) 59*h*. Nitrides plus wear-resistant additives bonded with iron, cobalt, or nickel, P (2) 59*a*. Noble metal metalizing compositions, P (9) 313*j*. Opacifying pigment glass composition, P (11) 372*c*. Polyurea bonded sand foundry cores, P (10) 343*a*. Porous silica coated titanium dioxide pigment, P (4) 125*f*. Preheating oxidizing gas reactant in TiO_2 pigment manufacture, P (9) 317*a*. Preparation of ferromagnetic chromium dioxide, P (5) 184*i*. Preparation of ferromagnetic CrO_2 by heating CrO_3 in the presence of O_2 and Cr_2O_3, P (9) 317*b*. Preparation of MCr_3O_8, where M is an alkali metal, from CrO_3, Cr_2O_3, and $M_2Cr_2O_7$, P (9) 317*c*. Preparation of metal nitrides, P (9) 309*c*. Preparation of silica sols of minimum turbidity, P (7) 263*c*. Preparation of zirconia and hafnia sols, P (8) 288*c*. Process for chlorinating titaniferous ores, P (4) 125*i*. Process for coating metal articles employing fluidized bed, P (2) 46*e*. Process for making porous lightweight zirconia bodies, P (5) 179*b*. Process for preparing chromium dioxide and product thereof, P (9) 317*c*. Process for producing titanium dioxide pigments, P (4) 125*b*. Process for sintering diamond particles, P (1) 1*j*. Process for synthesizing diamond, P (1) 20*f*. Rare earth silicate phosphor composition, P (1) 19*g*. Single crystals, P (7) 258*f*. Surface modified electrostatic enamel powders and method, P (1) 5*g*. Surface treating pigments with hydrous metal oxides, P (4) 126*a*. Thermistor compositions and thermistors made therefrom, P (2) 66*i*. Thermocouple reference junction compensating circuits, P (11) 381*d*. Thoria/europium fluoride luminophors, P (2) 66*j*. Thoria/terbium fluoride luminophors, P (2) 66*j*. TiO_2 production by chromium removal from beneficiated titaniferous ore, P (5) 191*g*. Titanium dioxide pigment coated with silica and alumina, P (7) 263*d*. Titanium pigment manufacture, P (11) 383*a*.

Dupuy, C. Rubidium and cesium in biotite, sanidine, and glass in Tuscany ignimbrites, Italy, (9) 329*d*.

Dupuy, C., and Schaeffer, B. Influence of color centers on the plastic deformation of halide crystals, (2) 78*j*.

Dupuy, J. See Ruch, J.

Durand, P. Gyratory crushers, P (5) 190*j*.

Durant, B. G. See Miller, C. F.

Durbin, H. A., and Pledger, T. R. Method and apparatus for testing hermetically sealed transistor devices, P (4) 114*h*.

Durham, J. L. See Barto, J.

Durif, A. See Averbach-Pouchot, M. T.; Joubert, J. C.; Lauegt, M.

Durif, A., Grenier, J. C., Joubert, J. C., and Duc, T. Q. Crystallographic structure of the orthovanadate of lithium and copper, $LiCuVO_4$, (2) 75*i*.

Durkee, F. P. Yttrium vanadate europium phosphor preparation by precipitaton using ammonium carbonate, P (7) 258*e*.

Durmann, G., and Longo, F. N. Plasma-sprayed alumina-titania composite, (5) 171*i*.

Duro-Test Corp. Incandescent lamp with addition of fluorine compounds to the operating gas filling, P (4) 99*j*. Machine for forming helical grooves in thin wall glass tubing, P (1) 11*b*. Metal vapor lamp with metal additive for improved color rendition and internal self-ballasting filament used to heat arc tube, P (8) 282*e*.

Dushina, A. P. See Smirnova, M. F.

Dusi, G. See Amato, I.

Dusollier, G. Application of the X-ray fluorescence contact radiographic method to the study of some diffusion phenomena in glass, (2) 46*g*.

Duthoit, J. See Plumat, E.

Dutta, S. K., and White, J. Compatibility relationships of uranium carbides with alloys of iron, nickel, and chromium, (4) 129*f*.

Dutz, H. Infrared spectroscopy of crystalline silicates, (11) 380*g*.

Duval, R., Pichoir, R., and Roques, B. Influence of allotropy on the silicidation of molybdenum and its alloys, (9) 304*j*.

Duval Corp. Method of producing ammonium sulfate, potassium sulfate, and magnesium oxide from langbeinite, P (7) 263*b*.

Duvall, J. L., and Otrhalek, J. V. Abrasive cleaning compositions, P (11) 367*f*.

Dvernyakova, A. A. See Belyakova, E. P.

Dvorakova, I. See Hanykyr, V.

Dvorina, L. A. Preparation of silicides of the rare-earth metals, (6) 216*a*.

Dyke, F. H., Jr. How to Manage and Use Technical Information, B (2) 85*g*.

Dykstra, L. See Ruka, R. J.

Dynamit Nobel Akt.-Ges. Method of producing electromagnesia having improved electric insulating power, P (9) 317*f*.

Dyson, N. F. See Scott, T. R.

Dyukov, V. G. See Spivak, G. V.

Dzhurinskii, B. V. See Denisov, Yu. V.

Dziedzic, J. M. See Bergman, J. G.

Dzurinskii, B. F. See Tananaev, I. V.

Eagan, R. J. See De Luca, J. P.

Eakins, W. J. Method of making improved glass fiber material and laminates thereof, P (9) 308*a*.

Eakins, W. J., and Humphrey, R. A. Glass-resin composite structure, P (5) 174*j*.

Eales, B. See Verderber, R. R.

Eanes, E. D., and Posner, A. S. Intermediate phases in the basic solution precipitation of alkaline earth phosphates, (5) 195*g*.

Eardley, R. P., and Mountford, A. H. Atomic Absorption Spectrophotometry in Ceramic Analysis—Evaluation of Some Commercial Spectrophotometers, B (4) 165*a*.

Eargle, F. L. How to analyze brick plant costs, (6) 214*b*.

Earl, J. A. Ceramic material, P (10) 337*d*. Ceramic material and method, P (8) 282*c*.

Easey, J. F. See Bagnall, K. W.

Easley, W. See Edelstein, N.

Eastman Kodak Co. Ceramic packing material for the prevention of methacrylate and acrylate ester polymerization, P (2) 67*g*. Hot-pressed polycrystalline laser material, P (10) 339*g*. Hot-pressing titanium dioxide, P (11) 371*a*. Lanthanum fluoride infrared transmitting optical elements, P (7) 249*a*. Method of forming zinc oxide infrared transmitting optical element, P (4) 99*i*. Method of forming zinc selenide infrared transmitting optical elements, P (10) 339*a*. Method for preparing pure stable ZnSe powder, P (10) 349*c*. Process of hot-pressing magnesium oxide infrared transmitting optical elements, P (1) 11*c*.

Eastwood, F. Apparatus for forming hot top liners, P (7) 252*c*.

Eastwood, F., Brindle, J. H., and Kolb, F. L., Jr. Hot top for big-end-up ingot molds and method of assembling same, P (11) 374*j*.

Eaton, E. P., Jr. See Smith, W. H.

Eaton Yale & Towne, Inc. Method and apparatus for cleaning foundry cores, P (10) 342*i*. Process for making permanently backed shell molds, P (8) 279*j*.

Eaves, C. A. See Seidel, J.

Ebata, Yoshihiro; Kinoshita, Makoto; Kadota, Masatane; and Kitaoka, Takeshi. Effect of kaolin addition on metalizing of CuS with alumina, (2) 62*b*.

Ebel, H., and Effenberger, E. X-ray determination of grain size between 10^4 and 10^5 Å, (2) 71*f*.

Ebel, H., Wagendristel, A., and Maix, R. Determination of grain size by means of X-ray absorption, (2) 69*i*.

Eberhart, J. G. Critical surface tension of uranium dioxide, (5) 193*g*.

Eberspacher, O. See Will, G.

Ebert, E., and Spielmann, W. K. Method of etching SiC, P (5) 183*d*.

Ebert, M. Secondary emission cathode or dynode of a porous matrix of tungsten or molybdenum impregnated with secondary emission material such as a tungstate or an alkali halide of calcium, P (11) 378*b*.

Ebisawa, Yasuo. Production method of semiconductor devices, P (4) 116*c*.

Ecart, J. Basic refractories, (1) 8*e*.

Eckerlin, P. System Be_3N_2-Si_3N_4 (IV) crystal structure of $BeSiN_2$, (8) 299*b*.

Eckerlin, P., Rabenau, A., and Nortmann, H. System Be_3N_2-Si_3N_4 (III) preparation and properties of $BeSiN_2$, (8) 299*b*.

Eckert, J. S. Method and apparatus for comminution, P (5) 186*c*.

Eckert, J. S., and Moore, F. D. Ball mill drum [design], P (10) 346*h*.

Eckert, O., and Stark, K. Electroless formation of electrical resistance films, P (1) 18*e*.

Eckhardt, H. A. Apparatus for feeding particulate materials, P (4) 118*a*.

Eclipse Fuel Engineering Co. Gas burner, P (2) 72*c*. Mounting for replaceable gas burner, P (2) 72*e*. Nozzle mixing gas burner, P (4) 123*b*. Radiant spiral flame gas burner, P (5) 189*f*.

Economy, J., and Anderson, R. V. Boron nitride fiber manufacture, P (6) 217*h*.

Edelson, D., Jaeger, R. E., and Williams, J. C. Transient effects of nuclear radiation on the dielectric properties of refractory low-loss ceramics at microwave frequencies, (9) 311*g*.

Edelson, M. R., and Angstadt, R. L. Cement set retarder, P (5) 170*e*.

Edelstein, N. See McLaughlin, R.

Edelstein, N., and Easley, W. Zero-field splittings of Am^{3+} and Cm^{3+} in cubic symmetry sites in CaF_2, (4) 164*c*.

Eden, D. D. Photoconductive electrooptic image intensifier utilizing polarized light, P (9) 313*b*. Solid-state crystal optical modulator, P (7) 258*a*.

Edgecombe, D. A., Marshall, H. W., and Evans, S. O. Hot drawing tubes, P (1) 10*i*.

Edgecombe, D. A., Trees, J. S., and Gioffre, V. C. Method and apparatus for descaling billets, P (4) 94*c*.

Edmeades, R. M., James, A. N., and Wheeler, J. Formation of ettringite on aluminum surfaces, (2) 44*b*.

Edmister, W. H. See Wosinski, J. F.

Edmonds, C. S. See Bauleke, M. P.

Edmonds, D. V., and Beevers, C. J. Effect of inclusions on the stress distribution in solids, (8) 291*e*.

Edmonds, H. See Griffin, R. S.

Edmondson, W. See Jones, P. M. S.

Edqvist, O., Svedberg, P., and Vedin, B. A. Thyristor with positively bevelled junctions, P (7) 258*c*.

Edwards, A. J., and Jones, G. R. Fluoride crystal structures (I) tungsten oxide tetrafluoride, (5) 194*i*; (III) rhenium oxide tetrafluoride, (8) 292*h*.

Edwards, A. J., and Steventon, B. R. Fluoride crystal structures (II) molybdenum oxide tetrafluoride, (8) 292*g*.

Edwards, G. C., and Angstadt, R. L. Effect of some soluble inorganic admixtures on the early hydration of portland cement, (2) 44*i*.

Edwards, J. A. See Aitken, E. A.

Edwards, J. W., and Coffey, R. B. Coated optical devices, P (5) 174*a*.

Edwards, R. See Arnold, S. R.

Edwards, R. H. Manufacture of alkali metal phosphates, P (5) 191*a*.

Edwards, R. K. See Battles, J. E.

Edwards, W. D. Distribution coefficient of oxygen in germanium, (11) 383*j*.

Edwards High Vacuum International, Ltd. Apparatus for measuring optical characteristics of coatings on lenses, P (8) 277*g*.

Effenberger, E. See Ebel, H.

Efimov, A. I. See Shchukarev, S. A.

Efremenkova, V. I. See Gladneva, L. I.

Egerton, L., and Bieling, C. A. Isostatically hot-pressed sodium-potassium niobate transducer material for ultrasonic devices, (1) 17*d*.

Eggert, W. C. See Kratochvil, R. F.

Ehlbeck, H. W. See Gerstner, D.

Ehlers, E. G. Discussion of "Technique for estimating thickness of a thin section," (10) 347*f*. See Birle, J. D.

Ehrenberg, N. S. Method of mounting semiconductor devices on thick film circuits, P (11) 377*f*.

Ehrig, R. See Schier, K. H.

Ehrlinger, H. P., III. See Bohor, B. F.

Eibschuetz, M., and Ganiel, U. Moessbauer studies of Fe^{3+} in paramagnetic fayalite (Fe_2SiO_4), (4) 145*g*.

Eibschuetz, M., Ganiel, U., and Shtrikman, S. Measurement of trigonal field splitting of Fe^{3+} in $GeFe_2O_4$ by the Moessbauer effect, (4) 143*e*.

Eichelberger, W. E. Miniature pressure transducer, P (7) 257*e*.

Eichenberger, W. W. Process for making sand molds, P (6) 218*h*.

Eick, G. H. See Stone, J. N.

Eick, H. A. See Haschke, J. M.; Raccah, P. M.; Sturgeon, G. D.

Eicker, R. Furnace for ceramic dental products, P (7) 261*i*.

Eigner, E. Improving the grinding process in drum mills, (6) 224*h*.

Ellerman, G. E. See Killmeyer, C. W.

Ellerman, G. E., Sanguigni, J. A., Klock, R. L., Fasnacht, J. J., and McWilliams, D. E. Forming glass fiber with combination resin coating, P (7) 248*g*.

Einstein, E., and McCreight, D. O. Insulating refractories, P (4) 106*b*.

Einthoven, W. G. High-voltage transistor with controlled base and collector doping and geometry, P (9) 312*b*.

Eipeltauer, E. Physicochemical studies on aluminosilicate glasses, (4) 96*j*.

Eischens, R. P. See Smith, D. M.
Eisentraut, K. J., and Sievers, R. E. Separation of chelates of rare earth compounds and promethium by fractional sublimation, P (6) 240*b*.
Eisentrout, C. H. Industrial furnace burner, P (6) 228*g*.
Eisenwerke-Gesellschaft Maximilianshutte m.b.H. Method of producing steel for sheets to be enameled by the single-coat method, P (4) 94*e*.
Eitel, W. Silicate Science (Vol. I) Silicate Structures; (Vol. II) Glasses, Enamels, Slags; (Vol. III) Dry Silicate Systems; (Vol. IV) Hydrothermal Silicate Systems; (Vol. V) Ceramics and Hydraulic Binders, B (2) 85*h*.
Ejiri, Koichi. See Setaka, Nobuo.
Ekdahl, W. G. Apparatus for delivering molten materials, P (5) 189*f*. Refractory fibers for service to 2700°F, P (9) 309*d*.
Ekkerman, V. M. See Gel'fman, A. Ya.
Eibern, V. H. Group of pseudo-ancient glass vessels from Italy, (4) 90*h*.
Eldridge, G. See Chernow, F.
Electra Midland Corp. Method of making a precision electric fuse, P (1) 18*c*.
Electric Furnace Co. Furnace heating control, P (9) 316*d*.
Electric Reduction Co. of Canada, Ltd. Blending apparatus for solids, P (4) 118*b*. Manufacture of alkali metal phosphates, P (5) 191*a*.
Electro-Optical Systems, Inc. Ion laser having a metal tube shrink-fitted onto the ceramic discharge tube, P (7) 256*f*. Method for detection of ultraviolet radiation, P (8) 286*c*. Production of semiconductor devices by use of ion beam implantation, P (8) 283*j*.
Elek, S. See Dobos, G.
Elektriska Svetsningsaktiebolaget. Arc welding flux and method of manufacturing the same, P (4) 93*a*, *e*. Method of making coated arc welding electrodes, P (9) 304*i*.
Elektroschmelzwerk Kempten G.m.b.H. Boron-carbon-silicon alloy and method of producing the same, P (8) 279*j*. Process for the manufacture of alkali metal borides, P (1) 24*d*.
Elemelt, Ltd. Furnaces for heating glass electrically, P (7) 248*h*. Method of melting and supplying glass along a feeder duct, P (1) 11*e*.
Ellert, G. V. See Zhabotinskii, M. E.
Ellington, J. P. Nuclear reactor fuel elements, P (6) 218*f*.
Elliot, J. C., and Young, R. A. Conversion of single crystals of chlorapatite into single crystals of hydroxyapatite, (4) 129*j*.
Elliott, C. H., Jr. Process for preparing molecular sieves, P (1) 24*b*.
Elliott, James F. Piezoresistive thermometer, P (2) 66*e*.
Elliott, John F. See Larson, H. R.; Sodi, J.
Ellis, J. L. Glass compositions, P (11) 371*h*.
Ellis, M. P. Adaptive control advances honing state-of-art, (8) 273*f*.
Ellis, W. C. Whisker crystals grown from solder terminations in an electrotransport process, (5) 203*h*.
Ellis, W. C., Frosch, C. J., and Zetterstrom, R. B. Morphology of gallium phosphide crystals grown by VLS mechanism with gallium as liquid-forming agent, (7) 267*e*.
Ellis, W. P. Low-energy electron diffraction studies of uranium dioxide, (6) 234*e*.
Ellyn, G. See Riha, J. G.
Elmer, T. H., and Nordberg, M. E. Electric lamp and method of production, P (1) 10*b*. Method of treating a porous high silica content glass, P (11) 371*j*.
Eloy, P. Method and apparatus for manufacturing float glass with internal circulatory bath heat exchange, P (7) 249*b*. See Plumat, E.
Elsken, J. C. See Nyrop, P.
Elston, J. See Carteret, Y.; Stevanovic, M.
Elton Industries, Inc. Method [solution etching] for machining fragile crystals, P (9) 314*h*.
Elwell, D. See Smith, S. H.
Ely, E. E. See Smith, C. C.
Elyard, C. A. See Potter, T. J.; Waterfield, C. G.
Elyutin, V. P., Maurakh, M. A., and Kostikov, V. I. Theory of deposition on high-temperature materials, B (5) 204*e*.
Embury, J. D. See Perrow, J. M.
Emel'yanov, V. B. See Uskova, E. T.
Emerson, R. B. See Osment, H. E.
Emerson & Cuming, Inc. Closed-cell ceramic article and method, P (5) 180*a*. Microsphere glass agglomerates and method for making them, P (11) 371*j*.
Emhart Corp. Apparatus and method for handling glassware for inspection or the like, P (6) 212*c*. Apparatus for moving newly formed glassware articles onto a continuously moving conveyor, P (1) 10*i*. Container inspection machine, P (5) 174*b*. Electrode holder for glass furnaces or the like, P (4) 98*c*. Glass contact [zircon] refractory and method of making the same, P [7] 252*j*. Glassmaking apparatus, P (4) 99*d*. [Hydraulic] shears for molten glass feeders, P (7) 248*j*. Liquid cooling device for glass furnace electrode, P (1) 10*j*. Mold closing boost mechanism for glassware forming machine, P (11) 371*j*. Valve lever [pneumatic] and latch mounting mechanisms for glassware forming machine, P (11) 372*c*.
Emhiser, D. E., and Pecoraro, G. A. Process for melting glassmaking ingredients on a molten metal bath, P (9) 308*b*.
Emi, T., and Shimoji, M. Thermoelectric power of the systems "FeO," "FeO"-SiO_2, and "FeO"-CaO, (4) 162*e*.
Emley, F. Process for producing thermoelectric elements, P (1) 19*d*.
Emmel, D. R., Blackburn, A. R., and Kendall, V. D. Method for making ware producing mold members, P (4) 109*b*.
Emmenegger, F. Crystal growth of ternary metal oxides by chemical transport, (10) 351*i*. Preparation of single crystals of $CaNb_2O_6$ by chemical transport, (7) 268*e*. See Brunner, H. R.
Emmenegger, F., and Petermann, A. Transport reactions and crystal growth of transition metal niobates, (6) 239*c*.
Emmenegger, F., and Robinson, M. L. A. Preparation and dielectric properties of niobium pentoxide crystals, (10) 359*f*.
Emmett, J. L. See Greene, R. L.; Holzrichter, J. F.
Emons, H. H., and Hellmold, P. Some properties of silicon monoxide, (9) 329*b*.
Emons, H. H., and Theisen, L. Silicon monoselenide, (7) 255*b*.
Emoto, Masayuki, and Nakano, Masahira. Phosphors, P (11) 378*d*.
Empresa Auxiliar de la Industria S. A. Method of producing oxide and hydroxide of zinc, P (10) 349*d*.
Emtage, P. R. See Mallick, G. T., Jr.
Engbert, W. Manufacture of semiconductor arrangements using a masking step, P (8) 282*d*.
Engeler, W. E. Semiconductor light emitter and combination light emitter-photocell wherein the reflector of the light emitter is comprised of a material different from that of the light emitter, P (11) 378*f*. See Brown, D. M.
Engelhard Hanovia, Inc. See Sinclair Research, Inc.
Engelhard Industries, Inc. Alumina production, P (6) 229*a*. Catalytic radiant heater, P (7) 261*g*. Method of preparing a supported catalyst, P (7) 263*a*. Noble metal thermocouple having base metal compensating leads, P (9) 315*j*.
Engelhard Minerals & Chemicals Corp. Attapulgite clay paper filler and method of forming newsprint therewith, P (6) 229*b*. Attapulgite product and method of preparing same, P (1) 23*g*. Clay treatment, P (7) 262*f*. Composite coated heat reflectors and infrared lamp heaters equipped therewith, P (8) 275*b*. Hydrogen diffusion and method for producing same, P (4) 109*c*. Method for beneficiating clay by flotation of colored impurities, P (11) 382*c*. Method for dispersing clay, P (4) 124*h*. Space vehicle, P (6) 208*b*. Talc beneficiation, P (11) 383*a*.
Engelhardt, L. M., and Figgis, B. N. Magnetic susceptibility of Pr^{4+} in CeO_2, (5) 196*d*.
Engell, H. J. See Pluschkell, W.
Engelman, R. W. H. See Atalla, M. M.
Engelter, A. Principle and basic theory of the quotient calorimeter, (4) 120*g*.
Engineers Joint Council. Thesaurus of Engineering and Scientific Terms, B (2) 86*d*.
England, R. E. See Steininger, J.
Englehardt, W. V., and Bertsch, W. Shock induced planar deformation structures in quartz from the Ries Crater, Germany, (9) 329*e*.
Engler, O. Ball mill, P (10) 346*g*.
Engler, P. H. Development and operation of box type enameling furnaces, (5) 171*e*. Development and operation of U-type enameling furnaces (I, II), (5) 171*f*. Optimum operating point of an industrial furnace and its determination as exemplified by an enameling U-kiln, (11) 368*i*.
English, F. L. Electron-mirror microscopy study of $BaTiO_3$ surface layers, (4) 134*j*.
English, J., Putner, T. I., Watts, J. F., and Hill, J. A. Apparatus for measuring optical characteristics of coatings on lenses, P (8) 277*g*.
English, J. E. See Rose, H. E.
English, J. F. Halogen regenerative cycle incandescent lamp, P (10) 339*g*.
English Clays Lovering Pochin & Co., Ltd. Processing of clay, P (9) 317*f*.
English Electric Co., Ltd. Glass fabric reinforced mica tape and process for production thereof, P (6) 212*c*. Method of coating a ceramic-carbon material with glass and article, P (11) 377*g*. Method of coating metallic wire or strip with glass, P (9) 304*i*.
English Electric Valve Co., Ltd. Krypton-xenon flash tube for pumping a ruby laser, P (7) 256*g*.
Engmann, F. Rationalization and improvement of the method of drying wall and floor tiles, (1) 15*c*
Engstrom, I. Crystal structure of Rh_5Si_3 and its relation to other members of the MnP structure family, (10) 351*c*.
Engstrom, I., and Persson, E. Crystal structure of Rh_3Si_4, (10) 351*b*.
Engstrom, I., and Pfeifer, H. U. Crystal structure of Pt_2Ge_3, (10) 351*j*.
Ennos, A. E., and Opperman, K. W. Birefringence of natural quartz, (1) 25*a*.
Enomoto, Goro. Glass composition for use as the faceplate of an image orthicon tube and the like, P (4) 98*i*.
Enos, J. H. See Von Tress, W. R.
Entelis, F. S. See Yurchak, I. Ya.
Entoleter, Inc. Method and apparatus for rotary processing and classification, P (6) 229*h*.
Eorgan, J. E. High temperature oxidation resistant articles, P (6) 208*b*.
Eorgan, J. E., and Fern, N. D. Vacuum vapor deposition, (4) 118*g*.
Epel'baum, M. B. See Bobrov, B. S.
Epple, R. See Gerstner, D.
Eppler, A. H. Method for wet abrasive blasting, P (9) 314*h*.
Eppler, R. A. Crystallization and phase transformation in TiO_2-opacified porcelain enamels (I) theory; (II) comparison of theory with experiment, (4) 93*d*. Reflectance of titania opacified porcelain enamels, (6) 207*f*.
Eppler, R. A., and Spencer-Strong, G. H. Role of P_2O_5 in TiO_2-opacified porcelain enamels, (7) 246*h*.
Epstein, G., Hewitt, R. R., and Mazelsky, B. Apparatus for and method of measuring thermal stress by nuclear resonance, P (1) 22*i*.
Epstein, J. See Weinstein, M.
Epstein, M. See Rosner, D. E.
Erdey, L. See Simon, J.
Erdman, S. See Weinstein, A. B.
Eremenko, V. V. See Kharchenko, N. F.
Ergun, S. Determination of longitudinal and transverse optical constants of absorbing uniaxial crystals—optical anisotropy of graphite, (4) 131*h*. See Berman, M.
Erickson, H., and Johnson, M. F. L. Crystalline aluminosilicate-containing catalyst and methods of treating and using same, P (6) 229*d*.
Eritsyan, G. N. See Vinetskii, V. L.
Ermachkov, V. I. See Diogenov, G. G.
Erman, L. Ya. See Gal'perin, E. L.
Erman, L. Ya., and Gal'perina, E. L. New data on the crystalline structure of $Bi_2O_3 \cdot 2MoO_3$, (4) 146*b*.
Ermenc, E. D., and Smith, M. F. Asbestos millboard conveyor rolls for high temperature use, P (10) 342*a*.
Ermolaeva, A. I. See Berenshtein, P. I.
Ermolaeva, E. V., Guzenko, G. F., and Mirak'yan, M. M. Determination of the viscosity of spinellite melts up to 2500°, (8) 290*f*.
Ernick, F. G. See Kisinko, P. M.; Tarneja, K. S.
Ernsberger, F. M. Method for making radiation induced crystallized glass, P (10) 339*c*. Reply to comments on "Role of densification in deformation of glasses under point loading," (7) 246*a*. Reply to note on "Dislocations and surface flaws on glass," (9) 305*a*. Reply to note on "Generation of deep cracks in glass," (8) 276*a*.
Ernst, E. O., Hurd, D. J., and Seeley, G. High capacity epitaxial apparatus and method, P (5) 183*d*.
Ernst, W. G. Amphiboles—Crystal Chemistry, Phase Relations, and Occurrence, B (1) 41*a*.
Ernst, W. G., and Calvert, S. E. Hydrothermal recrystallization of porcelainite to quartz, (9) 322*j*.
Eror, N. G., and Wagner, J. B., Jr. Electrical conductivity and thermogravimetric studies of single crystalline cobaltous oxide, (10) 352*f*.
Erosov, Yu. I. See Samsonov, G. V.
Ertel, A. Solid state microstripline attenuator, P (6) 224*b*.
Erwin Behn Verpackungsbedarf G.m.b.H. Apparatus for filling valve bags with pulverous material, P (8) 284*e*.
Esaki, L. See Chang, L. L.; D'Heurle, F. M.
Esaki, L., Howard, W. E., Jr., and Stiles, P. J. Metal-degenerate semiconductor-insulator-metal sandwich exhibiting voltage controlled negative resistance characteristics, P (8) 282*d*.
Eschenbach, R. C., and Stresino, E. F. Method of making refractory shapes, P (1) 14*g*.
Escher, B. See Flaks, S.
Esner, M. See Spicak, K.
Espe, W. Materials of High Vacuum Technology (Vol. 2) Silicates, B (2) 85*f*.
Essers, W. G., Verhagen, J. G., and Tichelaar, G. W. Core wire for electric arc welding, P (2) 46*d*.
Esso Research & Engineering Co. Apparatus and process for eliminating preferred orientation in X-ray diffraction in crystals, P (4) 121*d*. Cementitious systems, P (9) 304*a*. Dehydration magnesium chloride roasting and solvent, P (1) 23*h*. Glass fibers sized with hydroformylated polymer and laminate therefrom, P (5) 174*f*. High temperature fluid coke electrodes, P (8) 279*c*. Novel lithium silicate compositions and process for producing same, P (11) 382*g*. Process of making structural elements with compacted aggregate, P (6) 214*f*. Sizing glass fibers with polybutadiene - dicarboxylic acid anhydride amino salt adducts, P (4) 101*b*. Zeolitic materials, P (4) 126*b*.
Esu, F., Martinetti, S., and Ribacchi, R. Mechanical properties of the Roman pozzolanas, (5) 170*f*.
Esveldt, C. J., and Poels, J. P. J. Method of manufacturing lithium ferrite magnetic cores, P (4) 115*d*.
Etheridge, W. Conveyors for high production of appliances, (7) 245*j*.
Ethyl Corp. Oxidation catalysts, P (6) 229*j*.
Etten, N. L. See Hughes, R. O.
Ettinger, B. L. Deposition of pyrolytic material, P (10) 344*f*. See Clark, T. J.
Ettmayer, P. See Gugel, E.
Eugster, E. Controllable semiconductor element, P (6) 221*f*, P (7) 256*c*.
Eugster, E., and Spickenreuther, D. Process [diffusion] for making a semiconductor element, P (9) 313*d*.

Euratom. See European Atomic Energy Community.
European Atomic Energy Community—Euratom. Apparatus for the purification of an enclosed inert atmosphere, P (1) 20*c*. Process for the manufacturing of fuel elements, P (6) 218*j*. Process for processing irradiated ceramic reactor fuels, P (1) 14*d*.
Eutectic Engineering Co. Colloidal silica compositions containing set indicator, P (7) 252*h*.
Eutectic Welding Alloys Corp. Method [flame spray] for producing carbide containing materials, P (10) 337*b*.
Evamy, B. D. Precipitational environment and correlation of some calcite cements deduced from artificial staining, (11) 380*d*.
Evans, A. G., Roy, C., and Pratt, P. L. Role of grain boundaries in the plastic deformation of calcium fluoride, (2) 82*e*.
Evans, A. W., and Cleaver, D. Production of pigmentary size titanium dioxide, P (6) 230*b*.
Evans, B. See Pasternak, R. A.
Evans, B., and White, T. E. Argon sorption at 77.4°K on a microporous glass, (4) 94*j*.
Evans, B. E. See Samms, J. A. C.
Evans, B. J., Ghose, S., and Hafner, S. S. Hyperfine splitting of ^{57}Fe and Mg-Fe order-disorder in orthopyroxenes ($MgSiO_3$-$FeSiO_3$ solid solution), (4) 139*c*.
Evans, B. J., and Hafner, S. S. Moessbauer resonance of ^{57}Fe in oxidic spinels containing Cu and Fe, (10) 357*h*.
Evans, E. L. See Bahl, O. P.; Thomas, J. M.
Evans, H. J. See Kessler, D.
Evans, J. C. Electron microscope study of the transition from amorphous to crystalline condition of electron bombarded cadmium sulfide films, (7) 265*b*.
Evans, J. V., and Whateley, T. L. Infrared study of adsorption of carbon dioxide and water on magnesium oxide, (8) 293*c*.
Evans, L. F. Ice nucleation under pressure and in salt solution, (8) 293*h*.
Evans, P. E. See Driscoll, J. L.
Evans, P. F. See Lahr, R. J.
Evans, R. H., and Marathe, M. S. Microcracking and stress-strain curves for concrete in tension, (1) 3*f*. Stress distribution around holes in concrete, (1) 3*c*.
Evans, S. O. See Edgecombe, D. A.
Evans, W. See Baer, C. E., Jr.
Evans, W. D. J. Ceramic pigments—a structural approach, (2) 72*i*.
Evans, W. H. Determination of magnesium in silicate and carbonate rocks by the Titan Yellow spectrophotometric method, (1) 21*d*.
Everett, D. H. See Cadenhead, D. A.
Everhart, J. J. See Moser, F.
Everhart, J. O. See Schorr, J. R.
Evers, M. Plastic deformation of glass with diamond indenters, (6) 211*a*.
Evlanova, N. F., Kornienko, L. S., Rashkovich, L. N., and Rybaltovskii, A. O. Electron paramagnetic resonance of some lanthanide ions and Cr^{3+} in $LiNbO_3$ crystals, (2) 76*c*.
Evrard, R. See Kartheuser, E.
Evrard, R. P. See Devreese, J. T.
Evstrop'ev, K. K., and Pavlovskii, V. K. Ionic diffusion and electrical conductivity of single-alkali glasses, (2) 49*j*.
Evstrop'ev, K. S. See Vakhrameev, V. I.
Evstrop'ev, K. S., Gutorova, L. L., and Komleva, G. M. Viscosity of titania one-coat enamels, (6) 207*h*.
Evtjutov, A. A. See Telyatnikov, G. V.
Ewanizky, T. F. See Theissing, H. H.
Ewart, A. See Taylor, S. R.
Ewing, C. T. See Walker, B. E., Jr.
Ewing, G. W. Topics in chemical instrumentation. Mass spectrometers (II) mass-analyzer systems; detectors, (8) 285*j*.
Exner, H. E. Influence of sample preparation on Palmqvist's method for toughness testing of cemented carbides, (10) 347*h*.
Eyer, J. A. Gannett group of western Wyoming and southeastern Idaho, (11) 385*b*.
Eylon, D., and Rosen, A. Hydraulic driving system for a Bridgman type furnace, (4) 120*b*.
Eyre, B. L., and Bartlett, A. F. Effects of nickel on the structure of sintered uranium carbide, (4) 133*h*.
Eyre, B. L., and Bullough, R. Formation and behavior of gas bubbles in a nonuniform temperature gradient, (8) 292*i*.
Eyring, H. Search for significant structures, (6) 237*b*. See Lu, Wei-Chen.
Eyring, L. (editor). Advances in High Temperature Chemistry (Vol. I), B (4) 165*a*. See Burnham, D. A.; Felmlee, T. L.; Kordis, J.
Eysel, W. See Woermann, E.
Ezerskii, M. L., Kozlova, N. I., Bagotskii, V. S., Kalliga, G. P., Demonis, I. M., Rastorguev, L. N., and Prilepskii, V. I. Electrical conductivity of solid solutions of calcium oxide and zirconium dioxide at elevated temperatures, (6) 232*j*.

Fabricacion de Maquinas. Comblike catch pans for vertical draw sheet glass making machines, P (7) 248*c*. Machinery support, P (6) 212*i*. Roll bearing structures for glass-making machines, P (5) 176*a*.
Fabriques de Produits Chimiques de Thann et Boite Postale. Process for making titanium dioxide using carbon monoxide containing inorganic ashes, P (7) 263*e*.
Fabriques de Produits Chimiques de Thann et de Mulhouse. Process and apparatus for the production of metal oxides, P (1) 24*e*.
Fabry, G. See Algrain, A.
Fadner, T. A. Composite colloidal pigment [clay] particles, their formation and suspensions thereof, P (10) 349*c*.
Faerman, B. See Orient, I.
Faeth, P. A. Trapping level disposition in cadmium sulfide, (5) 202*b*.
Fagherazzi, G. See Colombo, U.
Fahey, J. J. See Reichen, L. E.; Ross, C. S.
Fahim, R. B. See Mikhail, R. Sh.
Fainberg, E. A. Chemical composition of phase reduced on surface of high-lead glasses during heating in hydrogen, (8) 276*b*.
Fairchild, J. L. See Schumacher, J. C.
Fairchild Camera & Instrument Corp. Contact metal system of an Al layer adjacent to semiconductor and layer of Au-Al intermetallics adjacent to the conductive metal, P (7) 256*b*. Lateral transistor with improved injection efficiency, P (5) 183*g*. Low melting oxide glass, P (2) 53*d*. Method of making stable semiconductor devices, P (5) 183*i*. Method of manufacturing semiconductor devices, P (2) 65*g*. Planar high voltage four layer structures, P (6) 223*e*. Remote-cutoff field effect transistor, P (2) 66*j*. Selective masking method of silicon during anodization, P (6) 223*b*. Thin-film resistors, P (11) 379*a*. Variable threshold insulated-gate field-effect device, P (6) 224*c*.
Faircloth, R. L. See Ackermann, R. J.; Cuthbert, J.
Fairman, R. D. See Kroemer, H.
Faivre, R., Hertz, J., and Gantois, M. Order-disorder transformations for some binary, ternary, and quaternary alloys of type Au-Cu and $AuCu_3$, (2) 81*f*.
Faktor, M. M. See Hanks, R.
Faktor, M. M., Fiddyment, D. G., and Newns, G. R. Preliminary study of the chemical polishing of α-corundum surfaces with vanadium pentoxide, (4) 150*f*.
Falcettoni, J. B. Method of stabilizing friction coefficient of carbonaceous base materials and the products thereof, P (5) 179*g*.
Falk, T. J. Shock-tube method for determining the vapor pressures of refractory metals at high temperatures, (5) 188*c*.
Falla, W. S. See Williams, E. G.
Fallon, J. Polyester seals for clay pipe (I, II), (4) 102*e*.
Fallos, G. See Campbell, D. R.
Fan, Fu-kan. See Kuznetsov, A. K.
Fang, F. F. Insulated-gate field-effect transistor exhibiting a maximum source-drain conductance at a critical gate bias voltage, P (2) 65*d*.
Fang, F. F., Walker, E. J., and Yu, Hwa N. Method for fabricating insulated-gate field-effect transistors, P (4) 114*c*.
Fang, P. H. See Brower, W. S.
Farbenfabriken Bayer Akt.-Ges. Glass fibers sized with polycarbonate, P (2) 52*i*. Radiation sensitive ampoule testing apparatus and method, P (4) 101*b*. Vapor phase process for the conversion of metal halides into their oxides, P (4) 126*b*.
Farber, M. See Blauer, J.; Greenbaum, M. A.; Ko, H. C.
Farbwerke Hoechst Akt.-Ges. Hardener for water glass cements, P (8) 274*c*.
Farbwerke Hoechst Akt.-Ges. vorm. Meister Lucius & Bruning. Apparatus for mechanically after-dehumidifying and further treating filter press cakes of pigment or dispersion dyes, P (11) 379*d*.
Farkas, O. Study on viscosity properties of blast furnace slags, (5) 178*f*.
Farkas-Jahnke, M. See Bertoti, I.
Farooq, M. K. See Lehmann, H.
Farr, A. E., and Treusch, A. L. Investigation of the solubility and aging behavior of cover coat enamels, (1) 4*f*.
Farrant, B. R. See Baker, P. M.
Farrar, T. C. See Tsang, Tung.
Farrell, E. See Lipson, H. G.
Farrer, T. C. See VanderHart, D. L.
Farrington, D. See Haitz, R. H.
Farrington, G. M., and Fay, W. X. Plastic chrome ore composition, P (2) 59*c*.
Farrington, G. M., Stein, J. L., and Treffner, W. S. Basic refractory lining brick and process, P (5) 178*a*.
Farrington, G. M., and Verduin, F. C. Refractory ramming composition, P (4) 107*i*.
Farrow, R. L. High temperature thermocouple, P (1) 22*c*.
Faruqi, F. A., Okuda, Susumu, and Williamson, W. O. Chemisorption of methylene blue by kaolinite, (7) 253*d*.
Fasano, G., Sacchi, G., and Pons, C. Thin-film rectifying device comprising a layer of CeF_3 between a metal and CdS layer, P (7) 258*c*.
Fasnacht, J. J. See Eilerman, G. E.
Fassle, F. See Rueter, H.
Fathmann, H. Measuring industrial water usage —methods and installation, (10) 363*j*.
Faucher, M., Dembinski, K., and Anthony, A. M. High temperature furnace for a neutral or oxidizing atmosphere ($T>2000°K$), (9) 316*c*.
Faulkner, R. A. See Dean, P. J.
Faulkner, R. D. Bonding graphite with fused silver chloride, P (10) 342*b*.
Faulring, G. M., and Malixie, E. S. Electron microprobe analyses and X-ray diffraction study of $SrSi_2$, B (1) 40*i*.
Faure, P. K. See Pearton, D. C. G.
Faust, J. W., Jr., John, H. F., and Pritchard, C. Influence of solvent and impurities on habit and morphology of semiconductor crystals, (8) 293*b*.
Faust, J. W., Jr., John, H. F., and Rubenstein, M. S. Formation of heterojunction devices by epitaxial growth from solution, P (9) 312*j*.
Faust, W. H. Preparation of dry ceramic bodies with the Mogensen sizer, (7) 258*j*.
Fawcett, W. R. See Dignam, M. J.
Fay, H. Electrical conductivity of liquid Al_2O_3 (molten corundum and ruby), (4) 134*d*.
Fay, H., Alford, W. J., and Dess, H. M. Dependence of second-harmonic phase-matching temperature in $LiNbO_3$ crystals on melt composition, (1) 26*j*.
Fay, W. X. See Farrington, G. M.
Faye, G. H., Manning, P. G., and Nickel, E. H. Polarized optical absorption spectra of tourmaline, cordierite, chloritoid, and vivianite —ferrous-ferric electronic interaction as a source of pleochroism, (9) 327*g*.
Feagin, R. C., Dahowski, E. L., Kosmos, P., and Robb, R. R. Refractory mold composition and method, P (6) 218*e*.
Feates, F. S. Diffusion of carbon in single crystal graphite, (10) 352*d*. Radiolytic oxidation of single crystal graphite, nature of active species, and G values, (9) 311*i*.
Feder, R., Asai, K. W., Charbnau, H. P., and Mannheimer, R. Metrology method for crystal defect detection, P (1) 22*g*.
Federal-Mogul Corp. Diamond abrasive saw blade, P (8) 273*f*.
Federal Tool Engineering Co. Back reflector for radiant energy glass-to-metal sealing means, P (11) 371*a*.
Federighi, T., Caresara, S., and Gualandi, D. Quenched-in resistivity in SAP (a sintered alloy of Al with dispersed Al_2O_3), (1) 17*j*.
Fedin, A. A., Chernyshev, E. M., and Pogrebnov, A. N. Production and uses of porous silicate concrete, (2) 45*c*.
Federov, N. F., and Brodkina, E. R. Solid solutions in the system $2CaO·SiO_2$-$Na_2O·CaO·SiO_2$, (10) 360*j*.
Fedorov, P. I., Dudareva, A. G., and Tsygankova, M. S. System InI_3-HgI_2, (8) 299*d*. Systems of indium iodide with the iodide and oxyiodide of bismuth, (8) 299*i*.
Fedorov, P. I., and Il'ina, N. I. Interactions of the chloride of indium with the chlorides of iron, cobalt, and bismuth, (4) 140*d*.
Fedorov, P. I., and Khagleeva, L. P. Systems $GaCl_3$-$SeCl_4$ and $GaCl_3$-$TeCl_4$, (8) 299*h*.
Fedorov, P. I., and Nedev, S. K. Interaction of gallium chloride with the tetrachlorides of carbon, silicon, germanium, and titanium, (8) 293*e*.
Fedorov, P. I., Nedev, S. K., and Liu, Kuo-Yuan. Interactions of gallium chloride with the chlorides of beryllium, magnesium, calcium, and barium, (4) 140*e*.
Fedorov, T. F. See Gladyshevskii, E. I.; Gorshkova, L. V.
Fedorova, G. M., and Shishakova, T. N. Structure of gmelinite, (7) 269*b*.
Fedorova, V. A. See Yudin, N. A.
Fedorovskii, Ya. A., Gendler, G. S., Mitrofanov, K. P., and Plotnikov, M. V. Study of initial stages of crystallization of lithia-alumina-silica glasses by means of the Moessbauer effect and X-ray phase analysis, (1) 9*a*.
Fedoseev, A. D. See Korytkova, E. N.
Fedoseev, D. V. See Aleshin, B. N.; Derjaguin, B. V.; Ryabov, V. A.
Fedulov, S. A. See Shapiro, Z. I.
Feenstra, R. Manufacturing diamond bits, P (10) 335*f*.
Fehlner, F. P. Method of making filamentary metal structures, P (2) 65*f*. Use of discontinuous metal films in determining the rate of formation of very thin oxide films, (5) 188*c*.
Feichter, H. R., Abernethy, I. A., Fishley, C. F., Cable, S. J., and Hoffman, O. M. Pregrouted ceramic tile assemblies, P (8) 280*d*.
Feingold, E. See Mehan, R. L.
Feitknecht, W. See Gallagher, K. J.
Feitknecht, W., and Mannweiler, N. Mechanism of transformation of γ-Fe_2O_3 to α-Fe_2O_3, (6) 235*b*.
Felder, J. L. Process for manufacturing structural material, P (1) 11*g*.
Feldman, A. See Anderson, J. A.
Feldman, R. F. See Ramachandran, V. S.
Feldmann, H. F., Simons, W. H., and Bienstock, D. Calculating equilibrium compositions of multiconstituent, multiphase, chemical reacting systems, (9) 318*h*.
Feldmann, T., and Treinin, A. I^- photosensitized reactions in metaphosphate glass, (5) 173*c*.
Feldtkeller, E., and Stein, K. U. Memory element with stacked magnetic layers, P (11) 377*e*.
Felix, D. W. Inexpensive recording settling tube for analysis of sands, (11) 380*f*.
Felix, F. W. Rare-gas diffusion in neutron-irradiated potassium halides, (8) 297*d*.
Felmlee, T. L., and Eyring, L. Ternary system samarium-nitrogen-oxygen and the question of lower oxides of samarium, (11) 388*d*.
Felsche, J. Crystal structure of β-aluminum oxide, (6) 231*h*.
Felten, E. J. Oxidation behavior of silicided niobium-titanium binary alloys, (7) 246*d*.

Fender, B. E. F., Jacobson, A. J., and Wedgwood, F. A. Covalency parameters in MnO, α-MnS, and NiO, (4) 130*a*.
Fenerty, M. J., and Somers, A. V. Method of manufacturing ceramics, P (8) 284*f*.
Fenner, E. See Brauer, H.; Ferckel, S.
Fenner, G. E. Method of making glass-silicon composite bodies, P (11) 371*h*. Selective absorption changes in Fe-doped CdTe under the influence of high electric fields, (4) 111*f*. Semiconductor junction laser with electronically displaceable and deflectable beam, P (7) 258*d*. Simplified piezoresistive force sensing device, P (4) 116*j*.
Fensham, P. J. See Larkins, F. P.
Fenske, D. H. Recovery of clay and sand from an ore, P (5) 191*c*.
Fenske, D. H., and McMurray, L. L. Flotation process, P (5) 190*i*.
Fenstermacher, J. E. Dimensional control of dry-pressed electrical ceramics, (10) 343*d*.
Fenwal, Inc. Ignition and flame monitoring control apparatus for fuel burners, P (2) 72*e*. Thermocouple probe assembly and temperature sensing circuits comprising the same, P (4) 122*b*.
Ferckel, S., and Fenner, E. Metalizing processes for electroceramics, (7) 255*f*.
Ferenc, S. See Gilde-Farkas, M.
Ferguson, C. W. See Rahrig, D. D.
Ferguson, C. W., and Welker, R. H. Drilling machines [sheet glass], P (11) 371*e*.
Ferguson, I. F. See Collins, J. F.
Ferguson, J. M. See Wood, G. C.
Fermor, J. H., and Kjekshus, A. Phase transition in KNO_3 at low temperatures, (9) 327*a*.
Fern, N. D. See Eorgan, J. E.
Ferrara, P. J. Gypsum wallboard and process of making the same, P (4) 92*h*.
Ferraresi, M. See Donati, E.
Ferraresso, G. Thermoluminescence of clay minerals, (4) 162*h*. See Bettinali, C.
Ferrario, A. See Ascoli, A.
Ferraro, J. R. See Postmus, C.
Ferretti, A., and Germann, R. W. Electric heating element and its fabrication, P (8) 282*e*.
Ferris, J. T. See Brumley, C. H.
Ferro Corp. Applicator for particulate material, P (5) 171*i*, P (6) 207*j*. Nozzle applicator for dry process enamels, P (1) 5*f*. Sizing composition for glass fibers, P (10) 340*a*.
Fertel, J. H. See Perry, C. H.
Fesenko, E. G., Filip'ev, V. S., and Kupriyanov, M. F. Conditions for the existence of perovskites, (4) 129*a*.
Fesenko, V. V. See Bolgar, A. S.
Fessler, T. E., Smith, A. B., and Vincent, J. S. Thin window drifted silicon charged particle detector, P (5) 185*g*.
Fetzer, H. See Wilke, W.
Fiddyment, D. G. See Faktor, M. M.
Flegna, A., and Weisgerber, P. Influence of thin noble metal films on zirconium oxidation, (5) 195*c*.
Field, J. E. See Bowden, F. P.
Field, M. B. Elastic and anelastic behavior of V_2O_5-P_2O_5 glasses, (11) 369*f*. High-temperature internal friction and transport mechanisms in sodium silicate glasses, (1) 7*g*.
Fielden, J. H., and Rubenstein, C. Grinding of glass by a fixed abrasive, (11) 370*d*.
Fields, D. P. Surface treating pigments with hydrous metal oxides, P (4) 126*a*.
Fieschi, R. See Bucci, C.
Fifield, J. A., and Blezard, R. G. Rapid routine determination of uncombined lime by an automatic absorptiometric method, (11) 380*g*.
Figgis, B. N. See Engelhardt, L. M.
Fijitsu, Ltd. Process of epitaxial deposition on one side of a substrate with simultaneous vapor etching of the opposite side, P (6) 223*h*.
Filby, J. D. Chemical polishing of single crystal α-alumina using silicon, (2) 75*c*.
Fildshtein, M. V. See Tobolov, P. N.
Filip'ev, V. S. See Fesenko, E. G.
Filipovich, V. N. Theoretical scheme for segregation in solutions and glasses—fluctuation stage of phase decomposition, (2) 52*a*. Theoretical system of liquefaction process in solutions and glasses—diffusion stage of phase decomposition, (10) 362*a*.
Filippi, L., and Dinner, H. Methods of and means for producing anhydrous alumina, P (2) 74*c*.
Finch, A., Gardner, P. J., and Gupta, K. K. S. Thermochemistry of some phosphorus halide-boron halide complexes, (4) 161*f*.
Finch, C. B. See Abraham, M. M.
Finch, C. B., and Clark, G. W. Flux growth and characterization of hexagonal germanium dioxide single crystals, (9) 321*h*.
Finch, E. D. See Rabideau, S. W.
Finch, W. I. See Olive, W. W.
Findlay, D. See Cockayne, B.
Fine, M. E. See Woods, K. N.
Finger, T. H., and Heaton, R. A. Inspecting open mouth translucent containers for defects, P (2) 53*a*.
Fink, A. See Stober, W.
Fink, D. W., Pivnichny, J. V., and Ohnesorge, W. E. Determination of iron at parts-per-billion levels by quenching of 2,2′2″-terpyridine luminescence, (8) 284*i*.
Fink, H. J. See Beeman, D. E.
Fink, J. L. See Warner, A. W.
Finkelman, R. B., and Duke, M. B. Technique for mounting, sectioning, and polishing particles smaller than 30 μm in diameter, (8) 285*h*.
Finlayson, M. J. Contact metal system of an Al layer adjacent to semiconductor and layer of Au-Al intermetallics adjacent to the conductive metal, P (7) 256*b*.
Finn, M. C. See Strauss, A. J.
Fiorenlini, M. P. Nonequilibrium mixing in natural alkali feldspars, (9) 325*g*.
Fires, H., and Pfeil, R. Methods of continuously firing ceramic charge material in tunnel kilns, and tunnel kilns for carrying out these methods, P (11) 381*j*.
Firestone, S., and McCarthy, J. Vapor deposition apparatus, P (9) 314*d*.
Firle, T. E. See Compton, D. M. J.
Firma Albert Klein K. G. Apparatus for the continuous extraction of moisture from suspended matter, P (11) 379*d*.
Firma Schneider & Co. Apparatus for manufacturing ceramic elements having a honeycomb structure, P (2) 67*g*.
Fisch, H. A. See Gadd, J. D.
Fischbach, D. B. Effect of substrate structure on deposition of evaporated carbon, (4) 110*c*. Stress dependence of tensile creep rate in carbons and graphites, (8) 298*a*.
Fischer, A. G. See Weisberg, L. R.
Fischer, D. W., and Baun, W. L. Effects of electronic structure and interatomic bonding on the soft X-ray Al *K* emission spectrum from aluminum binary systems, B (1) 40*i*.
Fischer, G. R. See Ostertag, W.
Fischer, H. C., and Fischer, H. C., Jr. Reinforced article, P (6) 205*g*.
Fischer, H. C., Jr. See Fischer, H. C.
Fischer, H. G. High expansion sealing glass and composite article, P (9) 307*f*.
Fischer, H. G., and La Due, A. W. Process for glass strengthening, P (11) 372*d*.
Fischer & Porter Co. Syringe and method of making same, P (4) 101*c*.
Fisher, A. W. See Amick, J. A.
Fisher, A. W., and Amick, J. A. Defect structure on silicon surfaces after thermal oxidation, (2) 75*b*. Diffusion characteristics of doped silicon dioxide layers deposited from premixed hydrides, (8) 281*d*.
Fisher, A. W., Amick, J. A., Hyman, H., and Scott, J. H., Jr. Diffusion characteristics and applications of doped silicon dioxide layers deposited from silane (SiH_4), (8) 281*c*.
Fisher, D. J., and McConnell, D. Aluminum-rich apatite, (8) 288*g*.
Fisher, G. W., and Medaris, L. G., Jr. Cell dimensions and X-ray determinative curve for synthetic Mg-Fe olivines, (11) 383*f*.
Fisher, I. S. Interrelation of mineralogy and texture within an Ordovician Lexington limestone section in central Kentucky, (1) 23*g*.
Fisher, J. Pottery as sculpture, (4) 90*d*.
Fisher, J. H., and Anderson, J. C. Nucleation and growth of thin lead films on amorphous substrates, (2) 63*j*.
Fisher, R. E. See Jacobs, L. J.
Fisher, R. J. See Szekely, J.
Fisher, W. L., and Rodda, P. U. Edwards formation (Lower Cretaceous), Texas — dolomitization in a carbonate platform system, (7) 262*b*.
Fishley, C. F. See Feichter, H. R.
Fishman, S. L. See Nimvitskaya, T. A.
Fishwick, J. H. Lightweight ceramic product and method of making, P (4) 109*d*.
Fitch, A. H. See Meitzler, A. H.
Fitch, F. T., and Shoup, R. D. Process for preparing high density uranium dioxide particles and compositions, P (8) 280*a*. Uranium trioxide aquasol process, P (10) 349*f*.
Fitch, F. T., and Smith, J. G. Process for preparing thorium dioxide-uranium dioxide sol, P (2) 59*c*.
Fitzer, E., Chvatal, T., Buchner, E., and Rubisch, O. Method of protectively treating an electrically and thermally conducting refractory body of sintered silicon carbide, P (4) 107*c*.
Fitzgerald, J. J., and Brownell, G. L. Radioisotopic heat source and method of production, P (5) 179*e*.
Fitzgibbon, G. C., and Holley, C. E., Jr. Heat of formation of lanthanum oxide, (1) 30*b*.
Fitzke, E. V. See Yim, W. M.
Fitzpatrick, T. H. See Culp, J. D.
Fix, W. See Troemel, G.
Fix, W., Heymann, H., and Heinke, R. Subsolidus relations in the system $2CaO \cdot SiO_2$-$3CaO \cdot P_2O_5$, (8) 299*a*.
Flaks, S., and Depoutot, R. Solid electrolytic capacitor having mixed dioxide semiconductor layer, P (11) 378*j*.
Flaks, S., and Escher, B. Process for manufacturing high porosity sintered parts, P (10) 347*a*.
Flatley, D. See Boesenberg, W. A.
Fleck, J. P., and Debuisser, J. P. Analysis of inclusions in glass with X-ray microfluorescence, (5) 172*c*.
Fleet, B., Liberty, K. V., and West, T. S. Determination of trace amounts of cobalt in alumina by atomic-absorption spectroscopy, (6) 226*a*.
Fleet, B., Win, S., and West, T. S. Polarographic determination of calcium and magnesium, (9) 315*b*.
Flehmig, W. See Harder, H.
Fleisch, H., Russell, R. G. G., Bisaz, S., Termain, J. D., and Posner, A. S. Influence of pyrophosphate on the transformation of amorphous to crystalline calcium phosphate, (5) 195*b*.
Fleischmann, M., Rangarajan, S. K., and Thirsk, H. R. Effect of diffusion through solution and along surface on electrocrystallization processes (I) potentiostatic case; (II) Faradaic impedance; (III) influence of finite rate of lattice formation, (4) 132*c*.
Fleming, G. S., Reed, R. G., and Seufert, J. L. Radome structural [glass fabric] composite, P (10) 340*a*.
Flengas, S. N. See Charette, G. G.
Fletcher, J. M., Gardner, W. E., Greenfield, B. F., Holdoway, M. J., and Rand, M. H. Magnetic and other studies of ruthenium dioxide and its hydrate, (5) 196*c*.
Fletcher, J. M., and Hardy, C. J. Application of sol-gel processes to industrial oxides, (2) 54*i*.
Fletcher, K. E., and Cole, A. E. Cathode ray tubes [evacuation], P (11) 371*b*.
Fletcher, N. H. See Perrott, C. M.
Fletcher-Terry Co. Glass cutting head, P (1) 10*e*.
Fleurence, A. Yellow color of ceramic bodies made from stoneware clays, (5) 180*a*.
Flintkote Co. Heat exchange structure for rotary kilns, P (6) 228*f*.
Flipot, A. J. See Mestdagh, G.
Flippen, R. B. See Bither, T. A.
Flitner, F. P. Exhaust equipment developments for electrostatic application of porcelain [enamel], (1) 4*a*.
Flockhart, M. G. See Davis, J. H.
Floros, J. Magnetic handling and purification equipment applied to the porcelain enamel manufacturing process, (1) 4*f*.
Flotow, H. E. See Westrum, E. F., Jr.
Flowers, R. H. See Cuthbert, J.
Floyd, J. R. Alumina abrasives—a market study, (6) 205*f*.
Fluid Energy Processing & Equipment Co. Apparatus [fluid impact] for treating solid granular material, P (10) 346*j*. Method for drying or treating wet solid and semisolid materials, P (2) 68*c*.
Flur, B. L., and Griest, A. J. Sputter deposition of nickel-iron manganese ferromagnetic films, P (1) 19*a*.
FMC Corp. Low melting metallic articles reinforced with modified chrysotile, P (6) 217*c*. Magnesia refractory and method of producing same, P (2) 58*i*. Method of preparing carbonized shaped cellulose crystallite aggregates, P (1) 14*i*. Method of producing high temperature resistant structures, P (6) 218*d*. Modified colloidal chrysotile and method of preparing same, P (11) 382*f*. Opening up asbestos with dimethylsulfoxide, P (4) 118*g*.
Fochs, P. D., George, W., and Augustus, P. D. Growth of cadmium sulfide single crystals of controlled composition from the vapor phase, (10) 354*h*.
Fodor, M. See Poko, Z.
Foeg, M. H. Grate cooler control method and apparatus, P (1) 3*g*.
Foerster, H. See Schiller, S.
Foex, M., and Traverse, J. P. Polymorphism in rare earth sesquioxides at high temperature, (1) 34*i*.
Fogarasi, G., Torok, F., and Vdovin, V. M. Vibrational spectra of silacyclohexane derivatives and the Si-C stretching frequencies of various-membered silacycloalkanes, (5) 203*b*.
Fogelberg, C. V., and Hough, W. D. Method for manufacturing hollow plastic articles, P (2) 53*g*. Sectional mold mounts, P (1) 11*d*.
Foldes, S., and Levinstein, M. A. Method for forming an oxidation resistant coating on a substrate, P (5) 172*b*.
Foldesi. I., and Torok, F. Investigation of the Si-O bond of aryloxysilanes on the basis of their infrared spectra, (5) 195*h*.
Foley, F. R. Silicon carbide device, P (2) 66*g*.
Folkman, Y. Diagenetic dedolomitization in the Albian-Cenomanian Yagur dolomite on Mount Carmel (northern Israel), (8) 290*g*.
Folloni, M. Application of the coherent diffusion of Cr*Kα* radiation by light elements to problems of analysis by X-ray fluorescence, (7) 259*i*.
Fomenco, V. S. See Samsonov, G. V.
Fomichev, V. A. Investigation of the energy structure of B and BN by ultralongwave X-ray spectroscopy, (4) 141*c*.
Foner, H. A. Chromatographic separation of sodium, potassium, calcium, and magnesium ions applied to the identification of soluble salts in clays and clay products and of efflorescent salts [on building brick], (9) 315*a*.
Foner, S. See Kurtin, S.
Fong, F. K., and Hiller, M. A. Behavior of F^- interstitials during reduction of Dy^{3+} ions in calcium fluoride, (4) 127*e*.
Fontana, M. G. See Herrnstein, W. H., III.
Fontyn, L. A., Bok, A. B., and Kennet, J. G. TPD electron probe X-ray microanalyzer, (6) 227*e*.
Foote Mineral Co. Lightweight ceramic product and method of making, P (4) 109*d*. Method for making lithium borohydride, P (11) 382*d*. Method for preparing lithium peroxide, P (8) 288*b*.
Footner, P. K., Holmes, D. R., and Mortimer, D. Oxidation of iron-chromium binary alloys, (4) 148*c*.

Forbes, D. H. See Manasevit, H. M.
Forbes, J. W. See Coleburn, N. L.
Ford, G. E., and Sainsbury, J. J. Radiation sensitive apparatus for detecting dirt in transparent bottles, P (4) 101*b*.
Ford, W. F. See Pickering, G. D.
Ford Motor Co. [Bent] laminated glass assembly, P (4) 98*i*. Glass conveyor and heat-treating process, P (10) 339*c*. Glassmaking apparatus with greater transverse heat conduction, P (1) 10*g*. Laminated glass assembly with tapered inner layer, P (7) 248*j*. Method of and chamber for the manufacture of glass, P (10) 339*j*. Method of making a solid ionic conductor, P (8) 283*c*. Process using gas inlets to laterally stretch glass during float glass manufacturing, P (7) 249*d*. Solid state electroluminescent device, P (8) 283*g*. Transducer utilizing electrically polarizable material, P (9) 314*c*.
Fordemwalt, J. N., and Van Pul, B. Isolation of semiconductor devices, P (2) 65*g*.
Fords (Fensbury), Ltd. Radiation sensitive apparatus for detecting dirt in transparent bottles, P (4) 101*b*.
Fordyce, J. S., and Baum, R. L. Infrared reflection spectra of molten fluoride solutions—hydrolysis of tantalum(V) in potassium fluoride-lithium fluoride, (2) 79*c*.
Foreman, D. W., Jr. Neutron and X-ray diffraction study of $Ca_3Al_2(O_4D_4)_3$, a garnetoid, (5) 197*b*.
Forgue, S. V. Vapor depositing infrasensitive antimony tritelluride, P (5) 185*i*.
Forman, A. W. See Mackenzie, B.
Forman, S. A., Kodama, H., and Maxwell, J. A. Trioctahedral brittle micas, (4) 162*h*.
Formigoni, N. P. Fabrication of semiconductor integrated circuits, P (4) 113*a*. See Wu, S. Y.
Fornari, J. C. Susceptor for growing polycrystalline silicon on wafers of monocrystalline silicon, P (1) 19*e*.
Forrest, R. A. High concentration doping of silicon using ammonium phosphate, P (4) 113*j*.
Forsberg, A. R. Stone and heavy grain discharge outlet for gravity separators, P (2) 74*g*.
Forschungslaboratorium. Semiconductive device for reducing distortion in electron optics, P (9) 313*h*.
Forty, A. J. See Forwood, C. T.
Forwood, C. T. Work of fracture in crystals of sodium chloride containing cavities, (2) 84*f*.
Forwood, C. T., and Forty, A. J. Structure of cleavage surfaces around precipitates in sodium chloride crystals, (1) 38*f*.
Foseco Fordath A. G. Process for the production of foundry cores and molds, P (6) 218*c*.
Foseco International, Ltd. Electric arc stabilization in electric arc melting using carbon electrodes, P (11) 374*h*. Hot top for big-end-up ingot molds and method of assembling same, P (11) 374*j*. Method of forming a casting mold, P (11) 375*c*.
Foseco Technik, Ltd. Testing of foundry sand, P (11) 381*c*.
Foseco Trading Akt.-Ges. Apparatus for forming hot top liners, P (7) 252*c*.
Foster, A. M. Method of forming glass-asbestos water-laid sheet, P (7) 252*e*.
Foster, D., and Laird, R. T. System of vertical casting of brick panels, (2) 54*g*.
Foster, D. B. Ovality measurement apparatus comprising two photoelectric gaging systems having an angle between their optical axes of the order of 70°, P (7) 249*a*.
Foster, E. G., and Bloom, M. S. Process for the production of formed gypsum castings, P (10) 336*c*.
Foster, J. D. See Osterink, L. M.
Foster, J. L. See Sisson, C. G.
Foster, J. P., and Reynik, R. J. Mechanism of oxidation of cobalt between 750° and 1000°C using inert gold spheroidal markers, (10) 357*d*.
Foster, L. M. See Plaskett, T. S.
Foster, L. M., and Scardefield, J. E. Process of making gallium phosphide dendritic crystals with grown-in *pn* light emitting junctions, P (5) 185*c*.
Foster, L. M., Woods, J. F., and Lewis, J. E. Anomalous electrical properties of solution-grown, *p*-type GaP, (9) 318*d*.
Foster, P. K. See Duncan, J. F.
Foster, W. E. Transparent safety laminates and method of making same, P (2) 54*b*.
Foster, W. R. Discussion of "Silica transformations in the system PbO-SiO_2," (8) 289*a*. See Lin, H. C.
Foster, W. R., and Lin, H. C. System BaO-Al_2O_3-SiO_2 (II) binary system celsian-silica, (9) 331*a*.
Foster, Benjamin, Co. Coating composition and process, P (8) 275*a*.
Fought, J. Discoloration of glass by vanadium in fuel oil, (4) 95*j*.
Foulon, L. Silica refractories, (1) 8*d*.
Fournier, J. T., and Bartram, R. H. Theory of the optical and magnetic properties of a radiation-induced molecule-ion in aluminum oxide, (10) 362*c*.
Fournier, R. G. See Blum, J. F.
Fournier, R. O. See Rowe, J. J.
Fouse, F. Z. Article transferring means, P (4) 98*h*.
Fowler, A., Howell, H. G., and Schiller, K. K. Dihydrate-hemihydrate transformation in gypsum, (9) 303*i*.
Fox, P. G. See Bowden, F. P.
Foxell, C. A. P., and Summers, J. G. Semiconductor device, P (8) 283*d*.
Foyt, A. G. See Donnelly, J. P.
Fradis, A. D. See Malyshev, M. V.
Fraker, A. C. Barium-iron-oxygen compounds with varying oxygen content and iron valence, (2) 74*f*.
Fraker, A. C., and Stadelmaier, H. H. Eta carbides of molybdenum-iron, molybdenum-cobalt, and molybdenum-nickel, (10) 353*g*.
France, R. W., and Nandor, R. P. Attachment of leads to semiconductor devices, P (4) 112*d*.
Francel, J., Jagodzinski, R. F., and Mansur, F. E. Coated glass and method of making same, P (11) 371*c*.
Francesconi, A. See Camozzo, G.
Francois, B. See Bailly, H.; Braun, C.
Francois, B., and Stora, J. P. Preparation and thermal conductivity of uranium dioxide-metal cermets with oriented structure, (10) 341*h*.
Francois, H. See Carpentier, S.
Frank, B., and Groth, R. Preparation and properties of films of Y_2O_3 and rare earth oxides on glass, (8) 281*d*.
Frank, B., Roeder, E., and Scholz, S. Compaction and shaping of glass powders, (1) 6*a*.
Frank, D. F. See Rizzo, F. E.
Frank, F. C., Lawn, B. R., Lang, A. R., and Wilks, E. M. Strains in abraded diamond surfaces, (1) 38*a*.
Frank, L., and Barr, H. N. Method for making oriented fiber or whisker composites, P (6) 217*j*.
Franke, W. See Heimann, R.
Franke, W., Heimann, R., and Willgallis, A. Formation of Mn-doped single crystals of α-alumina from the gas phase, (7) 265*j*.
Frankel, R. B. See Chappert, J.
Frankel, S. A. See Beebe, R. A.
Franklin, A. D. Born-model calculation of point-defect formation energies in alkaline-earth fluorides, (8) 288*i*. (Editor), Calculation of the Properties of Vacancies and Interstitials—Proceedings of a Conference Held in Shenandoah National Park, Va., May 1966, B (9) 333*h*. See Wachtman, J. B., Jr.
Franklin, W. S. Simplified stacked semiconductor device, P (9) 314*b*.
Franks, F., and Smith, H. T. Apparent molal volumes and expansibilities of electrolytes in dilute aqueous solution, (8) 288*i*.
Frankson, R. W. See West, R. R.
Fransen, J. J. B., and Gilsing, C. P. G. Non-evaporative getter, P (2) 53*j*.
Franz, H., and Kelen, T. Knowledge of the structure of alkali silicate glasses and melts from the bonding of OH groups, (6) 209*h*.
Franzen, H. F. See Gilles, P. W.
Franzini, M. A and B mica layers and the crystal structure of sheet silicates, (9) 317*h*.
Franzosini, P. See Sinistri, C.
Fraser, D. B. Factors influencing the acoustic properties of vitreous silica, (9) 305*c*.
Fraser, H. D. See Knochel, W. J.
Frauenschill, S. Practical experience in the heating of plate glass tanks using natural gas, (9) 306*h*.
Fray, D. J. See Boyer, A. J. G.
Frazee, O. P. See Jackson, D. M., Jr.
Frazer, B. C. See Shirane, G.
Frazer, F. W. See Freeman, A. G.
Frazer, J. See Bostroem, K.
Frechette, M. See Drake, E. G.
Frechette, V. D. Characteristics of fracture-exposed surfaces, (1) 25*g*.
Frechette, V. D., Holleran, L. M., Pasto, A., and Quackenbush, C. L. W. Commercial patch kits—tests and evaluation, (7) 245*h*.
Fredericks, W. J. See Mannion, W. A.
Frederikse, H. P. R., and Candela, G. A. Magnetic susceptibility of insulating and semiconducting strontium titanate, (1) 32*f*.
Fredrichsen, H. Oxygen isotopes of some minerals from the carbonatites of the Fen area, South Norway, (4) 148*c*.
Fredrick, R. E., and Richards, J. D. Thermoelectric compositions of tellurium, manganese, and lead and/or tin, P (1) 19*f*.
Freeberg, F. E., Hartman, K. O., Hisatsune, I. C., and Schempf, J. M. Kinetics of calcium oxalate pyrolysis, (4) 142*a*.
Freedman, B. J., Georgetti, R. A., and Tedeschi, W. R. Process for descaling steel strip in an aqueous organic chelating bath using alternating current, P (5) 172*b*.
Freeh, E. J. Coating thickness determination by means of measuring blackbody radiation resultant from infrared irradiation, P (4) 121*e*.
Freeman, A. G. See Clark, M. W.
Freeman, A. G., and Frazer, F. W. Pseudo-polymorphic transition—the amphibole → pyroxene reaction, (9) 328*h*.
Freeman, I. L., and Rayment, D. L. Scanning electron micrographs of some structural ceramic materials, (6) 227*i*.
Freeman, M. P. Synthesis of finely divided oxide powders, P (9) 317*g*.
Freeport Sulphur Co. Apparatus and process for determining particle size by X-ray absorption analysis, P (9) 315*h*. Process for improving the brightness of clay, P (7) 263*d*. Process for treating clay, P (8) 288*b*.
Freese, R. W., Jr. Infrared incandescent [quartz] lamp, P (8) 282*i*.
Fregerslev, S. See Christensen, A. N.
Frehn, F. Sintered [titanium] carbide hard alloy, P (9) 309*e*.
Freibergs, E. See Agrios, J. P.
Freidenfel'd, E. Zh. See Chkalova, V. V.
Freiman, S. W. See Gokularathnam, C. V.
Freiman, S. W., and Hench, L. L. Further analysis of glass crystallization kinetics, (4) 96*b*.
French, D. N. X-ray stress analysis of WC-Co cermets (I) procedures; (II) temperature stresses, (7) 270*g*.
French, J. W., and Miller, S. Glass [sheet] washing apparatus, P (9) 307*f*.
French, R. R. Crushed stone resources of the Devonian and Silurian carbonate rocks of Indiana, (9) 316*h*. Geology and mining of gypsum in southwestern Indiana, (4) 123*d*.
Frenkel, B. N. See Matveev, M. A.
Fresh, D. L., and Dooling, J. S. Kinetics of the solid-state reaction between magnesium oxide and ferric oxide, (4) 142*e*.
Freund, F., and Gentsch, H. Thermal splitting of H_2 from $Mg(OH)_2$, $Al(OH)_3$, and kaolinite, (6) 239*g*.
Freund, I. Self-*Q*-switching in ruby lasers, (4) 111*h*.
Frey, A. M., and Griffith, J. W. Voltage graded electrical insulator, P (9) 310*a*.
Frey, C. M. See Grosh, J. L.
Fricioni, R. B. Laboratory apparatus, P (2) 58*i*.
Fridman, Ya. B. See Solntsev, S. S.
Fridrich, E. G. Method of making vacuum type electric incandescent lamps, P (11) 371*i*.
Fried, L. J., and Froot, H. A. Thickness measurements of silicon dioxide films over small geometries, (9) 315*e*.
Friedberg, A. L. See Tummala, R. R.
Friedman, A. I. See Beaumont, D. H.
Friedman, G. M. See Allen, R. C.
Friedman, M. Tile setter loading device, P (4) 109*c*.
Friedrich, H. See Hofmann, U.
Friedrich, L. A., and Hirakis, E. Refractory metal articles having oxidation-resistant coating, P (8) 275*i*.
Frieser, R. G. Direct nitridation of silicon substrates, (5) 177*b*.
Fripiat, J. J. See Arjona, A. M.; De Kimpe, C. R.; Leonard, A. J.
Fripiat, J. J., Jelli, A., Poncelet, G., and Andre, J. Thermodynamic properties of adsorbed water molecules and electrical conduction in montmorillonites and silicas, (1) 39*e*.
Fripiat, J. J., Leonard, A., and Uytterhoeven, J. B. Structure and properties of amorphous silico-aluminas (II) Lewis and Bronsted acid sites, (1) 38*j*.
Frisch, B. See Dawihl, W.
Frischat, G. H. Effect of the α, β-quartz transformation on the diffusion of ^{22}Na in SiO_2 glass, (6) 208*i*. Sodium self-diffusion in sodium aluminosilicate glasses, (9) 307*c*. See Tomandl, G.
Frischat, G. H., and Oel, H. J. Diffusion of nitrogen in glass melts, (9) 305*a*.
Friskney, C. A. and Haworth, C. W. Electron probe microanalysis of metal oxides—comparison of correction methods, (1) 21*h*.
Fritsberg, V. Ya. See Grinvald, G. Zh.
Froberg, M. L. See Day, F.
Froemel, J. G. See Sapoff, M.
Froeschle, E. [*Pn*] junction transistor, P (7) 257*g*.
Frolov, A. S. See Verenkova, E. M.
Frondel, C. See Ito, Jun.
Frondel, C., and Ito, Jun. Synthesis of the scandium analog of beryl, (8) 299*h*; errata, (10) 362*c*.
Frondel, C., and Marvin, U. B. Lonsdaleite—a hexagonal polymorph of diamond, (4) 143*a*.
Froot, H. A. See Fried, L. J.
Frosch, C. J. See Ellis, W. C.
Frova, A. F. See Boddy, P. J.
Fruechte, E. See Dersin, H.
Fry, R. Applicator for particulate material, P (5) 171*i*, P (6) 207*j*. Nozzle applicator for dry process enamels, P (1) 5*f*.
Frydl, J. See Pospisil, Z.
Frydman, M. See Schedin, U.
Fryer, G. M., and Roberts, J. P. Tensile creep of porous polycrystalline alumina, (2) 84*c*.
Fryer, J. R. Oxidation of graphite catalyzed by palladium, (9) 326*i*.
Fryxell, R. E., Joyce, D. E., and Szwarc, R. Solubility of uranium in urania, (5) 199*j*.
Fuchino, Yoshio. See Nakai, Tsuneo.
Fuchs, E. O. See Swisher, J. H.
Fuchs, N. A. See Kirsch, A. A.
Fueki, Kazuo; Oguri, Yasuo; and Mukaibo, Takashi. Determination of the self-diffusion coefficient of nickel atoms in nickel sulfide, (8) 290*e*.
Fuerstenau, D. W. See Roy, P.; Somasundaran, P.
Fuhrman, N. See Gordon, E.
Fuhrman, N., Gordon, E., and Holden, R. B. High loaded UO_2-niobium cermets, P (6) 217*a*.
Fuji Kagaku Kogyo Kabushiki Kaisha. Continuous countercurrent washing system by thickener method, P (8) 287*g*.
Fujii, C. T., and Meussner, R. A. Carburization of Fe-Cr alloys during oxidation in dry carbon dioxide, (4) 127*f*. Chromium solubility in wustite at 1000°C: Changes in oxygen activity and lattice parameter, (4) 128*g*.
Fujii, Hironobu. See Okamoto, Tetsuhiko.
Fujii, I., Inouye, T., Muto, H., Onodera, K., and Tani, A. Investigation of rapid and nondestructive fast-neutron activation analysis for many elements by using a semiconductor detector, (9) 315*j*.
Fujii, Minoru, and Koyama, T. Effect of water

on crushed quantity and grain size of raw material during crushing process (II) crushing in edge-runner mill, (10) 341*d*.
Fujii, Mitsuhiro. Service tests on unburned brick in water-cooled cupola, (7) 251*e*.
Fujii, Rokuro. See Shindo, Akio.
Fujii, Satoshi, and Hirota, Masayoshi. Differential thermal analysis of the mixture of gypsum and EDTA, (4) 119*d*.
Fujii, Satoshi; Hirota, Masayoshi; and Seki, Koshi. Quantitative analysis of gypsum by DTA, (4) 120*j*.
Fujii, Takashi. Long-range order of aluminum and silicon in muscovite, (4) 142*i*.
Fujiki, Hideo, and Nomura, Shoichiro. Ferromagnetism in $LaNi_{1/2}Mn_{1/2}O_3$, (1) 29*g*.
Fujiki, Koichi. See Ishihara, Shigetoshi.
Fujimura, Tadato. See Ando, Yoshio.
Fujino, Yoshio. See Sugibuchi, Kiyoshi.
Fujita, Eiichi. Theoretical consideration of the densification process associated with sintering under applied pressure, (4) 160*c*.
Fujita, H. See Toyoshima, Y.
Fujita, Seiichi. See Higuchi, Masaki; Higuchi, S.
Fujita, Yosisige. See Yasutake, Yoshito.
Fujitani, Masataka. See Suzuki, Kazutaka.
Fujitsu, Ltd. Adhesive material and method of using same to adhere ceramic material to metal, P (8) 282*a*. Method of manufacture of glass-sealed semiconductor device, P (8) 283*c*. Method of manufacture of superhigh-frequency transistor, P (11) 377*e*. Method of producing a variable capacitance diode, P (7) 257*c*.
Fujiwara, Akinobu. See Suzuki, Kazutaka.
Fujiwara, Kazuhiko. See Ishiwara, Shigetoshi.
Fujiwara, Shinji, and Fukai, Masazu. Effects of ion pair concentration and temperature of firing on photoluminescence in ZnSe(Cu,In), (1) 28*h*.
Fujiwara, Shinobu. See Hayashi, Shigekazu.
Fujiwara, Shinobu, and Shiraiwa, Takao. Ceramic dielectrics, P (5) 182*j*, P (7) 255*j*.
Fujiwara, Toshiaki. See Terada, Kiyoshi.
Fukai, Hirotoshi. Forming capacity of friction press, (10) 341*i*.
Fukai, Masazu. See Fujiwara, Shinji.
Fukase, Masahiro. See Takeda, Takayoshi; Watanabe, Hiroshi; Yamamoto, Hisao.
Fukuda, Kenzo. See Noto, Yuko.
Fukuda, Kenzo; Noto, Yuko; Onishi, Takaharu; and Tamaru, Kenzi. Mechanism of dehydration decomposition of formic acid over alumina and silica—adsorption measurements during the catalytic reaction, (8) 295*a*.
Fukuda, Kuniya. See Nakagawa, Masuo.
Fukuda, Mitsushiti. See Arai, Yuzo.
Fukuda, Mitsutoshi. See Arai, Yuzo.
Fukuda, Tsuguo; Hirano, Hitoshi; and Koide, Shigenao. Growth and electrical properties of $KTa_xNb_{1-x}O_3$ single crystals, (2) 77*g*.
Fukui, Hiroshi. Method for producing porcelain suitable for insulator, P (6) 220*a*.
Fukui, H., and Higuchi, N. Toughness parameter of electrical porcelain materials, (6) 219*i*.
Fukui, Ichitaro. Method of making electric bulbs, P (11) 371*g*.
Fukui, Masao. See Uei, Isao.
Fukui, Tsunenori. See Tsuzuku, Takuro.
Fukunaga, Makoto. See Sakurai, Toshio.
Fukunaga, Osamu. See Nomura, Shoichiro.
Fukunaga, Tomio. See Suzuki, Osamu.
Fukuoka, Hiromi. See Ohba, Hiroshi.
Fukuoka, Nobuo. See Uchida, Enji.
Fulkerson, W., McElroy, D. L., and Moore, J. P. Comments on "Thermal conductivity of UO_2 at very high temperature gradients," (8) 289*a*.
Fuller, C. W. See Ottaway, J. M.
Fuller, M. See Kobayashi, Kazuo.
Fuller, M. D. See Carmichael, R. S.
Fuller, R. G., and Reilly, M. H. Anion contributions to the electrical conductivity of alkali chlorides, (4) 126*e*.
Fuller Co. Cooler comprising sloping grate sections, P (4) 118*c*. Method and apparatus for blending bulk solids, P (11) 379*f*. Surface area measurement of standard length sample of finely divided solids, P (11) 381*b*. Surface area measurement of variable length sample of finely divided solids, P (4) 122*b*.
Fultman, R. L. See Mitoff, S. P.
Fullman, R. L., and Mitoff, S. P. Electrical device comprising metal oxide-containing solid electrolyte and electrode, P (4) 112*d*.
Fulmor, T. G. See Crocker, B. S.
Fulop, J. See Korach, M.
Fulrath, R. M., and Pask, J. A. (editors). Ceramic Microstructures, B (8) 301*g*.
Funabashi, Wataru. Adhesive for coated abrasive (I), (4) 89*f*.
Funk, E. C. See Kane, J. L.
Funke, A. See Novak, J.
Furdyna, J. K. See Galeener, F. L.
Furey, J. T. See Rairden, J. R., III.
Furukawa, Mitsuhiko. See Sugita, Tadaaki.
Furukawa Electric Co., Ltd. and Mitsui Mihonbashi Muromachi. Electrolytic method for preparing manganese dioxide, P (7) 262*h*.
Furumi, Koichi. See Miyatake, Kazumi.
Furumoto, Shun-ichi. See Arai, Yuzo.
Furuya, H. Lattice and grain boundary diffusion of uranium in ThO_2 and ThO_2-UO_2 solid solutions, (8) 294*c*.
Furuya, H., and Yajima, S. Lattice and grain-boundary diffusions of protactinium in ThO_2 and in a ThO_2-UO_2 solid solution, (5) 196*i*.
Fuschillo, N. See Gimpl, M. L.
Fuseau, M. See Barzac, G.
Fushimi, F. C. See Lonadier, F. D.
Futaki, Hisao. Temperature detector, P (4) 117*d*.
Futaki, Hisao; Kobayashi, Kazuo; Aoki, Minoru; Shimoda, Takeshi; Yamada, Elzaburo; and Narita, Kozio. Thermistor composition containing vanadium dioxide, P (1) 19*e*.
Fuwa, Tasuku. See Iguchi, Yasutaka.
Fyfe, W. S. Some second thoughts on the alumina-silica system, (7) 269*d*. Stability of Al_2SiO_5 polymorphs, (1) 37*j*. See Bischoff, J. L.

Gaballe, T. H. See Robin, M. B.
Gabor, J. D. See Holmes, J. T.
Gadd, J. D., Fisch, H. A., Kmieciak, H. A., and Jones, E. E. Vacuum pack and vacuum slip-pack processes for coating refractory metals, (7) 246*a*.
Gaddy, O. L. See Keune, D. L.
Gado, P. See Asztalos, I.
Gaevoi, M. S. See Kruglitskii, N. N.
GAF Corp. Vitrifiable photosensitive emulsion, P (2) 61*a*.
Gagen-Torn, V. K., and Saksaganskii, G. L. Deformation-film method for preparing hermetic metal-ceramic joints, (2) 61*j*.
Gagne, A. F. See Hurlbut, G. K.
Gaidelis, V. See Viscakas, J.
Gainey, H. G. See Cowan, J. C.
Gaiser, C. J. Amorphous sodium silicate having inherent binding properties and method of producing same, P (9) 317*c*.
Gal, S. See Simon, J.
Galaktionova, A. N. See Kuz'min, N. M.
Galasso, F., Layden, G., and Ganung, G. ANb_2O_6 and ATa_2O_6 phases [A=Br, Sr, or Ca], (5) 192*d*.
Galasso, F. S. See Batt, J. A.
Galchenko, I. E. See Korshunov, B. G.
Galdina, N. M., Rogovoi, M. I., Verlotskii, A. A., and Rublevskii, I. P. Calculation of the temperature field of a cooling casting with different thermophysical characteristics in the mold and external insulation, (2) 47*a*.
Gale, A. J. Fabricating solid state devices by ion implantation, P (6) 221*j*.
Galeener, F. L., and Furdyna, J. K. Propagation and dimensional resonances of helicon-like waves in powdered semiconductors and semimetals, (11) 386*h*.
Galer, R. E. Kiln feed control, P (5) 170*f*.
Galey, W. F. Process for manufacture of glass utilizing gas pressure for glass sizing, P (6) 213*b*.
Galibina, E. A. Principles of fly ash use in the building industry, (2) 45*a*.
Galkin, Yu. M. See Chukhlantsev, V. G.
Gallagher, K. J., Feitknecht, W., and Mannweiler, U. Mechanism of oxidation of magnetite to γ-Fe_2O_3, (8) 295*a*.
Gallagher, K. J., and Phillips, D. N. Proton transfer studies in the ferric oxyhydroxides (I) hydrogen exchange between α-FeOOH and water, (9) 328*h*.
Gallagher, P. K. See O'Bryan, H. M., Jr.
Gallagher, P. K., MacChesney, J. B., and Sherwood, R. C. Moessbauer effect in the system $Co_{1-x}Fe_xS_2$, (11) 386*f*.
Gallagher, R. C., and Barditch, I. F. Integrated complementary MOS-type transistor structure and method of making same, P (7) 256*e*.
Gallagher, R. C., and Corak, W. S. MOS field-effect transistor Hall effect devices, P (9) 313*g*.
Gallagher, T. J. Method of sealing fiber optic devices, P (8) 278*b*.
Galli, G., Morritz, F. L., and Wiley, C. A. Composite heteroepitaxial structure, P (4) 112*i*.
Gallon, T. E. Ferromagnetic domain structure of hematite, (1) 29*e*. Remanent magnetization of hematite single crystals, (1) 36*c*.
Gallon, T. E., Higginbotham, I. G., Prutton, M., and Tokutaka, H. Growth of Ag on KCl observed by LEED and Auger emission spectroscopy, (8) 281*i*.
Galmiche, P. Methods of brazing, P (4) 94*f*.
Gal'perin, E. L., Erman, L. Ya., Kolchin, I. K., Belova, M. A., and Chernyshev, K. S. X-ray investigation of the system Bi_2O_3-WO_3, (8) 301*a*.
Gal'perina, E. L. See Erman, L. Ya.
Galtier, F. Plasma furnace and its adaptation to single crystal growth of ultrarefractory materials—some properties of single crystal calcium oxide, (1) 20*e*.
Galvin, J. L. Accuracy of Brinell impact tests, (11) 379*i*.
Galwey, A. K. See Jones, K. A.
Galwey, A. K., Jones, K. A., and Beckett, R. S. Observations on the relatively high strength of a chalk-aggregate concrete, (2) 44*j*.
Gamber, E. J., and Rauschenbach, R. R. Refractory composition, P (7) 253*b*.
Gambhir, R. S. Heat conduction through polyatomic gas mixtures, (7) 261*e*.
Gambino, R. J. See Cuomo, J. J.
Gamblin, R. L. See Akmenkalns, I. G.
Gammon, J. B., Borcsik, M., and Holland, H. D. Potassium-sodium ratios in aqueous solutions and coexisting silicate melts, (5) 198*f*.
Gane, N. See Bristow, T. J.
Ganguli, D. Crystal chemical considerations in beryl, (2) 73*b*.
Ganguly, A. K. See Panday, V. K.; Zemon, S.
Ganguly, J. Analysis of the stabilities of chloritoid and staurolite and some equilibria in the system FeO-Al_2O_3-SiO_2-H_2O-O_2, (6) 230*h*.
Ganguly, J., and Newton, R. C. Thermal stability of chloritoid at high pressure and relatively high oxygen fugacity, (4) 161*b*.
Ganguly, P. K. See Mitra, N. K.
Ganiel, U. See Eibschuetz, M.
Ganley, W. P., and Dove, B. Galvanoluminescence of tin, (8) 281*h*.
Gans, W., Knacke, O., and Maarouf, E. Erosion and impregnation of magnesite bricks, (4) 104*a*.
Gantois, M. See Faivre, R.
Gantz, R. D. Heat transfer elements for rotary kilns, P (8) 286*e*.
Ganung, G. See Galasso, F.
Gar, L. P. See Narain, J. C.
Gar Precision Products, Inc. Metal abrasive sheet and a method of making same, P (1) 1*h*.
Garasi, L. See Medved, D. B.
Garasi, L., Kaye, S., and Medved, D. B. Method for detection of ultraviolet radiation, P (8) 286*c*.
Garber, J. A., Leaman, T. R., and Skelly, D. C. Bottom pour ladle construction, P (5) 178*b*.
Gard, J. A. See Speakman, K.
Gardiner, J. R. See Regh, J.
Gardner, A. R. Electrets get new look as design uses emerge, (5) 180*j*. Materials for medical use challenge design engineers, (1) 40*e*.
Gardner, H. E. See Jones, F. G.
Gardner, P. J. See Finch, A.
Gardner, W. E. See Fletcher, J. M.
Gardon, R. Glass conveyor and heat-treating process, P (10) 339*c*.
Garfinkel, H. M. Ion-exchange equilibria between glass and molten salts, (5) 172*j*. Strengthening glass by ion exchange (I), (5) 173*d*. See Cramer, W. H.
Garfinkel, H. M., and Lindenthal, J. R. Method of treating glass, P (5) 175*j*.
Garfinkel, M. Solder-bonded semiconductor strain gages, P (9) 314*c*. See Brown, D. M.
Garfinkel, M., and Weininger, J. L. Lithiated nickel oxide crystals, P (6) 221*j*.
Garg, V. N. See Prasad, S.
Garin, L. N. See Shchukarev, S. A.
Garland, J. K., and Schroeder, J. W. Rate of hydrogen diffusion in room-temperature irradiated quartz, (5) 199*i*.
Garnache, R. R. See Lindmayer, J.
Garnero, A. L. Method of fabricating panels of expanded perlite, P (4) 102*g*.
Garnier, G. See Aitcin, P. C.
Garrison, L. H., and Winter, W. E. Apparatus for epitaxially producing a layer on a substrate, P (11) 376*g*.
Garrison, W. E. Glass laminate, P (6) 212*d*.
Garton, G., and Wanklyn, B. M. Crystal growth and magnetic susceptibility of some rare-earth compounds (I) crystal growth, (8) 289*i*. Rare-earth aluminates, (4) 152*d*.
Gartrell, J. T. Process for porcelain enameling and forming sheet metal, P (4) 94*b*.
Gartside, H. See Strafford, K. N.
Gashler, R. See Levy, S. A.
Gashurov, G., and Banks, E. Role of copper in the transformation of hexagonal zinc sulfide, (4) 153*h*.
Gashurov, G., and Levine, A. K. Low-temperature synthesis of manganese activated zinc silicate of superior crystallinity, (4) 143*d*.
Gasic, M. C. See Boskovic, S. B.
Gasiorek, S. Influence of thermal treatment on the polycrystalline structure of sintered TiO_2, (10) 355*f*.
Gaskill, J. R. See Jones, D. E.
Gasparac, R. J., and Peters, H. Bearing support for a crusher and the like, P (8) 287*e*.
Gasparac, R. J., and Szaj, A. P. Bowl securing and bowl removing means, P (7) 262*e*.
Gasper, W. L. Potential water pollutants from porcelain enameling operations, (5) 171*b*.
Gasser, R. P. H., Gowan, P. M., and Newman, D. G. Carbon monoxide isotope exchange with tantalum monocarbide, (10) 350*b*.
Gasson, D. B. See Cockayne, B.
Gastev, J. A. See Perelman, S. M.
Gastuche, M. C. See Brown, G.
Gastuche, M. C., Brown, G., and Mortland, M. M. Mixed magnesium-aluminum hydroxides (I) preparation and characterization of compounds formed in dialyzed systems, (9) 324*j*.
Gatos, H. C. See Morizane, K.; Mroczkowski, R. S.; Singh, R.; Witt, A. F.
Gatti, A. See Cree, R. F.
Gatti, A., and Laskow, W. Process for producing magnesia-alumina spinel whiskers, P (10) 343*c*.
Gatzke, H. Rapid firing — requirements, possibilities, and limits; for which products can present-day continuous production lines be used? (11) 381*i*.
Gaudin, A. M., and Decker, T. G. Contact angles and adsorption in the system quartz-water-dodecane modified by dodecyl ammonium chloride, (1) 26*a*.
Gault, J. M. Unijunction transistor with improved efficiency and heat transfer characteristics, P (5) 185*i*.
Gaur, H. C., and Sethi, R. S. Complex formation in molten salts—association constants of silver chlorocomplexes in molten K-NO_3 + $Ba(NO_3)_2$ and comparison with quasi-lattice theory, (9) 318*d*.

Gaur, J. N. See Jain, D. S.
Gautsch, O. Fission induced sorption of krypton in uranium carbide, (9) 321*e*. See Muatacchi, C.
Gavish, E. See Allen, R. C.
Gavrilov, O. R. See Nikolaev, R. K.
Gavrilov, O. R., Krivoshein, A. S., and Nisel'son, L. A. Phase relations in systems of the tetrachlorides of zirconium and hafnium with aluminum chloride, (8) 296*f*.
Gavrilov, O. R., and Nisel'son, L. A. Systems $NbCl_5$-NaCl and $NbCl_5$-KCl, (4) 159*j*.
Gavrilovic, J. See Holt, D. B.
Gavryuchenkov, F. G., and Novikov, G. I. System $ErCl_3$-KCl, (8) 299*c*.
Gay, P. See Champness, P. E.
Gaydosh, D. S. See Magor, J. K.
Gazza, G. E., Barfield, J. R., and Preas, D. L. Reactive hot-pressing of alumina with additives, (8) 284*g*.
Gazzarrini, F. See Colombo, U.
Gdula, R. A. High-field losses of adulterated lead zirconate-titanate piezoelectric ceramics, (1) 17*d*.
Geankoplis, C. J. See Cunningham, R. S.
Geary, D. A., and Hough, J. M. Thermal balance for measuring transport during vapor phase crystal growth, (5) 188*j*.
Gebhardt, F. See Kessler, W.
Gebhardt, F., and Kimmel, S. Supervision of raw materials and finished products in the glass industry by means of X-ray fluorescence spectroscopy, (9) 307*g*.
Gebhardt, M. See Neuhaus, A.
Gebruder Buhler, A. G. Pneumatic separator and bulk solids feeder, P (7) 263*c*.
Gebruder Giulini G.m.b.H. Method of treating titanium ores with hydrochloric acid to produce titanium tetrachloride therefrom, P (2) 74*g*. Production of α-calcium sulfate hemihydrate, P (4) 93*a*.
Geddes, A. L. See Bottger, G. L.
Gee, A. Method of treating semiconductor devices or components, P (6) 222*i*. *Pin* diode with a nonuniform intrinsic region width, P (11) 378*e*.
Gehenot, C. Process and installation for glass tempering and cooling, P (2) 54*b*.
Gelb, C. B., Jr., Jamison, G. E., and Scott, J. N. Selenium rectifier, P (7) 258*a*.
Geick, R., Hakel, W. J., and Perry, C. H. Temperature dependence of the far-infrared reflectivity of magnesium stannide, (2) 84*b*.
Geiger, G. E. See Tien, R. H.
Geiger, M. Conversation with the ceramist Benno Geiger, (4) 90*f*.
Geigling, D. See Schafer, H.
Geigy Chemical Corp. Method of patching ceramic lined equipment and patch therefor, P (4) 94*d*.
Gejyo, Tetsuo. See Minagawa, Shigekazu.
Gel'd, P. V. See Alyamovskii, S. I.
Geldart, D. Gas-solid reactions in industrial fluidized beds, (2) 67*h*.
Gel'fman, A. Ya., Tsirlin, Yu. A., and Ekkerman, V. M. Investigation of the distribution of impurities in solids with the aid of β-active isotopes, (2) 70*c*.
Gell, P. A. M. Method of melting and supplying glass along a feeder duct, P (1) 11*e*.
Gell, P. A. M., and Waterworth, T. H. Furnaces for heating glass electrically, P (7) 248*h*.
Geller, S., and Nesbitt, E. A. Garnet compositions, P (8) 282*h*.
Gemesi, J. Optimum steam-curing period for concrete investigated by ultrasonic methods, (8) 274*d*.
Genahr, R., and Brolde, K. Fiber-optic cable comprising a plurality of light conductive fibers, P (4) 98*e*. Fiber-optic cable comprising rows of interleaved light-conducting fibers with masking of fiber portions in zones common to fibers of adjacent rows, P (4) 98*f*.
Genco, J. I., and Almaula, B. C. Surface reduction of lead glass tubes, (10) 338*a*.
Gendelev, S. Sh., and Soboleev, Ch. S. Spiral growth of monocrystalline layers of ferrites, (4) 155*j*.
Gendler, G. S. See Fedorovskii, Ya. A.
General Dynamics Corp. Ceramic-to-metal bonding method, P (2) 64*h*. Process for descaling steel strip in an aqueous organic chelating bath using alternating current, P (5) 172*b*. Process for joining metals and ceramics having grossly different coefficients of thermal expansion, P (5) 172*b*. Process for reclaiming spent electrolytes used for electrolytically descaling steel, P (2) 46*b*.
General Electric Co. Alkaline earth yttrate luminescent materials [rare earth activated], P (9) 314*d*. Alumina-ceramic sodium vapor lamp, P (10) 344*a*. Arc tube mounting, P (2) 52*j*. Article comprising stabilized zirconia and a current collector embedded therein, P (2) 64*f*. Asbestos-phosphoric acid molding composition, P (1) 13*g*. Calcia-magnesia-alumina seal compositions, P (7) 255*g*. Calcium halophosphate phosphors, P (6) 220*h*. Cemented chromium carbide containing small additions of phosphorus, P (8) 279*a*. Coating glasses for electrical devices, P (7) 248*b*. Coherent light source utilizing pentavalent manganese activated calcium chlorophosphate crystal, P (6) 221*b*. Compact source discharge lamp manufacture, P (5) 174*b*. Compensating means for a [slotted] piezoelectric sensing element, P (1) 18*c*. Conductive electrode for reducing the electric field in the region of the junction of a junction semiconductor device, P (4) 112*a*. Cryogenic avalanche photodiode of InSb with negative resistance characteristic at potential greater than reverse breakdown, P (9) 312*e*. Deposition of pyrolytic material, P (10) 344*f*, P (11) 379*e*. Diamond and cubic boron nitride grains coated with photopolymerized material, P (2) 43*g*. Direct filament enclosed incandescent lamps and contact means therefor, P (9) 307*b*. Disk laser having pumping means in direct optical combination with the disk end faces, P (5) 174*b*. Disk laser having pumping means in direct optical communication with the disk end faces, P (5) 174*c*. Electric heat lamp and electric devices, P (4) 112*d*. Electric incandescent lamp and method of manufacture, P (9) 307*c*. Electric incandescent lamp with shock and vibration resistant filament support structure, P (7) 248*e*. Electrical device comprising metal oxide-containing solid electrolyte and electrode, P (4) 112*d*, P (7) 256*e*. Electrical device including stabilized zirconia solid electrolyte, P (2) 64*i*. Electrically conductive tool and method for making, P (6) 221*h*. Electron tunnel emission apparatus and methods, P (9) 312*f*. Envelope wall with two continuous ledges for positioning and supporting aperture mask, P (2) 64*d*. Filament mount structure for electric lamps [fused SiO_2] and manufacture thereof, P (7) 248*g*. Filament support for incandescent electric lamps, P (7) 248*g*. Fluorescent panel lamps with white emitting phosphor coated on envelope backplate and red emitting phosphor coated on envelope faceplate, P (2) 64*h*. Frequency modulated semiconductor junction laser, P (4) 113*f*. Fuel materials for nuclear reactors, P (4) 106*i*. Glass-silicon assemblies, P (2) 53*a*. Glower lamp and process, P (6) 221*b*. Halogen-cycle incandescent lamp with planar filament, P (7) 248*i*. Halogen regenerative cycle incandescent lamp, P (10) 339*g*. Heated cathode and method of manufacture, P (1) 18*g*. High gain silicon photodetector, P (7) 256*a*. High pressure reaction vessel for the preparation of diamond, P (2) 67*j*. High purity niobium films formed by glow discharge cathode sputtering, P (6) 221*f*. Image orthicon glass target with aluminum-tantalum oxide coating, P (7) 256*b*. Inorganic glass coating and method for making, P (11) 369*a*. Insulated electrical conductor or thermocouple assembly with a membrane gastight seal, P (4) 121*i*. Lamp bridge making method and apparatus, P (5) 175*c*. Lamp bulb conveyor mechanism, P (1) 10*j*. Lamp phosphor adherence, P (5) 183*g*. Lead-in conductor for electrical devices, P (5) 175*d*. Light emitting semiconductor devices of improved transmission characteristics, P (8) 282*b*. Light projection device and light source support means therefor, P (7) 249*a*. Lithiated nickel oxide crystals, P (6) 221*j*. Low pressure electric discharge lamp electrode, P (9) 312*f*. Luminescent materials of zinc magnesium germanate activated with manganese, P (11) 377*c*. Magneto-optic glass body and electric circuit element in readout apparatus including the same, P (4) 99*a*. Mercury bismuth halide photochemical arc lamp light sources, P (9) 307*h*. Metal boride-metal carbide-graphite deposition, P (11) 377*f*. Metal-insulator-metal tunneling device with exponential I-V characteristic only in the negative resistance range, P (8) 282*e*. Metallizing and bonding nonmetallic bodies, P (4) 114*e*. Method of analyzing materials to determine the impurity content thereof, P (6) 227*j*. Method of assembling lamp filament and support structure, P (2) 53*b*. Method of forming carbon resistor films, P (4) 114*e*. Method of forming metal boride coating on wire, P (6) 208*a*. Method for forming an oxidation resistant coating on a substrate, P (5) 172*b*. Method of heat-sealing flash lamps containing combustible gas mixtures, P (2) 53*d*. Method for making a coated silica fiber and product produced therefrom, P (6) 213*c*. Method of making glass-silicon composite bodies, P (11) 371*h*. Method of making a high frequency transistor structure, P (11) 377*d*. Method of making a molybdenum-tungsten thimble seal, P (6) 222*i*. Method of making superconductors containing flux traps, P (6) 222*j*. Method of making vacuum type electric incandescent lamps, P (11) 371*i*. Method of manufacturing electroluminescent display devices, P (11) 377*e*. Method of manufacturing semiconductor camera tube targets, P (1) 18*c*. Method and means for separating individual fibers from a fibrous mass, P (5) 186*e*. Method for producing electroluminescent zinc-cadmium sulfide-oxide phosphors, P (11) 377*g*. Method [vapor deposition] of forming a superconducting metallic film, P (7) 257*d*. Multiple surface glass seal for a high voltage discharge device contacting the inner and outer surface and the open end edge of the hollow tubular anode lead, P (10) 345*c*. Niobium end seal, P (9) 313*i*. Piezoresistive thermometer, P (2) 66*e*. Plural [lacquer] coated transparent colored lamp and method of forming same, P (5) 176*c*. Process for construction of high temperature capacitor, P (6) 223*g*. Process for growing diamond on a diamond seed crystal, P (5) 186*f*. Process for making aluminum-containing ferrites, P (4) 115*j*. Process for producing magnesia-alumina spinel whiskers, P (10) 343*c*. Processes of epitaxial deposition or diffusion employing a silicon carbide masking layer, P (9) 313*e*. Protection means for surface semiconductor devices having thin oxide films therein, P (11) 378*a*. Pyrolytic graphite electrical resistance element, P (4) 116*d*. Recrystallization of anhydrous calcium acid phosphate from the dihydrate form, P (5) 191*d*. Semiconductor devices, P (6) 223*h*. Semiconductor devices adapted for pressure mounting, P (10) 346*c*. Semiconductor junction laser with electronically displaceable and deflectable beam, P (7) 258*d*. Semiconductor light emitter and combination light emitter-photocell wherein the reflector of the light emitter is comprised of a material different from that of the light emitter, P (11) 378*f*. Semiconductor low voltage switch, P (5) 185*j*. Semiconductor strain gage, P (4) 116*h*. Semiconductor switching devices with a tunnel junction diode in series with the gate electrode, P (6) 223*j*. Sheathed conductor with hermetic seal, P (9) 314*b*. SiC *pn* junction electroluminescent diode with a donor concentration diminishing from the junction to one surface and an acceptor concentration increasing in the same region, P (11) 378*i*. Silicon controlled rectifier gating circuits with a high frequency triggering voltage and photocells, P (11) 378*i*. Silicon dioxide coatings utilizing a plasma, P (6) 224*a*. Simplified piezoresistive force sensing device, P (4) 116*j*. Single-ended electric incandescent lamp filament support, P (1) 19*i*. Solder-bonded semiconductor strain gages, P (9) 314*c*. Solid stabilized zirconia or thoria having a layer of tantalum pentoxide and titanium oxide thereon, P (1) 19*a*. Stabilization of cubic silicon carbide, P (2) 59*g*. Strontium yttrate luminescent materials [rare earth activated], P (9) 314*d*. Superconductor quaternary alloys with high current capacities and high critical field values, P (4) 117*c*. Temperature compensation of crystal-controlled circuit, P (10) 346*e*. Thermionic cathode, P (6) 224*d*. Thermistor device and method of producing said device, P (6) 224*e*. Tin-lead-tin layer arrangement to improve adherence of photoresist and substrate, P (9) 314*b*. Tubular halogen cycle incandescent lamp with inner cylinder for universal operation, P (6) 224*b*. Tunneling semiconductor device exhibiting storage characteristics, P (4) 117*b*. Type II superconductors containing magnetic particles, P (9) 314*d*. Yttrium vanadate europium phosphor preparation by precipitation using ammonium carbonate, P (7) 258*e*. Zinc silicate phosphor of improved maintenance, P (4) 117*c*.
General Electric Co., Ltd. Closure of tubes of refractory oxide material, P (6) 221*a*. Formation of coatings on germanium bodies, P (1) 18*e*. Method of making superconducting magnets, P (6) 222*j*.
General Electrodynamics Corp. Photoconductive device, P (5) 184*e*. Photoconductive layer separated from reactive opaque pattern by transparent conductive layer, P (4) 115*e*.
General Instrument Corp. Method of making a phosphorus-protected semiconductor device, P (7) 257*g*. Method for trimming cermet resistors, P (11) 377*i*. Process and apparatus for making thin film capacitors [vacuum deposition], P (11) 378*g*.
General Mills, Inc. Clay catalyst for polymerization of unsaturated fatty acids, P (4) 124*i*.
General Motors Corp. Ceramic foam, P (9) 307*a*. Glass seal for a turbine, P (1) 10*f*. High temperature-pressure metal-to-glass seal constructions, P (6) 212*g*. Method of fabricating ferrite bodies, P (5) 183*d*. Method for improving the switching coefficients of ferrites with hysteresis loops of rectangular shape, P (11) 377*b*. Method of making a ceramic core, P (5) 178*j*. Method of making a thermistor, P (6) 222*a*. Method of manufacturing ceramics, P (8) 284*f*. Spark plug and seal therefor, P (2) 66*h*. Thermocouple head, P (11) 381*d*. Thermocouple with reducing atmosphere producing sheath, P (9) 316*a*. Thermoprobe assembly, P (4) 122*c*. Vibratory bowl, P (6) 213*h*.
General Refractories Co. Basic refractory lining brick and process, P (5) 178*a*. Method of bonding a metal plate to a refractory brick with a chloroprene-phenolic adhesive, P (7) 252*d*. Plastic chrome ore composition, P (2) 59*c*. Refractory brick suspension arrangement, P (2) 59*e*. Refractory ramming composition, P (4) 107*i*.
General Steel Industries, Inc. Abrasion resistant glass bead with sharp softening range and process for making the same, P (4) 98*b*. High melting point glass beads with sharp melting range and process for making the same, P (6) 212*f*.
General Technologies Corp. Method of growing alpha alumina and beta silicon carbide whiskers, P (2) 59*c*. Method of growing alpha-alumina single crystal ribbons, P (5) 186*d*.
General Telephone & Electronics Laboratories, Inc. Cadmium-substituted ferrite materials, P (7) 255*g*. Electroluminescent cell matrix material of improved stability, P (7) 256*f*. Elements [TaC] for incandescent devices, P

(7) 248*f*. Europium doped yttrium oxide optical maser materials, P (10) 344*g*. Uranium activated fluorescent materials, P (10) 346*b*.

Geng, H. See Babl, A.

Genovese, E. R. See Chang, Hsu.

Genzer, M. See Blum, J. M.

Genser, M., and Smith, P. C. Method of assembly of power transistors, P (4) 114*i*.

Gensler, J. D. Production of low density rigid shapes, P (5) 176*g*.

Gentile, A. L. See Andres, F. H.

Gentile, A. L., and Stafsudd, O. M. Czochralski-grown proustite and related compounds, (9) 319*c*.

Gentsch, H. See Freund, F.

Genzabella, C. F., and Wade, R. C. Silicon semiconductor with metal-silicide heterojunction, P (11) 378*j*.

Geoffroy, J. Installation and method for the treatment at high temperature and cooling of granular or divided solid products utilizing a fluidized layer, P (5) 186*a*.

George, J. W., Katsaros, N., and Wynne, K. J. Infrared spectra of the tetrachlorides and tetrabromides of selenium and tellurium, (11) 385*h*.

George, T. D., and Wagner, J. B., Jr. Diffusion of nickel and chlorine into *p*-type lead telluride at 700°C, (10) 352*g*.

George, W. See Binns, D. B.; Fochs, P. D.

George, W., and Popper, P. Dielectric properties of some commercial alumina materials at 9368 MHz, (2) 61*g*.

Georgescu, V. See Viscrian, I.

Georgetti, R. A. See Freedman, B. J.

Georgia Kaolin Co. Aluminosilicate pigment and method of making same, P (1) 23*j*. Magnetic materials and methods of making the same, P (1) 24*a*. Modified montmorillonite containing exchangeable ammonium cations and preparation thereof, P (2) 74*h*. Potentiometric control of bleaching of kaolin clays, P (1) 24*b*.

Gerard, J. A. See Hill, T. E., Jr.

Gerasimov, E., and Kovachev, I. Effect of some additions on the sintering of corundum, (5) 177*c*.

Gerasimov, Y. M. See Distler, G. I.

Gerber, W. J. See Curran, D. R.

Gerber Scientific Instrument Co. Solid state matrix for display system or the like, P (11) 379*a*.

Gerecht, U. G. Economic problems in the mining of Bavarian clay, quartz, kaolin, feldspar, and pegmatite sand, (7) 262*a*.

Gerek, G. Apparatus for measuring and controlling film thickness, P (10) 346*f*.

Gereth, R. See Light, T. B.

Gerew, J. T., and Hoeft, R. Glass cutter [hand], P (11) 371*i*.

Gerhard, E. R. See Ramaswamy, E. R.

Gerhard, G. C., and Ing, S. W. High gain silicon photodetector, P (7) 256*a*.

Gerhard Mensel Glasbearbeitungswerk. Method of working [cutting] glass with absorbent by a laser beam, P (10) 339*d*.

Gerlach, J. L. See Lutwitzi, L. E.

Gerlach, L. O. See Thiele, T. N.

Gerlach, W. Controllable semiconductor rectifier unit, P (6) 221*g*. Four-zone semiconductor rectifier with spaced regions in one outer zone, P (2) 64*i*.

Gerloff, G. See Voelker, U.

Germann, K. Diagenetic patterns in the Wettersteinkalk (Ladinian, Middle Trias), Northern Limestone Alps, Bavaria and Tyrol, (1) 27*g*.

Germann, R. W. See Ferretti, A.

Gerrard, V. G. See Lu, Wei-Chen.

Gershenzon, M., Thomas, D. G., and Trumbore, F. A. Electroluminescent junction device including a bismuth doped group III(a)-V(a) composition, P (4) 112*g*.

Gersoene, H. See Duemecke, G.

Gerstein, B. C. See Rioux, F. J.

Gerstein, B. C., Jelinek, F. J., Habenschuss, M., Schickell, W. D., Mullaly, J. R., and Chung, P. L. Thermal study of groups II-IV semiconductors: lattice heat capacities and free energies of formation—heat capacity of Mg_2Si from 15°-300°K, (4) 161*b*.

Gerstner, D. Aligning [mask] method and apparatus, P (11) 376*e*. Semiconductor arrangement with capacitative shielding means between conductive strips and semiconductor body, P (2) 66*d*.

Gerstner, D., Ehlbeck, H. W., and Epple, R. Semiconductor device with an emitter, base, and collector region, P (11) 378*d*.

Gervids, I. A., Opaleichuk, L. S., and Mel'nikov, F. I. Properties of cordierite as a filler for heat-resistant concrete, (11) 368*a*.

Geschke, D., Pfeifer, H., and Winkler, H. Proton relaxation in liquids sorbed on alumina, (5) 199*f*.

Geschwind, S. See Imbusch, G. F.

Gessner, A. W. See Sze, M. C.

Gettins, R. B. See Heron, G. F.

Geus, J. W., Nobel, A. P. P., and Schutte, H. Effects of hydrogen and oxygen chemisorption on the ferromagnetic anisotropy of nickel-on-silica particles, (5) 194*c*.

Geusic, J. E. See Bonner, W. A.; Singh, S.; Smith, Richard G.

Geusic, J. E., Levinstein, H. J., Singh, S., Smith, Richard G., and Van Uitert, L. G. Continuous 0.532-μm solid-state source using $Ba_2NaNb_5O_{15}$, (4) 129*g*.

Gevers, R. See Socino, G.

Ghare, D. B., and Sinha, A. P. B. Electrical and magnetic properties of zinc-nickel manganites, (9) 321*b*.

Ghobadian, A. See Pregl, O.

Ghormley, J. A. Enthalpy changes and heat-capacity changes in the transformations from high-surface-area amorphous ice to stable hexagonal ice, (2) 76*h*.

Ghose, S. See Evans, B. J.

Ghosh, A., and King, T. B. Kinetics of oxygen evolution at a platinum anode in lithium silicate melts, (7) 267*i*.

Ghosh, A. K. See Addiss, R. R., Jr.

Ghosh, D. K. See Bishui, B. M.

Ghosh, R. K., and Chatterjee, M. R. Design of gap graded cement mixes with poor grades of sand using rounded aggregates, (1) 2*f*.

Giachi, A. Ceramic artists and their work—Bruno and Ingeborg Asshoff, (6) 205*j*; Goerge Hohlt, (11) 367*h*.

Giacomelli, A., and Indelli, A. Salt effects in reduction of inorganic anions at dropping mercury electrode, (10) 360*a*.

Giaever, I. Electron tunnel emission apparatus and methods, P (9) 312*f*.

Gianino, P. D. See Czerlinsky, E. R.

Gibb, F. G. F. Flow differentiation in the xenolithic ultrabasic dikes of the Cuillins and the Strathaird Peninsula, Isle of Skye, Scotland, (4) 136*j*.

Gibbon, D. See Caslavska, V.

Gibbon, D. L. See Brindley, G. W.

Gibbs, D. W. See Petersen, A. A.

Gibbs, G. B. Vacancy generation and the kinetics of oxidation, (9) 332*f*.

Gibbs, G. V. See Birle, J. D.; White, E. W.

Gibbs, G. V., and Grender, G. C. Inexpensive crystal structure models of framework tetrahedra, (8) 285*e*.

Gibbs, R. J. Quantitative X-ray diffraction analysis using clay mineral standards extracted from the samples to be analyzed, (7) 260*a*.

Gibson, D. W. Method of decreasing the metallic impurities of fibrous carbon products, P (4) 106*g*.

Gibson, H. D. See McVey, C. I.

Gibson, R. See Cummings, H. B.

Gie, O. T., Krijtenburg, G. S., and Nijhof, B. J. Method of manufacturing ferrites, P (6) 222*b*.

Gie, T. I. See Klein, M. V.

Giegerich, W., and Trier, W. (editors). Glass Machines—Construction and Operation of Machines for the Forming of Hot Glass, B (11) 389*a*.

Gielisse, P. J., and Doser, M. Thermistor device and method of producing said device, P (6) 224*e*.

Gier, T. E. See Rogers, D. B.

Gieseke, E. W., and Glasser, L. Dielectric behavior and proton conduction in solids (I) borax, (4) 131*a*.

Gieskieng, D. H. Method and apparatus for preheating particulate feed material for a rotary kiln [counterflow], P (7) 261*e*.

Giess, E. A. See O'Kane, D. F.; Scott, B. A.

Giess, E. A., Scott, B. A., Burns, G., O'Kane, D. F., and Segmueller, A. Alkali strontium-barium-lead niobate systems with a tungsten bronze structure—crystallographic properties and Curie points, (7) 254*e*.

Giessen, B. C. See Borromee-Gautier, C.

Gil'bert, E. N. See Artyukhin, P. I.

Gilbert, G. J. Method of fabricating semiconductor device, P (10) 345*g*.

Gilbert, M. C. High pressure stability of acmite, (9) 322*f*. See Richardson, S. W.; Wones, D. R.

Gilbert, V. Methods for evaluating basic refractories in glass tank regenerators, (8) 279*b*.

Gilde-Farkas, M., and Ferenc, S. Rheological characteristics and deposition of kaolinite suspensions, (9) 329*a*.

Giles, C. H., da Silva, A. P., and Cameron, A. Determination of pore size distribution of powders from solute adsorption, (6) 225*h*.

Gilkes, R. J. See Curry, D.

Gillen, F. M. See Beinert, W. B.

Gillery, F. H. Metal-tungsten bronze films, P (10) 337*a*.

Gilles, P. W. See Spear, K. E.

Gilles, P. W., Franzen, H. F., Stone, G. D., and Wahlbeck, P. G. High-temperature vaporization and thermodynamics of the titanium oxides (III) vaporization characteristics of the liquid phase, (1) 30*g*.

Gilles, P. W., Hampson, P. J., and Wahlbeck, P. G. Dissociation energy of $TiO(g)$ and the high-temperature vaporization and thermodynamics of the titanium oxides (V), (11) 383*j*.

Gillespie, G. J. See Detrick, R. S.

Gillespie, T., and Settineri, W. J. Effect of capillary liquid on the force of adhesion between spherical solid particles, (1) 27*e*.

Gillin, L. M., and Kelley, A. Electron microscopy of pyrolytic graphite, (8) 291*f*.

Gillis, P. P. Discussion of "Critical analysis of the theory of the double cantilever method of measuring fracture-surface energies," (2) 47*f*.

Gillooly, G. R. See Rabatin, J. G.

Gillot, J., Lux, B., Cornuault, P., and du Chaffaut, F. Catalysis of the graphitization of a furfuryl alcohol coke by titanium and vanadium, (1) 11*j*.

Gillott, J. E. Carbonatation of $Ca(OH)_2$ investigated by thermal and X-ray diffraction methods of analysis, (8) 289*b*. Study of the fabric of fine-grained sediments with the scanning electron microscope, (8) 285*g*.

Gillson, J. L. See Bither, T. A.; Bouchard, R. J.; Rogers, D. B.; Sleight, A. W.

Gilman, J. J. See Bonis, L. J.

Gilmore, J. P. See Oshida, O. A.

Gilsing, C. P. G. See Fransen, J. J. B.

Gilson Screen Co. Aggregate size testing apparatus and process, P (7) 262*d*. Pulsatory screening device, P (4) 118*i*.

Gilvey, J. P., and Hershoff, L. Mica membrane mounting structure for cathode-ray storage tube, P (8) 283*f*.

Gimesi, O. See Rady, G.

Gimpl, M. L., McMaster, A. D., and Fuschillo, N. Influence of orientation on properties of grain boundaries in NaCl, (1) 31*a*.

Gingerich, K. A. Mass-spectrometric evidence for the molecules UC and CeC and predicted stability of diatomic carbides of electropositive transition metals, (11) 385*j*.

Gingerich, K. A., and Placente, V. Dissociation energy of gaseous gallium monophosphide, (6) 231*h*.

Gingrich, R. I. Grinding fixture for television funnels, P (10) 339*f*.

Ginsberg, M. J., and Krock, R. H. Alloys for brazing silicon nitride material, P (6) 217*f*. Method of wetting silicon nitride, P (1) 18*e*.

Ginstling, A. M. See Budnikov, P. P.

Ginther, R. J. See Sigel, G. H., Jr.

Gioffre, V. C. See Edgecombe, D. A.

Giordmaine, J. A. See Porto, S. P. S.

Giorgi, A. L. See Krupka, M. C.

Giorgi, A. L., Szklarz, E. G., Krupka, M. C., Wallace, T. C., and Krikorian, N. H. Occurrence of superconductivity in lanthanum sesquicarbide, (10) 357*i*.

Giorgi, A. L., Szklarz, E. G., Krupka, M. C., Wallace, T. C., and Krikorian, N. H. Occurrence of superconductivity in yttrium dicarbide, (5) 197*j*.

Giorgi, A. L., Szklarz, E. G., and Wallace, T. C. Anomalous superconducting properties of carbides and nitrides of group IVA and VA elements, (10) 350*d*.

Giovanetti, A., and Sanders, R. F. Process for recovering pigmentary titanium dioxide from nonpigmentary waste titanium dioxide, P (11) 382*i*.

Girgis, B. S. See Razouk, R. I.

Girton, D. G., and Anderson, W. W. Diffusion of rare earths into II-VI compounds, (11) 383*e*.

Gissane, W. J. M. See Barrow, R. F.

Gittins, A., and Williams, H. D. Effect of creep rate on the mechanism of cavity growth, (1) 27*e*.

Gittos, A. J. Extraction of alumina from bauxite, P (1) 23*h*.

Gitzen, W. H., and Hart, L. D. Process for producing kappa alumina, P (8) 288*e*.

Gitzen, W. H., and MacZura, G. Production of ceramic bodies, P (6) 220*b*.

Giutronich, J. E. See Walter, L. S.

Gjelsvik, T. Laboratory testing of [fusion] sealed glazing units, (1) 7*d*.

Glaces de Boussois. Ornamental glass slab containing flat glass strips, P (5) 176*c*.

Gladneva, L. I., Efremenkova, V. I., Lebedeva, L. S., Spivak, G. V., Shelamov, V. A., and Yurasova, V. E. Detection of the structure of sintered materials of the Me-MeO system by ionic bombardment, (7) 265*a*.

Gladrow, E. M. See Smith, W. M.

Gladushchenko, V. A. See Zakharchenko, M. A.

Gladyshevskii, E. I., Fedorov, T. F., Kuz'ma, Yu. B., and Skolozdra, R. V. Isothermal section of the molybdenum-iron-boron system, (1) 31*c*.

Glaenzer, R. R. Distinctiveness with glass, (2) 48*h*.

Glanert, H. Source, distribution, supplies, and prospects of liquid gas [in Germany], (6) 228*e*.

Glantz, P. O. Wettability and adhesiveness of dental materials, (6) 220*a*.

Glanz, G. Thermal conductivity of the system UO_2-SiO_2 at 100°-800°C, (9) 331*e*. Thermal diffusivity of the uranium dioxide-silicon dioxide system with varying uranium dioxide concentrations at 100°-800°C, (10) 342*j*.

Glaser, H. I. Apparatus for melting and processing heat-softenable mineral materials, P (1) 10*h*. Method and apparatus for processing heat-softened mineral material, P (4) 99*f*.

Glasner, A., and Kenat, J. Crystallization of KCl from aqueous solutions in the presence of lead ions (I) a calorimetric study, (7) 264*i*.

Glass, A. M. Optical spectra of Cr^{3+} impurity ions in ferroelectric $LiNbO_3$ and $LiTaO_3$, (11) 386*a*. See Searle, T. M.

Glass, A. M., and Searle, T. M. Optical investigation of Cr^{3+} ion diffusion in magnesium oxide, (4) 147*i*.

Glass-Tite Industries, Inc. Wire beader, P (11) 379*c*. Work holder for aligning and sealing (4) 101*e*.

Glasser, F. P. New data on kentrolite and

melanotekite—ternary phase relations in the system PbO-Fe_2O_3-SiO_2, (4) 146*b*. See Imlach, J. A.

Glasser, L. See Giesekke, E. W.

Glasser, L. S. D. See Jamieson, P. B.

Glasson, D. R. Reactivity of lime and related oxides (XVI) sintering of lime, (8) 287*b*.

Glasson, D. R., Huff, E. G., Jones, J. A., and Sheppard, M. A. Formation and reactivity of oxides and basic salts (II) radioisotope studies of some calcareous materials, (10) 354*b*.

Glasson, D. R., and Jayaweera, S. A. A. Formation and reactivities of nitrides (I) review and introduction; (II) calcium and magnesium nitrides and calcium cyanamide, (10) 353*i*.

Glasson, D. R., and O'Neill, P. Reactivity of lime and related oxides (XVII) sulfating of lime with magnesium and aluminum sulfates; (XVIII) production of plasters, (8) 287*c*.

Glasson, D. R., O'Neill, P., and Sheppard, M. A. Formation and reactivity of oxides and basic salts (I) basic magnesium chlorides and sulfates, (10) 353*j*.

Glathart, J. L., and Preston, F. W. Behavior of glass under impact—theoretical considerations, (2) 46*f*.

Glaze, J. A. See Kemp, J. C.

Gleed, W. L., Hill, J. S., Hursey, K. H., and Stuart, P. R. Bakeable vacuum evaporator for the deposition of large area thin film circuits, (1) 20*i*.

Gleim, P. S. See Bean, K. E.

Gleim, P. S., and Sherer, J. B. Vapor deposition apparatus including orbital substrate support, P (10) 346*c*.

Gleim, W. K. T. See O'Hara, M. J.

Gleiter, H. Precipitation hardening by diffusion in the stress field of a dislocation, (1) 35*e*.

Gleiter, H., Hornbogen, E., and Baro, G. Mechanism of grain boundary glide, (1) 32*d*.

Glicksman, L. R. Cooling of glass fibers, (4) 95*a*.

Glicksman, M. E., and Schaefer, R. J. Investigation of solid/liquid interface temperatures via isenthalpic solidification, (6) 234*a*.

Gliemeroth, G. Phototropic glass with favorable kinetics of the phototropic process, (4) 96*f*.

Globe-Union, Inc. Process for establishing low Zener breakdown voltages in semiconductor regulators, P (10) 345*f*. Process for making photosensitive semiconductor devices, P (1) 19*c*. Semiconductor device having improved resistance to radiation damage, P (11) 378*c*.

Gloster, A. Process for producing sodium sesquicarbonate and soda ash from trona, P (10) 349*d*.

Glovatsky, A., Shinal, J. B., and Slobbe, W. W. Method for the fabrication of image display screens, P (7) 257*d*.

Glover, G. H. See Champlin, K. S.

Gloyna, E. F., and Ledbetter, J. O. Principles of Radiological Health, B (6) 242*a*.

Glozman, I. A. See Postnikov, V. S.

Gluck, J. V. See Chiang, Ping-Wang.

Glueck, R., Lutz, E., Riess, H., and Weinmann, K. Semiconductor elements with disturbed crystalline surface structure in a junction area, P (8) 283*f*.

Glushkova, V. B. See Davtyan, I. A.

Glynn, T. W. Strengthening glass sheets by ion exchange, P (4) 101*b*.

Gnatyuk, G. E. See Kainarskii, I. S.

Gnedashevskaya, E. S. See Bondarev, K. T.

Gnehm, C., Nitsche, R., and Wild, P. New phases in the system Zn-In-S, (9) 325*f*.

Gnesin, G. G. See Kurdyumov, A. V.

Goalby, B. B. See Waterfield, C. G.

Gobin, P. See Merlin, J.

Godejahn, G. C., Jr. Methods of making a semiconductor structure including opposite conductivity segments, P (1) 18*e*.

Godron, Y. Sintering of vitreous products and of refractories in the presence of a vitreous phase, (6) 211*e*.

Goeddel, W. V. See Tully, G. R., Jr.

Goedertier, P. V. Method of making high purity metal zeolite and product thereof, P (2) 74*e*.

Goerens, R. Manufacture of sheets or wicks from fibers of thermoplastic material such as glass fibers, P (8) 277*f*.

Goering, H. L. See Reid, F. J.

Goettsch, R. A. Construction pots, (10) 335*h*.

Goetz, J. Study of the glass polishing process (I) relation between polishing efficiency and crystalline structure of iron oxides; (II) role of mechanical processes during glass polishing (5) 173*e*; (III) action of material displacement on the leveling of the relief layer during polishing with free and bonded grains, (6) 211*b*.

Goetz, J., and Stanek, J. Study of the glass polishing process (IV) surface defects during polishing with bonded grains, (9) 307*f*.

Goetz, W., and Niebergall, R. Crystalline phase in the sodium titanium phosphate system, (9) 319*h*.

Gogotsi, G. A. See Antonenko, V. M.

Gokhale, B. G., Chesler, R. B., and Boehm, F. Chemical shift of the $K\alpha_1$ X ray of tin in its oxides, (4) 128*d*.

Gokularathnam, C. V., Freiman, S. W., DeHoff, R. T., and Hench, L. L. Thickness error in quantitative transmission microscopy of ceramics, (8) 277*b*.

Gold, D. P. Average and typical chemical composition of carbonatites, B (4) 167*h*.

Gold, L. W. See Krausz, A. S.

Goldberg, D. Contributions to the study of systems formed by alumina and some oxides of trivalent and tetravalent metals, especially titanium oxide, (5) 193*f*.

Golde, K. H., and Buschmann, H. Apparatus for pouring molten metal, P (11) 374*e*.

Golden, J. Whiskerlike fibers from chrysotile asbestos, (4) 124*e*.

Goldfinger, P. Definition of high temperature chemistry, B (4) 165*b*.

Goldheim, D. L. See Westwood, A. R. C.

Goldman, W. A. Zinc sulfide phosphor, P (7) 258*f*. See Strongin, O.

Goldsmith, J. R., and Newton, R. C. *P-T-X* relations in the system $CaCO_3$-$MgCO_3$ at high temperatures and pressures, (9) 328*i*.

Goldsmith, L. A. See Shaw, D.

Goldsmith, N. See Murray, L. A.

Goldstein, A. See Banks, E.

Goldstein, D., Buehler, W. J., and Wiley, R. C. Method for treating, working, and bonding refractory metals and alloys, P (4) 107*g*.

Goldstein, H. W. See Truison, O. C.

Goldstein, J. I., Majeske, F. J., and Yakowitz, H. Preparation of electron probe microanalyzer standards using a rapid quench method, B (1) 40*f*.

Goldstein, M. Comments on "Role of densification in deformation of glasses under point loading," (7) 247*a*.

Goldstein, N. H. Air flow determination, (1) 20*h*.

Golightly, J. S. Producing bent laminated windshields, P (10) 340*a*.

Golob, H. R. See Hammel, J. J.

Golub, A. M., Maidukova, T. N., and Limar, T. F. Preparation of lanthanum aluminate by joint precipitation, (5) 198*h*.

Golynko-Vol'fson, S. L., and Sudakas, L. G. Some correlations in the manifestation of the binding properties of phosphate systems, (7) 245*c*.

Gomaa, I. See Bishay, A.

Gomes, J. M., and Wong, M. M. Preparation of tungsten carbide by electrodeposition, (8) 286*i*.

Gomes de Mesquita, A. H. Polytypism in silicon carbide, (10) 359*c*.

Goncharov, V. P., Lashko, A. S., and Poltavtsev, Yu. G. High-temperature furnace for the X-ray diffraction analysis of melts, (2) 69*i*.

Gonser, B. W. (editor). Modern Materials—Advances in Development and Applications (Vol. 6), B (4) 166*h*.

Gontar, K. V., and Zakharchenko, M. A. Some cross sections of the quaternary reciprocal system Li,K,Ba||F,Cl, (8) 298*b*.

Gonzalo, J. A., Cox, D. E., and Shirane, G. Magnetic structure of $FeSb_2O_4$, (1) 32*f*.

Good, P. C., and Tress, J. E. Recovery of hydrofluoric acid from waste fluosilicic acid—preliminary studies, (5) 190*i*.

Goodenough, J. B. Band model for transition-metal chalcogenides having layer structures with occupied trigonal-bipyramidal sites, (5) 192*f*. See Longo, J. M.

Goodfellow, T. L. See Caffyn, J. E.

Goodman, A. M. Photoemission of electrons from *n*-type degenerate silicon into silicon dioxide, (4) 149*g*. Photoemission of holes from silicon into silicon dioxide, (4) 149*h*.

Goodman, J. F. See Asher, R. C.; Clunie, J. S.

Goodwin, D. W. See Cockayne, B.

Goodwin, G. L., and Coblentz, R. C. Environmental control system for glass manufacturing, P (4) 98*e*.

Goodwin, R. J., Mori, E. A., Pekarek, J. L., Schaub, P. W., and Zinkham, R. E. Hydraulic jet drilling method using ferrous abrasives, P (4) 89*i*.

Goodwin-Coblentz Associates, Inc. Environmental control system for glass manufacturing, P (4) 98*e*.

Goon, E. J. Tantalum nitride powder and method for its preparation, P (5) 179*f*.

Gooner, C. F. See Cross, L. E.

Goosey, M. H., Dexter, A. H., Wilson, J. N., Leep, R. W., Hodder, W. K., Brady, E. R., and Page, L. C. High speed temperature monitor, P (11) 381*e*.

Goossens, W. See Camozzo, G.

Gopal, B. S. V., and Reddy, K. V. Conductivity, Hall effect, and magnetic resistance in semiconductors, (4) 109*f*.

Gordienko, S. P. See Bolgar, A. S.

Gordon, E. See Fuhrman, N.

Gordon, E., and Fuhrman, N. Process of making high loaded UO_2-niobium cermets, P (4) 107*b*.

Gordon, E. I. See Crowell, M. H.

Gordon, R. S. See Terwilliger, G. R.

Gordon, W. D., and Norman, R. S. Sheathed conductor with hermetic seal, P (9) 314*b*.

Gordy, J. Synthetic gemstones, P (6) 224*c*.

Goren, S. L. See Spielman, L.

Goretzki, H. Structure and properties of high melting point intercalation compounds of the transition metals, (11) 374*h*.

Gorgenyi, T., Huschka, H., and Popp, W. Preparation of coated $(Th,U)C_2$-particles by reaction sintering and coating in a fluidized bed, (9) 308*i*.

Gorman, H. See Stanton, R. L.

Gormann, W. Effect of carbonic binder on the properties of hydrothermally hardened silica-lime compositions in the system CaO-SiO_2-H_2O-CO_2, (11) 372*j*.

Gornostansky, S. D., and Stager, C. V. Vanadium quadrupole coupling tensor in KVO_3, (4) 163*d*.

Gorobets, F. T. See Pivinskii, Yu. E.

Gorokh, A. V. See Novokhatskii, I. A.

Gorokhovskii, V. A. See Shabanov, A. G.; Shirkevich, T. L.

Goroshchenko, Ya. G. See Belyakova, E. P.

Gorshkova, L. V., Fedorov, T. F., and Kuz'ma, Yu. B. Rhenium-chromium-carbon system, (1) 36*e*.

Gorski, F. T. Structural [fibrous] panel and method of production, P (7) 249*f*.

Goshgarian, H. Monolithic integrated circuits with a plurality of isolation zones, P (6) 222*j*.

Gosse, G., Lehr, P., and Albert, P. Study of the kinetics and evaporation mechanisms during electron beam melting of Zr-O and Zr-Si alloys, (9) 309*c*.

Gosudarstvenny Vsesojuzny Nauchno-Issledovatelsky Institut Stroitelnykh Materialoi i Konstruktsy. Plant for calcining binding and refractory materials, P (4) 107*j*.

Goswami, A. K. Absolute reflective spectra of ceramic barium titanate, (1) 16*b*.

Goswami, A. K., Cross, L. E., and Buessem, W. R. Internal field theory of high permittivity in fine-grained barium titanate, (2) 79*f*.

Gotlib, L. I. Simplified methods for determining the strength of ceramic coatings, B (5) 204*e*.

Got'manova, T. T. See Mokhosoev, M. V.

Goto, Eizo. See Ose, Akira.

Goto, K. See Shibala, S.

Goto, Kazuhiro. See Kashida, Koichi.

Goto, M., Molony, B., and Ridge, M. J. Transformation of finely divided soluble anhydrite into orthorhombic anhydrite, (1) 39*i*.

Goto, Tsuneaki, and Okada, Toshihiro. High frequency conductivity of reduced rutile, (2) 78*e*.

Goto, Yasumasa. See Nishimoto, Kozo.

Gottardi, V. See Bettinali, C.

Gottardi, V., Locardi, B., Bianchini, A., and Martini, P. L. Structural compacting observed in some lead glasses at different temperatures, (4) 97*b*.

Gottlieb, G. E. See Wang, C. C.

Gottschalk, K. Arc tube mounting, P (2) 52*j*.

Gottschalk, K., and Wilson, J. Compact source discharge lamp manufacture, P (5) 174*b*.

Gotz, J. Polishing of glass with a bonded polishing agent (I) leveling of the surface relief, (10) 338*f*.

Gough, E., Isard, J. O., and Topping, J. A. Electrical properties of alkali-free borate glasses, (11) 369*h*.

Gould, R. E., and Simmons, G. A., Jr. Pumping vane type glass feeder, P (4) 100*j*.

Goulding, F. S., and Lothrop, R. P. Semiconductor detector having a lithium compensated shelf region between opposite conductivity type regions, P (4) 116*b*.

Goundry, P. C. Method and apparatus for producing crystalline semiconductor ribbon, P (10) 346*i*.

Govorov, A. A. Apparatus for thermal analysis, (7) 259*h*.

Gow, J., III. See Dietsch, H. E.

Gowan, P. M. See Gasser, R. P. H.

Graber, B. C. See Cary, K. H.

Grabowski, J. T. Development of a 64-output MOS transistor selection tree, (8) 281*a*.

Grace, R. E. See Rigdon, M. A.

Grace, W. R., & Co. Accelerator for portland cement, P (5) 170*j*. Amide grinding aid, P (11) 382*h*. Aromatic acetates as grinding aids, P (5) 170*d*. Cement set retarder, P (5) 170*e*. Cement set retarding composition, P (6) 207*c*. Coprecipitated $CaHPO_4{\cdot}2H_2O$ and $CaSO_4{\cdot}2H_2O$ pigment and method of preparation, P (8) 287*h*. Fluid energy mill, P (5) 186*f*. High temperature phosphorus containing molding compositions and ceramics, P (9) 309*f*. Ion exchange of crystalline zeolites, P (1) 23*j*. Method of increasing the grinding efficiencies of minerals and cement, P (5) 191*b*. Mineral grinding aids, P (8) 274*e*. P (8) 288*c*. Preparation of vermiculite paper, P (6) 218*h*. Process for preparing high density uranium dioxide particles and compositions, P (8) 280*a*. Process for preparing microspheroidal silica, P (10) 349*c*. Process for preparing molecular sieves, P (1) 24*b*. Process for preparing thorium dioxide-uranium dioxide sol, P (2) 59*c*. Set retarded portland cement, P (2) 45*f*. Stabilized zeolites, P (9) 317*g*. Synthetic zeolite, P (2) 61*b*. Uranium trioxide aquasol process, P (10) 349*f*. Vinyl acetate grinding aid, P (8) 288*e*.

Grach'yan, A. N. See Ponomarev, I. F.

Graefen, H. Use of porcelain enamel in the chemical industry, (5) 171*h*.

Graeme-Barber, C. See Bell, R. L.

Graf, R. B. Phase transformations in the system Cu_2S-Ag_2S, (5) 198*j*.

Graf, R. E. See Young, R. W.

Graff, E. A. See Ropp, R. C.

Graff, W. A. Coating glasses for electrical devices, P (7) 248*b*.

Graham, H. E. Drying compressed air, (2) 67*d*.

Graham, L. J. See Chang, R.

Graig & Seeley, Ltd. Radiant gas burner, P (7) 261*g*.

Gramlich, S., and Holdt, G. Spectroanalytical determination of chrome concentration in rubies, (5) 188*f*.

Granberry, D. S., McCalip, R. L., and Lovelace, B. K. Method of making diffused semiconductor devices, P (6) 222*g*.

Grand-Clement, A. M. See Carpentier, S.

Granguly, A. K. See Zemon, S.

Granitzki, K. E. High temperature properties of mullite bricks, (4) 104*g*.

Granovskii, Yu. V. See Komissarova, L. N.

Grant, N. J. See Borromee-Gautier, C.
Grant, P. M., and Suits, J. C. Reflectivity and band structure of EuO, (11) 387*b*.
Grant, W. A. See Konjevic, R.
Graulier, M., and Michel, M. Alumina agglomerates and method for producing same, P (4) 124*g*.
Gray, D. R. See Thompson, R. J.
Gray, H. B. See Basch, H.
Gray, M. Design—practical and impractical, (7) 244*f*.
Gray, N. B., Stump, N. W., Boundy, W. S., and Culver, R. V. Sulfation of lead sulfide, (1) 38*g*.
Gray, P. V. See Brown, D. M.; Taft, E. A., Jr.
Gray, R. J. New methods point the way, (1) 21*f*.
Gray, W. T. See Williams, A. J., Jr.
Great Lakes Carbon Corp. Graphite heating element assembly and furnaces containing same, P (1) 23*b*.
Greaves, E. I. Modulus of rupture of high-alumina refractories at elevated temperatures and their performance in arc-furnace roofs, (6) 216*d*.
Greaves, M. J., Werner, T., and Greenwalt, R. B. Agglomeration method and apparatus, P (6) 225*e*.
Grebene, A. B. Monolithic structure with three-region complementary transistors, P (4) 115*j*. Monolithic structure with three-region or field effect complementary transistors, P (4) 115*j*.
Grebenshchikov, R. G. Comparative crystallochemical systematics and morphotropic transformations of silicates and their analogs (germanates and fluoroberyllates), (4) 129*c*. See Shirvinskaya, A. K.
Grebenshchikov, R. G., Shirvinskaya, A. K., Parfenenkov, V. N., Shitova, V. I., and Toropov, N. A. System strontium oxide-germanium dioxide, (2) 84*a*.
Grebenyuk, A. A. See Karaulov, A. G.
Green, A. P., Refractories Co. Basic refractory for oxygen converters, P (8) 279*i*. Coke bonded [tar impregnated] basic refractory, P (7) 252*h*.
Green, C. F. See Bracken, A. T.
Green, D. See McAvoy, B. R.
Green, D. H. Tubular halogen cycle incandescent lamp with inner cylinder for universal operation, P (6) 224*b*.
Green, T. J. See Davidge, R. W.
Greenbaum, M. A. See Blauer, J.; Ko, H. C.
Greenbaum, M. A., Weiher, J., and Farber, M. Thermodynamics and physical properties of beryllium compounds (VIII) heat of fusion and high-temperature heat capacity of beryllium oxide, (1) 39*f*.
Greenberg, J. See Dornfeld, J. E.
Greenberg, L. S. See Desmond, T. J.
Greenberg, S. B., and Korostoff, E. Method of heat-treating thin magnetic films in a transverse magnetic field, P (2) 65*d*.
Greenblatt, M. See Banks, E.
Greene, C. H., and Platts, D. R. Behavior of bubbles of oxygen and sulfur dioxide in soda-lime glass, (4) 94*g*.
Greene, E. F. See Persky, A.
Greene, F. T., and Margrave, J. L. Vapor pressure of boron oxide over the range 1946°-2419°K, (4) 163*d*.
Greene, P. D. See Bradley, J. N.
Greene, P. D., Gross, P., and Hayman, C. Heat of formation and transition temperatures of solid lithium hexafluoroaluminate, (9) 322*c*.
Greene, P. E. See Burmeister, R. A., Jr.
Greene, R. L., Emmett, J. L., and Schawlow, A. L. Effect of ultraviolet pumping on ruby laser output, (1) 28*d*.
Greenfield, B. F. See Fletcher, J. M.
Greenhow, R. C., and Schmidt, A. J. Undamped regular spiking of a ruby laser in a misaligned cavity, (4) 111*g*.
Greenland, D. J. See Theng, B. K. G.
Greenland, L. P. Simultaneous determination of tantalum and hafnium in silicates by neutron activation analysis, (1) 22*b*.
Greenler, R. J. Method of and chamber for the manufacture of glass, P (10) 339*j*.
Greenler, R. J., and Augustin, E. H. Glassmaking apparatus with greater transverse heat conduction, P (1) 10*g*.
Greenwalt, R. B. See Greaves, M. J.
Greenwood, J. H. See Bowden, F. P.
Greenwood, R. Thermal behavior of SiO_2-X and its relation to the natural silica minerals—a correction, (9) 331*e*.
Greer, A. H. Composite spheroidal phosphorescent organic polymer article and process, P (11) 376*j*.
Greer, R. T. See Roy, R.
Grefco, Inc. Method for manufacturing improved perlite filter aid products, P (7) 263*a*.
Gregg, S. J. Surface chemical study of comminuted solids and compacted solids, (4) 157*j*. See Asher, R. C.; Bickley, R. I.
Gregg, S. J., and Saenz, J. P. Effect of grinding on precipitated magnesium hydroxide, (2) 73*c*.
Grego, P., and Howell, R. G. Red stained soda lime glass, P (6) 213*c*.
Gregor, L. V. See Hu, S. M.
Gregory, C. K., and Owen, A. J. New bricks—new problems, (4) 104*h*.
Gregory, J. W., and Nored, D. L. [Rocket] combustion chamber, P (11) 375*c*.
Gregory, N. W. See Rice, D. W.
Gregory, T. M. See Moreno, E. C.
Greiner, H. Molded graphite bodies and process for making the same, P (7) 252*i*.
Greiser, W. Porcelains of Dr. Ambrogio Pozzi, (11) 367*i*.
Grekila, R. B., and Needham, O. S., Jr. Method [flame spray] of coating with glass, P (10) 337*b*.
Grenawalt, J. J., Roblin, M. J., and Birkle, A. J. Yield strength after firing of low carbon enameling steels, (8) 275*g*.
Grender, G. C. See Gibbs, G. V.
Grenier, J. C. See Beucher, M.; Durif, A.
Grenot, M., and Huber, M. X-ray and neutron diffraction study of the Jahn-Teller type of tetragonal deformation in the spinels $MgGa_{2-x}Mn_xO_4$ and $MgCr_{2-x}Mn_xO_4$, (10) 363*g*.
Greskovich, C. See Stubican, V. S.
Grewen, O. Simple apparatus for measuring the load of a controlled stroke press, (6) 225*b*.
Gridnev, S. A. See Postnikov, V. S.
Griem, P. D., Jr. Method of and apparatus for heating material, P (5) 175*i*.
Grierson, R. See Bonis, L. J.
Griest, A. J. See Flur, B. L.
Grieveson, P. Investigation of the Ti-C-N system, (5) 195*h*.
Griffin, R. S., and Edmonds, H. Process control in the application of vitreous enamel to sheet iron, (4) 93*e*.
Griffin, T. A., Humrick, R. J., and Hill, E. R. Process of attaching a collector grid to a [CdS] photovoltaic cell, P (8) 283*j*.
Griffith, C. F. See Dickinson, G. A.
Griffith, J. W. See Frey, A. M.
Griffiths, R., and Pryde, J. A. Solubility of nitrogen in tantalum, (8) 298*a*.
Griggs, D. Hydrolytic weakening of quartz and other silicates, B (6) 241*d*.
Grigore, N. See Avram, C.
Grigson, C. W. B. Amorphous nucleation in metals, (4) 126*d*. See Thomsett, M. F.; Tillett, P. I.
Grigson, C. W. B., and Tillett, P. I. Filtered electron diffraction measurements from thick polycrystalline metal foils, (4) 136*h*.
Grill, A. See Schieber, M.
Grim, R. E. Clay Mineralogy, B (10) 364*i*.
Grimal'skii, N. P. See Bondarev, K. T.
Grimes, N. W., Hilleard, R. J., Waters, J., and Yerkess, J. X-ray diffraction study of disorder in $MgFe_2O_4$ and $Mg(Cr,Al)O_4$, (5) 203*h*.
Grimm, F. A., and Porter, R. F. Investigations of the photochemistry of $H_2B_2O_3$, (11) 385*j*.
Grimm, T. C. See Culp, J. D.
Grimmeiss, H. G. Photosensitive semiconductor with two radiation sources for producing two transition steps, P (4) 115*f*.
Grimshaw, R. W. Castables and moldables, (6) 224*g*.
Grinvald, G. Zh., and Fritsberg, V. Ya. Temperature dependence of the velocity and absorption of ultrasonic waves in some perovskite-type ferroelectric solid solutions, (4) 159*d*.
Griscom, D. L., Taylor, P. C., and Bray, P. J. Paramagnetic resonance of room-temperature-stable V-type centers in γ-irradiated alkali halide-boron oxide glasses, (6) 210*d*.
Griscom, D. L., Taylor, P. C., Ware, D. A., and Bray, P. J. ESR studies of lithium borate glasses and compounds gamma-irradiated at 77°K—evidence for a new interpretation of the trapped-hole centers associated with boron, (2) 48*i*.
Gritton, W. R. See Crookston, J. A.
Gritz, E. E. See Ropp, R. C.
Grizik, A. A., and Plyushchev, V. E. Properties of polymorphic modifications of rubidium trizirconate and trihafnate, (4) 151*g*.
Grjotheim, K. See Valla, O.
Grjotheim, K., and Zuca, S. Self-diffusion of Na^+ and K^+ in their molten fluorides, (8) 297*d*.
Grochowski, M., and Kulakowski, B. Procedure of batch correction, (4) 97*d*.
Grodkiewicz, W. H. See Van Uitert, L. G.
Groebler, H. The good old ever-young-again enameled cooking pot, (5) 171*f*.
Grofesik, J. Increase in strength of porcelain insulators, (2) 60*d*.
Grofesik, J., Naray-Szabo, I., and Peter, E. Quantitative determination of phase composition of ceramic raw materials and green and fired bodies, (8) 280*c*.
Grollier-Baron, T. See Delrieux, J.
Groom, C. M. See Seiwatz, H.
Grosh, J. L., and Frey, C. M. Process of making a glass fiber vessel having a clevis joint, P (5) 176*d*.
Grosheva, V. M. See Panasevich, V. M.; Tresvyatskii, S. G.
Groskaufmanis, E. Decorative bricks, tiles, or the like and methods of manufacturing the same, P (1) 11*h*.
Gross, P. See Greene, P. D.
Gross, P., Hayman, C., and Joel, H. A. Heats of formation of the fluoroborates of lithium, sodium, and potassium, (9) 322*d*.
Gross, P., Hayman, C., and Stuart, M. C. Halogen combustion calorimetry of refractory compounds—heats of formation of boron nitride and boron fluoride, (2) 55*i*.
Grosse, D. W. See Theissing, H. H.
Grosskopf, J. W., Jr., Thayer, A. G., and Welker, R. H. Mounting glass sheets, P (11) 372*a*.
Grosskopf, K., and Scholze, H. Microhardness of glasses, (6) 210*g*.
Grossman, D. G., and Isard, J. O. Lead titanate glass-ceramics, (6) 209*j*.
Grosvalet, J. Semiconductor device having dielectric and metal protectors, P (7) 258*b*.
Grosvenor, D. E. See Nelson, P. A.
Groth, R. Sodium vapor discharge lamp with infrared reflecting coating, P (1) 19*j*. See Frank, B.
Grove, R. M. Identification of ordinary portland cement and sulfate resisting cement in hardened concrete samples, (6) 206*i*.
Grover, J. E., and Orville, P. M. Partitioning of cations between coexisting single and multisite phases with application to the assemblages orthopyroxene-clinopyroxene and orthopyroxene-olivine, (6) 235*e*.
Groves, G. W. See Shockey, D. A.
Groves, J. D. Purification of pigments, P (8) 288*c*.
Groves, W. O. Method for the preparation of inorganic single crystal and polycrystalline electronic materials, P (6) 222*d*. Process for the preparation of compound semiconductors, P (11) 378*j*.
Grozdanov, L. Solubility of solid phases at high pressure and stability of some silica modifications, (1) 37*a*.
Grubb, A. D. L-O-F semicontinuous thermal evaporation plant, (10) 346*h*.
Grubb, E. F., Hammer, F. W., and Monks, J. R. Method of treating glassware, P (1) 11*b*.
Grubb, P. L. C. Phase changes in aged sesquioxide gels and some analogies with katamorphic process, (9) 326*h*.
Gruber, G. A. See Chu, T. L.
Gruber, J. B., and Menzel, E. R. Absorption spectrum of Np^{4+} in single-crystal thorium oxide, (11) 383*b*.
Gruber, P. Spray drying in the Kobanya Porcelain Works, (8) 280*c*.
Grudner, G. M. See Moldovan, I.
Gruen, D. M. See Angell, C. A.
Grum-Grzhimailo, O. S. See Bystrikov, A. S.
Grum-Grzhimailo, S. V. See Boikova, A. I.
Gruner, K., Koltermann, M., and Mueller, K. P. Quartz formation and crystallization from binary lithium silicate melts and glasses, (9) 306*i*.
Grungo, G. Structural changes in siliceous and silicoalumina refractories in metallurgy, (2) 58*b*.
Gualandi, D. See Federighi, T.
Guebert, K. W. See Olstowski, F.
Guenthard, H. H. See Oehler, O.
Guenther, W. P. Method and apparatus for rotary processing and classification, P (6) 229*h*.
Guerga, M. See Blin, C.
Guerrieri, S. Preparation of alkali metal carbonates from the corresponding sulfates or sulfides, P (1) 24*c*.
Guffy, J. C. See Larson, J. O.
Gugel, E., Ettmayer, P., and Schmidt, A. System silicon-carbon-nitrogen, (4) 159*f*.
Gugel, E., and Schuster, P. High temperature cross bending strength testing of ceramic materials, (6) 226*j*.
Gugeler, A. L. Study of the adherence of porcelain enamel to aluminum, (1) 5*b*.
Gugeler, A. L., and Ballard, D. B. Aluminum-porcelain enamel interface as observed by electron microscopy, (10) 336*e*.
Guggenheim, H. J. See Barker, A. S., Jr.; Chen, F. S.; Levinstein, H. J.; MacChesney, J. B.; Testardi, L. R.
Guha, S. K., Das, S. R., and Sen, S. Chemical decolorization of some Indian clays, (2) 73*a*.
Guha, S. K., and Sen, S. Infrared spectra of some Indian bentonites, (10) 355*g*. Two Rajasthan bentonites containing interstratified clay minerals, (10) 363*c*.
Guha, S. K., Sen, S., and Gupta, K. S. Effect of some organic additions on the rate and nature of casting of a porcelain composition, (5) 179*j*.
Guidi, G. See Bucci, C.
Guido, M. See Balducci, G.; De Maria, G.
Guillaud, C. See Paulus, M.
Guillaume, Y. Sheet handling apparatus and method, P (4) 101*f*.
Guillou, M. See Asquiedge, M.
Guillou, M., Millet, J., Asquiedge, M., Busson, N., Jacquin, M., Palous, S., Pithon, M., and Lecante, A. Electrochemical properties of the zirconia-neodymium oxide system at high temperatures, (1) 28*d*.
Guin, J. B. High speed crushers, P (6) 229*g*.
Guinier, A. Can atoms be seen? B (4) 168*j*.
Gulbransen, E. A. See Tallman, R. L.
Gulbransen, E. A., Andrew, K. F., and Brassart, F. A. Oxidation of silicon carbide at 1150° to 1400°C and at 9×10^{-3} to 5×10^{-1} torr oxygen pressure, (2) 81*i*. Oxidation of silicon at high temperatures and low pressure under flow conditions and the vapor pressure of silicon, (1) 34*d*.
Gulde, C. J. Apparatus for making concrete facing bricks with varied color and texture, P (5) 170*d*.
Gulevic, O. Effect of glaze on the strength of insulator porcelain, (2) 60*b*.
Gulf General Atomic, Inc. Deposition of massive pyrolytic carbon, P (1) 13*h*. Method of fabricating low permeability nuclear fuel bodies, P (2) 59*b*. Shock wave optically pumped laser, P (9) 314*b*.
Gulf Research & Development Co. Hydraulic jet drilling method using ferrous abrasives, P (4) 89*i*.
Gulotta, J. A. Manufacture of float glass of a thickness greater than equilibrium thickness, P (6) 212*i*. Method and apparatus for forming a compound bend in a glass sheet on a

gas support bed, P (2) 53*g*. Method and apparatus for initially restricting the divergent flow of float glass, P (6) 213*a*.
Gummel, H. K. See De Loach, B. C., Jr.
Gumulyauskas, A. See Vektaris, B.
Gundersen, G. See Almenningen, A.
Gundersen, G. E. See Battles, J. E.
Gunderson, J. M. See Clayton, W. A.
Gundlach, H. Behavior of quartz sands in mixture with lime under hydrothermal conditions, (1) 2*c*.
Gundlach, H., Hoerster, E., and Radermacher, G. Influence of pore space on the hydrothermal synthesis of calcium silicate hydrate, (11) 368*c*.
Gundlach, T. F. Gas-hydraulic system for crushers, P (4) 124*a*.
Gundlach, T. J., Co. Gas-hydraulic system for crushers, P (4) 124*a*.
Gundrum, J. H., and Hensel, V. B. Glassware inspection device, P (4) 99*d*.
Gungle, W. C., Peterson, C. L., and Waymouth, J. F. Harness construction for metal arc type lamp, P (5) 183*c*.
Gunicheva, T. N. See Losev, N. F.
Gunn, C. B. Origin of diamonds in drift of the north central United States—a discussion, (4) 147*i*.
Gunther, L., and Heckert, W. Dependence of the electrical resistance of SiC heating rods on the Al_2O_3 and Fe_2O_3 content of the SiO_2 used, (4) 103*d*.
Gupta, G. C., and Malik, W. U. Thermal analysis of synthesized chlorite structures, (4) 160*h*.
Gupta, G. P. See Sodha, M. S.
Gupta, H. N. D., and Mitra, N. K. Studies on commercial glasses (I) use of mercurous nitrate solution for the estimation of iron in glasses; (II) dealkalization of soda-lime-silica glasses, (1) 9*h*.
Gupta, J. G. S. Determination of microgram amounts of the six platinum-group metals in iron and stony meteorites, (1) 21*d*.
Gupta, K. K. S. See Finch, A.
Gupta, K. P., and Singh, S. Estimation of calcium and magnesium carbonates in limestones, dolomite, and other calcareous materials, (4) 119*f*.
Gupta, K. S. See Guha, S. K.
Gupta, M. P., and Gupta, N. P. X-ray investigation of green mica in khondalite from Auranga Koel Valley, Palamau, Bihar, India, (5) 203*a*.
Gupta, N. K. D. Silica—the wonder mineral, (4) 123*j*.
Gupta, N. P. See Gupta, M. P.
Gupta, P. K., and Kumar, S. Effect of surface dealkalization on the mechanical, chemical, and electrical properties of glass, (10) 337*h*.
Gupta, R. K. Solubility of calcium sulfate dihydrate in hydrochloric acid solutions, (9) 329*a*.
Gupta, S. C. Glass bonded alumina, P (10) 339*a*.
Gupta, S. K., and Porter, R. F. Thermodynamic stabilities of $H_4B_4O_4(g)$ and $H_4B_6O_7(g)$, (4) 161*j*.
Gupta, T. K. Comments on "Sintering kinetics based on geometric models," (6) 231*e*.
Gupta, Y. P., and King, T. B. Self-diffusion of sodium in sodium silicate liquids, (1) 36*j*.
Gurevich, M. A. See Popova, M. A.
Gurganus, T. B. See Manning, C. R., Jr.
Guriuc, V. See Deica, N.
Gurland, J. Some aspects of the fracture of metallic composites, B (1) 41*g*.
Gurnee, E. F. Fundamental principles of semiconductors, (10) 344*d*.
Gurvich, A. M., Gutan, V. B., and Tombak, M. I. Influence of impurity defects on the optical properties of calcium tungstate, (4) 140*c*.
Gusev, B. T. See Tebenikhin, E. F.
Guseva, I. N. Optical investigation of inhomogeneities of crystals grown by various methods, (10) 358*b*.
Gushchina, I. I., and Shadek, E. G. Molten glass as a protective medium in heating blanks before deformation, (2) 50*f*.
Gushchina, S. A. See Krinchik, G. S.
Gust, W. H. See Ahrens, T. J.
Gutan, V. B. See Gurvich, A. M.
Guth, Edwin F., Co. Luminaire reflector, P (1) 11*a*.
Guth, F. E. Luminaire reflector, P (1) 11*a*.
Guthrie, D. G. Coating of the surfaces of light transparent materials associated with light sources, P (4) 98*j*, P (6) 212*i*.
Gutierrez, W. A., and Wilson, H. L. Process for producing thin film rectifying junctions with graded CdSe-ZnSe film, P (4) 116*b*.
Gutorova, L. L. See Evstrop'ev, K. S.
Gutowsky, H. S. See Bos, W. G.; VanderHart, D. L.
Gutsche, W. See Zirngibl, H.
Gutstadt, A. M. Petrology and depositional environments of the Beck Spring dolomite (pre-Cambrian), Kingston Range, California, (6) 229*h*.
Gutt, W., and Osborne, G. J. Calcium silicofluoride of tentative composition $(3CaO{\cdot}SiO_2){\cdot}CaF_2$, (4) 127*h*. Effect of manganese, iron, and fluorine on the properties of tricalcium silicate, (10) 336*a*.
Gutt, W., and Smith, M. A. Studies of the role of calcium sulfate in the manufacture of portland cement clinker, (6) 206*g*.
Gutzeit, C. L., and Brown, H. J. Refractory fibers and method of preparing same, P (4) 107*i*.
Guye, R. See Chauvy, D.
Guyer, E. M. Electric flame generator, P (8) 286*d*. Electric sealing in the space age, (7) 247*g*.
Guyer, R. A., and Krumhansl, J. A. Thermal conductivity, second sound, and phonon hydrodynamic phenomena in nonmetallic crystals, (2) 84*f*.
Guyon, J. C. See Clowers, C. C., Jr.
Guyot, W., and Paulitsch, P. Measurements of quartz maxima on an X-ray rotating table, (6) 226*d*.
Guzenko, G. F. See Ermolaeva, E. V.
Guzewicz, E. A. Rocket nozzle, P (6) 218*e*.
Guzhavina, E. T. See Matveev, M. A.
Gyorgy, E. M. See Remeika, J. P.
Gyro Engineering Corp. Method of determining color using color maps, P (2) 72*a*.

Haacke, G., and Beegle, L. C. Anomalous thermoelectric power of $FeCr_2S_4$ near the Curie temperature, (2) 74*i*.
Haaland, A. See Almenningen, A.; Beagley, B.
Haas, C. Phase transitions in transition-metal chalcogenides, (4) 149*a*.
Haas, H. Process and apparatus for the determination of particle size distribution, P (6) 228*b*. Vaporization of chrome ore at high temperatures, (7) 252*a*.
Haas, L. A., and Khalafalla, S. E. Effect of physical parameters on the reaction of graphite with silica in vacuum, (5) 193*i*.
Haas, W. See Ing, S. W., Jr.
Hasse, L., and Pochert, R. Plasma burner, P (11) 369*b*.
Haase, T. See Hoer, H.
Habashi, Fathi, and Torres-Acuna, N. Anodic dissolution of copper(I) sulfide and the direct recovery of copper and elemental sulfur from white metal, (4) 126*f*.
Habenschuss, M. See Gerstein, B. C.
Haberecht, R. R. Integrated circuits and fabrication thereof, P (11) 377*a*. See Patterson, R. J.
Haberecht, R. R., Bracken, R. C., and McCrary, J. W. Suction box cover, P (7) 253*b*.
Habermann, H. Method of making refractory bodies formed with a multiplicity of closely spaced long and narrow passages therethrough, P (7) 252*g*.
Hach, C. C. Basic turbidity instrumentation, (5) 187*a*.
Hackenberg, P. Grain size determination with the Coulter Counter, (11) 380*d*.
Hackerman, N. See Meyer, D. E.
Hackett, R. J. Metal sampling device, P (10) 342*i*.
Hackley, L. W. Method of forming a temperature compensated reference diode, P (4) 114*h*.
Hacskaylo, M. Thin film ferrites, P (7) 258*b*.
Haddon, J. C., Rogers, E. A., and Williams, D. J. Absorption spectra of first row transition metal ions in phosphate glasses, (4) 94*g*.
Hadfield, D., and Harrison, J. Permanent magnets, P (9) 313*a*.
Hadley, D. J., and Jenkins, R. H. Two stage heat treatment of cobalt molybdate catalysts, P (4) 126*a*.
Haefelin, J. C. Cristal bottle, (10) 337*g*.
Haefling, J. F. See Clark, J. H.
Haefner, W. Method of working [cutting] glass with absorbent by a laser beam, P (10) 339*d*.
Haerter, M. See Rueter, H.
Haertling, G. H. See Land, C. E.
Haffty, J. See Noble, D. C.
Hafner, A., and Neubercer, J. Electron microscopy replicas for the study of porcelain structure, (10) 347*f*.
Hafner, S. S. See Evans, B. J.; Shenoy, G. K.
Hafner, S. S., and Raymond, M. Self-consistent ionic potentials, fields, and field gradients at the lattice sites of corundum (α-Al_2O_3), (9) 329*e*.
Hagedorn, E. C. Sealing glass compositions, method of sealing, and article, P (5) 176*a*.
Hagedorn, F. T. See Stickel, A.
Hagel, W. C. See Rosa, C. J.
Hagelueken, H., and Held, K. Abrasive article, P (10) 335*g*.
Hagemann, L., Konopicky, K., and Kowalczyk, F. Apparent elastic modulus of refractories at high temperatures, (4) 103*a*.
Hagemeyer, H. J., Jr., Blood, A. E., and Statman, M. Ceramic packing material for the prevention of methacrylate and acrylate ester polymerization, P (2) 67*g*.
Hagenmuller, P. See Portier, J.
Hager, H. Packing density of binary mixtures of granular abrasive materials, (1) 1*i*.
Haggerty, J. S. See Leombruno, W. J.
Haggerty, J. S., Cooper, A. R., and Heasley, J. H. Heat capacity of three inorganic glasses and supercooled liquids—correction, (2) 49*i*.
Haggerty, J. S., O'Brien, J. L., and Wenckus, J. F. Growth and characterization of single crystal ZrB_2, (9) 322*b*.
Hahn, E., and Hoch, W. Radiation source for reducing specimen contamination in electron microscopes, P (4) 122*d*.
Hahn, G. T., and Rosenfield, A. R. Systems-type approach to problems of fracture, B (1) 41*g*.
Hahn, H. See Divecha, A. P.
Hahn, H., and Strick, G. Quaternary chalcogenides with sphaleritic structure, (6) 236*f*. Quaternary chalcogenides with spinel structure, (6) 236*g*.
Hahn, H., and Wellmann, B. Ternary chalcogenides (XVIII) ternary chalcogenides of thallium with gallium and indium, (6) 238*j*.
Hahn, T. See Woermann, E.
Hahn, Th. See Behruzi, M.
Hahn, W. C., Jr. See Walker, B. F.
Haider, Z. See Cockram, D. R.
Haigh, H. E. [Sand] milling apparatus and process, P (10) 347*b*.
Hainke, G. Apparatus for production of armored sheet glass, P (11) 370*j*. See Bourggraff, R.
Hair, M. L. Infrared Spectroscopy in Surface Chemistry, B (9) 334*i*. Method for making hollow glass particle having a metallic copper coating, P (5) 175*e*. See Altug, I.
Hair, M. L., and Altug, I. Ion-selective properties of a polished porous glass, (4) 96*j*.
Haire, R. G. See Lloyd, M. H.
Haisty, R. W. See Conrad, R. W.
Haitz, R. H., and Farrington, D. Semiconductor device having controllable noise characteristics, P (1) 19*h*.
Hajela, P. B. See De, P. L.
Hakel, W. J. See Geick, R.
Halasz, D., and Szendy, K. High-grade ionization in cold gas, (5) 189*c*.
Halasz, D., Szendy, K., and Redey, L. Special role of peroxides in gas ionization, (5) 189*e*.
Halberstadt, E. S. Growth of single crystals of silver iodide in silica gel, (7) 266*a*.
Halden, F. A. See Bartlett, R. W.
Hale, D. K. Strengthening of silicate glasses by ion exchange, (4) 97*a*.
Haley, K. M., Molinaro, L. J., and Reed, R. L. Conveying and classifying apparatus, P (7) 259*e*.
Hall, A., and Walsh, J. N. Rapid method for the determination of F in silicate rocks and minerals, (8) 285*b*.
Hall, H. T. See Yund, R. A.
Hall, J. H. Method of providing electrical contacts by sputtering a film of gold on a layer of sputtered molybdenum, P (7) 257*c*.
Hall, J. W., III. See Neugebauer, C. A.
Hall, L. L. See Morgan, C. S.
Hall, P. G., and Kouvarellis, G. K. Dielectric behavior of water adsorbed by partially dehydrated potassium chrome alum, (9) 319*i*.
Hall, R. B. See Aven, M.
Hall, R. D. See Atalla, M. M.
Hall, R. N. Frequency modulated semiconductor junction laser, P (4) 113*j*. Semiconductor strain gage, P (4) 116*h*.
Hall, R. N., and Holonyak, N., Jr. Tunneling semiconductor device exhibiting storage characteristics, P (4) 117*b*.
Hall, R. N., and Tiemann, J. J. Method of making a high frequency transistor structure, P (11) 377*d*.
Hall, R. O. See Hodgson, J.
Hall, W. B. Method of making a vapor device, P (5) 183*j*.
Hall, W. K., and Dollish, F. R. Chemistry of radical ion formation on aluminosilicates, (5) 192*h*.
Haller, W. See Macedo, P. B.
Haller, W., and Macedo, P. B. Origin of phase connectivity in microheterogeneous glasses, (4) 96*d*; correction, (8) 276*j*.
Hallewell, R. T. Method of making a grinding member, P (4) 89*i*.
Halliburton Co. Delayed gelling of sodium silicate and use therefor, P (7) 262*g*.
Hallman, R. W. See Teeg, R. O.
Hallowell, A. L. See Safford, G. J.
Halperin, A., and Chen, R. Thermoluminescence of semiconducting diamonds, (2) 84*i*.
Halpern, A. S. Method for trimming cermet resistors, P (11) 377*i*.
Halpern, B. D., and Semmelman, J. O. Porcelain and resin tooth with silicon bonding agent, P (5) 180*d*. Tooth structure including means for chemically bonding diverse materials together, P (5) 180*d*.
Halpin, J. C. See Tsai, S. W.
Halstead, J. O. See Heron, G. F.
Halversen, R. A. Composition and process for producing an electrically resistant coating on ferrous surfaces, P (5) 171*j*.
Ham, E. J. See Harper, W. J.
Ham, F. S. See Slack, G. A.
Ham, R. K. See Perrow, J. M.
Hamada, Shuichi; Sato, Tadao; and Shirai, Toshiaki. Glass transition temperature and isothermal volume change of selenium, (4) 137*h*.
Hamaguchi, Hiroshi. See Tomura, Kenji.
Hamalainen, M. Cellular prefreezing and premelting phenomena in alkali halides, (7) 264*e*. Constitutional supercooling in the presence of convection cells, (4) 129*f*. Periodic oscillations in films of molten alkali halides, (9) 326*g*. Segregation of impurities in molten salts induced by cellular convection and its effect on crystal growth, (7) 268*j*.
Hamamoto, Fujio. Effect of water on crushed quantity and grain size of raw material during crushing process (III) crushing by impeller breaker, (10) 341*d*.
Hamano, Kenya. Dehydration of magnesium hydroxide and sintering behavior of the compressed body, (1) 26*h*.
Hamano, Kenya; Yoshino, Kazumichi; and Togashi, Hiromitsu. Effects of crystal habits of magnesium hydroxide and additions of iron oxide and silica on the sintering of magnesia, (1) 28*g*.
Hamano, Yoshimitsu. Densification of alumina by hot-pressing, (4) 131*b*.
Hamano, Yoshiteru. See Kinoshita, Makoto; Kose, Saburo.

Hamblin, W. K. Exposure charts for radiography of common rock types, (2) 69*e*.
Hamby, D. C., and Scott, A. B. Thermodynamic properties of molten mixtures of nickel chloride with some alkali halides, (10) 362*j*.
Hamdani, A. J. See Caffyn, J. E.
Hamelin, A. See Paulus, M.
Hamilton, J. F. See Brady, L. E.
Hamilton, J. R. Rotating dead plate mechanism, P (9) 308*c*.
Hamilton, T. N. See Collins, J. H.
Hamling, B. H. Process for producing metal carbide fibers, textiles, and shapes, P (1) 14*f*. Process for producing metal nitride fibers, textiles, and shapes, P (1) 14*g*. Process for producing metal [oxide] fibers, textiles, and shapes, P (2) 59*d*.
Hammel, J. J., Mickey, J., and Golob, H. R. Diffusion coefficients from light scattering in glass, (5) 172*i*.
Hammer, F. W. See Grubb, E. F.
Hammesfahr, J. E., and Stong, C. L. Creative Glass Blowing, B (10) 364*g*.
Hammond, D. L. Quartz crystal temperature transducer, P (5) 185*e*.
Hammond, V. J., and Lowman, R. F. Compositions for high-power heater elements, (2) 61*g*.
Hampikian, A. K., and Biddy, O. D., Jr. Metalized semiconductor device with fired-on glaze consisting of 25–35% PbO, 10–15% B_2O_3, 5–10% Al_2O_3, and the remainder SiO_2, P (11) 377*f*.
Hampson, P. J. See Gilles, P. W.
Hanak, J. J. Deposition of niobium stannide, P (5) 182*b*.
Hanaoka, Masakazu. See Yamaguchi, Tadashi.
Hancock, C. Chattahoochee to market prefab urethane bonded panels, (6) 213*j*.
Hancock, J., and Westerman, A. Postaerated gas jets, P (7) 261*f*.
Hancock, P. See Bruce, D.
Hancox, N. L. Form of the dry-rate curve for cement paste and its use in analyzing the drying behavior, (1) 2*d*.
Handke, H. Poroplast—a material with a great future for molds in the ceramic industry, (4) 108*h*.
Handwerk, J. H. See Moser, J. B.; White, G. D.
Hanes, M. H., and Helmke, G. E. [Epoxy] bonding transducers to delay lines, P (2) 64*e*.
Haneveld, H. B. K. See Bennema, P.
Hanfmann, A. M. Methods of manufacturing thin film components, P (1) 18*f*.
Hang, K. W. See Tennery, V. J.
Hangos, I. Problems of vacuum-tight soldering of metal to ceramic, (5) 181*e*.
Hanks, G. F. See Blumenfeld, J. F.
Hanks, R. See Newns, G. R.
Hanks, R., and Faktor, M. M. Quantitative application of dynamic differential calorimetry (II) heats of formation of the group IIIA arsenides, (4) 151*f*.
Hanna, R. Lattice energy of some cubic oxides, (1) 31*h*.
Hanna, R. T. Blast furnace stock line wall and method of constructing the same, P (4) 106*a*.
Hannam, A. L., and Shaffer, P. T. B. Revised X-ray diffraction line intensities for SiC polytypes, (10) 347*d*.
Hannant, D. J. Equipment for the measurement of creep of concrete under multiaxial compressive stress, (1) 21*j*.
Hanneman, R. E., Jorgensen, P. J., and Speros, D. M. Alumina-ceramic sodium vapor lamp, P (10) 344*a*.
Hanneman, R. E., and Westbrook, J. H. Effects of adsorption on the indentation deformation of nonmetallic solids, (4) 133*b*.
Hanocq, M., and Molle, L. Ultraviolet spectrophotometric determination of fluoride with Ce(III)- or La(III)-Alizarin F Blue in presence of dimethylsulfoxide, (1) 22*g*.
Hans, G., and Leontaritis, L. Degree of development of cold-rolled low-carbon sheet steel for white direct-on enameling, (5) 171*d*.
Hansen, G. R. Vibratory molding apparatus, P (11) 375*d*.
Hansen, H. See Juza, R.
Hansen, J. M., and May, M. Thin film nondestructive memory, P (9) 314*b*.
Hansen, J. P. See Wilkins, C. H. T.
Hansen, K. W., and Taylor, W. C. Dome-shaped electric furnace roof construction, P (9) 309*e*.
Hansen, M. Zinc silicate crystal glazes, (7) 244*f*.
Hansen, N. Discussion of "Physical and mechanical properties of blended and ball-milled aluminum-aluminum oxide alloys," (1) 12*a*.
Hansen, R. W. Miniature single pole-double throw ceramic-metal switch structure, P (2) 66*b*.
Hansen, T. C. Graduate program for engineers in building materials, (9) 333*d*.
Hansen, W. C. Basic chemistry of reactions of aggregates in portland cement concrete, (6) 206*g*.
Hansen, W. W., and Myers, R. E. Luminescent films containing rare earth oxides, P (6) 221*j*.
Hanson, C., and Marthy, S. L. N. The ocean, world's mineral storehouse, (9) 317*a*.
Hanson, J. A. Effects of curing and drying environments on splitting tensile strength of concrete, (1) 2*j*.
Hanson, R. N. Tensile strength testing device, P (11) 381*c*.
Hanssen, W. J. Process for determining the free-oxygen content of a gas or dust mixture, P (4) 122*c*.
Hantusch, G. H. See Davidson, I. A.
Hantzer, P., and Picard, J. Process for rendering glass and polyesters adhesive to rubber, P (11) 372*a*.
Hanusch, K. See Winterhager, H.
Hanykyr, V. See Spicak, K.
Hanykyr, V., Tyrolerova, P., and Dvorakova, I. Chemical preparation of strontium titanate, (7) 264*f*.
Hara, Shigeta. See Adachi, Akira.
Hara, Toshio. See Ohta, Z.
Harada, Jimpei, and Honjo, Goro. X-ray studies of the lattice vibration in tetragonal barium titanate, (5) 203*b*.
Harada, Jimpei; Motegi, Hiroshi; Honjo, Goro; Mitsui, Toshio; and Hoshino, Sadao. Temperature dependence of the low-frequency transverse optic lattice vibration of $BaTiO_3$, (1) 39*e*.
Harada, Jimpei, and Pedersen, T. Debye-Waller factors of tetragonal barium titanate, (8) 290*g*.
Haradome, Miyoshi, and Kawashima, Hirokuni. (Cd,Zn)S photoconductive sintered layer, (4) 109*i*.
Haraldson, H. C. See Anderson, S. B.
Harari, A., and Thery, J. Comparison of MO_2-$nM'O_2$ compounds, (9) 318*c*.
Harbeke, G., and Pinch, H. Magnetoabsorption in single-crystal semiconducting ferromagnetic spinels, (2) 80*h*.
Harbison-Walker Refractories Co. Bottom pour ladle construction, P (5) 178*b*. Metallurgical degasser vessels, P (6) 217*e*.
Harden, D. B. Canosa group of Hellenistic glasses in the British Museum, (4) 90*c*.
Harder, H., and Flehmig, W. Formation of quartz from dilute solutions at low temperature, (6) 232*h*.
Hardie, D., and Petch, N. J. Lowering of surface energy by adsorption on alumina, (1) 31*j*.
Harding, B. C. Diffusion of barium in magnesium oxide, (1) 27*j*.
Hardison, L. C. Semicatalytic infrared heat producing unit, P (2) 72*g*.
Hardman, J. M. See Loukes, D. G.
Hardy, C. J. See Fletcher, J. M.
Hardy, J. E., and Jordan, M. E. Method of producing extremely finely divided oxides, P (2) 74*f*.
Hardy, J. R. See Karo, A. M.
Hardy, L. E. See Stirling, J. F.
Hardy, R. G. See Crosier, C. M.; Huh, J. M.
Hardy, R. G., Huh, J. M., and Bauleke, M. P. Kansas raw materials for the manufacture of reflective glass beads, (2) 50*b*.
Hare, C. R. See Sleight, T. P.
Hare, W. A. Process for making porous lightweight zirconia bodies, P (5) 179*b*.
Hargasser, H. See Meer, W.
Hargis, L. G. Spectrophotometric reaction rate method for determination of bismuth using a dimeric heteropolymolybdate, (8) 285*f*.
Hargrove, C. K. See Kessler, D.
Hariu, Takashi; Seki, T.; Miyashita, Kazuo; and Wada, Masanobu. Electroluminescent properties of ZnSe-type phosphors, (5) 194*c*. Red electroluminescent (Zn,Cd) (S,Se)-type phosphors, (5) 199*a*.
Harker, H. See Robson, D.
Harker, H., Horsley, J. B., and Parkin, A. Effect of neutron bombardment on the reactivity of graphite to oxygen, (11) 384*h*.
Harker, R. I. See Hill, V. G.
Harkort, D., and Kling, H. G. Isostatic pressing of special shapes of high surface quality in a single operation, (4) 108*i*.
Harman, R., Lebeda, S., and Slosiar, J. Forsterite ceramics and their vacuum tightness, (6) 219*f*.
Harman, R. W. See Lamb, I. E.
Harman, T. C. See Butler, J. F.
Harmathy, T. Z. Simultaneous moisture and heat transfer in porous systems with particular reference to drying, (6) 228*d*.
Harmsworth, B. J. See Nelson, R. L.
Harnden, J. D., Jr. Silicon controlled rectifier gating circuits with a high frequency triggering voltage and photocells, P (11) 378*i*.
Harnischfeger Corp. Arc welding electrode, P (4) 93*c*.
Haroon, M. A. See Cable, M.
Haroun, N. A., and Budworth, D. W. Modifications to the Zener formula for limitation of grain size, (8) 295*g*.
Harp, G. D. See Berne, B. J.
Harper, E. A., Hedger, H. J., and Dalton, J. T. High temperature structure of plutonium dicarbide, (9) 322*g*.
Harper, F. C. Effect of calcination temperature on the properties of magnesium oxide for use in magnesium oxychloride cements, (8) 274*a*.
Harper, J. G. Selective gold doping for high resistivity regions in silicon, P (7) 257*j*.
Harper, L. E., Jr. See Dunlevy, B. O.
Harper, W. J., and Ham, E. J. Activation of phosphor films, P (11) 376*e*.
Harrah, J. F. Robots, (7) 259*a*.
Harrick, N. J. Infrared spectra of powders by means of internal reflection spectroscopy, P (6) 227*h*. Internal reflection element for microsample analysis, P (4) 121*j*.
Harrington, H. W. Method [electromagnetic radiation] for use in spectroscopic analysis, P (9) 315*h*. See Bauhaus, R. H.
Harrington, R. E. See Potter, A. E.
Harrington, R. E., Borgwardt, R. H., and Potter A. E. Reactivity of selected limestones and dolomites with sulfur dioxide, (1) 20*h*.
Harris, D. C. See Keys, J. D.; Petruk, W.
Harris, D. L. See Phelps, G. W.
Harris, D. M. Resistance heating elements and methods of conditioning the heating surfaces thereof, P (2) 72*e*.
Harris, L. A. See Kobb, O. C.
Harris, L. B. Dislocation conduction and decoration in potassium bromide, (9) 320*e*.
Harris, M. R. Pore volume uncertainties for microporous solids, (4) 150*e*.
Harris, M. R., and Sing, K. S. W. Use of argon adsorption for the determination of specific surface areas, (2) 71*j*.
Harris, N. H., and Cook, R. L. Solid-state reactions of $SrCO_3$ + TiO_2, (9) 329*j*.
Harris, R. F. See Beumel, O. F., Jr.
Harris, R. S., and Machlan, G. R. Glass composition, P (1) 10*d*.
Harris, W. H., Jr. Abrading wheel structure, P (2) 43*g*.
Harrison, D. E. Lamellar glass-crystal structures in the system ZnO-B_2O_3, (7) 247*f*.
Harrison, F. W., and Lang, G. K. Attempts to prepare $LiF{\cdot}Fe_2O_3$, (8) 288*g*.
Harrison, J. See Hadfield, D.
Harrison, J. D. L. See Cragg, D. G.
Harrison, J. G. See Springthorpe, A. J.
Harrison, J. W., and Davies, L. M. Variation of solid fission product and gas swelling in uranium compounds with thermal neutron dose rate, (8) 300*g*.
Harrison, M. C. See Vancil, D. O.
Harrison, P. F. Automation and modern glassmaking, (5) 172*e*.
Harrison, R. P. See Newey, C. W. A.
Harrison, R. P., and Newey, C. W. A. Particle hardening in manganese-doped sodium chloride single crystals, (2) 81*j*.
Harrison, W. See O'Brien, N. R.
Harrison, W. W., and Wadlin, W. H. Magnesium spinel interferences in air-acetylene vs nitrous oxide-acetylene flames in atomic absorption spectrometry, (8) 285*h*.
Harrop, P. J. Self-diffusion in simple oxides, (7) 268*b*. See Ridge, C. J.
Harrop, P. J., and Campbell, D. S. Selection of thin film capacitor dielectrics, (8) 281*f*.
Harrop, P. J., Wilkins, N. J. M., and Wanklyn, J. N. Radiation damage in zirconia, (8) 297*c*.
Harrop, P. J., Wood, G. C., and Pearson, C. Ac conduction in amorphous films, (8) 280*g*.
Harrop, R. See Blackman, L. C. F.
Harrop Ceramic Service Co. Furnace apparatus with a series of hearths, P (6) 228*f*.
Harsy, M. Synthesis and growth of ZnS, ZnSe, ZnTe, GaS, Ga_2Se_3, and InS crystals in Ga and In melts, (6) 238*g*. See Bertoti, I.
Hart, A. B. See Taylor, D. W.
Hart, E. W. Theory of the tensile test, (1) 22*f*.
Hart, H. G., and Stock, D. F. Preformed refractory block for strip heating furnaces, P (1) 14*c*.
Hart, L. D. See Gitzen, W. H.
Hart, M. See Bonse, U. K.
Hart, P. E., and Searcy, A. W. Vapor pressure, evaporation coefficient, and heat of sublimation of barium fluoride, (4) 163*f*.
Hartford, W. H., and Kelly, W. R. Manufacture of chromium spinels, P (7) 256*i*.
Harth, R. Behavior of porcelain decoration in domestic dishwashers, (1) 15*c*.
Harth, W., and Jaenicke, R. Theoretical explanation of the low-field microwave emission from InSb, (9) 331*a*.
Hartl, K. Volatile suboxides, (4) 163*f*.
Hartman, D. W. See Shaffer, J. W.
Hartman, K. O. See Freeberg, F. E.
Hartman, P. Theoretical morphology of crystals with the SnI_4 structure, (7) 270*h*.
Hartman, R. A. See Ortner, E.; Scott, A. A.
Hartman, T. E., Blair, J. C., and Mead, C. A. Electrical conduction through thin amorphous SiC films, (2) 62*g*.
Hartshorne, N. H. See Briske, C.
Harwood, C. F., and Pilpel, N. Rotational viscometer for powders and granules, (4) 121*e*.
Harzdorf, C. Precipitation of dodecamolybdosilicic acid with organic bases, (4) 120*e*. See Steinhauser, J.
Hasatani, Masanobu. See Sugiyama, Sachio.
Haschke, J. M., and Eick, H. A. Vaporization of ytterbium dicarbide, (5) 203*a*.
Hasegawa, Hiroshi. See Akimoto, Okikazu.
Hasegawa, Masaru. See Kato, Etsuro.
Hasegawa, Masashiko, and Tsuboya, Ichiro. Magnetic and crystallographic properties of η phase in Mn-Ga system, (2) 79*h*.
Haselton, T. P., and Pustell, R. A. Insulated electrical conductor or thermocouple assembly with a membrane gastight seal, P (4) 121*i*.
Hashi, Tsuneo. See Kunitomo, Masakazu; Tsutsumi, Yoshitaka.
Hashimoto, Hachiro. See Toibana, Yasuo.
Hashimoto, Hachiro, and Toibana, Yasuo. Effect of porosity and grain size on the strength of titanium diboride and zirconium diboride, (2) 55*f*.
Hashimoto, Hatsujiro. See Ishii, Makoto.
Hashimoto, Hidehisa. See Tomizawa, Toshiaki.
Hashimoto, Masami. See Sakurai, Toshio.
Hashimoto, Tsunekazu; Yamamoto, Koichi; So-

meya, Akira; and Tsuda, Isunekazu. Fluorescent lamps, P (11) 371*f*.
Hashino, T., and Kawai, T. Transport mechanism of uranium in the iodide process, (8) 300*a*.
Haskins, A. W. Methods of making sources of radioactive energy, P (10) 345*a*.
Hass, G. See Bradford, A. P.
Hassan, M. N. See Helmy, A. K.
Hassanein, M., and Azzam, A. M. Solid reactions in pyrophyllite-nickel (cobalt) oxide systems (II), (9) 329*i*.
Hassel, O. See Dahl, T.
Hasselman, D. P. H. Analysis of the strain at fracture of brittle solids with high densities of microcracks, (10) 349*h*. Crack growth and creep in brittle ceramics, (11) 383*i*. Griffith criterion and thermal shock resistance of single-phase versus multiphase brittle ceramics, (7) 266*e*. Griffith flaws and the effect of porosity on tensile strength of brittle ceramics, (10) 354*h*. Micromechanical thermal stresses and thermal stress resistance of porous brittle ceramics, (6) 235*e*.
Hastie, J. W. See Zmbov, K.
Hastik, W. See Schuetz, E.
Hastrup, N. E. Drum sieves, P (11) 382*j*.
Hasumi, Asataro, and Kogure, Masato. Ceramic dielectric for temperature compensating electric condensors, P (1) 17*j*.
Hatch, R. A. See Owens, K. E.
Hatch, S. E. See Carnall, E., Jr.
Hatch, W. E. Capacitance-adjusted ceramic capacitor, P (10) 344*c*.
Hatcher, H. R., and Holtzman, W. Iron powder for forming sintered articles of improved strength, P (4) 106*c*.
Hatcher, O. W., Jr. Isolated resistor for integrated circuit, P (6) 221*h*. Semiconductive field-controlled diode device, P (10) 346*a*.
Hathaway, C. E., Jr. Heat-resistant silicone resin coating, P (10) 337*e*. See Nielsen, M. L.
Hathwar, G. S. Sizing composition for glass fibers, P (10) 340*a*.
Hatschek, R. See List, H.
Hattori, Makoto. See Tsubaki, Takayuki.
Hattori, Makoto; Minami, Tsutomu; and Tanaka, Masami. Thermal conductivity of arsenic-sulfur binary glasses, (4) 97*e*.
Hattori, Tadamichi, and Nishida, Shingo. Spark ignited gas burner, P (7) 261*h*.
Hatwell, H. See Van Landuyt, J.
Hauffe, K., Pethe, L., Schmidt, R., and Morrison, S. R. Mechanism of formation of thin oxide layers on nickel, (5) 196*j*.
Hausen, D. M., Piper, H. L., and Ruzycki, J. Production of vanadium trioxide, P (4) 125*f*.
Hausmann, A., and Huppertz, H. Paramagnetic resonance of manganese(II)-doped zinc oxide single crystals, (9) 326*a*.
Hausner, H. H. Determination of the melting point of uranium dioxide, (1) 27*e*.
Hausner, H. H., and Bowman, M. G. (editors). Fundamentals of Refractory Compounds, B (4) 166*a*.
Haussuhl, S. See Nath, G.
Hauth, C. R., and Sheatsley, L. L. Checkerbrick and checkerwork construction for regenerators, P (7) 252*f*.
Haveg Industries, Inc. Glass bonded alumina, P (10) 339*a*. Intermediate furnace barrier, P (4) 106*b*. Sodium carbonate treatment of high silica fiber products, P (10) 340*b*.
Havlin, D. Sensitivity of raw brick materials during drying and its reduction, (10) 340*e*.
Hawk, E. A., Sr. Adapter for converting torch to powder spray work, P (7) 246*d*. Powder spray torch with explosion-proof hopper construction, P (4) 94*a*. Powder supply construction for spray torch, P (4) 94*a*. Torch for applying powdered material, P (2) 46*b*.
Hawke, R. S., Keeler, R. N., and Mitchell, A. C. Microwave dielectric constant of Al_2O_3 at 375 kilobars, (9) 311*a*.
Hawkes, J. H. Abrasive cutting device, P (7) 243*h*.
Hawkins, R. J., and Alcock, C. B. Study of cation diffusion in $UO_{2\pm x}$ and ThO_2 using α-ray spectrometry, (8) 298*f*.
Hawley, J. J. See Ryan, C. E.
Hawley, R. S. See Mertzweiller, J. K.
Haworth, C. W. See Friskney, C. A.
Haworth, D. T., and Munroe, J. H. Spectrometric determination of the copper(II) ion by N-8-quinolyl-*p*-toluenesulfonamide, (8) 285*e*.
Hay, W. J., Jr. Packaging device for sheet material, P (4) 100*f*.
Hayakawa, Shigeru. Capacitor comprising ferroelectric ceramic with oxidic silver electrodes and heterojunction barrier layer between electrodes and ceramic, P (4) 112*f*. See Ikushima, Hiroshi; Matsuo, Yoshihiro.
Hayakawa, Shigeru; Ikushima, Hiroshi; Nitta, Tsuneharu; Nagase, Kaneomi; Taki, Hiromitsu; and Lida, Yoshio. Ceramic capacitor comprising semiconductive barium titanate body and silver alloy electrodes containing minor amount of Cu, Ca, or Bi, P (4) 112*g*.
Hayakawa, Shigeru; Ouchi, Hiromu; and Nagase, Kaneomi. Piezoelectric composition and method of preparing the same, P (9) 313*b*.
Hayami, Ryozo, and Ogura, Toru. Kinetics and mechanism of formation of forsterite by solid state reaction of MgO and enstatite, (4) 142*j*.
Hayashi, Hiroaki. See Wakatsuki, Masao.
Hayashi, Hiroshi. See Takagi, Hiroyoshi.
Hayashi, J. See MacEwan, J. R.
Hayashi, Kanekichi, and Naito, Susumu. Burner, P (6) 212*i*.
Hayashi, Kazutami. See Tauji, Shigeru.
Hayashi, Kozi. See Suzuki, Hisashi.
Hayashi, Masakazu. See Tokiwano, Kazuo; Ueno, Tokihiro.
Hayashi, Shigekazu; Kobayashi, Sadao; and Fujiwara, Shinobu. Ceramic dielectric, P (6) 220*j*.
Hayashi, Takeshi. Penetration of eutectic minerals in chrome magnesite and magnesite refractories, (4) 104*i*. Prevention of spalling of sleeves by raising temperature gradually, (2) 57*b*. Results of corrosion test (by crucible method) on various refractory brick for cupola, (7) 251*h*. See Mori, Sadao; Tani, Tetsuro.
Hayashi, Takeshi; Danjo, Hiroyuki; and Doihara, Takeo. Deterioration of chromium oxide-sintered high alumina brick used in roof of electric furnace, (10) 340*f*.
Hayashi, Takeshi, and Ishizawa, Kenki. Behavior of zircon in contact with molten iron, (11) 372*h*. Results of corrosion and erosion test conducted on refractories immersed in molten iron (I); (II) deterioration in sample bricks; (III) comparison of tested sample bricks with pig iron and bricks dropped together into a cupola, (10) 342*d*. Results of study of erosion and mineralogical change of various refractory brick after service in cupola, (7) 251*d*. Studies on corrosion of refractories by molten steel (I), (7) 251*i*.
Hayashi, Takeshi; Ishizawa, Kenki; and Honjo, Kenji. Dissociation of zircon (I) influence of heating temperature and grain size on dissociation of zircon, (7) 250*e*.
Hayashi, Takeshi, and Kyoden, Hiroshi. Pores in firebrick (III) effect of various atmospheres, (11) 373*c*; (IV) influence of vacuum on pore texture of firebrick during heating, (2) 56*i*.
Hayashi, Takeshi, and Onoda, Mitsuaki. Pore texture of pouring pit refractories (II) role of pores in silica brick, (11) 373*b*.
Hayashi, Takeshi; Sakurai, Shigeo; and Doihara, Yoshio. Silica brick impregnated with chromium oxide used in electric furnace cover, (7) 251*f*.
Hayashi, Takeshi; Shibuno, Masao; and Honda, Hiroshi. Pore texture of pouring pit refractories (I) change in pore texture of ladle brick due to reheating, (11) 373*b*.
Hayashi, Takeshi, and Tabata, Katsuhiro. Effect of purity of magnesia clinker on durability of basic brick for open-hearth furnace roof, (11) 373*d*.
Hayasoko, K. See Tada, Takaharu.
Hayden, C. W. Proper methods and materials yield reliable oxide coatings, (6) 207*j*.
Hayes, W. See Stoneham, A. M.
Hayes, W., and Stott, J. P. Electron nuclear double resonance of the F center in CaF_2, (1) 28*i*.
Hayhurst, A. Effect of liquid formation on high-temperature creep, (2) 55*e*.
Hayman, C. See Greene, P. D.; Gross, P.
Haynes, J. W., and Brown, J. J., Jr. Preparation and luminescence of selected Eu^{2+}-activated rare earth-oxygen-sulfur compounds, (10) 359*g*.
Hayward, D. O., and Taylor, N. Sticking probabilities of hydrogen on molybdenum films and filaments, (9) 330*g*.
Hazart, J. P., and Weinryb, E. Electron microanalyzer in the study of glass defects, (2) 48*f*.
Hazdra, J. J., Sonnleitner, D., and Wesolowski, W. E. Increasing the strength of glass by overglazing, P (6) 212*h*.
Hazel, H. K., and Mueller, W. F. Method for wiring ferrite core matrices, P (11) 377*j*.
Hazelden, D. W. J., Norreys, J. J., and Wheeler, M. J. Fuel materials for nuclear reactors, P (4) 106*i*.
Hazell, I. F., and Irving, R. J. Thermal decomposition of iron(II), cobalt(II), and nickel(II) hydroxides, (1) 39*a*.
Hazell, R. G. See Christensen, A. N.
Hazelton, H. J. Abrasive device for finishing paint brushes, P (4) 89*h*.
Hazen, R. B. Spark gaps, P (8) 283*i*.
Head, E. L. Preparation of the carbonates of the rare earths, P (1) 24*d*.
Headrick, A. F. See Nazaruck, S.
Heald, E. F., Reeber, J. R., and Herrington, D. R. Gel preparation of starting materials in iron-containing silicate systems, (10) 354*g*.
Healy, A. M. See Armstrong, W. J.
Healy, G. W. See Sander, L. F.
Healy, T. W. See Somasundaran, P.
Healy, T. W., and Jellett, V. R. Adsorption-coagulation reactions of Zn(II) hydrolyzed species at the zinc oxide-water interface, (1) 24*i*.
Heard, H. C., and Carter, N. L. Experimentally induced "natural" intragranular flow in quartz and quartzite, (6) 232*f*.
Heasley, J. H. See Haggerty, J. S.
Heath, D. F., and Sacher, P. A. Effects of a simulated high-energy space environment on the ultraviolet transmittance of optical materials between 1050 and 3900 Å, (1) 28*i*.
Heath, H. E. Thin film capacitor and method of adjusting the capacitance thereof, P (1) 19*g*.
Heath, H. E., and Skaggs, C. W. Method of making a thin film circuit having a resistor-conductor pattern, P (5) 183*i*.
Heatlock Industrial Furnaces, Ltd. Electrical resistance furnaces, P (7) 261*h*.
Heaton, R. A. See Finger, T. H.
Hebert, N. C. Method of measuring potassium ion and glass electrode therefor, P (11) 381*f*.
Hechelhammer, W. See Streib, H.
Hecht, G., Herberger, J., and Weissmantel, C. Structure and electronic properties of chemically grown CdS films, (8) 281*g*.
Hecht, H. G. Copper in soda-boric oxide glasses, (6) 208*i*. See Taylor, E. D.
Heckel, R. W. See Tanzilli, R. A.
Hecker, R. See Schulten, R.
Heckert, W. See Gunther, I.
Heckingbottom, R. See Dickens, P. G.
Hecklau, F. L., and Allegrini, A. P. Attapulgite clay paper filler and method of forming newsprint therewith, P (6) 229*b*.
Heckmann, H. See Kroeger, C.
Hed, A. Z. Complex defects in CoO, (11) 383*h*. See Kofstad, P.
Hed, A. Z., and Tannhauser, D. S. Contribution to the Mn-O phase diagram at high temperature, (4) 129*i*.
Hedge, C. E. See Noble, D. C.
Hedger, H. J. See Harper, E. A.
Hedler, R. A., and Ryan, W. E. Method for separating phosphors, P (9) 313*e*.
Hedvall, J. A., Vannerberg, N. G., and Blomqvist, P. O. Investigation into the influence of electric charges on the corrosion of metals, (7) 267*h*.
Heffelfinger, R. E. See Adler, R. P. I.
Hegedus, A. J., and Kiss, A. B. Thermogravimetric analysis and simultaneous infrared absorption spectroscopy of gas phases—manganese(II) carbonate thermolysis, (5) 202*f*.
Hegstrom, R. A., and Lipscomb, W. N. Magnetic properties of the BF and BH molecules, (2) 80*c*.
Hehnen, J. See Schulz, E.
Heidrich, W., and Koerner, K. Method and means for producing foamed silicate articles, P (6) 213*d*.
Heier, K. S. See Lambert, I. B.
Heights Laboratory Glass, Inc. Apparatus for forming a helically shaped glass tube, P (5) 174*g*.
Heijligers, H. J. M. See Lieth, R. M. A.
Heijmer, G. B. Plastering or sealing body, P (6) 207*c*.
Heil, O. Ridged dielectric window with titanium suboxide solely on ridges, P (7) 249*e*.
Heiland, G., and Lueth, H. Multiphonon infrared absorption in zinc oxide, (4) 145*e*.
Heiligenstein, A. C. Precis of Decoration of Ceramic Artware — Glass, Porcelain, and Faience, B (8) 302*h*.
Heilmann, G., and Schneider, E. E. Ultramicroscopic study of defects in alkali halides, (8) 300*c*.
Heilmeier, G. H., and Heyman, P. M. Bistable ferroelectric field effect device, P (5) 182*g*.
Heilmeier, G. H., and Zanoni, L. A. Method [heating] for preparing a ferroelectric body and devices, P (9) 312*i*.
Heiman, F. P., and Azininger, K. H. Semiconductor device fabrication, P (4) 116*c*.
Heimann, R. See Franke, W.
Heimann, R., and Franke, W. Kinetics and morphology of the solubility of quartz (II) solubility in solutions with organic liquid mixtures, (9) 324*c*.
Heimann, R., and Willgallis, A. Kinetics and morphology of the solubility of quartz (I) solubility in aqueous solutions of hydrogen fluoride and ammonium hydrogen fluoride, (9) 324*b*.
Heimann, W., and Scherzer, O. Semiconductive device for reducing distortion in electron optics, P (9) 313*h*.
Helmke, G. Directionally solidified permanent magnet alloys with aligned ferromagnetic whiskers, P (6) 221*g*.
Hein, R. A., Sjodahl, L. H., and Szwarc, R. Heat content of uranium dioxide from 1200°-3100°K, (5) 194*h*.
Hein, T. F. See Claessens, F. D.
Hein, W., Schneider, H., and Schumann, H. Nitrogen and oxygen determination in uranium mononitride, (6) 226*i*.
Heinke, R. See Fix, W.; Troemel, G.
Heinrich, E. W. See Quon, S. H.
Hejduk, J., and Novak, J. Aluminum nitride analysis (I) determination of nitrogen and aluminum after decomposition under pressure with hydrochloric acid, (6) 225*f*.
Held, K. See Hagelueken, H.
Held, P. C., and Wilder, D. R. High-temperature hemispherical spectral emittance of uranium oxides at 0.65 and 0.70 μm, (6) 233*a*.
Heling, D. Relationships between initial porosity of tertiary argillaceous sediments and paleosalinity in the Rheintalgraben (SW. Germany), (8) 287*h*.
Heller, H. B., and Abraham, R. C. Semiconductive pressure transducer, P (4) 116*b*.
Heller, L. See Bodenheimer, W.
Heller, L., and Ben-Yair, M. Effect of chloride solutions on portland cement, (2) 44*g*.
Heller, L., and Weiss, A. (editors). Proceedings of the International Clay Conference, Jerusalem, Israel, June 1966 (Vols. I-II), B (4) 167*h*.
Hellmold, P. See Emons, H. H.
Helmberger, H. See Wirth, H.
Helming, B. See Lellep, O. G.
Helmke, G. E. See Hanes, M. H.
Helms, S. B., and Bowman, A. L. Corrosion of steel in lightweight concrete specimens, (4) 91*c*.

Helmy, A. K., Assaad, F. F., Hassan, M. N., and Sadek, H. Apparent and partial molal volumes of Na-kaolin and NaCl in kaolin suspensions, (8) 288*j*.
Helszajn, J. See Hines, M. E.
Heltai, F., Kysela, W., and Nemeth, A. Improvements in production of abrasives with Bakelite binders, (4) 89*f*.
Heltai, F., and Marino, D. Basic principles for the production of high quality abrasives, (1) 1*f*.
Helzel, M. Gas chromatographic analysis of gaseous inclusions in glass, (5) 172*f*.
Hem, J. D. See Roberson, C. E.
Hemmat, N., and Weinstein, M. Closed system vapor growth of bulk CdS crystals from the elemental constituents, (4) 109*j*. Growth of CdS from liquid Cd solution, (4) 137*d*.
Hemphill, J., and Monasebian, A. Machining technique yields precision wafers, (4) 110*e*.
Hench, C. J. Plant and machinery exports, (4) 164*i*.
Hench, L. L. See Freiman, S. W.; Gokularathnam, C. V.
Hench, L. L., and Russell, R., Jr. Effect of Cr_2O_3 vaporization on the sintering of MgO, (4) 132*a*.
Henderson, B. See King, R. D.; Miles, G. D.
Henderson, B., King, R. D., and Stoneham, A. M. Temperature dependence of the *F* band in magnesium oxide, (1) 39*d*.
Henderson, C. M., and Jankowsky, H. B. Graphite containing composition and thermoelectric generator, P (1) 18*f*.
Henderson, C. M. B. See Taylor, D.
Henderson Clay Products, Inc. Apparatus for applying fluid materials, P (5) 176*f*.
Hendriks, A. J. See Jacobs, J. M. H.
Hendrix, W. P. See Davis, D. K.
Henisch, H. K. See Dennis, J.
Henisch, H. K., and Srinivasagopalan, C. Properties of semiconducting lead iodide, (4) 151*i*.
Henkel, C. E. See Smith, R. E.
Henker, H. Epitactic vapor coating apparatus, P (11) 376*e*.
Henkes, H. See Van Stratum, A. J. A.
Henney, J., and Jones, J. W. S. Surface-diffusion studies on UO_2 and MgO, (6) 238*f*.
Hennicke, H. W. High temperature rheology of ceramic materials (I) drawing of flow curves, (2) 78*i*. See Ackermann, C.
Hennicke, H. W., and Kersting, R. High temperature rheology of ceramic materials (III) relaxation behavior of refractories, (4) 104*i*.
Hennicke, H. W., and Neuenfeld, K. Injection molding as a shaping method in ceramics, (6) 224*i*.
Hennicke, H. W., and Schluessler, H. High temperature rheology of ceramic materials (II) temperature dependence of internal friction and of modulus of elasticity of basic refractories, (2) 78*j*.
Hennicke, H. W., and Sturhahn, H. H. Determination of pore size with the mercury [penetration] porosimeter, (7) 259*h*. Fundamental scientific and technical problems relating to isostatic pressing, (4) 108*f*. Measurement and calculation of the thermal shock resistance of hollow tiles, (1) 15*j*.
Hennicke, H. W., and Vaupel, H. Comparison of some microhardness tests with different indenters, (4) 119*e*. Thermal decomposition of some zirconium compounds in the presence of aluminum hydroxides, (6) 239*c*.
Hennig, H. Colored glasses—effects of the oxides of copper and chromium in an Na_2O-CaO-SiO_2 glass and effect on color and spectral transmission, (11) 369*j*.
Hennig, W. See Herr, A. M.
Hennigan, R. Automatic brick setting, (8) 284*c*.
Henning, C. A. O. Condensation coefficients of gold on NaCl single crystals, (4) 129*j*.
Henning, C. A. O., Lombaard, J. C., and Botha, J. C. Unexpected effects of forced high nucleation densities by flash evaporation of gold on NaCl and KCl substrates, (9) 311*i*.
Hennings, K. See Schuetze, H. J.
Hennings, K., and Schuetze, H. J. Contacting arrangement for solid-state components, P (10) 344*e*. Method [epitaxial growth] of fabricating electrical devices, P (11) 377*i*.
Hennings, K., Schuetze, H. J., and Ulbricht, G. Electrical circuit manufacture, P (11) 376*c*.
Henry, D. L. Method for separating expanded perlite with minimum particle breakage, P (9) 308*g*.
Henry, G. R., and Lewis, T. W., II. Monolithic refractory, P (6) 218*e*.
Henry, G. R., and Miller, E. D., Jr. Method of slip casting basic refractory materials, P (4) 107*f*.
Henry, G. R., and Scott, R. K. Method of slip casting basic refractory materials, P (9) 309*a*.
Henry, J. L., Blickensderfer, R., and Thompson, G. G. Quaternary system U-C-O-N at 1700°C—phase relations in the low-nitrogen region, (1) 35*e*.
Hensel, E. Effect of pump capacity on the output of isostatic presses, (4) 108*e*.
Hensel, V. B. See Gundrum, J. H.
Hensiek, H. H. Shrink foils for up-to-date building material transport, (10) 364*a*.
Henslee, W. See McAtee, J. L., Jr.
Hensler, J. R. See Lell, E.
Hensler, J. R., and Letter, E. C. Method for forming ceramic metallic bonds, P (6) 208*d*.
Hensley, A. L., Jr. See Peri, J. B.
Hensley, E. B. See Chen, Y.
Hensley, W. T-band test for prefinished metal, (2) 71*b*.
Heny, S. Base mounted piezoelectric transducer assembly having intermediate stress absorbing member, P (7) 255*f*.
Hepplewhite, R. T., and Kahng, D. Process for introduction of oxygen vacancies in perovskite ferroelectric crystals, P (5) 185*a*.
Hepworth, M. T. See Stewart, A. K.
Herberger, J. See Hecht, G.
Herbert, J. M. Aging with ac, dc, and zero fields of a complex high-permittivity dielectric, (2) 61*c*. See Deeley, G. G.
Herbert, W. C., Minnier, H. B., and Brown, J. J. Luminescence of Dy^{3+}-activated β-Ga_2O_3, (4) 143*e*.
Herbert, W. F. Method for making curved ceramic plates, P (8) 280*c*.
Hercules, Inc. Crystallizable enamels for glass-ceramics, P (6) 212*j*. Satin finish vitrifiable enamels, P (2) 54*a*.
Herczog, A. See Layton, M. M.
Hergenhahn, R. Experience gained with rammed vs bricked ladles, (7) 250*b*.
Herinckx, C., Perret, R., and Rutland, W. Interstitial compounds of potassium with carbon fibers, (9) 323*e*.
Heritage, M. B. See Thomsett, M. F.
Heritage, R. J. See Mullin, J. B.
Herlet, A., and Patalong, H. Semiconductor rectifier diode for power current with a particular doping, P (7) 258*e*.
Herlet, A., and Rosenheinrich, R. Process of attaching electric connections to a semiconductor body, P (4) 115*h*.
Herley, P. J., and Levey, P. W. Effects of X- and γ-ray radiation on the thermal decomposition of solid orthorhombic ammonium perchlorate (I) experimental and results; (II) kinetics and discussion, (8) 291*a*.
Hermsen, A. A. M. See Jacobs, J. M. H.
Herning, G. M. Production of frost-resistant glazed tiles, P (6) 220*c*.
Heron, G. F., Halstead, J. O., and Gettins, R. B. Manufacture of asbestos products, P (9) 317*e*.
Herr, A. M., Hennig, W., and Scholze, H. Formation of spurrite in raw cement mixes, (11) 368*a*.
Herring, F. G., Hwang, J. H., and Lin, W. C. Electron spin resonance of X-ray irradiated polycrystalline and single-crystal sodium hexafluoroantimonate, (4) 135*b*.
Herrington, D. R. See Heald, E. F.
Herrington, R. A. See O'Connell, T. B.
Herrmann, H. See Wirth, H.
Herrnstein, W. H., III, Beck, F. H., and Fontana, M. G. Solubility and permeability of sulfur in alpha iron, (4) 155*f*.
Herron, R. H., and Smothers, W. J. Fine-grained magnesite-chrome refractories, (6) 215*b*.
Hersey, A. T., and Brownmiller, L. T. Steam cured cement and process, P (9) 304*e*.
Hershenov, B. Dielectrically loaded parallel-plane microwave ferrite devices, P (5) 182*d*.
Hershoff, L. See Gilvey, J. P.
Hertl, W. Fibers of submicroscopic beta silicon carbide crystals with sheath of silica, P (2) 58*f*. Manufacture of silicon carbide fibers, P (9) 309*f*. Method for making fibers of titanium carbide and of titanium dioxide, P (7) 252*f*. Oxidation kinetics of polydimensional silicon monoxide, (4) 148*e*.
Hertz, J. See Faivre, R.
Herzenberg, C. L., Riley, D. L., and Lamoreaux, R. Moessbauer absorption in zinnwaldite mica, (9) 325*j*.
Herzhoff, P. H. See Schwiete, H. E.
Herzog, A. H. Injection-luminescent GaAs diodes having a graded *pn* junction, P (4) 113*e*.
Herzog, T. Ceramics and glass in the municipal museum of Landshut, Germany, (5) 169*j*.
Heseketh, M. C. See Steele, B. R.
Heslop, P. G. Properties of borosilicate glass, (2) 50*d*.
Hess, M. S. See Agusta, B.
Hesse, T. Problems with heat-resistant steels especially in the porcelain enamel industry, (10) 337*b*.
Hester, R. E., and Krishnan, K. Vibrational spectra of molten salts (V) infrared and Raman spectra of some molten sulfates, (10) 363*i*. Vibrational spectra of some glasses of alkali metal nitrates with group IIA and IIB metal nitrates and with zinc chloride and water, (5) 174*a*.
Heuer, A. H. Transgranular and intergranular fracture in polycrystalline alumina, (11) 388*c*.
Heuer, A. H., and Roberts, J. P. Influence of annealing on the strength of corundum crystals, (2) 78*g*.
Heuer, A. H., Sellers, D. J., and Rhodes, W. H. Hot-working of aluminum oxide (I) primary recrystallization and texture, (11) 385*f*.
Heumann, F. G. Apparatus for driving filamentary material collectors, P (1) 10*e*. Creel adapter for filamentary material processing apparatus, P (6) 212*j*.
Heumann, F. K. See Brown, D. M.
Heunisch, G. W. Closed tube apparatus for the deposition of silicon oxide, (1) 20*j*.
Hever, K. O. Ion mobility in crystals of a mixed-alkali ferrite: $K_xNa_{1-x}Fe_7O_{11}$, (10) 356*d*. Solid-state electrochemical cell based on ion conductive ceramics, (5) 188*e*.
Hevesi, I. Optical properties of vanadium pentoxide single crystals, (5) 198*a*.
Hewitt, J. M. See Sherrington, L. G.
Hewitt, R. R. See Epstein, G.
Hewitt, T. G. See Beagley, B.
Hewlett-Packard Co. Method [electromagnetic radiation] for use in spectroscopic analysis, P (9) 315*h*. Method for spectroscopically analyzing a sample by detecting radiation field change as a function of the radiation power density in the sample, P (7) 261*b*. Quartz crystal temperature transducer, P (5) 185*e*. Semiconductor bulk oscillators, P (5) 185*g*.
Heyes, A. D. See Bowden, F. P.
Heyman, P. M. Photoconductivity of photochromic Gd:CaF_2, (10) 358*f*. See Heilmeier, G. H.
Heymann, H. See Fix, W.
Heymes, P. R. Method and apparatus for supporting sheets on a gaseous bed, P (9) 307*i*.
Heynes, M. S. R., and Coppen, P. J. Method of making a field-effect transistor by diffusion, coating with an oxide, and placing a metal layer on the oxide, P (9) 312*j*.
Heyraud, J. C., and Capella, L. Oriented thin films of CdS from vapor phase reaction, (5) 181*a*.
Heywang, W. Field effect transistor with a ferroelectric control gate layer, P (5) 183*b*. Mechanical to electrical semiconductor transducer, P (11) 377*e*. Properties of epitaxial silicon layers on spinel single crystals, (5) 199*e*.
Heywood, K. W., and Trampier, C. R., Jr. Method for production of titanium dioxide granules, P (2) 74*g*. Titanium dioxide granules and their use in a molten glass batch, P (6) 213*g*.
Hibino, Taizo; Miura, Eiji; and Sekiya, Hitoshi. Effects of low melting point impurities on the formation of zircon, (9) 320*c*.
Hibino, Taizo; Miura, Eiji; and Takano, Shuji. Effects of CuO on the formation of zircon, (8) 291*j*.
Hibino, Taizo; Yamazaki, Toshiji; and Sekiya, Hitoshi. Effects of NH_4VO_3 and NaF on the formation of zircon, (5) 177*g*.
Hickin, G. K. See Olivier, J. P.
Hickman, B. S. See Jostsons, A.; Walker, D. G.
Hickman, B. S., and Walker, D. G. Growth of ceramic oxides under neutron irradiation, (4) 137*e*.
Hickmott, T. W. Electroluminescence and photoresponse of Ta_2O_5 and TiO_2 diodes, (2) 76*b*. Metal-insulator-metal tunneling device with exponential I-V characteristic only in the negative resistance range, P (8) 282*e*. Photoconductivity, electroluminescence, and hole injection in thin Nb_2O_5 diodes, (8) 281*c*.
Hicks, W. T. See Cox, N. L.
Hidaka, Yasuharu. See Okamoto, Tetsuhiko.
Hider, P. F. See Muir, D. W. B.
Hien, T. D. See Sokolov, V. I.
Hieslmair, H. Field-enhanced thermionic emitter, P (11) 376*g*.
Hietanen, S., and Sillen, L. G. Studies on the hydrolysis of metal ions (LX) hydrolysis of the thorium(IV) ion in 3*M* (Na)Cl medium, (10) 361*j*.
Higginbotham, I. G. See Gallon, T. E.
Higgins, C. W. See Anderson, A. R.
Highberg, C. W. See Teeter, F. C.
Highfield, A. See Buist, D. S.
Higuchi, Hideo. See Tomura, Kenji.
Higuchi, Masaki, and Fujita, Seiichi. Hot gunning applied to electric furnace using BRI gun, (10) 341*i*.
Higuchi, Masaki, and Hiwatari, Yukio. Results of service test on nozzle seating blocks containing $SiZr_4$ and C-SiC-clay, (11) 373*j*.
Higuchi, N. See Fukui, H.
Higuchi, S., and Fujita, Seiichi. Result of hot-gunning in open-hearth furnace and its future problems, (2) 57*b*.
Hijikata, Kenzo, and Shirato, Yoshiaki. Sintering of stannic oxide (I) influence of addition of bismuth oxide, (4) 154*g*.
Hikino, Tadashi. See Mikoda, Masanari.
Hilbiber, D. F. Lateral transistor with improved injection efficiency, P (5) 183*g*. Remote-cutoff field effect transistor, P (2) 66*j*.
Hildebrandt, M. See Vassiliev, A.
Hildebrandt, R. D. Method of forming carbon-bonded silicon carbide bodies, P (8) 279*g*.
Hildenbrand, D. L. Bond energy relationships in polyvalent metal fluorides, B (4) 165*e*.
Hildenbrand, H., and Kitschen, L. Preparation of ceramic raw materials by strong-field magnetic and electrostatic separators, (7) 262*h*.
Hildisch, L. Nonstoichiometry of CdS crystals grown by different methods, (10) 357*g*.
Hilfman, L. Manufacture of spheroidal silica-alumina particles, P (7) 262*j*.
Hilge, H. Device for cleaning the electrodes in an electrostatic dust separator, P (6) 225*a*.
Hilger & Watts, Ltd. Radiometric analysis of powdered sample material, P (8) 286*b*.
Hill, E. R. See Griffin, T. A.
Hill, G. J., and Wanklyn, B. M. Fluxed-melt growth of nickel oxide crystals and their electrical properties, (7) 254*i*.
Hill, J. Method of making semiconductor devices, P (7) 257*h*.
Hill, J. A. See English, J.
Hill, J. L. Load control system [gyratory crusher], P (11) 382*b*.
Hill, J. S. See Gleed, W. L.
Hill, N. A. See O'Neill, J. S.
Hill, N. A., O'Neill, J. S., and Livey, D. T. Properties of BeO containing up to 15% SiC and up to 2% MgO, (4) 151*e*.
Hill, R. A. W., and Slessor, R. P. Differential scanning calorimeter with radiant heating and control, (9) 315*c*.

Hill, R. K. See Tauber, E.
Hill, R. M., and Ichiki, S. K. Infrared absorption by hydrogen bonds in single crystal KH_2PO_4, KD_2PO_4, and KH_2AsO_4, (2) 79*b*.
Hill, T. E., Jr., Kenworthy, H., Ritchey, R. A., and Gerard, J. A. Separation of feldspar, quartz, and mica from granite, (8) 287*j*.
Hill, U. T. Automatic analysis and control of pickling, (8) 274*h*.
Hill, V. G., and Chang, L. L. Y. Hydrothermal investigation of GeO_2, (10) 355*e*.
Hill, V. G., Chang, L. L. Y., and Harker, R. I. Subsolidus stability relations in the system $KTaO_3$-$KNbO_3$, (1) 38*g*.
Hill, V. G., and Harker, R. I. Hydrothermal growth of beryllium oxide single crystals, (4) 139*e*. System $PbNb_2O_6$ and its bearing on the growth of single crystals of the ferroelectric polymorph, (2) 83*j*.
Hill, V. G., and Zimmerman, K. G. Hydrothermal synthesis of single domain lithium niobate crystals by transport reactions, (10) 355*g*.
Hilleard, R. J. See Grimes, N. W.
Hiller, M. A. See Fong, F. K.
Hillert, L. H. Arc welding flux and method of manufacturing the same, P (4) 93*d*, *e*. Method of making coated arc welding electrodes, P (9) 304*i*.
Hillier, B. Turner factory—some new discoveries, (4) 90*i*.
Hillmann, E. Methods for measuring and recording the angle of deflection, the deviation of refractive power, and the amount of striae of machine-drawn plate glass, (9) 306*g*.
Hillner, E. Further observations on the oxidation of zirconium in dry oxygen, (4) 136*i*.
Hills, G. J. See Barton, A. F. M.
Hills, G. J., and Power, P. D. Electrical double layers in fused alkali metal nitrates, (9) 320*j*.
Hilton, A. R. Chemical composition and glass formation in chalcogenide systems, (4) 94*i*. See Jones, C. E., Jr.
Hiltz, R. H. Coating of refractory metals with metal modified oxides, P (4) 93*h*.
Hilzen, H. Heat-dissipating adaptors for single-ended halogen quartz lamps to existing electrical lighting apparatus, P (1) 18*g*.
Himmelberg, G. R., and Papike, J. J. Coexisting amphiboles from blue schist facies metamorphic rocks, (7) 264*h*.
Hincks, E. P. See Kessler, D.
Hinder, J. W. Development of modern German ceramics (I–IV), (7) 244*f*; (VII–VIII), (11) 367*h*.
Hinds, L. S. See Burke, W. E.
Hines, M. E., and Helszajn, J. Ferrite junction circulators having biasing connector wire at ferrite center, P (10) 344*h*.
Hini, P. Galvanomagnetic resistor with semiconductor top layer, P (4) 113*h*.
Hinkley, E. D. See Donnelly, J. P.
Hinssen, A. P. P., and Smeelen, T. J. H. Incandescent lamp having a filament surrounded by a wire screen, P (10) 345*a*.
Hippert, P. R. Dynamical selector device for crushers, P (5) 190*h*.
Hiragushi, Keisuke. See Ohba, Hiroshi.
Hirai, Akira. See Kubo, Takeji; Yasuoka, Hiroshi.
Hirai, Taketsugu. See Takahashi, Katsuaki.
Hirai, Taketsugu; Miura, Yoshinari; Yoshio, Tetsuo; and Takahashi, Katsuaki. Measurements of decomposition voltage of Na_2O-SiO_2 system at elevated temperature by commutator technique, (1) 7*g*.
Hirai, Taketsugu, and Takahashi, Katsuaki. Potential sweep voltammetry of Na_2O-SiO_2 glass melt by stationary platinum electrodes, (1) 8*b*.
Hirai, Toshio, and Yamasaki, Nakamichi. Tentative method for crystallite size determination of beryllium oxide, (8) 285*i*.
Hiraiwa, Osamu. See Suzuki, Kazuo.
Hirakawa, Michio. See Murakami, Keiichi.
Hirakis, E. C. See Friedrich, L. A.; Yenawine, D. L.
Hirano, Hitoshi. See Fukuda, Tsuguo.
Hirano, Kenichi. Diffusion in oxides, (1) 27*a*.
Hirano, Taizo. See Kaifu, Yozo.
Hirao, Eiji. Comparison test of direct bonded magnesite-chromite brick and unfired brick in open-hearth furnace roof, (11) 372*h*.
Hirata, Masako; Hirata, Mitsuji; Saito, H.; and Crawford, J. H., Jr. Annealing of irradiated silicon-containing phosphorus atoms, (1) 25*g*.
Hirata, Mitsuji. See Hirata, Masako.
Hirata, Takayoshi. Synthesis of mullite by sintering process, (2) 58*f*.
Hirayama, C., and Camp, F. E. Fluorescence of Fe, Co, and Ni in reduced germanate glass, (5) 172*e*.
Hirayama, C., Castle, J. G., Jr., and Kuriyama, M. Spectra of iron in alkaline earth phosphate glasses, (2) 51*e*.
Hirose, Yasuo, and Takeda, Seiji. Vibratory compaction method for the fabrication of ceramic nuclear fuel elements, P (4) 108*b*.
Hirota, Elichi. See Nishikawa, Tomozo.
Hirota, Elichi, and Neichi, Yutaka. Manganese-zinc ferrites, P (4) 114*b*.
Hirota, Hozumi. Magnetic properties of borides with a $Cr_{23}C_6$ structure, (1) 17*g*. See Yanase, Akira.
Hirota, Hozumi, and Yanase, Akira. Ferromagnetic material, P (2) 64*f*.
Hirota, Masayoshi. See Fujii, Satoshi.
Hirsch, P. B. See Booker, G. R.
Hirschberg, E. E., and Moore, E. E. Gas burner, P (2) 72*c*. Mounting for replaceable gas burner, P (2) 72*e*. Radiant spiral flame gas burner, P (5) 189*f*.
Hirschler, D. A., Jr. See Reitmeier, R. E.
Hirst, D. M. See Kaye, M. J.
Hirth, J. P. See Clauer, A. H.
Hirthe, W. M. See Blumenthal, R. N.
Hisano, Kumao. Spectral emission due to the lattice vibrations in LiF, (8) 298*e*.
Hisatsune, I. C. See Freeberg, F. E.
Hitachi, Ltd. Cathode ray tube screen structure, P (2) 64*g*. Insulated-gate field effect transistors with piezoelectric substrates, P (11) 377*a*. Method of manufacturing integrated circuits, P (6) 222*c*. Method of producing thin film integrated circuits, P (5) 184*f*. Phosphors, P (11) 378*d*. Production method of semiconductor devices, P (4) 116*c*. Reverse biased semiconductor laser light modulator fabricated from same material as laser light source, P (11) 378*a*. Semiconductor device for high frequency and high power use, P (8) 283*f*. Semiconductor integrated circuit device, P (9) 314*a*. Surface treatment of semiconductor device, P (8) 283*j*. Vibratory compaction method for the fabrication of ceramic nuclear fuel elements, P (4) 108*b*.
Hitachi Zosen Kabushiki Kaisha. Method for fixing a backwave deposited metal onto the beveling root, P (8) 275*f*.
Hitchcock, R. D. Movable substrate method of vaporizing and depositing electrode material layers on the substrate, P (9) 313*h*.
Hitco. Method of decreasing the metallic impurities of fibrous carbon products, P (4) 106*g*. Refractory fibers and method of preparing same, P (4) 107*i*.
Hitt, W. D. Creative personality in science and engineering, (1) 40*f*.
Hittman Associates, Inc. Method for making oriented fiber or whisker composites, P (6) 217*j*.
Hitz, E. See Bruegger, W.
Hitzemann, G., Kulling, A., and Steinbach, H. Process and apparatus for the manufacture of fine particle size titanium dioxide by reacting titanium tetrachloride with oxygen, P (4) 125*g*.
Hivert, A., and Poulignier, J. Mechanical properties at high temperatures of some ultrarefractory carbides, (1) 12*b*.
Hiwatari, Yukio. See Higuchi, Masaki.
Hjorth, L. Large rotating stage for polarizing microscope, (1) 21*d*.
Hlabse, T., and Kleppa, O. J. Thermochemistry of jadeite, (9) 332*d*.
Hladik, W. B., and Bauleke, M. P. Low-density ceramic bodies from clay and expanded volcanic ash from Kansas, (9) 316*f*.
Hlavac, J., and Nademlynska, H. Dissolution of spherical silica particles in molten sodium disilicate, (8) 276*d*.
Hlavac, J., and Sen, Tin Kun. Viscosity of vitreous silica in the transformation range, (8) 300*h*.
Hloch, A., Kohlhaas, R., Medic, N., and Neises, H. Hardener for water glass cements, P (8) 274*c*.
Ho, Er-Chun. Integrated crystal circuits and the method of making thereof, P (4) 113*f*.
Hoad, J. G. Method of making cement, P (8) 274*d*.
Hoad, John G., & Associates, Inc. Method of making cement, P (8) 274*d*.
Hoang, V. C. See Teichner, S. J.
Hoar, E. A. See Ostertag, W.
Hobart Brothers Co. Arc welding with ac power and cored electrode, P (6) 207*j*.
Hobbs, P. V. See Ketcham, W. M.
Hoch, M., Yoon, H. S., and Silberstein, A. Nonstoichiometry in ternary oxides with the fluorite structure, (5) 197*g*.
Hoch, W. See Hahn, E.
Hochberg, F. See Cheroff, G.
Hochino, Masahiro. Differential thermal analysis study of $BaTiO_3$ ceramics containing clay and dolomite, (4) 109*i*.
Hockey, J. A. See Taylor, J. A. G.
Hodder, W. K. See Goosey, M. H.
Hodges, J. A., Marshall, S. A., McMillan, J. A., and Serway, R. A. Superhyperfine interaction due to ^{13}C in the ESR absorption spectrum of Mn^{2+} in single-crystal calcite, (8) 299*c*.
Hodgkinson, H. R. See West, H. W. H.
Hodgson, J., and Hall, R. O. Process and apparatus for milling, P (4) 125*h*.
Hodgson, W. G. See Williams, E. F.
Hodgson, W. G., Brinen, J. S., and Williams, E. F. Electron spin resonance investigation of photochromic sodalites, (4) 135*a*.
Hodkin, E. N., Nicholas, M. G., and Poole, D. M. Dihedral angles of uranium inclusions in hypostoichiometric uranium carbide, (8) 290*h*. Ratio of grain boundary to surface energy for uranium carbide, (6) 236*j*.
Hodson, F. See Curry, D.
Hodson, P. T. A. See Richardson, H. M.
Hoeft, R. See Gerew, J. T.
Hoekje, H. H. See Wilson, W. L.
Hoekstra, A. H. See Wanmaker, W. L.
Hoelscher, H. E. See Roberts, G. L.
Hoenig, C. L. See Stout, N. D.
Hoer, H., and Haase, T. Development of strength of unfired and fired silica brick with temperature, (5) 177*a*.
Hoerster, E. See Gundlach, H.
Hoerster, H., and Pennekamp, J. C. Projection lamp with a wire screen for blackening prevention, P (11) 378*j*.
Hoeschl, P., Konak, C., and Prosser, V. Sublimation studies and preparation of CdO single crystals, (10) 361*d*.
Hoetink, B. J. Process dynamics of a glass furnace following a step change of one of the batch components, (11) 370*c*.
Hofer, D. E. See Coker, E. H.
Hoff, H. See Drossbach, P.
Hoffer, G. I. See Strnat, K. J.
Hoffman, E. See Pietsch, W.
Hoffman, L. C. Capacitor dielectric compositions and capacitors made therefrom, P (7) 255*h*. Copper/vanadium oxide compositions, noble metal metalizing compositions containing vanadium oxide additives, and electrical conductor elements made therewith, P (7) 256*d*. Metalizing compositions containing critical proportions of metal (Pt-Au or Pd-Au) and a specific high density frit, P (7) 256*j*. Surface modified electrostatic enamel powders and method, P (1) 5*g*. See Ballard, K. H.; Bugosh, J.
Hoffman, M. V. Alkaline earth yttrate luminescent materials [rare earth activated], P (9) 314*d*. Eu^{3+} activation in some alkaline earth strontium phosphate compounds, (8) 292*d*. Strontium yttrate luminescent materials [rare earth activated], P (9) 314*d*.
Hoffman, O. M. See Feichter, H. R.
Hoffmann, A. Telescope mirrors of skeleton construction are lightweight and rigid, (7) 248*e*.
Hoffmann, B. J., Olmsted, L. E., and Swartz, W. Preparation of a rutile titanium dioxide-anhydrite composite pigment, P (10) 349*e*.
Hoffmann, F. Heating process in a rotary kiln, P (2) 67*i*.
Hoffmann, H. Electrophoretic deposition of enamel, (9) 304*i*. Use of the electron microprobe to investigate enameling problems, (5) 171*g*. See Immel, W.
Hoffmann, H., and Immel, W. Problems of electrophoretic enamel deposition (II), (10) 337*a*.
Hoffmann, H., and Vitzthum, D. Indirectly heated dispenser cathode for electric discharge tubes, P (10) 345*b*.
Hoffmann, W. Lattice constants and space groups of tridymite at 20°C, (6) 234*j*. See Nager, H. E.
Hofmann, C. F., and Keto, A. I. Cast electrical bushing, P (6) 220*i*.
Hofmann, U., and Boehm, H. P. Graphite as a ceramic material, (11) 382*c*.
Hofmann, U., and Rothe, A. Changes in quartz on dry milling, (5) 192*j*.
Hofmann, U., Schembra, F. W., Schatz, M., Scheurlen, D., and Friedrich, H. Thixotropic volume and volume upon sedimentation of kaolins and clays, (4) 124*b*.
Hofmann, U., Schembra, F. W., Schatz, M., Scheurlen, D., Rothe, A., and Sandmair, K. Cause and influence of the thixotropic and sedimentation volumes of kaolin and clay suspensions and of ceramic bodies, (11) 375*f*.
Hofmann, U., and Scheurlen, D. Increasing the bending strength of humus-containing clays by adding calcium hydroxide, (11) 382*e*.
Hofsted, J. Bent ware, (7) 244*a*.
Hofstein, S. R. Insulated-gate field-effect transistor, P (6) 221*h*.
Hoftmeister, W., and Zuegel, M. Determination of the argon content of sputtered SiO_2 films by X-ray fluorescence, (8) 280*i*.
Hoganson, D. K., Lusk, D. I., and Beer, L. N. Electrocoating acid resistant porcelain enamel panels, (7) 245*j*.
Hogarth, C. A. See Bishop, B. A.
Hogg, W. R. See Coulter, W. H.
Hohlfeld, H. See Schuller, W.
Hohmann, H. H., Muller, W., Schmalzried, H., and Tretjakow, J. D. Disorder in ferrites, (2) 61*i*.
Hokkeling, P. See Berghout, C. W.
Holcomb, R. H. Lead-in conductor for electrical devices, P (5) 175*d*.
Holden, A. N. (editor). High Temperature Nuclear Fuels, B (7) 271*j*.
Holden, R. B. See Fuhrman, N.
Holderreed, F. L. See Crocker, B. S.
Holderreed, F. L., and Sullivan, R. E. Recovery of pure crystals of $AlCl_3$-$6H_2O$ and production of aluminum oxide product therefrom, P (2) 74*f*.
Holdoway, M. J. See Fletcher, J. M.
Holdridge, D. A., and Walker, E. G. DTA curves of some Israeli clays and associated materials, (4) 132*d*.
Holdt, G. See Gramlich, S.
Holland, H. D. See Gammon, J. B.; Kinsman, D. J. J.
Holland, H. J. See Bartholomew, R. F.
Hollander, N. B. See Saxena, S. K.
Holleck, H. Ternary carbides in the system U-M-C, (10) 362*a*.
Holleck, H., Smailos, E., and Thuemmler, F. Mixed crystal formation of UN with the nitrides, (9) 324*i*.
Holleck, H., and Thuemmler, F. Investigation of the formation of metalloid-stabilized zirconium-rich transition metal phases, (4) 141*f*.
Hollenbeck, R. P., and Tyrrell, M. E. Raw materials for lightweight aggregate in Appalachian Region, Alabama and Georgia, (8) 278*h*.
Holleran, L. M. See Frechette, V. D.
Holley, C. E., Jr. See Fitzgibbon, G. C.
Holliday, C. H. See Mullin, J. B.
Holliday, L. (editor). Composite Materials, B (4) 165*f*.
Hollingshead, E. A. See Chin, D. A.
Hollingsworth, A. J. Method and apparatus for

blowing cores using microwave energy, P (6) 217*f*.

Hollingsworth & Vose Co. Method of forming glass-asbestos water-laid sheet, P (7) 252*e*.

Holloway, D. G. See Johnson, J. W.; Linger, K. R.

Holloway, J. C. See Ireland, J. W.

Holloway, W. W., Jr. See Kestigian, M.

Hollox, G. E., and Smallman, R. E. Effect of stoichiometry on the yield stress of TiC and TiO_2, (2) 76*e*.

Holm, H. A. R. Method of firing clay slate and clay and the kiln used, P (6) 228*g*.

Holm, J. L. Heat of fusion of cristobalite, (7) 267*g*. Phase diagram of the system Na_3AlF_6-CaF_2, and the constitution of the melt in the system, (9) 327*a*.

Holm, J. L., and Kleppa, O. J. Enthalpies of mixing in binary liquid alkali fluoride mixtures, (8) 292*b*. Thermochemistry of the liquid system lead(II) oxide-boron oxide at 800°, (4) 161*e*. Thermodynamic properties of the aluminum silicates, (4) 161*i*. Thermodynamics of the disordering process in albite, (6) 239*h*.

Holmes, C. D. See Smith, R. E.

Holmes, D. R. See Footner, P. K.

Holmes, J. T., Koppel, L. B., Gabor, J. D., Ramaswami, D., and Jonke, A. A. Engineering-scale studies of the fluorination of uranium oxide with bromine pentafluoride, (5) 177*h*.

Holmquist, S. Thermodynamic aspects of melting and fining with sulfate, (1) 9*g*.

Holmstrom, R. See Oldham, W. G.

Holonyak, N., Jr. See Hall, R. N.; Keune, D. L.; Rossi, J. A.

Holschlag, J. B. See Day, F.

Holseth, H., and Kjekshus, A. Compounds with the marcasite type crystal structure (I) compositions of the binary pnictides; (II) crystal structures of the binary pnictides, (10) 350*g*.

Holstein & Kappert Maschinenfabrik "Phonix" G.m.b.H. Apparatus for manipulating bottles or the like, P (10) 338*g*.

Holt, D. B., Gavrilovic, J., and Jones, M. P. Scanning-electron-beam anomalous transmission patterns, (8) 297*a*.

Holt, J. B. Oxygen diffusion in CoO as measured by proton activation of ^{18}O, (8) 295*h*. See Condit, R. H.

Holt, J. B., Sockel, H. G., and Schmalzried, H. Mobility of cation vacancies in the solid solution KCl-RbCl, (9) 325*i*.

Holt, S. See Banks, E.

Holtzberg, F., and Methfessel, S. J. Ferromagnetic compounds and method of preparation, P (5) 183*a*. Superconductor materials and devices, P (1) 19*c*.

Holtzman, A. H. See Cowan, G. R.

Holtzman, W. See Hatcher, H. R.

Holzer, W. See Rolfe, J.

Holzrichter, J. F., and Emmett, J. L. Transient color centers in fused quartz, (9) 307*h*.

Hon, Ping-Kay. Some simple techniques to prepare powder samples for spark source mass spectrometric analysis, (10) 347*f*.

Honchar, A. P. Process for producing a titanium sulfate solution and a TiO_2 concentrate from a titaniferous ore, P (4) 125*b*.

Honda, Hiroshi. See Hayashi, Takeshi.

Honda, Takashi. See Nii, Riro.

Honeycutt, M. Light projection device and light source support means therefor, P (7) 249*a*.

Honeywell, Inc. Apparatus [glass electrode] for measuring pH with temperature compensating diode means, P (2) 71*i*. Photodetector, P (10) 345*e*. Semiconductor device with a lateral retrograded *pn* junction, P (6) 223*g*. Semiconductor method and apparatus, P (11) 378*g*. Solid state junction device for ultraviolet detection, P (4) 117*b*.

Hongo, Yasuo. See Jimbo, Yoshiro.

Honig, R. E. See Kramer, D. A.

Honig, W. M., and Wrobel, E. J. Ferrimagnetic couplers employing a transition from air dielectric waveguide to solid dielectric waveguide, P (4) 113*b*.

Honjo, Goro. See Harada, Jimpei.

Honjo, Kenji. See Hayashi, Takeshi.

Honma, Kunio. Ceramic dielectrics, P (4) 112*g*.

Hoock, W. S. Fuel block heater, P (4) 102*f*.

Hood, R. T., and Dietrick, M. I. Portland cement compositions, P (4) 93*c*.

Hoodless, I. M., and McNicol, B. D. Effects of alkaline earth impurities on ionic transport in cesium iodide, (4) 133*e*.

Hooker Chemical Corp. Composition and process for producing an electrically resistant coating on ferrous surfaces, P (5) 171*j*. Method of treating metal surfaces, P (5) 172*a*.

Hoover, W. G. Entropy for small classical crystals, (8) 292*b*.

Hope, B. See Thorne, R. P.

Hopfield, J. J. See Cuthbert, J. D.

Hopfinger, E. J., and Altman, M. Experimental verification of the dusty-gas theory for thermal transpiration through porous media, (11) 384*j*.

Hopkins, J. Technical merit wins judges' nod every time, (9) 303*h*.

Hopkins, R. H. See Mazelsky, R.

Hopkins, S. W. J. See MacLeod, A. C.

Hoppe, H., and Scherzberg, H. Method for making alkali metal sulfate, P (5) 191*b*.

Hoppe, H. J. See Berens, L. W.

Horacek, S. See Litomisky, J.

Horacsek, O., and Millner, T. Simple apparatus for investigating by electron optics the high-temperature metallographic phenomena of metals with high melting point, (6) 227*j*.

Horai, J. C. See Beyard, R. M.

Horak, F. A. See Cornelison, B.

Horak, W., and Rowland, G. R. Glass contact [zircon] refractory and method of making the same, P (7) 252*j*.

Hordis, V. A. Apparatus for heating and tempering glass sheets, P (1) 10*h*.

Hordis Bros., Inc. Apparatus for heating and tempering glass sheets, P (1) 10*h*.

Horeni, J. Coefficients expressing the influence of grain shape and surface texture in a computation of the specific surface, (1) 26*f*.

Horiba, Yasutaka. See Arizumi, Tetsuya.

Horibe, Toshiyasu, and Watanabe, Shiro. Wear of ruby single crystals along a plane close to the basal plane, (6) 239*e*.

Horibe, Toshiyasu; Watanabe, Shiro; and Katto, Shigeru. Wear of ruby single crystals along a plane slightly inclined to the basal plane, (4) 164*a*.

Horigome, Shinkichi. See Kitagawa, Hiroshi.

Horii, Shigeo. See Osaka, Matajiro.

Horikawa, Tsuyoshi. See Nameishi, Naoyuki.

Horn, F. H. Method of analyzing materials to determine the impurity content thereof, P (6) 227*j*.

Hornak, T. Apparatus for automatically measuring the reverse recovery transient of a semiconductor diode, P (11) 376*f*.

Hornbaker, A. L. See Bauleke, M. P.

Hornberger, L. B. See Kelly, W. T.

Hornbogen, E. See Gleiter, H.

Hornung, A. Improvement in the quality and economy of grinding, (5) 186*c*.

Horowitz, E. T. H. Patents on electrical glass-melting and furnaces, (9) 306*d*.

Horsley, G. W. Manufacture of nuclear fuel, P (10) 342*g*.

Horsley, J. B. See Harker, H.

Horton, N. H. Attapulgite product and method of preparing same, P (1) 23*g*.

Horton, R. A. See Watts, C. H.

Horton, R. E. See Cameron, E. M.

Horton, R. M. Oxidation kinetics of powdered silicon nitride, (6) 235*d*.

Horwood, J. L. See Keys, J. D.

Hosaka, Takao. See Suzuki, Hiroshige.

Hosek, J., and Sereda, P. J. Effect of organic surface agents on properties of hydrated cement compacts, (1) 2*i*.

Hoselitz, K. Crystals we need, (7) 254*g*.

Hoshina, Teruhiko. Electron spin resonance of photosensitive Fe^{3+} centers in CdSe, (1) 29*e*.

Hoshino, Masahiro. See Ikeda, Yutaka.

Hoshino, Masahiro; Kuroki, Hayashi; and Tokumoto, Yukitaka. Life characteristics of glass capacitor, (4) 96*a*.

Hoshino, Sadao. See Harada, Jimpei.

Hoskins, R. H., and Soffer, B. H. Solid state laser device using gadolinium oxide as the host material, P (5) 185*b*.

Hoskins Mfg. Co. Nickel alloy thermocouple, P (10) 348*a*.

Hosler, W. R. See Ambler, E.

Hosokawa, Shumei. See Miyatake, Kazumi.

Hoss, P. A. See Rivera, J.

Hoste, J. See Massart, D. L.; Op de Beeck, J.

Hou, S. L., Beck, K., and Marley, J. A., Jr. Type conversion and *pn* junction formation in ion-implanted ZnTe, (9) 311*h*.

Houck, J. C., and Ripple, J. W. Grinding conditions and resin-bond diamond wheels, (4) 89*j*.

Hough, A., and Marples, J. A. C. Pseudobinary phase diagrams of PuO_2 with alumina, beryllia, and magnesia and the pseudoternary PuO_2-ThO_2-BeO, (1) 35*d*.

Hough, J. M. See Geary, D. A.

Hough, R. L. Apparatus for the continuous formation of filaments, P (1) 13*f*. Fiber-containing pyrolytic composite material, P (11) 374*i*. Metal surfaced with boron and coating of silicon, silicon carbide, or titanium nitride, P (7) 246*f*. Method and apparatus for the manufacture of pyrolytic fibers, P (4) 106*f*. Method for the pyrolytic deposition of silicon carbide, P (4) 107*e*. Process for metal finishing boron and tungsten filaments, P (4) 118*h*. Wire coated with boron nitride and boron, P (9) 304*i*.

Hough, R. L., and Schwartz, R. T. Method and apparatus for manufacture of high strength and high modulus carbon filaments, P (1) 14*g*. Method of making metal or metalloid carbide yarn by decomposing the respective chloride in the presence of carbon yarn, P (6) 217*i*.

Hough, W. D. See Fogelberg, C. V.

Hough, W. H. Electric incandescent lamp with shock and vibration resistant filament support structure, P (7) 248*e*.

House, R. E. Protective packaging—a key to lower costs, (6) 225*a*.

Houseman, J. E., Perkins, R. A., and Koenig, C. J. Combating black coring in ceramic bodies with chemically combined water, (1) 11*g*.

Housh, L. M. Process for the recovery of magnesium values from dolomite, P (2) 74*d*.

Houston, H. H., Keitel, G. A., and Williamson, W. R. Materials having high corrosive resistance to attack by fluorine at cryogenic temperatures and method of preparing them, P (6) 217*d*.

Hovis, W. A., Jr. Infrared spectral reflectance of some common minerals, (1) 31*c*.

Howard, C. J., and Port, E. B. Method for preparing superdense sodium carbonate from Wyoming trona and the product thereof, P (5) 191*c*.

Howard, J. C. Refractory crucibles, P (7) 253*c*.

Howard, R. A., Kellar, A. A., and Meers, J. T. Method of manufacturing fuel elements [for nuclear reactors], P (7) 252*g*.

Howard, V. C. See Thorne, R. P.

Howard, W. E., Jr. See Esaki, L.

Howden, D. See Weinberg, F. J.

Howell, H. G. See Fowler, A.

Howell, R. G. See Grego, P.

Howie, R. A. See Bancroft, G. M.

Howmet Corp. Method for manufacture of refractory shell molds, P (6) 217*j*. Method for molding of glass and ceramic materials, P (5) 175*f*. Refractory mold composition and method, P (6) 218*e*.

Hoyle, W. C. See Schilt, A. A.

Hoyt, P. L. See Conrad, R. W.

Hr, E., and Avramov, A. Temperature and melting range of converter slags rich in manganese, (1) 13*j*.

Hrishikesan, K. G. Removal of fluorine from alumina by steam, P (8) 288*c*.

Hruby, A. See Rodot, H.

Hsieh, E. J. See Shimoda, R. Y.

Hu, S. M. Properties of amorphous silicon nitride films, (1) 35*i*.

Hu, S. M., and Gregor, L. V. Silicon nitride films by reactive sputtering, (4) 111*j*.

Huang, E. Y. Improved particle index test for the evaluation of geometric characteristics of aggregates, (5) 187*i*.

Huang, J. W., and Moos, H. W. Spectra of optically pumped $SrF_2:Sm^{2+}$ and $SrCl_2:Sm^{2+}$, (8) 298*d*.

Huang, N. L. See Simanek, E.

Huang, Yun-Yang, Benson, J. E., and Boudart, M. Krypton as a probe of electrostatic fields in Y zeolites, (10) 348*f*.

Hubbard, W. N. See O'Hare, P. A. G.

Hubbell, D. S. Porcelain enamel on aluminum, (8) 275*b*.

Hubble, D. H. Some properties of lime refractories, (8) 279*h*.

Hubble, D. H., and Powers, W. H. Refractory composition and method of making refractory shapes, P (4) 107*g*.

Huber, D. L. Spin-magnon relaxation in terbium-doped YIG, (4) 155*g*.

Huber, E. J., Jr. See Storms, E. K.

Huber, H., and Moncorge, G. Gas-filled discharge tube and electrical energy generators using the same, P (11) 376*h*.

Huber, J. M., Corp. Chemically treated clays, P (4) 124*i*, P (8) 287*f*. Process of producing highly porous and reactive silica materials, P (7) 263*b*.

Huber, M. See Grenot, M.

Huber-Panu, I., and Dumitrescu, M. Validity of equations for the kinetics of flotation, (4) 163*c*.

Hubner, K. Semiconducting resistance and a method for its manufacture, P (10) 346*a*.

Huc, J. Ceramic capacitor, P (4) 112*f*.

Huchenholz, H. G. Synthesis and stability of Ti-andradite, (9) 331*j*.

Hucke, K. Two variants of a glass trademark from the 17th century A.D., (6) 206*e*.

Hucks, R. T., Jr. Pipe coupling, P (4) 93*b*.

Hudson, A., and Whitfield, H. J. Moessbauer effect studies on calcium ferrites (I) temperatures above the Néel point, (4) 145*d*.

Hudson, R. B., and Mesmer, R. E. Production of sodium tripolyphosphate, P (6) 230*c*.

Huebner, K. See Chauvy, D.

Huebner, R. J. Glass forming container neck ring, P (5) 174*f*.

Huebscher, M. See Petzold, A.

Huehndorf-Richter, B., Von Der Decken, C. B., and Rausch, W. Sorting apparatus for spherical bodies, P (7) 253*a*.

Huet, H. See Delange, M.

Hueter, L., Losenske, C., and Schirmer, D. Process for treating silicic acids and silicates, P (5) 191*a*.

Huettner, D. J. See Caron, A. P.

Huettner, D. J., Ragle, J. L., Sherk, L., Stengle, T. R., and Yeh, H. J. C. Ion motion in tetrafluoroborate salts (II) (4) 141*c*.

Huff, E. G. See Glasson, D. R.

Huffcut, H. W. Porcelain enamel for heat transfer surface, (1) 4*j*.

Huffman, C. O. See Curtze, E. W.

Huffman, D. R. Total intensities of some crystal field transitions in MnO and MnS related to the antiferromagnetism, (9) 332*b*.

Huffman, D. R., and Wild, R. L. Specific heat of MnS through the Néel temperature, (2) 83*f*.

Huffman, D. R., Wild, R. L., and Shinmei, M. Optical absorption spectra of crystal-field transitions in MnO, (11) 386*a*.

Hughes, A. E. Symmetry properties of defects studied by uniaxial stress spectroscopy, (8) 299*f*.

Hughes, A. E., and Runciman, W. A. Stress and Zeeman spectra in bismuth-doped and undoped calcium oxide, (7) 269*a*.

Hughes, E. W. Report on the status of electrodeposition for porcelain enamels, (7) 246*h*.

Hughes, J. V., Jr., and Squier, C. A. Method of installing high temperature furnace insulation, P (6) 217*h*.

Hughes, M. A. See Buttress, G. D.

Hughes, R. C. See Bronnes, R. L.

Hughes, R. L. See Best, W. V.

Hughes, R. O., Orser, L. D., and Etten, N. L.

Means for and method of applying mosaic to curvate surfaces, P (4) 109*e*.
Hughes, T. See Lautenschlager, E. P.
Hughes, W. E. Wide bandwidth millimeter maser, P (7) 258*d*.
Hughes Aircraft Co. Automatic classifying device [semiconductors], P (9) 312*b*. Bistable two or three terminal double injection switching element, P (10) 344*c*. Electrolytic plating of metal bump contacts to semiconductor devices on nonconductive substrates, P (2) 64*d*. Electron gun having electrode cup in ceramic cavity, P (10) 344*g*. Field effect transistor having interdigitated source and drain and overlying insulated gate, P (4) 113*c*. Gate cooling structure for field-effect transistors, P (10) 344*j*. Integrated crystal circuits and method of making, P (4) 113*f*. Laser systems employing a solid laser material, P (9) 312*d*. Method of treating semiconductor devices or components, P (6) 222*i*. *Pin* diode with a nonuniform intrinsic region width, P (11) 378*e*. Potassium tantalate niobate crystal growth from a melt, P (6) 223*f*. Space-charge-limited current triode device, P (2) 66*h*. Surface-protected semiconductor devices and methods of manufacturing, P (7) 258*a*. Thin film nondestructive memory, P (9) 314*b*.
Huh, J. M. See Bauleke, M. P.; Hardy, R. G.
Huh, J. M., Hardy, R. G., Plummer, N., and Bauleke, M. P. Testing of Kansas clays and shales for nonceramic utilization, (2) 71*c*.
Hukki, R. T. Method and apparatus for sizing of discrete particles in a fluid medium, P (10) 346*j*.
Hukuda, Kenzi. See Koga, Hiroshi.
Hulbert, S. F., and Lane, G. Use of atomic absorption spectroscopy to study the kinetics of the reaction between MgO and SiO_2, (2) 71*a*.
Hull, E. M. See Light, T. B.
Hull, G. F., Smith, J. T., and Quesada, A. F. Alignment of Cr^{3+} in ruby, (1) 25*e*.
Hull, G. W., Jr., and Hulliger, F. Copper selenide ($CuSe_2$), a marcasite-type superconductor, (9) 318*j*.
Hullhorst, W. B. Method and apparatus for packaging materials, P (1) 11*e*. See Ullman, W. L.
Hulliger, F. Crystal chemistry of chalcogenides and pnictides of the transition elements, B (6) 242*g*. Rare earth metal compounds and their process of preparation, P (1) 19*f*. See Boelsterli, H. U.; Hull, G. W., Jr.
Hummel, F. A. See Kreidler, E. R.; McCauley, R. A.; Nath, D. K.; Tressler, R. E.
Hummel, F. A., Sarver, J. F., and Kreidler, E. R. Luminescent materials of zinc magnesium germanate activated with manganese, P (11) 377*c*.
Humphrey, F. B. See Patton, C. E.
Humphrey, R. A. See Eakins, W. J.
Humphreys, E. Method and apparatus for forming glass channels, P (5) 175*h*.
Humrick, R. J. See Griffin, T. A.
Hums, D., Leers, K. J., and Niesel, K. Wear of magnesia-chrome brick in the sintering zone of rotary cement kilns, (1) 13*d*.
Hundley, G. K. Nonglare sealed beam headlights, P (6) 213*g*.
Hunkel, L. Hopper with vibratory means for uniform rate of material delivery, P (7) 259*a*.
Hunt, C. R., Jr., and Raman, A. NbZn—a μ-phase, (6) 235*f*.
Hunt, G. J. J. Linking brick factories with building sites, (9) 308*g*.
Hunt, P. D. See Tetenbaum, M.
Hunter, E. A. See Segura, M. A.
Hunter, F. W., with McKearin, H. Stiegel Glass, B (1) 42*g*.
Hunter, I. C. See Bessent, R. G.
Hunter, J. L. Method for dispersing clay, P (4) 124*h*.
Hunter, J. W. See Rabatin, J. G.
Hunter, O., Jr. See Manning, W. R.
Hunton, A. E. See Piggott, M. R.
Hupperiz, H. See Hausmann, A.
Hurd, D. J. See Ernst, E. O.
Hurd, M. K. Ferrocement boats, (7) 244*h*.
Hurditch, R. J. See Dickens, P. G.
Hurlbut, G. K., and Gagne, A. F. Edge-grinding machine for lenses, P (11) 371*e*.
Hurle, D. T. J. See Mullin, J. B.
Hurley, F. R. See Angstadt, R. L.; Kraus, J. W.
Hurley, F. R., and Angstadt, R. L. Early hydration of tricalcium silicate and β-dicalcium silicate in neat portland cement pastes, (2) 44*f*.
Hursey, K. H. See Gleed, W. L.
Hurst, J. Vibratory mounting for sieves and like apparatus, P (8) 288*e*.
Hurwitz, C. E. See Dimmock, J. O.
Huschka, H. See Gorgenyi, T.
Husome, R. G. Empty bottle bottom and neck inspection machine using radiation sensitive means, P (4) 98*d*. Empty bottle inspection machine, P (6) 212*a*.
Hussman, W. Interpretation of wetting phenomena by electron theory, (7) 267*h*.
Hutaff, J. B. Bottle sorting apparatus, P (2) 52*c*.
Hutchinson, A. Photoconductive device, P (5) 184*e*.
Hutchinson, C. O. Electrocoating—summary of present status of electrodeposition of organic coatings from aqueous media onto conductive substrates, (1) 4*h*.
Hutchinson, G. E. See Cowgill, U. M.
Hutchison, C. R., and Williamson, W. O. Effects of varying water contents and pressures in the semidry compaction of Lower Kittanning clay, (5) 176*g*.
Hutkin, I. J. Filamentary thermal cell with ionically conductive glass coating, P (4) 94*a*.
Hutson, J. L. Photosensitive devices having large area light absorbing junctions, P (4) 115*e*.
Hwalek, D. C. See Snitzer, E.
Hwang, C. J. Photoluminescence study of thermal conversion in GaAs grown from silica boats, (7) 255*h*.
Hwang, J. H. See Herring, F. G.
Hyde, J. R. Process for preparing microspheroidal silica, P (10) 349*c*.
Hyman, H. See Fisher, A. W.
Hyman, S. Making the most of a good impression, (8) 273*i*.
Hyprez Electrometallics Corp. [Contoured] abrasive cutting tools, P (7) 243*i*.
Hyzer, W. G., and Bangasser, R. L. Annealing glass-to-metal seals (I-II), (1) 5*i*.

Ianache, P. See Avram, C.
Iannicelli, J. See Balentine, J. W.
Iannicelli, J., Whitley, J. B., and Balentine, J. W. Chemically treated clays, P (4) 124*i*.
IBM Corp. Apparatus for coating a thin uniform thickness stripe on a substrate, P (11) 376*f*. Bulk negative conductivity semiconductor oscillator, P (11) 376*h*. Connections for microminiature functional components, P (10) 344*d*. Diffused-epitaxial scanistors, P (7) 256*e*. Electric field tailoring of thin film resistors, P (4) 112*c*. Electrical shock wave devices and control thereof, P (6) 221*h*. Electrical temperature sensor device, P (2) 64*c*. Electrodeposition of magnetic thin films, P (2) 64*c*. Epitaxial deposition of gallium arsenide from an atmosphere of hydrogen and $Ga_2H_3 + AsCl_3 + AsH_3$ vapors, P (2) 64*e*. Epitaxial semiconductor layer as a diffusion mask, P (2) 64*e*. External standard method of X-ray diffraction analysis for determining the percentage of compounds in cement clinker, P (6) 207*c*. Ferriresonant memory system, P (11) 376*f*. Ferromagnetic compounds and method of preparation, P (5) 183*a*. Four terminal electrooptical logic device, P (4) 113*f*. High capacity epitaxial apparatus and method, P (5) 183*d*. Holder for highly reactive cathodes of rare-earth borides such as lanthanum hexaboride, the holder provided with a cooling means opposite the emissive end of the cathode to reduce tendency of holder deterioration, P (11) 376*j*. Indium oxide resistor composition, method, and article, P (4) 113*c*. Insulated-gate field-effect transistor exhibiting a maximum source-drain conductance at a critical gate bias voltage, P (2) 65*d*. Insulated-gate field-effect transistor with nonplanar gate electrode structure for optimizing transconductance, P (9) 312*c*. Integrated semiconductor devices and fabrication methods, P (4) 113*f*. Low power density sputtering on semiconductors, P (6) 221*j*. Low resistivity semiconductor underpass connector and fabrication method, P (8) 282*c*. Memory element having two orthogonally disposed magnetic films, P (11) 377*e*. Metal-degenerate semiconductor-insulator-metal sandwich exhibiting voltage controlled negative resistance characteristics, P (8) 282*d*. Method for adjusting contacts in reed switches, P (6) 212*j*. Method and apparatus for reverse sputtering selected electrically exposed areas of a cathodically biased workpiece, P (4) 114*g*. Method of continuously curing resistor elements, P (11) 377*h*. Method for controlling the electrical characteristics of a semiconductor surface and product produced thereby, P (1) 18*b*. Method for depositing silicon nitride insulating films and electric devices incorporating such films, P (4) 114*b*. Method of electrolytically etching a semiconductor having a single impurity gradient, P (4) 114*c*. Method of etching SiC, P (5) 183*d*. Method for fabricating insulated-gate field-effect transistors, P (4) 114*c*. Method for fabricating insulated-gate field-effect transistors having controlled operating characteristics, P (8) 282*g*. Method of fabricating uniform rare earth iron garnet thin films by sputtering, P (7) 257*c*. Method of forming a glass-filled gap, P (11) 377*a*. Method of forming solder mounds on substrates, P (11) 377*a*. Method of growing doped semiconductor material from a source which includes an unstable isotope which decays to a dopant element, P (9) 312*h*. Method of joining a component to a substrate, P (6) 222*c*. Method of making crystal shapes having optically related surfaces, P (11) 377*c*. Method of making fine line patterns using a ferromagnetic element, P (9) 313*a*. Method of making semiconductors by laser induced diffusion, P (5) 183*h*. Method of manufacturing recording heads, P (4) 115*g*. Method for plating and polishing a silicon planar surface, P (7) 257*a*. Method of rendering noble metal conductive composition nonwettable by solder, P (1) 18*d*. Method of selectively removing powdered glass, P (4) 115*i*. Method for [vapor] depositing glass particles on the entire exposed surface of an object, P (7) 257*c*. Method [vapor deposition] for producing thin films of rare earth chalcogenides, P (9) 313*e*. Method for wiring ferrite core matrices, P (11) 377*j*. Mica membrane mounting structure for cathode-ray storage tube, P (8) 283*f*. Monolithic silicon device containing dielectrically isolating film of silicon carbide, P (1) 18*f*. Multilevel terminal metallurgy for semiconductor devices, P (11) 377*j*. Multistable device operating on the principle of stimulated emission of radiation, P (5) 184*b*. Objects provided with protective coverings, P (4) 115*c*. Palladium ohmic contact to silicon semiconductor, P (6) 223*c*. Process of bonding chips in a substrate recess by epitaxial growth of the bonding material, P (6) 223*g*. Process control of indium sheet film memories, P (1) 19*c*. Process for etching silicon monoxide and etchant solutions therefor, P (6) 223*h*. Process of making gallium phosphide dendritic crystals with grown-in *pn* light emitting junctions, P (5) 185*c*. Process for preforming crystalline bodies, P (11) 378*j*. Schottky-barrier diode formed by sputter-deposition processes, P (9) 313*f*. Selective deposition method and article for use therein, P (2) 66*a*. Semiconductor bulk effect microwave oscillator, P (6) 223*e*. Semiconductor device [structure], P (9) 313*j*. Semiconductor devices with cup-shaped regions, P (11) 378*d*. Semiconductor negative resistance electroluminescent diode, P (7) 258*e*. Single diffused surface transistor and method of making, P (8) 283*g*. Solid state epitaxial growth of silicon by migration from a silicon-aluminum alloy deposit, P (4) 117*b*. Solid state transformer, P (8) 283*h*. Sputter deposition of nickel-iron-manganese ferromagnetic films, P (1) 19*a*. Sputtering processes for depositing thin films of controlled thickness, P (1) 19*b*. Superconductor materials and devices, P (1) 19*c*. Technique for obtaining isolated integrated circuits, P (5) 185*e*. Thermistor and method of fabrication, P (8) 283*j*. Thermocouple temperature measurement, P (1) 22*h*. Thin film decoupling capacitor incorporated in an integrated circuit chip and process for making, P (11) 379*c*. Ultrafast optical coincidence detector which utilizes the (1, −1, 0) surface or its crystallographic equivalent in [GaAs] crystals of the $42m$ or $\bar{4}3m$ class for mixing two orthogonally polarized pulses, P (8) 284*c*. Vacuum operated chip placement head, P (10) 346*c*. Wear resistant magnetic recording member, P (11) 379*b*.
Ibrahim, S. H. See Jellinek, H. H. G.
Ichiki, S. K. See Hill, R. M.
Ida, Ichiro. See Arai, Yuzo.
Iga, Atsushi. See Mizuno, Hideo; Yanase, Akira.
Iga, Takeo. See Ishii, Eiichi; Kato, Shuzo.
Ignat'eva, L. P. See Chebukov, M. F.
Ignatowicz, S., and Davies, M. W. Free energy of formation of NbO and Ta_2O_5, (8) 292*b*.
Iguchi, Shinichi. See Yoshino, Katsumi.
Iguchi, Yasutaka; Ban-Ya, Shiro; and Fuwa, Tasuku. Solubility of water in liquid CaO-SiO_2 with Al_2O_3, TiO_2, and FeO at 1550°C, (11) 374*g*.
Iida, Kiichi. See Miyatani, Shinya.
Iida, Shoji. Electrolysis and ion transport mechanism in uranium dioxide, (8) 291*c*.
Iida, Shuichi. Detailed electronic mechanism for low-temperature acoustic loss in magnetite, (1) 27*d*. Magnetostriction constants of rare earth iron garnets, (1) 32*g*. See Mizushima, Koichi; Ohbayashi, Kohji; Sugawara, Fuyuhiko; Yamada, Nobuyoshi.
Iida, Shuichi, and Iizuka, Tetsutaro. Cobalt impurity, cation vacancies, and magnetic relaxation of magnetite, (1) 26*e*.
Iida, Yoshio. See Nishimoto, Kazuyuki; Ozaki, Shunro.
Iizuka, Tetsutaro. See Iida, Shuichi.
Ikeda, Junichi. See Ohmori, Kazuo.
Ikeda, Koichi. See Yamamoto, Hiroshi.
Ikeda, Koichi, and Minagawa, Katsuji. Low melting point devitrified glass and method, P (5) 175*f*.
Ikeda, Koichi; Minagawa, Katsuji; and Nakagawa, Toru. Oxide coating for semiconductor surfaces, P (11) 378*b*.
Ikeda, Koichi; Tsuji, Shigeru; Anazawa, Shinzo; and Koyama, Tsukasa. Low melting glass, P (5) 175*e*.
Ikeda, Masayoshi. See Kanazawa, Takafumi.
Ikeda, Tadao. See Yamauchi, Shigeru.
Ikeda, Yutaka. Mechanisms in glass-to-metal bonding, (10) 336*f*.
Ikeda, Yutaka; Hoshino, Masahiro; and Kuroki, Hayashi. Method of making glass capacitors, P (11) 377*c*.
Ikegami, Seiji, and Ueda, Ichiro. Mechanism of aging in polycrystalline $BaTiO_3$, (8) 294*i*.
Iken, H., and Schrage, M. Process for producing cement and similar materials, P (7) 245*e*.
Ikushima, Hiroshi. Electron spin resonance of Mn^{3+} in reduced $BaTiO_3$ single crystals, (1) 29*c*. See Hayakawa, Shigeru.
Ikushima, Hiroshi, and Hayakawa, Shigeru. Electrical conduction in reduced single crystals of barium titanate, (9) 320*i*.
Iler, R. K. Multilayers of colloidal particles, (1) 33*d*.
Iles, P. A. Method for producing a solar cell

having an integral protective covering, P (7) 257*b*.
Iles, P. A., and Victoria, R. O. Process for making photosensitive semiconductor devices, P (1) 19*e*.
Il'ginova, V. T. See Chikanov, N. D.
Ilikon Corp. Method for the production of composite materials and articles produced thereby, P (11) 377*g*.
Il'in, M. A., Rashevskaya, E. P., and Shlyakov, O. N. Determination of nonhomogeneities in semiconducting materials by an optical reflection method, (2) 61*e*.
Il'ina, N. I. See Fedorov, P. I.
Ilschner, B., and Schmidt, H. Hardening of magnesium oxide by diffusion of iron, (4) 138*e*.
Il'yasov, I. I. System Na,K,Rb‖I, (4) 159*c*.
Il'yasov, I. I., and Barsegov, D. G. Fusibility diagram for a ternary system of bromides and iodides of thallium and cesium, (7) 266*e*.
Il'yasov, I. I., and Bergman, A. G. System $Na^+,K^+,Cs^+ \| I^-$, (4) 159*c*.
Il'yasov, I. I., and Chaurskii, N. I. System Cs,Pb‖Cl,Br, (9) 331*c*. System Na,Cs,Cd ‖ Br, (8) 299*g*.
Il'yasov, I. I., Chaurskii, N. I., and Barsegov, D. G. System Na,Cs,Cd‖I, (7) 270*b*.
Il'yasov, I. I., Dionis'ev, S. D., and Bergman, A. G. Inverse reciprocal systems of the bromides and iodides of sodium and lead, (9) 323*f*. System K,Cs,Pb‖Br, (7) 269*i*.
Ilyukhina, I. A. See Mikadze, I. S.
Imagawa, Hiroshi. See Yokota, Ryosuke.
Imai, M. See Bowden, F. P.
Imaizumi, Ichiro. Semiconductor integrated circuit device, P (9) 314*a*.
Imaizumi, Rikizo. See Soga, Minoru.
Imbusch, G. F. See Wood, D. L.
Imbusch, G. F., and Geschwind, S. Ground-state spin memory in the $\bar{E}(^2E)$ level of ruby in optical pumping via the bands, (2) 77*e*.
Imlach, J. A., and Glasser, F. P. Phase equilibria in the system $CaO-Al_2O_3-TiO_2$, (6) 235*h*.
Immel, W. See Hoffmann, H.
Immel, W., and Hoffmann, H. Technical problems of electrophoretic enameling (I), (5) 171*e*.
Immendorfer, M., and Spielmann, W. K. Epitaxial deposition of gallium arsenide from an atmosphere of hydrogen and Ga_2H_6 + $AsCl_3$ + AsH_3 vapors, P (2) 64*e*.
Imperial Chemical Industries, Ltd. Method of strengthening glass by a potassium nitrate-potassium borofluoride melt, P (8) 278*c*. Preparation of calcium sulfate alpha-hemihydrate slurries for casting in molds, P (6) 207*c*. Process for the production of formed gypsum castings, P (10) 336*c*.
Imperial Smelting Corp. (N.S.C.), Ltd. Process of preparing high purity cadmium hydroxide, P (10) 349*b*. Production of zinc oxide, P (4) 125*f*.
Imris, P. Method and apparatus for separating particles of different sizes, P (11) 381*f*.
Inagaki, Michio. See Noda, Tokiti.
Inanc, O. See Nickel, H.
Inazumi, Tadahiro. See Kojima, Kojiro.
Ince, N. S. See Cornelison, B.
Indelli, A. See Giacomelli, A.
Indiana University Foundation. Dentifrice compositions comprising zirconium silicate of particular particle size, P (10) 335*h*.
Indradev. See Seiler, H.
Industrial Nucleonics Corp. Coating thickness determination by means of measuring blackbody radiation resultant from infrared irradiation, P (4) 121*e*. Measuring ablation shield thickness, P (7) 261*a*.
Industrial Research & Manufacturing, Inc. Cementitious compositions, P (4) 92*f*. Portland cement compositions, P (4) 93*c*.
Ing, D. W. See McAvoy, B. R.
Ing, S. W. See Gerhard, G. C.
Ing, S. W., Jr., Chiang, Y. S., and Haas, W. Vapor grown SiAs crystals, (4) 163*d*.
Ing, S. W., Jr., and Jenzen, H. A. Light emitting semiconductor devices of improved transmission characteristics, P (8) 282*b*.
Ingersoll-Rand Co. Wear resistant cobalt bonded tungsten carbide composite, P (10) 343*c*.
Ingham, H. S., Jr., and Ingham, H. S., Sr. Molybdenum flame spray wire and process, P (10) 337*c*.
Ingham, H. S., Sr. See Ingham, H. S., Jr.
Ingraham, A. See Aronson, S.
Ingraham, R. C. See Baker, A. G.
Ingraham, T. R. Thermodynamics of the thermal decomposition of aluminum sulfate — Al-S-O system from 850° to 1050°K, (4) 162*c*.
Ingraham, T. R., and Marier, P. Kinetics of the formation of $MnSO_4$ from MnO_2, Mn_2O_3, and Mn_3O_4 and its decomposition to Mn_2O_3 or MnC_2, (4) 142*e*.
Ingram, D. J. E. See Robson, D.
Ingram, M. D. See Duffy, J. A.
Ingram, M. D., and Duffy, J. A. Octahedral-tetrahedral transitions of cobalt(II) in sulfate-chloride glasses, (5) 173*h*.
Inman, D., Lovering, D. G., and Narayan, R. Polarographic studies in molten $LiNO_3$+ $NaNO_3$+KNO_3 (I) half-wave potential and diffusion coefficients, (8) 296*j*.
Innes, W. B., and Michael, M. W. Caustic leach treatment of alumina particles to improve strength properties, P (11) 382*i*.
Inoguchi, Toshio. See Kaifu, Yozo.
Inomata, Y., Komatsu, H., Mitomo, M., and Inoue, Z. Direct observation of a cluster of screw dislocations in silicon carbide, (7) 265*d*.
Inoue, Keikichi. See Uei, Isao.
Inoue, Masashi. See Itoh, Kohji; Yamamoto, Ryoichi.
Inoue, Masayoshi. Anomalous thermal conductivity of $BaTiO_3$ near its ferroelectric transition point, (2) 74*i*.
Inoue, Toshiharu, and Tomotika, Tosiro. Electron spin resonance absorption in evaporated BaO films, (8) 291*g*.
Inoue, Toshio. See Kitagawa, Hiroshi.
Inoue, Toshio; Nishiwaki, Minoru; Tanaka, Isamu; and Kubota, Tatsuyuki. Operating condition of 185-ton ladle at LD converter plant of Sakai Iron Works — results achieved and means of improving them, (7) 251*c*.
Inoue, Yoshihiko. See Ando, Yoshio.
Inoue, Z. See Inomata, Y.
Inouye, Seiichi. Developing and application methods of ceramic coating, P (1) 5*e*.
Inouye, T. See Fujii, I.
Insley, M. J., and Parfitt, G. D. Precipitation of silver chloride from homogeneous solution (I) particle size and shape characteristics, (9) 327*j*.
Insolio, T. A., and Detorre, R. P. Glass cutting head, P (1) 10*e*.
Institut de Recherches de la Siderurgie Francaise. Process and apparatus for pneumatically classifying pulverulent material, P (8) 288*d*.
Institute of Silicate Chemistry. Temperature-Stable Protective Coatings — Proceedings of the Third Seminar on Heat-Resistant Coatings Held at the Institute of Silicate Chemistry, Leningrad, May 1966, B (5) 204*d*.
International Harvester Co. Electrical conductivity test method for determining active clay content in molding sand compositions, P (4) 121*f*.
International Minerals & Chemical Corp. Apparatus for making perforated bricks, P (4) 102*d*. Method of improving the operation of a cupola, P (4) 106*a*.
International Rectifier Corp. Adjustable variable voltage responsive two-terminal semiconductor switch device, P (8) 282*a*. Apparatus for [acid] dicing semiconductor wafers, P (5) 182*f* Compression assembled semiconductor device using spherical force transmitting member, P (1) 18*c*. Electrically insulating-heat conductive mass for semiconductor wafers, P (11) 376*c*. High-voltage diode for low pressure applications, P (2) 65*a*. High-voltage semiconductor device with electrical gradient-reducing groove, P (4) 113*b*. O-bend lead for semiconductor packages, P (9) 313*a*. Pinch-off shunt for controlled rectifiers, P (10) 345*e*. Pressure assembled semiconductor device using massive flexibly mounted terminals, P (9) 313*c*. Selenium rectifier, P (7) 258*a*. Semiconductor wafer forming a plurality of rectifiers, P (11) 378*h* Semiconductor wafer having low field junction surface, P (7) 258*f*. Unijunction transistor with improved efficiency and heat transfer characteristics, P (5) 185*i*.
International Society for Hybrid Microelectronics. Proceedings of First Technical Thick-Film Symposium, Palo Alto and Los Angeles, February 1967, B (5) 204*d*.
International Sorting Systems Corp. Apparatus for crushing and sorting solid particles, P (5) 190*d*.
International Standard Electric Corp. Ceramic-metal seals, P (1) 18*b*. P (6) 220*j*. Classy bistable electrical switching and memory device, P (7) 256*j*. Light emitting junction device using silicon as a dopant, P (5) 183*h*. [Method of making] microwave generators, P (10) 345*h* Method of making semiconductor devices, P (7) 257*h*. Method of making thyristors having electrically interchangeable anodes and cathodes, P (7) 257*i*. Method for the surface treatment of semiconductor devices, P (4) 115*i*. Multiple emitter transistor with improved frequency and power characteristics, P (10) 345*b*. Scanned line radiation source using a reverse biased *pn* junction adjacent a Gunn diode, P (8) 283*a*. Semiconductor process including reduction of the substrate thickness, P (6) 223*j*. Semiconductor switching device, P (4) 116*j*. Temperature compensating unit for piezoelectric crystals, P (4) 117*c*. Temperature compensation of crystal oscillators, P (10) 346*e*.
International Telephone & Telegraph Corp. Cylinder with internal photosensitive coating and prism on outer surface for admitting light at an angle to be totally internally reflected, P (8) 282*d*. Ferromagnetic materials and processes for their manufacture, P (10) 344*i*. High-frequency field-effect transistor, P (7) 256*a*. High permeability ferromagnetic ferrite materials, P (5) 183*e*. Method of shaping a crystal by acid cutting, P (2) 68*b*. Nonrectifying solid state element, P (10) 339*d*. Prestressed grinding wheel, P (6) 205*g*. Saturable solid state nonrectifying switching device, P (4) 116*i*. Semiconductor device having controllable noise characteristics, P (1) 19*h*. Simplified stacked semiconductor device, P (9) 314*b*. Solid state element comprising semiconductive glass composition exhibiting negative incremental resistance, P (9) 314*c*. Tunnel cathode in matrix form with integral storage feature, P (8) 284*b*.
Interpace Corp. Ceramic casting techniques, P (6) 220*d*. Pipe joint, P (6) 214*e*. Process of manufacturing ceramic articles and the products of such process, P (1) 16*a*. [Pulsed] pug mill apparatus, P (9) 314*h*.
Inuishi, Yoshio. See Yoshino, Katsumi.
Inuzuka, Hideo, and Wakatsuki, Masao. Process for preparing synthetic diamond by using direct electric current for heating, P (7) 243*i*.
Inuzuka, Tadao, and Ueda, Ryuzo. Nucleation density and epitaxy of gold deposited onto color-centered cleavage surface of rock salt, (6) 235*j*.
Ion Physics Corp. Fabricating solid state devices by ion implantation, P (6) 221*j*. High frequency field effect transistor, P (4) 113*j*.
Iosifescu, B. See Cavalerm, A.
Iowa State University Research Foundation, Inc. Laser small-particle detector and method, P (2) 71*j*.
Ip, J. See Murthy, M. K.
IRC, Inc. Semiconductor with trilayered metal contact, P (2) 63*f*
Ireland, J. W., and Holloway, J. C. Thin-film resistor adjustment, P (11) 379*a*.
Irie, Toshiaki. See Sato, Katsuo.
Irmler, H., and Voss, B. S.C.R. with emitter electrode spaced from semiconductor edge equal to 10 times base thickness, P (9) 313*g*.
Irving, G. M., Jr. Construction materials for breweries, (2) 45*h*.
Irving, R. J. See Hazell, I. F.
Irving, R. J., and McKerrell, H. Standard heat of formation of aqueous orthophosphoric acid, (8) 298*h*. Standard heats of formation of NaH_2PO_4, Na_2HPO_4, and Na_3PO_4, (8) 298*i*. Standard heats of formation of the sodium triphosphates $Na_5P_3O_{10}$(cI), $Na_5P_3O_{10}$(cII), $Na_5P_3O_{10}{\cdot}6H_2O$(*c*), (9) 330*e*; Standard heats of formation of two sodium pyrophosphates, sodium trimetaphosphate, and sodium tetrametaphosphate, (9) 330*e*.
Isaacs, J. W. See Cragg, D. G.
Isakhanov, G. V. See Beloivan, A. F.; Tresvyatskii, S. G.
Isard, J. O. See Gough, E.; Grossman, D. G.; Kaneko, H.
Isasa, S. See Anastassakis, E.
Isberner, A. W. See Klieger, P.
Iseki, Takayoshi. See Tagai, Hideo.
Isherwood, B. J. X-ray multiple diffraction study of $Y_3Fe{\cdot}O_{12}$, (11) 388*d*.
Isherwood, B. J., and Wallace, C. A. Analysis of epitaxic growth layers of silicon carbide by X-ray diffraction topography, (10) 349*j*.
Ishibashi, Michio. See Kaname, Yuichi.
Ishibashi, Tanezo. See Nameishi, Naoyuki.
Ishigame, Mareo. See Sakurai, Takemaro.
Ishigame, Mareo, and Sakurai, Takemaro. Electronic absorption spectrum of Ni^{2+} in CaO, (8) 291*j*
Ishihara, Shigetoshi, and Fujiki, Koichi. Basic investigation on stopper head for use at high temperature for long periods, (11) 372*h*.
Ishihara, T. See Yoshida, K.
Ishii, Eiichi. See Kato, Shuzo.
Ishii, Ichiro. Method of printing and baking scales on glass thermometers, P (10) 339*d*.
Ishii, Kikuo. See Tagawa, Hiroaki.
Ishii, Makoto, and Hashimoto, Hatsujiro. Electron microscopic observation of oxides formed on thin film of copper at elevated temperature, (8) 291*e*.
Ishii, Toshio. See Yamaguchi, Tadashi.
Ishii, Zensho. See Kawado, Seiji.
Ishino, Ken. See Tokue, Tetsuo.
Ishino, Toshio. See Adachi, Gin-ya.
Ishiwara, Shigetoshi. High-fired basic brick used in open-hearth furnace roof, (2) 56*a*.
Ishiwara, Shigetoshi, and Fujiwara, Kazuhiko. Service test on ladle with bottom of graphite-containing fireclay brick (II), (11) 374*c*.
Ishizawa, Kenki. See Hayashi, Takeshi.
Isoda, Masao. Corrosion mechanism in basic brick, (11) 372*i*.
Iso/Serve, Inc. Radioisotopic heat source and method of production, P (5) 179*e*.
Isreeli, J. See Rosin, S.
Istag A.-G. Suhr/A.-G. Sintering method, P (8) 280*a*.
Itakura, Kiyoshi, and Takigawa, Hideaki. Apparatus for stretching molten sheet glass laterally, P (9) 307*a*.
Itakura, Masayuki; Nilzeki, Nobukazu; Toyoda, Hiroo; and Iwasaki, Hiroshi. Hall effect and thermoelectric power in semiconductive TiO_2, (8) 292*g*.
Itaoka, Takashi. Trial use of special roseki (pyrophyllite) ladle brick, (11) 374*d*.
Ito, Akio. See Kawamura, Sukizo.
Ito, Atsuko. See Ono, Kazuo.
Ito, Hiroo. See Suzuishi, Masatsugu.
Ito, Jun. Strontium rare-earth hydro- and germanate garnets, (7) 269*a*. Study of chevkinite and perrierite, (4) 157*d*. Synthesis of cerite, (1) 39*a*. Synthetic indium silicate and indium hydrogarnet, (10) 362*e*. See Frondel, C.
Ito, Jun, and Frondel, C. New synthetic hydrogarnets, (4) 146*i*. Syntheses of lead silicates — larsenite, barysilite, and related phases, (4) 158*j*. Synthesis of the grossularite-spessartite series, (8) 299*f*. Synthetic zirconium and titanium garnets, (4) 158*g*.
Ito, Jun, and Johnson, H. Synthesis and study of yttrialite, (10) 362*c*.
Ito, Jun, and Peiser, H. S. Distorted tetrahedra in strontium copper akermanite, (6) 231*i*.

Ito, Kunihiko. See Kita, Hideo.
Itoh, Kohji. See Yamamoto, Ryoichi.
Itoh, Kohji; Yamamoto, Ryoichi; Inoue, Masashi; and Sato, Hisanao. Injection EL diode, P (4) 113*e*.
Ittyachen, M. A. See Joshi, M. S.
Ivaniov, W. See Mircea, S.
Ivanko, A. A. See Bazhenova, L. N.
Ivanov, B. G. See Belitskii, M. E.
Ivanov, M. I. See Vitman, F. F.
Ivanov, N. P. See Sedykh, E. M.
Ivanova, L. D. See Krokhina, A. I.
Ivanova, N. A. See Novokhatskii, D. F.
Ivanovskii, G. F., Blyumkin, L. M., Varnakov, S. V., and Lisovskii, L. P. Apparatus for the mass-spectrometric analysis of the distribution of gaseous impurities in materials by laser beams, (4) 118*j*.
Ivashentsev, Ya. I., and Timonova, R. I. Chlorination of rhodium and thermal transformations of the trichloride, (8) 289*j*.
Iverson, H. G., and Leitch, H. Alumina extraction by autoclave precipitation of basic sodium aluminum sulfate, (2) 72*i*.
Ivey, K. H. See Nichols, E. F.; Shell, H. R.
Iwai, Shinichi. See Tagai, Hideo.
Iwamoto, Kazumi, and Oishi, Jun. Escape behavior of nongaseous fission products recoiled into graphite, (10) 341*f*.
Iwamoto, Sadayuki. See Ogura, Hirokatsu.
Iwamoto, Yoshimi. See Ueda, Masao.
Iwanaga, Hiroshi. See Okazaki, Atsushi.
Iwanaga, Hiroshi, and Shibata, Noboru. Morphology and polarity of the ZnO crystal, (8) 295*j*.
Iwasaki, Bunji. See Katsura, Takashi.
Iwasaki, Hiroshi. See Itakura, Masayuki; Yamada, Tomoaki.
Iwasaki, Hiroshi, Bright, N. F. H., and Rowland, J. F. Polymorphism of the oxide Ti_3O_5, (10) 358*j*.
Iwasaki, Hiroshi; Yamada, Tomoaki; Niizeki, Nobukazu; and Toyoda, Hiroo. Piezoelectric and optical properties of $LiNbO_3$ single crystals, (1) 34*d*.
Iwasaki, M. Kinetics of the fluorination of uranium dioxide pellets by fluorine, (5) 196*c*.
Iwata, Koshi. See Mizuno, Hideo.
Iwata, Tadao, and Sato, Yoshiki. Optical absorption of neutron-irradiated graphite, (2) 81*e*.
Iyengar, G. N. K. See Alcock, C. B.
Iyengar, L. See Rao, K. V. K.
Iyengar, R. D. See Zettlemoyer, A. C.
Iyer, K. P. D., and Wariyar, N. S. New method for the comparison of surface areas of solids using adsorption from solution, (2) 70*j*.
Izaki, Toshiyuki. See Okada, Kichiji.
Izergina, E. V., Yakovlev, G. K., Zakharova, A. D., and Komin, N. E. Nickel ferrites containing cobalt, lead, and silicon, P (9) 313*h*.
Izrailevich, E. A. See Shuvaev, A. T.
Izrailevich, I. S., and Novikov, S. N. Determination of specific surface (particle size) of powders from the ratio of flow rates measured under different conditions of gas flow in a porous medium, (2) 69*a*.
Izumi, Hideo. See Nagatsu, Hiroshi.

Jablonska, B. See Sikora, W.
Jackson, B., and Laming, J. Significance of mechanical properties of basic refractories at elevated temperatures, (6) 216*e*.
Jackson, B. J. H., and Young, D. A. Ionic conduction and thermal disorder in thallous chloride, (5) 195*j*.
Jackson, D. M., Jr. Method of fabricating a semiconductor structure with an electrically isolated region of semiconductor material [epitaxial deposition], P (11) 377*j*.
Jackson, D. M., Jr., Frazee, O. P., and Waldow, P. Multilayer [epitaxial] semiconductor device, P (10) 345*b*.
Jackson, J. C., and Selpt, W. R. Method of curing hydraulic cement, P (6) 207*e*.
Jackson, P. W. See Cratchley, D.
Jackson, P. W., and Marjoram, J. R. Recrystallization of nickel coated carbon fibers, (9) 328*g*.
Jackson, R. A. See Chen, W. K.
Jacobi, R. Unexpected properties of thin films of silver, (1) 15*d*.
Jacobi, R., Stahl, R., Quenett, R., Achhammer, J., and Merkel, E. Method for sealing spacing members in a double or multiple glass pane assembly to the margins of the glass panes, P (1) 11*a*.
Jacobs, A. Furnace arrangement and method, P (11) 371*g*.
Jacobs, J. C. H. Practice of the casting process, (6) 224*i*.
Jacobs, J. M. H., Hermsen, A. A. M., Hendriks, A. J., and Teeling, G. A. M. [Conical] mixing apparatus, P (5) 186*e*.
Jacobs, L. J., Klaudinyi, B., and Fisher, R. E. Expendable pattern for precision investment casting, P (5) 178*g*.
Jacobs, P. W. M., and Menon, A. K. Temperature dependence of *F*-center absorption in KBr and NaBr, (9) 331*j*.
Jacobsen, A. Attachment for introducing light into an image-transmitting fiber-optical system for illuminating an object, P (9) 307*a*.
Jacobson, A. J. See Fender, B. E. F.
Jacobson, H. W. Process for coating metal articles employing fluidized bed, P (2) 46*e*.
Jacobus, L. A., Jr. See Olmstead, J.
Jacquin, M. See Asquiedge, M.; Guillou, M.
Jaeger, B. E. Rotary screen decorating machine, P (5) 176*a*.
Jaeger, R. E. See Edelson, D.
Jaeger, R. R. See Lipschutz, M. E.
Jaenicke, R. See Harth, W.
Jaenicke, W. See Reichenberger, H.
Jaffee, P. M. Cathodoluminescence spectra and coordination of Mn^{2+}, Fe^{3+}, and Cr^{3+} in β-$LiAl_5O_8$, (10) 350*c*.
Jaffee, R. I. See Bradley, E. F.
Jager, H. Apparatus for drying and preheating of pulverulent material, particularly raw cement material, P (5) 170*c*.
Jager, P. See Petzenhauser, I.
Jagodzinski, R. F. See Francel, J.
Jagolino, R. B. Simple field application of DTA for the determination of dolomitic limestone, (1) 22*c*.
Jahanbagloo, I. C. X-ray diffraction study of olivine solid solution series, (10) 363*e*.
Jahn, W. Optical crown glass on phosphate base, P (10) 339*f*.
Jahnberg, L., and Andersson, S. Studies on pentavalent tantalum oxide fluorides and the thermal decomposition of TaO_2F, (4) 156*j*.
Jain, D. S., Kumar, A., and Gaur, J. N. Polarographic study of the complexes formed by cadmium with oxalate ions, (1) 34*h*.
Jain, M. K. See Reddy, P. G.
Jain, R. K., and Trigunayat, G. C. Nucleation and epitaxial growth of polytypic crystals, (7) 267*h*; Observations of eight, nine, and twelve sided growth spirals on $[CdI_2]$ crystals of trigonal symmetry, (7) 267*h*.
Jaisle, A. See Kleintsich, R.
Jakas, R. P., and Chorne, J. Method and means for separating individual fibers from a fibrous mass, P (5) 186*e*.
Jakes, D., and Schauer, V. Heat capacity of some uranates, (5) 194*g*.
Jambor, J. L. New lead sulfantimonides from Madoc, Ontario (III) syntheses, paragenesis, origin, (1) 33*a*.
James, A. N. See Edmeades, R. M.
James, D. W. See Boston, C. R.
James, D. W., and Sekerka, R. F. Effect of impurities on solidification kinetics measured by the thermal wave technique, (4) 132*j*.
James, P. F., and McMillan, P. W. Direct observation of phase separation in glasses, (9) 315*d*.
James, S. D. Variations in hydraulic permeability of a crystal plug, (1) 40*b*.
James, W. G. Plural [lacquer] coated transparent colored lamp and method of forming, P (5) 176*c*.
Jamieson, P. B. Crystal structure of $Na_2Si_2O_5$—a new type of silicate sheet, (4) 130*j*. See Abrahams, S. C.
Jamieson, P. B., Abrahams, S. C., and Bernstein, J. L. Crystal structure of the transition-metal molybdates and tungstates (V) paramagnetic alpha-$Nd_2(MoO_4)_3$, (10) 351*e*. Ferroelectric tungsten bronze-type crystal structures (I) barium strontium niobate $Ba_{0.27}Sr_{0.75}Nb_2O_{5.75}$, (5) 194*f*; (II) barium sodium niobate $Ba_{(4+x)}Na_{(2-2x)}Nb_{10}O_{30}$, (11) 385*a*.
Jamieson, P. B., and Glasser, L. S. D. Sodium silicate hydrates (III) crystal structure of $Na_2O{\cdot}SiO_2{\cdot}6H_2O$ and of the isostructural $Na_2O{\cdot}GeO_2{\cdot}6H_2O$, (7) 268*d*.
Jamini, M. A. *P*-contact for compensated *p*-germanium crystal, P (11) 378*c*.
Jamison, G. E. See Geib, C. B., Jr.
Janah, A. Vitreous enameling aluminum—a review, (2) 46*c*.
Janakirama-Rao, B. V. Vanadium-zinc borate solder glasses, P (8) 278*c*.
Jandeleit, O. Study of the regularity of optical defects in bent glass plates, (5) 173*h*.
Janes, S., and Nixdorf, J. Production of dense bodies from carbides, borides, nitrides, silicides, oxides, and cermets by pressure sintering, (11) 373*c*.
Jangg, G., Kieffer, R., and Usner, L. Production of mixed carbides by the auxiliary metal bath technique, (6) 236*a*.
Jankowski, B. Effect of thermoelement adjustment on the magnitude of the differential thermal analysis effect, (4) 119*e*.
Jankowsky, H. B. See Henderson, C. M.
Janossy, M. See Csillag, L.
Janowski, K. R. See Carnahan, R. D.; Cost, J. R.
Janssens, H. H., Westerveld, W., and Nijland, L. M. Electroluminescent screen composition, P (9) 312*f*.
Jansson, R. See Beckman, L.
Janz, G. J. See Timidei, A.
Janz, G. J., Dampier, F. W., Lakshminarayanan, G. R., Lorenz, P. K., and Tomkins, R. P. T. Molten salts (Vol. 1) electrical conductance, density, and viscosity data, (7) 262*f*, B (10) 365*f*.
Japan Atomic Energy Research Institute. Brazing composition for carbonaceous materials, P (7) 252*e*. Method of brazing carbonaceous materials and brazing crabonaceous materials with metal and brazing material thereof, P (7) 252*e*.
Jaques, T. A. J. Electrical resistance furnaces, P (2) 72*g*.
Jarboe, E. D., and Soucy, P. L. Low temperature cured ceramic coating composition, P (4) 114*a*.
Jarrad, D. S. Ohmic contact consisting of a bilayer of gold and molybdenum over an alloyed region of aluminum-silicon, P (7) 257*f*.
Jarrett, P. M. Time-dependent consolidation of a sensitive clay, (8) 285*i*.
Jarrouse, B. See Schiller, C.
Jarzmik, B. See Schleifer, P.
Jaselskis, B., and Bandemer, M. K. Determination of micro and semimicro amounts of aluminum using fluoride activity electrode, (8) 284*i*.
Jasutis, V. See Tolutis, V.
Jaswal, S. S. Influence of additional cation impurities on localized vibration modes due to *U* centers in NaCl and KCl, (2) 78*g*.
Jaszfalusi, H. Corrosion of refractories for glass-melting furnaces, (1) 11*j*.
Jaupain, M. See Plumat, E.
Javaux, G. Glass furnace wall arrangement, P (8) 277*c*.
Javed, N. A. See Alcock, C. B.
Javorik, L. Method of manufacturing cathode ray tube, P (7) 249*h*.
Jayadevaiah, T. S. See Berry, W. B.
Jayaweera, S. A. A. See Glasson, D. R.
Jean, B. L. P. See Berth, M.
Jeanneau, J. Y. Serpentines of the Bay of Audierne, (2) 73*h*.
Jebsen-Marwedel, H. Glass as a model to reconstruct methods of working flint in the Stone Age, (9) 305*h*.
Jech, C. See Kelly, R.
Jech, C., and Kelly, R. High-resolution measurements of the diffusion of inert gas in α-Al_2O_3, (8) 293*c*.
Jeffery, J. W. See Chatterji, S.
Jeffes, J. H. E. Physical chemistry of transport processes, (10) 358*h*.
Jeffes, J. H. E., and Alcock, C. B. Production of refractory crystals by vapor transport reactions, (9) 328*f*.
Jeffrey Gallon Mfg. Co. Continuous muller, P (6) 225*a*. Drying particulate material, P (2) 67*h*.
Jegou-Vilnat, J., and Dubois, M. X-ray fluorescence analysis of silica-based materials—comparison of the results obtained by X-ray fluorescence, spectrography, and chemistry, (5) 188*d*.
John, W. F. Oral controlled pressure regulator for blowing glass, P (6) 213*h*.
Jelinek, F. J. See Gerstein, B. C.
Jellett, V. R. See Healy, T. W.
Jelli, A. See Fripiat, J. J.
Jellinek, H. H. G., and Ibrahim, S. H. Sintering of powdered ice, (1) 36*i*.
Jena, A. K. See Reti, A. M.
Jenaer Glaswerk Schott & Gen. Attachment for introducing light into an image-transmitting fiber-optical system for illuminating an object, P (9) 307*a*. Optical crown glass on phosphate base, P (10) 339*f*.
Jenkins, A. E. See Sheasby, J. S.
Jenkins, G. M. Effect of microporosity on the elastic modulus and yield curve of polycrystalline graphite, (10) 341*b*
Jenkins, R. H. See Hadley, D. J.
Jenkinson, D. A. See Carr-Brion, K. G.
Jennings, B. R., and Plummer, H. Study of the light scattered by hectorite solutions when subjected to electric fields, (5) 200*j*.
Jennings Radio Mfg. Corp. Miniature single pole-double throw ceramic-metal switch structure, P (2) 66*b*.
Jensen, G. A. Spray coating, P (7) 246*h*.
Jensen, H. A. See Barnett, A. M.; Ing, S. W., Jr.
Jensen, S. J. Crystal structure of $KMnCl_3{\cdot}2H_2O$, (8) 290*c*; Crystal structure of $K_2MnCl_4{\cdot}2H_2O$, (8) 290*c*.
Jensen, W. R. See Batchelor, C. S.
Jepsen, T. L. B. Selective flotation of dolomite away from magnesite, P (4) 125*j*.
Jerome, G. A. Manufacture of silicon carbide ribbons, P (8) 279*e*. See Kern, E. L.
Jerrett, S. H. British ceramic tile today, (4) 108*d*.
Jesenak, J. P. See Jesenakova, V.
Jesenakova, V., and Jesenak, J. P. Clay-water relations in stiff clays, (5) 192*i*.
Jesumann, A. Building materials and apparatus for testing, (4) 119*a*.
Jezussek, A. See Knoedler, D.
Jha, N. K. See Barlett, N.
Jimbo, Yoshiro, and Hongo, Yasuo. Variation of setting time of castable refractories with curing temperature, (11) 374*e*.
Jinnette, A. J. Process for dulling glass fibers with oxalic acid including pretreatment with calcium salts, P (2) 54*a*.
Jintan Terumo Co., Ltd. Method of printing and baking scales on glass thermometers, P (10) 339*d*.
Jirlow, K. See Brune, D.
Jitea, B. See Petri, L.
Jobling, A. Effect of calcining conditions on some physical properties of calcined bone, (6) 228*j*.
Jobling, James A., & Co., Ltd. [Glass tube] grinding machines, P (10) 339*f*.
Joe, C. J. See Adami, L. H.
Joel, H. A. See Gross, P.
Joergensen, C. K., Neilands, J. B., Nyholm, R. S., Reinen, D., and Williams, R. J. P. (editors). Structure and Bonding (Vols. 3–5), B (6) 242*b*.
Joergensen, P. Apparatus for detecting and recording the locations of defects in sheet material in two dimensions, P (4) 98*c*.

Joergensen, S. S. Solubility and dissolution kinetics of precipitated amorphous silica in 1*M* $NaClO_4$ at 25°C, (8) 297*i*.
Johannes, W. Formation of deposits of magnesite and siderite in the system Mg^{2+}-Fe^{2+}-CO_3^{2-}-Cl_2^{2-}-H_2O, (10) 353*h*.
Johansen, H. A., and Cleary, J. G. Incandescent lamp with a refractory metal carbide filament, P (2) 65*b*.
Johansson, A. See von Heidenstam, O.
Johansson, G. Structure of the hydrolysis products of thorium, (8) 298*e*.
Johansson, K., Karlsson, A., and Kozyczkowski, J. Instrument for the study of excited nuclear states by angular correlation methods (III) transistorized electronic equipment, (1) 21*b*.
Johari, O. Scanning electron microscope—its operation and use, (1) 22*a*.
John, H. F. See Faust, J. W., Jr.
John, W. Shrink foil packaging in the whiteware industry, (10) 343*f*.
Johns, K. A. See Landsberg, P. T.
Johns, W. D. See Bissada, K. K.
Johns, W. D., and Sen Gupta, P. K. Hydrogen-bonding site distribution on layer silicate surfaces, B (4) 167*h*.
Johns-Manville Corp. Apparatus for delivering molten materials, P (5) 189*f*. Apparatus for forming glass fiber products, P (1) 10*f*. Effect of cryolite on calcium silicate compositions, P (9) 304*b*. Inorganic fiber riser sleeves, P (10) 342*f*. Method of blending ceramic and carrier fibers, P (4) 106*g*. Method for separating asbestos fibers from foreign solids, P (5) 191*d*. Nonporous asbestos-reinforced plastic pipe, P (11) 375*d*. Pipe coupling, P (4) 93*b*. Refractory fibers for service to 2700°F, P (9) 309*d*. Slag cement compositions, P (9) 304*e*. Thermal insulation of fibrous brucite, P (6) 218*h*.
Johnson, A. C. W. Low intensity radiant heater system and burner therefor, P (1) 23*b*.
Johnson, A. F. Carbon furnace electrode assembly, P (6) 217*i*.
Johnson, A. F., Jr. See Bippus, J. R.
Johnson, A. J. See Conaway, W. A.
Johnson, A. L., and Alexander, J. M. Melting glass batch—the submerged combustion principle, (5) 173*d*.
Johnson, B. A., and Adamski, M., Jr. Surface area measurement of variable length sample of finely divided solids, P (4) 122*b*.
Johnson, B. A., Adamski, M., Jr., and Lichodziejewski, W. L. Surface area measurement of standard length sample of finely divided solids, P (11) 381*b*.
Johnson, B. L. Alloy for metalizing ceramics, P (2) 64*c*.
Johnson, D. L. New method of obtaining volume, grain-boundary, and surface diffusion coeff. cients from sintering data, (9) 325*d*.
Johnson, D. S., Jr. See O'Shea, C. J.
Johnson, E. J. Continuous [fast fire] pottery kiln with slidable stretchers, P (10) 348*c*.
Johnson, G. G., Jr., and Vand, V. Computerized powder diffraction identification system, (1) 21*a*.
Johnson, H. See Ito, Jun.
Johnson, H. B., and Kessler, F. Kaolinite dehydroxylation kinetics, (6) 234*d*.
Johnson, H. E. See D'Eustachio, D.
Johnson, H. E., and D'Eustachio, D. Method of making a shaped article from coated multicellular glass nodules, P (6) 213*d*.
Johnson, J. H. See Merchant, C. O.
Johnson, James R. Structural articles [honeycomb] and method of making, P (8) 280*e*.
Johnson, James R., and Sowman, H. G. Composite green structures for nuclear fuel element, P (7) 252*i*. Fuel elements, P (10) 342*d*.
Johnson, John R. Container indexing and rotating, P (11) 371*c*.
Johnson, J. W., and Holloway, D. G. Microstructure of the mist zone on glass fracture surfaces, (1) 7*i*.
Johnson, K. E. See Bartlett, H. E.
Johnson, L. F., and Van Uitert, L. G. Fluorescent garnet compositions and optical maser devices utilizing such compositions, P (2) 64*g*.
Johnson, L. R., and Terrell, M. P. Calculation of empirical formulas using linear programming, (2) 47*a*.
Johnson, M. F. L. See Erickson, H.
Johnson, M. N. Electrostatic hand gun comes of age, (1) 20*b*.
Johnson, P. D. Mercury bismuth halide photochemical arc lamp light sources, P (9) 307*h*.
Johnson, R. D. New exports from industrial research, (6) 229*f*
Johnson, R. E. See Olsen, D. A.
Johnson, R. E., and Muan, A. Activity-composition relations in solid solutions of the system CaO-"FeO"-SiO_2 in contact with metallic iron at 1080°C, (1) 24*i*.
Johnson, S. A. See Stokowski, S. E.
Johnson, T. A. Combustion chamber design and material for internal combustion cylinders and engines, P (4) 93*i*.
Johnson, V. A. See Walker, B. F.
Johnson, W., Phillips, L. N., and Watt, W. Production of carbon fibers and compositions containing the fibers, P (4) 107*e*.
Johnson, W., and Watt, W. Structure of high modulus carbon fibers. (4) 156*g*.
Johnson, Walter E. Understanding the steel strength problem, (8) 275*e*.
Johnson, William E. Electrical printing apparatus using screen with thick coating to define image, P (8) 277*h*. Electrical printing methods and apparatus for decorating cylindrical articles, P (11) 371*f*. Electrical printing process using an opposing field, P (5) 186*e*.
Johnson, W. L. Butt joint for flexible abrasive sheet material, P (1) 1*g*.
Johnson Brothers (Hanley), Ltd. See West Midlands Gas Board.
Johnson Service Co. Cross-linked electrical resistance humidity sensing element, P (11) 381*e*.
Johnston, T. J. See Richards, N. E.
Johnston, T. L. Fracture of polycrystals, B (1) 41*f*.
Joiner, J. C. See Badami, D. V.
Joksic, Z. Correlation between the modulus of compressibility and the density of cohesive materials, (5) 189*h*.
Joly, F. H. E. See Van Den Steen, A. J.
Jones, B. W. Dielectric constant of ionic solids and its change with hydrostatic pressure, (1) 27*h*.
Jones, C. E., Jr., and Hilton, A. R. Optical absorption in chromium doped high resistivity GaAs in the 0.6 to 1.5 eV range, (1) 33*g*.
Jones, D. A., and Shand, W. A. Crystal growth of fluorides in the lanthanide series, (7) 264*f*.
Jones, D. E., and Gaskill, J. R. Thermoluminescent radiation dosimetric material, P (4) 117*e*.
Jones, D. W., Matthews, R. S., Ruddlesden, K., and Williams, D. J. Proton magnetic resonance in borate glasses, (1) 8*a*.
Jones, E. D. Nuclear magnetic resonance in the paramagnetic states of MnO, α-MnS, and α-MnSe, (4) 147*a*.
Jones, E. E. See Gadd, J. D.
Jones, F. G., Gardner, H. E., and Pehlke, R. D. Equilibrium between aluminum and nitrogen in liquid 18% Cr-8% Ni stainless steel, (6) 232*c*.
Jones, F. T. Spindle stage with easily changed liquid and improved crystal holder, (8) 285*f*.
Jones, G. A. See Badami, D. V.
Jones, G. D., and McMillan, W. J. Foamable granule product with method of preparation and molding, P (11) 371*f*.
Jones, G. R. Optical absorption spectrum and optical Zeeman effect in $CaWO_4$:Yb^{3+}, (4) 147*g*. See Edwards, A. J.
Jones, J. A. See Glasson, D. R.
Jones, J. L., and Mieure, J. P. Piezoelectric transducer for determination of metals at the micromolar level, (8) 285*i*.
Jones, J. W. S. See Henney, J.
Jones, K. A. See Galwey, A. K.; Kirsch, H.
Jones, K. A., Acheson, R. J., Wheeler, B. R., and Galwey, A. K. Thermal decomposition of nickel malonate, (9) 331*i*.
Jones, M. E. Color TV tube structure, P (2) 64*i*. See Cornelison, B.
Jones, M. P. See Holt, D. B.
Jones, N. W. Discussion of "Subsolidus equilibria in the system MgO-GeO_2-MgF_2," (6) 231*g*.
Jones, O. See Bardsley, W.
Jones, P. M. S., Edmondson, W., and McKenna, N. J. Stability of metal tritides-yttrium tritide, (4) 156*a*.
Jones, R. A. See Long, R. A.
Jones, R. E., Winters, H. F., and Maissel, L. I. Effect of oxygen on the rf-sputtering rate of SiO_2, (4) 133*c*.
Jones, R. L. (Baton Rouge). See Osment, H. E.
Jones, R. L. (Canoga Park). See Langrod, K.
Jones, T. L. See Webster, R. K.
Jones, T. P., Coble, R. L., and Mogab, C. J. Defect diffusion in single crystal aluminum oxide, (8) 290*i*.
Jones, W. L. Metalizing and bonding nonmetallic bodies, P (4) 114*e*.
Jonke, A. A. See Holmes, J. T.
Jonker, G. H. Method of treating objects of oxidic ceramic polycrystalline materials, P (11) 377*h*. Semiconducting properties of $LaCoO_3$, (10) 365*f*.
Jonscher, A. K. See Argall, F.
Jorba, M. P. y. See Perez y Jorba, M.
Jordan, C. C. See Cropp, D. I.
Jordan, E. P. See Lumley, J. L.
Jordan, M. E. See Hardy, J. E.
Jorgensen, M. H., Meyers, N. I., and Bruel, N. Field dependence of ultrasonic attenuation in semiconducting ZnO, (4) 136*f*.
Jorgensen, P. J. Comments on "Transport processes in the thermal oxidation of silicon," (4) 129*c*. Electrolysis of SiO_2 on silicon, (8) 291*d*. Silicon dioxide coatings utilizing a plasma, P (6) 224*a*. See Hanneman, R. E.; Laska, H. M.; Westbrook, J. H.
Jorgensen, P. J., and Norton, F. J. Proton transport during hydrogen permeation in vitreous silica, (7) 248*b*.
Joseph, H. C., and Zook, J. D. Semiconductor device with a lateral retrograded *pn* junction, P (6) 223*g*.
Joseph, P. T., and Mony, C. N. New method for opening up monazite, (2) 73*g*.
Joseph, R. A. See Aitken, E. A.
Joshi, M. S., and Ittyachen, M. A. Growth mechanism of apophyllite crystals studied by surface microstructures, (6) 233*a*. Rotation of etch pits on the basal cleavages of apophyllite crystals, (1) 36*i*.
Joshi, M. S., and Kotru, P. N. Hillocks on first-order prism faces of synthetic quartz, (8) 293*d*.
Joshi, M. S., Kotru, P. N., and Vagh, A. S. Microtopographical studies of first order prism faces of synthetic quartz, (9) 324*f*.
Jost, K. H., Wolf, H., and Thilo, E. Evidence of monomeric structures in polygermanatosilicate melts, (7) 265*f*.
Jostsons, A. See Watanabe, D.
Jostsons, A., and Hickman, B. S. Effect of irradiation on chrysoberyl, (6) 232*e*.
Joubert, J. C. See Durif, A.
Joubert, J. C., and Durif, A. New spinel compositions with type 1:1 cation ordering on tetrahedral sites, (1) 33*c*.
Joubert, J. C., Shirk, T., White, W. B., and Roy, R. Stability, infrared spectrum, and magnetic properties of $FeBO_3$, (2) 83*g*.
Joubert, J. C., White, W. B., and Roy, R. Synthesis and crystallographic data of some rare-earth iron borates, (11) 387*i*.
Jouenne, C. A. Earthenware, stoneware, and porcelain, (6) 219*e*.
Jouquet, G. See Merlin, J.
Jourdain, A. Refractories in the glass industry—introduction, (1) 8*c*.
Journeaux, D. Tall candlesticks from a short kiln, (7) 244*d*.
Jouwersma, C. See Monneraye, M.
Joy, A. S. See Kini, K. A.
Joyce, B. A. Growth and perfection of chemically deposited epitaxial layers of Si and GaAs, (7) 255*a*. See Brown, A. S.
Joyce, B. D. Semiconductor integrated circuits and method of making the same, P (5) 185*i*.
Joyce, D. E. See Fryxell, R. E.
Joynson, R. E., Jr. See MacKellar, D.
Judd, D. M. Porcelain enamel—permanent color for aluminum, (1) 5*a*.
Judd, M. D., and Pope, M. I. Simple, inexpensive Pyrex-to-aluminous porcelain vacuum seal for use in thermal analysis, (6) 227*b*.
Judge, J. S. See Bate, G.
Judin, V. M., and Sherman, A. B. Weak ferromagnetism of $YCrO_3$, (4) 163*j*.
Juhola, A. J., and Pferdehirt, T. A. Preparation of boron filaments in an electrical discharge, P (7) 253*a*.
Juillet, F., Vergnon, P., and Teichner, S. J. Effect of atmosphere on the properties of some refractory oxides, (1) 12*a*.
Julian, C. L., and Lane, F. O., Jr. Calculation of the elastic constants of alpha quartz from a model, (4) 127*j*.
Jun, J. See Niemyski, T.
Junge, A. E., and Chabal, J. Colored transparent durable titania films on glass, P (5) 174*a*. Tinted mirror, P (10) 340*c*.
Jungreis, E., and Ben-Dor, L. Means and method for the detection of uranium, P (1) 22*d*.
Junichi, Ikeda. See Ohmori, Kazuo.
Junkison, A. R. See Allbutt, M.
Juretschke, H. J. Third-order elastic constants of polycrystalline media, (2) 84*i*.
Jurid Werke G.m.b.H. Sintered friction material, P (7) 253*c*.
Juskevicius, A. See Kudaba, V.
Juza, R., Laudt, U., and Hansen, H. Reaction of calcium carbide with aluminum oxide, (6) 237*a*.
Juza, R., Trapp, H. D., and Seidel, H. Magnetochemical studies of the phase $Mg_{3-x_2/2}Mn_xAs_2$, (5) 181*g*. Magnetochemical studies of phases of the ternary lithium-manganese-arsenic system, (5) 181*h*.
Juza, R., Voelling, A., and Schuster, H. U. Reaction of calcium carbide with silicon dioxide, (6) 237*b*.

Kaae, J. L. Mathematical model for calculating stresses in pyrocarbon- and silicon carbide-coated fuel particles, (10) 341*a*.
Kaarlela, W. T. Process for joining metals and ceramics having grossly different coefficients of thermal expansion, P (5) 172*b*.
Kabai, L. Compressibility of sands and sandy gravels, (5) 189*j*.
Kabanov, A. N., Mikhailovskii, G. A., Panteleev, N. I., and Seleznev, I. P. E-8 high-vacuum electron-beam setup, (2) 62*a*.
Kabanovich, I. V. See Kashkurov, K. F.; Kleshchev, G. V.
Kabashima, Shigeharu, and Kawakubo, Tatsuyuki. High frequency conductivity of NiO, (2) 78*c*.
Kabashima, Shigeharu; Tsuchiya, Yoshimi; and Kawakubo, Tatsuyuki. High frequency conductivity of VO_2, (8) 292*j*.
Kabel'skii, I. M. See Boginskii, L. S.
Kabushiki Kaisha Crown Samgyo. Spark ignited gas burner, P (7) 261*h*.
Kabushiki Kaisha Hitachi Seisakusho. Infrared ray detector utilizing ferroelectric single crystal, P (10) 345*b*. Magnetic materials having rectangular hysteresis loops, P (7) 256*h*. Method of forming a glass coating on semiconductor, P (4) 114*f*. Method of producing ceramic piezoelectric vibrator, P (9) 313*d*. Method of producing insulated-gate field-effect transistors with improved characteristics, P (4) 115*g*. Surface treatment for semiconductor devices, P (9) 314*e*. Temperature detector, P (4) 117*d*. Thermistor composition containing vanadium dioxide, P (1) 19*e*.
Kabushiki Kaisha Maruto Seisakusho. Apparatus for cutting, grinding, and polishing ornamental stone, P (9) 314*g*.
Kabushiki Kaisha Obara Kogaku Garasu Seizosho. Glass composition for use as the faceplate of an image orthicon tube and the like, P (4) 98*i*.

Kabushiki Kaisha Rinnai Seisakusho. Burner, P (6) 212*i*.
Kabushiki Kaisha Sanko Seisakusho. Dust collector, P (6) 225*a*.
Kachalov, N. N. See Shabanov, A. G.
Kachel, I. Method of preparing a slurry coating composition, P (2) 65*j*.
Kacheva, K. M. See Mathur, S.
Kachi, S. See Kobayashi, K.
Kachi, Sukeji. See Nishimoto, Kozo; Okinaka, Hideyuki.
Kachik, R. H. See Boggs, W. E.
Kachina-Pullo, E. B. See Ukshe, E. A.
Kacker, K. P. See Ramachandran, V. S.
Kadlecek, V., and Septla, Z. Effect of size and shape of test specimens on the direct tensile strength of concrete, (1) 21*g*.
Kadokura, Toshio. See Suzuki, Hiroyoshi.
Kadono, Atsuro. Results of gunning castable refractories on inside walls of blast furnace, (11) 373*h*.
Kadota, Masatane. See Ebata, Yoshihiro.
Kadowaki, Kouichi. See Tsuji, Shigeru.
Kaduk, E. E. Zinc silicate phosphor of improved maintenance, P (4) 117*c*.
Kaether, H. U. Method and device for improving the temperature equalization of gases in tunnel furnaces and ovens, P (8) 286*f*.
Kafalas, J. A. See Longo, J. M.
Kafalas, J. A., and Longo, J. M. Effect of pressure on the structure and magnetic properties of $RbNiF_3$, (7) 265*j*.
Kagami, Yoshiki. Densification of alumina ceramics, (4) 131*a*.
Kageyama, Setsuo. Results of using castable refractories in roof of electric lead smelting furnace, (11) 374*b*.
Kahan, A. See Lipson, H. G.
Kahle, H. G., Koch, V., Plamper, J., and Urban, W. Zero-field resonance of Gd^{3+} in YVO_4 and YPO_4, (8) 301*a*.
Kahn, D. See Venables, J. D.
Kahn, M. Controlled reduction and reoxidation of $BaTiO_3$ capacitors and resulting capacitor, P (5) 182*a*.
Kahng, D. Electroluminescence of rare-earth and transition metal molecules in II-VI compounds via impact excitation, (9) 321*g*. See Berglund, C. N.; Hepplewhite, R. T.
Kahng, D., and Morton, J. A. Camera tube target including *n*-type semiconductor having higher concentration of deep donors than shadow donors, P (1) 17*i*.
Kahng, D., and Wemple, S. H. Surface-barrier diode transducer using high dielectric semiconductor material, P (8) 283*i*.
Kaifu, Yozo; Komatsu, Teruo; Hirano, Taizo; and Inoguchi, Toshio. Temperature dependence of absorption edge in ferroelectric $KNbO_3$ crystals, (1) 39*d*.
Kainarskii, I. S. See Degtyareva, E. V.
Kainarskii, I. S., Karaulov, A. G., and Gnatyuk, G. E. Dependence of rheological and technological properties of suspensions on alumina pretreatment, (4) 123*i*.
Kaiser, E. See Rady, G.
Kaiser, E. W., Muenter, J. S., and Klemperer, W. Molecular structure of B_2O_3, (5) 197*g*.
Kaiser, G., Laser, M., Merz, E., and Riedel, H. J. Behavior of ceramic oxides toward sulfur hexafluoride at high temperatures, (1) 11*i*.
Kaiser, H. D. See Delaney, R. A.
Kaiser, L. F. See Barton, F. L., Jr.
Kaiser Aluminum & Chemical Corp. Apparatus for adhesively bonding a metal plate to a refractory brick, P (8) 279*i*. Method of forming carbon-bonded silicon carbide bodies, P (8) 279*g*. Preparation of white fused alumina, P (2) 74*b*. Process for porcelain enameling and forming sheet metal, P (4) 94*b*. Process for the recovery of magnesium values from dolomite, P (2) 74*d*. Refractory composition, P (8) 280*b*. Rotary kiln linings, P (8) 286*f*.
Kaiser Gypsum Co., Inc. Process for making structural gypsum board for neutron shielding, P (10) 336*c*.
Kaita, Takao. See Miyatake, Kazumi.
Kajaiwal, G. Method of casting cylindrical grinding media and mold therefor, P (1) 20*e*.
Kajiura, Masako. See Aoyagi, Kiyoshi.
Kalabukhova, V. F. See Chkalova, V. V.
Kalashnikov, Ya. A. See Vereshchagin, L. F.
Kaldis, E. High temperature vapor phase growth of europium sulfide, selenide, and telluride, (9) 322*h*.
Kaldis, E., Krausbauer, L., and Wildmer, R. Cd_4SiS_6 and Cd_4SiSe_6, new ternary compounds —synthesis, photoconductive and fluorescent properties, (4) 109*i*.
Kali-Forschungsinstitut. Method for making alkali metal sulfate, P (5) 191*b*.
Kalish, D., and Clougherty, E. V. Densification mechanisms in high-pressure hot-pressing of HfB_2, (4) 131*b*. High pressure hot-pressing refractory materials, (6) 215*c*.
Kalish, D., Clougherty, E. V., and Kreder, K. Strength, fracture mode, and thermal stress resistance of HfB_2 and ZrB_2, (4) 156*c*.
Kaliwoda, K. Heat shrink packaging in the brick industry, (7) 250*a*.
Kalliga, G. P. See Ezerskii, M. L.
Kalmykova, L. P. See Bobrov, V. S.
Kalnin, I. L. Silicon coated graphite, P (6) 218*g*.
Kalousek, G. L. See Benton, E. J.
Kalra, A. K. Chromatographic separation of Sr from barites for mass spectrometric analysis, (9) 315*a*.
Kalvenas, S., Pozela, J., and Klimka, L. Effect of space-charge-region surface conductivity on the change of resistance of thin germanium and silicon samples in high electric fields, (5) 180*f*.
Kalvius, G. M. See Shenoy, G. K.
Kamada, Osamu. See Sakurai, Takemaro.
Kamath, G. S., and Bowman, D. Preparation and properties of epitaxial gallium phosphide, (4) 150*e*.
Kamb, B. Structural basis of the olivine-spinel stability relation, (10) 361*b*.
Kambara, Ginjiro. See Takahashi, Katsuaki.
Kamei, Hiromi. Workability of castable refractories and some problems in the method of measuring their consistency, and importance of standardizing working conditions, (5) 178*h*.
Kameras, B. M. Abrasion resistance testing apparatus, P (2) 71*h*.
Kametani, Hiroshi, and Azuma, Kiyoshi. Dissolution of calcined ferric oxides, (4) 132*b*.
Kaminow, I. P., and Turner, E. H. Electrooptic light modulators, (1) 29*e*.
Kaminskii, A. A., and Osiko, V. V. Inorganic laser materials with an ionic structure, (2) 63*b*.
Kamiya, Kanichi. See Noda, Tokiti.
Kamiya, Shigeru. See Mizuno, Hideo.
Kamiyama, Shinichi. See Katori, Kaichiro.
Kampf, L. Dimensionally stabilized concrete and mortar, P (8) 274*b*.
Kampwirth, R. See Primak, W.
Kamstrup-Larsen, H. Insulating structural sheets, P (7) 252*j*.
Kamur, A. Rapid solid solution hardening in bcc iron and LiF, (1) 35*h*.
Kana'an, A. S. See Besenbruch, G.
Kanai, Yasuo. Optical absorption and conduction due to Co^{2+} in ZnO crystals, (2) 81*d*.
Kanamaru, Fumikazu. See Matsuo, Yoshihiro.
Kaname, Yuichi; Nagata, Takashi; Ishibashi, Michio; and Tsujimoto, Hiroshi. Piezoelectric ceramic resonators, P (6) 223*d*.
Kanazawa, Takafumi, and Ikeda, Masayoshi. Confirmation of the form of phosphate ion in fused calcium magnesium silicophosphate glass, (4) 94*j*.
Kanazawa, Yasunori. See Kanda, Yozo.
Kanclir, E. Investigation of the system MgO-CaO-Cr_2O_3-SiO_2 with the high temperature microscope, (4) 141*j*. See Lach, V.
Kanda, Yozo, and Kanazawa, Yasunori. Insulated-gate field-effect transistors with piezoelectric substrates, P (11) 377*a*.
Kane, J. L., Mattern, E. E., and Funk, E. C. Fiber aligning apparatus, P (10) 338*i*.
Kaneko, H., and Isard, J. O. Effect of structural changes in the transformation range on the electrical conductivity of glass, (1) 6*c*.
Kang, C. See Tiller, W. A.
Kano, Hiroshi. See Miyatake, Kazumi.
Kantor, K. See Caillag, L.
Kanzaki, Jiro. Results of service test on material for molten-iron-tapping branch spout of blast furnace, (7) 251*i*.
Kapany, N. S. Apparatus for coupling and amplifying light between optical fibers, P (2) 52*i*.
Kaplan, S. H. Process for screening a color cathode-ray tube, P (6) 223*j*.
Kapur, P. C., and Fuerstenau, D. W. Coalescence model for granulation, (4) 117*f*.
Kar, K. R., and Singh, G. Microdetermination of Ca and Mg in a mixture, (9) 315*j*.
Karabasov, Yu. S. See Menkovskii, M. A.
Karal'nik, S. M. See Kirichok, P. P.
Karan, C. See Napier, J.
Karapetyan, G. O., and Reishakhrit, A. L. Luminescent glasses as material for optical quantum generators (lasers), (2) 50*b*.
Karasinski, F. J. See Battista, O. A.
Karaulov, A. G. See Kainarskii, I. S.
Karaulov, A. G., Grebenyuk, A. A., and Rudyak, I. N. Influence of phase composition of ZrO_2 on thermal stability, (8) 293*a*.
Karcher, E. A. Method of fabricating an integrated circuit structure including unipolar transistor and bipolar transistor portions, P (2) 65*b*. See Lin, Hung C.
Karkalits, O. C., Jr. See Woskow, M. Z.
Karlak, R. F. Method of coating articles with titanium and related metals and the article produced, P (8) 280*f*.
Karlson, K. See Demarest, P. C.
Karlsson, A. See Johansson, K.
Karo, A. M., and Hardy, J. R. Lattice dynamics and specific-heat data of CsCl, CsBr, and CsI, (5) 196*i*.
Karrer, A. S. Factors to consider in planning for pickling equipment, (1) 4*b*.
Karsulin, M. See Stepinac, M.
Kartheuser, E., Evrard, R., and Devreese, J. T. Excitations of polarons, (10) 353*j*.
Kartman, H. C. C. Apparatus and method for making a slurry, P (11) 382*h*.
Kasahara, Kiyoshi. See Seki, Shingo.
Kasahara, Komei. See Kubo, Yasushi.
Kasai, P. H. See Mueller, K. R.
Kase, M. See Akita, K.
Kashida, Koichi; Goto, Kazuhiro; and Someno, Mayumi. Measurement of oxygen pressure change in oxide powders by oxygen concentration cells, (1) 32*b*.
Kashirin, V. F. See Sobel'man, E. I.
Kashkurov, K. F., Ushakovskii, V. T., Chernyi, L. N., Kabanovich, I. V., and Kleshchev, G. V. Some peculiarities of internal structure and growth of a quartz crystal, (4) 155*i*.
Kasper, H. Coordination in zinc niobate and tantalate, (9) 318*i*. Light absorption of Ni^{2+} and Co^{2+} in 2,6-spinels, (7) 267*j*. Light absorption of semiconductive phases in the system ZnO-In_2O_3, (10) 356*h*. Spectrophotometric determination of coordination ratios in crystal lattices (III) magnesium tellurate, Mg_3TeO_6, and magnesium indium antimonate, Mg_2InSbO_6, (9) 329*f*.
Kasper, H. M. $LnCr_2TeO_6$—a new series of compounds based on the $PbSb_2O_6$ structure, (10) 356*a*. Preparation of $\{A^{2+}{}_3\}$ $[Te_2]$ $(B^{2+}{}_2)$ garnets, (2) 82*b*.
Kasper, J. S. See Moore, M. J.
Kasugai, Takahiko, and Nojima, Susumu. Negative resistance semiconductor devices, P (4) 115*a*.
Kasuya, Takahiro; Minoh, Arimichi; and Shimoda, Koichi. New laser emission from deuterium oxide vapor, (8) 295*e*.
Katagawa, Takeshi. See Kato, Norio.
Katayama, Yoshifumi, and Komatsubara, K. F. Oscillatory tunnel conductance induced by the longitudinal optic phonons in InSb-oxide-metal structure, (4) 148*a*.
Kato, Akira. See Uetani, Keiji.
Kato, Chuzo, and Doi, Akira. Dehydration of clay minerals under N_2 reduced pressure by differential thermal analysis, (7) 264*j*.
Kato, Chuzo, and Tsunashima, Yutaka. Differential thermal analysis of adsorbed water of porous glass and silica gel at room temperature to −90°C, (4) 95*i*.
Kato, Etsuro, and Hasegawa, Masaru. Electrical resistivity of sintered composite carbon black-kaolin materials (IX) effects of firing time, firing atmosphere, and forming process on resistivity; (X) effects of carbon materials on temperature dependence of resistivity; (XI) resistivity-temperature dependence of compositions containing excess silica, (4) 134*g*, (5) 181*b*.
Kato, Iwao. See Adachi, Gin-ya.
Kato, Ken, and Ogata, Masahiko. Inquiries into causes of breakdowns in top part of stopper head used at high temperature for long periods, (2) 56*i*.
Kato, Makoto. See Minowa, Susumu.
Kato, Masanori. See Kubo, Teruichiro.
Kato, Masanori; Taniguchi, Masao; and Kubo, Teruichiro. Thermal decomposition of ammonium metavanadate, (8) 300*d*.
Kato, Norio. See Patel, J. R.
Kato, Norio; Usami, Katsuhisa; and Katagawa, Takeshi. X-ray diffraction image of a stacking fault, B (1) 40*h*.
Kato, Shuzo. See Ishii, Eiichi.
Kato, Shuzo; Iga, Takeo; Ishii, Eiichi; and Sano, Shiro. Effect of metal oxides on surface grain growth of alumina, (1) 28*a*.
Kato, Takeshi. Application of composite nozzle brick to LD converter taphole, (7) 250*d*.
Kato, Yogoro. See Yamazaki, Syunpei.
Katona, I. Body and glaze experiments in the Herend China Factory in 1840–42, (8) 273*h*.
Katori, Kaichiro, and Kamiyama, Shinichi. Method of manufacture of glass-sealed semiconductor device, P (8) 283*c*.
Katrekar, S. A. See Das, C. R.
Kats, E. I. Anomalous properties of V_3Si-type superconducting compounds, (2) 74*i*.
Katsaros, N. See George, J. W.
Katsura, Takashi. See Kitayama, Kenzo.
Katsura, Takashi; Iwasaki, Bunji; Kimura, Shigeyuki; and Akimoto, Syun-iti. High pressure synthesis of the stoichiometric compound FeO, (4) 138*a*.
Katsurai, T. See Yamaguchi, S.
Katto, Shigeru. See Horibe, Toshiyasu.
Katyshev, Yu. I. See Kichkina, E. S.
Katz, S. See Schock, R. N.
Katzschmann, R. Crystalline inclusions in glasses (I, II), (4) 95*c*.
Kauer, E. Incandescent lamp with filament consisting of a hexaboride of a rare earth metal, P (1) 18*i*.
Kauffmann, Y. See Kingery, W. D.
Kaufman, I. See Oltman, H. G., Jr.
Kaufman, L. P. See Clougherty, E. V.
Kaufman, L. P., and Clougherty, E. V. Oxidation resistant refractory compounds, P (4) 107*i*.
Kaufman, M., Muenter, J., and Klemperer, W. Geometry of some refractory metal dioxides, (4) 137*f*.
Kawabe, Kazuo. See Yoshino, Katsumi.
Kawado, Seiji; Maruyama, Toshiyuki; and Ishii, Zensho. X-ray observation of magnetic domains in Mn ferrite, (2) 84*h*.
Kawai, Naoto. Sintering under ultrahigh pressure, (4) 154*j*. See Sawaoka, Akira.
Kawai, T. See Hashino, T.
Kawaji, Akira. Optical semiconductor device, P (10) 345*d*.
Kawaji, Shinji. See Koizumi, Haruhiko.
Kawakita, Kikuji. See Nakamichi, Hiroshi.
Kawakubo, Tatsuyuki. See Kabashima, Shigeharu.
Kawamura, J. See Lipson, H. G.
Kawamura, Junichi. See Tada, Takaharu.
Kawamura, Sukizo; Nishimura, Teruo; Ito, Akio; Asano, Kiyoshi; Mizuta, Hiroshi; and Kumazawa, Seiichi. Cracking in pottery glazes (II) cracking during decoration firing of dolomite earthenware glazes, (5) 179*j*.
Kawanami, Shunpei. Dust collector, P (6) 225*a*.
Kawarada, Kuniyasu. See Kumagai, Yasuji.
Kawasaki, Junko. See Shimada, Kinji.
Kawasaki, Yasuhiro. See Nii, Riro.
Kawashima, Hirokuni. See Haradome, Miyoshi.
Kawasumi, Makoto. See Seki, Shingo.

Kawecki, R. E. Continuous operation [gravity fed] mulling apparatus and method for accurately proportioning foundry sand ingredients, P (6) 217*i*.
Kawecki Chemical Co. High temperature oxidation resistant articles, P (6) 208*b*. Process for producing high purity niobium oxide, P (2) 74*d*. Purification of niobium and tantalum pentoxides, P (7) 263*c*.
Kay, E. See Sawatzky, E.
Kay, E., and Sawatzky, E. Method of fabricating uniform rare earth iron garnet thin films by sputtering, P (7) 257*c*.
Kay, H. F. See Reed, J. S.
Kayalova, S. S. See Appen, A. A.
Kayatz, K. H. Cooler comprising sloping grate sections, P (4) 118*c*.
Kaye, M. J., Dunham, A. C., and Hirst, D. M. Comparison of two methods of quantitative mineralogical analysis of sedimentary rocks, (1) 20*j*.
Kaye, S. See Garasi, L.
Kazantseva, N. M. See Telyatnikov, G. V.
Kazimir, J. Content of dihydrate in argillaceous gypsum and strength of hardened hemihydrate plaster, (7) 244*i*.
Kaznoff, A. I. See Marlowe, M. O.
Kear, B. H., Silverstone, C. E., and Pratt, P. L. Latent hardening, work hardening, and plastic deformation of NaCl single crystals, (2) 79*c*.
Kearn, L. J. Glass fiber cloth [heat treatment], P (10) 339*d*.
Keasler, B. M. Process for treating glass fabric, P (5) 176*e*.
Keating, P. N. Theory of the third-order elastic constants of diamond-like crystals, (4) 160*h*.
Keattch, C. J. Analysis of gypsum plasters and minerals by thermogravimetry, (8) 284*h*.
Kedem, D., and Rothem, T. Internal fields in nickel ferrite, (4) 140*f*.
Keefer, G. E. Gas fired frit melter, P (11) 371*g*. Method and apparatus for producing hollow glass articles by module immersion technique, P (10) 339*i*.
Keefer, G. E., and Pei, Yu K. Molten addition of colorant in a glass furnace forehearth, P (8) 278*d*.
Keeler, R. N. See Hawke, R. S.
Keen, I. M., King, W. J., and Walls, R. Hydrothermal synthesis of sodium mordenite in pebble form, (8) 293*g*.
Keenan, A. G., Notz, K., and Wilcox, F. L. Pyrex membrane potential in binary nitrate melts, (5) 199*g*.
Keene, B. J. See Champion, J. A.
Keenum, J. C., Jr., and Angstadt, R. L. Cement set retarding composition, P (6) 207*c*.
Keep Chemical Co. Gypsum wallboard and process of making the same, P (4) 92*h*.
Keepin, G. R. Detection, identification, and analysis of fissionable isotopes, P (10) 347*i*.
Keesom, P. H. See Van der Hoeven, B. J. C., Jr.
Keezer, R. C., Bowman, D. L., and Becker, J. H. Electrical and optical properties of lead oxide single crystals, (1) 28*b*.
Kegg, R. R. See Doering, W. E.
Keig, G. A. Influence of the valence state of added impurity ions on the observed color in doped aluminum oxide single crystals, (9) 323*g*.
Keitel, G. A. See Houston, H. H.
Keith, C. D. Method of preparing a supported catalyst, P (7) 263*a*.
Keith, C. D., and Cornely, K. W. Alumina production, P (6) 229*a*.
Keith, C. D., and Mooney, J. J. Catalytic radiant heater, P (7) 261*g*.
Keichner, J. R. See Verrando, M. G.
Kelen, T. See Franz, H.
Keler, E. K. See Andreeva, A. B.; Andreeva, G. T.; Kuznetsov, A. K.
Kelkar, G. N. See Bhide, G. K.
Kellam, B. See Clendenning, T. G.
Kellar, A. A. See Howard, R. A.
Kellar, A. A., and Carter, M. B. High temperature cement, P (6) 217*a*.
Kelleher, J. J. Lasers and E. B. [electron beam] welders open new design vistas, (11) 379*f*.
Keller, E. K. See Davtyan, I. A.
Keller, F. J., and Murray, R. B. Thermal motion of holes in potassium iodide, (4) 160*g*.
Keller, L. D. See Wallace, G. C.
Keller, W. Method and apparatus for increasing the cross section of a crystalline rod during crucible-free zone melting, P (4) 114*g*. See Raithel, K.
Keller, W., and Berger, G. Apparatus for crucible-free floating zone melting of crystalline rods, P (10) 344*a*.
Keller, W., and Schmidt, O. Device for inductively heating semiconductor material, P (7) 256*a*.
Keller, W. D. See Reesman, A. L.
Keller Ofenbau G.m.b.H. Methods of continuously firing ceramic charge material in tunnel kilns, and tunnel kilns for carrying out these methods, P (11) 381*j*.
Kellerer, H., and Piatti, G. Crack formation in sintered two-phase alloys, (8) 289*g*. Influence of microporosity on the ductility of Al/Al_2O_3 alloys, (9) 323*f*. Time and temperature dependence of the hardness of dispersion strengthened aluminum alloys, (9) 332*b*.
Kellett, E. A. See Richards, B. P.
Kelley, J. E., Sumner, D. H., and Kelly, H. J. Joining refractory metal compounds by hot-pressing, (6) 215*j*.
Kelley, L. W. See Provance, J. D.
Kellner, T. Growth through design, (4) 90*i*.
Kelly, A. See Gillin, L. M.
Kelly, B. T. Thermal vibration amplitudes of carbon atoms in the graphite lattice parallel to the *c* axis, (4) 161*c*.
Kelly, E. J. Method and apparatus for blending pulverulent materials, P (2) 38*b*.
Kelly, H. J. See Kelley, J. E.
Kelly, R. See Jech, C.
Kelly, R., and Jech, C. Inert-gas diffusion as a probe for lattice defects in ionic crystals, (8) 293*j*.
Kelly, R., and Padley, P. J. Shape of chromium oxide particles in hydrogen-oxygen-nitrogen premixed and diffusion flames, (6) 237*d*.
Kelly, T. M., Mielenz, R. C., and Peppler, R. B. Hydraulic cement mix containing saccharide polymers, P (6) 207*d*.
Kelly, T. M., Peppler, R. B., and Ray, J. A. Hydraulic cement mix and additive, P (6) 207*d*.
Kelly, W. R. See Hartford, W. H.
Kelly, W. T., Hornberger, L. B., and Strief, M. J. Cermet resistors, their composition and method of manufacture, P (4) 112*h*.
Kelsey, P. S. Method for stabilizing brick cubes and brick cubes stabilized thereby, P (1) 11*h*.
Kelsey, R. H. See Krock, R. H.
Kelsey, R. H., and Krock, R. H. Tension testing alumina whiskers, (5) 188*h*.
Kelsey, R. W. See Crooks, D. D.
Kelsey, R. W., Crooks, D. D., and Sumsion, H. T. Alloys for improving properties of graphite, P (7) 252*b*.
Kemmler-Sack, S. Magnetic and spectroscopic properties of uranium oxide fluorides and their structural relation to uranium oxides, (10) 356*i*.
Kemp, J. C., Ziniker, W. M., and Glaze, J. A. Faraday rotation studies in MgO and CaO color centers, (8) 292*g*.
Kempe, D. R. C. Topaz-sillimanite and kyanite bearing rocks from Tanzania, (1) 23*e*.
Kempeners, L. Method of dividing a body comprising a number of electric circuit elements into parts, P (4) 114*b*.
Kempers, H. See Biegler, H.
Kempter, C. P. See Clinard, F. W., Jr.
Kenat, J. See Glasner, A.
Kendall, V. D. See Emmel, D. R.
Keneshea, F. J., and Cubicciotti, D. Thermodynamics of vaporization of thallous fluoride and its gaseous dimerization, (2) 84*i*.
Kennard, O., Speakman, J. C., and Donnay, J. D. H. Primary crystallographic data, (7) 268*f*.
Kennecott Copper Corp. Process of producing high purity alumina from aluminum-bearing acidic sulfate solutions, P (7) 263*a*. Zinc tellurite glasses, P (5) 176*d*.
Kennedy, D. I. See Russ, M. J.
Kennedy, G. C. Electrically conductive tool and method for making, P (6) 221*h*. See Yamamoto, H.
Kennedy, S. O. See Klein, M. V.
Kennet, J. G. See Fontyn, L. A.
Kenney, J. T., and Powell, F. X. Raman spectra of fused indium and bismuth chlorides, (9) 328*b*.
Kent, G. A. Recovery of high purity magnesium oxide and calcium oxide from magnesite and calcite ores, P (4) 125*h*.
Kentucky Electronics, Inc. Color gun beading apparatus, P (6) 212*i*.
Kenward, J. R. See Andrews, R. W. J.
Kenworthy, H. See Hill, T. E., Jr.
Kenwright, R. See O'Hara, C.
Keown, R. Energy bands in diamond, (4) 135*h*. See Wiff, D. R.
Kerbe, F. See Budnikov, P. P.
Kerenyi, I. See Vacz, I.
Kern, E. L. Coating with silicon carbide by immersion reaction, P (10) 342*c*. See Robbins, W. B.
Kern, E. L., and Jerome, G. A. Coating of objects with tetraboron silicide, P (10) 344*d*.
Kern, H. See Raase, P.
Kern, H. C. Rotary crusher feeding aid, P (8) 288*d*.
Kern, R. See Masson, A.
Kern, R. S. See Beals, R. J.
Kern, W. Apparatus for chemical vapor deposition of oxide and glass films, (8) 280*j*. Technique for measuring etch rates of dielectric films, (8) 281*i*.
Kernforschungsanlage Julich Gesellschaft mit beschrankter Haftung Nordrhein-Westfalen-e.V. Fuel or fertile element for nuclear reactions, P (4) 106*h*.
Kernforschungsanlage Julich des Landes Nordrhein-Westfalen-e.V. Method of and apparatus for the treatment of graphite-coated particles for nuclear reactors and the like, P (10) 342*j*. Method of treating coated-particle nuclear-reactor fuels, P (2) 59*g*.
Kerr, B. M. Passivation of semiconductor devices, P (10) 345*e*.
Kerr, D. R. See Doo, V. Y.
Kerr, G. T. Chemistry of crystalline aluminosilicates (IV) factors affecting the formation of zeolites X and B, (5) 192*g*.
Kerr, G. T., Dempsey, E., and Mikovsky, R. J. Number of hydroxyl groups at the exterior surfaces of faujasite crystals, (2) 81*b*.
Kerr, J. M., Carlson, R. V., and Shield, W. A. Alpha autoradiography of $(U,Pu)O_2$ microspheres, (10) 347*b*.
Kerry, H. A., and Mirliss, M. J. Process for preparing improved titanium dioxide pigment compositions, P (9) 317*c*.
Kershaw, D. D. Method of making a molybdenum-tungsten thimble seal, P (6) 222*i*. See Campbell, J. H.
Kershaw, R., Vlasse, M., and Wold, A. Preparation and electrical properties of niobium selenide and tungsten selenide, (11) 376*d*.
Kershaw, S. S., Jr. Combined overvoltage protective device and conductor support, P (9) 312*d*.
Kerslake, W. R. Electronic cathode having a brushlike structure and a relatively thick oxide emissive coating, P (4) 112*i*.
Kerstan, W. Relation between particle size and firing temperature of an enamel color, (11) 368*h*.
Kerstetter, D. R. Process for sealing connectors in a planar structure, P (8) 278*b*.
Kersting, R. See Hennicke, H. W.
Kesel, G. Tunnel diodes wherein the height of the reduced cross section of the mesa is minimized and process of making, P (2) 67*b*.
Kesler, C. E. See Lott, J. L.
Kessler, D., Anderson, H. L., Dixit, M. S., Evans, H. J., McKee, R. J., Hargrove, C. K., Barton, R. D., Hincks, E. P., and McAndrew, J. D. μ-atomic Lyman and Balmer series in Ti, TiO_2, and Mn, (4) 145*e*.
Kessler, F. See Johnson, H. B.
Kessler, W., and Gebhardt, F. Determination of minor constituents in limestone and dolomite by quantitative emission spectroscopy using a high-frequency plasma jet, (9) 315*b*.
Kesten, P. N. See Blum, J. F.
Kesten, P. N., and Schwartzwalder, K. Ceramic foam, P (9) 307*a*.
Kestigian, M. See Croft, W. J.
Kestigian, M., and Holloway, W. W., Jr. Incorporation of increased concentrations of rare-earth activator ions in optical quality single crystals of yttrium aluminum garnet, (10) 355*a*.
Ketcham, W. M., and Hobbs, P. V. Preferred orientation in the growth of ice from the melt, (5) 198*g*. Step growth on ice during the freezing of pure water, (5) 200*h*.
Keto, A. I. See Hofmann, C. F.
Ketterson, J. B., Tait, J. S., and Windmiller, L. R. Conversion of an electron beam zone refiner to rf heating, (4) 119*i*.
Kettner, I. Low-fire metallic glazes, (10) 335*j*.
Keune, D. L., Rossi, J. A., Gaddy, O. L., Merkelo, H., and Holonyak, N., Jr. Time behavior of exciton formation and laser emission in Cd(SeS) platelets, (9) 311*f*.
Kevan, L., and Chen, D. H. Spatial distribution of trapped electrons in gamma-irradiated organic glasses, (8) 298*d*.
Kevane, C. J. See Warmkessel, B. M.
Keve, E. T., and Skapski, A. C. Structure corresponding to the ideal composition $3Bi_2O_3{\cdot}17Nb_2O_5$, (8) 298*d*.
Kevern, J. Ceramic coatings help analyze overall stress, (6) 225*h*.
Kewanee Oil Co. Colored titanium pigment materials having a spinel structure and method of preparing same, P (5) 190*h*. Process of attaching a collector grid to a [CdS] photovoltaic cell, P (8) 283*j*. Process for coating [glass] with epoxy compositions, P (4) 100*h*. Sodium activated cesium iodide scintillator, P (8) 283*g*.
Keyes, R. W., and Weiser, K. Semiconductor negative resistance electroluminescent diode, P (7) 258*e*.
Keys, J. D., Horwood, J. L., Baleshta, T. M., Cabri, L. J., and Harris, D. C. Iron-iron interaction in iron-containing zinc sulfide, (1) 31*b*.
Keys, L. K. Ti_3O_5 effective mass, (2) 84*a*.
Keys, L. K., and Mulay, L. N. Magnetism of the titanium-oxygen system, (8) 294*a*.
Kezdi, A. Distribution of grains and voids according to their volume, (5) 190*c*. Theory of plasticity of granular substances, (5) 201*c*.
Kezdi, A., and Nagyvati, B. Strength of stabilized soils, (5) 190*c*.
Khadzhi, V. E. See Chernov, A. A.
Khaenko, B. V. See Arbuzov, M. P.
Khagleeva, L. P. See Fedorov, P. I.
Khalafalla, S. E. See Haas, L. A.
Khalilev, V. D. Influence of gas atmosphere in melting fluoroberyllate glasses on their light transmission in the ultraviolet region of the spectrum, (1) 7*h*.
Khalyapina, O. B. See Ni, L. P.
Khan, A. See Wiedemeier, H.
Khan, A. H. See Qaiser, M. A.
Khandelwal, S. See Bohor, B. F.
Khangenkar, P. R. See Kulkarni, S. D.
Khanis, Yu. B. See Moshkov, A. D.
Kharchenko, N. F., Eremenko, V. V., and Belyi, L. I. Faraday effect and reversal of magnetic sublattices of lanthanide ferrite garnets, (2) 77*c*.
Kharitonov, F. Ya. See Budnikov, P. P.
Kharitonov, N. P. See Krivov, V. A.; Krivtsov, V. A.; Krotikov, V. A.
Kharitonov, N. P., and Krotikov, V. A. Transformations occurring in organosilicate materials at temperatures up to 700°C, B (5) 204*j*.
Kharitonov, Ya. G. See Moroz, I. I.

Khazanov, E. I., Stakheeva, S. A., and Kuz'mina, G. V. Reaction of sodium aluminate with dicalcium silicate, (1) *3a*.

Khinich, I. Y. See Maslennikov, V. A.

Khitarov, N. I. See Leonidov, V. Ya.

Khodakovskaya, R. Ya. See Pavlushkin, N. M.

Khodorov, E. I. See Telyatnikov, G. V.

Khomeriki, G. P. Electromagnetic ball mill, P (1) *20d*.

Khomyakov, K. G. See Korzhukov, N. G.

Khopkar, S. M. See Shinde, V. M.

Khosla, R. P. See Trautweiler, F.

Khrestin, V. A. See Vatman, A. P.

Khripunova, T. P. See Shirkevich, T. L.

Khudolei, V. I. See Oblival'nyi, F. A.

Khvostenkov, S. I. Determination of the hardening kinetics of binders, (2) *44e*.

Kichkina, E. S., Abramson, I. G., Bednyakov, F. I., Katyshev, Yu. I., Klimov, V. V., and Chebotarev, V. L. Use of tagged atoms to study movement of material and dust formation in rotary furnaces, (1) *3f*.

Kidder, J. E. Jomon Pottery, B (7) *271j*.

Kido, Tsuyoshi. See Suzuki, Kazutaka.

Kieffer, R. See Jangg, G.

Kiehl, J. P. High alumina refractories, (1) *8d*. Prefiring of refractory materials, P (5) *179a*.

Kiel, A., and Crane, G. R. Microwave-optical double resonance using circularly polarized light—spectrum of Yb^{3+} in $CaWO_4$, (5) *197d*.

Kiel, G. See Behrends, K.

Kienow, S. Torsional strength of basic bricks, (4) *105g*.

Kierkegaard, P. See Nyberg, B.

Kierzek-Pecold, E. See Niemyski, T.

Kihlborg, L. See Arend, H.

Kikuchi, C. See Mahootian, N.

Kikuchi, M. See Kushida, T.

Kilby, J. S Capacitor for miniature electronic circuits or the like, P (6) *220i*. Transistor with an isolated region having a *pn* junction extending from the isolation wall to a surface, P (4) *117a*. See Biard, J. R.

Killmeyer, C. W., and Eilerman, G. E. Novel reaction product and use thereof as a glass fiber size, P (11) *372b*.

Kim, C., and Armstrong, L. D. High-power and high-efficiency GaAs avalanche diodes, (10) *344e*.

Kim, K. H. Method of making electrical resistor by recrystallization, P (8) *283a*.

Kim, S. C., and McCarty, L. V. Calculation of the diffusion of water into fused quartz lamps, (7) *246j*.

Kim, Y. M., and Bray, P. J. Electron spin resonance studies of gamma-irradiated glasses containing lead, (4) *95h*.

Kim, Y. M., Reardon, D. E., and Bray, P. J. ESR studies of radiation-induced niobium centers in Nb_2O_5-Na_2O-SiO_2 glasses, (2) *48i*.

Kimball, L. W. See Menelly, R. A.

Kimberlin, C. N., Jr. Dehydration magnesium chloride roasting and solvent, P (1) *23h*.

Kimmel, R. M., and Uhlmann, D. R. Energy spectrum of densified silica glass, (7) *247j*.

Kimmel, S. See Gebhardt, F.

Kimura, H. See Pastor, R. C.

Kimura, Morihiro. Sillimanite ore deposit in Argentina and properties of the ore, (7) *262a*.

Kimura, Shigeyuki. See Katsura, Takashi.

King, B. W., Jr. See Chaille, C. E.; Sullivan, T. A.

King, H. A. Lightweight armor with laminated base member resistant to delamination, P (8) *280f*. Lightweight protective armor plate, P (7) *252a*.

King, H. G. C., and Pruden, G. Colorimetric determination of calcium in silicate minerals, (7) *259j*. Purification of commercial Alizarin Red S for the determination of aluminum in silicate materials, (4) *120i*.

King, J. F., Jr., and Davis, W. R. Apparatus and method for removing concentration of particles in liquids, P (10) *349a*.

King, R. D. See Henderson, B.; Miles, G. D.

King, R. D., and Henderson, B. Optical absorption studies of color centers in heavily irradiated magnesium oxide, (8) *295g*.

King, S. V. Analysis of X-ray and neutron diffracted intensities calculated for a random network of vitreous silica, (4) *126d*. Ring configurations in a random network model of vitreous silica, (4) *153g*.

King, T. B. See Ghosh, A.; Gupta, Y. P.

King, W. J. See Keen, I. M.

King Laboratories, Inc. Quick flash high yield getter with means to restrain warping and breaking of the getter material, P (10) *345i*.

Kingery, W. D. Effect of low temperature neutron irradiation and 20°–400°C annealing on the density and lattice parameters of aluminum oxide and magnesium oxide, (4) *133a*. See Campbell, W. B.

Kingery, W. D., Kauffmann, Y., Bruet, M., and de Sigoyer, Bruno de B. Density measurements on samples of uranium dioxide and uranium carbide irradiated at low temperatures, (8) *290a*.

Kingsley, J. D., and Prener, J. S. Coherent light source utilizing pentavalent manganese activated calcium chlorophosphate crystal, P (6) *221b*.

Kingston, P. W. Studies of mineral sulfosalts (XII) nuffieldite, a new species, (1) *38a*.

Kini, K. A., Manser, R. M., and Joy, A. S. Surface area of silicate minerals by the BET method using the adsorption of xenon at −78°, (5) *200e*.

Kinkade, W. A., and McCleary, R. E. Calcined gypsum and a method for its preparation, P (4) *92e*.

Kinoshita, Akira, and Nakano, Tomoyasu. Cu_2O crystal growth by hydrothermal technique, (9) *319a*.

Kinoshita, Makoto. See Ebata, Yoshihiro; Kose, Saburo.

Kinoshita, Makoto, and Hamano, Yoshiteru. Synthesis of titanium diboride by carbon reduction, (1) *39c*.

Kinoshita, Makoto; Kose, Saburo; and Hamano, Yoshiteru. Creep of sintered zirconium diboride at high temperatures, (5) *176j*.

Kinsman, D. J. J., and Holland, H. D. Coprecipitation of cations with $CaCO_3$ (IV) coprecipitation of Sr^{2+} with aragonite between 16° and 96°C, (6) *231f*.

Kinter, E. B. See Diamond, S.

Kintner, P. L. See Whittaker, A. G.

Kinuta, Tsunekazu, and Toda, Masumi. Refractory lining of soaking pit furnace by prefabrication method, (7) *251f*.

Kirakosyan, T. M. See Manvelyan, M. G.

Kirchner, H. P. Thermal expansion anisotropy of oxides and oxide solid solutions, (9) *332c*.

Kireev, P. S. See Ryabov, V. A.

Kirichok, P. P., and Karal'nik, S. M. X-ray spectroscopy of spinel-type ferrites and garnets of different compositions and in different states, (4) *164f*.

Kirk, D. L., and Pratt, P. L. Ionic conductivity in pure and manganese-doped crystals of sodium chloride, (8) *293j*.

Kirk, J. L. See Schmidt, E. D. D.

Kirkman, W. Apparatus for bending glass sheets, P (5) *174f*. Apparatus for press bending glass sheets, P (4) *98e*.

Kirkorian, O. H., and Carpenter, J. H. Enthalpies of formation of gaseous tantalum oxide and tantalum dioxide, (2) *76h*.

Kirn, J. F., and Leidheiser, H., Jr. Progress in efforts to grow large single crystals of hydroxyapatite, (7) *268g*.

Kirsch, A. A., and Fuchs, N. A. Fluid flow in a system of parallel cylinders perpendicular to the flow direction at small Reynolds numbers, (1) *29i*.

Kirsch, H. (transl. by Jones, K. A.). Applied Mineralogy for Engineers, Technologists, and Students, B (8) *301c*.

Kirstein, T. B. A. See Asher, R. C.

Kischlo, W. Boron phosphide, (6) *230i*.

Kiselev, A. V. See Aristov, B. G.; Berezin, G. I.; Davydov, V. Ya.

Kiser, R. W. See Dillard, J. G.

Kishida, Masao. Improvement of teeming practice by changing shape of stopper head for large capacity open-hearth furnace, (2) *56i*. Pouring sleeve brick for LD converter, (11) *373c*. Results of service test on runner brick placed in eight radial mold gutters, (11) *373j*. Results of using unfired Mg-Cr brick of high-purity magnesia clinker in furnace roof, (11) *374c*.

Kishii, Toru. See Ooka, Kazuo.

Kishii, Toru, and Ooka, Kazuo. ESR spectra of a sodium borate glass irradiated by ultraviolet light, (1) *7b*. Stress in glass caused by ultraviolet radiation (VIII) kinetics of stress buildup in glasses by ultraviolet radiation, (6) *211i*.

Kishk, F. M. See Barshad, I.

Kishk, F. M., and Barshad, I. Morphology of vermiculite clay particles as affected by their genesis, (11) *386f*.

Kisinko, P. M., and Ernick, F. G. Constant gain power transistor, P (11) *376b*.

Kistiuk, P. See Wood, D. L.

Kislyi, P. S., and Kuzenkova, M. A. Regularities of sintering of zirconium diboride-molybdenum alloys, (2) *57j*.

Kiss, A. B. See Hegedus, A. J.

Kiss, L. Raw batches for pottery bodies from ready-mixed Tokaj-Hegyalja materials, (2) *65c*.

Kiss, Z. J. Luminescent materials and apparatus for generating coherent radiation, P (8) *282c*. Method of preparing luminescent materials, P (7) *257a*. See Staebler, D. L.

Kister, E. G. See Lerner, R. S.

Kistler, S. S., and Rue, C. V. Prestressed grinding wheel, P (6) *205g*.

Kita, Hideo, and Ito, Kunihiko. Apparatus for the manufacture of sheet glass utilizing gas-permeable vertical dampers, P (8) *277f*.

Kitagawa, Hiroshi; Inoue, Toshio; Kurokawa, Susumu; and Horigome, Shinkichi. Magnetic materials having rectangular hysteresis loops, P (7) *256h*.

Kitaj, W., and Levene, L. Method of rendering glass surfaces abrasion-resistant and glass articles produced thereby, P (2) *53h*.

Kitaoka, Takeshi. See Ebata, Yoshihiro.

Kitayama, Kenzo, and Katsura, Takashi. Composition of fayalite and its standard free energy of formation, (4) *129j*.

Kitely, K. Tunnel kiln maintenance, (10) *348e*.

Kitschen, L. See Hildenbrand, H.

Kitts, E. L., Jr. See Sihvonen, Y. T.

Kivel, J. See Olsen, D. A.

Kiyama, Masao. See Yasuoka, Hiroshi.

Kizel, V. A. See Denisov, Yu. V.

Kizer, D. E., and Lozier, D. E. Method of preparing spherical uranium nitride particles having a porous interior, P (4) *106j*.

Kjekshus, A. See Bjerkelund, E.; Fermor, J. H.; Holseth, H.

Kjellberg Elektroden & Maschinen G.m.b.H. Plasma burner, P (11) *369b*.

Klasens, H. A. Method of manufacturing semiconductor devices [printed circuits] and semiconductor devices manufactured by such methods, P (8) *283e*.

Klaudinyi, B. See Jacobs, L. J.

Klebanov, D. L. See Perelman, S. M.

Klein, A. Ceramic artists and their work—Wolfgang Henze, (7) *244c*. Ceramic centers in Italy (I) early periods, (1) *2a*; (II) beginnings of Italian majolica and the most important stages of its development, (4) *90e*. Ceramics of the eastern Mediterranean (I-IV), (5) *169i*. Thoughts on glaze designing, especially flow and crystal glazes, (7) *254c*.

Klein, C., Jr. Coexisting amphiboles, (1) *26f*.

Klein, C., Jr., and Waldbaum, D. R. X-ray crystallographic properties of the cummingtonite-grunerite series, (4) *164c*.

Klein, C. A., and Rudko, R. I. CO_2 laser radiation absorption in semi-insulating gallium arsenide, (9) *318b*.

Klein, D. L., and Lawley, K. L. Silicon oxide tunnel diode structure and method of making same, P (5) *185j*.

Klein, G. P. Method for making porous electrodes comprising freezing wet powder and sintering, P (5) *183h*. Powder on foil solid tantalum capacitor, P (11) *378f*.

Klein, H. "Tornado-Flow" dust extractor—operation and application, (4) *118d*.

Klein, J., and Mansard, B. Device for polishing specimens, P (7) *260h*.

Klein, M. V., Kennedy, S. O., Gie, T. I., and Wedding, B. Hydroxyl ion in alkali halide crystals—crystal growth and characterization, (2) *78d*.

Klein, O. C., and Mason, G. E. Zinc oxide, P (6) *230e*.

Klein, T. Integrated circuits using heavily doped surface region to prevent channels and methods for making, P (10) *345c*. Process of making a [epitaxial] transistor with an inverted structure, P (7) *257h*.

Kleinerman, M. Y. Fluorescent lanthanide chelates of dibenzylamine, P (5) *183c*.

Kleinert, P. See Novak, J.

Kleinknecht, H. P. Beam-of-light transistor utilizing *pn* junctions which are nonabrupt and nontunneling with a base region of degenerate material, P (5) *182f*.

Kleintsich, R., and Jaissle, A. Sealing of glass to other materials by a solderable metal layer, (1) *17b*.

Kleist, D. Method and apparatus for producing fibers, P (4) *99h*.

Klement, W., Jr. Thermodynamics of the λ transition in sodium nitrate, (5) *202c*.

Klemperer, W. See Kaiser, E. W.; Kaufman, M.

Kleppa, O. J. Application of high-temperature solution calorimetry to oxide systems, (5) *192e*. See Anderson, P. A. M.; Hlabse, T.; Holm, J. L.; Meschel, S. V.; Navrotsky, A.

Kleppa, O. J., and Meschel, S. V. Heats of formation of solid solutions in the system (Na-Ag)Cl and (Na-Ag)Br, (1) *30d*.

Kleshchev, G. V. See Kashkurov, K. F.

Kleshchev, G. V., Kabanovich, I. V., and Chernyi, L. N. Nature of optical non-homogeneity of quartz, (5) *197j*.

Klevtsov, P. V. See Mill, B. V.

Klieger, P., and Isberner, A. W. Laboratory studies of blended cements—portland blast-furnace slag cements, (1) *3b*.

Klimka, L. See Kalvenas, S.

Klimov, V. V. See Kichkina, E. S.

Kline, D., Bray, P. J., and Kriz, H. M. Structure of crystalline boron oxide, (6) *238b*.

Kling, A. J. Heated cathode and method of manufacture, P (1) *18g*.

Kling, H. G. See Harkort, D.

Klingler, E. See Dawihl, W.

Kliya, M. O. Motion of dislocations in corundum crystals grown by the verneuil method, (10) *357d*.

Klockner-Humboldt-Deutz Akt.-Ges. Apparatus for classifying particulate material, P (8) *284d*. Device for cleaning the electrodes in an electrostatic dust separator, P (6) *225a*.

Klock, R. L. See Eilerman, G. E.

Klosak, E. J. Method of preparing concentrated silica sols, P (11) *382d*.

Kment, V. See Kvapil, J.

Kmieciak, H. A. See Gadd, J. D.

Knacke, O. See Gans, W.

Knacke, O., Laser, M., and Riedel, H. J. Method of treating coated-particle nuclear-reactor fuels, P (2) *59g*.

Knapp, O. Comparison of equations with two and three constants for calculating viscosity-temperature data for silicate glass, (5) *172h*. Emptying and removing the contents of a glassmelting tank at the end of a campaign, (6) *209g*. Reply to "Calculation of the viscosity-temperature curve of glass from fixed points," (4) *94h*. Semiconductive glasses, (2) *51b*.

Knapp, W. E. See Bolkcom, W. T.

Knapsack Akt.-Ges. Apparatus for monitoring the temperature prevailing in a grate of the type used for drying and calcining shapes, P (1) *22a*.

Knappwost, A., and Metz, W. Spontaneously magnetized monoatomic iron layers in graphite, (9) *329h*.

Knausenberger, W. H., Vedam, K., White, E. W., and Zeigler, W. Thin film characterization by electron microprobe and ellipsometry—SiO_2 films on silicon, (9) 311*f*.

Knauss, D. L. Irradiated temperature compensated Zener diode device, P (1) 18*i*.

Kneschke, G., and Schrader, R. Behavior of the fine structure of polycrystalline magnesia during sintering, (7) 263*f*.

Knigin, G. E. See Bondarev, K. T.

Knochel, W. J., and Fraser, H. D. Ceramic discharge lamp, P (11) 376*i*.

Knochel, W. J., and Fraser, H. D. Ceramic means for refractory ceramic discharge device envelopes [Al_2O_3], P (9) 313*g*.

Knochel, W. J., Lin, F. C. M., and Fraser, H. D. Ceramic arc tube and closure member construction, P (5) 182*i*.

Knoedler, D., and Jezussek, A. Seal for enclosures subjected to high pressures and temperatures, P (11) 379*g*.

Knoops, E. Belgian industry of mirror making, (9) 305*b*.

Knop, O. See Brisse, F.

Knorre, H., and Kuhner, G. Production of boron nitride, P (4) 107*d*.

Knorring, O. V. See Sahama, T. G.

Knotik, K. See Bildstein, H.

Knotik, K., Leichter, P., and Wagner, H. Process for disintegrating graphite bodies, P (10) 343*a*.

Knowles, C. R. See Chinnor, G. A.

Knox, B. E. Mass spectrometric studies of laser-induced vaporization (I) selenium, (5) 196*f*.

Knox, B. E., Ban, V. S., and Schottmiller, J. Mass spectrometric studies of laser-induced vaporization (II) bismuth-selenium system, (5) 196*f*.

Knozinger, H., and Stolz, H. Adsorption relations of aluminum oxide (III) adsorption of ethanol and tertiary butanol on γ-aluminum oxide, (4) 126*f*.

Knueppel, H., and Brotzmann, K. Method of producing steel for sheets to be enameled by the single-coat method, P (4) 94*e*.

Ko, Hon Chung, Greenbaum, M. A., Blauer, J. A., and Farber, M. Enthalpy of formation and entropy of aluminum(I) fluoride (g), (1) 29*g*.

Ko, Hon Chung, Greenbaum, M. A., and Farber, M. Thermodynamic and physical properties of beryllium compounds (XI) heat of formation and entropy of beryllium(I) hydroxide(g), (5) 201*d*.

Ko, Hon Chung, Greenbaum, M. A., Farber, M., and Selph, C. C. Thermodynamic and physical properties of beryllium compounds (X) heats of formation and entropies of $BeCl_2(g)$ and $Be_2Cl_4(g)$, (5) 201*d*.

Kobashi, Tomoko. Reaction of calcium hydroxide with allophane-kaolinite clay minerals, (8) 278*i*.

Kobatake, Y. See Toyoshima, Y.

Kobayashi, Haruhiro. Three-electrode cold-cathode gas laser tube, P (1) 19*g*.

Kobayashi, K., Kosuge, K., and Kachi, S. Electric and magnetic properties of $Li_xV_{2-x}O_2$, (10) 352*a*.

Kobayashi, Kazuo. See Futaki, Hisao.

Kobayashi, Kazuo, and Fuller, M. Stable remanence and memory of multidomain materials with special reference to magnetite, (5) 200*g*.

Kobayashi, Kazuo, and Yamauchi, Michiaki. Method of production of active beryllium oxide powders, P (6) 229*i*.

Kobayashi, Kenzi K. Dynamic theory of phase transition in KH_2PO_4-type ferroelectric crystals, (2) 75*j*.

Kobayashi, Nariaka, and Toril, Michihiro. High speed memory in computer, (4) 110*i*.

Kobayashi, Sadao. See Hayashi, Shigekazu.

Kobayashi, Taneo. Solid solubilities of $FePO_4$ and $CrPO_4$ in $AlPO_4$, (1) 37*e*.

Kobayashi, Waichi. See Suzukawa, Yuichi.

Kobayashi, Yoshichika; Masuda, Mutsuo; Mizuno, Hideo; and Murayama, Setsuko. Process for preparing phosphors, P (10) 345*h*.

Kobayashi, Yoshichika; Masuda, Mutsuo; and Murayama, Setsuko. Preparation of borax-fluxed europium-activated rare earth oxide phosphors, P (11) 378*f*.

Kobayashi, Yoshichika; Masuda, Mutsuo; Murayama, Setsuko; and Mizuno, Hideo. Europium-activated phosphors containing lithium fluoride and method for preparing the same, P (11) 378*g*.

Kobayashi, Yoshichika, and Takamura, Tohru. Relaxation processes of Eu^{3+} in Y_2O_3 and YVO_4 using pulsed cathode-ray excitation, (8) 297*i*.

Kobb, O. C., and Harris, L. A. Synthesis of grunerite and other phases in the system SiO_2-NaOH-Fe-H_2O, (4) 158*c*.

Kobilyatskii, V. G. See Vatman, A. P.

Koblischek, P. See Dithmar, K.

Kobzareva, S. A. See Distler, G. I.

Koch, G. See Rausch, W.

Koch, V. See Kahle, H. G.

Kockaerts, R. F. See Nuyens, J. G. E.

Kocsis, G. Effect of melting aids on the activation energy of silicate glasses, (2) 48*c*.

Kodama, H. See Forman, S. A.

Kodata, Masatane. See Nakamichi, Hiroshi.

Koehler, E. K., and Routschka, G. Investigation of Westerwald clay deposits in Melsbach and Breitscheid, (1) 31*h*.

Koellmann, E. Ceramic artists and their work—Walter A. Heufelder, (11) 367*h*.

Koenen, H. Thermocouples for temperature control, (1) 22*g*.

Koenig, C. J. See Houseman, J. E.

Koenig, H. R. See Chernoch, J. P.

Koepp, R. L. Low capacitance field effect transistor, P (8) 282*b*.

Koerner, K. See Heidrich, W.

Koester, C. J. Fiber laser structures and the like, P (10) 344*j*. Fiber-optical image-enhancing devices, systems, and the like, P (9) 307*d*.

Koester, C. J., Dixon, E. O., and Snitzer, E. Laser systems and the like employing solid laser components and light-absorbing claddings, P (8) 282*a*.

Koester, C. J., and Williams, N. S. Laser amplifier construction, P (4) 99*j*.

Kofstad, P. Comment on the defect structure of a-Nb_2O_5, (5) 193*b*. Note on the defect structure of rutile (TiO_2), (4) 146*i*.

Kofstad, P., and Hed, A. Z. Defect structure model for wustite, (4) 130*h*.

Koga, Hiroshi, and Hukuda, Kenzi. Electron paramagnetic resonance of Cu^{2+} in KH_2PO_4, (2) 76*b*.

Koga, Masashi. See Takami, Katsumi.

Koga, Yasumasa. Methods of the determination of the percent of crystallinity of partly crystallized glass, (4) 120*d*.

Koganovsky, A. M. Adsorption of colloid electrolyte micelles by inhomogeneous porous materials, (7) 263*h*.

Kogure, Masato. See Hasumi, Asataro.

Kogut, V. See Coberly, C. J.

Kohatsu, Iwao. See Kubo, Teruichiro.

Kohl, H. Behavior of decorated table ware in household dishwashers, (1) 15*a*.

Kohlenberger, L. B. See Anderson, S.

Kohlhaas, R. See Hloch, A.

Kohls, D. E., Moe, D. L., and Reece, H. W. Method and apparatus for handling bulk cement, P (6) 207*e*.

Kohnke, E. E. See Matthews, H. E.

Kohn, E. J., Sands, A. G., and Clark, R. C. Quantitative measurement of void content in glass-filament-wound composites and correlation of interlaminar shear strength with void content, (1) 8*a*.

Kohn, K. See Siratori, Kiiti.

Koide, Kazushige. See Niwa, Shohei.

Koide, Shigenao. See Fukuda, Tsuguo; Takei, Humihiko.

Koide, Shigenao, and Takei, Humihiko. Epitaxial growth of VO_2 single crystals and their anisotropic properties in electrical resistivities, (10) 353*c*.

Koizumi, Haruhiko; Sato, Shuichi; and Kawaji, Shinji. Effects of light and temperature on the growth of silicon stain films, (9) 320*b*.

Koizumi, M. See Shimada, M.

Koizumi, Mitsue. See Matsuo, Yoshihiro.

Kojima, Kojiro; Nagano, Kyoichi; Inazumi, Tadahiro; Takagi, Katushiro; and Shimada, Kohichi. Study of the mineralogical and metallurgical properties of synthetic calcium ferrite, (11) 374*j*.

Kojima, Yasujiro. See Shimada, Shinro.

Kokorina, V. F. Crystallization of oxygen-free sulfoselenide glasses, (7) 247*a*.

Kokotailo, G. T. See Olson, D. H.

Kolar, D. See Blinc, R.

Kolarov, T. See Scheludko, A.

Kolb, E. D., Caporaso, A. J., and Laudise, R. A. Hydrothermal crystallization of some II-VI compounds, (8) 293*e*.

Kolb, F. L., Jr. See Eastwood, F.

Kolb, K. M. See Willcox, O. B.

Kolbow, P. New radiation pyrometer for glass temperature measurement, (7) 260*i*. Optical temperature measurement in glass works, (7) 260*j*.

Kolchin, I. K. See Gal'perin, E. L.

Kolek, R. L., and Bartrug, N. G. Glass fiber cord construction, P (8) 277*b*.

Kolesh, V. A. Abrasive tool, P (5) 169*f*.

Kolesov, Yu. I. See Nagulevich, K. V.; Pavlushkin, N. M.

Kolinsky, M. See Litomisky, J.

Kolkman, D., and Reynders, A. Apparatus for manufacturing fluorescent lamps, P (1) 10*h*.

Kolle, G. F. Graphite continuous casting mold, P (11) 374*j*.

Koller, A., Rambousek, V., Koukal, V., and Schwarzbach, J. Formation of texture defects and their influence on the properties of electrotechnical ceramics, (1) 16*j*.

Kollmar, H. J. See Dawihl, W.

Kolluri, R. V. See O'Shea, D. C.

Kolostori, J. Possibilities of automation in cement plants, (8) 274*g*.

Kolpack, R. L., and Bell, S. A. Gasometric determination of carbon in sediments by hydroxide absorption, (1) 21*a*.

Koltermann, M. See Gruner, K.

Kol'tsov, S. I., and Aleskovskii, V. B. Nature of the products of the interaction of iodine with silica gel, (4) 145*j*.

Kol'tsov, Yu. I. See Sorokin, I. P.

Komac, T., and Spirko, E. J. Process for repairing refractory walls, P (4) 107*e*.

Komatsu, Eiichi. See Yamamoto, Junnosuke.

Komatsu, H. See Inomata, Y.

Komatsu, Teruhiko, and Shibata, Goro. Treatment of a phosphor screen in a cathode ray tube, P (2) 67*b*.

Komatsu, Teruo. See Kaifu, Yozo.

Komatsubara, K. F. See Katayama, Yoshifumi.

Kometani, T. Y. See Remeika, J. P.

Komeya, Katsutoshi. See Matsue, Shigetomo.

Komin, N. E. See Izergina, E. V.

Komine, Yoshiharu. See Torikai, Naochika.

Komissarova, L. N. See Spiridinov, F. M.

Komissarova, L. N., Pokrovskii, B. I., Granovskii, Yu. V., and Shaplygin, I. S. Investigation of the region of scandium oxide solid solutions in the system Sc_2O_3-Fe_2O_3-MnO_x by the statistical method of averaging, (4) 141*h*.

Komiya, Yoshio. See Tarui, Yasuo.

Komleva, G. M. See Evstrop'ev, K. S.

Komrska, J., and Satava, V. Study of the hardening of inorganic cements (II) effect of some bivalent and trivalent ions on structure and strength of hardened zinc-phosphate cements, (7) 245*f*.

Konak, C. See Hoeschl, P.

Kondo, Hiroshi. Shrinkage of large size plaster model used for making dies, (4) 92*g*.

Kondo, Renichi, and Daimon, Masaki. Early hydration of tricalcium silicate—solid reaction with induction and acceleration periods, (11) 384*c*.

Kondo, Takayoshi. See Sugiyama, Sachio.

Kondo, Y. See Yamazaki, S.

Kondo, Yoshihiro. See Soga, Minoru.

Kondoh, Hisamoto. See Uchida, Enji.

Kondrashev, Yu. D., Markevich, G. S., and Markovskii, L. Ya. Structure of a zeta phase in the system Be-B, (7) 269*b*.

Kondratov, I. Ya. See Samsonov, G. V.

Koneval, D. J. See Curran, D. R.

Konig, U., and Chol, G. X-ray and neutron diffraction studies on the ferrite Mn_xZn_{1-x}-Fe_2O_4, (9) 333*b*.

Konjevic, R., Grant, W. A., and Carter, G. Ion impact desorption of hydrogen from glass, (5) 173*a*.

Konno, Hiroshi. See Kudaka, Katsuya.

Kono, Masae. See Shimada, Kinji.

Konopicky, K. See Hagemann, L.; Patzak, I.; Von Kahler, U.

Konrad, H. E., and Speil, S. Inorganic fiber riser sleeves, P (10) 342*f*.

Konrad, K., and Neubert, T. J. F-aggregate centers in sodium fluoride (I), (4) 136*d*.

Konstantinov, B. P., and Oshurkova, O. V. Analysis of silicates, (7) 259*h*.

Konta, J. Raw kaolin from Osmosa-Bogicany in West Bohemia, (6) 229*i*.

Kontorovich, S. I. Effect of magnesium sulfate on the strength of highly dispersed fine-pore structures of magnesium hydroxide and magnesia, (6) 232*f*.

Kontrimas, R., Krohl, R. J., and Wajda, E. S. Electrical temperature sensor device, P (2) 64*c*.

Konvisar, L. V. See Sysoev, L. A.

Kopanda, J. E. See Maravilla, S.

Kopp, O. C., and Clark, G. W. Hydrothermal synthesis, optical perfection, and surface topography of quartz grown in RbOH and other alkali hydroxides, (7) 267*a*.

Kopp, P. E. Clay tile building block with passageways, P (4) 102*e*.

Koppel, L. B. See Holmes, J. T.

Koppers Co., Inc. Method of resin impregnating a spool of fiber glass roving, P (9) 308*c*.

Koppius, O. G. Secondary emission cathode or dynode of a porous matrix of tungsten or molybdenum impregnated with secondary emission material such as a tungstate or an alkali halide of calcium, P (11) 378*b*.

Kor, G. J. W., and Richardson, F. D. Sulfide capacities of basic slags containing calcium fluoride, (7) 245*b*.

Korach, M., and Fulop, J. Heat effect in continuous furnaces, (5) 189*b*.

Korbitz, F. W. See Chiotti, P.

Korda, E. J., Pruden, L. H., and Williams, J. P. Three-dimensional and stereo observations in glass and ceramic systems, (4) 97*i*.

Kordis, J. See Burnham, D. A.

Kordis, J., and Eyring, L. Some tensimetric studies in the mixed ceria-terbia system, (5) 200*d*. Tensimetric study of the terbia and praseodymia systems and the mixed praseodymia-terbia system, (5) 201*b*.

Koretzky, H. Electrodeposition of magnetic thin films, P (2) 64*c*.

Kormer, S. B., Krishkevich, G. V., and Yushko, K. B. Investigation of the optical properties of shock-compressed lead glass (elastic-plastic waves in glass), (1) 7*a*.

Kornienko, L. S. See Evlanova, N. F.

Kornienko, V. E. See Ostrovskii, O. P.

Kornprobst, J. See Velde, B.

Korobkin, V. V. See Alcock, A. J.

Korostoff, E. See Greenberg, S. B.

Korovyachenko, F. K. See Moleva, N. G.

Korshikova, N. G., Kunin, L. L., and Malkin, V. I. Evaluation of diffusion potential in silicate systems with a unipolar conductivity, (2) 48*j*.

Korshunov, B. G. See Safonov, V. V.

Korshunov, B. G., Drobot, D. V., Borodulenko, G. P., and Galchenko, I. E. Interaction of the chloride of europium(III) and terbium with sodium and potassium chlorides, (7) 267*d*.

Korshunov, B. G., Drobot, D. V., Galchenko, I. E., and Shevtsova, Z. N. Interactions of holmium chloride and erbium chloride with potassium chloride in melts, (4) 140*e*.

Korytkova, E. N., Fedoseev, A. D., and Makarova, T. A. Production of synthetic asbestos from the wastes of asbestos-concentration plants, (2) 73*b*.
Koryukov, V. N., Kuznetsov, S. I., and Derevyankin, V. A. Influence of radiations on the decomposition rate of aluminate solutions, (1) 31*a*.
Korzhavyi, A. P. See Nichiporenko, E. P.
Korzhukov, N. G., and Khomyakov, K. G. Phase diagram of the system $MnCl_2$-$NiCl_2$, (9) 327*a*.
Korzhukov, N. G., Ozerova, M. I., Khomyakov, K. G., and Onikienko, L. D. System $FeCl_2$-$MgCl_2$, (4) 158*j*.
Kosaki, Akio. See Sorai, Michio.
Kose, Saburo. See Kinoshita, Makoto.
Kose, Saburo, and Hamano, Yoshiteru. Dielectric properties of hot-pressed alumina, (1) 27*h*.
Kose, Saburo; Kinoshita, Makoto; and Hamano, Yoshiteru. Hot-pressing of ZrC-Ni mixtures, (2) 56*e*, (6) 215*e*.
Koshy, J. See Patel, A. R.
Kosiorek, R. Satin finish vitrifiable enamels, P (2) 54*a*. See Wolf, W. F.
Kosmos, P. See Feagin, R. C.
Kostanyan, K. A. Electrical conducitvity of molten glasses and some problems in electric glassmelting, (1) 8*g*. See Manvelyan, M. G.
Koster van Groos, A. F., and Wyllie, P. J. Melting relations in the system $NaAlSi_2O_5$-NaF-H_2O to 4 kbars pressure, (4) 144*d*.
Kostikov, V. I. See Elyutin, V. P.
Kostyukov, N. S. Influence of irradiation on ceramic materials, (2) 60*f*. See Budnikov, P. P.
Kosuge, K. See Kobayashi, K.
Kosuge, Koji. Phase transition in VO_2, (8) 296*f*. See Okinaka, Hideyuki.
Kotelnikov, A. F. See Moldavsky, F. G.
Kotera, Yoshihide. Kinetics of transformation of germanium oxide, (4) 142*g*.
Kotera, Yoshihide, and Yonemura, Michiko. Role of catalysts in the transformation of germanium dioxide, (6) 237*a*.
Kotlyar, G. Kh. See Modylevskaya, K. D.
Koto, Kichiro. See Morimoto, Nobuo.
Kotru, P. N. See Joshi, M. S.
Kotyk, M. Method of enameling steel, P (7) 246*g*.
Koubek, F. J. Ceramic plastic composite material for radomes, P (7) 252*f*.
Koukal, V. See Koller, A.
Koukal, V., and Rambousek, V. Effect of some active admixtures on the dielectric strength of porcelain, (7) 253*f*. Factors affecting electrical breakdown of ceramic insulators, (2) 60*c*.
Koump, V. See Olsson, R. G.
Koury, F. See Waymouth, J. F.
Koury, F., Matheson, W. G., and Waymouth, J. F. Arc discharge tube having an electrode which contains a light-emitting metal, P (2) 52*j*.
Koury, F., and Waymouth, J. F. High pressure electric discharge device containing mercury, halogen, scandium, and alkali metal, P (2) 65*a*.
Koutecky, J. See Tomasek, M.
Kouvarellis, G. K. See Hall, P. G.
Kouvel, J. S., and Rodbell, D. S. Magnetic equation of state for CrO_2 and nickel near their Curie point, (4) 143*g*.
Kovachev, I. See Gerasimov, E.
Kovacs, P. See Bertoti, I.
Koval'chuk, V. Yu. See Vidavskii, L. M.
Kovar, E. Electric boosting of glassmelting tank furnaces, (2) 48*e*.
Kovba, L. M. See Bkhargava, Kh. D.; Trunov, V. K.; Vidavskii, L. M.
Kover, F., and Musselin, M. J. Comparative study of anodic oxide films on titanium, niobium, and tantalum, (8) 280*h*.
Kowai, L. B. See Offenbacher, W.
Kowaki, Hirokazu. See Shirakashi, Shigeru.
Kowalczyk, F. See Hagemann, L.
Kowalenko, W. Method and apparatus for the production of lightweight aggregates, P (2) 54*f*.
Kowalski, W. See Schmeisser, K.
Kowalski, Z., and Zarebski, J. Simultaneous determination of iron and titanium by polarographic methods, (5) 188*c*.
Koyama, K. Thermal conductivity of magnesium fluoride between 25° and 900°C, (6) 239*a*.
Koyama, T. See Fujii, Minoru.
Koyama, Tsukasa. See Ikeda, Koichi.
Kozielski, M. Growth of ZnS single crystals from the melt at 1850°C under argon pressure of 50 atm, (6) 233*e*.
Kozlova, N. I. See Ezerskii, M. L.
Kozuka, Takeshi. See Noguchi, Tetsuo.
Kozyczkowski, J. See Johansson, K.
Kragle, H. A. Use of programmed robots in glass handling operations, (4) 98*b*.
Kraitchman, J. See Oroshnik, J.
Krakauer, S., Musikant, S., and Rosenberg, D. J. Apparatus for production of glass fibers, P (6) 212*g*.
Kralove, H. See Balcar, O.
Kramer, D. A., and Honig, R. E. Evidence of laser-induced stimulated Brillouin scattering in CdS, (9) 321*a*.
Kramer, W. E. See Mazelsky, R.
Kranje, K. Quantitative investigation of domain structures by Berg-Barrett X-ray diffraction microscopy (I) determination of small tilt angles in various lattice planes of the crystal, (10) 359*d*.
Krasnikova, G. V. See Kuz'min, N. M.
Krasnousova, A. S. See Berenshtein, P. I.
Kratochvil, R. F., and Eggert, W. C. Device for separating plates and frames of filter presses, P (8) 284*e*.
Kraus, H., Parker, S. G., and Smith, J. P. $Cd_xHg_{1-x}Te$ films by cathodic sputtering, (4) 128*e*.
Kraus, J. W., and Hurley, F. R. Preparation of vermiculite paper, P (6) 218*h*.
Krausbauer, L. See Kaldis, E.
Krause, E. Technology of Heavy Clayware (Vol. 2) Fundamentals of Drying, B (8) 302*c*.
Krause, E., Plaul, T., and Zoellner, R. Technology of Heavy Clayware (Vol. 4) Firing and Furnace Design Fundamentals, B (8) 302*e*.
Krause, E., and Zoellner, R. Technology of Heavy Clayware (Vol. 5) Firing Systems, B (8) 302*f*.
Krause, J. T. Gold-indium bond for measurement of ultrasonic properties in solids at high temperatures, (7) 260*e*.
Krause, J. T., and Northover, W. R. Glass bonding medium for ultrasonic devices, P (4) 98*h*.
Krause, P. W. See Nelson, P. A.
Krause, R. F., Jr., and Douglas, T. B. Vapor pressure, vapor dimerization, and heat of sublimation of aluminum fluoride, using the entrainment method, (5) 202*i*.
Krausz, A. S. Rate theory of dislocation mobility, (1) 35*i*.
Krausz, A. S., and Gold, L. W. Surface features observed during thermal etching of ice, (5) 200*g*.
Krauth, A. Changes in the properties of powders during the pressing of hard materials, (6) 230*i*. Measurement of strain in vanadium carbide and its significance, (5) 177*f*.
Krautkraemer, J. Method [ultrasonic pulse echo] and apparatus for detecting flaws in materials, P (10) 348*a*.
Kravchenko, G. G. Structural etching of chrome spinellids, (4) 156*j*.
Kravchenko, V. I. See Broude, V. L.
Kravchenko-Berezhnoi, R. A., and Polezhaeva, L. I. Preparation of emitters for the X-ray fluorescence analysis of powders, (6) 227*a*.
Kravchuk, T. A., and Lazebnik, Yu. D. Study of the borates of iron under hydrothermal conditions, (9) 330*e*.
Krebs, H. Fundamentals of Inorganic Crystal Chemistry, B (11) 388*g*.
Kreder, K. See Kalish, D.
Kreidl, N. J. Glass reasearch in review (I), (5) 172*g*; (II), (7) 247*c*. See Lell, E.
Kreidl, N. J., and Maklad, M. S. Effect of water content on phase separation in soda-silica glasses, (11) 369*f*.
Kreidler, E. R. See Hummel, F. A.
Kreidler, E. R., and Hummel, F. A. Phase equilibria in the system $Ca_3(PO_4)_2$-$Zn_3(PO_4)_2$, (4) 149*e*. Phase relations in the system SrO-P_2O_5 and the influence of water vapor on the formation of $Sr_4P_2O_9$, (11) 386*e*.
Kreim, F. Ceramic artists and their work—Otto Hufnagel, (6) 205*j*.
Kremm, G. F. Process for pickling metal, P (8) 275*h*.
Kren, J. G., Regh, J., and Seto, D. K. Technique for obtaining isolated integrated circuits, P (5) 185*e*.
Kreuchen, K. H. New ways with ceramics in electronic valves, (2) 63*h*.
Kreuter, J. C. Enameling of aluminum, (11) 368*h*.
Kreuzer, L. B. High-efficiency optical parametric oscillation and power limiting in $LiNbO_3$, (8) 292*i*.
Krieger, K. [Radiant] gas burners, P (8) 286*f*.
Kriek, H. J. S., and Segal, B. B. Factors influencing the rate of wear of magnesite rotary [metallurgical] furnace linings (I) effect of slag and brick compositions; (II) laboratory study of used bricks; (III) research methods of metallurgical operation and progress in refractories, (2) 55*a*.
Kriens, B. Increased use of machinery for the winning of clay in Westerwald [Germany], (10) 348*j*.
Kriger, J. A. See Tobolov, P. N.
Krijtenburg, G. S. See Gie, O. T.
Krikorian, N. H. See Giorgi, A. L.; Krupka, M. C.
Krinchik, G. S., and Gushchina, S. A. Effect of a magnetic field on the Faraday effect in ferrite garnets, (2) 76*c*.
Krischner, H. Incorporation of heterogeneous ions into γ-Al_2O_3, (6) 233*g*.
Krishkevich, G. V. See Kormer, S. B.
Krishna, P. See Rai, K. N.
Krishnan, K. See Hester, R. E.
Krishnan, R. S. See Porto, S. P. S.
Krishnaswami, S. P. See Sharma, M. R.
Krishtofori, I. I. See Belen'kaya, I. M.
Kristiansen, L. A., and Krogh-Moe, J. Vibrational assignment and valence force field of the boroxol skeleton, (1) 9*h*.
Krivaite, E. See Babonas, G.
Krivoshein, A. S. See Gavrilov, O. R.
Krivov, V. A., and Kharitonov, N. P. Protective coatings for the construction elements, B (5) 204*i*.
Krivovyazov, E. I., Sokolova, I. D., and Voskresenskaya, N. K. Surface tension of zinc metaphosphate, (8) 299*d*.
Krivtsov, V. A., Kharitonov, N. P., Veselov, P. A., and Appen, A. A. Protective coatings from organosilicate materials for electrodes up to 1200°C, B (5) 204*i*.
Kriz, H. M. See Kline, D.
Kriz, H. M., Bishop, S. G., and Bray, P. J. ^{11}B NMR in polycrystalline calcium metaborate, (2) 46*j*.
Kriz, M. Change in color of melts in glass-melting kilns, (8) 276*a*.
Krleza, F., Stanicic, N., and Ruzdic, E. Mutual precipitation effects of aluminum hydroxide-iron hydroxide, aluminum hydroxide-silicic acid, and iron hydroxide-silicic acid sols, (6) 235*e*.
Krock, R. H. See Broutman, L. J.; Ginsberg, M. J.; Kelsey, R. H.; Zdanuk, E. J.
Krock, R. H., and Kelsey, R. H. Preparation [vapor deposition] of silicon nitride whiskers, P (4) 107*b*.
Kroeger, C., and Heckmann, H. Electrical conductivity of soda-lime-silica batches during the latter stages of melting — a contribution to the fining process, (6) 209*f*.
Kroeger, F. A. *P-T-x* phase diagram of the system zinc-tellurium, (1) 35*e*. See Yanagida, Hiroaki.
Kroemer, H., and Fairman, R. D. Heterojunction semiconductor devices employing carrier multiplication in a high gap ratio emitter-base heterojunction, P (4) 113*i*.
Kroener, E. Elastic moduli of perfectly disordered composite materials, (4) 133*j*.
Kroenke, W. J. See Carman, C. J.
Kroes, G. H. Process for preparing amorphous germanium dioxide, P (10) 349*b*.
Kroes, R. L. See Chen, Y.
Kroeyer, K. K. K. Aggregate for building materials, especially road surfacing materials, P (6) 207*b*. Method of manufacturing relatively high calcia-silica ceramic materials, P (11) 375*c*. Method of manufacturing a whitish granular aggregate for building purposes from a crystallizable vitreous material, P (11) 371*i*. Method of producing a white, grained aggregate with a devitrifiable glassy material as one of the components, P (6) 207*b*.
Krogh-Moe, J. See Kristiansen, L. A.
Kroglus, E. A., and Vlasov, V. A. Study of metal oxide coatings by infrared spectroscope, (1) 9*d*.
Krohl, R. J. See Kontrimas, R.
Krohl, R. J., and Wajda, E. S. Diffused-epitaxial scanistors, P (7) 256*e*.
Kroichuk, L. A. See Budnikov, P. P.
Krokhina, A. I., Sizikova, N. G., Ivanova, L. D., Vasil'eva, N. V., and Dobroklonskaya, N. S. Structure of thin dielectric films prepared by cathodic sputtering of single-phase and multiphase materials, (2) 63*g*.
Kroko, L. J. Growth studies of silicon carbide crystals, (1) 30*j*.
Kroll, J. M., and Borchert, W. Geological and petrographic studies of West German kaolin deposits (I) sampling and investigational methods; (II) deposits at Lohrheim near Dietz an der Lahn, (7) 262*e*; (III) Geisenheim/Rheingau; (IV) granite kaolins in East Bavaria — Tirschenreuth, (11) 382*b*.
Kromin, I. P. Corrosion of the reinforcement in autoclave silicate concrete from lime-silica cement using hydrated lime, (2) 44*a*.
Krongelb, S. Environmental effects on chemically vapor-plated silicon dioxide, (1) 16*d*. Method of growing doped semiconductor material from a source which includes an unstable isotope which decays to a dopant element, P (9) 312*h*.
Kronlage, J. W. See Wisman, E. C.
Kroone, B. Reaction between hydrating portland cement and ultramarine blue, (2) 45*e*.
Krotikov, V. A. See Kharitonov, N. P.
Krotikov, V. A., Kharitonov, N. P., and Belinskaya, G. V. Thermographic and thermogravimetric studies of organosilicate materials, B (5) 204*j*.
Krotova, L. V., Mikaelyan, R. G., and Osiko, V. V. Fluoride crystals with impurities of scandium, yttrium, and lanthanum, (10) 353*g*.
Krouskop, N. C. See Castellucci, N. T.
Kruger, J. See Yolken, H. T.
Kruger, O. L. See Moser, J. B.
Kruger, O. L., and Savage, H. Heat capacity and thermodynamic properties of plutonium dioxide, (10) 354*e*.
Kruglitskii, N. N. See Orobchenko, V. I.; Ovcharenko, F. D.
Kruglitskii, N. N., Mamatkanov, A. M., Ovcharenko, F. D., Tretinnik, V. Yu., and Kukharenko, T. A. Controlling the structural-mechanical properties of montmorillonite-kaolinite dispersions, (7) 262*a*. Effect of sodium humus on the structure formation and mechanism of development of deformations in aqueous dispersions of montmorillonite, (7) 262*d*.
Kruglitskii, N. N., Ovcharenko, F. D., Simurov, V. V., Nichiporenko, S. P., and Barshchevskaya, S. V. Mechanism of formation of coagulation structures in aqueous dispersions of tremolite and hydromica under the action of ultrasound, (7) 267*b*.
Kruglitskii, N. N., Skalskaya, U. L., and Gaevoi, M. S. Method of introducing clay powders

into drilling muds in the absence or presence of electrolyte coagulators, (7) 258*h*.
Kruh, R. F. See Lawrence, R. M.
Krukowska-Fulde, B., and Niemyski, T. Preparation and some properties of CdF_2 single crystals, (5) 199*a*.
Krumhansl, J. A. See Guyer, R. A.
Krumme, J. P. See Straumanis, M. E.
Krupka, M. C. See Giorgi, A. L.
Krupka, M. C., Giorgi, A. L., Krikorian, N. H., and Szklarz, E. G. High-pressure synthesis and superconducting properties of yttrium sesquicarbide, (10) 354*j*.
Krylov, Yu. I. See Balakir, E. A.
Ku, Han Y. *Pn* junction formation by thermal oxidation, P (4) 115*f*.
Ku, S. M. Preparation and properties of boron arsenides and boron arsenide-gallium arsenide mixed crystals, (1) 35*g*.
Kubichan, R. E. See Saunders, A. E.
Kubo, Takeji; Abe, Hisashi; and Hirai, Akira. ^{55}Mn nuclear magnetic resonance of Mn^{3+} ions located at B-sites in manganese ferrite single crystals, (1) 32*j*.
Kubo, Takeji; Tsuda, Toshinobu; Abe, Hisashi; and Hirai, Akira. Spin echo spectra of manganese ferrite at liquid helium temperature, (8) 298*e*.
Kubo, Teruichiro. See Kato, Masanori.
Kubo, Teruichiro; Kato, Masanori; and Kohatsu, Iwao. Thermal expansion of zirconia and formation reaction of stabilized zirconia, (8) 300*f*.
Kubo, Yasushi; Yamaguchi, Goro; and Kasahara, Komei. Hydrated sodium aluminosilicates by hydrothermal metamorphosis of nepheline-carneg.e.te minerals, (6) 233*a*. Hydrated sodium aluminosilicates relating to nepheline-carnegieite minerals — relations among the crystal lattices and thermal transformations, (6) 233*c*. Kinetic and electron optical studies of the reaction processes between kaolinite and sodium carbonate, (8) 293*j*.
Kubota, Fumio. Semiconductor having reinforced lead structure, P (9) 314*a*.
Kubota, H., and Sakane, K. Study of an electrical method for measuring strain of a hardening cement mortar by a molded polyester resin strain gage, (1) 3*c*.
Kubota, Joe. See Yanagida, Hiroaki.
Kubota, Tatsuyuki. See Inoue, Toshio.
Kuboyama, Jun. See Suzuki, Osamu.
Kubsh, L. M. Abrasive disk, P (5) 169*f*.
Kucharski, J. See Schleifer, P.
Kudaba, V., Juskevicius, A., and Brazdziunas, P. Quantity of low-frequency current noise in CdSe single crystals, (5) 199*h*.
Kudaka, Katsuya, and Konno, Hiroshi. Effect of ultrahigh pressure on boron nitride, (5) 177*d*.
Kudaka, Katsuya; Konno, Hiroshi; and Matoba, Toshio. Effect of ultrahigh pressure on the oxidation of graphite, (8) 291*h*.
Kudinov, V. V. See Rykalin, N. N.
Kudman, I. Thermoelectric lead telluride base compositions and devices utilizing them, P (11) 379*c*.
Kudrak, D. R., and Sienko, M. J. Solid-state studies of oxygen-deficient tantalum pentoxide, (11) 387*d*.
Kudryakova, M. L. See Bogdanova, G. S.
Kuebler, N. A. See Robin, M. B.
Kuemmerer, F. See Rheinberger, P.
Kuendig, W. See Ando, K. J.
Kueneman, D. Jaw crushers, P (5) 190*j*.
Kuenen, P. H. Settling convection and grain-size analysis, (1) 22*a*.
Kuenstle, J. F., and Rosen, J. E. Method of dressing grinding wheels, P (5) 169*h*.
Kuepper, K. A. Artificial tooth, P (8) 280*e*.
Kues, H. A. See Murphy, J. C.
Kuhn, D. A. Subterranean consolidation silicate cement, P (9) 304*f*.
Kuhner, G. See Knorre, H.
Kuiper, L. L. Solid state epitaxial growth of silicon by migration from a silicon-aluminum alloy deposit, P (4) 117*b*.
Kukharenko, T. A. See Kruglitskii, N. N.
Kukui, A. L., Parkhomovskii, V. L., and Bud'ko, I. A. Production and study of artificial crystals of the isomorphous series scheelite-powellite, (4) 151*e*.
Kulagin, I. D. See Rykalin, N. N.
Kulakowski, B. See Grochowski, M.
Kulcinski, G. L., and Leggett, R. D. Dissolution of UC particles in uranium during post-irradiation annealing, (10) 340*i*.
Kulcsar, A. See Marino, D.
Kuleshov, F. P. See Shabanov, A. G.
Kulevskii, L. A., Prokhorov, A. M., and Smirnov, V. V. Generation of giant pulses in $CaF_2:Dy^{2+}$ crystals, using an electrooptical shutter with a $LiNbO_3$ crystal, (2) 77*b*.
Kulevskii, L. V. See Melamed, Sh. G.
Kulicke & Soffa Industries, Inc. Semiconductor wafer pickup and bonding tool, P (11) 378*h*.
Kulig, C. W. Apparatus and method for handling glassware for inspection or the like, P (6) 212*c*.
Kulkarni, A. K., Prasad, R., Vyas, B. R., and Moorthy, V. K. Influence of microstructures on the dielectric properties of barium titanate, (10) 344*f*.
Kulkarni, S. D., and Khangenkar, P. R. Calculation of phase boundaries in the thallium-lead system from activity data, (1) 25*c*.
Kulling, A. See Hitzenann, G.
Kulling, A., Steinbach, H., and Thumm, H. Process for the manufacture of a rutile pigment by reacting titanium tetrachloride with oxygen or gases containing oxygen, P (10) 349*f*.
Kul'skii, L. A. See Slipchenko, V. A.
Kuma, J. See Chabra, K. C.
Kumada, Akio. Method of producing ceramic piezoelectric vibrator, P (9) 313*d*.
Kumagai, Naojiro. Method of manufacturing graphite-bond grinding wheels for precision grinding, P (10) 335*g*.
Kumagai, Yasuji; Kawarada, Kuniyasu; and Shibata, Yukio. Energy distribution of electrons tunneling through a metal-insulator-metal sandwich structure, (8) 292*a*.
Kumar, A. See Jain, D. S.
Kumar, R. L. Blast furnace slags—standardization for efficient use, (4) 91*c*.
Kumar, S. See Deo, P. G.; Gupta, P. K.
Kumar, S., and Maitra, A. K. Water attack on lithia glasses in relation to phase separation phenomena, (2) 52*j*.
Kumar, S., and Nag, B. B. Influence of boric oxide on vitrification of amorphous and crystalline forms of silica, (10) 337*h*.
Kumazawa, Seiichi. See Kawamura, Sukezo.
Kume, S. See Shimada, M.
Kunert, H., and Biermann, W. Safety glass, P (6) 213*d*.
Kunev, D. K., Belyaevskaya, L. V., and Zelikman, A. N. Systems MoO_3-$CaMoO_4$, MoO_3-$PbMoO_4$-$ZnMoO_4$, (7) 270*a*.
Kunin, L. L. See Korshikova, N. G.
Kunitomi, Minoru, and Kunugi, Toshio. Additives to synthetic quartz (II) effects of additives on the growth of synthetic colored quartz, (9) 317*h*.
Kunitomo, Masakazu. See Tsutsumi, Yoshitaka.
Kunitomo, Masakazu; Terao, Takehiko; Tsutsumi, Yoshitaka; and Hashi, Tsuneo. NMR of ^{39}K in $KrIr_2P_2O_4$ by double resonance method, (8) 295*f*.
Kuntaric, A. See Persin, A.
Kuntze, R. A. Aging of gypsum plaster, (11) 367*j*. Retarded gypsum plaster compositions, P (9) 304*d*.
Kunugi, Toshio. See Kunitomi, Minoru.
Kuo, C. C. Y. Technique for fabrication of printed circuit resistors, P (5) 185*d*.
Kupkova, D. Utilization of CN bands for determining arc temperature in electrodes in the presence of silicates containing higher amounts of iron, (2) 71*e*.
Kuppermann, A. See Persky, A.
Kuprii, Yu. M. See Dibrov, G. D.
Kupriyanov, M. F. See Fesenko, E. G.
Kupriyanova, L. A. See Belyavskaya, V. V.
Kupzog, E., and Lehmann, H. Behavior of commercial feldspars in ceramic casting slips, (6) 219*a*.
Kurdyumov, A. V., Pilyankevich, A. N., and Gnesin, G. G. Structure of low-temperature pyrographite, (1) 38*i*.
Kurdyumov, G. M., Molochko, V. A., and Chekunov, A. V. Some properties of silicon monoxide, (6) 237*i*.
Kuriakose, A. K., and Whalley, E. Phase diagram of ammonium fluoride to 20 kbars, (4) 148*j*.
Kuriyama, M. See Hirayama, C.
Kuriyama, Takeo. See Seki, Shingo.
Kurkjian, C. R., and Sigety, E. A. Coordination of Fe^{3+} in glass, (1) 6*a*.
Kuroda, Takayuki. See Mikoda, Masanari.
Kurokawa, Susumu. See Kitagawa, Hiroshi.
Kuroki, Hayashi. See Hoshino, Masahiro; Ikeda, Yutaka.
Kurosawa, Toshio, and Shiba, Hiroshi. Semiconductor device having regions with preselected different minority carrier lifetimes, P (5) 185*g*.
Kurosawa, Toshio; Shiba, Hiroshi; Sasaki, Ichiemon; and Yanagawa, Takayuki. Transistor body enclosing a submerged integrated resistor, P (2) 67*a*.
Kurpisz, Z. J., Connor, G. J., and Curtis, J. P. Method of making thyristors having electrically interchangeable anodes and cathodes, P (7) 257*i*.
Kurtin, S., Foner, S., and Lax, B. Ferromagnetic resonance in single-crystal $BaO{\cdot}6Fe_2O_3$, (9) 321*d*.
Kuschke, R. See Brauer, H.
Kushakovskii, V. I., and Loktev, A. M. Uranium dioxide as a fuel for atomic reactors, (2) 58*h*.
Kushida, T., and Kikuchi, M. *R*, *R'*, and *B* absorption line widths and phonon-induced relaxation in ruby, (2) 82*j*.
Kushihashi, Akira. Glass having a colored zone whose boundary has been blurred and method of producing the same, P (10) 339*d*.
Kushiro, I. System forsterite-diopside-silica with and without water at high pressures, (9) 331*c*.
Kusman, L. Quantitative analysis by electron microprobe in oxide combinations, (9) 328*b*.
Kust, R. N. Study of the orthotungstate condensation in fused equimolar sodium nitrate-potassium nitrate solvent, (4) 157*a*.
Kutukova, E. S. Study of glassforming regions in the system La_2O_3-B_2O_3-P_2O_5, (1) 9*i*.
Kuwamoto, Hidehiko; Saito, Shunjiro; and Takei, Takeshi. Formation of zinc ferrite by hydrothermal method, (4) 136*c*.
Kuzenkova, M. A. See Kislyi, P. S.
Kuz'ma, Yu. B. See Gladyshevskii, E. I., Gorshkova, L. V.
Kuz'ma, Yu. B., Lakh, V. I., Stadnyk, B. I., and Veroshilov, Yu. V. X-ray diffraction study of the system niobium-tungsten-boron, (7) 270*f*.
Kuz'ma, Yu. B., Serebryakova, T. I., and Plakhina, A. M. Polymorphic transformation of W_2B_5, (9) 327*j*.
Kuzmenkov, M. I. Influence of trace impurities on the crystallization of some glasses, (1) 7*a*.
Kuz'min N. M., Kuzovlev, I. A., Tsykunova, S. V., Krasnikova, G. V., and Gaiaktionova, A. N. Determination of trace impurities in high-purity CaO, (2) 69*d*.
Kuz'mina, G. V. See Khazanov, E. I.
Kuz'minskaya, L. N. See Balakir, E. A.
Kuznetsov, A. K., Keler, E. K., and Fan, Fukan. Polymorphism of ZrO_2 and the formation of zirconates of some rare-earth elements by the method of complex thermoanalysis, (1) 35*b*.
Kuznetsov, S. I. See Koryukov, V. N.; Tikhonov, V. N.
Kuznetzov, V. A. Crystallization of titanium, zirconium, and hafnium oxides and some titanate and zirconate compounds under hydrothermal conditions, (8) 290*f*.
Kuznetsova, I. K. See Sobolev, N. V., Jr.
Kuznetsova, L. A. See Antonova, E. A.
Kuzovlev, I. A. See Kuz'min, N. M.
Kuzyakina, E. B. Silicone lubricants for glass molding machine molds, (6) 211*c*.
Kvapil, J., Dolejs, V., and Kment, V. Corundum ceramics for high-temperature furnaces with a hydrogen atmosphere, (2) 54*h*.
Kwestroo, W., and Vromans, P. H. G. M. Method of producing pure red lead monoxide, P (9) 317*g*.
Kwok, P. C. See Miller, P. B.
Kydd, P. H. Pyrolytic graphite electrical resistance element, P (4) 116*d*.
Kynel, M. See Slunecko, M.
Kyoden, Hiroshi. See Hayashi, Takeshi.
Kysela, W. See Heitai, F.; Marino, D.

LaBelle, H. E., Jr., and Mlavsky, A. I. Growth of sapphire filaments from the melt, (7) 266*i*.
Labino, D. Apparatus for forming glass fiber products, P (1) 10*f*.
Labuda, E. F. See Crowell, M. H.
Lach, V. After-expansion of fireclay refractory, (4) 102*j*.
Lach, V., and Kanclir, E. Volume changes of portland cement on heating, (6) 206*j*.
Lach, V., and Moravek, J. Importance of measuring macroporosity during the sintering of clays, (6) 233*f*.
Lachman, I. M. High density alumina and method for producing it, P (11) 382*a*. Method for improving the visible and infrared transmission of hot-pressed magnesium fluoride, P (2) 53*e*.
Lachmann, P. F. J. Apparatus for applying fluid materials, P (5) 176*f*.
Lacina, B. See Chang, R. K.
Lacroix, R. See Bill, H.
Lacy, A. D. Greek Pottery in the Bronze Age, B (11) 389*b*.
Lad, R. A. Adsorption of water on sodium chloride — effect of prior exposure to hydrogen chloride, carbon dioxide, and water vapor, (4) 126*h*.
Ladell, J. See Abowitz, G.
La Due, A. W. See Fischer, H. G.
Lagaly, G. See Weiss, A.
Lagos, C. C. Luminescence of divalent europium in the BaO-MgO-P_2O_5 system, (10) 356*d*.
Lahajnar, G. See Blinc, R.
Lahav, N. See Banin, A.
Lahav, N., and Banin, A. Tactoid rearrangement and the optical density of montmorillonite suspensions during Na-Ca exchange reaction, (5) 200*j*.
Lahr, R. J., Evans, P. F., and Lees, H. D. Solid state storage device, P (11) 379*a*.
Laidler, K. J. See Muirhead-Gould, J. S.
Laidler, K. J., and Muirhead-Gould, J. S. Continuous dielectric model for hydration of monatomic ions, (4) 129*f*.
Laird, R. T. See Foster, D.
Laird, R. T., and Wickens, A. A. Moisture expansion of full-size bricks, (6) 214*d*.
L'Air Liquide, Societe Anonyme pour l'Etude et l'Exploitation des Procedes Georges Claude. Method for the production of a hard-porosity lime-silica porous body, P (2) 59*g*.
Laitinen, H. A. Polarography in molten salts, (4) 150*d*.
Lake, R. E., and Rees, D. Krypton-xenon flash tube for pumping a ruby laser, P (7) 256*g*.
Lakewood Brick & Tile Co. Apparatus for producing mottled brick, P (11) 372*f*.
Lakh, V. I. See Kuz'ma, Yu. B.
Lakshmanan, T. K. Photoconductive cell having high stability and dark resistance, P (8) 283*g*.
Lakshmanan, T. K., and Mitchell, J. M. Method of forming films of compounds having at least two anions by cathode sputtering, P (4) 114*f*.
Lakshminarayanan, G. R. See Janz, G. J.
Lal, R. B. Magnetic susceptibilities of group II, group VI semiconductor ZnO, (4) 143*j*.
Lalak, J. J. See Milch, A.
Lallement, R. Some electrical and magnetic properties of compounds of rare earths and actinides, (10) 360*d*.
LaLonde, R. E., and Anthony, G. H. Factors affecting slag penetration of refractory mortar joints, (1) 12*d*.

Lamb, F. E. See Atwood, G. E.
Lamb, F. W. See Reitmeier, R. E.
Lamb, I. E., and Harman, R. W. Method of testing transparent materials, P (4) 100*a*.
Lambden, R. L. See Dieman, W. R.
Lambe, J. J., and Vassell, W. C. Solid state electroluminescent device, P (8) 283*g*.
Lambe, K. A. D. See Lange, F. F.
Lambert, I. B., and Heier, K. S. Geochemical investigations of deep-seated rocks in the Australian shield, (4) 137*d*.
Lambert, I. B., Robertson, J. K., and Wyllie, P. J. Melting reactions in the system $KAlSi_2O_6$-SiO_2-H_2O to 18.5 kilobars, (10) 357*d*.
Lambert, K. T., and Prior, S. [Glass tube] grinding machines, P (10) 339*f*.
Lambert, W. G. Shear strain responsive strain gage elements and circuits for utilizing such elements, P (10) 348*a*.
Lambot, M. Insulation of glassmelting furnaces, (9) 308*j*.
Lambourne, R. See Doroszkowski, A.
LaMer, V. K. See Dixon, J. K.
Laming, J. See Jackson, B.
Lamoreaux, R. See Herzenberg, C. L.
Lampani, A., Colombo, M., and Margola, G. B. Abrading apparatus for finishing plates, P (1) 15*i*.
Lamprey, H. See Culbertson, J. B.
Lamy, A. Electrocast refractories for the glass factory, (1) 12*d*.
Land, C. E., and Haertling, G. H. Multiremanence ferroelectric ceramic memory element, P (6) 222*j*.
Landauer, R. W. Electrical shock wave devices and control thereof, P (6) 221*h*.
Landes, B. D., and Paricio, R. Means for indicating wear of ball mill lining bricks and the like, P (6) 225*b*.
Landes, B. D., Paricio, R., and Andrews, R. E. Liner [lifter bar] for grinding mills, P (11) 375*j*.
Landis, G. W. Collecting the dust, (8) 274*i*.
Landis Tool Co. Abrasive disk, P (5) 169*f*.
Landreth, J. O. High calcium limestone deposit in the Rattler Gulch area, Granite County, Montana, (2) 73*f*.
Landrum, T. C., and Waghorne, R. H. High temperature fluid coke electrodes, P (8) 279*c*.
Landry, R. J. ESR and optical absorption study of Mo^{3+} in a phosphate glass, (1) 7*b*.
Landsberg, P. T., and Johns, K. A. Problem of moving thermometers, (5) 187*f*.
Landt, U. See Juza, R.
Lane, F. O., Jr. See Julian, C. L.
Lane, G. See Hulbert, S. F.
Lane, J. E. Stability and transitions of surface phases, (9) 330*b*.
Lanewala, M. A., Bolton, A. P., and Pickert, P. E. Treatment of oxidatively regenerated molecular sieve catalysts, P (9) 317*g*.
Lang, A. R. Some recent applications of X-ray topography, B (1) 40*h*. X-ray moire topography of lattice defects in quartz, (9) 333*b*. See Frank, F. C.
Lang, G. K. See Harrison, F. W.
Lang, K. A. Diffusion furnace hearth plate, P (2) 72*f*.
Langdon, T. G. See Bell, R. L; Cropper, D. R.
Lange, F. F. Mathematical characterization of a general bicrystal, (1) 32*b*. Transgranular fracture studies on magnesium oxide bicrystals, (5) 202*i*.
Lange, F. F., and Lambe, K. A. D. Interaction between a crack front and cleavage steps, (4) 140*j*.
Lange, H. Determination of particle size by turbidity and refractive index increment, (4) 119*c*. Polishing method for the removal of material from monocrystalline semiconductor bodies, P (7) 257*h*.
Lange, J. R. Ceramic relief, (6) 205*j*.
Lange, K. R. Reactive organic molecules on silica surfaces, (4) 153*d*.
Langel, H. Thickness measurement of hot glass ribbons in flat glass manufacture, (9) 307*g*.
Langen, J. See Rossmaier, V.
Langenfeld, A. See Meffert, A.
Langenhoff, W. F. Th. See Rooymans, C. J. M.
Langer, G. Apparatus for acoustically detecting minute particles suspended in a gaseous atmosphere, P (6) 227*g*.
Langer, H. G. Process for preparing compounds containing silicon and fluorine, P (10) 349*b*.
Langley, L. W. See Richmond, J. F.
Langley, R. C. Composite coated heat reflectors and infrared lamp heaters equipped therewith, P (8) 275*b*. Space vehicle, P (6) 208*b*.
Langley, R. C., and Myers, H. Hydrogen diffusion and method for producing same, P (4) 109*c*.
Langlois, R. E. Fibrous bodies including strands and methods of producing such bodies, P (8) 277*i*.
Langmyhr, F. J., and Paus, P. E. Analysis of inorganic siliceous materials by atomic absorption spectrophotometry and the hydrofluoric acid decomposition technique (I) analysis of silicate rocks, (5) 186*j*; (IV) analysis of cements, clinkers, raw mixes, and siliceous limestones, (8) 284*i*; (V) analysis of ferrosilicon, (9) 314*j*; (VI) analysis of feldspars, (9) 314*j*; (VII) analysis of iron ores and slags, (9) 314*j*.
Langrock, P. See Bock, R.
Langrod, K., and Jones, R. L. Impregnation of graphite with refractory carbides, P (6) 217*b*.
Lankin, Yu. N. See Antonenko, V. M.
Lannan, J. L. Porcelain enameling range ware electrostatically, (1) 5*b*. Vignetting or highlighting practices after application by electrostatic spray, (7) 246*c*.
Lannoo, M., and Stoneham, A. M. Optical absorption of the neutral vacancy in diamond, (10) 357*j*.
Lanstrom, D. K. See Adler, R. P. I.
Lantelme, F. See Mecta, O. P.; Touray, J. C.
Lanz, R. See Cogliati, G.
Lanzavecchia, G. See Colombo, U.
Lapage, R., and Bunce, J. L. Heat of combustion of plutonium nitride, (4) 138*g*.
Lapin, V. V., and Solovova, I. P. Crystallization of phases and decomposition of melilite during cooling of molten blast-furnace slag, (6) 231*i*.
Laporte Titanium, Ltd. Manufacture of titanium dioxide, P (4) 124*d*.
Lapoujade, P., Lecrivain, L., and Marethеu, A. Testing and standardization of refractories, (1) 13*j*. Test methods and specifications in the refractory industry, (6) 216*j*.
Lapple, C. E. Particle classification device and method, P (7) 259*e*.
Lapshin, P. V. Method of manufacturing a three-component water-resisting binding agent, P (4) 92*j*.
Lapshov, Yu. K. See Samsonov, G. V.
Laptev, V. I. Discontinuous control of the molten glass level in the basin of a tank furnace, (2) 48*g*.
Lapteva, A. S., Bondarevskaya, E. A., and Merkulova, E. N. Gasometric microdetermination of nitrogen in boron nitride, (6) 226*i*.
LaQue, F. L. Corrosion tests and service performance, B (10) 366*a*.
Larach, S. Luminescent image device and combinations thereof with optical filters, P (10) 345*d*.
Larach, S., Shrader, R. E., and Yocom, P. N. Luminescent image device and combinations thereof with optical filters, P (10) 345*d*.
Larach, S., and Yocom, P. N. Phosphor and method of preparation thereof, P (11) 378*c*.
Lare, P. J. See Divecha, A. P.
Larkin, D. M. See Wood, D. L.
Larkins, F. P., and Fensham, P. J. Decomposition of nickel oxide, (4) 130*g*.
Larkins, T. H., Jr., Young, H. S., and Akin, G. A. Process for producing manganese dioxide, P (9) 317*e*.
La Rocque, A. P., and McNeil, G. Solid state device with reduced leakage current at *np* junctions over which electrodes pass, P (5) 185*b*.
Larrabee, G. B. See Clark, J. H.
Larsen, F. K., Christensen, A. N., and Rasmussen, S. E. Crystal structure of an ordered sodium tin germanium oxide hydroxide, (4) 130*a*.
Larsen, R. J. See Rodgers, J. T.
Larson, A. H. See Zunkel, A. D.
Larson, D. A. High-pressure metallic vapor discharge lamp including mercury and thallium iodide, P (6) 221*f*. Metal vapor discharge lamp, P (9) 312*g*.
Larson, H. R., and Elliott, J. F. Standard free energy of formation of certain sulfides of some transition elements and zinc, (1) 37*j*.
Larson, J. O., Winkler, R. A., and Guffy, J. C. Glass fusion method for X-ray fluorescence analysis, B (1) 40*j*.
Larson, T. D., Cady, P. D., and Malloy, J. J. Protected paste volume concept using new air-void measurement and distribution techniques, (5) 187*g*.
Larsson, I. F. Method for adjusting thin film resistors, P (6) 222*b*.
Larsson, R. Infrared absorption intensity of the ν_3 vibration of the UO_2^{2+} ion in nitrate and thiocyanate media, (9) 323*j*.
Laser, M. See Kaiser, G.; Knacke, O.
Lasher, G. J. Multistable device operating on the principle of stimulated emission of radiation, P (5) 184*b*.
Lashko, A. S. See Goncharov, V. P.
Laska, H. M., Doremus, R. H., and Jorgensen, P. J. Permeation, diffusion, and solubility of deuterium in Pyrex glass, (6) 210*h*.
Laskow, W. See Gatti, A.
La Soudure Electrique Autogene, Procedes Arcos. Coated electrode and process for electric arc welding, P (5) 171*j*.
Laubenheimer, H. Use of Posidonia shales Lias Epsilon from Brunswick-Hondelage for the manufacture of hydraulic cement and aeroconcrete, (4) 92*d*.
Laudelout, H., Van Bladel, R., Bolt, G. H., and Page, A. L. Thermodynamics of heterovalent cation exchange reactions in a montmorillonite clay, (9) 332*e*.
Laudise, R. A. See Kolb, E. D.; Marshall, D. J.; Wehmeier, F. H.
Laudise, R. A., and Marshall, D. J. Hydrothermal growth of potassium tantalate-potassium niobate mixed crystals and material so produced, P (7) 256*b*.
Lauegt, M., Scory, M., and Durif, A. Systems $Cu(PO_3)_2$-$TlPO_3$ and $Cu(PO_3)_2$-$RbPO_3$ — crystallographic data for $CuTl(PO_3)_3$ and $CuRb(PO_3)_3$, (9) 331*f*.
Laugier, J., and Martin, J. M. Phase relations between the two varieties of uranium sesquinitride, (10) 358*b*.
Laurenson, L. See Baker, M. A.
Lautenschlager, E. P., Hughes, T., and Brittain, J. O. Slip in hard-sphere CsCl models, (1) 37*c*.
Lautsyus, A. S., Meshkuotis, Yu. A., Tolutis, V., and Chyapas, A. F. Phase composition of thin layers in the system Cr-SiO, (9) 311*e*.
Laval, R. See Chartier, G.
Laverlochere, J. Application of activation analysis to refractory materials, (5) 187*a*.
Laves, F. See Bambauer, H. U.
Lavrentyev, A. V. See Derjaguin, B. V.
Lawless, K. R. See Swank, T. F.
Lawless, W. N. Ferroelectricity and antiferroelectricity in $BaTiO_3$, (1) 16*h*. Single-particle and equilibrium collective effects of hydroxyl impurities in KCl, (2) 83*d*.
Lawley, K. L. See Klein, D. L.
Lawn, B. R. See Frank, F. C.
Lawrence, D. E. Wide field technique for viewing rock textures, (9) 315*g*.
Lawrence, L. H. Noise diode having an alloy Zener junction, P (10) 345*c*.
Lawrence, R. M., and Kruh, R. F. X-ray diffraction studies of aqueous alkali-metal halide solutions, (4) 164*d*.
Laws, J. W., Jr. Heat transfer members and method of fabrication thereof, P (4) 99*g*.
Lawson, F. Tin oxide Sn_3O_4, (4) 162*j*.
Lax, B. See Kurtin, S.
Lay, K. W., and Carter, R. E. Time and length corrections in the analysis of the initial stages of diffusion-controlled sintering, (6) 239*b*.
Lay, L. A. See Barry, T. I.
Layden, G. See Galasso, F.
Layne, D. K. Treatment of glass with silsesquioxanes to improve durability of subsequent silicone treatments to washing, P (8) 278*c*.
Layton, M. M., and Herczog, A. Structure and crystallization of glasses of low network-former content, (8) 276*i*.
Lazebnik, Yu. D. See Kravchuk, T. A.
Leach, J. S. L., and Neufeld, P. Influence of electrical field on the mechanical properties of surface oxide layers, (2) 45*j*.
Leak, R. J., Brandenburg, J. T., and Behrens, M. D. Use of alumina-coated filaments in catalytic mufflers testing with single cylinder engine, (7) 260*e*.
Leake, J. A. See Shirane, G.
Leaman, T. R. See Garber, J. A.
Leask, M. J. M. See Cashion, J. D.
Leask, M. J. M., Maxwell, K. J., and Wanklyn, B. M. Nonstoichiometry in the rare-earth aluminum borates, (4) 146*h*.
Leatham, E. See Campbell, W. W.
Leaver, K. D. Magnetization ripple in ferromagnetic thin films, (2) 63*e*.
Lebda, E. and Olszewski, E. Fly ash as a cement substitute, (1) 2*d*.
Lebeda, S. See Harman, R.
Lebedeva, L. I., and Ptushkina, M. N. Determination of phosphorus and silicon (when both are present) by an IR-spectroscopy method, (2) 69*i*.
Lebedeva, L. S. See Gladneva, L. I.
Lecante, A. See Asquiedge, M.; Guillou, M.
Lecrivain, L. See Lapoujade, P.
Lecrivain, L., and Provost, G. Properties of plasma-sprayed borides and nitrides, (4) 93*f*.
Ledbetter, J. O. See Gloyna, E. F.
LeDuc, J. M. See Andre, E.; Besselere, J. P.
Lee, C. H. See Chu, T. L.
Lee, G. R. Magnetoelectric effect in yttrium iron garnet, (9) 310*j*.
Lee, H. A., Jr., and Rapp, C. F. Glass compositions for laser application, P (10) 339*b*. Laser glasses having a relatively low thermal expansion, P (10) 339*b*.
Lee, H. M., and Barrett, L. R. Diffusion of carbon and uranium in uranium carbide, (10) 352*e*. Measurements of self-diffusion in uranium carbide and their application to related activated processes, (4) 143*e*.
Lee, J. M. Perlite composition, porous low density perlite structure, and method of making same, P (8) 278*i*.
Lee, R. E., and White, R. M. Excitation of surface elastic waves by transient surface heating, (1) 29*d*.
Lee, R. G. See Szekely, J.
Lee, R. H. Tube wire electrode, P (2) 46*c*. See Annunziata, C.
Leeds, H. R., and McWilliams, R. J. Glassed heat exchanger construction, P (5) 172*a*.
Leeds & Northrup Co. Electronic radiant energy pyrometers, P (4) 121*g*. Laminated glass electrode diaphragm, P (11) 371*b*.
Leep, R. W. See Goosey, M. H.
Leers, K. J. See Hums, D.
Lees, H. D. See Lahr, R. J.
Leesona Corp. Glass yarn having controlled torsional forces, P (6) 212*f*.
Lefever, R. A. See Baughman, R. J.
Lefever, R. A., Chang, Nien-Chih, White, R. L., and Wickersheim, K. A. Europium doped yttrium oxide optical maser materials, P (10) 344*g*.
Leflet, H. A., Jr. Method of and apparatus for bending and tempering glass sheets, P (2) 53*f*. See Wampler, D. M.
Leflet, H. A., Jr., and Wampler, D. M. Glass bending furnace with partitions defining separate longitudinally disposed heating areas, P (10) 339*a*.
Le Floch, G. Study of the formation of heterojunctions CdTe-InSb, (8) 281*h*.
Legat, W. H. See Rosvold, W. C.

Legat, W. H., Russell, L. K., and Rosvold, W. C. Microcircuit with complementary dielectrically isolated mesa-type active elements, P (5) 184*h*.
Legendre, V. J. Vacuum seal for a thin beryllium X-ray window, P (4) 122*c*.
Leger, L. See Lelong, J.
Leger, L., and Bray, J. Phase separation in glass—nucleation of the crystallization of aluminosilicate glasses by spinodal decomposition into vitreous phases, (6) 210*i*.
Legeza, T. B., and Gautnier, W. D. Self-cleaning tip for airless spray guns, P (4) 118*i*.
Leggett, R. D. See Kulcinski, G. L.
Legras, C. See Lerner, P.
Lehman, H. S. Method for controlling the electrical characteristics of a semiconductor surface and product produced thereby, P (1) 18*b*. See Barson, F.
Lehmann, H. See Kupzog, E.
Lehmann, H., Abraham, D., and Farooq, M. K. Moisture expansion (I) kinetics and mechanisms in the literature, (9) 325*a*; (II) dynamic measurement, (11) 380*i*.
Lehmann, H., and Rauschenfels, E. New frost dilatometer for specimens up to the size of standard prisms, (7) 260*h*.
Lehmann, K. See Schmeiser, K.
Lehmann, W. Emission spectra of impurity activated (Zn,Cd) (S,Se,Te) phosphors (II) silver activated phosphors, (1) 29*f*; (III) self-activated phosphors, (4) 135*g*. Zinc oxide and zinc-cadmium oxide phosphors, (5) 203*g*.
Lehner, N. Refiring black- and red-figured Grecian vases [discolored by wartime conflagrations, etc.], (5) 170*b*.
Lehner, W. H. Method of inspecting all-glass multiple glazed units [for dew point], P (4) 100*b*.
Lehovec, K., and Schier, H. Method for inspecting semiconductor devices using electron mirror microscopy, P (2) 65*e*.
Lehr, G. J., Oelke, W. W., O'Connell, T. B., and Badger, A. E. Tempering glass between roughened glass contacting surfaces, P (4) 101*c*.
Lehr, P. See Gosse, G.
Lehrer, E., and Woelihaf, J. Continuous wet grinding of solid materials in tube mills, P (7) 259*e*.
Lehtinen, M. See Sahama, T. G.
Leibenzeder, S. See Merkel, H.
Leichter, P. See Knotik, K.
Leider, H. R. See Smith, D. K.
Leidheiser, H., Jr. See Kirn, J. F.
Leiga, A. G. See Drews, R. E.
Leiser, R. S. See Darr, D. E.
Leishman, E. G. See Oleson, R. W.
Leistner, C. J., and Radtke, A. W. Method of purifying graphite, P (4) 107*d*.
Leisure, R. G., and Bolef, D. I. Temperature dependence of ultrasonic paramagnetic resonance in MgO:Fe^{2+}, (4) 159*d*.
Leitch, H. See Iverson, H. G.
Leiter, H. A. See Crowe, K. R.
Leith, F. A. High frequency field effect transistor, P (4) 113*j*.
Leitnaker, J. M. See Lindemer, T. B.; Spear, K. E.
Leitsch, H. Shrunk film packing for pallets, (4) 118*b*.
Leitte, R. C. C., and Porto, S. P. S. Enhancement of Raman cross section in CdS due to resonant absorption, (2) 76*g*.
Leitz, Ernst, G.m.b.H. Optical crown glasses, P (9) 308*d*. Optical flint glasses, P (8) 278*d*.
Leko, V. K. Electrical properties and structure of lithium, sodium, and potassium silicate glasses, (10) 337*j*.
Lekus, M. Problems in coining international brand names, (10) 363*j*.
Lelak, J. W. Furnace roof construction [contour controlled], P (10) 342*d*.
Lele, R. V., and Ray, R. N. Leadless boron-free earthenware glazes (I), (10) 343*f*.
Lele, V. N. Chemicals from mineral resources of Saurashtra and Gujarat, (4) 123*g*.
Lell, E., Kreidl, N. J., and Hensler, J. R. Radiation effects in quartz, silica, and glasses, B (7) 272*g*.
Lellep, M. See Lundkvist, M.
Lellep, O. G., and Helming, B. Device for the periodic delivery of preheated material, P (7) 261*h*.
Lelong, J., and Leger, L. Possibilities of using the vacuum deposition of thin films in mirror making, (9) 306*g*.
Le Maitre, R. W. Chemical variation within and between volcanic rock series—statistical approach, (1) 25*h*.
Le Mat, Y. Zircon, chromium oxide, and mullite, (1) 8*e*.
Lempicki, A. See Brecher, C.
Lempicki, A., and Samelson, H. Comments on "Laser emission lines and materials," (2) 75*d*.
Lendvay, E. See Bertoti, I.
Lenev, L. M. See Novokhatskii, I. A.
Lengyel, G. See Brafman, O.
Lengyel, I. See Duma, G.
Lenk, P. See Schiller, S.
Lenning, R. L. Controlling residual stresses in cylindrical grinding, (4) 89*g*.
Lenzlinger, M., and Snow, E. H. Fowler-Nordheim tunneling into thermally grown SiO_2, (9) 310*f*.
Lenzo, P. V., Spencer, E. G., and Ballman, A. A. Optical activity and electrooptic effect in bismuth germanium oxide ($Bi_{12}GeO_{20}$), (1) 33*g*. Photoactivity in bismuth germanium oxide, (4) 149*f*.
Lenzo, P. V., Spencer, E. G., and Remeika, J. P. Some optical properties of lithium gallium oxide, (1) 37*d*.
Leombruno, W. J., Haggerty, J. S., and O'Brien, J. L. Structure and orientation of the second phase in ZrB_2 crystals, (5) 200*i*.
Leonard, A. See Fripiat, J. J.
Leonard, A. J., Van Cauwelaert, F., and Fripiat, J. J. Structure and properties of amorphous silicoaluminas (III) hydrated aluminas and transition aluminas, (4) 156*a*.
Leonhard, F. W. See O'Neal, J. E.
Leonidov, V. Ya., and Khitarov, N. I. New data on the thermodynamic properties of talc, (4) 146*e*.
Leonov, A. I. Role of surface phenomena in the kinetics of chemical reactions, sintering, and collective recrystallization of refractory oxides, (7) 268*h*.
Leontaritis, L. See Hans, G.
Lepeshova, V. I. See Budnikov, P. P.
Lepeuve, A. See Chadenson, P.
Leplane, D. C. Method for fabricating double-diffused semiconductive devices, P (8) 282*g*.
Lepicard, G., and Protas, J. Structural study of double oxide of manganese and calcium, orthorhombic $CaMn_2O_4$ (marokite), (1) 38*d*.
Lepselter, M. P. Method of fabricating semiconductor contacts, P (8) 282*h*. Method for making closely spaced conductive layers, P (11) 377*b*. Semiconductive device including beam leads, P (5) 185*h*. Semiconductor integrated circuitry with improved isolation between active and passive elements, P (4) 116*e*.
Lerner, I. See Schrader, M. E.
Lerner, P., Legras, C., and Dumas, J. P. Stoichiometry of single crystals of lithium metaniobate, (9) 330*i*.
Lerner, R. S., and Kister, E. G. Thermophysical properties of aqueous clay suspensions, (6) 239*j*.
Lerner, S. See White, J. G.
Leroi, G. E. See Miller, R. E.
Lescroart, L. C. J., and Marlot, P. L. M. Devices for the continuous manufacture of tiling sheets, P (7) 254*a*.
Lescroel, Y. See Pierrot, A.
Lesk, I. A. Method for making [lapping] thin semiconductor dice, P (8) 283*a*. Semiconductor switching devices with a tunnel junction diode in series with the gate electrode, P (6) 223*j*.
Lesnikov, A. K. See Vakhrameev, V. I.
Lesnyak, K. See Briyak, E.
Lester, J. E., and Somorjai, G. A. Effect of dislocations on vaporization rate of NaCl single crystals, (2) 75*j*. Studies of the evaporation mechanism of sodium chloride single crystals, (9) 330*e*.
Lester, M. See Richardson, H. M.
Lesueur, D., and Bloch, J. Effects of irradiation by fission products, (2) 73*e*.
Letort, Y. Cracking of refractory lining under the influence of stresses and thermal shock, (4) 103*c*. Installation and use of refractories, (1) 12*i*.
Letter, E. C. Method for forming strong metallic bonds to lead-containing glass, P (5) 175*d*. Method of making infrared transmitting element, P (6) 213*c*. See Hensler, J. R.
Leung, K. Y. See Calvo, C.
Levene, L. Method of imparting abrasion and scratch resistance to glass surfaces and glass articles produced thereby, P (4) 99*j*. Method of rendering glass surfaces abrasion and scratch resistant, P (7) 249*a*. Titanium oxide compounds, P (4) 126*b*. See Kitaj, W.
Levene, L., and Thomas, I. M. Abrasion resistant glass surfaces, P (7) 248*g*.
Levengood, W. C. Dislocations and surface flaws on glass, (9) 305*a*. Stress induced defects in vitreous calcium aluminates, (1) 38*a*.
Leventhal, E. A., Neumark, G. F., and Rittner, E. S. Scintillation detector using a single crystal of gallium arsenide, P (4) 116*j*.
Leveque, M. Thermal energy consumption of glass furnaces, (2) 52*c*.
Leversant, G. R., and Sullivan, C. P. Effect of dispersed hard particles on the high-strain fatigue behavior of nickel at room temperature, (6) 232*b*.
Levick, Swift & Sons, Ltd. Permanent magnets, P (9) 313*a*.
Levillain, J., and Bardonnet, P. Lens trimming machines, P (10) 399*h*.
Levin, D. I., and Nikulina, L. N. Methods of studying fusion in porcelain glazes, (6) 219*i*.
Levin, E. M. X-ray determination of the thermal expansion of silver nitrate, (4) 121*a*.
Levin, E. M., Robbins, C. R., and McMurdie, H. F. Phase Diagrams for Ceramists—1969 Supplement, B (11) 390*d*.
Levin, I. W. See Abramowitz, S.
Levin, N. D. Color tube with mask interior peripheral shield of treated steel foil for improved heat radiation, P (2) 64*i*.
Levin, V. Ya. See Mitin, B. S.
Levine, A. K. See Gashurov, G.; Palilla, F. C.
Levine, B. H. Survey of methods of testing the strength of decarburized steel after porcelain enamel firing, (1) 5*c*.
Levine, E., and Tauber, R. N. Preparation and examination of PbTe by transmission electron microscopy, (4) 150*a*.
Levine, S. L. Quantitative determination of binder and lubricant in ceramic materials by TGA, (5) 187*j*.
Levinson, A. A. See Tettenhorst, R.
Levinstein, H. J. See Bergman, J. G.; Chen, P. S.; Geusic, J. E.; Rubin, J. J.; Smith, Richard G.; Testardi, L. R.
Levinstein, H. J., and Guggenheim, H. J. Dislocations in $RbFeF_3$, (7) 265*e*.
Levinstein, H. J., Guggenheim, H. J., and Capio, C. D. Phase transformations and magnetic domains in $RbFeF_3$, (7) 267*j*.
Levinstein, M. A. See Foldes, S.
Levishko, A. A. Bearing device for a vertical shaft of a crushing cone of a gyratory crusher, P (4) 124*h*.
Levitan, J., Draley, J. E., and Van Drunen, C. J. Low-pressure oxidation of zirconium, (4) 143*b*.
Levitskii, V. K. See Sobolev, G. P.
Levitt, R. S., and Zwicker, W. K. Infrared spectra of silicon nitride deposited on gallium arsenide, (4) 110*j*.
Levy, P. W. See Herley, P. J.
Levy, R. M., Bauer, D. J., and Roth, J. F. Effect of thermal aging on the physical properties of activated alumina, (1) 20*a*.
Levy, S. A., and Gashler, R. Origin of lamellas in high resistivity KTN [$KTa_{0.65}Nb_{0.35}O_3$], (5) 198*a*.
Lewicki, G., and Mead, C. A. Currents through thin films of aluminum nitride, (9) 319*a*.
Lewis, A. See Provance, J. D.
Lewis, B., and Stirland, D. J. Growth and morphology of epitaxial lead telluride deposits on rock salt, (9) 322*i*.
Lewis, D. C., and Westwood, W. D. Method of making ferrimagnetic films by cathodic sputtering, P (7) 257*e*.
Lewis, E. S., Jr. Method of drawing glass articles, P (5) 175*c*.
Lewis, E. T. See Sewell, F. A., Jr.
Lewis, E. W., Mills, J. H., and McNickle, B. F. Method and package for producing dental molds or molding material, P (2) 61*a*.
Lewis, G. K., Jr., and Drickamer, H. G. High-pressure Moessbauer studies of ^{57}Fe in silicate and phosphate glasses, (5) 172*g*.
Lewis, J. E. See Foster, L. M.
Lewis, J. M., and Verhine, C. J. Drying particulate material, P (2) 67*h*.
Lewis, M. F., and Patterson, E. Microwave phonon attenuation in magnesium aluminate spinel, (4) 144*d*.
Lewis, M. H. Defect structure and mechanical properties of spinel single crystals, (2) 75*j*.
Lewis, T. W., II. See Henry, G. R.
Lexin, B. G. See Mazurov, D. J.
Lexington Laboratories, Inc. Epitaxially coating ruby with doped alumina, P (9) 312*g*. Method for controlling the feed of nuclei in the production of crystals by vapor deposition, P (4) 114*a*. Preparation of alumina crystals from a vapor phase reaction by monitoring the spectral scattering of light, P (9) 317*a*. Process for manufacture of porous abrasive articles, P (4) 90*a*.
Leyarovska, L. See Peshev, P.
Lherault, J. A. D. P., and Nuckols, D. E. Tile assembly for radiant gas burners, P (7) 253*b*.
Li, C. See Dixon, J. K.
Li, C. T. See Weaver, E. A.
Li, Che-Yu. See Tabor, J. B.
Li, Kun. See Simkovich, A.
Li, P. See Williamson, K.
Li, P. C., Pontarelli, D. A., Olson, O. H., and Schwartz, M. A. Fused quartz fiber optics for ultraviolet transmission, (5) 172*f*.
Liass, A. M., and Borsook, P. A. Liquid mixes for foundry cores and molds and method of manufacturing foundry cores and molds from same, P (5) 178*i*.
Libbey-Owens-Ford Glass Co. Apparatus for bending glass sheets, P (5) 174*f*, P (6) 212*b*. Apparatus for bending glass sheets with aligning means, P (11) 370*h*. Apparatus for minimizing open bottom blisters on float glass, P (6) 212*e*. Apparatus for press bending glass sheets, P (4) 98*e*. Apparatus for producing multiple sheet glazing units, P (7) 248*i*. Drilling machines [sheet glass], P (11) 371*e*. Edge grinding machine [plate glass], P (9) 307*c*. Glass bending furnace, P (6) 212*a*. Glass bending furnace with partitions defining separate longitudinally disposed heating areas, P (10) 339*a*. Glass sheet [air] tempering apparatus, P (10) 339*f*. Glass tank coolers, P (11) 371*j*. Laminated transparent panel incorporating electrical heating wires and method of producing same, P (2) 53*d*. Manufacture of a continuous glass sheet on a molten metal bath, P (8) 277*e*. Method and apparatus for bending glass plates for grinding and polishing, P (4) 99*c*. Method of and apparatus for bending and tempering glass sheets, P (2) 53*f*. Method of feeding glass batch material, P (7) 249*d*. Mounting glass sheets, P (11) 372*a*. Oscillatory [air] spray tempering apparatus, P (10) 339*h*. Seal for glass furnace joints, P (11) 372*b*. Sheet glass manufacturer, P (4) 101*e*. Tempering glass

between roughened glass contacting surfaces, P (4) 101*c*. Transparent articles coated with gold, chromium, and germanium alloy film, P (1) 11*e*.
Liberty, K. V. See Fleet, B.
Licentia Patent-Verwaltungs G.m.b.H. Controllable semiconductor rectifier unit, P (6) 221*g*. Four-zone semiconductor rectifier with spaced regions in one outer zone, P (2) 64*i*.
Lichodziejewski, W. L. See Johnson, B. A.
Lichter, B. D., and Sommelet, P. Thermal properties of $A^{III}B^{V}$ compounds (I) high-temperature heat contents and heats of fusion of InSb, GaSb, and AlSb; (II) high-temperature heat contents and heats of fusion of InAs and GaAs, (10) 362*g*.
Lichtner, E., and Szalek, G. Effect of alkali, especially of K^+ addition, on the transition of γ-Fe_2O_3 into α-Fe_2O_3, (11) 384*c*.
Lida, Yoshio. See Hayakawa, Shigeru.
Lide, D. R., Jr. See Matsumura, Chi.
Lidiard, A. B. Point defects in ceramics, (8) 296*j*. Point defects in solids, (4) 150*c*. See Boswarva, I. M.; Norgett, M. J.
Lidiard, A. B., and Nelson, R. S. Gas bubbles in solids, (2) 77*a*.
Lidstroem, L. Surface and bond-forming properties of quartz and silicate minerals and their application in mineral processing techniques, (6) 238*j*.
Liebermann, O. Synthesis of dolomite, (4) 158*b*.
Liebler, C. F. See Caldwell, C. W.
Liebmann, H. J. See Smith, W. D.
Lieck, K. Heat and energy balance of a tunnel kiln (I,II), (10) 348*c*.
Lieth, R. M. A., Heijligers, H. J. M., and van der Heijden, C. W. M. *P-T-X* phase diagram of the system Ga-S, (1) 35*e*.
Light, T. B., Hull, E. M., and Gereth, R. Formation of thick semi-insulating GaAs films by flash evaporation, (5) 186*a*.
Light, T. B., and Wagner, C. N. J. Structure of vapor-quenched Ag-Ge films, (9) 311*d*.
Lightfoot, E. N. See Scattergood, E. M.
Lighty, P. E. Saturable solid state nonrectifying switching device, P (4) 116*i*. See Shanefield, D. J.
Ligon, E. R., De Gasperi, F. E., and Reed, N. D. Ceramic molding apparatus, P (10) 340*e*.
Lilley, E. See Barsis, E.
Lim, M., and Searcy, A. W. Vapor pressure and heat of sublimation of cerium(III) fluoride, (4) 163*f*.
Limar, T. F. See Golub, A. M.
Limes, R. W. Refractory practice in basic oxygen furnaces, (4) 105*g*.
Lin, F. C. M. See Knochel, W. J.
Lin, H. C. See Foster, W. R.
Lin, H. C., and Foster, W. R. Studies in the system BaO-Al_2O_3-SiO_2 (I) polymorphism of celsian, (6) 238*d*.
Lin, Hung C. Method of making complementary transistor structure, P (4) 115*a*. Semiconductor integrated circuit, P (7) 258*d*.
Lin, Hung C., and Karcher, E. A. Semiconductor structure particularly for performing unipolar transistor functions in integrated circuits, P (4) 116*i*.
Lin, Hung C., and Shiota, P. S. Insulated-gate field-effect transistor structure with reduced current leakage, P (7) 256*d*.
Lin, Sin-Shong. See Stock, S. J.
Lin, W. C. See Herring, F. G.
Linares, R. C. Epitaxial growth of narrow line width yttrium iron garnet films, (7) 254*g*. Growth of cubic zinc sulfide from molten lead chloride, (2) 77*f*. See Schroeder, J. B.
Linares, R. C., and Sigsway, R. L. Some optical defects in barium sodium niobate, (8) 298*c*.
Lincoln Electric Co. Tubular welding electrode, P (11) 369*c*.
Lind, J. E., Jr. See Morrison, G.
Linde, R. K., and DeCarli, P. S. Polymorphic behavior of titania under dynamic loading, (10) 358*h*.
Lindemer, T. B., Allen, M. D., and Leitnaker, J. M. Kinetics of the graphite-uranium dioxide reaction from 1400° to 1756°C, (7) 267*i*.
Linden Laboratories, Inc. Base mounted piezoelectric transducer assembly having intermediate stress absorbing member, P (7) 255*f*.
Lindenberger, W. A. Sealed reed switch with adjustable reed, P (5) 185*f*.
Lindenthal, J. R. See Garfinkel, H. M.
Lindholm, R. C. Detrital dolomite in Onondaga limestone (Middle Devonian) of New York —its implications to the dolomite question, (9) 319*h*.
Lindley, W. T. See Donnelly, J. P.
Lindmayer, J. See Busen, K. M.
Lindmayer, J., Garnache, R. R., and Casey, J. J. Method of making a transistor with a very thin diffused base and an epitaxially grown emitter, P (2) 65*h*.
Lindmayer, J., and Wrigley, C. Y. Negative resistance diode, P (2) 66*c*.
Lindmayer, J., Wrigley, C. Y., and Garnache, R. R. Method [epitaxial growth] of making a narrow base transistor, P (10) 345*f*.
Lindquist, R. H., and Mulaskey, B. F. Process for producing ferrimagnetic materials, P (5) 185*d*.
Lindqvist, O. Refinement of the structure of α-TeO_2, (9) 328*g*.
Lindsley, D. H., and Munro, J. L. Subsolidus reactions along the join hedenbergite-ferrosilite, (10) 361*f*.
Lindsley, D. H., Speidel, D. H., and Nafziger, R. H. *P-T-f_{O_2}* relations in the system Fe-O-SiO_2, (10) 359*d*.
Lindsley, J. F. See Sanborn, W. E.
Lindstrom, R. E. See Bauer, D. J.
Linebaugh, J. T. See Cornelison, B.
Linford, H. B. See Dixon, J. K.
Linford, R. G. See Waterfield, C. G.
Linger, K. R., and Holloway, D. G. Fracture energy of glass, (9) 305*f*.
Lingl, H., Jr. Fully automatic palletizing and drying in the heavy clay industry, (7) 250*a*.
Lingo, R. W. See Cropp, D. I.
Linnett, J. W. See Dickens, P. G.
Linning, D. L. Nuclear reactor fuel elements, P (5) 179*g*.
Linton, H. R. Inorganic blue to green pigments, P (9) 317*d*.
Linz, A. See Shirane, G.
Lipatova, N. P. See Morozov, I. S.
Lipchanskaya, R. V., and Demichev, S. A. Development of technology for production of luminescent hardened glass panels, (1) 6*f*.
Lipinsky, F. A. Burner for liquid fuel, P (8) 286*f*.
Lipman, P. W., Christiansen, R. L., and Van Alstine, R. E. Retention of alkalis by calc-alkalic rhyolites during crystallization and hydration, (10) 359*h*.
Lipp, A. Boron-carbon-silicon alloy and method of producing the same, P (8) 279*j*. Process for the manufacture of alkali metal borides, P (1) 24*d*.
Lippmann, F. Comparison of crystal structure of norsethite, $BaMg(CO_3)_2$, with dolomite, $CaMg(CO_3)_2$, (6) 231*e*.
Lipschutz, M. E., and Jaeger, R. R. Shock-induced preferred disorder in solids, (10) 360*g*.
Lipscomb, W. N. See Hegstrom, R. A.
Lipson, H. See Bicknell, J. A.
Lipson, H. G., Kahan, A., Adamski, J. A., Farrell, E., Redman, M. J., and Kawamura, J. Growth and characterization of variable stoichiometry spinels, (9) 322*c*.
Llrones, N. G. Method for molding of glass and ceramic materials, P (5) 175*f*.
Lishanskii, B. A., Mikhailov, N. V., and Rebinder, P. A. Physicochemical mechanics of concrete — scientific basis of vibration displacement of concrete mixtures, (8) 274*e*.
Lisovskii, L. P. See Ivanovskii, G. F.
List, H. Piezoelectric pressure transducer, P (11) 378*e*.
List, H., Zeiringer, R., and Hatschek, R. Piezoelectric pressure transducer and process for its manufacture, P (5) 184*h*.
List, K. H., and Noeltner, G. Apparatus for mechanically after-dehumidifying and further treating filter press cakes of pigment or dispersion dyes, P (11) 379*d*.
List, W. F. See Schuster, M. A.
Lister, R. R. Investigation into failure mechanisms in aluminosilicate blast furnace boshes, (7) 250*j*.
Litomisky, J., Kolinsky, M., Paukner, O., Drahovzalova, M., Zitova-Nemcova, H., and Horacek, S. Iron determination in high purity quartz by emission spectral analysis, (5) 187*a*.
Littin, R. J. Gypsum wallboard, P (11) 368*e*.
Little, A. See Shaw, D.
Little, J. R., and Sanford, E. A. Semicrystallized ground coats and enameled articles manufactured therefrom, P (11) 369*c*.
Little, Arthur D., Inc. Pyrometic device, P (7) 261*a*. Rotating [telescopic] sectioned furnace, P (7) 261*h*. Thin-film cold cathode, P (8) 284*a*.
Litton Precision Products, Inc. Method and apparatus for blowing cores using microwave energy, P (6) 217*f*.
Litvan, G. G. See Antoniou, A. A.
Litvinov, I. P. See Tobolov, P. N.
Litvinov, P. I. See Bogdanova, G. S.
Litvinov, P. I., and Loginova, T. Z. Region of glass formation in the system SiO_2-Ga_2O_3-MgO, (2) 50*i*.
Litvinova, G. N., and Bukhalova, G. A. System of the chlorides and fluorides of sodium, potassium, and calcium, (4) 158*i*.
Litvinova, Z. S. See Ved. E. I.
Liu, Kuo-Yuan. See Fedorov, P. I.
Liu, Y-Z., Moll, J. L., and Spicer, W. E. Effects of heat cleaning on the photoemission properties of GaAs surfaces, (10) 343*j*.
Livey, D. T. See Hill, N. A.; O'Neill, J. S.
Livingston, H. K., and Luk, D. C. Dimensionality and mechanical properties of inorganic polymers, (4) 131*h*.
Livingston, J. D. See Alden, T. H.
Livingstone, R. L. See Boicey, J. H.
LKB-Produkter Aktiebolag. Fluorescence radiation device radiating at 280 nm wavelength and method of making same, P (5) 188*f*.
Llacer, J. Lithium drifted semiconductor radiation detector, P (4) 113*i*.
Llewelyn, G., and Ubank, R. G. Method of producing refractory metal articles, P (8) 275*g*.
Lloyd, H. Fuel element fabrication, P (4) 106*g*.
Lloyd, M. H., and Haire, R. G. Process for preparing plutonia aquasols, P (11) 382*h*.
Lloyd, M. K. See Conley, R. F.
Lloyd, R. H. F. See Domenico, R. J.
Loasby, R. G. See Martin, A. J.
Locardi, B. See Gottardi, V.
Lochner, H. P., and Dersin, H. Method of epitaxially growing layers of semiconducting compounds, P (11) 377*i*.
Locker, L. D., and Skolnick, L. P. Sputtering of oxide films in plasma anodization of aluminum, (4) 111*a*.
Lockheed Aircraft Corp. Ferrimagnetic pressure transducer, P (6) 221*a*. Method of coating articles with titanium and related metals and the article produced, P (8) 280*f*.
Loesel, B. Decrease of crystallization temperature of vitroceramics, (11) 369*d*. Kinetics of mullite formation in the system aluminum fluoride-silica (II) mechanism of mullite formation with anhydrous aluminum fluoride, (5) 196*h*. Possible technical developments in the manufacture of fireclay refractory materials (III) mechanism of the synthesis of mullite in the system kaolinite-aluminum fluoride, (4) 105*d*. Processes during the calcination of ceramic products (II) effect of small quantities of AlF_3 on the formation of phases during the calcination of Grossalmerode clay, (5) 199*b*.
Loeffler, J. Physical and chemical reactions leading to joint corrosion and upward drilling in glass tanks (II), (9) 306*e*.
Loehr, C. E. See Darr, D. E.
Loewenschuss, A., Ron, A., and Schnepp, O. Vibrational spectra and thermodynamics of the zinc halides, (6) 239*e*.
Loewenstein, K. L., and Dowd, J. Investigation of the relationship between glass fiber tensile strength, the temperature of the glass from which the fiber is drawn, and fiber diameter, (6) 209*f*.
Logan, R. A., White, H. G., and Wiegmann, W. Efficient green electroluminescence in nitrogen-doped GaP *pn* junctions, (9) 320*f*.
Loginova, T. Z. See Litvinov, P. I.
Logothetis, E. M. See Lye, R. G.
Lohmeyer, S. Behavior of porcelain colors in wash tests, (1) 15*b*. Optical evaluation of the change in decoration on porcelain during machine washing, (11) 375*f*.
Loiacono, G. M., and Nassau, K. Growth of lithium niobate crystals, P (8) 282*i*. Lithium metaniobate crystalline growth from melt containing magnesium oxide, P (4) 113*i*.
Loktev, A. M. See Kushakovskii, V. I.
Lombaard, J. C. See Henning, C. A. O.
Lonadier, F. D., Brown, W. B., Fushimi, F. C., and Silver, G. L. Ion exchange method for preparing metal oxide microspheres, P (7) 262*i*.
Long, B. Flat glass and method and apparatus for making flat glass, P (4) 98*g*. Flat glass sheet and method and apparatus for making sheet, P (4) 98*g*. Manufacture of a continuous glass sheet on a molten metal bath, P (8) 277*e*.
Long, J. V. P. See Sweatman, T. R.
Long, L. See Murthy, M. K.
Long, R. A. Ceramic structural composite, P (11) 374*f*.
Long, R. A., and Jones, R. A. Filament reinforced metal composites for gas turbine blades, P (11) 374*i*.
Longenecker, L. S. Furnace suspended skimmer wall, P (1) 10*c*.
Longford, J. I. Variance and other measures of line broadening in powder diffractometry (II) determination of particle size, (9) 315*f*.
Longini, R. L. High-speed semiconductor switch, P (1) 18*h*.
Longo, F. N. See Durmann, G.
Longo, J. M. See Kafalas, J. A.; Raccah, P. M.
Longo, J. M., and Kafalas, J. A. Pressure-induced structural changes in the system $Ba_{1-x}Sr_xRuO_3$, (2) 82*e*.
Longo, J. M., Raccah, P. M., and Goodenough, J. B. $Pb_2M_2O_{7-\delta}$ (M=Ru,Ir,Re) — preparation and properties of oxygen deficient pyrochlores, (10) 358*h*.
Longo, J. M., and Sleight, A. W. Characterization and structure of $La_4Re_6O_{19}$ — a new metal cluster compound, (11) 383*h*.
Lonza-Werke G.m.b.H. Preparation of hexagonal boron nitride, P (4) 107*a*.
Loomis, A. A. Lunar and planetary petrographic microscope, (8) 285*f*.
Loomis, D. G. Isostatic pressing as a production process, (4) 108*h*.
Loose, G. H. Stressed hermetic seal and method of making said seal, P (7) 249*f*.
Lopacki, J. Method of stabilizing resistance in semiconductor manufacture, P (8) 283*e*.
Lopato, L. M. See Tresvyatskii, S. G.
Loral Corp. Ferrimagnetic couplers employing a transition from air dielectric waveguide to solid dielectric waveguide, P (4) 113*b*.
Lorant, M. Ceramics from liquids, (5) 189*j*.
Lorch, E. Neutron diffraction by germania, silica, and radiation-damaged silica glasses, (7) 247*i*.
Lord, P. A. See Akmenkalns, I. G.
Lorec, S. Determination of fluorine in silicates, (4) 119*b*.
Lorenz, M. R. See Onton, A.
Lorenz, P. K. See Janz, G. J.
Lorenzelli, R. See de Novion, C. H.
Loriers, J. See Makram, H.
Lorken, H. Apparatus for manipulating bottles or the like, P (10) 338*g*.
L.O.R. Lentilles Ophtalmiques Rationnelles So-

ciete Anonyme. Preformed blank for multifocal lens, P (2) 54*a*.

Loro, A. Fabrication of semiconductor devices, P (9) 312*h*.

Loro, A., and Rosenbaum, S. D. Semiconductor devices, P (2) 66*e*.

Losenske, C. See Hueter, L.

Losev, N. F., Smagunova, A. N., Pavlinskii, G. V., Afonin, V. P., Gunicheva, T. N., and Revenko, A. G. Modern methods of X-ray fluorescence analysis, (2) 70*h*.

Loshkarev, B. A., and Sermirikov, I. S. Influence of oxides of different valence on certain properties of ceramics in the system ZnO-TiO_2, (2) 62*i*.

Lotemp Ignition, Inc. Spark plug with an annular heat dam recess in the insulator nose, P (8) 280*e*.

Lotgering, F. K., and van Stapele, R. P. Cation-anion distances in chalcogenide spinels, (7) 264*b*. Magnetic and electrical properties of copper containing sulfides and selenides with spinel structure, (4) 143*e*.

Lothaller, W. E. Glow-discharge tubes containing a radioactive primer, P (11) 376*h*.

Lothrop, R. P. See Goulding, F. S.

Lotsberg, O. Electrical glass melting in pot furnaces with Kanthal-Super elements, (9) 305*c*.

Lott, H., Jr., See Wilson, W. L.

Lott, J. L. See Naus, D. J.

Lott, J. L., and Kesler, C. E. Service behavior of concrete for radiation shielding, (11) 368*d*.

Lotz, J. Separation [scoring] of individual wafers of a semiconductor disk, P (11) 378*h*.

Lou, F. H., and Baillentyne, D. W. G. Visible and ultraviolet emission and absorption spectra of $MgAl_2O_4$:Cr, (5) 203*c*.

Loub, J., and Rosicky, J. Thermal decomposition of orthotelluric acid, (5) 182*c*.

Louda, G. New methods of packing wall tiles, (4) 108*e*.

Louden, W. C. Niobium end seal, P (9) 313*i*. See Sarver, J. F.

Loukes, D. G., and Buckley, E. A. Method of coloring glass, P (7) 249*c*.

Loukes, D. G., and Hardman, J. M. Oxidation method of producing glass having an increased breaking strength, P (10) 339*h*.

Loukes, D. G., and Smith, R. Method of forming a glass sheet on a molten metal bath, P (5) 175*c*.

Louw, H. N. J. See Van Der Walt, C. M.

Love, J. A., III, and Sizelove, J. R. Low ohmic semiconductor tuned narrow bandpass barrier photodiode, P (9) 312*f*.

Lovegreen, A. T. Classification of granular materials, P (8) 287*f*.

Lovelace, B. K. See Granberry, D. S.

Loveland, W. See Warshaw, S.

Lovering, D. G. See Inman, D.

Loveshaw Corp. Marble sorter selectively rejectable of misshapen marbles and fragments thereof, P (4) 99*b*.

Lovreck, B. See Moslavac, K.

Low, M. J. D. See Abrams, L.

Low, M. J. D., and Ramasubramanian, N. Dehydration of porous glass, (4) 95*e*. Role of surface boron as adsorption center for the sorption of water by porous glass, (4) 97*e*.

Low, M. J. D., Ramasubramanian, N., and Ramamurthy, P. Reaction of HF with porous glass, (6) 211*c*.

Lowe, J. H. See Oshida, O. A.

Lowman, R. F. See Hammond, V. J.

Lown, D. A., Thirsk, H. R., and Wynne-Jones, L. Effect of pressure on ionization equilibria in water at 25°C, (11) 384*a*.

Lowsky, W. See Scholze, H.

Lozier, D. E. See Kizer, D. E.

Lu, Chih-Shun. See Milgram, A. A.

Lu, Wei-Chen, Ree, Taikyue, Gerrard, V. G., and Eyring, H. Significant-structure theory applied to molten salts, (6) 237*e*.

Lu, W. K. See Nabi, G.

Lu, W-K. See Tyrolerova, P.

Lubatti, E., and Pappalardo, S. Production of boron nitride, P (5) 179*d*.

Lubey, J. Method of molding shaped refractory bodies having an attached spacer of nonmetallic sheet material, P (2) 59*d*.

Lublin, P. See Aia, M. A.

Lucas, Joseph, (Industries), Ltd. Semiconductor devices, P (4) 116*e*.

Lucas, L. High-voltage semiconductor diode with ceramic envelope, P (4) 113*c*.

Luchsinger, E. B. See Oldham, K. B.

Luciani, L., and Corsi, G. Crystalline $TiCl_3$ and method of preparing same, P (11) 382*j*. Preparation of delta form crystalline titanium trichloride, P (9) 317*b*.

Lucy, W. See Crocker, B. S.

Ludlow, I. K. Spin-orbit coupling and stress spectra of trigonal color centers in magnesium oxide, (4) 155*h*.

Ludovici, B. F. See Megla, G. K.

Ludwig, P. F. Foamed silicates—slags and glass, (4) 104*c*.

Luebke, D. V. Preparation of zirconia and hafnia sols, P (8) 288*c*.

Lueck, A. M. Film thickness monitoring apparatus, P (1) 22*b*.

Luecke, K. See Nickel, H.

Lueth, H. See Heiland, G.

Luft, H. Substrates and "snapstrates" made of alumina ceramics, (7) 255*e*.

Luhrs, M. E. See Bracken, A. T.

Luk, D. C. See Livingston, H. K.

Lukes, R. M. See Abolins, V.

Lukin, E. S. See Bakunov, V. S.

Luk'yanov, A. E. See Spivak, G. V.

Lukyanovich, V. M. See Derjaguin, B. V.

Lumley, J. L., and Jordan, E. P. Thermistor and method of manufacture, P (4) 117*d*.

Lumley, R. M. Controlled separation of brittle materials using a laser, (10) 343*j*.

Lummus Co. Preparation of alkali metal carbonates from the corresponding sulfates or sulfides, P (1) 24*c*. Process for producing a mixed oxide oxidation catalyst having improved selectivity, P (1) 24*b*.

Lumsden, D. N., and Pelletier, B. R. Petrology of the Grimsby sandstone (Lower Silurian) of Ontario and New York, (11) 386*d*.

Lund, H. H. Increase strength by fine grinding, (8) 278*g*.

Lundkvist, M. Conductance and equilibrium studies on the system Se-Cl (I) influence of Cl on the conductivity of liquid Se, (7) 264*c*.

Lundkvist, M., and Lellep, M. Conductance and equilibrium studies on the system Se-Cl (II), (7) 264*d*.

Lundquist, R. H. See Ando, K. J.

Lundqvist, S. See Burstein, E.

Lundstroem, T., and Tansuriwongs, P. New hafnium phosphides, (8) 295*d*.

Lundstrom, T. See Andersson, S.

Lundstrom, T., and Snell, P. O. Studies of crystal structures and phase relations in the Ti-P system, (4) 156*g*.

Lundy, T. S. See Reimann, D. K.

Lundy, T. S., and Pawel, R. E. Effects of short-circuiting paths on diffusion coefficient measurements, (7) 265*a*.

Lunina, G. E. Photocolorimetric determination of calcium in minerals with the aid of Arsenazo, (6) 226*j*.

Lunkwitz, H. D. See Asmus, E.

Lunsford, J. H. EPR spectra of radicals formed when NO_2 is adsorbed on magnesium oxide, (5) 194*e*.

Luova, P., and Muurinen, M. Anomalies in the structure of KCl-NaCl solid solutions as revealed by enthalpies of crystallization, (10) 350*c*.

Lusk, D. I. See Hoganson, D. K.

Luszcz, S. See Witt, F.

Luteijn, A. I. See Berghout, C. W.

Luth, W. C. Systems $NaAlSi_3O_8$-SiO_2 and $KAlSi_3O_8$-SiO_2 to 20 kbars and the relation between H_2O content, P_{H_2O} and P_{total} in granitic magmas, (11) 387*g*.

Luther, L. C., and Roccasecca, D. D. Epitaxial growth of zinc- and cadium-doped gallium phosphide by gallium chloride vapor transport, (10) 353*e*.

Luthra, J. See Primak, W.

Lutwitzi, L. E., and Gerlach, J. L. Process for preparing alkali metal aluminate tetrahydrate crystals, P (5) 191*f*.

Lutz, E. Method and article for making switchable semiconductor elements, P (6) 222*c*. See Glueck, R.

Lux, B. See Gillot, J.

Luxon, J. T., and Summitt, R. Interpretation of the infrared absorption spectra of stannic oxide and titanium dioxide (rutile) powders, (10) 355*h*.

Luyckx, A. See Van Hove, H.

Luyckx, S. B. Microscopic aspects of fracture in WC-Co alloys, (1) 32*e*.

Lybarger, R. A. Wire beader, P (11) 379*c*.

Lye, R. G. See Venables, J. D.; Westwood, A. R. C.

Lye, R. G., and Logothetis, E. M. Optical properties and band structure of titanium carbide, (1) 33*i*.

Lykova, L. N., and Trunov, V. K. Determination of lattice parameters of $Y_{0.33}TaO_3$, (8) 290*c*.

Lyle, D. L. See Coffman, R. E.

Lyn, V. See Pink, F. X.

Lynch, C. See Mazdiyasni, K. S.

Lynch, C. T. See Robinson, L. B.; Vahldiek, F. W.

Lynch, R. T. Growth of ZnTe single crystals in a Zn atmosphere, (7) 266*c*. See Panish, M. B.

Lynch, R. T., and Thomas, D. G. Solution growth of nitrogen doped gallium phosphide, P (11) 379*b*.

Lynch Corp. Rotating dead plate mechanism, P (9) 308*c*.

Lyng, S. Effect of fluoride as a crystallization promoter in glasses in the system Na_2O-CaO-MgO-Al_2O_3-SiO_2, (6) 209*c*. Understanding the crystallization of glasses in the system Na_2O-MgO-CaO-Al_2O_3-SiO_2, (6) 211*f*.

Lyon, W. G., and Westrum, E. F., Jr. Low-temperature thermal properties of calcium tungstate, (9) 324*g*.

Lyons, S. C., and Chapman, J. H. Aluminosilicate pigment and method of making same, P (1) 23*j*.

Lythe, T. W., and Padgett, G. C. Equipment for determining the high-temperature properties of basic refractories, (6) 215*i*.

Lyubarskaya, G. V. See Segalova, E. E.

Lyutaya, M. D., and Bartnitskaya, T. S. Decomposition of specimens in the analysis of boron phosphide, (2) 69*c*.

Maarouf, E. See Gans, W.

Macak, J., and Malecha, J. Determination of metallic nickel in catalysts and ceramic materials by differential thermal analysis, (8) 284*i*.

McAllister, P. V., and Cutler, I. B. Evaluation of thermal grooving data, (8) 292*e*.

McAllister, P. V., and McGregor, J. D. Tungsten oxide coated rocket motor throat insert, P (4) 108*a*.

McAllister, W. A. Mixed valence europium phosphors, (5) 197*d*. Rare earth activated strontium lithium germanate phosphors, P (5) 185*f*. Strontium and barium substituted lanthanum phosphate phosphors, P (5) 185*c*. Terbium activated calcium and magnesium germanate phosphors, P (9) 314*a*.

McAndrew, J. D. See Kessler, D.

McAtee, J. L., Jr., and Henslee, W. Electron microscopy of montmorillonite dispersed at various pH, (11) 384*i*.

McAtee, J. L., Jr., and Wells, L. M. Mutual adsorption of clay minerals and colloidal hydrous aluminum oxide—an electron microscopy investigation, (1) 33*e*.

McAvoy, B. R., Green, D., Ing, D. W., and Ure, R. W., Jr. Study of inhomogeneities in GaAs using a scanning electron microscope, (7) 255*b*.

McCabe, C. L. See Simkovich, A.

McCabe, N. R., and Pearce, M. L. Production of ultrapure titanium nitride refractory articles, P (9) 309*d*.

McCain, W. S. See Wilcox, B. A.

McCaldin, J. O., and Widmer, A. E. Semiconducting device, P (8) 283*b*.

McCalip, R. L. See Granberry, D. S.

McCall, R. J. Method of generating a lens, P (9) 307*j*.

McCandless, L. C. See Adler, R. P. I.

McCarthy, D. E. Reflection and transmission of infrared materials (III) spectra from 2μ to 50μ; (IV) bibliography, (1) 36*b*.

McCarthy, G. J., White, W. B., and Roy, R. Phase equilibria in the 1375°C isotherm of the system Sr-Ti-O, (11) 386*e*.

McCarthy, H. E. See Bertrand, L.

McCarthy, J. See Firestone, S.

McCartney, E. J. Optical inspection system, P (7) 259*d*.

McCartney, E. R. See Baggaley, B. J.; Steele, J. L.

McCartney, J. S. Method of selective stressing and birefringent article, P (9) 308*c*.

McCarty, L. V. See Kim, S. C.

McCauley, R. A., and Hummel, F. A. Phase relationships in a portion of the system BaO-P_2O_5, (6) 236*b*.

MacChesney, J. B. See Gallagher, P. K.

MacChesney, J. B., Potter, J. F., and Guggenheim, H. J. Preparation and properties of vanadium dioxide films, (5) 181*c*.

McCleary, R. E. See Kinkade, W. A.

McCleary, R. E., and Decker, R. L. Apparatus for producing cast gypsum articles, P (11) 368*e*.

McCloskey, J. P. Electrograph method for locating pinholes in thin silicon dioxide films, (1) 21*h*.

McClure, J. W. See Marchand, A.

McClure, R. E. Laser fluid flow sensor insensitive to rotation, P (9) 312*d*.

McCollum, W. A. See Darnell, A. J.

McConnaughey, N. See McVey, C. I.

McConnell, D. See Fisher, D. J.

McCormick, G. R. Reply to discussion of "Subsolidus equilibria in the system MgO-GeO_2-MgF_2," (6) 231*h*.

McCormick, J. E. See Nelson, R.

McCormick, P. Y. Drying, (4) 122*f*.

McCown, W. E. See Mambourg, J. E.

McCrary, J. W. See Haberecht, R. R.

McCready, N. W. See Sams, R. H.

McCreight, D. O. See Einstein, E.

McCullough, H. M. See Ortner, M. H.

McDade, J. C. See Saxena, A. N.

McDaniel, C. L. See Schneider, S. J.

McDaniel, C. L., and Schneider, S. J. Phase relations in the Ru-Ir-O_2 system in air, (9) 327*d*.

McDaniel, C. V. See Maher, P. K.

McDaniel, C. V., and Maher, P. K. Stabilized zeolites, P (9) 317*g*.

McDonald, J. See Davis, H. T.

McDonald, N. R. See Rotsey, W. B.

McDonnell-Douglas Corp. Refractory metal coating, P (4) 94*e*.

MacDowell, J. F. Alpha- and beta-cristobalite glass-ceramic articles and methods, P (8) 277*e*.

MacDowell, J. F., and Beall, G. H. Immiscibility and crystallization in Al_2O_3-SiO_2 glasses, (4) 96*d*.

Macedo, P. B. See Haller, W.; Napolitano, A.

Macedo, P. B., and Napolitano, A. Inadequacies of viscosity theories for B_2O_3, (4) 96*e*.

Macedo, P. B., Simons, J. H., and Haller, W. Spectrum of relaxation times and fluctuation theory—ultrasonic studies on an alkali-borosilicate melt, (4) 97*e*.

McElroy, D. L. See Fulkerson, W.

McEvoy, J. E. Contact masses containing zeolite, P (9) 317*c*.

MacEwan, J. R. See Matzke, Hj.

MacEwan, J. R., and Hayashi, J. Grain growth in UO_2 (III) some factors influencing equiaxed grain growth, (4) 137*b*.

MacEwan, J. R., and Stoute, R. L. Annealing of irradiation-induced thermal conductivity changes in ThO_2-1.3 wt% UO_2, (6) 208*e*.

MacEwan, J. R., Stoute, R. L., and Notley, M. J. F. Effect of porosity on the thermal conductivity of UO_2, (4) 133*e*.

McFarland, M. See Bradford, A. P.
Macfarlane, E. K. A. P. Green uses closed circuit TV in a pug mill, (4) 117*f*.
Macfarlane, J. C. Thin film atomic hydrogen detector, (2) 71*f*.
Macfarlane, J. C., and Weaver, C. Low frequency polarization effects in thin evaporated dielectric films, (1) 17*e*.
McFarlane, R. A. Nontranslating variable output coupler for optical masers, P (9) 313*j*.
Macfarlane, R. M. See Wood, D. L.
McFarlane, S. H., III. See Wang, C. C.
McFee, J. H. See Buchsbaum, S. J.
McGarvey, B. R. See Banks, E.
McGarvey, J. M. Abrasive belts and method of making same, P (6) 205*g*.
McGee, T. D. See Vojnovich, T.
McGhee, J. D. Thermocouple reference junction compensating circuits, P (11) 381*d*.
McGinnis, G. Air bag dunnage provides rail shipment protection for $0.28/M brick, (8) 278*e*.
McGinnis, W. J. Porous silica coated titanium dioxide pigment, P (4) 125*f*.
McGlynn, S. P. See Maria, H. J.
McGrath, J. W. See Ossman, G. W.
McGrath, R. S., and Silcox, N. W. Selective deposition method and article for use therein, P (2) 66*a*.
McGraw-Edison Co. Combined overvoltage protective device and conductor support, P (9) 312*d*.
MacGregor, I. D. System MgO-SiO$_2$-TiO$_2$ and its bearing on the distribution of TiO$_2$ in basalts, (11) 387*d*.
McGregor, J. D. See McAllister, P. V.
MacGregor, R. R. See Moore, W. P.
McGroddy, J. C., and Nathan, M. I. Bulk negative conductivity semiconductor oscillator, P (11) 376*h*.
McGuire, R. C. See Tettenhorst, R.
McGuire, T. R. See Ahn, K. Y.
Mach, W. Determination of the permeability coefficient of cohesive soils, (5) 190*a*.
McHenry, T. F. Pyroelectric radiation detector providing compensation for environmental temperature changes, P (10) 345*h*.
Machiyama, Katsuhide, and Yanagida, Yoshiro. Stopper for ladle with air-cooled head, P (4) 108*a*.
Machlan, G. R. See Harris, R. S.
Machlett Laboratories, Inc. X-ray collimating device wherein a plurality of adjustable overlapping leaves define a collimating cone, P (9) 316*b*.
Macht, C. M. Rookwood pottery, (6) 206*c*.
McInisch, E. See Tung, S. E.
MacInnes, Paul A., Tool Corp. Glass cutter [hand], P (11) 371*i*.
MacInnis, C. See Clendenning, T. G.
McIntosh, H. H. Noneroding rocket nozzle, P (7) 252*j*.
MacIntyre, I. G., Mountjoy, E. W., and D'Anglejan, B. F. Occurrence of submarine cementation of carbonate sediments off the west coast of Barbados, W.I., (1) 23*i*.
McIntyre, P. N. See Bolton, H. C.
McIrvine, E. C. Comment on the ferroelectric-polarization field effect, (2) 75*d*.
Mackay, R. A., and Schneider, R. F. Experimental evidence concerning the electronic structure of the NbCl$_{12}$ cluster, (4) 136*d*.
Mackay, S. See Theodosopoulos, J.
McKay, S. A. Blending apparatus for solids, P (4) 118*b*.
McKearin, H. See Hunter, F. W.
McKee, R. J. See Kessler, D.
McKee, R. L. Abrasives industry—an appraisal, (4) 89*f*. Abrasives and machines in the bearing industry, (2) 43*f*. Belts condition stainless, (5) 169*f*. New approach to abrasive engineering at NCR, (8) 273*g*.
McKee, Arthur G., & Co. Agglomeration method and apparatus, P (6) 225*e*.
MacKellar, D., and Joynson, R. E., Jr. Tin-lead-tin layer arrangement to improve adherence of photoresist and substrate, P (9) 314*b*.
McKenna, N. J. See Jones, P. M. S.
Mackenzie, B., and Forman, A. W. Automatic weigher with rapping means to aid discharge of materials, P (1) 20*d*.
Mackenzie, J. D. See Neely, J. E.; Secrist, D. R.; Sperry, L. L.
MacKenzie, K. J. D. Development of electric potentials in clay minerals and alumina-silica systems, (10) 352*a*. Effects of impurities on the formation of mullite from kaolinite-type minerals (I) effect of exchangeable cations; (II) effect of exchangeable anions; (III) effect of the firing atmosphere, (11) 384*c*. See Duncan, J. F.
McKeough, E. L. See Arnold, A. J.
McKerrell, H. See Irving, R. J.
Mackey, R. W., and Morgan, W. J. Electrostatic method for decorating glass and vitreous enamels for use therein, P (7) 248*e*.
McKibben, R. K. Self-discharging finishing mill, P (5) 186*f*. Vibratory separator, P (5) 186*g*.
McKinney, C. N., Smith, H. F., and Pollard, W. K. X-ray spectrometer sample cell having an adjustable secondary X-radiation radiator and taut X-ray transparent window, P (2) 72*i*.
McKinnon, N. A. See Bennett, C. E. G.
McKinnon, N. A., Bennett, C. E. G., Williams, L. S., and McTaggart, F. K. Plasma sintering, P (6) 225*d*.
McKinstry, H. A. See Stubican, V. S.
McLaren, J. R. See Cragg, D. G.
McLaughlin, H. C., and Ramos, J. Delayed gelling of sodium silicate and use therefor, P (7) 262*g*.
McLaughlin, R., White, R., Edelstein, N., and Conway, J. G. Optical spectra of Pu in CaF$_2$, (4) 147*c*.
McLay, J. F. Syringe and method of making same, P (4) 101*c*.
Maclean, C. See Downs, A.
McLellan, R. B. See Dunn, W. W.
McLellan, W. D. See Ramey, R. L.
MacLeod, A. C., and Hopkins, S. W, J. High-temperature adiabatic drop calorimeter—enthalpies of α-Al$_2$O$_3$, UC$_2$, and US between 330° and 1700°K, (5) 195*b*.
McLeod, D. L. See Olsen, G. F.
McLeod, G. D. Preparation of molds, P (6) 218*g*.
McLouski, R. M. See Cricchi, J. R.
MacMackin, J. J. See Ryder, R. J.
McMahon, C. J., Jr. Microstructural aspects of tensile fracture, B (1) 41*h*.
McMaster, A. D. See Gimpl, M. L.
McMaster, D. H. Method and apparatus for conveying and curving glass sheet material on a gas support bed, P (1) 11*d*.
McMaster, H. A. Gas support bed apparatus for treating glass, P (10) 338*f*. Pivotal conveyor attachment for moving glass sheets over a hot gaseous support bed, P (1) 11*c*.
McMaster, H. A., and McMaster, R. A. Apparatus for heat-treating glass on a fluid support, P (10) 338*f*.
McMaster, H. A., and Nitschke, N. C. Method and apparatus for conveying and heat treating glass sheets over a gas support bed, P (1) 11*d*. Method for tempering glass utilizing an organic polymer gaseous suspension, P (5) 175*j*.
McMaster, R. A. Heat exchange apparatus for treating glass, P (10) 338*f*. See McMaster, H. A.
McMillan, J. A. See Hodges, J. A.; Marshall, S. A.
McMillan, J. A., and Marshall, S. A. Motional effects in the electron spin resonance absorption spectrum of CO_3^- molecule-ions in single-crystal calcite, (2) 80*f*.
McMillan, P. W. See James, P. F.
McMillan, P. W., and Partridge, G. Method of coating a ceramic-carbon material with glass and article, P (11) 377*g*.
McMillan, W. J. See Jones, G. D.
McMillen, H. E. Hot-press insulating system, P (11) 374*j*.
McMorris, D. W. Trapped electron dating—ESR studies, (10) 363*a*.
McMullen, J. C. Rocking electric tube furnace, P (4) 123*b*.
McMurdie, H. F. See Levin, E. M.
McMurray, L. L. See Fenske, D. H.
Macnair, J. M. Testing of foundry sand, P (11) 381*c*.
McNally, R. N. See Alper, A. M.; Doman, R. C.
McNamara, V. M. See Weston, T. B.
McNeil, G. See La Rocque, A. P.
McNeily, T. F. See Perry, C. H.
McNicholas, J. J. Specific conductivity of molten lead bromide, (10) 360*h*.
McNickle, B. F. See Lewis, E. W.
McNicol, B. D. See Hoodless, I. M.
McNutt, R. D. See Davis, E. M., Jr.
MacPherson, A. R., Saunders, G. L., and Meaders, R. C. Autogenous grinding mill, P (2) 73*j*.
McPherson, R. Magnesium sulfate formation in the basic linings of copper smelting furnaces, (10) 341*j*.
McRae, R. C. Outgassing of Al$_2$O$_3$ and BeO in vacuum at 540° and 870°C, (6) 220*h*. See Reed, L.
McRae, T. F., and Wheeler, W. C. Application of porcelain enamel on a gas-fired heat exchanger—to beat corrosion, (1) 3*j*.
McShane, P. C. Method of bonding a metal plate to a refractory brick with a chloroprene-phenolic adhesive, P (7) 252*d*.
McTaggart, F. K. See McKinnon, N. A.
McVeagh, W. J. See Brenner, S. S.
McVey, C. I., McConnaughey, N., Gibson, H. D., and Smith, Jack V. Zirconia-based thermoelectric compositions, P (9) 314*e*.
McVey, H. J. Approach to automatic control of metal treatment systems, (1) 3*j*.
McWhan, D. B. See Robin, M. B.
McWhorter, A. L. See Mooradian, A.
McWilliams, D. E. See Eilerman, G. E.
McWilliams, R. J. Innovations with glass-ceramic coatings, (1) 4*e*. See Leeds, H. R.
MacZura, G. See Gitzen, W. H.
Madan, M. P. See Srivastava, S. P.
Maddock, A. G. See Bancroft, G. M.
Maddox, D. See Yeaple, F. D.
Mader, K. H. See Wallace, W. E.
Mader, K. H., and Wallace, W. E. Magnetic characteristics of europium-aluminum intermetallics, (4) 110*f*.
Madeyski, A., and Smeltzer, W. W. Oxygen diffusion in monoclinic zirconia, (5) 198*e*.
Madly, A. Aspects of labor safety activities in the fine ceramics industry, (4) 164*h*.
Madonna, L. A. Mathematical model of the glass processing tanks, (4) 96*b*.
Mae, Shinji. Void formation during nonbasal glide in ice single crystals under tension, (4) 163*f*.
Maeda, Kazuo. Process of epitaxial deposition on one side of a substrate with simultaneous vapor etching of the opposite side, P (6) 223*h*.
Maerker, R. Suggestions for the partial mechanization of the enameling of cast iron bathtubs, (5) 171*c*.
Maetz, H. Highly refractory electrofused materials for precision castng molds, (6) 215*d*.
Maetz, H., and Ost, H. L. Electrofused products—highly refractory materials for severe conditions, (4) 104*a*.
Magee, J. E. See Wittenwyler, C. V.
Maghrabi, C. See Bishay, A.
Magnetfabrik Bonn G.m.b.H. vorm. Gewerkschaft Windhorst. Directionally solidified permanent magnet alloys with aligned ferromagnetic whiskers, P (6) 221*g*.
Magnier, P. See Accary, A.; Boncoeur, M.
Magnier, P., Marchal, M., and Accary, A. High-temperature compressive creep and hot extrusion of uranium-carbon alloys, (4) 138*d*.
Magor, J. K., and Gaydosh, D. S. Vitreous enameling steel and method of making same, P (2) 46*d*.
Magoteaux, O. R. How uniform crucibles are made isostatically, (6) 215*f*.
Maguire, D. E. Apparatus and method for directly measuring capacitance and dissipation factor of capacitors, P (11) 376*g*.
Mah, A. D. Heats of formation of chromium carbides, (5) 194*i*.
Maher, P. K. See McDaniel, C. V.
Maher, P. K., and McDaniel, C. V. Ion exchange of crystalline zeolites, P (1) 23*j*.
Mahler, R. J. Interaction of Gunn domains with ^{71}Ga nuclei in GaAs, (11) 385*i*.
Mahoney, J. F. See Crocker, B. S.
Mahoney, J. P. See Brumage, W. H.
Mahootian, N., Kikuchi, C., and Viehmann, W. Spin-resonance properties of scheelites (I) vanadium in CaWO$_4$, (4) 155*i*.
Maida, F. X. Method of manufacturing a capacitor, P (4) 115*c*.
Maida Development Co. Method of manufacturing a capacitor, P (4) 115*c*.
Maidukova, T. N. See Golub, A. M.
Maier, C. E. Multiple surface glass seal for a high voltage discharge device contacting the inner and outer surface and the open end edge of the hollow tubular anode lead, P (10) 345*c*.
Maier, K. M., Mayer, V., Moertl, G., and Skalla, N. Process for the manufacture of refractory magnesia-chrome and chrome-magnesia products, P (6) 218*i*.
Maihold, B. See Witzmann, H.
Maiman, T. H. Laser systems employing a solid laser material, P (9) 312*d*.
Maines, R. Q. Transformer including boron nitride insulation, P (6) 224*a*.
Maissel, L. I. See Davidse, P. D.; Jones, R. E.
Maissel, L. I., and Wilcox, D. L. Method of forming a glass-filled gap, P (11) 377*a*.
Maitra, A. K. See Kumar, S.
Maix, R. See Ebel, H.
Majeske, F. J. See Goldstein, J. I.
Major, A. See Ringwood, A. E.
Majumdar, A. J. See Rehsi, S. S.
Majumdar, A. J., and Ryder, J. F. Glass fiber reinforcement of cement products, (1) 7*e*.
Majumdar, A. J., Ryder, J. F., and Rayment, D. L. Fracture studies in glass-reinforced gypsum plaster using the scanning electron microscope, (4) 91*g*.
Majumdar, N. C., Ahmad, F. U., and Das, K. Survey of thermal efficiency of Bull's trench kilns, (10) 348*d*.
Majumdar, N. S. See Bavrilov, V. A.
Mak, Ting H. See Reggia, F.
Makarat, H. Studies on silicon phosphates, (6) 238*c*.
Makarova, T. A. See Korytkova, E. N.
Makino, Motohiko. See Tokue, Tetsuo.
Makishima, Shoji. See Yamamoto, Hajime.
Maklad, M. S. See Kreidl, N. J.
Makram, H. Growth of nickel manganite single crystals, (6) 233*b*. Improvement in yield of yttrium iron garnet, (7) 255*b*.
Makram, H., Touron, L., and Loriers, J. Effect of pressure on the homogeneous distribution of gallium in single crystal yttrium iron garnet, (11) 384*j*.
Malakoff, J. L., Ramirez-Munoz, J., and Scott, W. Z. Computer techniques for three-dimensional analysis in atomic-absorption flame photometry, (1) 21*a*.
Malaspina, L. See Piacente, U.
Malchaire, M. J. J. Coated electrode and process for electric arc welding, P (5) 171*j*.
Malden, P. J. See Meads, R. E.
Malecha, J. See Macak, J.
Maley, D. R. Material tester, P (6) 227*i*. Nondestructive tester, P (6) 228*a*.
Malhotra, V. M., and Zoldners, N. G. Comparison of ring-tensile strength of concrete with compressive, flexural, and splitting-tensile strengths, (5) 187*b*.
Malik, W. U. See Gupta, G. C.
Malin, A. S. See Baggaley, B. J.
Malinowski, E. See Baer, C. E., Jr.
Malinowski, J. See Marowska, R.
Malizie, E. S. See Faulring, G. M.
Malkin, J. E. See Mazurov, D. J.
Malkin, V. I. See Korshikova, N. G.
Malkin, V. I., Mogutnov, B. M., and Ryl'nikova, A. G. Refraction of the oxygen ion in three-component silicate melts, (2) 50*g*.

Malkova, T. I. See Berg, L. G.
Mallary, M. B. Clay treatment, P (7) 262*f*.
Mallett, G. R. See Newkirk, J. B.
Mallick, G. T., Jr., and Emtage, P. R. Current-voltage characteristics of semiconducting barium titanate ceramic, (2) 61*h*.
Mallinder, F. P., and Proctor, B. A. Preparation of high-strength sapphire crystals, (2) 82*c*.
Mallory, P. R., & Co., Inc. Addition agents for sintering processes, P (4) 112*a*. Alloys for brazing silicon nitride material, P (6) 217*f*. Bonding electrically conductive metals to insulators, P (4) 112*d*. Five-layer light-actuated semiconductor device having bevelled sides, P (5) 183*c*. Method for making porous electrodes comprising freezing wet powder and sintering, P (5) 183*h*. Method of producing tungsten powder bodies infiltrated with zirconium, P (9) 309*g*. Method of wetting silicon nitride, P (1) 18*e*. Powder on foil solid tantalum capacitor, P (11) 378*f*. Powder on wire capacitor, P (5) 184*h*. Preparation [vapor deposition] of silicon nitride whiskers, P (4) 107*b*. Tungsten-indium powder bodies infiltrated with copper, P (5) 185*h*.
Malloy, J. J. See Larson, T. D.
Maloney, F. J. T. Glass in the Modern World—A Study of Materials Development, B (2) 85*e*.
Mal'tsev, G. Z., and Mashovets, V. P. Heat capacity of sodium aluminate solutions at 25°–90°, (1) 30*a*.
Mal'tsev, V. T. See Bukhalova, G. A.
Malyshev, M. V., and Fradis, A. D. Strength criterion for sands, (5) 190*a*.
Mamantov, G. See Young, J. P.
Mamatkanov, A. M. See Kruglitskii, N. N.
Mambourg, J. E., and McCown, W. E. Seal for glass furnace joints, P (11) 372*b*.
Manaila, R. Cation migration in tetragonal spinels ($MgMn_2O_4$), (10) 350*c*.
Manasevit, H. M. Gas phase etching of sapphire (II) fluorinated hydrocarbons, (5) 194*c*. Single-crystal gallium arsenide on insulating substrates, (1) 17*d*. Single crystal silicon on spinel insulators, P (4) 117*a*.
Manasevit, H. M., and Morritz, F. L. Gas phase etching of sapphire with sulfur fluorides, (4) 137*c*.
Manasevit, H. M., Morritz, F. L., and Forbes, D. H. Heteroepitaxial growth of molybdenum thin films on insulating substrates, (1) 30*f*.
Manconi, J. W. See Bettinali, C.
Mandal, S. S. See Bhadra, A. K.
Mandelkorn, J. Gd or Sm doped silicon semiconductor composition, P (2) 64*f*.
Mandelkorn, J., and Broder, J. Method of making electrical contact on silicon solar cell and resultant product, P (6) 222*h*.
Mandonas, N. J., and Sevigny, A. J., Jr. Apparatus for helixing a path in a carbon film deposited on a ceramic core, P (2) 64*f*.
Mandonas, N. J., and Smith, N. F. Apparatus for helixing and sorting filmed resistors, P (8) 282*b*.
Mank, V. V. See Brekhunets, A. G.
Manlabs, Inc. Oxidation resistant refractory compounds, P (4) 107*i*.
Manley, A. J. Transmission electron microscopy of irradiated UO_2 fuel pellets, (8) 300*j*.
Manley, J. C. Method of making an electrical component, P (10) 345*h*.
Mann, J. R. See Baker, L. R.
Mannami, Michi-hiko; Akisue, Osamu; and Tanaka, Kenzo. Defect clusters in electron and neutron irradiated lithium fluoride, (8) 290*h*.
Manneville, M. See Masson, A.
Mannheimer, R. See Feder, R.
Mannheimer, R. J., and Schechter, R. S. Analysis for Bingham plastic surface flow in a canal viscosimeter, (1) 20*i*.
Manning, C. R., Jr., and Gurganus, T. B. Wetting of binary aluminum alloys in contact with Be, B_4C, and graphite, (6) 207*i*.
Manning, F. S. See Spitzer, R. H.
Manning, J. P. See Coleman, W. L.
Manning, P. G. See Faye, G. H.
Manning, W. R., and Hunter, O., Jr. Elastic properties of polycrystalline yttrium oxide, holmium oxide, and erbium oxide—high-temperature measurements, (11) 384*h*.
Manning, W. R., Hunter, O., Jr., and Powell, B. R., Jr. Elastic properties of polycrystalline yttrium oxide, dysprosium oxide, holmium oxide, and erbium oxide—room temperature measurements, (10) 352*a*.
Mannion, W. A., Allen, C. A., and Fredericks, W. J. Diffusion of lead ions in purified NaCl crystals, (4) 131*e*.
Mannweiler, N. See Feitknecht, W.
Mannweiler, U. See Gallagher, K. J.
Manoharan, P. T., and Rogers, M. T. ESR study of VOF_5^{3-} ion, (10) 353*g*.
Manring, W. H., and Conroy, A. R. Effect of cullet in melting soda-lime glasses (I), (1) 6*i*.
Mans, B. Scandinavian creations, (5) 170*b*.
Mansard, B. See Klein, J.
Manser, R. M. See Kini, K. A.
Mansfield Sanitary, Inc. Method and apparatus for dusting mold cores, P (2) 60*j*. Method [casting] of making ceramic shapes, P (2) 61*a*.
Mansur, F. E. See Francel, J.
Mantey, P. G. See Ruettiger, K.
Manuil'skii, A. D. See Broude, V. L.
Manvelyan, M. G., Rustambekyan, S. F., Melik-Akhnazaryan, A. F., Kostanyan, K. A., and Kirakosyan, T. M. Perlites as raw materials for the glass industry, (6) 210*g*.
Many, A. See Balberg, I.
Maple, T. G. Semiconductor contact and interconnection structure, P (8) 283*b*.
Mapother, T. C. Semiconductor low voltage switch, P (5) 185*f*.
Maradudin, A. A. See Wallis, R. F.
Maradudin, A. A., and Wallis, R. F. Lattice-dynamical calculation of the surface specific heat of a crystal at low temperatures, (2) 79*d*.
Marathe, M. S. See Evans, R. H.
Marathon Oil Co. Manufacture of coke and low CTE graphite from petroleum derived feed materials, P (11) 375*c*.
Maravilla, S., and Kopanda, J. E. Oil well cement and method of making the same, P (4) 93*a*.
Marchal, M. See Accary, A.; Magnier, P.
Marchand, A., Dupart, E., and McClure, J. W. Electrical properties of BiSb alloys with small antimony content, (5) 181*a*.
Marchese, M. A., and Taft, L. G. Apparatus for coating a thin uniform thickness stripe on a substrate, P (11) 376*f*.
Marcon, J. P., and Pascard, R. Study of the higher sulfides of the lanthanides and the actinides, (1) 38*e*.
Marcus, R. B., and Quigley, S. Formation of fcc, bcc, and β-tantalum films by evaporation, (8) 281*h*.
Marczal, L. New method of particle size analysis, (5) 187*d*.
Mardirosova, I. V. See Bukhalova, G. A.
Marechal, J. C. Apparatus for measurements at high temperatures, (1) 20*j*. Apparatus for testing at low temperature, (1) 20*j*.
Mareschal, J. See Bertaut, E. F.
Maretheu, A. Measurement of the moisture content of ceramic pastes, (2) 70*d*. See Lapoujade, P.
Marezio, M., Remeika, J. P., and Zocchi, M. Cation distribution in the garnet $Eu_3Fe_{1.94}Ga_{3.06}O_{12}$, (4) 127*i*.
Margason, L. L. See Burgmaa, J. A.
Margerum, D. W. See Pausch, J. B.
Margerum, D. W., Pausch, J. B., Nyssen, G. A., and Smith, G. F. Differential kinetic analysis of the metallic elements, (8) 285*a*.
Margola, G. B. Equipment for varnishing ceramic stock semifinished products, in particular crockery, P (5) 180*b*. See Lampani, A.
Margolis, J. M. Recrystallization of anhydrous calcium acid phosphate from the dihydrate form, P (5) 191*d*.
Margrave, J. L. See Besenbruch, G.; Greene, F. T.; Zmbov, K. F.
Margulis, E. V., and Sannikov, Yu. I. Synthesis of large crystals of copper sulfide, CuS, (9) 331*i*.
Maria, H. J., Armstrong, A. T., and McGlynn, S. P. Luminescence of inorganic nitrite salts, (5) 196*b*.
Maricic, A., Radovanovic, S., Maricic, D., and Brenholz, G. Behavior of magnesite brick at high temperature, (4) 103*d*.
Maricic, D. See Maricic, A.
Marier, P. See Ingraham, T. R.
Marinace, J. C. Epitaxial semiconductor layer as a diffusion mask, P (2) 64*e*. Method of electrolytically etching a semiconductor having a single impurity gradient, P (4) 114*c*. Process of bonding chips in a substrate recess by epitaxial growth of the bonding material, P (6) 223*g*. Process for preforming crystalline bodies, P (11) 378*j*.
Marinace, J. C., and Rutz, R. F. Method of making crystal shapes having optically related surfaces, P (11) 377*c*.
Marincek, V. B. Study of the resistance of carbon bricks to the attack of pig iron melts, (4) 105*c*.
Marino, D. See Heltai, F.
Marino, D., Barta, S., Kysela, W., Kulcsar, A., and Serdean, A. Harghita kaolin as a ceramic bond for abrasives, (4) 89*f*.
Marino, G. P. Radiation transfer across a spherical pore in a linear temperature gradient, (10) 359*f*.
Marino, J., and Schaefer, W. R. Semiconductor device contact structure, P (4) 116*c*.
Marino, R. A., and Bray, P. J. Charge distribution of the NO_2^- radical in ferroelectric sodium nitrite, (5) 192*d*.
Marinov, M., and Radenkova-Yaneva, M. Electron-microscope study of the chemical stability of glasses in the system Li_2O-SiO_2-Li_2O-Al_2O_3-$4SiO_2$, (2) 48*g*.
Marinsky, J. A. (editor). Ion Exchange—A Series of Advances (Vol. 2), B (7) 271*f*.
Marjoram, J. R. See Jackson, P. W.
Markel, H., and Leibenzeder, S. Method of epitaxially producing *pn* junctions in silicon, P (2) 65*a*.
Markelova, M. Ya. See Boguslavskii, I. A.
Markevich, G. S. See Kondrashev, Yu. D.
Markin, T. L. See Roberts, L. E. J.
Markin, T. L., Bones, R. J., and Wheeler, V. J. Galvanic cells and gas equilibration techniques, (2) 69*f*.
Markovic, B. See Persin, A.
Markovskii, L. Ya. See Kondrashev, Yu. D.
Marley, J. A., Jr. See Hou, S. L.
Marlot, P. L. M. See Lescroart, L. C. J.
Marlowe, M. O., and Kaznoff, A. I. Tracer study of the surface diffusivity of UO_2, (7) 270*c*.
Marmo, V. Origin of granite, a hydrothermal model, (4) 147*i*.
Marotta, R. Method of preparing silica materials, P (6) 229*h*.
Marowska, R., and Malinowski, J. Preparation of cermet thin films by electron bombardment evaporation, (5) 178*c*.
Marples, J. A. C. See Hough, A.
Marriott, J. See Derham, L. J.
Marriott, J. A. See Petrocelli, A. W.
Marschall, H. L. Magnesia refractory and method of producing same, P (2) 58*i*.
Marsden, J. G. See Sterman, S.
Marsden, J. G., and Sterman, S. Antistatic agents for glass fiber materials, P (4) 98*c*.
Marsh, A., and Clark, C. C. Magnetic interactions and crystal structure in the $(La,Gd)_2CoMnO_6$ system, (10) 356*g*.
Marshall, D. J. See Barrer, R. M.; Laudise, R. A.
Marshall, D. J., and Laudise, R. A. Hydrothermal solubility of lithium metagallate in NaOH solutions, (4) 139*b*.
Marshall, F. G., and Rampton, V. W. Acoustic paramagnetic resonance spectrum of chromous ions in magnesium oxide, (1) 24*h*.
Marshall, H. W. See Edgecombe, D. A.
Marshall, J. K. See Woods, W. W.
Marshall, P. A., Jr., Rishel, P. A., and Roman, H. Method of treating alumina, P (1) 14*a*.
Marshall, R. C. Growth and characterization of a transition metal silicide, (9) 322*b*. See Ryan, C. E.
Marshall, S. A. See Hodges, J. A.; McMillan, J. A.
Marshall, S. A., McMillan, J. A., and Serway, R. A. Electron spin resonance absorption spectrum of Y^{3+}-stabilized Co_2^{3-} molecule-ion in single-crystal calcite, (5) 194*d*.
Marshall, S. A., and Serway, R. A. Electron spin resonance absorption spectrum of the AsO_2^{2-} molecule-ion in γ-irradiated single-crystal calcite, (10) 353*a*.
Marshall, V. R. Carborundum-Latrobe, (5) 179*h*.
Marshall, W. B., and Norman, H. W. Apparatus for horizontal zone refining of semiconductive materials, P (1) 17*i*.
Marthy, S. L. N. See Hanson, C.
Martin, A. J., Buck, R. H., Loasby, R. G., and Savage, J. Production of electrically conductive tracks by the electron or laser-beam decomposition of inorganic metallic compounds (I) oxide systems, (8) 281*e*.
Martin, D. D. Structure and fabrication of microwave oscillators, P (6) 224*b*. See Conrad, R. W.
Martin, D. G. Observation of radiation-induced defects in BeO by means of long-wavelength neutron-scattering measurements, (4) 147*d*.
Martin, D. L. See Woods, W. W.
Martin, D. L., and Benz, M. G. Method of making superconductors containing flux traps, P (6) 222*j*.
Martin, D. N. See Rochte, J. E.
Martin, F. W. Crystalline glazed ceramic containing lead titanate crystals and method, P (2) 52*f*. Kovar sealing glass, P (5) 175*b*. Process for producing seals, P (4) 100*i*. See Asher, J. W.
Martin, F. W., and Smith, W. C. Method of sealing and resilient seal for elements having different coefficients of expansion, P (5) 175*g*.
Martin, G. D. Preparation of sheet steel for porcelain enameling—a survey of current industry practices, (1) 5*d*.
Martin, J. Comblike catch pans for vertical draw sheet glassmaking machines, P (7) 248*c*. Machinery support, P (6) 212*i*. Roll bearing structures for glassmaking machines, P (5) 176*a*.
Martin, J. E. Filter utilizing glass balls for filtering fluids, P (4) 98*g*.
Martin, J. F. Techniques for the measurement of entropy and their application to some uranium compounds, (5) 200*j*. See Counsell, J. F.
Martin, J. M. See Laugier, J.
Martin, R. J. See Tien, P. K.
Martin, R. W. Plating waste treatment: Which system? (1) 20*g*.
Martin, T. J. Abrasive wheel having a metal coated graphite lubricant therein, P (1) 1*j*.
Martin-Marietta Corp. Ceramic filled plastic system, P (11) 369*b*. Electronic thickness meter having direct readout of coating thickness, P (7) 260*i*. Hydraulic cement mix and additive, P (6) 207*d*. Hydraulic cement mix containing saccharide polymers, P (6) 207*d*. Process of making Mn_4Si_7 thermoelectric element and product of the process, P (2) 66*h*. Unusual structural material, P (9) 309*f*.
Martinet, J. R. Refractory composition, P (8) 280*b*.
Martinetti, S. See Esu, F.
Martini, P. L. See Gottardi, V.
Marton, M. Disk sanding apparatus, P (4) 89*h*.
Martynenko, L. I. See Bkhargava, Kh. D.
Martyny, W. C., and Underwood, P. J. Fluorescent panel lamps with white emitting phosphor coated on envelope backplate and red emitting phosphor coated on envelope faceplate, P (2) 64*h*.

Marusak, F. J. Double ion exchange method for making glass article, P (4) 98*b*.
Marvin, U. B. See Frondel, C.
Maruyama, Toshiyuki. See Kawado, Seiji.
Marzocchi, A. Elastomeric-glass fiber products and process and elements for use in same, P (4) 98*c*. Glass fiber reinforced elastomers and composition for sizing and impregnating such glass fiber systems, P (1) 10*e*. Treated glass fiber bundles and combinations thereof with elastomeric material, P (10) 340*a*.
Marzocchi, A., and Rammel, G. E. Method of coating fibers and fibers formed therefrom, P (11) 371*f*.
Marzocchi, A., and Tamosauskas, A. E. Glass fiber reinforced elastomers, P (5) 174*f*.
Marzocchi, A. and Waugh, J. A. Method for the impregnation of fibrous glass [bundles], P (6) 213*b*.
Mas, R. J., and Michaud, A. L. Process and apparatus for the production of metal oxides, P (1) 24*e*. Process for making titanium dioxide using carbon monoxide containing inorganic ashes, P (7) 263*e*.
Mase, Kazuo. See Shimizu, Keiichi.
Maselli, J. M., and Rice, R. G. High temperature phosphorus containing molding compositions and ceramics, P (9) 309*f*.
Maserjian, J. Theory of conduction through thin insulating films with [large] ionic space charge, (10) 362*b*.
Maserjian, J., and Mead, C. A. Conduction through TiO_2 thin films with large ionic space charge, (10) 351*a*.
Mashovets, V. P. See Mal'tsev, G. Z.
Maskal, J. See Thompson, I. M.
Maslennikov, V. A., and Khinich, I. Y. Cone crusher with noneccentric drive, P (8) 287*g*.
Mason, B. Pyroxenes in meteorites, (4) 151*c*.
Mason, B., and Berry, L. G. Elements of Mineralogy, B (1) 41*a*.
Mason, D. R. See Chiang, Ping-Wang.
Mason, G. See Clark, W. C.
Mason, G. E. See Klein, O. C.
Massachusetts Institute of Technology. Electric heating element and its fabrication, P (8) 282*e*. High temperature furnace, P (4) 123*a*.
Massart, D. L., Sainte, G., and Hoste, J. Thin layer chromotography of the rare earths, (5) 188*a*.
Masson, A., Manneville, M., and Kern, R. Cleavage device for use in ultrahigh vacuum, (4) 119*b*.
Masterson, D. J. See Coglaiti, J. S., Jr.
Masuda, Masayoshi. See Chisaka, Haruo.
Masuda, Mutsuo. See Kobayashi, Yoshichika.
Masuda, Satoru. See Watanabe, Hideo.
Masuda, Senichi. Apparatus for electrostatic precipitation of dust, P (8) 284*d*. Electrostatic characteristics of powder, (4) 117*h*.
Masuda, Shoichiro. Use of castable and plastic refractories in continuous slab heating furnace, (7) 251*j*.
Masuda, Yoshihiro. Nagatsu, Hiroshi.
Matarrese, L. M. See Cook, A. R.
Matarrese, L. M., Wells, J. S., and Peterson, R. L. EPR spectrum of Fe^{3+} in synthetic brown quartz, (11) 384*j*.
Matcha, R. L. Theoretical analysis of the electronic structure and molecular properties of the alkali halides (III) sodium chloride, (2) 84*e*.
Matchen, B. See Watson, G. R.
Mateiko, Z. A., Yagub'yan, E. S., and Bukhalova, G. A. System Na,Cs,Ba‖Cl, (8) 299*f*.
Matejka, J. Kinetics of wet grinding in the ball mill (I); (II) Effect of peripheral speed, (10) 346*g*.
Mathe, G. Investigation of the signal shape given by *np*- and *pn*-type semiconductor detectors with pulse shape discrimination, (5) 195*g*.
Mathers, J. E. See Toma, S. Z.
Matheson, J. K. Total energy in the brick and tile industry, (1) 11*g*.
Matheson, W. G. See Koury, F.
Mathews, A. L., and Baes, C. F., Jr. Oxide chemistry and thermodynamics of molten LiF-BeF_2 solutions, (11) 386*b*.
Mathews, F. R. See Perrine, R. J.
Mathewson, W. F., Jr. See Wright, A. N.
Mathur, S., Kacheva, K. M., and Saxena, S. C. Crystal properties of some heavy metal halides and alkaline earth chalcogenides, (4) 130*f*.
Mathur, V. K., and Singh, S. P. Force constants and cohesive energies of some diatomic crystals, (2) 77*g*.
Matiash, I. V. See Brekhunets, A. G.
Matkovich, V. I., and Colton, E. Method of preparing tetraboronsilicide (B_4Si), P (5) 179*f*.
Matoba, Toshio. See Kudaka, Katsuya.
Matousek, J. Diffusion of silver in alkali-calcium-silica glasses, (1) 6*g*. Method of measuring the diffusion coefficient of Ag^+ ions in glass by means of ^{110}Ag radioisotope, (6) 210*c*.
Matousek, J., and Sychra, V. Atomic fluorescence study on iron, cobalt, and nickel, (8) 284*j*.
Matsuki, Yosiaki. See Matsuo, Shigetomo.
Matsumoto, Hideo. See Yamauchi, Shiro.
Matsumoto, Hiroshi. Additive for production of spheroidal graphite cast iron consisting mostly of calcium-silicon, P (4) 93*i*.
Matsumura, Chi., and Lide, D. R., Jr. Structure of the alkali hydroxides (III) microwave spectra of RbOH and RbOD, (10) 361*d*.
Matsumura, T. See Nameishi, Naoyuki.
Matsunaga, Kichinosuke. Results of service tests on special roseki ladle brick, (7) 251*c*.
Matsuno, Seiichi. See Ando, Jumpei.
Matsuo, Masataka. See Ohba, Hiroshi.
Matsuo, Shigetomo; Matsuki, Yosiaki; and Komeya, Katsutoshi. Method for the manufacture of alumina refractories having an aluminum nitride coating, P (5) 179*c*. Method of preparing sintered masses of aluminum nitride, P (7) 252*h*.
Matsuo, Yoshihiro; Sasaki, Hiromu; Hayakawa, Shigeru; Kanamaru, Fumikazu; and Koizumi, Mitsue. High-pressure synthesis of perovskite-type $Pb(Zn_{1/3}Nb_{2/3})O_3$, (11) 385*f*.
Matsuoka, Hideki. Test results on basic brick used in ladle lining, (11) 374*c*.
Matsuoka, Hidenori. Life of brick used in dust collecting hole in roof of electric furnace, (10) 341*j*.
Matsushima, Isao. Automatic preforming device for continuous pottery forming machine, P (5) 180*e*.
Matsushima, K. See Ohtsuki, T.
Matsushiro, A. BOF lining development at NKK Tsurumi plant, (4) 103*g*.
Matsushiro, Ayasaburo. Service tests on ladle brick containing chromium oxide, (11) 374*c*. Use test on high-silica sleeves having low refractoriness, (2) 58*i*.
Matsushita Electric Industrial Co., Ltd. Capacitor comprising ferroelectric ceramic with oxidic silver electrodes and heterojunction barrier layer between electrodes and ceramic, P (4) 112*f*. Ceramic capacitor comprising semiconductive barium titanate body and silver alloy electrodes containing minor amount of Cu, Ca, or Bi, P (4) 112*g*. Composite glass electrode, P (1) 10*a*. Ferromagnetic materials, P (2) 64*f*, P (5) 183*a*. Fluoride-containing glass electrode compositions, P (9) 307*d*. Glass electrode compositions, P (6) 212*b*. Injection EL diode, P (4) 113*e*. Manganese-zinc ferrites, P (4) 114*b*. Method of making a variable capacitance silicon diode with hyper abrupt junction, P (4) 115*c*. Negative resistance semiconductor device having an intrinsic region, P (11) 378*a*. Piezoelectric ceramic compositions, P (1) 18*i*, P (5) 184*f*. Piezoelectric ceramic materials, P (5) 184*g*. Piezoelectric ceramic resonators, P (6) 223*d*. Piezoelectric composition and method of preparing the same, P (9) 313*b*. Pressure-responsive semiconductor device, P (8) 283*i*. Process for producing butterfly twin barium titanate single crystals and barium titanate mixture used therein, P (2) 66*h*. Semiconductor comprising plural deep-level-forming impurities, P (9) 313*h*. Semiconductor devices, P (7) 258*c*. Vitreous ceramic compositions, P (5) 176*c*.
Matsushita Electronics Corp. Discharge tube, P (5) 182*e*. Discharge tube satisfactorily low in radio-interfering noise, P (5) 182*f*. Field-effect transistor having insulated gates, P (10) 344*j*. Method for the deposition of silica films, P (8) 282*f*. Method of manufacturing semiconductor devices [masking], P (7) 257*j*. Method of producing semiconductor devices, P (5) 184*e*. Preparation of borax-fluxed europium-activated rare earth oxide phosphors, P (11) 378*f*. Process for preparing phosphors, P (10) 345*h*.
Matsuzaki, Hiroyuki; Shimizu, Shokichi; and Mizuo, Masahiko. Adhesive material and method of using same to adhere ceramic material to metal, P (8) 282*a*.
Matsuzaki, Teizo; Minami, Kuniyuki; and Sasagawa, Yoshiaki. Apparatus for automatically cutting a glass sheet, P (7) 248*h*.
Mattern, E. E. See Kane, J. L.
Matthaei, H. Essential characteristics of rocks and the requirements of an apparatus for disintegrating limestone by electromagnetic-thermal means, (6) 224*g*.
Matthews, H. E., and Kohnke, E. E. Effect of chemisorbed oxygen on the electrical conductivity of Zn-doped polycrystalline SnO_2, (9) 320*g*.
Matthews, R. S. See Jones, D. W.
Matthies, H. See Saalfeld, H.
Mattison, D. R. See Coffman, R. E.
Mattson, R. A. See Bernstein, F.
Matukura, Yasuo. See Miura, Yoshio.
Matumaru, Haruo. See Douta, Kikuo.
Matveev, G. M. See Matveev, M. A.
Matveev, M. A. See Budnikov, P. P.
Matveev, M. A., Frenkel, B. N., and Matveev, G. M. Thermodynamics of reactions in Li_2O-SiO_2 mixtures, (4) 161*j*.
Matveev, M. A., and Guzhavina, E. T. Structural and mineral-phase conversions during the hardening of aqueous solutions of alkali silicates, (2) 45*c*.
Matvienko, A. S. Petrographic control of clinker quality, (1) 3*f*.
Matyushenko, N. N., Rozen, A. A., and Pugachev, N. S. Triangulation of the system C-Si-Be, (1) 40*b*.
Matzke, Hj., and MacEwan, J. R. Effect of bombardment temperature on the trapping of xenon in some oxides and halides, (11) 384*d*.
Maurakh, M. A. See Elyutin, V. P.
Maurer, D. W., and Please, C. M. Preparation of metal-coated powders and cathode structures, P (2) 66*g*.
Maurer, K. Accelerated strengthening of extruded ceramic bodies, (5) 176*f*. Mechanical properties of ceramic bodies during drying, (5) 179*i*.
Maxwell, D. H. Coated nickel base engine alloys, P (9) 304*h*.
Maxwell, J. A. See Forman, S. A.
Maxwell, K. J. See Leask, M. J. M.
May, C. A., and Ashbee, K. H. G. Twist boundaries in alumina-chromia alloys, (4) 162*i*.
May, G. A. See Davidson, I. A.
May, M. See Hansen, J. M.
May, P., Nallet, J. P., and Daneyrolle, C. Texture of microporous materials—apparatus for the automatic determination of sorption isotherms and pore size distribution curves, (1) 25*f*.
May, P., Nallet, J. P., Sapet, J. C., and Daneyrolle, C. Analysis of experimental data in determining the texture of microporous material—size distribution of pores, (1) 25*e*.
May, W. See Stablein, H.
Mayaux, P., and Descurieux, S. Kinetics of silvering reactions, (9) 306*c*.
Mayeda, K. See Shimoda, R. Y.
Mayer, D. W. Tungsten filament iodine cycle incandescent lamp with alkali metal getter, P (4) 117*b*.
Mayer, I., and Shidlovsky, I. Crystal data on $La_5Ge_3C_{1.5}$, (9) 319*b*.
Mayer, I., Yanir, E., and Shidlovsky, I. Dimorphism of rare earth disilicides, (4) 131*h*.
Mayer, S. E. Radiation resistant semiconductor grade silicon containing a metal oxide, P (8) 283*j*.
Mayer, V. See Maier, K. M.
Mayer, W. G. See Auth, D. C.
Mayes, P. See Aspinall, A.
Mays, R. E. See Dodge, F. C. W.
Mays, R. K., and Bertorelli, O. L. Process of producing highly porous and reactive silica materials, P (7) 263*b*.
Maywald, H. See Schaeffer, H.
Mazdiyasni, K. S., Lynch, C., and Smith, J. S., II. Transparent zirconia composition and process for making same, P (6) 218*h*.
Mazelsky, B. See Epstein, G.
Mazelsky, R., Hopkins, R. H., and Kramer, W. E. Czochralski growth of calcium fluorophosphate, (9) 319*c*.
Mazelsky, R., Kramer, W. E., and Hopkins, R. H. Crystal growth of $GdAlO_3$, (7) 264*g*.
Mazelsky, R., Ohlmann, R. C., and Steinbruegge, K. Crystal growth of a new laser material, fluorapatite, (4) 130*d*.
Mazheika, R. A. See Meshkauskas, Yu. I.
Mazurin, O. V. Internal friction of phase separated sodium borosilicate glass at high temperatures, (4) 96*g*. See Dgebuadze, T. P.; Douglas, R. W.
Mazurin, O. V., Streltsina, M. V., and Totesh, A. S. Viscosity and transformation temperature of phase-separated sodium borosilicate glasses, (8) 277*b*.
Mazurov, D. J., Zakharov, G. V., Malkin, J. E., Chernyshov, I. P., Lexin, B. G., Seliverstov, V. T., Nikitin, A. A., and Potanin, D. N. Plant for calcining binding and refractory materials, P (4) 107*j*.
Mead, C. A. See Hartman, T. E.; Lewicki, G.; Maserjian, J.
Meaders, R. C. See MacPherson, A. R.
Meadowcroft, T. R. See Boyer, A. J. G.
Meadows, F. W., and Dowley, A. Manufacture of pottery, P (7) 254*b*.
Meadows, F. W., and Podmore, D. Manufacture of pottery ware, P (4) 123*c*.
Meadows, G. W. Cobalt-bonded tungsten carbide, P (10) 335*h*. Hot-pressing process, P (4) 118*e*.
Meads, R. E., and Malden, P. J. Substitution of iron in kaolinite, (4) 157*f*.
Meaker, R. E. See Porter, B.
Mearl Corp. Process for producing stabilized titanium dioxide pigments, P (4) 125*a*.
Measor, J. C. See Chattopadhyay, B.
Meckwitz, J. Importance of control technology in highly mechanized porcelain plants, (10) 343*e*.
Mecta, O. P., Lantelme, F., and Chemla, M. Electrolytic conductance of melts in the system LiBr-KBr, (9) 321*h*.
Medaris, L. G., Jr. See Fisher, G. W.
Medek, J. Determination of apparent density of rough porous matter, (5) 187*d*.
Medert, W. C., and Petticrew, R. W. Art of decorating glass-ceramic substrates, P (4) 98*g*.
Medic, N. See Hloch, A.
Medved, D. B. See Garasi, L.
Medved, D. B., and Garasi, L. Production of semiconductor devices by use of ion beam implantation, P (8) 283*j*.
Medved, T. How Dickey Clay developed new uses for polyurethanes, (8) 278*f*.
Mee, J. E. Growing garnet on nongarnet single crystal, P (6) 221*d*. See Collins, J. H.
Mee, J. F. Climate for creativity and innovation, (1) 40*f*.
Meehan, J., and Salomon, R. E. Crystal field studies on vanadium and chromium in zirconium oxide, (4) 130*c*.
Meer, W., and Hargasser, H. High frequency transistor with sloping emitter junction, P (6) 221*e*.
Meer, W., Hargasser, H., and Schembs, W. Mesa transistor with an asymmetrical U-shape base electrode, P (9) 312*g*.
Meers, J. T. See Howard, R. A.
Meffert, A., and Langenfeld, A. Rapid method

for surface area determination of fine particles, (6) 227*e*.
Megaw, A. H. S. More gilt and enameled glass from Cyprus, (4) 90*d*.
Meggy, A. B. See Semmens, B.
Megla, G. K., and Ladovici, B. F. Photochromic glass image display and storage system, P (6) 213*i*.
Megles, J. E. Method of differential chemical tempering glass and article, P (8) 277*i*.
Mehal, E. W. See Shaw, D. W.
Mehan, R. L., and Feingold, E. Room and elevated temperature strength of α-Al_2O_3 whiskers and their structural characteristics, (6) 216*c*
Mehta, P. K. Morphology of calcium sulfoaluminate hydrates, (11) 368*e*.
Mehta, P. K., and Shah, M. J. External standard method of X-ray diffraction analysis for determining the percentage of compounds in cement clinker, P (6) 207*c*.
Mehta, R. R. See Swann, R. C. G.
Meibuhr, S. G. See Sharpe, T. F.
Meijer, R. A. J. M. See T'Jampens, G. R.
Meikle, J. E. Spectrophotometric apparatus for rapid analysis having deflection means to prevent vortex formation, P (4) 122*a*.
Meinders, B. See Dettingmeijer, J. H.
Meinert, N. See Bromer, H.
Meiresonne, A. C. Glass parts for forming cathode-ray tube envelopes, P (1) 10*e*.
Meissnerova, H. See Stanek, J.
Meitzler, A. H. See Warner, A. W.
Meitzler, A. H., and Fitch, A. H. Acoustoelastic effect in vitreous silica, Pyrex, and T-40 glass, (11) 369*d*.
Meixner, A. E. See Reynolds, F. W.
Meixner, A. E., and Reynolds, F. W. Method of making a moisture sensitive capacitor, P (10) 345*i*.
Melamed, Sh. G., Antonov, A. V., and Kulevskii, L. V. Determination of rare earths in yttrium oxide on the basis of luminescence spectra of crystalline phosphors, (2) 75*e*.
Melde, G. Cinematic measurement of firing shrinkage, (5) 187*b*.
Melik-Akhnazaryan, A. F. See Manvelyan, M. G.
Melkeraaen, T. O., and Capek, R. G. Leadless inverted device forming process, P (11) 377*c*.
Melkonyan, M. T. See Abramyan, A. V.
Mellen, E. J., Jr., Baker, E. M., and Webb, J. M. Method of making a permeable shell mold, P (10) 342*j*.
Melngailis, I. See Stillman, G. E.
Mel'nichenko, L. G., and Minakov, V. A. Study of sitall formation in glasses in the system CaO-Al_2O_3-SiO_2, (2) 51*j*.
Mel'nikov, F. I. See Gervids, I. A.
Melpar, Inc. Preparation of fiber-reinforced metal alloy composites by compaction in the semimolten phase, P (7) 253*a*. Process for producing thin film rectifying junctions with graded CdSe-ZnSe film, P (4) 116*b*. Thin film ferrites, P (7) 258*b*.
Melrose, J. C. Immersion heat relations for homogeneous surfaces, (1) 30*i*.
Mench & Miksits Research & Mfg. Co., Inc. Vane control for air classifier, P (7) 263*d*.
Mendelson, M. I. Average grain size in polycrystalline ceramics, (10) 350*h*.
Menelly, R. A., and Kimball, L. W. Apertured fluorescent lamp with lens along the aperture, P (10) 344*a*.
Menis, O., and Rains, T. C. Determination of arsenic by atomic absorption spectrometry with an electrodeless discharge lamp as a source of radiation, (10) 347*e*.
Menkovskii, M. A., Churbakov, V. F., Chernov, N. I., Spektor, A. N., Karabasov, Yu. S., and Churbakova, T. I. Germanates of trivalent iron, (4) 137*g*.
Menon, A. K. See Jacobs, P. W. M.
Meny, L. See Bailly, H.
Menzel, E. R. See Gruber, J. B.
Mercade, V. Method for beneficiating clay by flotation of colored impurities, P (11) 382*c*. Talc beneficiation, P (11) 383*a*.
Merchant, C. O., and Johnson, J. H. Color gun beading apparatus, P (6) 212*i*.
Merchant, H. D. See Bhatt, S. J.; Weaver, E. A.
Mercuri, R. A. Densification of boride compositions, P (7) 252*j*. See Volk, H. F.
Merdian, A. W., Jr. Temperature compensation of crystal-controlled circuit, P (10) 346*e*.
Merdian, J. T. See Blumenfeld, J. F.
Merkel, E. See Jacobi, R.
Merkelo, H. See Keune, D. L.
Merkulova, E. N. See Lapteva, A. S.
Merlin, J., Gobin, P., Jouquet, G., and Rappeneau, J. Internal friction of graphites, (4) 140*f*.
Merritt, F. R. See van der Ziel, J. P.
Mersol, S. A. See Vahldiek, F. W.
Mertsoc, M. M. See Claypoole, S. A.
Mertzweiller, J. K., Cull, N. L., and Hawley, R. S. Glass fibers sized with hydroformylated polymer and laminate therefrom, P (5) 174*f*. Sizing glass fibers with polybutadiene-dicarboxylic acid anhydride amino salt adducts, P (4) 101*b*.
Merz, E. See Kaiser, G.
Meschel, S. V. See Kleppa, O. J.
Meschel, S. V., and Kleppa, O. J. Enthalpies of mixing in ternary fused nitrates, (5) 194*e*.
Meschi, J. E. See Bartlett, P. G.
Meshkauskas, Yu. I., Barkauskas, V. I., Mazheika, R. A., and Zhlinskas, R. P. Keramsit Porous Concrete, B (8) 302*g*.
Meshkuotis, Yu. A. See Lautsyus, A. S.
Meshkuotis, Yu. A., and Pranauskene, G. B. Stability of electrical parameters of thin layers, (9) 311*a*.
Meshkuotis, Yu. A., and Tolutis, V. Conductivity of thin-film metal-dielectric systems, (9) 310*c*.
Mesler, L. L. Semiconductor diode construction and mounting, P (11) 378*e*.
Mesmer, R. E. See Hudson, R. B.
Messer Griesheim G.m.b.H. Process for producing cement and similar materials, P (7) 245*e*.
Messler, D. R. Evaporation of hypostoichiometric plutonium dioxide from 2070° to 2380°K, (1) 29*c*. Kinetics of hydrolysis of single crystal CaF_2 from 1000° to 1120°C, (5) 196*e*.
Messinger, S. See Dixon, J. K.
Messner, E. Practical testing of adhesion of sheet ground-coat enamels, (1) 5*c*.
Mestdagh, G., Flipot, A. J., and Smolders, A. Considerations on the nature and importance of the cladding/UO_2 gap under irradiation, (2) 54*h*.
Metacon AG. Molten metal pouring spout, P (11) 375*d*.
Metallgesellschaft Akt.-Ges. Method and apparatus for controlling sintering processes in conveyor type sintering machines, P (1) 23*b*.
Metco, Inc. Composite carbide flame spray material, P (4) 93*j*. Molybdenum flame spray wire and process, P (10) 337*c*. Nozzle and gas mixing arrangement for powder type flame spray gun, P (10) 337*d*.
Meth, M. Method of tempering glass, P (9) 308*c*.
Methfessel, S. J. See Holtzberg, F.
Mettke, P. Ceramic impressions of a journey in Persia—mosques in Isfahan, (5) 169*i*; (II) Teheran—formerly Rhages, (6) 205*j*.
Metz, W. See Knappwost, A.
Metzger, G. W. Heat exchange structure for rotary kilns, P (6) 228*f*.
Meuleman, J. Radiation detectors having a semiconductor body, P (10) 345*i*.
Meussner, R. A. See Fujii, C. T.
Meyer, D. A. See Daly, J. H.
Meyer, D. E., and Hackerman, N. Adsorption thermodynamics of the interaction of water and various silica powders, (4) 126*g*.
Meyer, D. E., and Wells, J. E. Surface areas and *c* values for chemically etched and thermally oxidized silicon single-crystal surfaces by krypton absorption, (1) 38*i*.
Meyer, J. H. See Thompson, R. J.
Meyercord Co. Method of applying a [heat release] vitreous decalcomania, P (7) 249*c*, P (8) 277*h*.
Meyers, N. I. See Jorgensen, M. H.
Mezi, E. See Cogliati, G.
Mezoff, J. G. See Olstowski, F.
Micale, F. J., and Zettlemoyer, A. C. Kinetics of desorption of water from the rutile surface, (1) 31*d*.
Michael, B. D. See Adams, G. E.
Michael, M. W. Process for preparing a crystalline zeolite catalyst composite, P (6) 230*a*. See Innes, W. B.
Michal, E. J., and Nilsen, A. E. Titanium dioxide concentrate and method for producing the same, P (8) 288*d*.
Michalec, R. See Zelenka, J.
Michalko, E. Crystalline zeolite, P (6) 229*f*.
Michaud, A. L. See Mas, R. J.
Miche, A. Process for agglomerating vitrifiable masses and the products thereof, P (9) 308*b*.
Michel, D. See Collongues, R.
Michel, H., and Seiter, G. Process of fabricating a metal base transistor, P (5) 185*c*.
Michel, M. See Graulier, M.
Michel, M., and Papee, D. Preparation of hydrargillite, P (4) 125*g*. Process for producing water dispersible hydrargillite, P (4) 125*c*.
Michels, H. Natural gas burners with added compressed air for heating glassmelting tanks, (9) 306*a*.
Michigan Chemical Corp. Method of separating yttrium from rare earths by ion exchange, P (10) 349*e*.
Mickelsen, R. A. Effects of ultraviolet irradiation on the properties of evaporated silicon oxide films, (6) 220*f*.
Mickey, J. See Hammel, J. J.
Microwave Associates, Inc. Ferrite junction circulators having biasing connector wire at ferrite center, P (10) 344*h*. Semiconductor diode construction and mounting, P (11) 378*e*. Semiconductor diodes of the junction type having a heat sink at the surface nearer to the junction, P (10) 346*c*. Silicon semiconductor with metal-silicide heterojunction, P (11) 378*j*.
Middlehock, A. See Dekker, A.
Middlemost, E. Petrogenetic model for the evolution of the anorthosite kindred, (8) 296*b*.
Midkiff, L. J., Jr., and Thomas, G. Unique kiln design can save up to 75% fuel costs, (8) 286*e*.
Midwinter, J. E. Infrared up-conversion in lithium niobate with large bandwidth and solid acceptance angle, (9) 323*i*.
Mields, A., and Piotrowski, P. Possibilities of determining grain sizes below 1 μm, (11) 380*d*.
Mielenz, R. C. See Kelly, T. M.
Mieure, J. P. See Jones, J. L.
Migeotte, P. Critical study of some methods of measuring the optical characteristics of glass for glazing, (6) 208*f*. Optical characteristics of the windshield, (6) 210*d*.
Migitaka, Masatoshi. Reverse biased semiconductor laser light modulator fabricated from same material as laser light source, P (11) 378*a*.
Mignen, B. Preformed blank for multifocal lens, P (2) 54*a*.
Mihama, K., and Tanaka, M. Electrostatic field effect in the epitaxial growth of gold particles evaporated onto sodium chloride, (6) 232*c*.
Mikadze, I. S., Zaionts, R. M., and Ilyukhina, I. A. Acid-resistant plates for lining sufite cellulose digesting vessels, (11) 372*g*.
Mikaelyan, R. G. See Krotova, L. V.
Mikelberg, S. Glare reduced light ray screen, P (1) 10*c*.
Mikhail, R. Sh. See Brunauer, S.; Razouk, R. I.
Mikhail, R. Sh., Brunauer, S., and Bodor, E. E. Investigations of a complete pore structure analysis (I) analysis of micropores, (1) 31*i*.
Mikhail, R. Sh., and Fahim, R. B. Thermal treatment of thorium oxide gel at low temperatures, (8) 287*c*.
Mikhailov, N. V. See Lishanskii, B. A.
Mikhailovskii, G. A. See Kabanov, A. N.
Mikheeva, V. I., and Arkhipov, S. M. Borohydrides of rubidium and cesium, (7) 264*b*.
Miki, Hiroshi. Effects of the initial reaction between milky lime and carbon dioxide gas on the crystal of calcium carbonate, (4) 91*c*.
Mikoda, Masanari; Hikino, Tadashi; and Kuroda, Takayuki. Vitreous ceramic compositions, P (5) 176*c*.
Mikos, M. See Brzozowski, W.
Mikovsky, R. J. See Kerr, G. T.
Miksitz, F. J. Vane control for air classifier, P (7) 263*d*.
Mikus, C. A. See Curtze, E. W.
Mikus, F. F. See Toma, S. Z.
Milberg, M. E., and Peters, C. R. Cation distribution in thallium silicate glasses, (8) 275*j*.
Milberg, Z. P. See Chkalova, V. V.
Milch, A., Lalak, J. J., and Ahlert, R. H. Method of forming ceramic-to-metal seal, P (7) 257*d*.
Miles, G. D., Clarke, F. J. P., Henderson, B., and King, R. D. Heat treatment and deformation of magnesium oxide single crystals, (2) 78*a*.
Milewski, J. V. See Shyne, J. J.
Milford, M. H. See Smith, D. L.
Milgram, A. A., and Lu, Chih-Shun. Electrical and structural properties of mixed chromium and silicon monoxide films, (4) 110*e*.
Mill, B. V. Hydrothermal synthesis of silicates and germanates with garnet-type structure, (7) 267*b*.
Mill, B. V., and Klevtsov, P. V. Conditions of hydrothermal synthesis of yttrium-iron garnet, (7) 264*b*.
Mill, B. V., Zadneprovskii, G. M., and Bakanin, V. V. New compounds with garnet type structure, (7) 267*f*.
Millen, D. J. Mircrowave spectroscopy and its potentialities for chemical analysis, (4) 120*d*.
Miller, A. Determination of the valence state of copper in cubic $CuMn_2O_4$ spinel by X-ray absorption edge measurements, (9) 319*f*.
Miller, A. A. Polymer-melt viscosity and the glass transition—an evaluation of the Adam-Gibbs and the free-volume models, (4) 97*b*.
Miller, A. D. See Vozzella, P. A.
Miller, C. A. High density sintering of pure barium titanate, (2) 67*h*.
Miller, C. E. See Pearson, A. D.
Miller, C. F. See Angstadt, R. L.
Miller, C. F., and Zenker, R. O. Apparatus to sever [gold] wire bonded to semiconductor devices, P (9) 312*b*.
Miller, C. F., Zenker, R. O., and Durant, B. G. Apparatus for effecting bonding of semiconductor parts, P (9) 312*a*.
Miller, D. C. See Neugebauer, C. A.
Miller, D. G. Glass seal for a turbine, P (1) 10*f*.
Miller, E. D., Jr. Continuous casting of steel, P (4) 93*j*. See Henry, G. R.
Miller, H. D. Plurality of ceramic spacers for separating planar grids, P (6) 223*f*.
Miller, I. C. Method of connecting together a plurality of transducer segments, P (10) 345*e*.
Miller, J. D. Package for elongate frangible articles [glass stemware] having wide thin extremity portions, P (10) 339*i*.
Miller, J. G., and Bolef, D. I. Acoustic wave analysis of the operation of quartz-crystal film-thickness monitors, (7) 254*e*.
Miller, J. R. See Tredennick, W. T.
Miller, K. F., and Smith, M. H. Method of making a piezoelectric device, P (11) 377*e*.
Miller, L. F. Method of joining a component to a substrate, P (6) 222*c*.
Miller, L. F., and Spielberger, R. K. Method of rendering noble metal conductive composition nonwettable by solder, P (1) 18*d*.
Miller, P. B., and Kwok, P. C. Microscopic free energy and order parameters of antiferroelectrics, (4) 144*j*.
Miller, R. C. Generation of second harmonic optical wave energy, P (2) 65*a*. See Ryan, F. M.
Miller, R. E. Heat-initiated phosphate-bonded compositions, P (5) 178*h*.

Miller, R. E., and Lerol, G. E. Raman spectrum of crystalline sodium nitrate, (5) 199*i*.
Miller, R. J., and Russell, R., Jr. BaO glasses in high alumina ceramics, (10) 343*d*.
Miller, R. R. See Walker, B. E., Jr.
Miller, S. See French, J. W.
Miller, S. E. Clay catalyst for polymerization of unsaturated fatty acids, P (4) 124*i*. See Reid, F. J.
Millet, J. See Asquiedge, M.; Guillou, M.
Milliler, A. Variations in the soluble salt content of clays, (5) 179*j*.
Millikan, R. C. Electric heat lamp and electric devices, P (4) 112*d*. Electric incandescent lamp and method of manufacture, P (9) 307*c*.
Millikan, R. C., and Osburg, L. A. Direct filament enclosed incandescent lamps and contact means therefor, P (9) 307*b*.
Milliken, T. J. Method of applying a [heat release] vitreous decalcomania, P (7) 249*c*, P (8) 277*h*.
Millington, A. D. See Barrer, R. M.
Millner, T. See Horacsek, O.
Mills, D., and Craig, G. B. Plastic deformation of zirconium-oxygen alloy single crystals in the range 77° to 950°K, (4) 149*j*.
Mills, J. H. See Lewis, E. W.
Mills, R. See Spedding, P. L.
Mills, W. H., and Dillard, P. D. Homogenization of glass, (2) 49*i*.
Millward, A. F. Effects of light on glass pH electrodes, (7) 260*b*.
Milyukov, E. M. Crystallization of glasses in the Li_2O-Al_2O_3-SiO_2 system, (8) 276*c*. Electron microscopy of crystallization of glasses in the system Li_2O-Al_2O_3-SiO_2, (1) 6*i*. See Avgustinik, A. I.; Zorina, M. L.
Mimura, Yoshiaki. See Nagatsu, Hiroshi.
Minagawa, Katsuji. See Ikeda, Koichi.
Minagawa, Shigekazu, and Gejyo, Tetsuo. X-ray microtopographs of alpha alumina whiskers, (7) 270*f*.
Minakov, V. A. See Mel'nichenko, L. G.
Minami, Kuniyuki. See Matsuzaki, Teizo.
Minami, Tsutomu. See Hattori, Makoto.
Minar, S. Fine lines on flat glass drawn by the Pittsburgh method, (1) 7*d*.
Mine Safety Appliances Co. Preparation of boron filaments in an electrical discharge, P (7) 253*a*.
Mineeva, R. M. See Morfunin, A. S.
Minehisa, Setsuji. See Nakai, Tsuneo.
Minkiewicz, V. J. See Shirane, G.
Minks, F. M. Resistor unit and method of making same, P (7) 257*i*.
Minnesota Mining & Mfg. Co. Abrasive flap wheel, P (2) 43*f*. Ceramic greensheets, P (11) 371*b*. Coating solid particles with refractory metals, P (8) 279*b*. Composite green structures for nuclear fuel element, P (7) 252*i*. Fuel elements, P (10) 342*d*. Piezoelectric semiconductor [ZnO] acoustic wave signal device, P (6) 223*e*. Retroreflective structure and method of making same, P (5) 176*e*. Structural articles [honeycomb] and method of making, P (8) 280*e*. Thermoelectric compositions of tellurium, manganese, and lead and/or tin, P (1) 19*f*. Zinc oxide maximum efficiency transverse wave crystals and devices, P (7) 258*e*.
Minnier, H. B. See Herbert, W. C.
Minoh, Arimichi. See Kasuya, Takahiro.
Minowa, Susumu; Yamada, Mamoru; Kato, Makato; and Nishizaki, Kenichi. Wettability of refractories by molten slag and molten glass, (5) 174*c*.
Mirak'yan, M. M. See Ermolaeva, E. V.
Mirak'yan, V. M. See Satarin, V. I.
Mircea, S., Corneanu, A., Mogosanu, E., and Ivaniov, W. Study of some refractory clays for chamotte quality improvement, (1) 13*f*.
Mires, R. W. See Arnold, D. J.
Mirliss, M. J. See Kerry, H. A.
Mironov, K. E. Transport reaction for the growth of praseodymium phosphide, (9) 332*d*.
Mirsoyanov, V. N. See Dibrov, G. D.
Miselbach, R. G. See Stirling, J. F.
Mishchenko, S. F. See Orobchenko, V. I.
Miska, W. S. Refractory use patterns in the iron and steel industry of the United States, (2) 57*h*.
Misra, S. K. See Chaklader, A. C. D.
Missiroli, A. See Donati, G.
Mississippi Glass Co. Method and apparatus for forming glass channels, P (5) 175*h*.
Mita, Masaaki. Contribution of titanium dioxide to the manufacture of firebrick, (10) 340*i*.
Mita, Masaru. Magnon analysis of ferromagnetic resonance in a planar ferrite, Zn_2Y, (8) 294*d*. Two-magnon ferrimagnetic resonance line width of hexagonal ferrite Zn_2Y, (2) 84*d*.
Mitchell, A. Reactions of calcium silicates in solution in liquid calcium fluoride, (4) 152*g*.
Mitchell, A. C. See Hawke, R. S.
Mitchell, J. H. Writing for Professional and Technical Journals, B (2) 86*b*.
Mitchell, J. M. See Lakshmanan, T. K.
Mitchell, J. T. See Anderson, W. W.
Mitchell, L. How variables in raw materials influence engineered brick properties, (8) 278*g*.
Mitchell, M. M. See Dawson, R. H.
Mitchell, W. B. Contacts for insulation isolated semiconductor integrated circuitry, P (7) 256*c*.
Mitin, B. S., and Levin, V. Ya. Surface reaction of liquid oxides with high-melting metals, B (5) 204*j*.
Mitoff, S. P. Electrical conduction mechanisms in oxides, B (7) 272*h*. Electrical device comprising metal oxide-containing solid electrolyte and electrode, P (7) 256*e*. Electrical device including stabilized zirconia solid electrolyte, P (2) 64*i*. See Fullman, R. L.
Mitoff, S. P., Tragert, W. E., and Fullman, R. L. Article comprising stabilized zirconia and a current collector embedded therein, P (2) 64*f*.
Mitomo, M. See Inomata, Y.
Mitra, N. K. See Gupta, H. N. D.
Mitra, N. K., Ganguly, P. K., and Datta, R. K. Effect of zirconia substitution on durability of some zirconia soda-silica glasses, (10) 337*i*.
Mitra, S. S. See Brafman, O.
Mitrofanov, K. P. See Fedorovskii, Ya. A.
Mitsui Mihonbashi Muromachi. See Furukawa Electric Co., Ltd.
Mitsui, Toshio. See Harada, Jimpei.
Mitsuka, Yuichi. See Murakami, Keiichi.
Miura, Eiji. See Hibino, Taizo.
Miura, Yoshinari. See Hirai, Taketsugu; Takahashi, Katsuaki.
Miura, Yoshio, and Matukura, Yasuo. Instabilities of MOS structure, (9) 323*c*.
Miyashita, Kazuo. See Hariu, Takashi.
Miyata, Kenichi. Variation of surface characteristics of quartz powder with particle size (I) variation of amorphous character of the surface and water vapor adsorption characteristics of quartz powder with particle size, (4) 163*a*. See Oya, Yoshiko.
Miyatake, Kazumi. Properties of high-fired basic brick used in open-hearth furnace, (11) 373*f*. Results of tests on tar dipped brick for cupola lining—erosion due to changes in atmosphere, (10) 342*g*.
Miyatake, Kazumi, and Furumi, Koichi. Results of refractoriness-under-load test conducted on some magnesia clinker samples, (10) 342*e*.
Miyatake, Kazumi; Furumi, Koichi; and Kano, Hiroshi. Chemical and physical changes in direct-bonded basic brick used in walls of electric furnace, (10) 340*i*. Comparison of fused and dead-burned magnesias, (4) 103*j*. High-fired basic brick used in 150-ton open-hearth furnace roof, (2) 56*a*. Mechanism of wear in fused-cast magnesia brick used in walls of electric furnace, (10) 341*c*. Slag corrosion resistance of high-fired, fired, and unfired basic brick, (11) 374*f*.
Miyatake, Kazumi; Furumi, Koichi; and Ohishi, Masamoto. Effect of heating atmosphere on crystal growth of periclase, (7) 250*f*.
Miyatake, Kazumi; Furumi, Koichi; and Shikano, Hiroshi. Changes in properties of direct-bonded basic brick in electric furnace walls having different SiO_2 contents, (7) 250*g*.
Miyatake, Kazumi; Furumi, Koichi; and Yagi, Takuo. Corrosive effect of slag composition on dolomite clinker, (11) 372*i*.
Miyatake, Kazumi, and Kaita, Takao. Corrosion resistance of Cr_2O_3-containing high silica pyrophyllite brick for cupola, (7) 250*e*. Results of service test on unfired brick used in cupola lining (II), (11) 374*a*.
Miyatake, Kazumi; Semba, Kimio; and Hosokawa, Shumei. Effect of tar saturation on performance of high-silica nozzle, (2) 55*h*.
Miyatake, Kazumi; Ueda, Masao; and Tasaki, Sueo. Stress analysis of stopper brick screw parts by photoelasticity, (7) 251*h*.
Miyatani, Shinya; Toyota, Yukio; Yanagihara, Takashi; and Iida, Kiichi. α-Ag_2Se as a degenerate semiconductor, (1) 25*a*.
Miyauchi, Takeshi; Sonomura, Hajimu; and Yamamoto, Nobuyuki. Electroluminescence and crystallographic polarity of gallium antimonide, (9) 321*f*.
Miyazaki, Hidetoshi. Dehydration process of calcium sulfate dihydrate, (5) 170*d*.
Miyazaki, Hidetoshi, and Mizuguchi, Jun. Microscopic observation of the formation of calcium sulfate hemihydrates, (5) 170*g*.
Mizuguchi, Jun. See Miyazaki, Hidetoshi.
Mizuno, Hideo. See Kobayashi, Yoshichika.
Mizuno, Hideo; Akutsu, Hidezo; Moriguchi, Eijiro; Yamashita, Katsuyuki; Kamiya, Shigeru; Iwata, Koshi; Tawara, Yoshio; and Iga, Atsushi. Discharge tube, P (5) 182*e*. Discharge tube satisfactorily low in radio-interfering noise, P (5) 182*f*.
Mizuno, Koichi. Process for the manufacture of a bearing surface on a steel article including a single sintered layer of bronze particles and a layer of polytetrafluoroethylene, P (4) 94*a*.
Mizuno, Masao. See Noguchi, Tetsuo.
Mizuno, Masao, and Noguchi, Tetsuo. System Y_2O_3-Al_2O_3 (I) formation of compounds; (II) liquidus curve measurement, (4) 159*g*. ZrO_2-TiO_2 system (III) change of mineral composition in ZrO_2-TiO_2 system by heat treatment, (4) 164*e*.
Mizuno, Shigeki. Results of refractoriness-under-load test conducted on some magnesia clinker samples, (10) 342*e*. See Ohta, Z.
Mizuo, Masahiko. See Matsuzaki, Hiroyuki.
Mizushima, Koichi, and Iida, Shuichi. Direct check of electron diffusion in ferrites by a microwave technique, (1) 16*h*.
Mizushima, Masahiro. Induced anisotropy in $Mn_{1+x}Fe_{2-x}O_4$ single crystals at low temperatures, (2) 78*f*.
Mizushima, Yoshihiko. See Daikoku, Kazuhiro.
Mizuta, Hiroshi. See Kawamura, Sukezo.
Mizutani, Chihiro. See Yamada, Tamotsu.
Mlavsky, A. I. See Di Benedetto, B. A.; LaBelle, H. E., Jr.
Mobay Chemical Co. Transparent safety laminates and method of making same, P (2) 54*b*.
Mobil Oil Corp. Conversion of ammonium aluminosilicate to hydrogen aluminosilicate, P (4) 124*j*. Conversion of clays to crystalline aluminosilicates and catalysts therefrom, P (6) 229*c*. Crystalline galliosilicates, P (6) 229*e*. Lithium-containing crystalline aluminosilicate, P (4) 124*d*. Method for preparing high-silica faujasite, P (11) 382*e*.
Mochel, E. L. Method of treating strengthened glass surface to increase acid durability, P (9) 308*d*.
Mochel, J. M. Radiation filters, P (4) 107*f*.
Modarresi, H. G. Contact gage for rapid and accurate three-dimensional grain size measurement of loose sand particles, (11) 380*a*.
Modesto, M. See Cevc, P.
Modlen, G. F. Reorientation of fibers during mechanical working, (10) 342*b*.
Modylevskaya, K. D., and Kotlyar, G. Kh. Determination of free carbon in titanium, zirconium, and hafnium carbides, (2) 69*h*.
Moe, D. L. See Kohls, D. E.
Moegele, L. Method of producing highly pure halogen compounds of gallium and indium, P (5) 184*c*.
Moehling, W. Dislocations and their origin in cadmium sulfide crystals grown from the vapor phase, (4) 131*j*.
Moertl, G. See Maier, K. M.
Moertl, G., Skalla, N., Weidner, A., and Zednicek, W. High duty Simultansinter chrome ore basic brick, (4) 104*d*.
Mogab, C. J. See Jones, T. P.
Mogosanu, E. See Barbulescu, E.; Mircea, S.
Mogucheva, V. V. See Nisel'son, L. A.
Mogutnov, B. M. See Malkin, V. I.
Moiseitseva, Z. K. See Balakir, E. A.
Mokhosoev, M. V., and Got'manova, T. T. Production of high-purity chromium oxide by zone melting, (7) 262*a*.
Molbach, A. Lamp bulb conveyor mechanism, P (1) 10*j*.
Moldavsky, F. G., and Kotelnikov, A. F. Glass preserving jars, P (6) 212*f*.
Moldovan, I., and Grudner, G. M. Method of removing titanium tetrachloride from gases, P (11) 382*e*.
Moldovan, T. See Veiser, I.
Moldovan, T., and Alexinschi, T. Manufacture of silica brick for coking plants, (10) 341*a*.
Moldvai, R., and Bubik, I. Formation of ceramic bodies having a negative coefficient of thermal expansion, (2) 60*c*.
Molecular Energy Corp. Method of producing semiconductive electronegative element of a battery, P (9) 313*d*.
Moleva, N. G., and Korovyachenko, F. K. Effect of lime on the quantity of water-soluble vanadium pentoxide in melts of the CaO-V_2O_5-Na_2O system, (8) 291*g*.
Molinaro, L. J. See Haley, K. M.
Molins Organisation, Ltd. Optical inspection devices employing light-conducting fibers, P (10) 339*g*.
Moll, J. L. See Liu, Y-Z.
Molle, L. See Hanocq, M.
Mollenkopf, H. See Weber, P.
Molochko, V. A. See Kurdyumov, G. M.
Molony, B. See Goto, M.; Ridge, M. J.
Molony, B., and Ridge, M. J. Sintering of trigonal iron(III) oxide at low temperatures, (4) 154*i*.
Momii, R. K., and Nachtrieb, N. H. Nuclear magnetic resonance in thallium borate glasses (I) thallium-205 chemical shift, (5) 173*f*.
Monasebian, A. See Hemphill, J.
Monchamp, R. R., Putthach, R. C., and Nielsen, J. W. Large noble metal can technique for hydrothermal crystal growth, (5) 187*c*.
Moncorge, G. See Huber, H.
Mones, A. H. See Block, M. L.; Davis, E. M., Jr.
Monfore, G. E. Review of fiber reinforcement of portland cement paste, mortar, and concrete, (5) 170*g*.
Monforte, F. R. See O'Bryan, H. M., Jr.
Monier, J. C. See Cadoret, R.
Monk, H., and Pepworth, D. P. Process of preparing high purity cadmium hydroxide, P (10) 349*b*.
Monks, J. R. See Grubb, E. F.
Monks, J. R., Jr. Forehearth addition process for viscosity change, P (8) 277*j*.
Monneraye, M., Serindat, J., and Jouwersma, C. Control of dielectric losses and temperature coefficient of permittivity by doping in some glass-ceramic materials, (1) 6*b*.
Monogram Industries, Inc. Toilet bowl construction, P (4) 109*c*.
Monroe, E. S., Jr. Preheating oxidizing gas reactant in TiO_2 pigment manufacture, P (9) 317*a*.
Monroe, W. H. See Ross, C. S.
Mons, W. See Paulitsch, P.
Monsanto Co. Adhered windshield with concealed adherent, P (5) 174*e*. Coated optical devices, P (5) 174*a*. Gauze catalyst support, P (5) 178*g*. Heat-initiated phosphate-bond-

ed compositions, P (5) 178*h*. Injection-luminescent GaAs diodes having a graded *pn* junction, P (4) 113*e*. Laminated safety glass, P (1) 10*j*. Low capacitance field effect transistor, P (8) 282*b*. Method for the preparation of inorganic single crystal and polycrystalline electronic materials, P (6) 222*d*. Method of preparing silica materials, P (6) 229*h*. Methods and apparatus for zone melting, P (6) 227*j*. Process for manufacture of crystalline pyrophosphoric acid, P (10) 349*f*. Process for the preparation of compound semiconductors, P (11) 378*j*. Process for preparing crystalline boron arsenide, P (4) 116*b*. Process for producing multivalent metal pyrophosphates, P (1) 24*c*. Production of alkaline earth metal pyrophosphates, P (2) 74*e*. Production of sodium tripolyphosphate, P (6) 230*c*. Resistance heating elements and methods of conditioning the heating surfaces thereof, P (2) 72*e*.

Monsanto Research Corp. Graphite containing composition and thermoelectric generator, P (1) 18*f*. Heat-resistant coatings, P (10) 337*e*. Heat-resistant silicone resin coating, P (10) 337*e*. Incused graphite segmented thermoelement, P (6) 221*g*. Thermoelectric body including pyrolyzed reaction product of pyromellitonitrile and alkanol and with comminuted metal, P (1) 19*f*.

Montagut-Buscas, M., Salvat, J. O., and Rodriguez, E. Determination of cobalt in cement, (4) 91*e*.

Montecatini Edison S.p.A. Crystalline $TiCl_3$ and method of preparing same, P (11) 382*j*. Preparation of delta form crystalline titanium trichloride, P (9) 317*b*. Production of boron nitride, P (5) 179*d*.

Montgomery, D. S., and Parsons, B. I. Process for the preparation of an inorganic gel having a predetermined pore structure, P (4) 125*i*.

Montgomery, R. S. Wear resistant cobalt bonded tungsten carbide composite, P (10) 343*c*.

Montgomery, T. S. Lattice spacings of periclase-chromite solid solutions, (4) 142*h*. Optical reflectance spectra of Cr^{3+} in MgO solid solutions, (11) 370*b*.

Mony, C. N. See Joseph, P. T.

Monzo, A. B. Present day Spanish art ceramics, (6) 206*a*.

Moodie, A. F., and Warble, C. E. Observation of primary step growth in magnesium oxide by direct transmission electron microscopy, (1) 33*f*.

Moody, P. M. R. See Steele, B. C. H.

Mooi, J. See Ballard, H. D., Jr.

Moolenaar, R. J., and Neipert, M. P. Process for removing polyvalent metal impurities from lithium aluminate, P (9) 317*e*.

Mooney, E. F. (editor). Annual Review of NMR Spectroscopy (Vol. 1), B (4) 165*i*.

Mooney, J. J. See Keith, C. D.

Mooradian, A., and McWhorter, A. L. Polarization and intensity of Raman scattering from plasmons and phonons in gallium arsenide, (4) 150*c*.

Mooradian, A., and Wright, G. B. First order Raman effect in III–V compounds, (4) 136*i*.

Moore, A. See Taylor, H. F. W.

Moore, A. R. Zinc oxide maximum efficiency transverse wave crystals and devices, P (7) 258*e*.

Moore, E. E. See Hirschberg, E. E.; Spielman, L. S.

Moore, F. D. Vibratory mill and its operation, P (6) 225*e*. See Eckert, J. S.

Moore, F. L. Extraction of berkelium values in the tetravalent state using 2-thenoyltrifluoroacetone, P (2) 67*i*. Method of extracting soluble metal complexes using amine solvents, P (2) 68*b*. Method of separating berkelium from cerium, P (1) 24*a*.

Moore, J. P. See Fulkerson, W.

Moore, K. E., and Young, W. A. Phase studies of the zirconium-hydrogen system at high hydrogen concentrations, (9) 327*h*.

Moore, M. J., and Kasper, J. S. Crystal structure of AgI at 3 kbar, (4) 130*f*.

Moore, P. B. Crystal structure of sapphirine, (9) 319*g*, (10) 351*d*. See Birle, J. D.

Moore, P. B., and Smith, Joseph V. High-pressure modifications of Mg_2SiO_4 crystal structure and crystallochemical and geophysical implications, (10) 354*h*.

Moore, P. B., and Smyth, J. R. Crystal chemistry of the basic manganese arsenates (III) crystal structure of eveite, $Mn_2(OH)(AsO_4)$, (10) 351*g*.

Moore, W. G. Method of preparing manganese dioxide, P (7) 263*a*.

Moore, W. J. See Shenker, H.

Moore, W. P., and MacGregor, R. R. Process for the production of phosphoric acid and cement material, P (7) 245*f*.

Moorthy, V. K. See Kulkarni, A. K.

Moorthy, V. K., and Anandan, N. S. Sintering of UO_2—a study of the development of high density and controlled microstructure in sintered urania pellets, (11) 374*e*.

Moorthy, V. K., and Bhat, R. Sintering of beryllia (IV) mechanism of sintering during hot-pressing of beryllia, (11) 374*d*.

Moorthy, V. K., and Rao, S. V. K. Evaluation of crystallinity of urania powders by streaming potential studies, (2) 55*h*. Role of crystallinity in the sintering of urania powders, (2) 57*d*.

Moos, H. W. See Huang, J. W.

Mooser, E., and Brebner, J. L. Electroluminescence from cooled homogeneous gallium sulfide crystal, P (8) 282*f*.

Mora, A. Process for manufacturing resiliently yielding bases provided with abrasive surfaces and product thus obtained, P (1) 1*i*.

Morane, S. J. Production of beryllium fluoride, P (4) 125*e*.

Moravek, J. See Lach, V.

Mordovin, O. A., Timofeeva, N. I., and Drozdova, L. N. Determination of the melting points of oxides of rare-earth elements, (8) 290*c*.

Moreau, C. See Poncelet, J.

Moreau, J. M. Crystallographic and magnetic study of rare-earth double oxides of the type $LaTO_3$ where T=Ho, Y, Er, Tm, Yb, Lu, (6) 231*b*.

Morel, P. H. Field effect transistor in an integrated circuit having an embedded grid, P (6) 221*a*.

Morel, R. C. M., and Tauveron, P. Method and apparatus for the electrostatic sorting of granular materials, P (1) 20*e*, P (2) 74*d*.

Moreland, A. K. See Burke, M. F.

Moreland, G. C. Preparation of polished thin sections, (8) 285*i*.

Moreno, E. C., Gregory, T. M., and Brown, W. E. Preparation and solubility of hydroxyapatite, (6) 236*e*.

Morey, G. H. Method for making electric resistance heaters, P (5) 183*f*.

Morey, G. W. See Rowe, J. J.

Morfunin, A. S., Bershov, L. V., and Mineeva, R. M. Electron paramagnetic resonance of VO^{2+} in sphene and apophyllite and Mn^{2+} in tremolite, apophyllite, and scheelite, (1) 28*i*.

Morgan, A. M. See Sewell, P. A.

Morgan, C. S. Activation energy in sintering, (10) 349*h*. Comment on "Dorn method in the study of initial phase of uranium dioxide sintering," (1) 26*g*.

Morgan, C. S., and Hall, L. L. Creep of ThO_2 and ThO_2-CaO solid solutions, (2) 75*f*.

Morgan, D. V., and Chadderton, L. T. Fission fragment tracks in semiconducting layer structures, (4) 136*i*.

Morgan, E. S. Effect of stress on the thermal emf of platinum-platinum/13% rhodium thermocouples, (6) 228*f*.

Morgan, J. F. See Schmidt, R. L.

Morgan, J. H. See Dickinson, G. A.

Morgan, J. J. See Black, A. P.

Morgan, W. J. See Mackey, R. W.

Morgan Refractories, Ltd. Protecting and insulating covering for furnace support members, P (9) 309*d*.

Mori, E. A. See Goodwin, R. J.

Mori, Hideo. See Shibata, Shinichi.

Mori, Kazumi, and Suzuki, Kanae. Density of iron oxide melt in equilibrium with CO_2-CO gas mixture, (8) 290*j*.

Mori, Sadao, and Hayashi, Takeshi. Results of cooperative studies concerning refractoriness-under-load test conducted on some magnesia clinker samples—Area of Chuugoku and Shikoku, Japan, (10) 342*d*. Results of refractoriness-under-load test conducted on some magnesia clinker samples, (10) 342*e*.

Mori, Tokio. See Oda, Zenjiro.

Moriguchi, Eijiro. See Mizuno, Hideo.

Morimoto, Nobuo. Polymorphism of $MgSiO_3$, (1) 34*i*.

Morimoto, Nobuo; Akimoto, Syun-iti; Koto, Kichiro; and Tokomani, Masayasu. Modified spinel, beta-manganous orthogermanate—stability and crystal structure, (11) 386*e*.

Morimoto, Nobuo, and Tokonami, Masayasu. Domain structure of pigeonite and clinoenstatite, (11) 384*a*.

Morimoto, Tetsuo, and Nagao, Mahiko. Rate of surface hydration on alumina, (4) 152*a*.

Morin, E. P. See Zilberman, E. K.

Morita, Eiichi. See Chisaka, Haruo.

Moritz, H. Use of platinum in the glass industry, (4) 98*a*.

Moriya, Yoshiro, Warrington, D. H., and Douglas, R. W. Study of metastable liquid-liquid immiscibility in some binary and ternary alkali silicate glasses, (2) 51*f*.

Morizane, K., Witt, A. F., and Gatos, H. C. Impurity distribution in single crystals (III) impurity heterogeneities in single crystals rotated during pulling from the melt, (4) 139*e*; (IV) growth characteristics and impurity incorporation during facet growth, (10) 355*j*.

Morley, A. R., and Campbell D. S. Annealing behavior in vacuum-deposited films of silicon oxide, (8) 280*i*.

Morley, A. R., Campbell D. S., and Anderson, J. C. Conduction processes in vacuum-deposited films of silicon oxide, (10) 343*h*.

Morley, H. B., Skrzec, A. E., and Shiloff, J. C. Process for producing boric acid from alkali metal borates, P (10) 349*c*.

Morlotti, R. See Pizzini, S.

Moroney, W. J., and Chalifour, H. R. Semiconductor diodes of the junction type having a heat sink at the surface nearer to the junction, P (10) 346*c*.

Moroshima, Heiji. Semiconductor device for high frequency and high power use, P (8) 283*f*.

Morosin, B. Crystal structures of anhydrous rare-earth chlorides, (9) 319*h*.

Moroz, I. I., and Kharitonov, Ya. G. Relationship of water resistance, water absorption, and strength of porcelain greenware to heating temperature, (6) 219*d*.

Moroz, I. I., and Sarkisov, G. G. Thermal shock resistance of porcelain, (6) 219*h*.

Morozov, I. S., and Lipatova, N. P. Properties of compounds formed by tetrachlorides and oxychlorides of tetravalent niobium with the chlorides of the alkali metals and ammonia, (7) 268*g*.

Morrell, H. P. See Chandler, H. H., Jr.

Morrill, V., Jr. Apparatus for forming precision glass tubing from a molten glass supply, P (1) 10*g*.

Morris, D. F. C. Ionic radii and enthalpies of hydration of ions, B (6) 242*g*.

Morris, H. H., and Olivier, J. P. Process for improving the brightness of clay, P (7) 263*d*.

Morris, R. W. Mesa type combined direct viewing storage target and fluorescent screen for cathode ray tube, P (1) 18*a*.

Morris, W. C., and Baran, R. J. Process for coating [glass] with epoxy compositions, P (4) 100*h*.

Morrisette, M. J. Thermocouple probe assembly and temperature sensing circuits comprising the same, P (4) 122*b*.

Morrisey, R. G. Increasing use of LP-gas, (2) 72*c*.

Morrish, A. H. See Sawatzky, G. A.

Morrison, G., and Lind, J. E., Jr. Effect of the internal coulomb field on the viscosity of a fused salt, (11) 384*f*. Friction constants for fused salts, (8) 292*c*.

Morrison, I. R., and Wilson, A. L. Absorptiometric determination of silicon in water (VI) determination of polymeric silicic acid, (7) 259*g*.

Morrison, J. R. See Bate, G.; Reed, L. J.

Morrison, S. R. See Hauffe, K.

Morritz, F. L. See Galli, G.; Manasevit, H. M.; Zanowick, R. L.

Morse, S. A. Revised dispersion method for low plagioclase, (6) 237*i*.

Morse, T. H. See Valley, R. B.

Morse, W. C. Second overtone DT-cut quartz resonator, P (2) 66*a*.

Mortimer, D. See Footner, P. K.

Mortland, M. M. See Gastuche, M. C.

Mortley, W. S. Diffusion paths in quartz, (10) 352*h*.

Morton, J. A. See Kahng, D.

Morton, J. R. Method of separating yttrium from rare earths by ion exchange, P (10) 349*e*. See Brailsford, J. R.

Morton, W. A. Shuttle hearth furnaces, P (1) 23*b*.

Moser, F. See Trautweiler, F.

Moser, F., and Everhart, J. J. Treatment of glass surfaces, P (4) 101*d*.

Moser, J. B., Kruger, O. L., and Handwerk, J. H. Electrical and thermal properties of some actinide compounds, (10) 352*h*.

Moses, R. L. See Wiederhorn, S. M.

Mosheim, C. E. Process for producing high purity columbium oxide, P (2) 74*d*.

Moshkina, M. K. See Sazhin, V. S.

Moshkov, A. D., and Khanis, Yu. B. Increasing wear resistance of components of glass-shaping machines, (2) 49*j*.

Moslavac, K., and Lovreck, B. Anodic passivation of Si single crystals, (7) 263*j*.

Moss, H. I. See Stollar, W. P.

Moss, H. I., and Stollar, W. P. Method for pressing particulate material, P (9) 314*f*.

Moss, S. C. See Renninger, A.

Motegi, Hiroshi. See Harada, Jimpei.

Moteki, Kesakichi. See Nishino, Tadashi; Tomizawa, Toshiaki.

Motomura, Kinsi. Thermodynamics and phase transitions in monolayers, (1) 39*f*.

Motorola, Inc. Apparatus for horizontal zone refining of semiconductive materials, P (1) 17*i*. Encapsulated semiconductor device including a ceramic substrate, P (7) 256*g*. [Growth of] single crystal silicon rods, P (9) 312*a*. Heat conductive mounting base for a semiconductor device, P (6) 221*e*. Isolation of semiconductor devices, P (2) 65*g*. Method of fabricating a semiconductor structure with an electrically isolated region of semiconductor material [epitaxial deposition], P (11) 377*j*. Method of forming a semiconductor by masking and diffusing, P (4) 114*h*. Method of forming a temperature compensated reference diode, P (4) 114*h*. Method for making [lapping] thin semiconductor dice, P (8) 283*a*. Method for making semiconductor structure with layers of preselected resistivity and conductivity type, P (7) 257*i*. Method for polarizing piezoelectric material, P (6) 222*c*. Methods for making semiconductor structures having glass insulated islands, P (10) 345*a*. Multilayer [epitaxial] semiconductor device, P (10) 345*b*. Noise diode having an alloy Zener junction, P (10) 345*c*. Ohmic contact consisting of a bilayer of gold and molybdenum over an alloyed region of aluminum-silicon, P (7) 257*f*. Semiconductor controlled rectifier device, P (6) 223*f*.

Moudry, F. New drying methods for ceramic clays, (7) 258*i*.

Mould, R. E. Strength of inorganic glasses, B (1) 41*g*.

Moulik, S. P., Cooper, F. C., and Bier, M. Forced-flow electrophoretic filtration of clay suspensions, (1) 29*j*.

Moulson, A. J., and Popper, P. Problems associated with the measurement of the volume

resistivity of insulating ceramics at high temperature, (2) 70*f*.
Mountford, A. H. See Eardley, R. P.
Mountford, G. A. See Reimschuessel, H. K.
Mountjoy, E. W. See MacIntyre, I. G.
Moutaud, G. Process for the manufacture of macroporous vitreous carbon, P (8) 279*j*.
Mowry, C. Method of determining color using color maps, P (2) 72*a*.
Moyer, R. E. See Wilkins, C. H. T.
Moynihan, C. T. See Cantor, S.
Moynihan, C. T., and Cantor, S. Viscosity and its temperature dependence in molten BeF_2, (1) 10*a*.
Moynihan, R. E. Glass-polyurethane-polyvinyl butyral-polyurethane-glass laminate, P (11) 371*i*.
Mozzherin, Yu. V. Rotating plagioscopic method in microscopy, (2) 70*i*.
Mozzo, C. See Cuenat, P.
Mroczkowski, R. S., Witt, A. F., and Gatos, H. C. Effects of back-melting on the dislocation density in single crystals—GaSb, (5) 194*a*.
Muan, A. Determination of thermodynamic properties of silicates from locations of conjugation lines in ternary systems, (4) 131*i*. Stabilities of oxide compounds and activity/composition relations in oxide solid solutions, (5) 200*e*. See Johnson, R. E.; Nafziger, R. H.; Valla, O.; Woermann, E.
Muatacchi, C., Gautsch, O., and Wahl, H. Process for the manufacturing of fuel elements, P (6) 218*j*.
Muchow, G. M. See Ray, S.
Mueller, A., and Wagner, G. Process for preparing sand cores using CO_2 cured silicate binders, P (8) 280*a*.
Mueller, A., and Wilhelm, M. Apparatus for producing striationless bodies of metal and semiconductor substances containing impurities, P (4) 112*d*. Semiconductor crystals of fibrous structure and method of their manufacture, P (8) 283*c*.
Mueller, C. (editor). Data-Book for Ceramics, Glass, Silicates, B (4) 166*a*.
Mueller, E. Testing the properties of tamping materials, (11) 381*a*.
Mueller, E. E. High-temperature temporary protective ceramic coating compositions for metals and resulting coated metal articles, P (11) 369*c*. Low temperature temporary protective ceramic coating compositions for metals and resulting coated metal articles, P (10) 337*a*.
Mueller, F. See Schloemer, H.
Mueller, H. Shrink foil packaging of palletized goods [drain tile], (10) 340*d*.
Mueller, H. R. Method of producing electromagnesia having improved electric insulating power. P (9) 317*f*. See Patzak, I.
Mueller, K. See Reuter, B.
Mueller, K. P. See Gruner, K.
Mueller, K. R., Rabo, J. A., and Kasai, P. H. Crystalline zeolite containing singly charged nickel cations, P (4) 124*j*.
Mueller, O. H. Cyclic jet drying of clay with special consideration of the Rotomixair system, (7) 258*h*.
Mueller, R. F. High temperature and pressure aqueous solubility data bearing on the stability of silicates, (4) 138*g*. Stability of metamorphic amphiboles—the tremolite-ferroactinolite series: a discussion, (4) 156*a*.
Mueller, W. F. See Hazel, H. K.
Mueller-Buschbaum, H. Investigation of the phase transition from the monoclinic B- into the hexagonal A-form in rare-earth oxide single crystals, (9) 323*f*.
Muenchberg, W. See Obst, K. H.
Muenter, J. S. See Kaufman, M.; Kaiser, E. W.
Muhler, J. C. Dentifrice compositions comprising zirconium silicate of particular particle size. P (10) 335*h*.
Muir, D. W. B., and Hider, P. F. Optical inspection devices employing light-conducting fibers. P (10) 339*g*.
Muirhead-Gould, J. S. See Laidler, K. J.
Muirhead-Gould, J. S. and Laidler, K. J. Discontinuous model for hydration of monatomic ions, (4) 131*i*.
Mukaibo, Takashi. See Fueki, Kazuo; Yamauchi, Shigeru.
Mukerji, A. See Tanton, G. A.
Mukerji, J. See Biswas, S. R.; Dhargupta, K. K.
Mukherjee, D. K., and Roy, S. Investigations of Indian clays to trend the use of Rajmahal china clay, (4) 123*f*.
Mukhina, Z. S. See Sokolova, A. A.
Mulaskey, B. F. Hydrocracking of hydrocarbons with a catalyst composite comprising nickel and tin associated with a porous acidic inorganic oxide carrier, P (1) 23*i*. See Lindquist, R. H.
Mulay, L. N. See Dehn, J. T.; Keys, L. K.
Mulcahy, M. F. R., and Williams, D. J. Kinetics of combination of oxygen atoms with oxygen molecules, (8) 294*b*.
Mulfinger, H. O. See Upadhyaya, V. G.
Mulford, C. O., Jr., and Normington, P. J. C. Negative resistance semiconductor device, P (11) 378*a*.
Mulford, R. N. R. See Olson, W. M.
Mulhern, J. F., Rogers, T. G., and Spencer, A. J. M. Continuum model for fiber-reinforced plastic materials, (1) 28*b*.
Mullaly, J. R. See Gerstein, B. C.
Mullen, A. J. Temperature variation of the piezoelectric constant of quartz, (11) 388*b*.
Muller, A. C. Controlled defect [fused quartz] coloration dosimeter, P (10) 344*e*.
Muller, O., and Roy, R. Synthesis and crystal structure of Mg_2PtO_4 and Zn_2PtO_4, (10) 362*a*.
Muller, O., Roy, R., and White, W. B. Phase equilibria in the systems $NiO-Cr_2O_3-O_2$, $MgO-Cr_2O_3-O_2$, and $CdO-Cr_2O_3-O_2$ at high oxygen pressures, (1) 34*i*.
Muller, W. See Hohmann, H. H.
Mulligan, W. A., and Murphy, R. M. Vitreous enamel resistor composition and resistor made therefrom, P (7) 246*i*.
Mullin, J. B. Crystal melt-growth process wherein the melt surface is covered with an inert liquid, P (1) 18*d*.
Mullin, J. B., Heritage, R. J., Holliday, C. H., and Straughan, B. W. Liquid encapsulation crystal pulling at high pressures, (7) 255*d*.
Mullin, J. B., and Hurle, D. T. J. Process of growing a single crystal utilizing differences in chemical potential, P (11) 378*h*.
Mulski, F. P. Semiconductor devices adapted for pressure mounting, P (10) 346*c*.
Multani, M. S. See Bhide, V. G.
Mumper, T. O. Intermediate furnace barrier, P (4) 106*b*.
Munakata, Chusuke. Electron beam method of measuring diffusion voltage in semiconductors, (5) 187*g*. Measurement of potential distribution in a semiconductor crystal with an electron beam, (5) 187*c*.
Munge, C. G. Industrial applications of furan resins, (5) 176*g*.
Munier, M. T. L. J. Manufacture of ferroelectric parts, more particularly of transducers, P (10) 345*d*.
Munir, Z. A. See Blair, R. C.
Munn, R. W. Grueneisen functions for axial crystals, (2) 77*j*.
Munro, J. L. See Lindsley, D. H.
Munroe, J. H. See Haworth, D. T.
Murakami, Kazo; Takeda, Tsuneo; and Tsuchiya, Nobujiro. Abnormal structure of tantalum carbide phase in WC-TaC-Co alloys, (4) 102*i*.
Murakami, Keiichi; Hirakawa, Michio; and Serisawa, Yoshikiyo. Pneumatic conveyor calcination, (4) 92*b*.
Murakami, Keiichi; Tanaka, Hirobumi; and Nakura, Yoshitomi. Early stage of hydration of $3CaO \cdot Al_2O_3$ and $Na_2O \cdot 8CaO \cdot 3Al_2O_3$ as clinker minerals of portland cement, (4) 91*g*.
Murakami, Keiichi; Tanaka, Hirobumi; Narita, Mitsuaki; and Mitsuka, Yuichi. Anomalous properties of hemihydrate obtained from Kola phosphate rock, (4) 126*h*.
Murakami, Keiichi; Tanaka, Hirobumi; and Sato, Kenro. Procedures for the chemical analysis of impurities of phosphogypsum, (4) 120*g*.
Murakami, Toshiaki. Barrier height of metal-$BaTiO_{3-x}$ contacts, (1) 25*j*. Electrical conduction of metal-to-reduced $BaTiO_3$ single crystal contacts, (1) 16*b*. Properties of barrier layers of metal-to-reduced $BiTiO_x$ single crystal contacts, (2) 63*d*.
Murata, Yorihiro, and Whitney, E. D. Densification and wear resistance of ceramic systems (III) tantalum mononitride-zirconium diboride, (8) 278*j*.
Murayama, Setsuko. See Kobayashi, Yoshichika.
Murdoch, A. W., *et al.* Report of further work of the subcommittee, "to investigate a test for the measurement of adhesion of enamel to metal," (1) 5*e*.
Murdock, Inc. Hot-press insulating system, P (11) 374*j*.
Murley, E. M., Jr. Inspecting sealed [glass] containers in closed cartons, P (9) 307*g*.
Murphy, J. C., and Bohandy, J. Electric effect in ruby, (9) 320*h*.
Murphy, J. C., Kues, H. A., and Bohandy, J. Growth of crystals in silica gel using a cosolute. (9) 322*d*.
Murphy, N. A. See Banner, J. G.
Murphy, R. M. See Mulligan, W. A.
Murphy, W. F. See Rolfe, J.
Murray, D. P. Cost controls using ferric sulfate pickling for direct-on, (1) 4*f*.
Murray, J. R. Apparatus for producing mottled brick, P (11) 372*f*.
Murray, L. A. See Rivera, J.
Murray, L. A., and Goldsmith, N. Nondestructive determination of thickness and perfection of silica films, (2) 81*b*.
Murray, R. B. See Keller, F. J.
Murray, R. W. Method of forming a flip-chip integrated circuit, P (8) 282*i*.
Murray, T. P. Apparatus and method for measuring temperatures, P (5) 188*e*.
Murthy, H. P. S. See Subrahmanyam, A. V.
Murthy, M. K., Long, L., and Ip, J. Studies in germanium oxide systems (IV) phase equilibria in the system K_2O-GeO_2. (1) 38*a*.
Muschelknautz, E. Centrifugal sedimentation balance for measuring particle size of very fine powders, (4) 119*a*.
Musikant, S. See Krakauer, S.
Muskovac, N. G. See Stone, L. R.
Musselin, M. J. See Kover, F.
Muto, H. See Fujii, I.
Mutter, W. E. Semiconductor device [structure], P (9) 313*j*.
Mutter, W. E., and Totta, P. A. Multilevel terminal metallurgy for semiconductor devices, P (11) 377*j*.
Muurinen, M. See Luova, P.
Myers, C. B. See Sisson, C. G.
Myers, H. See Langley, R. C.
Myers, R. E. See Hansen, W. W.
Myers, R. L. Pretreated steel sheets for porcelain enameling, (7) 246*g*.
Myers, T. E. Metal silicate coating utilizing electrostatic field, P (7) 256*i*.
Myuller, A. M. See Tikhonov, V. N.

Nabi, G., and Lu, W. K. Reduction kinetics of hematite to magnetite in hydrogen-water vapor mixtures, (6) 237*f*.
Nachtrieb, N. H. See Momii, R. K.
Nadachowski, F. Periclase-lime-chrome refractory materials, (4) 105*a*.
Nadeau, J. S. Dependence of flow stress on nonstoichiometry in oxygen-rich uranium dioxide at high temperatures, (4) 131*c*.
Nademlynska, H. See Hlavac, J.
Nafziger, R. H. See Lindsley, D. H.; Speidel, D. H.
Nafziger, R. H., and Muan, A. Equilibrium phase compositions and thermodynamic properties of olivines and pyroxenes in the system MgO-"FeO"-SiO_2, (4) 135*d*.
Nag, B. B. See Kumar, S.
Nag, B. D. See Nayar, P. S.
Nagai, Chikahisa. Results of comparative service tests on ladle bricks (of roseki and kyanite) in lining of electric furnace ladle, (7) 251*f*. Results of service test on special corrosion-resisting tar-bonded dolomite brick, (7) 251*a*. Results of service test on tar-bonded dolomite brick used in electric furnace, (10) 342*f*. Service tests on 85-ton ladle at Nadahama LD converter plant of Kobe Steel Works, Ltd., (7) 251*e*.
Nagai, Haruo, and Nilmi, Tatsuya. Preparation and properties of amorphous germanium nitride films, (9) 328*b*.
Nagai, Shoichiro. See Suzuki, Kazutaka; Yamada, Tamotsu.
Nagai, Sumiaki. Hyperfine interaction in MnO crystal, (2) 78*e*. Total energy and $2p$ O^{2-} ion wave function of MnO crystal, (5) 202*h*.
Nagamatsu, H. T. See Cary, K. H.
Nagamiya, Takeo. See Uchida, Enji.
Nagano, Kyoichi. See Kojima, Kojiro.
Nagao, Mahiko. See Morimoto, Tetsuo.
Nagasawa, Masahiro, and Shionoya, Shigeo. Weak-field magnetoresistance in SnO_2 single crystals, (10) 363*i*.
Nagase, Kaneomi. See Hayakawa, Shigeru.
Nagashima, Kozo. See Uetani, Keiji.
Nagata, Kazukiyo, and Tomono, Yuzo. Far-infrared absorption in the ferrimagnetic spiral $MnCr_2O_4$, (2) 77*c*.
Nagata, Takashi. See Kaname, Yuichi.
Nagatsu, Hiroshi; Mimura, Yoshiaki; Izumi, Hideo; and Masuda, Yoshihiro. Nonrectifying laminated ohmic contact for semiconductors consisting of chromium and 80% nickel, P (7) 257*e*.
Nagel, G. A. See Thakar, D. H.
Nagels, P., and Denayer, M. Hall effect in Li-doped MnO. (4) 138*c*.
Nager, H. E., Hoffmann, W., and Nissen, H. U. Mixed series (Ca, Sr) $[Al_2Si_2O_8]$, (10) 357*g*.
Nagulevich, K. V., and Kolesov, Yu. I. Effect of alkaline-earth metal sulfates and nitrates on the gas content of glass, (6) 208*h*.
Nagy, G. See Upor, E.
Nagy, L. G. Nondestructive and destructive neutron activation analysis of the impurities of silicon of semiconductor purity, (5) 187*e*.
Nagyvati, B. See Kezdi, A.
Naidu, S. V. N. See Rao, K. V. K.
Naito, Keiji. Thermal conductivity of nuclear fuel ceramics at high temperatures, (6) 217*b*.
Naito, Susumu. See Hayashi, Kanekichi.
Naito, Toru, and Nishiyama, Michio. Apparatus for cutting, grinding, and polishing ornamental stone, P (9) 314*g*.
Najder, J. See Werno, M.
Nakada, Ichiro. See Yasunaga, Hitosi.
Nakagawa, Hideo. See Shimada, Nobuo.
Nakagawa, Ichiro; Tsuchida, Atsushi; and Shimanouchi, Takehiko. Infrared transmission spectra and lattice vibration analysis of some perovskite fluorides. (4) 140*j*.
Nakagawa, Masuo. Phonon-assisted optical absorption in irradiated MgO, (2) 81*f*.
Nakagawa, Masuo, and Ozawa, Kunio. Zero-phonon lines and phonon coupling in neutron-irradiated MgO crystals, (2) 84*i*.
Nakagawa, Masuo; Uemura, Yukikazu; and Fukuda, Kuniya. "Mirror" absorption and fluorescence in MgO. (1) 32*i*.
Nakagawa, Takehiko. Magnetic and electrical properties of the ordered perovskite $Sr_2(Fe-Mo)O_6$ and related compounds. (2) 79*j*. See Nakayama, Seikoh; Nomura, Shoichiro.
Nakagawa, Toru. See Ikeda, Koichi.
Nakagawa, Yasuaki. See Ogawa, Seiya.
Nakai, Tsuneo; Minehisa, Setsuji; Fuchino, Yoshio; and Tsuchihira, Hisao. Method for fixing a backwave deposited metal onto the beveling root. P (8) 275*f*.
Nakaido, Yasuaki, and Toyoshima, Satoshi. Deposition of new binary oxide thin films by the pyrolytic decomposition of trimethylsiloxy-aluminum-isopropoxide $(Me_3SiO)_nAl(O^i-Pr)_{3-n}$, (5) 190*a*.
Nakajima, Nagahisa. Advancement made in technology of lining LD converter at Muroran Works of Fuji Iron and Steel Co., Ltd., (7) 250*d*.

Nakajima, Nagahisa; Takano, Sumio; and Sakamoto, Yoshinitsu. Studies conducted at Muroran LD converter steel plant to improve quality and shape of ladle brick and mode of lining ladle to reduce quantity of ladle brick required to produce a ton of steel, (11) 374*i*.
Nakajima, S. See Totani, A.
Nakamichi, Hiroshi; Sakurai, Tai; Kawakita, Kikuji; and Kadota, Masatane. Study of low-temperature titania-opacified enamel, (2) 46*a*.
Nakamori, Hiroo. See Tsutsumi, Kenjiro.
Nakamura, Masaru. See Okada, Takasi.
Nakamura, Mitsuyoshi. See Tamura, Michio.
Nakanishi, Norihiko. See Nishimoto, Kozo.
Nakano, Kikuo; Tabata, Hideyo; and Okuda, Hiroshi. Crystal growth of spinels in the system MgO-Al_2O_3-Al_2O_3 by flame fusion, (9) 319*c*.
Nakano, Masahira. See Emoto, Masayuki.
Nakano, Tomoyasu. See Kinoshita, Akira; Nemoto, Tomihiro.
Nakashige, Eitaro. See Nakazawa, Michihiko.
Nakashima, R. See Shibala, S.
Nakayama, Nobuo. See Nishikawa, Tomozo.
Nakayama, Seikoh; Nakagawa, Takehiko; and Nomura, Shoichiro. Neutron diffraction study of $Sr_2(FeMo)O_6$, (2) 80*i*.
Nakayama, Takashi, and Collins, F. C. Kinetics of thermal growth of silicon dioxide films in water vapor-oxygen-argon mixtures, (1) 31*f*.
Nakazawa, Ehchiro, and Shionoya, Shigeo. Energy transfer between trivalent rare-earth ions in inorganic solids, (4) 135*h*.
Nakazawa, Michihiko. Performance of steelmaking arc furnace roof constructed of unshaped refractories and construction method, (7) 251*c*.
Nakazawa, Michihiko, and Nakashige, Eitaro. Physical properties of chrome castable refractories (11) 373*b*.
Nakazawa, Michihiko, and Tsurumi, Takematsu. Design and construction of continuous heating furnace (15 tons/h), (11) 381*g*.
Nakazawa, Yasuro; Uetsuki, Toru; and Uei, Isao. Dissolution of zircon in molten glasses, (11) 372*i*.
Nakazumi, Yoshihide. See Uchida, Enji.
Nakura, Yoshitomi. See Murakami, Keiichi.
Nalco Chemical Co. Method of making silica sols containing large particle size silica, P (7) 262*j*. Method of preparing concentrated silica sols, P (11) 382*d*. Polyphosphate glasses and water treatment uses thereof, P (6) 213*a*. Precision metal casting molds comprising alumina coated silica and a refractory, P (8) 279*i*. Process for preparing alkali metal aluminate tetrahydrate crystals, P (5) 191*f*. Process for separation of red mud from dissolved alumina, P (8) 288*b*.
Naldrett, A. J. Portion of the system Fe-S-O between 900° and 1080°C and its application to sulfide ore magmas, (11) 386*g*.
Nale, R. F. See Taylor, W. C.
Nalesnik, W. J. See Boer, K. W.
Nallet, J. P. See May, P.
Nameishi, Naoyuki. Effect of high-temperature firing on properties of magnesia brick, (11) 373*b*. Refractories for LD converter, (7) 251*e*. Results of refractoriness-under-load test conducted on some magnesia clinker samples, (10) 342*e*. Slagging action of alkali on blast furnace refractories, (11) 374*f*.
Nameishi, Naoyuki; Ishibashi, Tanezo; and Utsu, Shigetoshi. Results of service tests on corundum-containing high silica and high alumina ladle brick, (7) 251*b*.
Nameishi, Naoyuki, and Matsumura, T. Corrosion of high-fired magnesite-chromite brick, fired dolomite brick, and fired magnesia brick by different basicity slags, (11) 372*h*.
Nameishi, Naoyuki; Ohmatsu, Tomio; and Matsumura, T. Results of service test on semistabilized firebrick for LD converter and consideration of ways and means for quality improvement based on the results, (7) 251*f*.
Nameishi, Naoyuki; Yoshino, Hajime; and Horikawa, Tsuyoshi. Effect of fireclay and aluminum in molten steel on dissociation of zircon, (4) 103*i*.
Nandi, D. N., and Salim, A. Note on high alumina cement, (10) 336*d*.
Nandor, R. P. See France, R. W.
Nannichi, Yasuo. Twin semiconductor laser, P (6) 224*c*.
Naoumidis, A., Nickel, H., Rottmann, J., and Stoecker, H. J. Nitrogen determination in ceramic uranium compounds, (4) 120*h*.
Naoumidis, A., and Stoecker, H. J. Thermodynamic data of UN_x (x=1.5–1.75), (5) 201*b*.
Napier, B. A., and Spencer, D. H. T. Access of gases to the porosity of graphite at high temperatures, (9) 317*j*.
Napier, J., Sopher, R. P., Totta, P. A., De Witt, D., and Karan, C. Method of forming solder mounds on substrates, P (11) 377*a*.
Napolitano, A. See Macedo, P. B.
Napolitano, A., and Macedo, P. B. Spectrum of relaxation times in GeO_2 glass, (1) 9*b*.
Napora, N. Metallurgical degasser vessels, P (6) 217*e*.
Napple, C. E. Method of connecting a fiber glass rodlike member to a metallic terminal, P (11) 377*h*.
Nara, Jiyuichi. Device having rotating members for separating powder into fine and coarse particles, P (10) 346*h*.
Naradi, Narodni Podnik. Diamond tool, P (7) 243*i*.
Narain, J., and Ayyar, T. S. R. Review of shear strength parameters for saturated clays, (4) 153*d*.
Narain, J., and Gar, I. P. Preconditioning cohesive soils for stabilization with cement, (4) 92*c*.
Narain, J., Singh, B., and Chakraborty, S. K. Sedimentary consolidation, (4) 154*c*.
Narasaraju, T. S. B. See Chickerur, N. S.; Singh, R. P.
Narayan, R. See Inman, D.
Naray-Szabo, I. See Grofcsik, J.
Nardelli, G. F. See Benedek, G.
Nariai, Noriyuki. See Okutsu, Shinkichi.
Narita, Koziro. See Futaki, Hisao.
Narita, Mitsuaki. See Murakami, Keiichi.
Narken, B., and Whitaker, H. L. Method for [vapor] depositing glass particles on the entire exposed surface of an object, P (7) 257*c*.
Nassau, K. Model for the Fe^{2+}-Fe^{4+} equilibrium in flux-grown yttrium iron garnet, (9) 325*i*. See Loiacono, G. M.; Wood, D. L.
Nassau, K., and Abrahams, S. C. Growth and properties of single crystal cupric molybdate, (7) 266*h*.
Nassau, K., and Shiever, J. W. Cupric oxide-molybdenum oxide phase diagram in air and in oxygen, (4) 130*g*. KNb_3O_8—a micalike crystal, (4) 142*g*.
Nassibian, A. G. Semiconductor device with inversion layer, underneath an oxide coating, compensated by gold dopant, P (9) 313*j*.
Natansohn, S. Uranium activated fluorescent materials, P (10) 346*b*. See Baird, D. H.
Natansohn, S., and Baird, D. H. Effect of synthesis parameters on the magnetic properties of manganese zinc ferrites, (6) 220*e*.
Natera, M. G., Pineda, V. M., and Navarro, Q. O. Neutron diffraction studies on MnAl, Mn_2Ni_3C, and $MnZn_3$, (1) 12*f*.
Natesh, R., and Ansell, G. S. Oxide growth in an Al-Al_2O_3 SAP-type alloy by hot stage transmission electron microscopy, (1) 34*e*.
Nath, D. K., and Hummel, F. A. Crystal field studies of Co^{2+} in α-$Zn_3(VO_4)_2$, (1) 26*d*. Crystal field studies of Ni^{2+} in α-$Zn_3(VO_4)_2$, (7) 264*e*. Synthesis of vanadate and arsenate spodiosites and interpretation of optical spectra of manganese-doped Sr_5VO_4Cl, (4) 158*f*.
Nath, G., and Haussuhl, S. Large nonlinear optical coefficient and phase matched second harmonic generation in $LiIO_3$, (9) 310*i*.
Nathan, M. I. See McGroddy, J. C.
National Airoil Burner Co., Inc. Burners, P (5) 189*g*.
National Beryllia Corp. Dense refractory zirconium boride bodies, P (6) 217*j*.
National Cash Register Co. *Pn* junction formation by thermal oxidation, P (4) 115*f*.
National Forge Co. Automatically operating air vent for isostatic molding press [wet bag], P (9) 314*h*.
National Gypsum Co. Impregnation of asbestos-cement products with thermosetting formaldehyde resin, P (4) 92*i*. Kiln feed control, P (5) 170*f*. Programing switch and kiln unloader control, P (7) 261*g*.
National Lead Co. Boratozirconium chloride, P (5) 190*g*. Crystalline zirconium phosphates, P (4) 124*a*. Foundry core and molding sand composition, P (1) 14*a*. Method and means for sampling pulverulent material, P (8) 286*a*. Method for producing titanium dioxide concentrate from massive ilmenite ores, P (10) 349*a*. Method for production of titanium dioxide granules, P (2) 74*g*. Molding sand, P (8) 279*i*. Preparation of a rutile titanium dioxide-anhydrite composite pigment, P (10) 349*e*. Process for producing a titanium sulfate solution and a TiO_2 concentrate from a titaniferous ore, P (4) 125*b*. Titanium dioxide concentrate and method for producing the same, P (8) 288*d*. Titanium dioxide granules and their use in a molten glass batch, P (6) 213*g*.
National Research Corp. Apparatus for evaporation of low temperature semiconductor material by electron beam impingement on the material and comprising means for draining electric charge from the material, P (4) 112*b*. Codeposition of boron containing coatings, P (11) 369*c*. Method of making a niobium stannide coated niobium wire, P (2) 65*h*. Process of epitaxial growth of silicon carbide, P (11) 378*h*. Silicon carbide device, P (2) 66*g*. Tantalum nitride powder and method for its preparation, P (5) 179*f*.
National Research Development Corp. Apparatus for and methods of testing lenses, P (7) 248*i*. Continuous X-ray fluorescent analysis of the solid component of a slurry, P (8) 286*c*. Crystal melt-growth process wherein the melt surface is covered with an inert liquid, P (1) 18*d*. Dry separation of mixtures of solid materials, P (8) 287*i*. Electrical insulating bodies, P (2) 64*j*. Gravity separation of particulate material, P (7) 262*h*. Method of growing a crystal or crystalline layer by means of a direct current arc discharge, P (8) 282*j*. Process of growing a single crystal utilizing differences in chemical potential, P (11) 378*h*. Production of carbon fibers and compositions containing the fibers, P (4) 107*e*.
National Semiconductor Corp. Contacts for insulation isolated semiconductor integrated circuitry, P (7) 256*c*.
National Video Corp. Magnetic shielding means [coating] for cathode ray tube, P (8) 282*d*. Method of manufacturing cathode ray tube, P (7) 249*h*.
Natsenko, A. I. See Orlova, I. G.
Nauchno-Issledovatelsky Institute Zhelezobetonnykh Izdely, Strollelnykh i Nerudnyk Materialov. Method of manufacturing a three-component water-resisting binding agent, P (4) 92*j*.
Naughton, T. J., and Towles, R. J. Temperature distribution in an end-fired melter, (1) 9*e*.
Naumann, A. W. See Dresher, W. H.; Safford, G. J.
Naumann, A. W., and Dresher, W. H. Colloidal suspensions of chrysotile asbestos: Specific anion effects, (4) 128*i*; Surface charge enhancement, (5) 193*a*.
Naumann, E. C., and Corbin, P. L. Automatic fatigue test temperature programmer, P (2) 71*i*.
Naumescu, V. See Deica, N.
Nauroth, P. Process for producing sodium aluminum silicate pigments, P (5) 191*a*. See Reinhardt, H.
Naus, D. J., and Lott, J. L. Fracture toughness of portland cement concretes, (10) 336*c*.
Navarro, Q. O. See Natera, M. G.
Navias, L. Glass-silicon assemblies, P (2) 53*a*.
Navon, D. H., and Bakalar, D. Matrix-type permanent memory device, P (11) 377*d*.
Navon, D. H., and Davis, E. S. Semiconductor device doped with gold just to the point of no excess and method of making, P (8) 283*e*.
Navrotsky, A., and Kleppa, O. J. Calorimetric study of molten Na_2MoO_4-MoO_3 mixtures at 970°K, (11) 383*e*.
Nayar, P. S., Verma, J. K. D., and Nag, B. D. Semiconducting properties of thallium selenide, (1) 17*c*.
Nazarchuk, N. V. See Dobrovol'skii, A. G.
Nazarchuk, T. N. See Pechentkovskaya, L. E.
Nazaruk, S., Rosa, C., and Headrick, A. F. Apparatus for forming spherical pellets, P (6) 225*e*.
Neal, W. J. Carbonate facies and paleogeography of the Blackjack Creek formation (Pennsylvanian), Missouri, (8) 286*h*.
Neale, D. F. See Sutherland, H. B.
Neathery, T. L. Talc and anthrophyllite deposits in Tallapoosa and Chambers counties, Alabama, (2) 72*h*.
Neave, J. H. See Brown, A. S.
Nedelec, M. Glass sheet forming apparatus with coated silica core roller and roller, P (2) 52*j*. Method of and apparatus for the shaping of plastic sheets, P (11) 371*e*.
Nedelec, M., and Chaumont, H. Method and apparatus for supporting sheets on a gaseous bed, P (9) 307*i*.
Nedev, S. K. See Fedorov, P. I.
Needham, O. S., Jr. See Grekila, R. B.
Neely, H. E. See Cameron, N. M.
Neely, J. E., and Mackenzie, J. D. Hardness and low-temperature deformation of silica glass, (4) 96*b*.
Negas, Taki. System PbO-chromium oxide in air, (1) 39*d*.
Negas, Taki, and Roth, R. S. High temperature dehydroxylation of apatitic phosphates, (6) 233*j*.
Negas, Taki, and Sorrell, C. A. Silica transformations in the system PbO-SiO_2, (1) 36*b*.
Neichi, Yutaka. See Hirota, Eiichi.
Neilands, J. B. See Joergensen, C. K.
Neild, D. J. See Dickens, P. G.
Neill, R. H. See Thomas, P. M.
Neilsen, G. F. Spinodal decomposition in soda-silica glass, (8) 276*g*.
Neiman, M. See Afonskii, N. S.
Neipert, M. P. See Moolenaar, R. J.
Neises, H. See Hloch, A.
Nekhamkin, L. G. See Pustil'nik, A. I.
Nekhoroshev, A. V. See Budnikov, P. P.
Nekrasov, M. M. Investigation of the nonlinearity of ferroelectrics at ultrahigh frequencies, (2) 63*d*.
Nellessen, A. H., and Schoonover, R. J. Retroreflective structure and method of making same, P (5) 176*e*.
Nelson, C. M. See Sibley, W. A.
Nelson, F. W. Engineering properties of inorganic coatings, (8) 274*i*.
Nelson, G. D. Process for producing multivalent metal pyrophosphates, P (1) 24*c*.
Nelson, H. Light-emitting semiconductor having relatively heavy outer layers for heat-sinking, P (6) 221*i*.
Nelson, J. A. See Sturgis, D. H.
Nelson, P. A., Grosvenor, D. E., Vogler, S., Quattropani, N. P., and Krause, P. W. Synthesis and fabrication of (U,Pu)C nuclear fuel pellets from U-Pu alloy, (10) 342*j*.
Nelson, R., and McCormick, J. E. Production of a cooling module for microelectronic circuits by cathodic sputtering, P (7) 257*i*.
Nelson, R. F. See Rindner, W.
Nelson, R. L. See Tench, A. J.
Nelson, R. L., and Tench, A. J. Chemisorption on some alkaline earth oxides (II) intrinsic bulk defects and adsorption of oxygen on MgO, CaO, and SrO, (8) 289*g*.
Nelson, R. L., Tench, A. J., and Harmsworth, B. J. Chemisorption on some alkaline earth

oxides (I) surface centers and fast irreversible oxygen adsorption on irradiated MgO, CaO, and SrO, (4) 128*d*.

Nelson, R. L., Tench, A. J., and Wilkinson, R. W. Chemisorption of oxygen on some alkaline earth oxides, (1) 25*i*.

Nelson, R. S. Influence of irradiation in the nucleation of gas bubbles in reactor fuels, (5) 195*j*. See Lidiard, A. B.

Nelson, W. E. See Bartlett, R. W.

Nemec, D. Micas of the metamorphic skarns in Western Moravia, (9) 316*g*.

Nemecz, E. See Dobos, G.

Nemeth, A. See Heltai, F.

Nemilov, S. V. New type of temperature function of the viscosity of inorganic glasses, (2) 50*g*.

Nemoto, Tomihiro, and Nakano, Tomoyasu. Effect of silicon on cuprous oxide, (9) 320*j*.

Nenarokov, A. V. See Zil'bershtein, Kh. I.

Nenorta, A. See Vektaris, B.

Nesanelis, M. Z., Zolotovitskaya, E. S., and Shevchenko, V. K. Spectroscopic determination of trace impurities in yttria-alumina garnets, (2) 70*j*.

Nesbitt, E. A. See Geller, S.

Nesterova, A. I. See Savin, L. S.

Nestler, W. Indirectly heated dispenser cathode for electric discharge tubes, P (10) 345*b*.

Nethercot, A. H., Jr. See von Gutfeld, R. J.

Netting, D. I. See Weldes, H. H.

Nettleton, R. E. Effective mass of 180° domain wall in single crystal $BaTiO_3$, (1) 28*e*.

Neubereer, J. See Hafner, A.

Neubert, T. J. See Konrad, K.

Neuenfeld, K. See Hennicke, H. W.

Neuenschwander, E., Schuett, K., and Scheller, W. Process for the preparation of finely divided nonpyrophoric nitrides of zirconium, hafnium, niobium, and tantalum, P (6) 218*a*.

Neufeld, P. See Leach, J. S. L.

Neugebauer, C. A. Method [vapor deposition] of forming a superconducting metallic film, P (7) 257*d*.

Neugebauer, C. A., Miller, D. C., and Hall, J. W., III. Polycrystalline CdS thin film field effect transistors—fabrication, stability, and temperature dependence, (2) 63*a*.

Neugebauer, W. Process for the production of extremely finely divided inorganic mixtures, particularly those containing silicon dioxide, P (6) 230*b*. See Biegler, H.

Neuhaus, A., and Gebhardt, M. Phase formation and structural behavior in sand-lime brick hardened with water vapor, (11) 373*i*.

Neumann, H., and Nilsen, B. Tombarthite, a new mineral from Hoegetveit, Evje, South Norway, (8) 300*i*.

Neumann, H., and Wijn, H. P. J. Polycrystalline hexagonal Fe_2W with varying ferrous content—correction, (4) 150*c*.

Neumann, J., Ditz, J., and Suk, V. New metallochromic indicators of the "calcon" type—determination of calcium, (6) 235*g*.

Neumark, G. F. See Leventhal, E. A.

Neuroth, N. Special application of glass in electronics, (10) 338*j*.

Nevins, M. J. Molding sand, P (8) 279*i*.

Nevzorov, A. N. See Spivak, G. V.

New Nippon Electric Co., Ltd. Method of making glass capacitors, P (11) 377*c*.

Newbury, R. S., Barton, G. W., Jr., and Searcy, A. W. Vapor species of the barium-oxygen system, (2) 84*e*.

Newcomer, F. Specialty refractories by automat, (4) 105*a*.

Newey, C. W. A. See Harrison, R. P.; Radford, K. C.

Newey, C. W. A., Harrison, R. P., and Pratt, P. L. Precipitation hardening and dislocation locking in doped NaCl, (2) 81*j*.

Newkirk, H. W. See Cline, C. F.

Newkirk, J. B. See Austerman, S. B.; Bonse, U. K.

Newkirk, J. B., and Mallett, G. R. (editors). Advances in X-Ray Analysis (Vol. 10) Proceedings of the 15th Annual Conference on Applications of X-Ray Analysis, August 1966, Denver, Colorado, B (1) 40*h*.

Newkirk, J. B., Mallett, G. R., and Pfeiffer, H. G. (editors). Advances in X-Ray Analysis (Vol. 11)—Proceedings of the 16th Annual Conference on Applications of X-Ray Analysis, August 1967, Denver, Colorado, B (9) 333*e*.

Newkirk, T. F. See Poirier, A. R.

Newman, A. C. D. Simple apparatus for separating fluorine from aluminosilicates by pyrohydrolysis, (6) 227*a*.

Newman, D. G. See Gasser, R. P. H.

Newman, H. How General Shale uses quality control from pit to shipping, (8) 284*f*.

Newman, P. C. Semiconductor device comprising III–V epitaxial deposit on substitutional III–V substrate, P (7) 258*b*. See Beale, J. R. A.

Newman, R. Optical computer comprising semiconductor *pn* junction components, P (6) 223*c*.

Newnham, R. E. See Dehn, J. T.; Dorrian, J. F.

Newns, G. R. See Faktor, M. M.

Newns, G. R., and Hanks, R. Thermal behavior of germanium dioxide, (1) 39*i*.

Newport, J. B. See Taylor, J. J.

Newton, G. W. A. See Baptista, J. L.

Newton, R. C. High pressure hydrothermal measurements on heavily ground kyanite and sillimanite, (7) 266*c*. See Ganguly, J.; Goldsmith, J. R.

Newton, R. C., and Smith, Joseph V. Investigations concerning the breakdown of albite at depth in the earth, (4) 141*b*.

Newton, R. G. Observations on the weathering crusts of ancient glass, (8) 273*j*.

Ney, R. J. Image orthicon glass target with aluminum-tantalum oxide coating, P (7) 256*b*.

NGK Insulators, Ltd. Method for producing porcelain articles, P (11) 376*a*. Method for producing porcelain suitable for insulator, P (6) 220*a*. Method of production of active beryllium oxide powders, P (6) 229*i*.

Nguyen Van Mau, A., Ance, C., and Bougnot, G. Growth of single crystals of gallium antimonide by the floating zone technique, (5) 181*f*.

Ni, L. P., Bunchuk, L. B., Khalyapina, O. B., and Ponomarev, V. D. Reaction in the system Na_2O-Al_2O_3-CaO-SiO_2-H_2O at 280°, (1) 35*i*.

Nice, N. C. High voltage connection for cathode ray tube, P (6) 221*f*.

Nichiporenko, E. P., Osipov, A. D., Zmil, V. I., Korzhavyi, A. P., and Poltavtsev, N. S. Effect of conditions of the preparation of silicide layers on molybdenum on some of their properties, B (5) 204*f*.

Nichiporenko, S. P. See Kruglitskii, N. N.; Orobchenko, V. I.; Ovcharenko, F. D.

Nicholas, J. V. Origin of luminescence in natural zircon, (4) 147*j*.

Nicholas, M. Strength of metal/alumina interfaces, (9) 330*j*.

Nicholas, M. G. See Hodkin, E. N.

Nicholls, D. Reduction of boric oxide to boron monoxide, (1) 36*a*.

Nichols, D. R. See Doo, V. Y.

Nichols, E. F., Ivey, K. H., and Shell, H. R. Method and apparatus for growing large monocrystals of nonmetallics, P (8) 287*j*.

Nichols, F. A. Pore migration in ceramic fuel elements, (8) 296*a*. Theory of sintering of wires by surface diffusion, (1) 39*h*.

Nichols Engineering & Research Corp. High temperature multiple hearth furnace structures, P (4) 123*b*.

Nicholson, D. See Dollimore, D.

Nicholson, G. C. See Olsen, K. H.

Nicholson, P. S. Technique for estimating thickness of a thin section, (6) 227*e*.

Nickel, D. Standard costs—what are they? (6) 240*d*.

Nickel, E. H. Sulfide research contributions from the Mineral Sciences Division, Mines Branch, Department of Energy, Mines, and Resources, (9) 316*j*. See Faye, G. H.

Nickel, H. See Naoumidis, A.

Nickel, H., Inanc, O., and Luecke, K. Phases of the uranium-zirconium-carbon systems, (9) 327*b*.

Nickel, H., and Saeger, H. Stability of U_3C_2, (9) 330*d*.

Nickl, J. See Sprenger, H.

Nicklas, W. H. Envelope wall with two continuous ledges for positioning and supporting aperture mask, P (2) 64*d*.

Nicol, M. See Asell, J. F.

Nicolas, J. See Vassiliev, A.

Nicoll, F. H. Experimental pulsed CdS laser cathode-ray tube, (8) 281*g*.

Nicoll, S. B., Jr. Apparatus for the manufacture of ceramic products, P (10) 346*f*.

Niebergall, R. See Goetz, W.

Niel, E. M. M. G. Chemical and mineralogical processes in the portland cement clinker kiln, (6) 206*h*.

Nielsen, J. Cement testing according to the RILEM-Cembureau method, (1) 2*e*.

Nielsen, J. W. See Monchamp, R. R.

Nielsen, K. F. Growth of ZnO single crystals by the vapor phase reaction method, (10) 354*c*.

Nielsen, M. L., Hathaway, C. E., Jr., and Butler, J. M. Heat-resistant coatings, P (10) 337*e*.

Nieminen, I. Radioactive capture of positrons by electrons and the use of Born approximation, (4) 111*e*.

Niemyski, T. See Krukowska-Fulde, B.

Niemyski, T., and Klerzek-Pecold, E. Crystallization of lanthanum hexaboride, (9) 319*i*.

Niemyski, T., and Piekarczyk, W. Growth of rutile (TiO_2) single crystals by chemical transport with $TeCl_4$, (5) 194*e*.

Niemyski, T., Pracka, I., Jun, J., and Paderno, J. Zone melting of alkaline and rare-earth metal hexaboride rods, (8) 301*a*.

Niesel, K. See Hums, D.

Nieveistein, M. J. W. E. See Schuetz, E.

Niewiadomski, J. See Brzozowski, W.

Nigam, R. C. Determination of calcium and magnesium in magnesite by a complexometric method employing coprecipitation of calcium and strontium sulfate, (6) 225*f*. Rapid volumetric determination of magnesium in limestone, dolomite, and magnesite, (6) 227*f*.

Niguchi, Noboru. See Yamamoto, Noboru.

Nihon Genshiryoku Kenkyusho. Electric furnace having a heating element of carbon or graphite for producing temperatures under high pressures, P (1) 23*a*.

Nii, Riro; Kawasaki, Yasuhiro; Honda, Takashi; and Yamada, Tomoaki. GaAs bulk oscillators, (7) 254*j*.

Niimi, Tatsuya. See Nagai, Haruo.

Niizeki, Nobukazu. See Itakura, Masayuki; Iwasaki, Hiroshi; Yamada, Tomoaki.

Niizeki, Nobukazu; Yamada, Tomoaki; and Toyoda, Hiroo. Growth ridges, etched hillocks, and crystal structure of lithium niobate, (8) 292*e*.

Nijhof, B. J. See Gie, O. T.

Nijhar, R. S., and Williams, D. J. Surface tensions of molten polyphosphate mixtures, (9) 330*j*.

Nijland, L. M. See Janssens, H. H.

Nikitin, A. A. See Mazurov, D. J.

Nikitina, K. T. See Sobolev, G. P.

Nikolaev, R. K., Orshanskaya, Z. N., Gavrilov, O. R., and Nisel'son, L. A. System $TaCl_5$-$WOCl_4$, (9) 331*f*.

Nikol'skaya, I. V. See Vereshchagin, L. F.

Nikonova, I. N. See Berul, S. I.

Nikulina, L. N. See Levin, D. I.

Nilosic, V. S. See Boskovic, S. B.

Nilsen, A. E. See Michal, E. J.

Nilsen, W. G., and Skinner, J. G. Raman spectrum of strontium titanate, (4) 152*d*.

Nilsson, B. See Neumann, H.

Nilsson, T. M. Anisotropy in mechanical properties of extruded commercial S.A.P. materials, (10) 349*j*. Influence of grain size on the high-temperature ductility of an aluminum-alumina alloy, (4) 140*b*.

Nimvitskaya, T. A., and Fishman, S. L. Deposition of high-melting coatings by means of a plasma, B (5) 204*f*.

Nininger, R. C., Jr. See Schroeer, D.

Nippon Electric Co., Ltd. Avalanche transistor having reduced width in depletion region adjacent gate surface, P (8) 282*c*. Device for glass glazing electronic housing members, P (7) 248*e*. Diffusion type semiconductor device having plural protective coatings, P (5) 182*d*. Flame fusion crystal growing employing vertically displaceable pedestal responsible to temperature, P (8) 282*g*. Low melting glass, P (5) 175*e*. Low melting point devitrified glass and method, P (5) 175*f*. Method for growing high-melting-point single crystals and an apparatus therefor, P (4) 114*j*. Optical semiconductor device, P (10) 345*d*. Oxide coating for semiconductor surfaces, P (11) 378*b*. Piezoelectric ceramic composition, P (11) 378*d*. Sealed enclosure for electronic device, P (2) 66*j*. Semiconductor device, P (2) 66*d*. Semiconductor device [Ge,Si] utilizing an $AuAl_2$ layer as a diffusion barrier that prevents "purple plague," P (1) 19*h*. Semiconductor device having regions with preselected different minority carrier lifetimes, P (5) 185*g*. Semiconductor device with Schottky barrier formed on (100) plane of GaAs, P (10) 346*b*. Stabilized low pressure triode sputtering apparatus, P (7) 258*a*. Three-electrode cold-cathode gas laser tube, P (1) 19*g*. Transistor body enclosing a submerged integrated resistor, P (2) 67*a*. Twin semiconductor laser, P (6) 224*c*. Vitreous material for use in semiconductor devices, P (8) 284*a*.

Nippon Sheet Glass Co., Ltd. Apparatus for the manufacture of sheet glass utilizing gas-permeable vertical dampers, P (8) 277*f*. Apparatus for stretching molten sheet glass laterally, P (9) 307*a*. Glass having a colored zone whose boundary has been blurred and method of producing the same, P (10) 339*d*.

Nippon Telegraph & Telephone Public Corp. Process for producing a ferromagnetic thin film, P (5) 185*d*.

Nippon Telegraph & Telephone Public Corp. and Shiba Electric Co., Ltd. Nonrectifying laminated ohmic contact for semiconductors consisting of chromium and 80% nickel, P (7) 257*e*.

Nippon Toki Kabushiki Kaisha. Automatic preforming device for continuous pottery forming machine, P (5) 180*e*.

Nisel'son, L. A. See Gavrilov, O. R.; Nikolaev, R. K.; Pustil'nik, A. I.

Nisel'son, L. A., and Mogucheva, V. V. System $SbCl_3$-$AsCl_3$, (4) 159*e*.

Nishida, Masamitsu. See Ouchi, Hiromu.

Nishida, Shingo. See Hattori, Tadamichi.

Nishida, Toshihiko. See Shimizu, Satoshi.

Nishigaki, Shigeru. See Sudo, Toshio.

Nishikawa, Tomozo; Nakayama, Nobuo; and Hirota, Elichi. Electrical resistivity and electron-microscopic observation of sintered chromium dioxide, (1) 28*d*.

Nishimoto, Kazuyuki, and Iida, Yoshio. Composite glass electrode, P (1) 10*a*. Fluoride-containing glass electrode compositions, P (9) 307*d*. Glass electrode compositions, P (6) 212*b*.

Nishimoto, Kozo; Goto, Yasumasa; Nakanishi, Norihiko; and Kachi, Sukeji. Dielectric properties and crystal structure of barium titanate fine particles, (4) 131*b*. Pressure-squeezing effect on the phase transition in barium titanate, (4) 150*j*.

Nishimura, Takeo. Method of producing thin film integrated circuits, P (5) 184*f*. See Douta, Kikuo.

Nishimura, Teruo. See Kawamura, Sukezo.

Nishino, Tadashi; Moteki, Kesakichi; and Sakurai, Tadashi. Reaction between $BaCO_3$ and Cr_2O_3, (8) 297*d*.

Nishino, Tadashi; Sakurai, Tadashi; Nishiyama, Shusaku; and Uzuki, Takao. New metastable phase of $BaCO_3$, (1) 33*b*.

Nishiwaki, Minoru. See Inoue, Toshio.
Nishiyama, Michio. See Naito, Toru.
Nishiyama, Shusaku. See Nishino, Tadashi.
Nishizaki, Kenichi. See Minowa, Susumu.
Nissen, H. U. See Nager, H. E.
Nitsche, R. See Gnehm, C.
Nitsche, R., and Wild, P. Vapor growth of new single-crystalline phases in the system Cu-Nb-S, (9) 332*i*.
Nitschke, N. C. See McMaster, H. A.
Nitta, Tsunecharu. Properties of sodium-lithium niobate solid solution ceramics with small lithium concentrations, (1) 17*j*. See Hayakawa, Shigeru.
Nitzsche, S., Pirson, E. H., and Roth, M. Water repellent masonry articles, P (10) 336*d*.
Niwa, Shohei. High-fired magnesia brick used in walls of electric furnace, (2) 56*b*.
Niwa, Shohei, and Koide, Kazushige. Erosion tests on ladle brick of various kinds—observation by means of RI ^{45}Ca, (11) 373*d*.
Niwa, Shohei, and Saga, Senzo. Results of corrosion test on high silica ladle brick by induction furnace method, (7) 251*h*.
Niwa, Shohei, and Yamashita, Hajime. Impurities of sillimanite ore from the Union of South Africa, (11) 373*g*.
Nixdorf, J. Inorganic fibers, (2) 79*d*. See Janes, S.
Nixdorf, J., and Rochow, H. Microwires, (9) 306*h*.
Nixon, D. E. See Parry, G. S.
Nizheviasov, V. V. See Yakobson, K. K.
Nobbs, J. M. Effect of water vapor on the photoconductivity of zinc oxide, (9) 320*b*.
Nobel, A. P. P. See Geus, J. W.
Noble, D. C., Haffty, J., and Hedge, C. E. Strontium and magnesium contents of some natural peralkaline silicic glasses and their petrogenetic significance, (10) 348*i*.
Noble, J. V. Athenian vases, (6) 205*i*.
Nobuhara, Shiro. Ramming of electric furnace hearth, (11) 373*g*.
Nobuoka, Soichiro, and Ado, Kazuaki. Formation of single crystals of α-Fe_2O_3 by hydrothermal treatment of α-FeOOH, (7) 266*b*.
Nobuoka, Soichiro; Ado, Kazuaki; and Takahashi, Akira. Lattice constant and thermal decomposition of α-FeOOH prepared by different methods, (9) 324*d*.
Noda, Tokiti; Kamiya, Kanichi; and Inagaki, Michio. Effect of pressure on graphitization of carbon (I) heat treatment of soft carbon under 1, 3, and 5 kbars, (4) 133*g*.
Noda, Tokiti, and Ushio, Masumi. High pressure synthesis and stability field of cobalt garnet ($CO_3Al_2Si_3O_{12}$), (6) 233*h*.
Noeltner, G. See List, K. H.
Noguchi, Tetsuo. See Mizuno, Masao.
Noguchi, Tetsuo, and Mizuno, Masao. Freezing points and melting behaviors of lanthanide oxides measured with a solar furnace, (4) 136*g*.
Noguchi, Tetsuo; Mizuno, Masao; and Conn, W. M. Fundamental research in refractory system with a solar furnace—ZrO_2-CaO system, (5) 194*i*.
Noguchi, Tetsuo; Mizuno, Masao; and Kozuka, Takeshi. Freezing point measurement of metal oxides with a solar furnace, (7) 266*d*.
Noguchi, Tetsuo; Mizuno, Masao; Kozuka, Takeshi; and Yamamoto, Tetsuo. Heating curves and melting point measurements with a solar furnace, (5) 187*h*.
Noguchi, Tetsuo; Okubo, Tsutomu; and Yonemochi, Osamu. Reactions in the system ZrO_2-SrO, (6) 237*f*.
Noguchi, Toyomasa. See Okazaki, Kiyoshi.
Nojima, Susumu. See Kasugai, Takahiko.
Nolte, A. C., Jr. Method for producing yttrium aluminum oxide garnet crystals, P (6) 222*g*.
Nolte-Reflor, B. Egyptian glass articles of the New Kingdom, (6) 206*a*.
Nomura, Shoichiro. See Fujiki, Hideo; Nakayama, Seikoh.
Nomura, Shoichiro; Nakagawa, Takehiko; Fukunaga, Osamu; and Saito, Shinroku. Phase transitions in $Pb_2(NiW)O_6$ synthesized under high pressures, (2) 81*d*.
Nomura, Takateru. See Ohba, Hiroshi.
Norcott, A. See White, A. E. S.
Nordberg, M. E. See Elmer, T. H.
Nordberg Mfg. Co. Autogenous grinding mill, P (2) 73*j*. Bearing support for a crusher and the like, P (8) 287*e*. Bowl securing and bowl removing means, P (7) 262*e*.
Norden, H. See Peisson, A.
Nordine, P. C. See Stout, N. D.
Nored, D. L. See Gregory, J. W.
Norgett, M. J., and Lidiard, A. B. Migration of inert gases in ionic crystals, (9) 324*g*.
Norman, H. W. See Benedict, T. S.; Marshall, W. B.
Norman, R. S. See Gordon, W. D.
Normington, P. J. C. See Mulford, C. O., Jr.
Norreys, J. J. See Hazelden, D. W. J.
Norris, A. W. See Baily, D. F.
North American Philips Co., Inc. Apparatus for feeding articles to an endless or closed path conveyor, P (1) 10*f*. Apparatus for manufacturing fluorescent lamps, P (1) 10*h*. Cathode-ray tube having a nondiscoloring X-ray absorptive display window, P (5) 182*h*. Coatings on germanium bodies, P (7) 256*a*. Color television display tube with ferromagnetic screening member, P (5) 182*a*. Core wire for electric arc welding, P (2) 46*d*. Europium activated yttrium and gadolinium vanadate-phosphate and vanadate-arsenate phosphors, P (4) 112*j*. Filament wire for use in the cathode of a thermionic valve, P (4) 113*d*. Fluorine-resistant electrical terminal, P (4) 113*e*. Fluoro-substituted europium activated gadolinium, yttrium, and lanthanum oxides, P (4) 113*e*. Fusion bonding to nonmetals, P (4) 113*g*. High-voltage semiconductor diode with ceramic envelope, P (4) 113*c*. Incandescent lamp with filament consisting of a hexaboride of a rare earth metal, P (1) 18*i*. Infrared spectra of powders by means of internal reflection spectroscopy, P (6) 227*h*. Insulated-gate field-effect transistor with plural overlapped gates, P (7) 256*e*. Insulated-gate field-effect transistor with widening current path between source and drain, P (7) 256*e*. Internal reflection element for microsample analysis, P (4) 121*j*. Metal-oxide-semiconductor capacitor using genetic semiconductor compound as dielectric, P (1) 18*a*. Method of bonding two different materials by electromagnetic radiation, P (5) 183*a*. Method of controlling the atmosphere in preparing ferrites, P (4) 114*i*. Method of dividing a body comprising a number of electric circuit elements into parts, P (4) 114*b*. Method of forming ceramic-to-metal seal, P (7) 257*d*. Method of joining a semiconductor to a base, P (6) 222*c*. Method of manufacturing ferrites, P (6) 222*b*. Method of manufacturing lithium ferrite magnetic cores, P (4) 115*d*. Method of manufacturing solid bodies containing Nb_3Sn, P (5) 184*a*. Method for refining glass baths, P (8) 278*a*. Methods [gas discharge] and arrangements for melting material which melts only with difficulty, P (7) 261*e*. Nonevaporative getter, P (2) 53*j*. Opto-*pn* junction semiconductor having greater recombination in *p*-type region, P (4) 115*d*. Photosensitive semiconductor with two radiation sources for producing two transition steps, P (4) 115*f*. Process of making a [epitaxial] transistor with an inverted structure, P (7) 257*h*. Regenerative cycle electric incandescent lamp, P (4) 116*h*. Scintillation detector using a single crystal of gallium arsenide, P (4) 116*j*. Semiconductor device, P (8) 283*d*. Semiconductor device comprising III–V epitaxial deposit on substitutional III–V substrate, P (7) 258*b*. Sodium vapor discharge lamp with infrared reflecting coating, P (1) 19*j*. Tapered insulated gate field-effect transistor, P (7) 258*b*. Terbium or terbium and gadolinium activated mixed alkaline earth alkali metal borate luminescent substance, P (5) 185*f*. Three region semiconductor having rectifying junctions of different compositions so that wavelength of emitted radiation depends on direction of current flow, P (2) 67*a*. X-ray converter having terbium activated lanthanum compound phosphor, P (1) 19*h*.
North American Rockwell Corp. Combined waste treatment and cement-making method and means, P (8) 274*a*. Composite heteroepitaxial structure, P (4) 112*i*. Growing garnet on nongarnet single crystal, P (6) 221*d*. Impregnation of graphite with refractory carbides, P (6) 217*b*. Magnetic materials, P (1) 18*j*. Methods of making a semiconductor structure including opposite conductivity segments, P (1) 18*e*. Multilayer semiconductor heteroepitaxial structure, P (6) 222*j*. Photosensitive semiconductor device for obtaining light source position data, P (8) 283*h*. Piezoelectric transducer, P (7) 257*f*. Process for making graphitic-type fibers, P (8) 279*j*. Radome structural [glass fabric] composite, P (10) 340*a*. Semiconducting device, P (8) 283*b*. Single crystal silicon on spinel insulators, P (4) 117*a*. Spinel ferrite epitaxial composite, P (5) 185*c*.
North Atlantic Research Products, Ltd. Ovality measurement apparatus comprising two photoelectric gaging systems having an angle between their optical axes of the order of 70°, P (7) 249*a*.
Northern Electric Co., Ltd. Fabrication of semiconductor devices, P (9) 312*h*. Field-effect electroacoustic transducer, P (7) 256*h*. Integrated parametric amplifier consisting of a material with both semiconductive and piezoelectric properties, P (4) 113*f*. Method of coating refractory ware with magnesia, P (9) 309*g*. Method of making ferrimagnetic films by cathodic sputtering, P (7) 257*e*. Method of making large scale integrated circuit, P (5) 183*g*. Semiconductor devices, P (2) 66*e*.
Northover, W. R. See Krause, J. T.
Northrop, H. V. Light control panel, P (7) 249*a*.
Northwestern Steel & Wire Co. Apparatus for melting metals by resistance heating, P (7) 252*d*.
Nortmann, H. See Eckerlin, P.
Norton, B. Method of producing immersed bolometers, P (5) 175*f*.
Norton, F. J. See Jorgensen, P. J.
Norton Co. Abrasive cutting device, P (7) 243*h*. Electric fusion crystallization of magnesium, zirconium, and calcium oxides, P (4) 106*d*. Granular electrically insulating material of magnesia and fused zircon, P (10) 342*e*. Grinding apparatus, P (6) 205*f*. High temperature [electric] tunnel kiln for production of crystalline refractory and abrasive materials, P (6) 228*f*. Method and apparatus for heating formed products, P (4) 123*a*. Method of making impregnated sintered bauxite grains and the product thereof, P (10) 335*g*. Method [pressure sinter] of preparing plates of boron carbide powder, P (7) 252*i*. Process for producing shaped mordenite bodies, P (8) 288*a*. Protective coated article, P (4) 94*d*. Sintered alpha-alumina and zirconia abrasive product and process, P (10) 335*h*.
Nosova, Z. A. Zircon glazes for structural ceramics, (11) 375*i*.
Notari, B. Method for preparing spheroidal alumina, P (4) 124*i*.
Notley, M. J. F. See MacEwan, J. R.
Noto, Yuko. See Fukuda, Kenzo.
Noto, Yuko; Fukuda, Kenzo; Onishi, Takaharu; and Tamaru, Kenzi. Dynamic treatment of chemisorbed species by means of infrared technique—mechanism of decomposition of formic acid over alumina and silica, (5) 193*g*.
Notz, K. See Keenan, A. G.
Nouveau, H. Insulating and refractory composition and elements for the lining of metal casting molds incorporating such compositions, P (2) 58*h*.
Novak, J. See Hejduk, J.
Novak, J., Funke, A., and Kleinert, P. Determination of small amounts of divalent iron in nickel ferrite and hematite, (6) 225*i*.
Novak, J. E., and Orzechowski, J. F. Production of asbestos yarn, P (10) 343*a*.
Novak, R. E. See Tennery, V. J.
Novikov, G. I. See Gavryuchenkov, F. G.
Novikov, S. N. See Izrailevich, I. S.
Novokhatskii, D. F., and Ivanova, N. A. Plugging cement from ferromanganese slags, (1) 3*g*.
Novokhatskii, I. A., and Lenev, L. M. Thermodynamic properties of Cr_2O_3 and $FeCr_2O_4$ at high temperatures, (8) 300*h*.
Novokhatskii, I. A., Lenev, L. M., Savinskaya, A. A., and Gorokh, A. V. Diagram of phase equilibria in the system MnO-Al_2O_3 (corundum), (4) 131*j*.
Novotny, A. Physical conditions of enameling the inside of long tubes of small ID, (10) 336*j*.
Novotny, J. See Deren, J.
Nowik, I., and Wickman, H. H. Relaxation phenomena in Moessbauer spectra of magnetically ordered erbium ions in $ErFeO_3$, (2) 82*c*.
Nowotny, H. See Yvon, K.
Nuckols, D. E. See Lherault, J. A. D. P.
Nuclear Materials & Equipment Corp. Apparatus for producing vapor coated particles, P (6) 217*h*.
Nunlist, E. J. Connection with a glass coated sealing surface, P (7) 246*e*.
Nuyens, J. G. E., and Kockaerts, R. F. Reliable technique for determining plastic limit, (8) 285*c*.
N. V. Koninklijke Sphinx-Ceramique v/h Petrus Regout. Method of drying a molded ceramic article on a form, P (7) 259*c*.
N. V. Vereenigde Glasfabrieken (United Glassworks). Method and device for the production of glass footed stemware, P (10) 339*a*.
Nyberg, B., and Kierkegaard, P. Crystal structure of ammonium copper(I) sulfite, (8) 290*b*.
Nyberg, D. W. See Colbow, K.
Nyholm, R. S. See Joergensen, C. K.
Nyman, G. E., and Schultz, L. K. Thermocouple temperature measurement, P (1) 22*h*.
Nyrop, P., and Elsken, J. C. Wash arrangement for screen centrifuges, P (5) 191*g*.
Nyssen, G. A. See Margerum, D. W.

Oak Ridge Technical Enterprises Corp. Method for producing semiconductor nuclear particle detectors by diffusing, P (4) 115*h*.
Oakley, D. R. See Copley, G. J.
Oates, W. A. See Dunn, W. W.
Oates, W. L. Probe assembly for testing semiconductor wafers including a wafer vibrator for effecting good test connections, P (10) 345*f*.
Oberg, M. Evaluation of quartz in airborne dust in the 0.5- to 2-μm size range, (7) 260*b*.
Obermayer, S., Co. Expendable pattern for precision investment casting, P (5) 178*g*.
Oberschmidt, L. E. Acme Brick builds for growth, (6) 213*j*. BOF refractories, the Basic, Inc., way, (4) 103*h*. Continental builds top-fired kiln in new expansion, (4) 122*e*. Corhart takes a giant step in isostatic forming of refractories, (6) 214*j*. Dickey first to extrude 36-48 inch pipe horizontally, (6) 214*a*. Freeport Brick moves into lightweight aggregate production, (4) 101*h*. From management through production—a new Stark Ceramics, (4) 164*i*. Globe Refractories takes giant step in plant design, (4) 104*c*. Greenlite—a new refractory by a new process, (8) 279*a*. How Logan Clay improves customer service, (4) 123*e*. Johns-Manville expands IFB plant to push larger unit concept, (5) 177*d*. Kaiser reveals its growth strategy, (6) 216*b*. Kerabedarf makes brick from rubble, (6) 214*b*. Manor Brickcrafters to serve handmold brick market, (6) 214*c*. Milliken Brick gears for growth, (4) 101*j*. "One high" features production cycle of less than 24 hours, (4) 122*j*. Operation bootstrap builds Waccamaw brick plant, (4) 102*b*. Ottumwa automates with setting machine and tunnel kiln, (4) 102*c*. Plain-end pipe dominates Canadian production, (4) 102*d*. Plants being

readied for expanded brick market, (4) 102*e*. Popularity of sand-molded colonial brick—a growing market, (8) 278*h*. Refractories serve with new zest, (5) 178*d*. SCPI Region 12 tells how and why they lead nation in panels, (4) 102*h*. "Specialties" featured in plant production, (4) 105*j*. Why Belden Brick chose flexibility over mass production, (4) 102*b*. Why Cherokee Brick and Tile chose a new approach to flexibility; two firsts seen at the new plant, (4) 102*c*. Widespread interest signals the resurgence of sand-lime brick, (8) 278*g*.

Oblival'nyi, F. A., Vainshtein, A. L., Khudolel, V. I., Alekseev, V. N., and Pakhunkov, I. N. Large glass blocks—a new building material, (6) 209*i*.

Obnovlenskii, P. A. See Ukrainskii, L. Z.

O'Brien, J. L. See Haggerty, J. S., Leombruno, W. J.

O'Brien, N. R., and Harrison, W. Fabric of a nonfissile Pleistocene clay, (10) 353*a*.

O'Bryan, H. M., Jr., Gallagher, P. K., Monforte, F. R., and Schrey, F. Microstructure control in nickel ferrous ferrite, (5) 181*j*.

Obst, K. H., and Muenchberg, W. Formation of mixed crystals in the system CaO-SrO, (2) 77*g*.

Obst, K. H., and Stradtmann, J. New lime products for quicker slag formation in oxygen-blowing [steel] processes, (6) 216*c*.

Obst, K. H., Stradtmann, J., and Muenchberg, W. Influence of reheating on the reactivity of lime, (6) 215*i*.

Obst, M. Beneficiation of raw materials by means of optical-electronic devices, (5) 189*i*.

Obst, M., and Simon, I. Study of feldspars by high-temperature microscopy, (8) 296*i*.

Obukhovskii, V. V., and Smirnov, P. V. Apparatus for investigating isothermal tranformation kinetics by an X-ray method, (6) 225*g*.

O'Connell, M. See Pao, H. C.

O'Connell, T. B. See Lehr, G. J.

O'Connell, T. B., and Herrington, R. A. Glass sheet [air] tempering apparatus, P (10) 339*f*.

O'Connor, D. J., and Patterson, J. H. Thermal decomposition of crocidolite, (2) 84*f*.

O'Connor, J. J. See Armington, A. F.

O'Connor, T. J. See Dropkin, D.

Oda, Zenjiro; Saito, Koichi; Asamaki, Tatsuo; and Mori, Tokio. Stabilized low pressure triode sputtering apparatus, P (7) 258*a*.

Odberg, L. See Andersson, L. O.

Odom, I. E., and Parham, W. E. Petrography of Pennsylvania underclays in Illinois and their application to some mineral industries, (2) 73*i*.

O'Donnell, P. M. Kinetics of fluorination of beryllium, (4) 142*d*.

Oehler, O., and Guenthard, H. H. $Ca(OH)_2$ and and $Ca(OD)_2$ vibrational crystal structure, normal coordinate, analysis, and assignment, (4) 127*c*.

Oel, H. J. Leaching of glazes and enamels, (1) 15*h*. See Dietzel, A.; Doerbecker, K.; Frischat, G. H.; Tomandl, G.

Oelke, W. W. See Lehr, G. J.

Oess, F. G. Electron gun having electrode cup in ceramic cavity, P (10) 344*g*.

Oesterheld, K. A. Apparatus for dressing crude asbestos separated from the source rock, P (6) 229*b*.

Oesterhelt, G. See de Bucs, E. S.

Oestvold, T. Determination of partial thermodynamic functions for sodium bromide and potassium bromide in the respective bromide-chloride mixtures, (8) 290*d*.

Oetiker, H. Pneumatic separator and bulk solids feeder, P (7) 263*c*.

Oetting, F. L. See Sinke, G. C.

Offenbacher, E. L. See Shapiro, L.

Offenbacher, W., and Kowal, L. B. Detecting ribbon formation abnormalities in drawing glass sheets, P (4) 98*a*.

Office National d'Etudes et de Recherches Aerospatiales. Methods of brazing, P (4) 94*f*.

Offner, M., and Yucelen, Y. Integrated complementary transistor circuit, P (10) 345*c*.

Oftedal, I. Note on the iron content of microcline, (9) 325*h*.

Oganesyan, R. B., and Varuzhanyan, A. A. Apparatus for firing and bloating ceramic and refractory materials in various atmospheres at increased pressures, (2) 54*h*.

Oganesyan, V. Kh. See Dudnik, E. M.

Ogata, Masahiko. See Kato, Ken.

Ogawa, Kazuya. See Tanemura, Fumikazu.

Ogawa, Seiya, and Nakagawa, Yasuaki. Cation diffusion coefficients and vacancy densities in Mn-Zn ferrites, (1) 25*c*.

Ogawa, Seiichiro. Comparative service tests on some nozzles, (11) 372*g*. General problems of refractories for iron and steelmaking from standpoint of the iron industry, (5) 177*d*.

Ogawa, Tomoya. Estimation of the spontaneous polarization of hexagonal ZnS, CdS, and ZnO crystals, (8) 292*c*.

Ogawa, Tomoyasu. See Ohba, Hiroshi.

Ogden, H. R. See Bradley, E. F.

Ogimura, Yoshiko. See Uetani, Keiji.

Ogino, Kazumi. See Adachi, Akira.

Oglebay Norton Co. Apparatus for lining a hot top, P (6) 217*f*. Hot top structure, P (4) 106*j*.

Oguchi, Takehiko. See Ono, Ikuo.

Ogura, Hirokatsu, and Iwamoto, Sadayuki. Method of producing boron carbide, P (1) 14*j*.

Ogura, Seiki. See Viswanathan, C. R.

Ogura, Toru. See Hayami, Ryozo.

Oguri, Yasuo. See Fueki, Kazuo.

Ohanian, M. High voltage low temperature resistance device, P (4) 113*b*.

O'Hanlon, J. F. Plasma anodization of germanium, (9) 311*g*.

O'Hara, C., Kenwright, R., and Whitehead, R. C. Effect of sintering conditions on the magnetic properties of a manganese-zinc ferrite, (2) 62*f*.

O'Hara, M. J. See Biggar, G. M.

O'Hara, M. J., and Biggar, G. M. Diopside + spinel equilibria, anorthite and forsterite reaction relations in silica-poor liquids in the system CaO-MgO-Al_2O_3-SiO_2 at atmospheric pressure and their bearing on the genesis of melilites and nephelinites, (11) 383*g*.

O'Hara, M. J., and Gleim, W. K. T. High surface area alumina and catalyst composite, P (4) 124*b*.

O'Hara, S. Some interface growth features of Czochralski sapphire crystals, (7) 269*c*.

O'Hare, P. A. G., and Hubbard, W. N. Fluorine bomb calorimetry (XIII) enthalpy of formation of arsenic pentafluoride, (1) 29*i*.

Ohashi, Masayoshi. See Watanabe, Hiroshi.

Ohashi, Shigeru. See Takashima, Yoshimasa.

Ohba, Hiroshi. Refractories currently used for iron- and steel-making in Japan and the trend of studies on refractories in foreign countries, (11) 373*h*. Spalling test for casting pit refractories at Yawata Iron Works, (2) 57*j*.

Ohba, Hiroshi; Hiragushi, Keisuke; and Ogawa, Tomoyasu. Corrosion of casting pit refractories by slag (II) observations on slagging action during crucible test, (10) 340*j*. Mechanism of wear of zircon refractories used in tuyere of ladle, (11) 373*h*.

Ohba, Hiroshi; Hiragushi, Keisuke; Ogawa, Tomoyasu; and Fukuoka, Hiromi. Corrosion of casting pit refractories by slag (III) corrosion of acid refractory minerals by slag, (10) 340*i*.

Ohba, Hiroshi; Hiragushi, Keisuke; Tanaka, Masayoshi; and Matsuo, Masataka. Study of blast furnace wall drying, (2) 58*d*.

Ohba, Hiroshi; Hiragushi, Keisuke; and Yamamoto, Hiromi. Property changes in various refractory mortars caused by molten iron and the effects of atmosphere, (11) 373*g*.

Ohba, Hiroshi; Sugita, Kiyoshi; and Nomura, Takateru. Changes which occur in the physical and chemical properties of dolomite when fired at 1600°, 1800°, and 2000°C, (10) 340*h*.

Ohba, Hiroshi; Sugita, Kiyoshi; and Shimada, Kohei. Changes in microstructure and composition of magnesia brick during firing and cooling, (7) 250*f*. Changes in physical properties of basic refractories due to repeated heating and cooling, (11) 372*j*. Formation of direct bond in chrome-magnesia brick and the changes in properties after high-temperature firing, (11) 373*e*. Properties of direct-bonded magnesia-chrome brick after service in an open-hearth furnace roof and its mechanism of wear, (2) 57*c*.

Ohba, Hiroshi; Sugita, Kiyoshi; Shimada, Kohei; and Taniyama, Mitsuya. Properties of high purity magnesia brick after service in mixer lining, (2) 57*e*.

Ohbayashi, Kohji, and Ilda, Shuichi. Oxygen content and thermomagnetic properties in $Cu_{1-x}Mg_xFe_2O_4$, (1) 34*e*.

Ohda, T. See Takamiya, Yoichi.

Ohio Brass Co. Spark gaps, P (8) 283*i*.

Ohio Crankshaft Co. Apparatus and method of growing a crystal from a vapor, P (4) 112*c*.

Ohishi, Masamoto. See Miyatake, Kazumi.

Ohlgren, H. A. Preparation of finely divided crystalline metal carbides, P (7) 253*b*.

Ohlmann, R. C. See Mazelsky, R.

Ohmatsu, Tomio. See Nameishi, Naoyuki.

Ohmega Laboratories. Light bulb with a plurality of independently connected filaments for indicating graphic symbols, P (2) 65*h*.

Ohmori, Kazuo; Otiai, Tsunemi; and Ikeda, Junichi. Spalling test for stopper head and sleeves, (2) 58*a*.

Ohnemueller, W., and Solf, A. Synthesis of wollastonite from calcium hydrosilicates, (11) 387*j*.

Ohnesorge, W. E. See Fink, D. W.

Ohno, Tomeli. See Akashi, Tsuneo.

Ohta, Z.; Mizuno, Shigeki; and Hara, Toshio. Results of cooperative studies concerning refractoriness-under-load test conducted on some magnesia clinker samples—Area of Tokai, Japan, (10) 342*d*.

Ohtsuka, Atsushi. Formation and color development of titanium-chromium spinels containing Co^{2+} and Ni^{2+} ions, (1) 30*b*. Research on titanium-aluminum spinel containing Co^{2+} and Ni^{2+} ions, (1) 36*e*.

Ohtsuka, Minao. Results of comparative service tests on various refractory brick in cupola lining, (7) 251*g*.

Ohtsuki, T., Matsushima, K., Watanabe, K., Sonoda, T., and Yamaji, N. Heat oxidation of self-supported magnesium thin films and their structure, (8) 281*i*.

Oi, N., and Tanabe, I. Fission product segregation at the surface of irradiated UO_2 particles, (6) 232*g*.

Oishi, Jun. See Iwamoto, Kazumi.

Okabe, Takahiro. See Soga, Minoru.

Okada, Kazuo; Sakane, Hideo; and Sugioka, Yasoichi. Properties of thermally grown silicon nitride films, (1) 35*i*.

Okada, Kenichi. Physical properties of alumina cement, (11) 373*a*.

Okada, Kichiji, and Izaki, Toshiyuki. Spalling resistance of sleeves, (2) 57*i*.

Okada, Takasi, and Nakamura, Masaru. Semiconductor device with Schottky barrier formed on (100) plane of GaAs, P (10) 346*b*.

Okada, Takuya. See Watanabe, Hiroshi; Yamamoto, Hisao.

Okada, Toshihiro. See Goto, Tsuneaki.

Okada, Yoshiji, and Abe, Heiji. Study of $ZrSiO_2$-Al_2O_3-SiO_2 brick used for 80-ton open-hearth furnace ladle, (11) 374*b*.

Okahara, Masamichi. See Takahashi, Katsuaki.

Okamoto, Shoichi; Arase, Masahiko; and Okamoto, Shoka. Reactive hot-pressing of $Ni_{1/3}Fe_{2/3}$ oxyhydroxides, (4) 153*c*.

Okamoto, Shoko. See Okamoto, Shoichi.

Okamoto, Tetsuhiko; Fujii, Hironobu; Hidaka, Yasuharu; and Tatsumoto, Eiji. Effect of hydrostatic pressure on the Néel temperature in FeO and CoO, (1) 27*j*.

Okamoto, Yoshiyuki. See Blank, Z.

O'Kane, D. F. See Chiang, Ping-Wang; Giess, E. A.; Scott, B. A.

O'Kane, D. F., Burns, G., Scott, B. A., and Giess, E. A. Crystal growth and electrical properties of potassium-strontium and potassium-lead niobates containing lanthanum, (10) 351*h*.

Okaya, Akira, and de Witte, S. Ion laser having a metal tube shrink-fitted onto the ceramic discharge tube, P (7) 256*f*.

Okazaki, Atsushi; Iwanaga, Hiroshi; and Tsukuda, Noboru. Crystal structure of the $GdFeO_3$ type, (2) 75*h*.

Okazaki, H. See Totani, A.

Okazaki, Kiyoshi, and Noguchi, Toyomasa. Study on the granulation and forming of raw powders of ceramic dielectrics, (6) 220*f*.

O'Keeffe, M., and Valigi, M. Madelung potentials and ordering energy in TiO, (10) 356*e*.

Okikawa, Shinji. See Saito, Shinroku.

Okinaka, Hideyuki; Kosuge, Koji; and Kachi, Sukeji. Phase diagram of (Fe,Mn)O at 1260°K, (4) 149*a*.

Okubo, Tsutomu. See Noguchi, Tetsuo.

Okuda, Hiroshi. See Nakano, Kikuo.

Okuda, Minoru. See Osaka, Matajiro.

Okuda, Shigeru. See Tani, Tetsuro.

Okuda, Susumu. See Faruqi, F. A.

Okumura, Tomisaburo. Field-effect transistor having insulated gates, P (10) 344*j*. Method of producing semiconductor devices, P (5) 184*e*.

Okutsu, Shinkichi; Narial, Noriyuki; Takagi, Takeshi; and Uehara, Keijiro. Surface treatment for semiconductor devices, P (9) 314*e*.

Oldershaw, G. A., and Robinson, K. Ultraviolet absorption spectra of SnBr and SnI, (9) 332*f*.

Oldham, K. B., and Luchsinger, E. B. Hot-wire method for the determination of thermal conductivities, (4) 119*i*.

Oldham, W. G., and Holmstrom, R. Growth and etching of Si through windows in SiO_2, (4) 137*h*.

Olds, L. E. See Wesel, J. R.

Oldshue, J. Y. Mixing, (1) 20*e*, (4) 117*i*.

Oleson, R. W., and Leishman, E. G. Means for measuring movement in masses of rock or the like, P (4) 124*e*.

Olin Mathieson Chemical Corp. Preparation of pure monocalcium phosphate, P (1) 24*d*.

Olive, W. W., and Finch, W. I. Stratigraphic and mineralogic relations and ceramic properties of clay deposits of Eocene Age in the Jackson Purchase region, Kentucky, and in the adjacent parts of Tennessee, (9) 316*i*.

Oliver, A., Jr. Millefiori glass in classical antiquity, (4) 90*b*.

Oliver, D. W. Elastic moduli of MnO, (9) 320*h*.

Oliver, E. M., and Willson, R. M. Aging of enameling steels, (1) 3*j*.

Oliver, P. E. See Bass, S. J.

Oliver, R. H. See Bean, C. M.

Olivier, J. P. See Morris, H. H.; Sennett, P.

Olivier, J. P., and Hickin, G. K. Apparatus and process for determining particle size by X-ray absorption analysis, P (9) 315*h*.

Olmstead, J., Jacobus, L. A., Jr., and Athanassiadis, E. G. MOS tetrode, P (5) 184*a*.

Olmstead, J. A. See Scott, J. H., Jr.

Olmsted, L. E. See Hoffmann, B. J.

Olofsson, G. Thermodynamic properties and frequency shifts of some molecular adducts of antimony pentachloride and molecules containing the carbonyl group, (7) 270*b*.

Olofsson, O. Crystal structure of Sn_4P_3, (4) 130*d*.

Olsen, A. H. See Trutner, D. G.

Olsen, C. W. See Broyles, J. E.

Olsen, D. A., Johnson, R. E., Kivel, J., and Albers, F. C. Kinetics of leaching of lead glass by ethylenediaminetetraacetic acid, (8) 276*d*.

Olsen, G. F., and McLeod, D. L. Rotary kiln linings, P (8) 286*f*.

Olsen, K. H., and Nicholson, G. C. Anomalous sintering behavior as revealed by in situ electron microscopy, (1) 25*h*.

Olsen, K. M., Smith, D. H., Stockbridge, C. D. G., and Tolman, E. M. Magnetic memory element comprising Ni-Fe and Zr and composition comprising Ni-Fe-Zr, P (5) 183*h*.

Olson, D. H. X-ray evidence for residual water in calcined divalent cation faujasite-type zeolites, (5) 203*a*.

Olson, D. H., Kokotailo, G. T., and Charnell, J. F. Crystal structure of cerium(III) exchanged faujasite, (4) 130*g*.
Olson, J. C. See Strnat, K. J.
Olson, J. H. Forming metals using liquid dies, P (4) 94*b*.
Olson, N. J., and Toop, G. W. Predicting ternary phase diagrams and quaternary excess free energy using binary data, (10) 359*d*.
Olson, O. H. See Li, P. C.
Olson, P. A. Glass article having a birefringence pattern and method of production, P (5) 174*d*.
Olson, W. M., and Mulford, R. N. R. Melting point and decomposition pressure of neptunium mononitride, (4) 144*d*.
Olsson, R. G., Perzak, T. F., and Koump, V. Rate of dissolution of alumina in molten iron oxide, (4) 152*i*.
Olstowski, F. Hyperconductive graphite structures, P (2) 56*g*. Process for preparing resilient graphite structures, P (5) 179*b*.
Olstowski, F., and Guebert, K. W. Method of preparation of compressed vermicular graphite, P (9) 309*g*.
Olstowski, F., and Mezoff, J. G. Process for producing structures containing shaped voids, P (6) 218*b*.
Olstowski, F., and Osborn, O. Method for preparing compressed vermicular graphite structures, P (7) 252*h*.
Olstowski, F., and Watson, J. D., Sr. Method for producing carbon-bonded graphite structures, P (8) 279*h*. Method for producing low density graphite structures, P (4) 107*a*.
Olszewski, E. See Lebda, E.
Oltman, H. G., Jr., and Kaufman, I. Ultrasonic transducer, P (10) 346*a*.
Omel'chenko, Yu. A. See Vil'k, Yu. N.
O'Melia, C. R., and Stumm, W. Aggregation of silica dispersions by iron(III), (1) 25*b*.
Omsteel Industries, Inc. Electromechanical transducer material [colloidal graphite], P (9) 312*f*.
Ondracek, G., and Patrassi, E. Unstable cermet combination U_3O_8-Al (II) reaction behavior and properties of the cermets, (6) 217*e*.
Ondracek, G., and Petzow, G. Thermochemical and technological investigation of the uranium mononitride-carbon system, (5) 201*j*.
Ondracek, G., and Schulz, B. Unstable cermet combination U_3O_8-Al (I) technology, (6) 217*c*.
O'Neal, J. E., and Leonhard, F. W. Epitaxy of GaAs on vacuum-cleaved rock salt, (7) 265*e*.
O'Neil, J. R., and Taylor, H. P., Jr. Oxygen isotope and cation exchange chemistry of feldspars, (4) 148*a*.
O'Neill, J. J., Jr. See Vossen, J. L.
O'Neill, J. S. See Hill, N. A.
O'Neill, J. S., Hill, N. A., and Livey, D. T. Observations on the strength and Young's modulus of BeO as a function of density and grain size, (2) 81*c*.
O'Neill, P. See Glasson, D. R.
O.N.E.R.A. See Office National d'Etudes et de Recherches Aerospatiales.
Onikienko, L. D. See Korzhukov, N. G.
Onishi, Takaharu. See Fukuda, Kenzo; Noto, Yuko.
Ono, Ikuo, and Oguchi, Takehiko. Magnetization process in spinel lattice, (2) 80*g*.
Ono, Kazumasa; Yashiro, Takehisa; and Yagi, Shoji. Investigation of SiO_2 surface topography and SiO_2 interface structure, (7) 255*c*.
Ono, Kazuo; Chandler, L., and Ito, Atsuko. Moessbauer study of the ulvospinel, $TiFe_2O_4$, (2) 80*e*.
Ono, Minoru. Method of producing insulated-gate field-effect transistors with improved characteristics, P (4) 115*g*.
Ono, Shuichiro. See Yamaguchi, Goro.
Ono, Shusuke, and Sugihara, Ko. Trigonal warping of the bands and Hall effect in graphite, (2) 84*d*.
Onoda, Mitsuaki. See Hayashi, Takeshi.
Onoda Cement Co., Ltd. Apparatus for electrostatic precipitation of dust, P (8) 284*d*.
Onoders, K. See Fujii, I.
Onoders, Yutaka. See Saito, Yukinori.
Onoe, Morio, and Warner, A. W., Jr. Oriented $LiTaO_3$ crystal and devices using same, P (11) 378*b*.
Onton, A., and Lorenz, M. R. Dependence of radiative efficiency in GaP diodes on heat treatment, (1) 26*j*.
Onuma, K. See Yagi, K.
Onuma, Naoki. See Tomura, Kenja.
Onuma, Takeshi, and Terasaki, Takeshi. Method of making a variable capacitance silicon diode with hyper abrupt junction, P (4) 115*c*.
Ooka, Kazuo. See Kishii, Toru.
Ooka, Kazuo, and Kishii, Toru. Observations on the thermally released current in glasses damaged by ultraviolet radiation, (4) 96*c*.
Opaleichuk, L. S. See Gervids, I. A.
Op De Beeck, J., and Hoste, J. Determination of copper and bismuth in high purity lead metal by neutron activation analysis, (5) 187*e*.
Opoczky, L. Overgrinding of cement clinker, (11) 368*f*.
Opperman, K. W. See Ennos, A. E.
Optical Coating Laboratory, Inc. Antireflection coating and assembly having synthesized layer of index of refraction, P (6) 212*b*.
Optics Technology, Inc. Apparatus for coupling and amplifying light between optical fibers, P (2) 52*i*. Electrooptic image intensifier and method of making same, P (11) 376*e*.
Orcutt, D. R. Method for producing [laminated] window panels, P (4) 100*c*. Method for producing window panels, P (4) 100*e*.
Orcutt, F. D. See Boyer, C. B.
Ordan'yan, S. S. See Vil'k, Yu. N.
O'Reilly, B. E. See Palilla, F. C.
Orient, L., and Faerman, B. Scientific apparatus, (2) 70*i*.
Orlansky, R. Method for making slides of fine-grained unconsolidated sediment and ooze, (6) 226*d*.
Orlova, E. M. See Ananich, N. I.
Orlova, I. G., and Natsenko, A. I. Microstructure and heat resistance of corundum ceramics, (10) 341*d*.
Ormesher, E. R. Method and apparatus for electrical viscosity control of float glass, P (8) 277*g*.
Ornitz, M. N. Centrifugal casting apparatus with smooth refractory nonhydrocarbon mold coating, P (7) 252*e*. Mold coating composition, particularly for centrifugal molds, P (9) 309*a*.
Orobchenko, V. I., Ovcharenko, F. D., Kruglitskii, N. N., Nichiporenko, S. P., and Mishchenko, S. F. Effect of duration of magnetic field action on formation of coagulation structures in aqueous suspensions of clay minerals, (4) 132*c*.
Oron, M., and Barlow, I. C. Chemical interaction between gadolinium iron garnet and fused quartz, (4) 128*c*.
Oron, M., Barlow, R., and Traber, W. F. Ferrimagnetic garnet thin films—growth, structure, and some magnetic properties, (10) 344*b*.
Oroshnik, J., and Kraitchman, J. Pyrolytic deposition of silicon dioxide in an evacuated system, (9) 328*a*.
Orr, C., Jr. See Davis, D. K.
Orser, L. D. See Hughes, R. O.
Orshanskaya, Z. N. See Nikolaev, R. K.
Ortega, R. F. See Cloete, F. L. D.
Ortel, W. C. G. Techniques for charting and removing defects in thin film capacitors, P (2) 66*i*.
Ortner, E., and Hartman, R. A. O-bend lead for semiconductor packages, P (9) 313*a*.
Ortner, M. H., and McCullough, H. M. Sulfidation corrosion-resistant coating containing rare-earth metal aluminides, P (9) 304*j*.
Orville, P. M. See Grover, J. E.
Orzechowski, J. F. See Novak, J. E.
Osaka, Matajiro; Ueda, Hidetaka; Horii, Shigeo; and Okuda, Minoru. Continuous countercurrent washing system by thickener method, P (8) 287*g*.
Osborn, E. F. See Speidel, D. H.
Osborn, O. See Olstowski, F.
Osborne, D. W. See Westrum, E. F., Jr.
Osborne, G. J. See Gutt, W.
Osborne, H. N. Composite light transmitting and light reflecting panels and the like, P (10) 338*i*.
Osborne, R. H. American Upper Ordovician standard (XI) multivariate classification of typical Cincinnatian calcarenites, (11) 383*b*.
Osburg, L. A. See Millikan, R. C.
Ose, Akira, and Goto, Eizo. Method of making baseless lamp bulb, P (2) 53*f*.
O'Shea, C. J., Quinn, R., and Johnson, D. S., Jr. Apparatus for determining wall thickness utilizing radiation absorption, P (5) 174*g*.
O'Shea, D. C. See Shapiro, S. M.
O'Shea, D. C., Kolluri, R. V., and Cummins, H. Z. Temperature dependent Raman spectrum of strontium titanate, (4) 159*f*.
Oshida, O. A., Gilmore, J. P., and Lowe, J. H. Method for manufacturing improved perlite filter aid products, P (7) 263*a*.
Oshurkova, O. V. See Konstantinov, B. P.
Osiko, V. V. See Kaminskii, A. A.; Krotova, L. V.
Osipov, A. D. See Nichiporenko, E. P.
Osment, H. E., Emerson, R. B., and Jones, R. L. Preparation of white fused alumina, P (2) 74*b*.
Osovitz, E. E. See Zysk, E. D.
Ossman, G. W., and McGrath, J. W. Nuclear magnetic resonance study of Li_3Sb, Na_3Sb, and Na_3As powders, (6) 235*j*.
Ost, H. L. See Maetz, H.
Ostberg, W., and Patzias, T. Process for forming special cements, P (7) 245*d*.
Osterholtz, C. E. Graphite bearing high MgO mortar, P (8) 279*b*.
Osterink, L. M., and Foster, J. D. Thermal effects and transverse mode control in an Nd : YAG laser, (1) 17*e*.
Osterreichisch-Amerikanische Magnesit Akt.-Ges. Process for the manufacture of refractory magnesia-chrome and chrome-magnesia products, P (6) 218*i*.
Osterreichische Studiengesellschaft fuer Atomenergie G.m.b.H. Method for the extraction of materials embedded in a graphite body, P (5) 178*f*. Process for disintegrating graphite bodies, P (10) 343*a*.
Ostertag, W. Magnetic susceptibility of uranium (IV) glasses, (4) 96*b*. See Strnat, K. J.
Ostertag, W., Fischer, G. R., and Williams, J. P. Thermal expansion of synthetic β-spodumene and β-spodumene-silica solid solutions, (1) 9*e*.
Ostertag, W., Hoar, E. A., and Fischer, G. R. Stereographic projection of crystal structures: Example, β-spodumene, (6) 237*i*.
Ostrander, G. W. See Pendleton, W. W.
Ostrander, G. W., and Pendleton, W. W. Method of making high-temperature encapsulated apparatus, P (5) 172*c*.
Ostrikov, M. S. See Dibrov, G. D.
Ostroff, N. See Colgan, J. D.
Ostrovskii, O. P., Kornienko, V. E., and Shklyarenko, N. G. Effect of tunnel kiln channel width on uniformity of firing, (6) 228*g*.
Otenbaker, J. T. See Saad, O. C.
Otiai, Tsuneni. See Ohmori, Kazuo.
O'Toole, J. T. See Shendalman, L. H.
Otrhalek, J. V. See Duvall, J. L.
Otsubo, Katsuhiko, and Tada, Takaharu. Results of test on high-fired basic brick used in an open-hearth furnace roof, (2) 57*c*. Results of using high-fired basic brick in roof of open-hearth furnace, (11) 374*b*.
Ottaway, J. M., and Fuller, C. W. Interference of vanadium in the titrimetric determination of iron by the tin(II) chloride-mercury(II) chloride-dichromate method, (9) 315*i*.
Otto, E. M. Equilibrium pressures of oxygen over oxides of lead at various temperatures, (1) 29*j*.
Ouchi, Hiromu. See Hayakawa, Shigeru.
Ouchi, Hiromu, and Nishida, Masamitsu. Piezoelectric ceramic compositions, P (1) 18*i*, P (5) 184*f,g*.
Ouweltjes, J. L. See Wanmaker, W. L.
Ovcharenko, F. D. See Brekhunets, A. G.; Kruglitskii, N. N.; Orobchenko, V. I.; Tarasevich, Yu. I.
Ovcharenko, F. D., Agabal'yants, E. G., and Ryabchenko, V. I. Coagulative structure formation in suspensions (II) effect of sodium and calcium chlorides on the structure formation of lime-clay suspensions; (III) influence of pressure-vessel treatment on structural-mechanical properties of lime-clay suspensions, (7) 253*j*. Effect of calcium hydroxide on structural formation of clay suspensions, (7) 253*e*.
Ovcharenko, F. D., Belik, F. A., and Tarasevich, Yu. I. Adsorption of hydrocarbons on clay minerals—adsorption of benzene, (10) 349*h*.
Ovcharenko, F. D., Nichiporenko, S. P., Kruglitskii, N. N., and Tretinnik, V. Yu. Investigation of the Physicochemical Mechanics of Clay-Mineral Dispersions, B (2) 85*h*.
Ovenston, A., and Benbow, J. J. Effects of die geometry on the extrusion of claylike material, (6) 224*i*.
Overcashier, R. H., Shain, S. A., and Schlaudt, C. M. Method of producing foamed glass having uniform cell size, P (8) 278*a*.
Overman, K. T. Constant force internal [refractory] support for glass overflow wedge, P (7) 248*d*.
Ovitron Corp. Transformer including boron nitride insulation, P (6) 224*a*.
Owada, Atsushi. See Shibata, Shinichi.
Owen, A. J. See Gregory, C. K.
Owen, J. E. Colored titanium pigment materials having a spinel structure and method of preparing same, P (5) 190*h*.
Owens, B. B. See Topol, L. E.
Owens, K. E., and Hatch, R. A. Ceramic greensheets, P (11) 371*b*.
Owens, W. H. Process for recovering Zr values from ores, P (4) 125*d*.
Owens-Corning Fiberglas Corp. Acoustical panels, P (9) 307*j*. Apparatus for bulking yarn, P (1) 10*c*. Apparatus for driving filamentary material collectors, P (1) 10*e*. Apparatus for melting and processing heat-softenable mineral materials, P (1) 10*h*. Creel adapter for filamentary material processing apparatus, P (6) 212*j*. Elastomeric-glass fiber products and process and elements for use in same, P (4) 98*c*. Fiber aligning apparatus, P (10) 338*i*. Fibrous bodies including strands and methods of producing such bodies, P (8) 277*i*. Glass composition, P (1) 10*d*. Glass fiber reinforced elastomers, P (5) 174*f*. Glass fiber reinforced elastomers and composition for sizing and impregnating such glass fiber systems, P (1) 10*e*. Gypsum wallboard, P (11) 368*e*. Internal combustion burner nozzle construction, P (2) 53*c*. Light control panel, P (7) 249*a*. Method and apparatus for handling fibrous materials, P (1) 11*e*. Method and apparatus for handling strand, P (2) 53*h*. Method of and apparatus for heating material, P (5) 175*i*. Method and apparatus for packaging materials, P (1) 11*e*. Method and apparatus for processing filament-forming mineral materials, P (2) 53*j*. Method and apparatus for processing heat-softened material, P (2) 53*a*. Method and apparatus for processing heat-softened mineral material, P (4) 99*f*. Method and apparatus for producing fibers, P (4) 99*h*. Method of coating fibers and fibers formed therefrom, P (11) 371*f*. Method for the impregnation of fibrous glass [bundles], P (6) 213*b*. Method and means for strand dispersal, P (4) 100*c*. Method for production of tubular fibrous bodies, P (2) 53*h*. Molten material furnace hole closures, P (1) 14*b*. Opalescent glass fibers, P (4) 100*e*. Reinforced hydraulic cements and casts therefrom, P (11) 368*f*. Slurry pouring means and mold, P (11) 375*d*. Structural [fibrous] panel and method of production, P (7) 249*f*. Treated glass fiber bundles and combinations thereof with elastomeric material, P (10) 340*a*. Wall construction for melting tanks, P (7) 249*g*.
Owens-Illinois, Inc. Abrasion resistant glass article and method for producing same, P (8) 277*d*. Abrasion resistant glass surfaces, P (7) 248*g*. Apparatus for applying [resin]

bonding material between implosion band and glass for cathode ray tubes, P (2) 52*i*. Apparatus for centrifugally casting glass articles, P (8) 277*e*. Apparatus for controlling glass tube and rod dimensions, P (1) 10*c*. Apparatus for forming glass articles with [air] treating means, P (8) 277*f*. Apparatus and method for producing silica and other oxides, P (5) 190*f*. Apparatus for producing glass rod and tubing, P (4) 98*f*. Apparatus for supporting and glazing glass articles, P (4) 98*f*. Art of decorating glass-ceramic substrates, P (4) 98*g*. Art of producing metal salt impregnated silica-coated substrates, P (7) 248*a*. Banding machine, P (10) 338*h*. Bottle forming apparatus, P (1) 10*j*. Bottle gaging, P (5) 174*a*. Cathode-ray and other vacuumized tubes resistant to violent devacuation, P (2) 52*c*. Cathode-ray tube envelopes, P (2) 52*c*. Coated glass and method of making same, P (11) 371*c*. Coated refractory for contacting molten glass and method of making, P (7) 252*g*. Composite lamp article with glass-ceramic lamp envelope, P (9) 307*b*. Container indexing and rotating, P (11) 371*c*. Crystalline luminescent ceramic materials, P (11) 371*d* Electrical printing apparatus using screen with thick coating to define image, P (8) 277*h*. Electrical printing methods and apparatus for decorating cylindrical articles, P (11) 371*f*. Electrical printing process using an opposing field, P (5) 186*e*. Electrostatic method for decorating glass and vitreous enamels for use therein, P (7) 248*e*. Forehearth addition process for viscosity change, P (8) 277*j*. Gas fired frit melter, P (11) 371*g*. Glass-ceramic product and method for making same, P (10) 339*a*. Glass compositions, P (11) 371*h*. Glass compositions for laser application, P (10) 339*b*. Glass compositions, method, and articles, P (11) 371*h*. Glass forming container neck ring, P (5) 174*f*. Glass parts for forming cathode-ray tube envelopes, P (1) 10*c*. Glass surfaces having dual protective label accepting coatings and method, P (5) 174*j*. Grinding fixture for television funnels, P (10) 339*f*. High expansion sealing glass and composite article, P (9) 307*f*. High silica content glasses, P (11) 371*j*. Inspecting open mouth translucent containers for defects, P (2) 53*a*. Inspecting sealed [glass] containers in closed cartons, P (9) 307*g*. Laser glasses having a relatively low thermal expansion, P (10) 339*b*. Method and apparatus for heating rollers, P (5) 175*j*. Method and apparatus for inspecting glass containers, P (4) 99*d*. Method and apparatus for producing hollow glass articles by module immersion technique, P (10) 339*i*. Method of assembling a composite container, P (7) 249*c*. Method of fabricating transparent reinforced glass pipe, P (10) 339*a*. Method of forming a glass body of devitrifiable glass and devitrifying the same, P (11) 371*f*. Method of forming a glass-ceramic article having an internal cavity, P (7) 249*e*. Method of imparting abrasion and scratch resistance to glass surfaces and glass articles produced thereby, P (4) 99*j*. Method for initiating and controlling crystallization of glass, P (8) 277*i*. Method of installing high temperature furnace insulation, P (6) 217*h*. Method of rendering glass surfaces abrasion-resistant and article produced, P (4) 100*g*. Method of rendering glass surfaces abrasion and scratch resistant, P (7) 249*a*. Method of rendering glass surfaces abrasion-resistant and glass articles produced thereby, P (2) 53*h*, P (4) 100*h*, P (7) 249*i*. Method of sealing copper in silica body, P (8) 278*b*. Method of sealing fiber optic devices, P (8) 278*b*. Method for sealing glass to metal and seal produced thereby, P (2) 66*b*. Method of staining glass and glass staining composition, P (5) 175*h*, *i*. Method for surface treatment of glass articles, P (6) 213*f*. Method of treating glassware, P (1) 11*b*. Molten addition of colorant in a glass furnace forehearth, P (8) 278*d*. Offset plate decorating methods and apparatus, P (2) 53*j*. Package for elongate frangible articles [glass stemware] having wide thin extremity portions, P (10) 339*i*. Parison transfer and invert mechanism, P (8) 278*a*. Photoluminescent glass systems, P (7) 249*b*. Pipet plugger, P (11) 372*c*. Preparation of luminescent silica glass modified with a rare earth metal, P (11) 372*c*. Process for glass strengthening, P (11) 372*d*. Process for preparing indium and scandium antimonates, P (9) 317*d*. Process of producing oxides of metals and metalloids, P (4) 125*j*. Process for treating glass cathode-ray tube envelopes, P (4) 100*j*. Pumping vane type glass feeder, P (4) 100*j*. Sealed glass article of manufacture, P (4) 101*d*. Sealing glass compositions, method of sealing, and article, P (5) 176*a*. Sintered glass article and method of making, P (4) 101*a*. Solder glass compositions and method of sealing metal therewith, P (10) 340*b*. Strengthened crystalline article and method of making the same, P (6) 213*f*. Surface treatment of glasses, P (11) 372*c*. Titanium oxide compounds, P (4) 126*b*. Vacuum forming glass articles with vented modules, P (10) 340*b*. Vanadium-zinc borate solder glasses, P (8) 278*c*.

Oxford Paper Co. Composite colloidal pigment [clay] particles, their formation and suspensions thereof, P (10) 349*c*.

Oxley, B. W. See Dickinson, G. A.

Oya, Yoshiko, and Miyata, Kenichi. Variation of surfaces characteristics of quartz powder with particle size (II) relation between heats of immersion of quartz powder in water and particle size, (4) 163*d*.

Oyama, Hojiro. See Shimada, Nobuo.

Ozaki, Hiroshi. See Sogawa, Satori.

Ozaki, Shunro. See Yamauchi, Shiro.

Ozaki, Shunro, and Iida, Yoshio. Titanium carbide formation by the reaction of TiO_2 and carbon powder, (5) 178*g*.

Ozawa, Kunio. See Nakagawa, Masuo.

Ozenne, G. J., and Stephen, F. M. Automatic apparatus with continuously moving conveyors for casting ceramic articles, P (4) 109*b*.

Ozerova, M. I. See Korzhukov, N. G.

Packard, R. Q. Measurement of aqueous conductivity of unfired ceramic bodies, (1) 21*d*.

Packer, M. E. See Bristow, T. J.

Packter, A. Kinetics of the heterogeneous reaction of silica with basic alkali-metal salt solutions in chloride melts, (9) 323*j*.

Packter, A., and Dhillon, H. S. Reaction of alumina hydrate powders with sodium hydroxide, (4) 152*b*

Paderno, J. See Niemyski, T.

Paderno, Yu. B. See Samsonov, G. V.

Padgett, G. C. See Lythe, T. W.

Padgett, G. C., Cox, J. A., and Clements, J. F. Stress/strain behavior of refractory materials at high temperatures, (10) 342*g*.

Padley, P. J. See Kelly, R.

Pagano, M., and Vilnat, J. Measurement of stresses on earthenware tiles set on reinforced concrete slabs, (4) 108*d*.

Pagano, N. J. See Tsai, S. W.

Page, A. L. See Laudelout, H.

Page, J. A. See Zinser, E. J.

Page, L. C. See Goosey, M. H.

Page, P. B. Temperature compensation of crystal oscillators, P (10) 346*e*.

Paidossi, J., and Caillat, R. Transport phenomena in fluorite-type, cubic phases related to zirconia, (5) 202*j*.

Pajisek, F. See Bezouska, V.

Pakhunkov, I. N. See Oblival'nyi, F. A.

Pakulski, F. J., and Wright, W. L. Electric field tailoring of thin film resistors, P (4) 112*c*.

Palenik, G. J. Crystal structure of potassium manganate, (4) 130*c*. Crystal structure of potassium permanganate, (4) 130*d*.

Palermo, J. A. Crystallization, (4) 164*i*.

Palermo, J. J., Bonazoli, R. P., Scoledge, R. F., and Audesse, E. G. Incandescent lamp, P (4) 99*i*.

Paletto, R. Method of making *pn* alloy junctions, P (5) 183*g*.

Pallilla, F. C., Levine, A. K., and Tomkus, M. R. Fluorescent properties of alkaline earth aluminates of the type MAl_2O_4 activated by divalent europium, (9) 321*g*.

Pallilla, F. C., and O'Reilly, B. E. Alkaline earth halophosphate phosphors activated by divalent europium, (10) 349*j*.

Palin, F. T. See Richardson, H. M.

Pall, D. B., Belfield, R. E., Rosenberg, D. J., and Vogel, A. C. Method and apparatus for forming tubular fibrous insulating articles, P (8) 277*g*.

Pall Corp. Swing mounted thermocouple assembly, P (11) 381*b*.

Palmer, A. C. Stress strain relations for clays—an energy theory, (1) 38*b*.

Palmer, A. O. Metal abrasive sheet and a method of making same, P (1) 1*h*.

Palmer, A. W. See Drabble, J. R.

Palmer, D. J. Reaction of hydrogen with graphite, (4) 152*f*.

Palmer, D. W., and d'Artemare, E. Orientation dependence of Rutherford scattering of protons from quartz, (4) 147*f*.

Palmer, N. J. Toilet bowl construction, P (4) 109*c*.

Palmour, H., III. Multiple slip processes in magnesium aluminate at high temperature, (2) 80*g*.

Palous, S. See Asquiedge, M.; Guillou, M.

Pamnani, K. Formaldehyde-volatilization method for the decomposition of sands, quartzites, etc., (5) 187*g*. Rapid gravimetric determination of silica in carbonate rocks using gelatin, (5) 187*j*.

Pamplin, B. R. See Springthorpe, A. J.

Panasevich, V. M., Yaremenko, Z. A., Grosheva, V. M., and Tresvyatskii, S. G. Effect of crystallization cycles on the formation of fine needle-shaped mullite, (6) 215*e*.

Panday, V. K., and Ganguly, A. K. Atomic absorption spectrophotometry as a technique in the determination of vapor pressures of metallic elements, (1) 20*i*.

Pande, P. C. Bauxite deposits of India, (4) 164*i*.

Pandian, N. S. S. See Ranganatham, B. V.

Panis, C. J. W. See Bathelt, R. R.

Panish, M. B. Arsenic-rich region of the Ga-As-Zn ternary phase system—modification of the ternary diagram, (1) 25*h*. Ga-As-Si ternary phase system, (2) 77*a*. Ga-P-Te system, (4) 137*b*. Pseudobinary system Ge-GaAs, (1) 35*d*. Ternary condensed phase diagram of the Ga-As-Te system, (4) 159*i*. Ternary condensed phase systems of gallium and arsenic with group IB elements, (4) 159*i*. See Casey, H. C., Jr.

Panish, M. B., Lynch, R. T., and Sumski, S. Phase and thermodynamic properties of the Ga-Al-P system — solution epitaxy of $Ga_xAl_{1-x}P$ and AlP, (9) 327*j*.

Panke, D., and Woelfel, E. Effect of multiple diffraction on the determination of electron density distributions, (11) 384*g*.

Pankeeva, N. E. See Sazhin, V. S.

Pankey, T. See Davey, J. E.

Pankhurst, R. J. Strontium isotope studies related to petrogenesis in the Caledonian basic igneous province of NE. Scotland, (7) 262*b*.

Pankova, N. A. See Bavich, V. I.

Pankova, N. A., and Variamova, L. S. Prospects for the use of vacuum to intensify the fining process of glass, (2) 53*e*.

Pankove, J. I. Semiconductor plasma laser, P (4) 116*g*.

Pankratz, L. B. High-temperature heat contents and entropies of four crystalline sodium-calcium silicates, (5) 195*c*.

Panteleev, N. I. See Kabanov, A. N.

Panteilis, P. See Allnatt, A. R.

Pao, H. C., and O'Connell, M. Memory behavior of an MNS capacitor, (4) 144*f*.

Paoricl, C. Sodium-doped hollow CdS crystals, (7) 268*d*.

Papee, D. See Michel, M.

Papen, E. L. J. Automation of isostatic presses for production, (4) 108*c*.

Papike, J. J. See Dodge, F. C. W.; Himmelberg, G. R.

Pappalardo, S. See Lubatti, E.

Paramonova, V. A. See Butt, Yu. M.

Paranjape, B. V. Theory of pinch effect in semiconductors, (5) 201*c*.

Paret, G. Possibilities and prob'ems of decorating plates with edging machines, (7) 254*b*. Possibilities and problems of plate decoration with banding machines, (4) 108*i*.

Parfenenkov, V. N. See Gregenshchikov, R. G.

Parfitt, G. D. See Cooper, W. D.; Insley, M. J.

Parham, W. E. See Odom, I. E.

Parham, W. E., and Austin, G. A. Clay mineralogy, fabric, and industrial uses of the shale of the Decorah formation, southeastern Minnesota, (9) 316*g*.

Paricio, R. See Landes, B. D.

Paris, J. M. See Roubin, M. P.

Paris, R. A. See Roubin, M. P.

Parisi, A. J. Thin slab of ceramic can display color images, (4) 111*e*. See Yeaple, F. D.

Parke, S., and Watson, A. I. Absorption and fluorescence spectra of trivalent molybdenum in aluminoborophosphate glasses, (8) 275*j*.

Parker, C. D. See Stillman, G. E.

Parker, E. B. Portable grinding—higher speed means lower costs, (2) 43*f*.

Parker, J. B., and Parker, S. T. Czechoslovakia's expanding trade in glassware, (7) 247*b*.

Parker, R., Rigden, C. J., and Tinsley, C. J. Solid-state reaction between zinc oxide and ferric oxide, (9) 311*j*.

Parker, S. G. See Kraus, H.

Parker, S. G., and Pinnell, J. E. Growth and properties of ZnSe crystals by chemical transport, (9) 322*a*. Molten flux growth of cubic zinc sulfide crystals, (10) 357*a*.

Parker, S. T. See Parker, J. B.

Parkhomovskii, V. L. See Kukui, A. I.

Parkin, A. See Harker, H.

Parkinson, J. R. See Slocombe, J. W.

Parks, G. A. See Anderson, J. H.

Parks, J. K. Broadband reciprocal dual meander line ferrite phase shifter, P (9) 312*c*.

Parmer, W. F. Field-effect transistors, P (7) 256*i*.

Parodi, J. A. Electronic paramagnetic resonance study of the chemistry of Mn^{2+} during the formation of fluorapatite, (4) 135*b*.

Parrent, G. B., Jr. See Silverman, B. A.

Parry, G. S., and Nixon, D. E. Order-disorder transformation in potassium graphite, (9) 326*g*.

Parry, W. T., and Reeves, C. C., Jr. Clay mineralogy of pluvial lake sediments, southern high plains, Texas, (1) 23*c*.

Parsons, B. I. See Montecomery, D. S.

Parsons, D. S. See Watkins, D. A. M.

Parsons, J. R. Carbon composition and process, P (8) 279*f*.

Parsons, W. F. See Carnall, E., Jr.; Roy, D. W.

Partridge, G. See McMillan, P. W.

Parvatikar, K. G. Verification of empirical equations in computing surface tension by the sessile-drop method, (1) 40*b*.

Pascard, R. See Marcon, J. P.

Pasinski, I. Design in architectural products, (2) 48*c*.

Pask, J. A. See Blank, S. L.; Cropper, D. R.; Fulrath, R. M.

Pasternak, M., and Sonnino, T. Studies of IBr, ICl, and I_2Cl_6 crystal properties by means of the Moessbauer effect in ^{129}I: (I) chemical bonds; (II) lattice dynamics, (4) 156*j*.

Pasternak, R. A., and Evans, B. Adsorption, absorption, and degassing in the oxygen-niobium system at very low pressure, (4) 126*e*.

Pasto, A. See Frechette, V. D.

Pastoors, E., and Saller, R. Apparatus for the continuous extraction of moisture from suspended matter, P (11) 379*d*.

Pastor, R. C., Kimura, H., Podoksik, L., Cernichiari, O., and Pearson, M. A. Retention of additives in Y_2O_3, Gd_2O_3, La_2O_3, and α-Al_2O_3, (5) 199*e*.

Patalong, H. See Herlet, A.

Patankar, A. V., and Schneider, E. E. Electron spin resonance and optical studies of low-

temperature radiation effects in lead halide crystals, (8) 291*i*.
Pataud, P. See Apostolov, A.
Patel, A. R., and Agarwal, M. K. Studies on dodecahedral form of diamond, (7) 269*c*.
Patel, A. R., Agarwal, M. K., and Desai, C. C. Fission tracks on (10$\bar{1}$0) cleavages of natural apatite crystals, (1) 29*g*.
Patel, A. R., and Koshy, J. Cleavage and etching of barite, (1) 26*c*. Etching of synthetic barite [$BaSO_4$] single crystals, (10) 353*i*. Growth of barium sulfate single crystals by chemically reacted flux method, (7) 266*f*.
Patel, A. R., and Singh, R. P. Variations in orientation of etch pits on the (111) surface of barium fluoride, (8) 300*h*.
Patel, C. K. N. Infrared modulators and detectors employing single crystal Te or Se, P (4) 113*d*.
Patel, J. R., and Kato, Norio. X-ray dynamical diffraction effects of oxide films on silicon substrates, (4) 111*i*.
Paterson, M. S. See Weaver, C. W.
Patrassi, E. See Ondracek, G.
Patrovsky, V. Determination of magnesium in the presence of calcium by fluorometry, using 8-hydroxyquinoline-5-sulfonic acid, (5) 187*e*.
Patrushev, D. A. See Amelin, E. S.
Patterson, E. See Lewis, M. F.
Patterson, J. A. Method for preparing a slide for viewing, P (9) 315*f*.
Patterson, J. H. See O'Connor, D. J.
Patterson, J. W., Bogren, E. C., and Rapp, R. A. Mixed conduction in $Zr_{0.85}Ca_{0.15}O_{1.85}$ and $Th_{0.85}Y_{0.15}O_{1.925}$ solid electrolytes, (4) 144*i*.
Patterson, M. M. Basics of filtration, (10) 335*f*.
Patterson, R. D. See Culp, J. D.
Patterson, R. J. Method for melt-casting infrared transmitting glasses, P (9) 308*b*.
Patterson, R. J., and Haberecht, R. R. Process for making boron nitride film capacitors, P (4) 115*j*.
Patterson, R. J., and Tilton, A. E. Amorphous glass compositions, P (7) 248*h*.
Patterson, W. R. Gyratory crusher, P (4) 124*b*.
Patton, C. E., and Humphrey, F. B. Domain wall in motion in double nickel-iron films, (4) 132*c*.
Patton, D. M. Tubular welding electrode, P (11) 369*c*.
Pattoret, A. See Drowart, J.
Pattoret, A., Drowart, J., and Smoes, S. Mass-spectrometric study of the evaporation of UO_2 and UC, (1) 32*j*.
Patzak, I., and Konopicky, K. Spalling of refractory brick containing grog from shale, (9) 309*b*. Transformation behavior of various Al_2O_3-SiO_2 minerals, (11) 388*e*.
Patzak, I., Wohlleben, K., and Mueller, H. R. Impurities in electrofused corundum, (11) 382*c*.
Patzias, T. See Ostberg, W.
Paukner, O. See Litomisky, J.
Paukste, J. See Tolutis, V.
Paul, F. B. See Cole, W. C.
Paul, P. J. See Dionne, G. F.
Paulik, I., and Somody, A. Manufacture of brown glass using Hungarian pyrolusite, (2) 50*c*.
Paulitsch, P. See Guyot, W.
Paulitsch, P., Schicht, R., and Mons, W. Rock structure of hematite, (3) 237*a*.
Paulson, G. P. Ultra thin-section improves studies, (5) 188*b*.
Paulson, W. M. See Carlson, O. N.
Paulus, M., and Guillaud, C. Manufacture of ferrite monocrystals, P (4) 114*b*.
Paulus, M., and Hamelin, A. Crystal growth of manganese ferrite, (7) 254*g*.
Paulusz, A. G. See Burrus, H. L.
Paus, P. E. See Langmyhr, F. J.
Pausch, J. B. See Margerum, D. W.
Pausch, J. B., and Margerum, D. W. Differential kinetic analysis of alkaline-earth ions using stopped-flow spectrophotometry, (8) 284*j*.
Pausewang, G., and Ruedorff, W. Alkali metal oxofluorometallates of transition metals—$A'_xMO_yF_{z-y}$ compounds [$x = 1,2,3$; M = titanium(IV), vanadium(IV and V), niobium(V), molybdenum(VI), tungsten(VI)], (10) 349*h*.
Pavlath, A. E. See Christe, K. O.
Pavlica, S. R., and Wisbon, B. E. Aluminosilicate refractory brick, P (5) 178*j*.
Pavlikov, V. N. See Tresvyatskii, S. G.
Pavlikov, V. N., and Tresvyatskii, S. G. System Nd_2O_3-Cr_2O_3, (7) 270*b*.
Pavlinskii, G. V. See Losev, N. F.
Pavlov, V. F. Pyroplastic properties of clays and their role in the formation of the structure of ceramic materials, (11) 372*e*.
Pavlov, V. S. See Postnikov, V. S.
Pavlova, A. K. See Berg, L. G.
Pavlovskii, V. K. See Evstrop'ev, K. K.
Pavlushkin, N. M., and Khodakovskaya, R. Ya. Sitalls—new polycrystalline materials based on glass, (2) 51*c*.
Pavlushkin, N. M., Kolesov, Yu. I., Zhitkevich, Z. V., and Petrov, S. V. Crystallization of slag glasses—fluorine-containing glasses, (2) 47*h*.
Pavlyuchenko, O. P. See Spivak, G. V.
Pawel, R. E. See Lundy, T. S.
Payne, D. A., and Sing, K. S. W. Standard data for the adsorption of N_2 at −196°C on nonporous Al_2O_3, (10) 360*j*.
Payne, R. Specific adsorption of chloride ions at the mercury aqueous solution interface, (9) 329*d*.
Peacock, R. D. Method of making semiconductor devices, P (7) 257*h*.
Peake, J. S., and Arens, R. P. Coating solid particles with refractory metals, P (8) 279*b*.
Pearce, M. L. See McCabe, N. R.
Pearce, M. L., and Basch, C. Oxidation kinetics of single crystal titanium nitride by optical measurements, (11) 386*a*.
Pearne, F. J., Pearne, F. S., and Robson, F. G. Wrapping and palletizing of cylindrical products [drain tile], P (7) 250*b*.
Pearne, F. S. See Pearne, F. J.
Pearne & Lacy Machine Co., Inc. Wrapping and palletizing of cylindrical products [drain tile], P (7) 250*b*.
Pearson, A. D., and Miller, C. E. Filamentary conduction in semiconducting glass diodes, (10) 337*g*.
Pearson, A. D., Peterson, G. E., and Porto, S. P. S. Nd and Yb doped borate laser glass, P (11) 372*b*.
Pearson, A. J. See Ullman, W. L.
Pearson, C. See Harrop, P. J.
Pearson, G. L. See Allen, J. W.
Pearson, M. A. See Pastor, R. C.
Pearton, D. C. G., Taylor, J. D., Faure, P. K., and Steele, T. W. Determination of vanadium in silicate materials by atomic absorption spectrophotometry, (7) 259*j*.
Pechenkovskaya, L. E., Dubovik, T. V., and Nazarchuk, T. N. Data on the oxidizability of boron nitride at high temperatures, (2) 54*j*.
Pechiney-Compagnie de Produits Chimiques et Electrometallurgiques. Process for treatment of aluminous ores for production of purified aluminum oxide, P (5) 191*b*.
Pechini, M. P. Method of preparing +2 valent metal yttrium and rare earth ferrites, P (7) 257*b*. Resistance element utilizing group III or VB metal, P (4) 116*h*.
Pechkovskii, V. V., and Sofronova, A. V. Thermal transformations of the iodides of cobalt and nickel, (7) 270*h*. Thermographic investigation of strontium iodide, (7) 270*b*.
Pecht, I. See Anbar, M.
Pechukas, P. See Berne, B. J.
Peck, H. Book of Rookwood Pottery, B (7) 271*c*.
Pecoraro, G. A. See Emhiser, D. E.
Pecoraro, R. P. See Castrucci, P. P.
Pecoraro, R. P., and Bilous, O. Single diffused surface transistor and method of making same, P (8) 283*g*.
Pector, H., and Tausheck, R. W. Glass transporting rack, P (5) 175*a*.
Pedersen, B. Deuteron and proton magnetic resonance study of partly deuterated crystals (I) potassium oxalate monohydrate, (8) 290*f*. Least squares analysis of NMR spectra of pair-powders, (8) 294*d*.
Pedersen, T. See Harada, Jimpei.
Peeler, C. E., Jr. Inhibiting thermal decomposition of alkali metal silicates, P (4) 124*c*.
Pegler, K. C. Modern setting machinery, (6) 214*d*.
Pehlke, R. D. See Blossey, R. G.; Daines, W. L.; Jones, F. G.
Pei, Yu K. Vacuum forming glass articles with vented modules, P (10) 340*b*.
Peiser, H. S. See Ito, Jun.
Peisl, H., Blazer, R., and Waidelich, W. Schottky and Frankel disorder in KCl with color centers, (2) 82*g*.
Peisson, A., Blomqvist, C. E., and Norden, H. New technique for measuring thickness and optical properties of thin films grown on rough surfaces, (4) 120*g*.
Pekarek, J. L. See Goodwin, R. J.
Pelletier, B. R. See Lumsden, D. N.
Pellissier, G. E. See Boggs, W. E.
Peloschek, H. P. See Perduijn, D. J.
Pemsler, J. P. Studies on the oxygen gradients in oxidizing metals (IV) kinetics of the oxidation of hafnium at high temperatures, (1) 38*b*; (V) oxidation of oxygen-saturated zirconium, (2) 83*a*. See Cox, B.
Penberthy, H. L. Furnace electrode assembly, P (2) 72*h*.
Pendleton, W. W. High-temperature magnet wire, P (8) 275*d*. See Ostrander, G. W.
Pendleton, W. W., and Ostrander, G. W. High-temperature magnet wire and apparatus and enamel composition for the insulation thereof, P (8) 275*d*.
Penez, A. See Delrieux, J.
Pennebaker, W. B. Method for depositing silicon nitride insulating films and electric devices incorporating such films, P (4) 114*b*.
Pennekamp, J. C. See Hoerster, H.
Pennsalt Chemicals Corp. Coating cementitious articles with hexavalent chromium-resinous dispersions, P (5) 170*f*. Method of preparing rhombohedral crystalline tungsten disulfide, P (1) 14*i*. Vapor coating employing degassing of coating metal, P (2) 67*a*.
Peppler, P. See Clausmeyer, H.
Peppler, R. B. See Kelly, T. M.
Pepworth, D. P. See Monk, H.
Perduijn, D. J., and Peloschek, H. P. Mn-Zn ferrites with very high permeabilities, (2) 63*g*.
Perelman, S. M., Prager, I. A., Tolmachev, A. F., Klebanov, D. L., and Gastev, J. A. Radioactive radiation counter tube with improved high temperature properties, P (8) 283*a*.
Perez y Jorba, M. See Collongues, R.
Perfilova, I. L. See Shchukarev, S. A.
Peri, J. B. Effect of fluoride on surface "acid" sites on γ-alumina and silica-alumina, (8) 291*e*.
Peri, J. B., and Hensley, A. L., Jr. Surface structure of silica gel, (8) 299*d*.
Perieres, R., and de Bard, Y. Process for treatment of aluminous ores for production of purified aluminum oxide, P (5) 191*b*.
Perkin-Elmer Corp. Monochromator system with selective diffraction grating system, P (4) 122*b*.
Perkins, C. W. Radiation effects in metal-insulator-semiconductor capacitors as determined from conductance measurements, (1) 17*a*.
Perkins, C. W., Aubuchon, K. G., and Dill, H. G. Radiation effects and electrical stability of metal-nitride-oxide-silicon structures, (6) 236*h*.
Perkins, E., Jr. See Robinson, M. W., Jr.
Perkins, G. E. See Dudzik, C. J.
Perkins, H. K. See Reid, A. F.
Perkins, R. A. See Houseman, J. E.
Perlman, S. S., and Silver, R. S. Ferroelectric insulated-gate field-effect device, P (9) 312*i*.
Perlstein, J. See Bouchard, G. H., Jr.
Perlstein, J. H., and Sienko, M. J. Single-crystal studies of electrical conductivity, Seebeck effect, and Hall voltage in sodium vanadium bronze and a crystal-field model of electron transport, (1) 17*e*.
Permaglass, Inc. Apparatus for heat-treating glass on a fluid support, P (10) 338*f*. Gas support bed apparatus for treating glass, P (10) 338*f*. Heat exchange apparatus for treating glass, P (10) 338*f*. Method and apparatus for conveying and curving glass sheet material on a gas support bed, P (1) 11*d*. Method and apparatus for conveying and heat-treating glass sheets over a gas support bed, P (1) 11*d*. Method for tempering glass utilizing an organic polymer gaseous suspension, P (5) 175*j*. Pivotal conveyor attachment for moving glass sheets over a hot gaseous support bed, P (1) 11*c*.
Perraudin, R., Perrin, C., and Seris, G. Method for the production of a hard-porosity lime-silica porous body, P (2) 59*g*.
Perrault, G., Semenov, E. I., Bikova, A. V., and Capitonova, T. A. Lemoynite, a new silicate hydrate of zirconium and sodium from St. Hilaire, Quebec, (9) 324*e*.
Perret, R. See Herinckx, C.
Perri, J. A., and Riseman, J. Objects provided with protective coverings, P (4) 115*c*.
Perrin, C. See Perraudin, R.
Perrine, R. J., and Mathews, F. R. Furnace heating control, P (9) 316*d*.
Perron, P. O. Oxygen redistribution in uranium dioxide fuels, (8) 296*a*.
Perrott, C. M., and Fletcher, N. H. Heat capacity of silver iodide (I) experiments on annealed samples, (4) 138*g*. Heat capacity of silver sulfide, (11) 385*c*.
Perrow, J. M., Smeltzer, W. W., and Embury, J. D. Role of structural defects in the growth of nickel oxide films, (5) 181*j*.
Perrow, J. M., Smeltzer, W. W., and Ham, R. K. Nature of short-circuit diffusion paths in nickel oxide films, (1) 33*h*.
Perry, C. H. See Geick, R.
Perry, C. H., Fertel, J. H., and McNelly, T. F. Temperature dependence of the Raman spectrum of $SrTiO_3$ and $KTaO_3$, (4) 159*c*.
Perry, G. S., and Alderton, J. R. Dielectric properties of titanate-alumina ceramics, (8) 281*e*.
Perry, P. D. See Dollimore, D.
Perry, W. M. Method and apparatus for conveying and for treating glass fibers, P (8) 277*f*.
Pershan, P. S. See Chang, R. K.
Pershing, J. A. Method and apparatus for handling fibrous materials, P (1) 11*e*.
Persiani, C., and Cosgrove, J. F. Analysis of thin films for silcon, oxygen, and aluminum by fast neutron activation, (8) 280*h*.
Persin, A., Markovic, B., and Kuntaric, A. Effect of laser radiation on the properties of dielectric multilayer laser mirrors, (8) 281*e*.
Persky, A., Greene, E. F., and Kuppermann, A. Formation of positive and negative ions on rhenium, oxygenated tungsten, hafnium, lanthanum hexaboride, and thoriated tungsten surfaces, (8) 292*i*.
Persson, E. See Engstrom, I.
Persson, G. Laboratory investigations on isostatic compacting, (4) 108*j*. Thin foils of tungsten carbide-cobalt hard metal, (9) 332*a*.
Perucchetti, A. Refractory lining for arc furnaces adapted to facilitate dismembering on completion of a campaign, P (11) 375*c*.
Perzak, T. F. See Olsson, R. G.
Peshev, P. Thermodynamic study of some reactions used for the preparation of borides of metals belonging to groups II-VI of the periodic table, (1) 13*a*.
Peshev, P., and Bliznakov, G. Borothermic preparation of titanium, zirconium, and hafnium diborides, (5) 192*g*.
Peshev, P., Bliznakov, G., and Toshev, A. Preparation and some physical properties of

gadolinium sesquisulfide and gadolinium monosulfide, (6) 236*h*.
Peshev, P., Leyarovska, L., and Blaznakov, G. Borothermic preparation of some vanadium, niobium, and tantalum borides, (8) 288*j*.
Pestrong, R. Shear strength of tidal marsh sediments, (8) 285*d*.
Petch, N. J. See Hardie, D.
Peter, E. See Grofcsik, J.
Peter, K. Blackening and structural changes on the surface of tubular glass lamps, (9) 305*b*. See Dick, E.
Peter, K., and Dick, E. Material dislocation during scratching of glass, (9) 306*d*.
Peter, P. W. Method of color coating bloated aggregate, P (8) 278*h*.
Petermann, A. See Emmenegger, F.
Petermoeller, H. Plant laboratory in the container glass industry, (10) 338*f*.
Peters, C. R. See Milberg, M. E.
Peters, F. G. Bond strength of metallic films deposited on polycrystalline garnets, (5) 180*f*.
Peters, H. See Gasparac, R. J.
Peters, L. Wax resist and glaze decoration, (7) 244*f*.
Petersee, B. Hard metals (II), (11) 379*d*.
Petersen, A. A., and Gibbs, D. W. Inertial type pneumatic separator, P (2) 68*b*.
Petersen, G. F. See Cathcart, J. V.
Peterson, C. L. Electric lamps and method of detecting leaks in such lamps, P (2) 52*h*. See Gungle, W. C.
Peterson, C. W. Photoelectric effects in the silver halides, (2) 81*g*.
Peterson, D. F. Semiconductor controlled switch circuit component, P (9) 313*i*.
Peterson, D. T., and Skaggs, R. L. Effect of carbon on the strength of thorium, (4) 132*h*.
Peterson, G. D., and Schaffer, H. J. Centrifugal forming mold, P (11) 371*b*.
Peterson, G. E. Optical $LiNbO_3$ modulator, P (8) 283*g*. See Pearson, A. D.
Peterson, G. E., and Bridenbaugh, P. M. NMR study of ferroelectric $LiNbO_3$ and $LiTaO_3$ (II), (5) 197*f*.
Peterson, J. D. Effect of fine grain, narrow band powders upon plasma coating characteristics, (1) 4*h*.
Peterson, J. L. Method and apparatus for wet sizing finely divided solid materials, P (7) 259*b*.
Peterson, R. L. See Matarrese, L. M.
Pethe, L. See Hauffe, K.
Pethica, B. A. See Taylor, J. A. G.
Petkus, J. J. Acid-resistant cement products, P (9) 304*f*.
Petree, M. C. See Skalski, J. F.
Petrescu, M. See Spinulescu-Carnaru, I.
Petrescu, V. See Cosneanu, C.
Petri, I. See Catana, V.
Petri, L. See Veiser, I.
Petri, L., Jitea, B., and Szabo, A. Sintering of kyanite concentrate in rotary-type furnaces, (10) 348*h*.
Petri, L., Philip, F., and Petroni, M. High quality acid resistant refractory products, (1) 12*d*.
Petrichenko, A. M. See Vatman, A. P.
Petrocelli, A. W., Marriott, J. A., Turco, J. F., and Capotosto, A. Process for reclaiming spent electrolytes used for electrolytically descaling steel, P (2) 46*b*.
Petroff, Y. See Balkanski, M.
Petroni, M. See Petri, L.
Petro-Tex Chemical Corp. Dehydrogenation process using cobalt or nickel ferrite, P (6) 229*f*.
Petrov, S. V. See Pavlushkin, N. M.
Petrov, V. I. See Spivak, G. V.
Petrov, Yu. F. See Bystrikov, A. S.; Tumanov, S. G.
Petrovic, P. Spectral analysis of bentonites in solutions, (6) 227*c*.
Petrovskii, G. T. Specific features of the structure and some chemical properties of beryllium fluoride in its glasses, (2) 51*d*. See Abdrashitova, E. I.
Petruk, W., Harris, D. C., and Stewart, J. M. Langisite, a new mineral, and the rare minerals cobalt pentlandite, siegenite, parkerite, and bravoite from the Langis Mine, Cobalt-Gowganda area, Ontario, (9) 316*e*.
Petrzilka, V. Neutron diffraction of piezoelectric resonators, (9) 325*d*. See Zelenka, J.
Petterson, R. B. (editor). Ceramic Art in America, B (10) 364*h*.
Pettierew, R. W. Surface treatment of glasses, P (11) 372*c*. See Medert, W. C.
Pettit, F. S. Diffusion coefficients, oxygen activities, and defect concentrations across a *p*-type oxide layer on a metal, (2) 75*f*.
Petz, J. I., Jr. Structure of aluminum hydroxide gel, (2) 83*i*.
Petzenhauser, I., and Jager, P. Method of quantitative determination of crystalline phases with X rays, (6) 226*e*.
Petzold, A., and Huebscher, M. Influence of iron oxides on some properties of glasses and enamels, (1) 7*j*.
Petzoldt, J. Metastable crystalline solid solutions with quartz structure in the oxide system Li_2O-MgO-ZnO-Al_2O_3-SiO_2, (9) 306*f*.
Petzow, G. See Ondracek, G.
Peyches, I. Composites, (2) 73*b*. Radiation induced changes in the spectral emission of transparent materials, (4) 152*b*.
Peyches, P. I. Polychrome striped screens for color television receiver comprising filaments of homogeneous glass, P (1) 18*j*.
Peyches, P. I., and Bourgeaux, M. Process and apparatus for supporting a sheet of glass on a gas and liquid support bed, P (7) 249*c*.
Peyser, L. F. X-ray collimating device wherein a plurality of adjustable overlapping leaves define a collimating cone, P (9) 316*b*.
Pfeifer, H. See Geschke, D.
Pfeifer, H. U. See Engstroen, I.
Pfeiffer, E. R., and Schooley, J. F. Effect of stress on the superconductive transition temperature of strontium titanate, (4) 133*b*.
Pfeiffer, H. G. See Newkirk, J. B.
Pfeil, R. See Fires, H.
Pfeiler, W. A., and Valentine, C. K. Hot-isostatic-pressing apparatus, P (5) 186*g*.
Pferdehirt, T. A. See Juhola, A. J.
Pfizer, Chas., & Co., Inc. Method for depositing pyrolytic graphite, P (8) 279*e*.
Pflan, W. G. Zone refining, (4) 118*i*.
Pfrunder, V. R., and Wickert, H. Determination of silica in glasses and similar silicates, (11) 380*b*. Effect of gypsum addition on the hydration of a cement clinker, (4) 91*i*. Rapid method for the determination of free lime in cement clinker, (2) 70*h*.
Pham, H. See Staronka, A.
Phelps, G. W., and Harris, D. L. Specific surface and dry strength by methylene blue adsorption, (1) 15*d*.
Philadelphia Quartz Co. Expanded silica insulation material, P (4) 106*f*. Expanded silicate particles, P (9) 317*d*.
Philbrook, W. O. See Spitzer, R. H.
Philco-Ford Corp. High voltage connection for cathode ray tube, P (6) 221*f*. Metalization of silicon semiconductor devices for making ohmic connections thereto, P (10) 345*e*. Susceptor for growing polycrystalline silicon on wafers of monocrystalline silicon, P (1) 19*e*.
Philip, F. See Petri, L.
Philip Carey Corp. Asbestos millboard conveyor rolls for high temperature use, P (10) 342*a*.
Philipp, H. R. See Brown, D. M.
Phillips, D. N. See Gallagher, K. J.
Phillips, J. F. See Burns, R. E.
Phillips, L. N. See Johnson, W.
Phillips, T. G., Townsend, R. L., Jr., and White, R. L. Piezomagnetism of CoF_2 and α-Fe_2O_3 from electron-paramagnetic-resonance pressure experiments, (4) 149*j*.
Phillips Petroleum Co. High temperature zirconia coated thermocouple, P (11) 381*f*.
Phosphate Development Corp., Ltd. Flotation of apatite, P (2) 74*a*.
Physical Sciences Corp. Ceramic material, P (10) 337*d*. Ceramic material and method, P (8) 282*c*.
Piacente, U., Malaspina, L., and Bardi, G. Thermodynamic study of the sublimation of selenium oxide, (9) 332*i*.
Piacente, V. See Gingerich, K. A.
Piatti, G. See Kellerer, H.
Picard, J. See Hantzer, P.
Picholr, R. See Duval, R.
Pick, G. G. See Snyder, A. W.
Pickard, J. E. See Scholes, A. B.
Pickel, H. High vacuum-tight ceramic-to-metal seals, (7) 255*a*.
Picken, R. N. Performance of walls built of wire-cut bricks with and without perforations (IV) photoelastic investigations of the stress distribution in perforated sections, (6) 214*b*.
Pickering, G. D., and Ford, W. F. Effect of composition and microstructure on the deformation in bend of periclase-silicate mixtures at high temperatures, (6) 215*b*.
Pickering, R. E. Prevention of alkali-aggregate reactions in concrete, P (6) 207*d*.
Pickert, P. E. See Lanewala, M. A.
Pickles, A. See Dieman, W. R.
Picus, G. S. See Van Atta, L. B.
Picus, G. S., DuBois, D. F., and Van Atta, L. B. Influence of ionized impurity scattering on Gunn effect and impact ionization in CdTe, (1) 31*a*.
Pie, Yu K. See Keefer, G. E.
Piegols, N. L., and Bon, C. K. Removal of halide ions from crude lithium aluminate, P (9) 317*f*.
Piekarczyk, W. See Niemyski, T.
Pierce, J. T., and Pritchard, J. P., Jr. Process for making thin film circuit devices, P (1) 19*c*.
Pierce, J. W., and Siegel, F. R. Quantification in clay mineral studies of sediments and sedimentary rocks, (8) 285*a*.
Pierce, W. E. Dishwasher coating costs—porcelain enamel vs plastisol, (1) 4*g*.
Pierce Specialized Equipment Co. Air conveyor and unloader for granular materials and unloading process therefor, P (10) 346*j*.
Pierini, G. See Camozzo, G.
Piermarini, G. J. See Weir, C. E.
Pierrot, A., and Lescroel, Y. High permeability ferromagnetic ferrite materials, P (5) 183*e*.
Pietsch, D. See de Bucs, E. S.
Pietsch, W., Hoffman, E., and Rumpf, H. Tensile strength of moist agglomerates, (7) 260*d*.
Pietsch, W. B. Tensile strength of granular materials, (10) 362*f*.
Piggott, M. R., and Hunton, A. E. Properties of irradiated silica-fiber-reinforced aluminum, (10) 341*i*.
Piggott, M. R., and Yokom, J. C. Weakening of silica fibers by heat treatment, (6) 211*j*.
Pighini, G. P. See Burmeister, R. A., Jr.
Pike, J. N. Model for solid-phase heat conduction in glass fiber pad insulation, (9) 306*h*.
Pilkey, O. H., and Blackwelder, B. W. Mineralogy of the sand size carbonate fraction of some Recent marine terrigenous and carbonate sediments, (1) 32*h*.
Pilkington Brothers, Ltd. Apparatus for manufacturing flat glass, P (6) 212*c*. Apparatus and method for manufacture of float glass with restricted lateral spread, P (6) 212*d*. Apparatus for molding of glass articles, P (4) 98*e*. Composite tweel with internal suspension system, P (8) 277*h*. Method and apparatus for electrical viscosity control of float glass, P (8) 277*g*. Method of and apparatus for the manufacture of flat glass on a molten metal bath, P (2) 53*i*; P (5) 175*a*. Method and apparatus for toughening sheets of glass, P (6) 213*a*. Method of bending sheet glass with gas pressure cushions, P (10) 339*j*. Method of coloring glass, P (7) 249*c*. Method of forming a glass sheet on a molten metal bath, P (5) 175*c*. Oxidation method of producing glass having an increased breaking strength, P (10) 339*h*. Tongs, P (10) 340*a*.
Pilling, D. J., and Dumesnil, M. E. Selective masking method of silicon during anodization, P (6) 223*b*.
Pilloton, R. L. See Bowman, R. A.
Pilpel, N. Cohesiveness of powders, (8) 284*h*. See Harwood, C. F.
Pils, S. Wear of porcelain decoration in industrial and domestic dishwashers, (1) 15*h*.
Piltz, G. Influence of production methods on frost resistance of bricks and roofing tiles, (4) 101*h*.
Pilyankevich, A. N. See Kurdyunov, A. V.
Pinch, H. See Harbeke, G.
Pineda, V. M. See Natera, M. G.
Pink, F. See Wang, P.
Pink, F. X., and Lyn, V. Nondestructive determination of phosphorus in phosphosilica films on silicon substrates, (4) 120*j*.
Pink, P., and Schlitter, W. Particle size classification method and apparatus, P (4) 125*e*.
Pinnell, J. E. See Parker, S. G.
Pionke, G. Tubular cutting tools, P (9) 308*d*.
Piotrowski, P. See Mields, A.
Piper, H. L. See Hausen, D. M.
Pipitz, E., Strohmeier, G., and Sedlatschek, K. Glassmelting electrodes for glassmelting furnaces, P (4) 123*a*. Shaped bodies with high temperature strength and corrosion resistance against molten metals, particularly molten iron and steels, P (1) 14*h*.
Pirlet, R. A. J. E. Measuring temperatures, P (1) 22*e*.
Pirling, R. Roman glass bowl from Krefeld-Gellep, (4) 90*g*.
Pirogov, Yu. A. See Svirskii, L. D.
Pirrello, A., and Sproles, J. D. Vibratory bowl, P (6) 213*h*.
Pirrung, P. F., and Schmidt, D. L. Ablative product and method for its manufacture, P (4) 105*j*.
Pirson, E. H. See Nitzsche, S.
Piryutko, M. M. See Boikova, A. I.
Pisano, A. M., and Barnard, J. K. Electric furnace having replaceable liner tube sections, P (5) 189*a*.
Pistorius, C. W. F. T. Melting parameters of some alkali halides, (4) 144*d*.
Pistorius, C. W. F. T., Rapoport, E., and Clark, J. B. Phase diagrams of H_2O and D_2O at high pressures, (6) 235*g*.
Pithon, M. See Asquiedge, M.; Guillou, M.
Pitirimov, B. Z. See Shchukarev, S. A.
Pitkjaan, E. Sealed-beam type electric lamp with noncircular lens component, P (4) 101*d*.
Pitsch, W. See Ryder, P. L.
Pitt, E. E. H., and Stanway, V. M. Spectrophotometric determination of iron with 2-pyridyl-2′-hydroxymethane sulfonic acid, (10) 347*h*.
Pitt, K. E. G. Nature of residual gases during evaporation of silicon oxide, (2) 80*h*. See Allam, D. S.
Pittman, G. E. See Biard, J. R.; Bonin, E. L.
Pittsburgh Corning Corp. Arcuately shaped cellular glass article and method of making the same, P (11) 370*j*. Method of making a shaped article from coated multicellular glass nodules, P (6) 213*d*. Process for making cellular materials, P (7) 249*c*.
Pityo, E. L. Back reflector for radiant energy glass-to-metal sealing means, P (11) 371*a*.
Piven, A. I. See Zaika, R. G.
Pivinskii, Yu. E., and Gorobets, F. T. Some features of slip casting fused quartz ceramics, (6) 216*g*.
Pivnichny, J. V. See Fink, D. W.
Pizzarello, F. A. See Collins, J. H.
Pizzini, S., and Morlotti, R. Thermodynamic and transport properties of stoichiometric and nonstoichiometric nickel oxide, (4) 161*f*.
Plakhina, A. M. See Kuz'ma, Yu. B.
Plamper, J. See Kahle, H. G.
Plank, C. J., and Rosinski, E. J. Conversion of clays to crystalline aluminosilicates and catalysts therefrom, P (6) 229*c*. Method

for preparing high-silica faujasite, P (11) 382*e*.
Plankenhorn, W. J. Direct-on cover coat enamel defects, (7) 245*i*. Evaluating adherence of direct-on cover coat porcelain enamels, (1) 4*i*.
Plas-Chem Corp. Low temperature cured ceramic coating composition, P (4) 114*a*.
Plaskett, T. S. See Title, R. S.
Plaskett, T. S., Blum, S. E., and Foster, L. M. Preparation and properties of large, solution grown GaP crystals, (4) 111*d*.
Plass, G. N. Temperature dependence of the Mie scattering and absorption cross sections for aluminum oxide, (1) 39*f*.
Platt, D. M. H. Response of a glass tank to variations in the batch composition, (1) 8*f*.
Platts, D. R. See Greene, C. H.
Platz, P. Shift of a mercury line by a high power laser pulse, (11) 387*c*.
Plaul, T. See Krause, E.
Pleass, C. M. See Maurer, D. W.
Pledger, T. R. See Durbin, H. A.
Plessey Co., Ltd. Silicon nitride, P (10) 343*b*.
Plieninger, T. See Salzmann, E.
Pliskin, W. A. Evaluation of thin film insulators, (2) 62*a*. Fused glass penetration into thermally grown silicon dioxide films, (1) 17*b*. See Valletta, R. M.
Ploc, R. A. Transmission electron microscopy of thin (<2000 Å) thermally formed zirconia films, (9) 332*d*.
Plocek, L. See Schwarzbach, J.
Ploetscher, G. See Bauer, H.
Ploog, K. See Amberger, E.
Plotnikov, M. V. See Fedorovskii, Ya. A.
Plumat, E. Apparatus for supporting and conveying glass sheets on a gas support bed, P (5) 174*h*. Glassmelting furnace with vacuum feed means, P (6) 212*e*.
Plumat, E., Eloy, P., Dutholt, J., and Barbier, J. C. New trends in glass furnace construction, (9) 306*b*.
Plumat, E., and Jaupain, M. Refractory composition and process for producing same, P (5) 179*e*
Plummer, H. See Jennings, B. R.
Plummer, N. See Huh, J. M.
Pluschkell, W., and Engell, H. J. Ionic and electronic conductivity in magnesium orthosilicate, (4) 141*e*.
Plyushch, G. V. Determination of copper and cobalt in nickel ferrites by atomic absorption analysis, (6) 225*g*.
Plyushchev, V. E. See Grizik, A. A.
Plyushchev, V. E., and Samusева, R. G. Solid solutions of alkali halides, (5) 199*g*.
Poad, W. J. Sintered glass article and method of making, P (4) 101*a*.
Pober, R. L. See Clougherty, E. V.
Pobst, D. F., Jr., and Rowlett, B. J. Apparatus for forming aggregates of powdered materials, P (2) 67*f*.
Poch, W. High pressure densification of oxides, (11) 373*e*. Properties and structure of NaF-B_2O_3 glasses, (9) 306*i*.
Pochert, R. See Haase, L.
Pocius, Z. See Viscakas, J.
Podchernyaeva, I. A. See Samsonov, G. V.
Poddar, S. N., and Biswas, D. K. Compounds of Schiff's bases with uranium(IV), zirconium(IV), and thorium(IV), (4) 129*j*.
Podmore, D. See Meadows, F. W.
Podoksik, L. See Pastor, R. C.
Podolsky, G. See Conroy, L. E.
Podvigalkina, G. Ya. See Abukov, A. A.
Poehler, T. O. See Apel, J. R.
Poels, J. P. J. See Esveldt, C. J.
Poeschmann, H., and Schneider, H. Chemical de-enameling of gray cast iron, (6) 207*f*.
Pogorelov, N. M. See Bobrov, B. S.
Pogrebnov, A. N. See Fedin, A. A.
Poh, K. J., and Anderson, J. C. Structure and growth of epitaxial PbSe films, (8) 281*h*.
Pohl, K. D. See Schwiete, H. E.
Pointon, A. J., and Robertson, J. M. Effect of tetrahedral site Ni^{2+} ions in nickel ferrite, (2) 76*f*.
Pointon, A. J., and Saull, R. C. Solid state reactions in lithium ferrite, (6) 220*f*.
Poirier, A. R., and Newkirk, T. F. Thin film piezoelectric oscillator, P (5) 185*f*.
Poko, Z., Fodor, M., and Szabo, E. Formation, thermal decomposition, and structure of the system UO_3-H_2O (III) thermal decomposition of β-$UO_3 \cdot 2H_2O$ produced from γ-UO_3, (5) 194*j*. Properties of uranium trioxide dihydrate, (5) 199*f*.
Pokorny, O. See Bezouska, V.
Pokrovskii, B. I. See Komissarova, L. N.
Polasek, K. H., Rudestedt, S. J. E., and Umblia, E. J. Procedure for producing a ferrite, especially adequate for use in pulse relay cores, P (5) 184*j*.
Polezhaev, Yu. M. Selection of mineralizers for solid-state reactions, (4) 154*c*.
Polezhaeva, L. I. See Kravchenko-Berezhnoi, R. A.
Polito, W. J. See Rozgonyi, G. A.
Polito, W. J., and Rozgonyi, G. A. Cathodic sputtering of films of stoichiometric zinc oxide, P (5) 192*i*.
Pollard, E. R. See Reed, T. B.
Pollard, L. J. See Angell, C. A.
Pollard, L. W. Refractory coating compositions, P (6) 218*c*.
Pollard, W. K. See McKinney, C. N.
Polledri, J. See Boulet, F.
Pollock, L. J. Fabrication of structures for semiconductor integrated circuits, P (5) 182*j*.
Pollock, L. J., and Shaunfield, W. N. Semiconductor structures for integrated circuitry and method of making the same, P (7) 258*f*.
Pol'skii, L. L. Improving the hydraulic classification of slurry, (1) 2*j*.
Poltavtsev, N. S. See Nichiporenko, E. P.
Poltavtsev, Yu. G. See Goncharov, V. P.
Poltorak, E. J. Method of blending ceramic and carrier fibers, P (4) 106*g*.
Poluboyarinov, D. N. See Akopov, F. A.; Bakunov, V. S.
Polukhin, Yu. M. See Berezhnoi, A. I.
Polyachenok, O. G. Determination of the enthalpies of formation of the rare-earth fluorides, (9) 319*e*.
Polyakov, V. E. See Tarasevich, Yu. I.
Polyakov, V. E., Tarasevich, Yu. I., and Alekseev, O. L. Preparation of cation-substituted types of clay minerals, (7) 262*h*.
Polysius G.m.b.H. Apparatus for thermal treatment of minerals, P (4) 122*g*. Device for the periodic delivery of preheated material, P (7) 261*h*. Method of and apparatus for making porous clay, P (2) 54*e*.
Pomerantz, D. I., Wallis, G., and Dorsey, J. J. Bonding electrically conductive metals to insulators, P (4) 112*d*.
Poncelet, G. See Fripiat, J. J.
Poncelet, J., Bochirol, L., Blum, P., and Moreau, C. Composite structure electrode and process for manufacturing such electrode, P (4) 106*c*.
Pong, W. Photoemission from Al-Al_2O_3 films in the vacuum ultraviolet region, (11) 376*c*.
Ponomarev, I. F., Grach'yan, A. N., and Zubekhin, A. P. Trends in the influence of mineralizers on the formation of white portland cement clinker, (4) 92*a*.
Ponomarev, V. D. See Ni, L. P.
Pons, C. See Fasano, G.
Pontarelli, D. A. See Li, P. C.
Poole, A. J. Burner throat, P (10) 342*b*.
Poole, D. A. Stencil screen, P (5) 176*b*.
Poole, D. M. See Hodkin, E. N.
Poole, R. R. Infrared quartz heater, P (11) 377*a*.
Pope, M. I. See Judd, M. D.
Popescu, C. Automation of rotary clinker ovens. Automatic control system for combustion air flow in long ovens operating on the wet process principle, (10) 336*a*.
Popko, V. N. Hardening of slag portland cement during steaming, (1) 2*g*.
Poplavko, Yu. M. See Dimarova, E. N.
Poplawsky, R. P. See Weaver, E. A.
Poplawsky, R. P., and Wright, M. R. Nickel iron ferrite crystals using arc image furnace techniques, (4) 146*b*.
Popov, N. N., Appen, A. A., and Antonova, E. A. Protective action of silicate coatings of various compositions on Armco iron, B (5) 204*h*.
Popova, A. A. Behavior of solid solutions of rare earth oxides in binary systems during crystallization by the verneuil method, (9) 318*g*.
Popova, M. A., Darvoid, T. I., and Gurevich, M. A. Change in the lattice period and microhardness of homogeneous solid solutions in the system TlBr-TlCl, (7) 264*e*.
Popova, S. V. See Bendeliani, N. A.
Popp, W. See Gorgenyi, T.
Popper, P. (editor). Special Ceramics (Vol. 4) Proceedings of the Fourth Symposium on Special Ceramics Held by the British Ceramic Research Association at Stoke-on-Trent, July 1967. B (10) 366*g*. See Binns, D. B.; George, W.; Moulson, A. J.
Popper, P., and Riley, F. L. Texture of pyrolytic silicon carbide, (4) 160*a*.
Porath, H. Stress-induced magnetic anisotropy in natural single crystals of hematite, (2) 83*h*.
Port, E. B. See Howard, C. J.
Portal, G. See Carpentier, S.
Portal, M. L. Apparatus for the purification of an enclosed inert atmosphere, P (1) 20*c*.
Portco Corp. Press for making blocks from loose fiber material, P (2) 68*c*.
Porter, B., Meaker, R. E., and Bremner, P. R. Phase diagram for the KF-YF_3 system, (8) 296*d*.
Porter, C. Abrasives widen scope of investment casting, (5) 169*f*.
Porter, D. D. See Arnold, A. J.
Porter, R. F. See Brooks, W. V. F.; Grimm, F. A.; Gupta, S. K.
Portier, J. See de Pape, R.
Portier, J., Tressaud, A., de Pape, R., and Hagenmuller, P. Structural classification of compounds of fluorine with iron and monovalent cations and the relation to their magnetic properties, (6) 237*j*.
Portier, J., Tressaud, A., Dupin, J. L., and de Pape, R. Structures and magnetic properties of compounds of the formula, $MFeF_3$ (M=Na,K,Rb,Cs,NH_4,Tl), (10) 361*i*.
Porto, S. P. S. See DiDomenico, M., Jr.; Leitte, R. C. C.; Pearson, A. D.
Porto, S. P. S., Giordmaine, J. A., and Damen, T. C. Depolarization of Raman scattering in calcite, (1) 27*b*.
Porto, S. P. S., and Krishnan, R. S. Raman effect of corundum, (4) 152*c*.
Posner, A. S. See Eanes, E. D.; Fleisch, H.
Pospisil, Z. Errors of platinum thermocouples in continuous operation, (10) 348*b*.
Pospisil, Z., and Frydl, J. Study of the kinetics of $BaTiO_3$ sintering, (7) 255*d*.
Post, B. See Sklar, N.
Postmus, C., and Ferraro, J. R. Infrared studies of the rare-earth sulfates (4000–80 cm^{-1}), (5) 195*d*.
Postnikov, V. S., Pavlov, V. S., Gridnev, S. A., Turkov, S. K., Darinskii, B. M., and Glozman, I. A. Internal friction in lead zirconate titanate ferroelectric ceramics, (2) 63*c*.
Postnova, N. I. Use of active soldering for making vacuum-tight aluminate glass-to-metal seals, (4) 97*j*.
Potanin, D. N. See Mazurov, D. J.
Potebnya, Yu. M., Pshegorlinskii, A. A., and Rikhter, R. G. Automatic temperature control for laboratory furnaces, (2) 68*j*.
Potter, A. E. Sulfur oxide capacity of limestones, (10) 336*b*. See Harrington, R. E.
Potter, A. E., Harrington, R. E., and Spaite, P. W. Limestone-dolomite processes for flue gas desulfurization, (1) 20*c*.
Potter, J. F. See MacChesney, J. B.
Potter, R. M. See Blank, J. M.
Potter, R. M., and Cusano, D. A. Luminescence efficiency of silicon carbide doped with boron and nitrogen, (4) 110*d*.
Potter, T. J., and Elyard, C. A. Columnar grain growth in uranium dioxide, (4) 128*j*.
Potts, H. R., and Speicher, C. A. Method of making semiconductors by laser induced diffusion, P (5) 183*h*.
Poulignier, J. See Hivert, A.
Poulsen, E. See Bredsdorff, P.
Poulter, H. C. See Bauhaus, R. H.
Pouzet, C. See Aleonard, S.
Povarennykh, A. S. See Boldyrev, A. I.
Powell, B. E. See Steele, B. C. H.
Powell, B. R., Jr. See Manning, W. R.
Powell, D. E. See Damm, D. A.
Powell, D. E., and Spear, B. W. Cathode-ray and other vacuumized tubes resistant to violent devacuation, P (2) 52*c*.
Powell, F. X. See Kenney, J. T.
Powell, J. E. Methods and apparatus for treating glass sheets, P (6) 213*g*.
Powell, J. L. Isotopic composition of strontium in carbonatites and kimberlites, B (4) 167*g*.
Powell, R. C. See Adamski, J. A.
Powell, W. A. Cemented chromium carbide containing small additions of phosphorus, P (8) 279*a*.
Power, P. D. See Hills, G. J.
Power Jets (Research & Development), Ltd. Method of [diffusion] coating metals with a silicide layer and an outer layer of aluminum silicate, P (8) 275*e*.
Powers, T. C. Some observations on the interpretation of creep data, (1) 37*b*.
Powers, W. H. See Hubble, D. H.; Yount, J. G., Jr.
Pozela, J. See Kalvenas, S.
PPG Industries, Inc. Alkyd resin-aminoplast resin coating composition for glass, P (5) 174*f*. Apparatus for measuring and controlling film thickness, P (10) 346*f*. Apparatus for severing glass sheets, P (1) 10*i*. Apparatus for shaping and tempering glass sheets with means to transport the sheets therebetween, P (10) 338*g*. Automatically sizing and severing glass sheets, P (5) 174*i*. Colored transparent durable titania films on glass, P (5) 174*a*. Detecting ribbon formation abnormalities in drawing glass sheets, P (4) 98*a*. Float glass takeout roll, P (8) 277*j*. Forming glass fiber with combination resin coating, P (7) 248*g*. Glass fiber cord construction, P (8) 277*b*. Glass forming machine having molds with movable bottom sections, P (4) 99*a*. High strength fiber glass, P (11) 371*a*. Load-bearing member for curved ceramic segments subjected to high compressive loads, P (9) 307*h*. Manufacture of float glass of a thickness greater than equilibrium thickness, P (6) 212*i*. Manufacture of float glass using enclosed bath zones, P (11) 371*c*. Material distributing device in a vertical kiln, P (4) 123*c*. Metal-tungsten bronze films, P (10) 337*a*. Method and apparatus for [downward] bending glass sheets, P (2) 53*f*. Method and apparatus for forming a compound bend in a glass sheet on a gas support bed, P (2) 53*g*. Method and apparatus for initially restricting the divergent flow of float glass, P (6) 213*a*. Method and apparatus for the manufacture of float glass on a bilevel support bath, P (11) 371*e*. Method of and apparatus for press bending vertically suspended glass sheets, P (9) 307*i*. Method and apparatus for severing glass sheets, P (10) 339*i*. Method and apparatus for shaping glass sheets, P (4) 99*h*. Method of inspecting all-glass multiple glazed units [for dew point], P (4) 100*b*. Method for making radiation induced crystallized glass, P (10) 339*c*. Method for producing [laminated] window panels, P (4) 100*c*. Method for producing window panels, P (4) 100*e*. Method for treating raw pigmentary titanium dioxide, P (8) 288*b*. Mold cover for bending glass sheets, P (5) 176*b*. Novel reaction product and use thereof as a glass fiber size, P (11) 372*b*. Packaging device for sheet material, P (4) 100*f*. Process for classifying pigmentary metal oxide, P (2) 74*b*. Process for manufacture of glass utilizing gas pressure for glass sizing, P (6) 213*b*. Process for melting glassmaking ingredients on a

molten metal bath, P (9) 308*b*. Process of preparing barium carbonate by carbonation of aqueous barium sulfide, P (5) 191*g*. Process for preparing pigmentary metal oxide, P (8) 288*e*. Process for preparing pigmentary titanium dioxide, P (6) 230*a,b*. Process for recovering pigmentary titanium dioxide from nonpigmentary waste titanium dioxide, P (11) 382*i*. Process for recovering Zr values from ores, P (4) 125*d*. Producing bent laminated windshields, P (10) 340*a*. Providing low viscosities for aged siliceous slurries, P (1) 24*e*. Pyrometer and control of manufacturing processes therewith, P (5) 188*g*. Radiation sensitive apparatus for severing [moving] glass [sheet] along a score mark, P (4) 101*c*. Scraped removal of metal oxide deposit by a ceramic edge, P (5) 191*e*. Strengthening glass by multiple alkali ion exchange, P (6) 213*f*. Stress inspection apparatus with sine wave modulation of the photomultiplier tube output, P (7) 261*b*. Tinted mirror, P (10) 340*c*. Transferring sheets, P (4) 101*d*. Treatment of glass surfaces, P (4) 101*d*.

Prabhakaram, P. Exchangeable cations and the high-temperature reactions of kaolinite, (4) 135*a*. Some aspects of cation exchange of kaolinite, (10) 360*a*.

Pracka, I. See Niemyski, T.

Prado Laboratories, Inc. Device for measurement of pore size and pore volume, P (7) 260*g*.

Prager, I. A. See Perelman, S. M.

Pralow, W. E. L. See Wagner, E.

Pranatis, A. L. Coaxing effect during the dynamic fatigue of glass, (8) 276*c*.

Pranauskene, G. B. See Meshkuotis, Yu. A.

Prasad, E. A. Black sand concentrates, (1) 23*c*.

Prasad, R. See Kulkarni, A. K.

Prasad, S., and Garg, V. N. Thermal decomposition of ammonium molybdoselenite and its iron salt, (4) 160*i*.

Prasad, S. N. See Ram, A.

Prasad, S. N., and Srivastava, K. P. Origin of color in copper-red glasses (III) low temperature viscosity, (10) 338*d*.

Pratt, P. L. Strength and deformation of ionic materials, B (6) 241*d*. See Evans, A. G.; Kear, B. H.; Kirk, D. L.; Newey, C. W. A.; Quin, J.; Stoebe, T. G.; Thompson, D. S.

Pratt, W. R. Diamond abrasive saw blade, P (8) 273*f*.

Preas, D. L. See Gazza, G. E.

Preaux, L., and Bred, L. Ornamental glass slab containing flat glass strips, P (5) 176*c*.

Precht, W. Thermoelectric device comprising an oxide base thermoelectric element, P (11) 379*c*.

Precision Metalsmiths, Inc. Ceramic shell molds and methods of production, P (4) 106*b*.

Preece, R. E. Precision metal casting molds comprising alumina coated silica and a refractory, P (8) 279*i*.

Pregl, O., and Ghobadian, A. Effect of the ion sheath on the mechanical properties of clay soils, (5) 190*c*.

Preller, G. S., and Schoeman, B. J. K. Flotation of apatite, P (2) 74*a*.

Prendergast, J. R. Apparatus for centrifugally casting glass articles, P (8) 277*e*.

Prener, J. S. Growth and crystallographic properties of calcium fluor- and chlorapatite crystals, (4) 137*g*. See Aven, M.; Kingsley, J. D.

Presiman, L. Pyrometer and control of manufacturing processes therewith, P (5) 188*g*.

Pressley, G. A., Jr. See Steck, S. J.

Pressley, H. See Buist, D. S.

Preston, A. See Dickinson, G. A.

Preston, F. W. See Glathart, J. L.

Preuss, L. E. See Toothacker, W. S.

Prewitt, C. T. See Bither, T. A.; Shannon, R. D.

Prewitt, C. T., and Sleight, A. W. Garnet-like structures of high-pressure cadmium germanate and calcium germanate, (5) 194*b*.

Pribik, R. See Strnad, P.

Price, R. J. Structure and properties of pyrolytic silicon carbide, (10) 342*i*.

Price, W. J. See Roos, J. T. H.

Price, W. L. Method for making semiconductor structure with layers of preselected resistivity and conductivity type, P (7) 257*i*.

Prilepskii, V. I. See Ezerskii, M. L.

Primak, W., and Kampwirth, R. Impurity effect in the ionization dilatation of vitreous silica, (9) 306*a*. Ionization expansion of pile-exposed vitreous silica, (11) 385*j*. Ionization expansion of pressure-compacted vitreous silica, (9) 306*b*. Radiation compaction of vitreous silica, (9) 307*a*.

Primak, W., and Luthra, J. Radiation-induced expansion and increase in refractive index of magnesium oxide—evidence of the *F* center, (4) 152*b*.

Prins, J. A. Amorphous substances, especially sulfur and other elements, B (4) 168*j*.

Prinz, G. A. Optical absorption spectra of coupled Nd^{3+} ions in $NdCl_3$ and $NdBr_3$, (4) 147*g*.

Prior, S. See Lambert, K. T.

Prismo Safety Corp. Reflective markers and reflective elements therefor, P (4) 101*c*.

Pritchard, C. See Faust, J. W., Jr.

Pritchard, J. P., Jr. See Pierce, J. T.

Pritchett, R. L. See Arnold, S. R.

Probst, R. O. Electrostatic spray device, P (5) 186*f*.

Probst, R. O., Thatcher, C. R., and Zupan, N. M. Electrostatic coating apparatus, P (7) 246*f*.

Prochazka, R. Modern method of air pollution control and evaluation of industrial hygiene in the ceramic industry, (9) 333*c*.

Proctor, B. A. See Mallinder, F. P.

Proctor, E. M. See Beard, D. W.

Proctor, W. E., Jr. Laminated glass electrode diaphragm, P (11) 371*b*.

Prod'homme, M. Bacterial attack on a glass containing a radioactive tracer, (2) 46*i*. Results concerning the microhardness of glasses, (1) 8*g*.

Produits Chimiques Pechiney-Saint-Gobain. Alumina agglomerates and method for producing same, P (4) 124*g*. Preparation of hydrargillite, P (4) 125*g*. Process for producing water dispersible hydrargillite, P (4) 125*c*.

Proffitt, J. R., Jr. Offset plate decorating methods and apparatus, P (2) 53*j*.

Progelhof, R. C., and Throne, J. L. Effect of surface porosity on emittance of an opaque substance, (6) 232*h*.

Prokhorov, A. M. See Kulevskii, L. A.

Prokof'ev, E. N. Determination of mechanical properties of glass foam, (2) 48*d*.

Prokopowicz, T. I. Donor-acceptor ion-modified barium titanate capacitor and process, P (5) 182*g*.

Prokopyuk, N. F. See Broude, V. L.

Pron, G. F. See Smirnova, R. I.

Pronin, V. A. See Artyukhin, P. I.

Prosser, V. See Hoeschl, P.

Prost, L. Insulating refractories, (1) 12*j*.

Protas, J. See Lepicard, G.

Protex Corp., Ltd. Elastic insulating bodies of inorganic fiber material [asbestos] and method of producing such bodies, P (11) 374*h*.

Provance, J. D., Lewis, A., and Kelley, L. W. Glass fiber compositions, P (2) 52*h*.

Provisor, H. Filament wire for use in the cathode of a thermionic valve, P (4) 113*d*.

Provost, G. See Bentz, G.; Lecrivain, L.

Pruden, G. See King, H. G. C.

Pruden, L. H. See Korda, E. J.

Pruett, G. R. *Pn* photocell epitaxially deposited on transparent substrate and method for making same, P (7) 257*g*.

Pruslin, G. Sh. Measurement of wear of diamond grinding wheel in processing glass and sitall shapes, (1) 7*f*. See Brodskii, Yu. A.

Prutton, M. See Gallon, T. E.

Pryde, J. A. See Griffiths, R.

Pshegorlinskii, A. A. See Potebnya, Yu. M.

Ptushkina, M. N. See Lebedeva, L. I.

Pueschner, H. A. Apparatus for heating material by means of microwave device, P (8) 287*d*.

Pugachev, G. S. See Vitman, F. F.

Pugachev, N. S. See Matyushenko, N. N.

Pulham, R. J. See Addison, C. C.

Pulliam, G. R. Magnetic materials, P (1) 18*j*. Spinel ferrite epitaxial composite, P (5) 185*c*. See Collins, J. H.

Pultz, W. W. Temperature and oxygen pressure dependence of silicon carbide oxidation, (4) 159*h*.

Pulvari, C. F. Ohmic contact to a substrate of insulating material having a doped semiconductive oxide providing a stepped energy gap, P (8) 283*g*.

Pulverizing Machinery Division of Slick Industrial Co. Fine granulator, P (7) 259*a*.

Pummery, F. C. W. See Cuthbert, J.

Purdie, N., and Vincent, C. A. Ultrasonic absorption in the lanthanide sulfates, (8) 300*c*.

Purton, M. J. See Coldrey, J. M.

Purviance, E. See Purviance, L.

Purviance, L., Purviance, E., and Schneider, N. F. Zanesville Art Pottery in Color, B (4) 168*j*.

Pustell, R. A. See Haselton, T. P.

Pustil'nik, A. I., Denisova, N. D., Nekhamkin, L. G., and Nisel'son, L. A. Some properties of $BiCl_3$ and $BiBr_3$ and fusibility in their systems, (9) 329*b*.

Putner, T. I. See English, J.

Puttbach, R. C. See Monchamp, R. R.

Putzig, M. Method and apparatus for production of mineral wool, P (7) 252*c*.

Pyrotel Corp. Infrared quartz heater, P (11) 377*a*.

Pytel, R. N. See Couch, P.

Qaiser, M. A., Ali, M. K., and Khan, A. H. Mineralogy of some asbestos from northwest Pakistan, (6) 229*d*.

Quaas, J. F. Method [flame spray] for producing carbide containing materials, P (10) 337*b*.

Quackenbush, C. L. W. See Frechette, V. D.

Quaker Oats Co. Alkaline refractory mixtures containing formaldehyde-furylethyleneal-dehyde resins and gunning therewith, P (2) 58*j*.

Quality Components, Inc. Method of manufacturing cylindrical ceramic capacitors, P (7) 257*j*.

Quan, J. T. See Adams, C. E.

Quan, J. T., and Adams, C. E. Infrared spectra of rubidium borates of varying composition, (4) 140*h*.

Quattropani, N. P. See Nelson, P. A.

Quebec Iron & Titanium Corp. Process for producing a product high in titanium dioxide content, P (6) 230*e*.

Queen, W. D. Apparatus for holding silicon slices, P (10) 344*b*.

Quenett, R. See Jacobi, R.

Quesada, A. F. See Hull, G. F.

Quetsch, J. G. See Saia, F. J.

Quickfit and Quartz, Ltd. Method of manufacturing an article of vitreous material and apparatus therefor, P (4) 100*b*.

Quigley, S. See Marcus, R. B.

Quilliam, R. M. P. See Dickens, P. G.

Quin, J., Redfern, B. A. W., and Pratt, P. L. Study of the dispersion of divalent cations in NaCl, (8) 298*h*.

Quinn, C. A. See Rieger, C. J.

Quinn, C. M. See Cox, J. T.

Quinn, R. See O'Shea, C. J.

Quirk, J. P. See Theng, B. K. G.

Quon, S. H., and Heinrich, E. W. Abundance and significance of some minor elements in carbonatite calcites and dolomites, B (4) 167*g*.

Qureshi, A. A. See Bhatty, M. I.

Qureshi, M. H., and Brett, N. H. Phase equilibria in ternary systems containing zirconia and silica (I) system CaO-ZrO_2-SiO_2, (4) 149*g*; (II) system Al_2O_3-ZrO_2-SiO_2, (6) 235*j*.

Raal, F. A. Study of some gold mine diamonds, (8) 287*b*.

Raase, P., and Kern, H. Synthesis of albites at temperatures in the range 250°–700°C, (9) 331*h*.

Rabatin, J. G., Gillooly, G. R., and Hunter, J. W. Stoichiometry of luminescent apatites, (4) 156*b*.

Rabenau, A. See Eckerlin, P.

Rabideau, S. W., Finch, E. D., Arnold, G. P., and Bowman, A. L. Neutron diffraction study of ice polymorphs (I) ice IX, (8) 295*c*.

Rabinovich, E. M. Behavior of fluorine in silicate glasses, (2) 46*j*.

Rabinowicz, E. Polishing, (4) 117*j*.

Rabo, J. A. See Mueller, K. R.

Raccah, P. M. See Longo, J. M.

Raccah, P. M., Longo, J. M., and Eick, H. A. Crystal structure of neodymium monotelluro-oxide—NdO_2Te, (11) 383*c*.

Radcliffe, D., and Berry, L. G. Safflorite-loellingite solid solution series, (10) 359*i*.

Radczewski, O. E. Ceramic Raw Materials—Minerals and Occurrence, B (8) 302*c*. Fine particles (dusts) in nature and technology, their determination as impurities, and the detection of fluorine compounds in the air, (6) 226*g*.

Rade, D. See Scholder, R.

Rademacher, G. F. High temperature-pressure metal-to-glass seal constructions, P (6) 212*g*.

Rademakers, F. M. A. See Daniels, H. P. C.

Radenkova-Yaneva, M. See Marinov, M.

Radermacher, G. See Gundlach, H.

Radford, C. Hydrometer method of particle size analysis, (1) 21*b*.

Radford, K. C., and Newey, C. W. A. Plastic deformation in magnesium aluminate spinel, (8) 296*i*.

Radford, W. E. See Trott, W. J.

Radio Corp. of America. See RCA Corp.

Radmacher, H. W., and DeSwardt, M. C. Spectrometric analysis of powdered samples using a dc arc fusion technique, (4) 121*i*.

Rado, T. A. See Schumacher, J. C.

Radoev, B. See Scheludko, A.

Radomysel'skii, I. D. See Beloivan, A. F.

Radosevich, L. G., and Williams, W. S. Low-temperature thermal conductivity of uranium nitride, (11) 385*e*.

Radovanovic, S. See Maricic, A.

Radtke, A. W. See Leistner, C. J.

Rady, G., Sajo, I., and Kaiser, E. Thermometric analysis of sintered nickel oxide (I) determination of iron content, (2) 71*e*; (II) determination of nickel and cobalt content, (2) 71*f*.

Raentsch, K. Lightweight optical mirror for astronomical equipment, P (10) 339*h*.

Raevsky, G. V. [Pneumatic] supporting device for rotary multiple-support kilns, P (7) 261*f*.

Ragan, R. C. Method of making a precision electric fuse, P (1) 18*c*.

Ragle, J. L. See Caron, A. P.; Huettner, D. J.

Ragone, D. V. See Craig, J. A.

Ragone, S. E., Datta, R. K., Roy, D. M., and Tuttle, O. F. System potassium carbonate-magnesium carbonate, (4) 159*e*.

Rahn, H. W. Process for classifying pigmentary metal oxide, P (2) 74*b*.

Rahrig, D. D., and Ferguson, C. W. Edge grinding machine [plate glass], P (9) 307*c*.

Rai, K. N., and Krishna, P. Distribution of stacking faults in zinc sulfide crystals grown from the vapor, (11) 383*j*.

Raicevic, D. Process for producing a product high in titanium dioxide content, P (6) 230*e*.

Rains, T. C. See Menis, O.

Rairden, J. R. Thin films of niobium nitride and tantalum nitride deposited by reactive evaporation, (1) 17*g*.

Rairden, J. R., III, and Furey, J. T. High purity niobium films formed by glow discharge cathode sputtering, P (6) 221*f*.

Raiskin, E. K. See Sysoev, L. A.

Raithel, K. Method of inserting manganese into semiconductors serving to produce electronic semiconductor structural components, P (9) 312*i*. See Bauerlein, R.

Raithel, K., Reuschel, K., and Keller, W.

Semiconductor structural component, P (11) 378*g*.

Rajac, T. J. See Clark, K.

Rajagopalan, K. S. See Rangaswamy, N. S.

Rakhimbaev, Sh. M. See Bash, S. M.

Rakhmukov, B. Kh. See Bering, B. P.

Raleigh, C. B. Plastic deformation of upper mantle silicate materials, B (6) 241*d*.

Raleigh, D. O. Transport processes in the thermal oxidation of silicon, (1) 40*a*.

Ralkova, J., and Seidl, J. Diffusion of strontium in irradiated basalt, (7) 265*c*.

Rall, W. Metal vaporization crucible with upstanding walls for confining and condensing vapor, P (4) 106*e*.

Ralph, J. E., and Townsend, M. G. Near-infrared fluorescence and absorption spectra of Co^{2+} and Ni^{2+} in MgO, (2) 80*h*.

Ram, A., Prasad, S. N., and Srivastava, K. P. New conception of the origin of color in copper ruby glass, (9) 306*a*.

Ram, Inc. Method for making ware producing mold members, P (4) 109*b*.

Ramachandran, V. S. Applications of Differential Thermal Analysis in Cement Chemistry, B (10) 364*b*.

Ramachandran, V. S., and Feldman, R. F. Length change characteristics of $Ca(OH)_2$ compacts on exposure to water vapor, (8) 286*j*.

Ramachandran, V. S., Kacker, K. P., and Srivastava, R. S. Catalytic action of NaCl on the decomposition of dolomite for the manufacture of magnesium oxychloride cement, (2) 43*i*.

Ramamurthy, P. See Low, M. J. D.

Raman, A. Ternary FeB- and CrB-type phases with yttrium, lanthanum, and some rare earths, (11) 388*c*. See Hunt, C. R., Jr.

Raman, C. V. Diamond—its structures and properties, (1) 23*d*.

Raman, V. Identification of expansive clays from the plasticity index and the shrinkage index data, (4) 120*b*.

Ramasubramanian, N. See Low, M. J. D.

Ramasubramanian, N., Sewell, P. B., and Cohen, M. Oxidation of iron single crystals at 350°C, (4) 148*c*.

Ramaswami, D. See Holmes, J. T.

Ramaswamy, E. R., and Gerhard, E. R. Performance estimate of a granular solids heater, (4) 122*f*.

Rambousek, V. See Koller, A.; Koukal, V.

Ramey, R. A., Jr. Method [float glass] and apparatus for the manufacture of glass envelopes, P (11) 371*f*.

Ramey, R. L., and McLennan, W. D. Depositing semiconductor films utilizing a thermal gradient, P (5) 182*b*.

Ramirez-Munoz, J. See Malakoff, J. L.

Ramm, E. J. See Reeve, K. D.

Rammel, G. E. See Marzocchi, A.

Ramos, J. See McLaughlin, H. C.

Rampton, V. W. See Marshall, F. G.

Ramsden, A. R. See Zeidler, W.

Ramsey, T. H., and Rice, S. B. Effects of heat treatment on electron-gun-deposited SiO_2 films, (6) 220*f*.

Ramsey, T. H., Jr., Van Tassel, J. H., and Abraham, R. P. Method for the fabrication of integrated circuits, P (10) 345*g*.

Ramsey Engineering Co. Load control system [gyratory crusher], P (11) 382*b*.

Ranachowski, J. Effect of structure on electric properties of ceramics, (4) 110*b*.

Rand, M. H. See Ackermann, R. J.; Fletcher, J. M.

Rand, M. J. Nitric oxide process for the deposition of silica films, (4) 146*d*.

Rand, M. J., and Roberts, J. F. Preparation and properties of thin film boron nitride, (5) 198*i*.

Randle, W. R. Electronic thickness meter having direct readout of coating thickness, P (7) 260*i*.

Randolph, A. D. Process for producing borax decahydrate crystals, P (1) 24*b*.

Ranganatham, B. V., and Pandian, N. S. S. Strength and deformation characteristics of anisotropically consolidated kaolinite clay, (5) 190*a*.

Rangarajan, L. M. See Bhide, G. K.

Rangarajan, S. K. See Fleischmann, M.

Rangaswamy, N. S., Balasubramanian, T. M., and Rajagopalan, K. S. Effect of fly ash on steel reinforcement, (1) 2*h*.

Ransburg Electro-Coating Corp. Electrostatic coating apparatus, P (7) 246*f*. Electrostatic spray device, P (5) 186*f*.

Rantell, A. See Wilkes, J. G.

Rao, C. N. R. See Rao, K. J.

Rao, D. B., and Dadape, V. V. Reaction of AlCl(*g*) with MgO(*c*) and the heat of formation of $MgAl_2O_4$(*c*), (4) 152*d*.

Rao, G. V. S. See Rao, K. J.

Rao, K. J., Rao, G. V. S., and Rao, C. N. R. *Pm3m-Fm3m* transformations of alkali halides and the Born-Mayer model—CsCl and its solid solutions with RbCl, KCl, and CsBr, (4) 150*b*.

Rao, K. V. K., Naidu, S. V. N., and Iyengar, L. Thermal expansion of tetragonal phase of VO_2, (2) 84*g*.

Rao, K. V. S., Sastry, M. D., and Venkateswarlu, P. Electron paramagnetic resonance studies of VO^{2+} in KNO_3 and $CsNO_3$ single crystals, (8) 291*g*.

Rao, M. L. B. Addition agents for sintering processes, P (4) 112*a*.

Rao, R. Comparison of the thermal expansions of selenium and tellurium, (4) 129*e*.

Rao, S. V. K. See Moorthy, V. K.

Rapoport, E. Pressure dependence of the orthorhombic-cubic transformation in lead zirconate, (2) 82*e*. See Pistorius, C. W. F. T.

Rapp, C. F. See Baak, N. T. E. A.

Rapp, C. F. See Lee, H. A., Jr.

Rapp, R. A. See Patterson, J. W.

Rappeneau, J. See Merlin, J.

Rasch, H. Sintering characteristics of oxide-ceramic materials based on MgO-Al_2O_3-spinel, (1) 36*f*.

Rase, D. E. Comments on "Silica transformations in the system PbO-SiO_2," (8) 289*j*.

Rasheed, A. Z. See Bhatty, M. I.

Rashevskaya, E. P. See Il'in, M. A.

Rashkovich, L. N. See Evlanova, N. F.

Rasmussen, R. A. Vibrational relaxation in the tetrachlorides of C, Si, Ge, Sn, and Ti, (5) 203*b*.

Rasmussen, S. E. See Larsen, F. K.

Rastorguev, L. N. See Ezerskii, M. L.

Rastrelli, J. E. Production of magnesium hydroxide from aqueous solutions containing magnesium and boron values, P (5) 191*c*.

Rastyapin, V. A., and Rozenblit, A. B. Electric resistivity of slurries with a conducting liquid and an insulating solid phase, (2) 76*i*.

Rasul, S. H., and Ali, M. A. Proposed codification of carbonate rocks associated with low temperature hydrothermal ore deposits, (1) 23*j*.

Rath, R. H. Coating composition and method of applying, P (7) 246*e*.

Ratz, G. A. Niche for automated quantitative microscopy, (1) 21*f*.

Rau, R. C. Neutron damage in beryllium oxide irradiated at high temperatures, (1) 33*i*.

Rauch, G. C., Courtney, T. H., and Wulff, J. Aging in Nb(Cb)-Ti-O superconductors (with appendix), (6) 230*f*.

Raudonis, A. See Babonas, G.

Rauh, E. G. See Cater, E. D.

Rauland Corp. Method of preparing a slurry coating composition, P (2) 65*j*. Process for screening a color cathode-ray tube, P (6) 223*j*.

Raunie, G., and Svensson, O. X-ray total reflection studies of germanium, gold, and glass by a three-crystal spectrophotometer, (4) 121*c*.

Rausch, H. See Szabo, E.

Rausch, W. See Huehndorf-Richter, B.

Rausch, W., and Koch, G. Method of treating metal surfaces, P (5) 172*a*.

Rauschenbach, R. R. See Gamber, E. J.

Rauschenfels, E. See Lehmann, H.

Rauschenfels, E., and Thormann, P. Routine measurement of static moduli of elasticity of ceramic and building materials with an electromechanical transducer, (6) 227*g*.

Rauscher, H. E. Transformation of surface layers, (5) 204*j*.

Rautio, W. S. See Barron, S.

Rautschke, R. Influence of chemical reactions in graphite electrodes on the intensity of spectral lines, (2) 78*i*.

Ravich, L. E. Method for the production of amorphous cadmium sulfide, P (6) 222*h*.

Rawski, D. P. Method of rendering glass surfaces abrasion-resistant and glass articles produced thereby, P (4) 100*h*.

Ray, H. S. New viscometer for measuring the vicosities of molten silicates, (2) 70*a*.

Ray, J. A. See Kelly, T. M.

Ray, N. H. Method of strengthening glass by a potassium nitrate-potassium borofluoride melt, P (8) 278*c*.

Ray, N. H., and Stacey, M. H. Increasing the strength of glass by etching and ion exchange, (8) 276*a*.

Ray, R. N. See Lele, R. V.

Ray, S., and Muchow, G. M. High-quartz solid solution phases from thermally crystallized glasses of compositions $(Li_2O,MgO)\cdot Al_2O_3\cdot nSiO_2$, (1) 7*f*.

Raybestos-Manhattan, Inc. Production of asbestos yarn, P (10) 343*a*.

Rayment, D. L. See Freeman, I. L.; Majumdar, A. J.

Raymond, M. See Hafner, S. S.

Raytheon Co. Controlled breakdown voltage diode, P (4) 112*c*. Gas-filled discharge device having a grid with an element particularly spaced from the cathode, P (2) 64*i*. Isolated cathode array semiconductor, P (9) 312*c*. Method of making a field-effect transistor by diffusion, coating with an oxide, and placing a metal layer on the oxide, P (9) 312*j*. Method of making semiconductor diodes, P (6) 222*i*. Microcircuit with complementary dielectrically isolated mesa-type active elements, P (5) 184*h*. Multiple semiconductor device, P (10) 345*c*. Piezojunction device with an encapsulating *pn* junction, P (8) 283*i*. Semiconductor contact and interconnection structure, P (8) 283*b*.

Razouk, R. I., Mikhail, R. Sh., and Girgis, B. S. Surface area and pore structure of mixed hydroxides and oxides of magnesium and iron, (1) 38*g*.

RCA Corp. Beam-of-light transistor utilizing *pn* junctions which are nonabrupt and nontunneling with a base region of degenerate material, P (5) 182*f*. Bistable ferroelectric field effect device, P (5) 182*g*. Color picture display containing a red-emitting europium-activated yttrium oxysulfide phosphor, P (5) 182*j*. Complementary MOS transistor integrated circuits with inversion layer formed by ionic discharge bombardment, P (11) 376*j*. Cryoelectric memories, P (9) 312*d*. Cubic crystal light modulator, P (10) 344*e*. Deposition of niobium stannide, P (5) 182*b*. Dielectrically loaded parallel-plane microwave ferrite devices, P (5) 182*d*. Ferroelectric control circuits, P (10) 344*h*. Ferroelectric insulated-gate field-effect device, P (9) 312*i*. Grooved bulk semiconductor oscillator, P (10) 345*a*. High frequency transistor structure with two-conductivity emitters, P (5) 183*d*. High speed controlled rectifiers with deep level dopants, P (8) 282*j*. High voltage semiconductor transistor, P (5) 183*f*. Insulated-gate field-effect transistor, P (6) 221*h*. Insulated-gate field-effect transistor with critical bulk characteristics for use as an oscillator component, P (7) 256*d*. Light-emitting semiconductor having relatively heavy outer layers for heat-sinking, P (6) 221*i*. Luminescent image device and combinations thereof with optical filters, P (10) 345*d*. Luminescent material and [liquid] laser apparatus utilizing said material, P (9) 312*f*. Luminescent materials and apparatus for generating coherent radiation, P (8) 282*c*. Method of fabricating insulated-gate field-effect devices, P (10) 345*f*. Method of fabricating semiconductor devices, P (10) 345*g*, P (7) 257*b*. Method of forming aligned oxide patterns on opposite surfaces of a wafer of semiconductor material, P (2) 65*c*. Method of forming a crystalline semiconductor layer on an alumina substrate, P (4) 114*e*. Method [heating] for preparing a ferroelectric body and devices, P (9) 312*i*. Method of making high purity metal zeolite and product thereof, P (2) 74*e*. Method of making a laminated ferrite memory, P (1) 18*b*. Method of making a vapor device, P (5) 183*j*. Method of preparing luminescent materials, P (7) 257*a*. Method for pressing particulate material, P (9) 314*f*. Monolithic integrated circuits with a plurality of isolation zones, P (6) 222*j*. Monolithic semiconductor microcircuits with improved means for connecting points of common potential, P (5) 184*a*. MOS tetrode, P (5) 184*a*. Phosphor and method of preparation thereof, P (11) 378*c*. Photoconductive device having a target including a selenium blocking layer, P (2) 66*c*. *Pn* junction semiconductor with polycrystalline layer on one region, P (8) 283*i*. Probe assembly for testing semiconductor wafers including a wafer vibrator for effecting good test connections, P (10) 345*f*. Rare earth activated lanthanum and lutetium oxychalcogenide phosphors, P (4) 116*e*. Rare earth activated yttrium and gadolinium oxychalcogenide phosphors, P (4) 116*e*. Remote cutoff junction gate field-effect transistor, P (9) 313*f*. Semiconductor device fabrication, P (4) 116*c*. Semiconductor device having increased resistance to second breakdown, P (9) 313*i*. Semiconductor devices and methods of making them, P (6) 223*h*. Semiconductor junction device, P (11) 378*f*. Semiconductor plasma laser, P (4) 116*g*. Thermoelectric device having a graphite member between thermoelement and refractory hot strap, P (8) 284*a*. Thermoelectric device with graphite elements, P (9) 314*b*. Thermoelectric lead telluride base compositions and devices utilizing them, P (11) 379*c*.

Rea, R. F. Method for making an insulator, P (8) 280*c*.

Rea, R. F., and Dulin, F. H. Method of accurately producing an abrasive surface of revolution, P (7) 243*j*.

Read, P. J. Method of coating refractory ware with magnesia, P (9) 309*g*.

Reardon, D. E. See Kim, Y. M.

Reardon, D. E., Wallace, R. W., and Beals, R. S. Inclined kiln, P (7) 261*c*.

Reber, R. L. See Worchel, G. S.

Rebhun, M., and Sperber, H. Optical properties of diluted clay suspensions, (1) 33*i*.

Rebinder, P. A. (editor). Physicochemical Mechanics of Dispersed Structures, B (9) 334*j*. See Lishanskii, B. A.

Rebstock, H. See Dorendorf, H.

Recasens, J., Bortaud, P., and Bonnier, E. Melting and electrolysis of refractory metallic oxide, (1) 23*h*.

Reddig, H. Progress in the production of piezoceramics and their properties, (7) 255*j*.

Reddy, A. S., and Basavanna, B. M. Studies on creep of partially saturated clays, (1) 23*j*.

Reddy, K. V. See Gopal, B. S. V.

Reddy, P. G., and Jain, M. K. Hydromagnetic laminar flow through conducting parallel porous walls, (1) 30*h*.

Redey, L. See Halasz, D.

Redfern, B. A. W. See Quin, J.

Redington, R. W. Method of manufacturing semiconductor camera tube targets, P (1) 18*c*.

Redland Tiles, Ltd. Tiled roofs, P (6) 214*g*.

Redman, J. H. Cathode ray tube display device having a hemispherical display area, P (2) 64*g*.

Redman, M. J. Zinc tellurite glasses, P (5) 176*d*. See Lipson, H. G.

Redman, M. J., Binnie, W. P., and Carter, J. R. Compound formation in the systems rare-earth oxides-tellurium dioxide, (9) 318*f*.

Ree, Taikyue. See Lu, Wei-Chen.
Reece, H. W. See Kohls, D. E.
Reece Construction Co., Inc. Method and apparatus for handling bulk cement, P (6) 207*e*.
Reed, B. S. See Bonin, E. L.
Reed, G. C. Controlled deflection strainline test, (7) 245*i*.
Reed, J. S., and Kay, H. F. Optical spectra of 3*d* transition metal ions in $MgO{\cdot}3.5Al_2O_3$ spinel, (8) 295*h*.
Reed, L. Ceramic-to-metal seal and method of making same, P (4) 93*e*.
Reed, L., and McRae, R. Advanced components using fused quartz-to-metal sealing techniques, (8) 280*g*.
Reed, L. J., and Morrison, J. R. Method of making fine line patterns using a ferromagnetic element, P (9) 313*a*.
Reed, N. D. See Ligon, E. R.
Reed, N. L. See Burke, J. J.
Reed, R. A. See Bennett, H.
Reed, R. D. Burner assembly producing radiant heat, P (4) 122*h*.
Reed, R. G. See Fleming, G. S.
Reed, R. L. See Haley, K. M.
Reed, T. B. High temperature furnace, P (4) 123*a*. Plasmas for high temperature chemistry, B (4) 165*c*. See Dimmock, J. O.
Reed, T. B., and Pollard, E. R. Tri-arc furnace for Czochralski growth with a cold crucible, (5) 185*b*.
Reedyk, C. W. Field-effect electroacoustic transducer, P (7) 256*h*.
Reeher, J. R. See Heald, E. F.
Rees, D. See Lake, R. E.
Reese, R. C., and Wesel, P. E. Device for scoring glass articles, P (2) 52*g*.
Reese, T. J., and Corsi, R. J. Method and apparatus for shaping glass sheets, P (4) 99*h*.
Reesman, A. L., and Keller, W. D. Aqueous solubility studies of high-alumina and clay minerals, (8) 288*j*.
Reeve, D. A., and Bright, N. F. H. Phase relations in the system $CaO{-}Ta_2O_5{-}SiO_2$, (10) 358*d*.
Reeve, K. D., Buykx, W. J., and Ramm, E. J. System $BeO{-}Al_2O_3{-}MgO$ at subsolidus temperatures, (11) 387*b*.
Reeves, C. C., Jr. See Parry, W. T.
Refractories, Ltd. Foamed refractories, P (1) 13*j*.
Regehr, R. W. See Burmeister, R. A., Jr.
Reggia, F. Nondispersive electrically variable microwave acoustic delay line comprising a ferrite Faraday rotator coupled to an anisotropic piezoelectric crystal, P (6) 223*b*.
Reggia, F., and Mak, Ting H. Reciprocal ferrite attenuator, P (4) 116*f*.
Regh, J. See Kren, J. G.
Regh, J., Silvey, G. A., and Gardiner, J. R. Method for plating and polishing a silicon planar surface, P (7) 257*a*.
Rehage, G. See Breuer, H.
Rehfeld, G. See Schwiete, H. E.
Rehm, K. New methods of testing the chemical resistance of silicate glasses, (6) 210*c*.
Rohsi, S. S., and Majumdar, A. J. Quantitative determination of uncombined MgO in portland cement by X-ray diffractometry, (9) 304*b*.
Reich, H. F. Discussion of "After-expansion of fireclay refractory," (4) 102*j*.
Reichel, R. A. Apparatus for crushing and sorting solid particles, P (5) 190*d*.
Reichen, L. E., and Fahey, J. J. Determination of nitrates in saline minerals, (4) 119*b*.
Reichenberger, H., and Jaenicke, W. Mechanical tension in the system metal-oxide (IV) anodic oxidation of tantalum, (10) 357*b*.
Reid, A. F., Perkins, H. K., and Sienko, M. J. Magnetic, electron spin resonance, optical, and structural studies of the isomorphous series $Na(Sc,Fe)TiO_4$, (11) 385*g*.
Reid, A. F., and Ringwood, A. E. High-pressure $NaAlO_2$, an α-$NaFeO_2$ isotype, (11) 385*e*.
Reid, A. F., and Sienko, M. J. Scandium titanite and scandium vanadite, $ScTiO_3$ and $ScVO_3$, (4) 153*j*. Some characteristics of sodium titanium bronze and related compounds, (4) 155*g*.
Reid, A. F., Wadsley, A. D., and Sienko, M. J. Crystal chemistry of sodium scandium titanate, $NaScTiO_4$, and its isomorphs, (11) 383*j*.
Reid, F. J., Baxter, R. D., and Miller, S. E. GaSb prepared from nonstoichiometric melts, (1) 30*e*.
Reid, F. J., Miller, S. E., and Goering, H. L. Vapor growth of AlP single crystals, (1) 40*a*.
Reid, L. R. Elastic moduli of chalcogenide infrared optical materials, (2) 48*e*.
Reijners, P. Phase equilibria in the system $MgO{-}FeO{-}Fe_2O_3$, (9) 327*c*.
Reilly, M. H. See Fuller, R. G.
Reim, T. E. See Stone, L. R.
Reimann, D. K., and Landy, T. S. Diffusion of ^{233}U in UO_2, (11) 383*f*.
Reimers, P. See Seiler, H.
Reimschuessel, H. K., and Mountford, G. A. Adsorption of ozone on silica gel, (1) 24*i*.
Rein, R. G., Jr., Sliepcevich, C. M., Babb, S. E., Jr., and Tuma, G. Change in resonant frequency with pressure to 8000 atm of quartz-crystal viscometers, (9) 305*e*.
Reinen, D. Ligand field effect and the structure of oxidic solids (I) spinel phases containing Ge^{4+}, (10) 356*g*. See Joergensen, C. K.
Reinhart, F. Carbon bodies, (11) 372*i*.
Reinhardt, H., and Nauroth, P. Process for producing finely divided precipitated silica, P (6) 230*e*.
Reinitz, K. Extended area semiconductor radiation detectors and a novel readout arrangement, P (4) 113*a*. See Schuster, M. A.
Reishakhrit, A. L. See Karapetyan, G. O.
Reismueller, K. H., Alexander, R. E., and Reismueller, M. W. Electrolytic plating of metal bump contacts to semiconductor devices on nonconductive substrates, P (2) 64*d*.
Reissmueller, M. W. See Reismueller, K. H.
Reitmeier, R. E., Hirschler, D. A., Jr., Lamb, F. W., and Stephens, R. E. Oxidation catalysts, P (6) 229*j*.
Rem Metals Corp. Method of making investment shell molds for the high integrity precision casting of reactive and refractory metals, P (5) 179*a*.
Remeika, J. P. Growth of *a*-domain barium titanate, P (11) 376*i*. See Lenzo, P. V.; Marezio, M.; Walsh, W. M., Jr.
Remeika, J. P., Gyorgy, E. M., and Wood, D. L. Preparation and magnetic properties of Bi-substituted single-crystal rare-earth orthoferrites, (10) 359*h*.
Remeika, J. P., and Kometani, T. Y. Lead substitution in flux-grown single crystal rare earth orthoferrites, (8) 294*d*.
Remeika, J. P., and Wood, D. L. Ferrimagnetic light transmission garnets, P (9) 312*h*.
Remenyi, K. See Bassa, G.
Remey, W. D. Relation between specific gravity and state of order in plagioclase from anorthosite rocks, (9) 328*i*.
Remington, W. J. See Brown, M. L.
Remmey, G. B., Sr. Jet firing creates new tunnel kiln design, (4) 122*i*.
Reneau, J. T., Jr. Means for detecting filter cake buildup, P (6) 225*b*.
Renkey, A. L. Carbon baking furnaces, P (9) 309*e*. Induction furnace construction, P (6) 217*c*. Induction furnace having a composite lining composed of refractory brick, P (1) 14*d*. See Cope, G. R.
Renkey, A. L., and Troell, P. T. Induction furnace, P (1) 14*c*.
Renninger, A., Moss, S. C., and Averbach, B. L. Local antiferromagnetic order in single-crystal MnO above the Néel temperature, (1) 31*i*.
Renshaw, G. D. See Thomas, J. M.
Rep, R., and Winterhalter, B. G. L. Observation on the weathering of limestone in glaciogenic material in the Lohja region, SW. Finland, (9) 325*i*.
Republic Steel Corp. Nuclear gaging system for moisture content of irregular stream of bulk material, P (6) 228*b*. Process for repairing refractory walls, P (4) 107*c*.
Res, M. Theoretical bases of sintered filter technology, (1) 39*g*.
Reseo Products, Inc. Refractory floor construction, P (6) 218*d*.
Research Corp. Indium arsenide Gunn oscillator, P (2) 65*d*. Thermistor and method of manufacture, P (4) 117*d*.
Reser, M. K. (editor). Phase Diagrams for Ceramists—1969 Supplement, B (11) 390*d*.
Reserve Mining Co. Conveying and classifying apparatus, P (7) 259*e*. Infeed and sealing means for grinding mills [ball or rod], P (1) 23*j*.
Reshetnikov, M. A. Toward the equation of heat content of corundum from 0° to 2000°K, (7) 270*c*.
Reshetov, K. V. See Vidavskii, L. M.
Resource Processors, Inc. Talc beneficiation method, P (4) 126*a*.
Restall, J. E. Development and testing of protective coatings on F_{48} and SU_{16} niobium alloys, (4) 103*e*. Method of [diffusion] coating metals with a silicide layer and an outer layer of aluminum silicate, P (8) 275*e*.
Reti, A. M., Jena, A. K., and Bever, M. B. Solid solutions of tin telluride and lead telluride, (2) 83*d*.
Reum, H. See Winter, G.
Reumann, O. New central laboratory of the porcelain factory Lorenz Hutschenreuther AG, Selb, Bavaria [West Germany], (10) 343*g*.
Reuschel, K. Method of crucible-free zone melting of semiconductor material, particularly silicon, P (10) 345*f*. See Raithel, K.
Reuter, B., and Mueller, K. Relation between V-V bond distances, infrared spectra, and electronic properties in the system ZnV_2O_4-LiV_2O_4, (6) 237*h*.
Revay, M. See Dolezsai, K.
Rev, E. See Borus, S.
Revenko, A. G. See Losev, N. F.
Revesz, A. G., and Zaininger, K. H. Si-SiO_2 solid-solid interface system, (4) 155*a*.
Revina, O. Ya. See Belyaev, I. N.
Revolinsky, E., Beerntsen, D. J., and Spiering, G. A. Anisotropic superconductor, P (2) 64*d*.
Rex Asbestwerke Graf von Rex K.G. Manufacture of purified asbestos products, P (10) 342*g*.
Reynders, A. Apparatus for feeding articles to an endless or closed path conveyor, P (1) 10*f*. See Kolkman, D.
Reynik, R. J. See Foster, J. P.
Reynolds, F. W. See Meixner, A. E.
Reynolds, F. W., and Meixner, A. E. [Method of making] photoconductive thin film cell responding to a broad spectral range of light input, P (9) 313*b*.
Reynolds, G. L. Surface self-diffusion of uranium dioxide, (4) 158*f*.
Reynolds, J. A. Infeed and sealing means for grinding mills [ball or rod], P (1) 23*j*.
Reynolds, R. A. Phase relations and thermoelectric properties of the alloy systems SnTe-Bi_2Te_3 and PbTe-Sb_2Te_3, (4) 149*i*.
Reynolds, R. A., Stroud, D. G., and Stevenson, D. A. Phase equilibria in the zinc-tellurium system, (4) 149*i*.
Reynolds, R. W. See Abraham, M. M.; Boatner, L. A.
Reynolds Metals Co. Beneficiation of cryolite material, P (10) 349*a*. Electrically conductive cermet compositions, P (2) 58*c*. Method for extracting alumina from its ores, P (4) 124*i*. Removal of fluorine from alumina by steam, P (8) 288*c*. Viscosity reduction of alumina hydrate filter cake, P (2) 74*h*.
Rez, I. S. Data on the crystallochemical selection of materials for control of infrared beams, (2) 61*i*.
Rezek, J., and Childs, B. G. Structure and properties of yttria-zirconium dispersions, (10) 361*e*.
Reznicek, K. Lapping machine, P (11) 371*b*.
Rheinberger, P., and Kuemmerer, F. Electrically conductive solderable metallic coatings on nonmetallic bases, P (5) 182*h*.
Rheinische Kalkstein-Werke G.m.b.H. Heating process in a rotary kiln, P (2) 67*i*. Plant for the simultaneous grinding of differently grindable materials, P (1) 24*b*. Production of hydraulic binders, P (5) 170*i*.
Rhodes, D. Kilns: Design, Construction, and Operation, B (9) 334*g*.
Rhodes, E., Smith, W. E., and Ubbelohde, A. R. Relaxation processes in supercooled nitrate melts, (4) 153*j*.
Rhodes, J. R. X-ray source and measuring means for backscatter analysis of samples, P (9) 316*a*.
Rhodes, W. H. See Heuer, A. H.
Ribacchi, R. See Esu, F.
Ribbe, P. H. See Colville, A. A.
Ribner, A. See Weinreich, O. A.
Ricciardi, R. J. Apparatus for conditioning and dispensing particulated material, P (7) 259*d*.
Riccius, H. D., and Turner, R. Electroabsorption of zinc telluride films, (10) 344*a*.
Rice, D. W., and Gregory, N. W. Vaporization characteristics of zinc chloride, bromide, and iodide, (10) 363*h*. Vaporization equilibria in the sodium chloride-zinc chloride system, (10) 363*h*.
Rice, R. G. See Maselli, J. M.
Rice, R. W. CaO (I) fabrication and characterization; (II) properties, (10) 350*j*.
Rice, S. B. See Ramsey, T. H.
Rich, L. G. Solid state matrix for display system or the like, P (11) 379*a*.
Richards, B. P., and Kellett, E. A. Changes in the structure of graphite on irradiation under restraint, (5) 192*a*.
Richards, D. See Barrow, R. F.
Richards, E. A., Vetere, J. J., and Appolloni, J. Method of fabricating an incandescent lamp and its construction, P (4) 99*i*.
Richards, J. D. See Fredrick, R. E.
Richards, K. J., and Wagstaff, F. E. Diffusion of iron in single-crystal nickel oxide, (4) 131*d*.
Richards, N. E., Berry, J. S., Jr., and Johnston, T. J. Electrically conductive cermet compositions, P (2) 58*c*.
Richards, R. Madrid Congress Report, (4) 108*c*. See Beard, R.
Richards, R. S., and St. John, D. F. Method and apparatus for heating rollers, P (5) 175*j*.
Richardson, D. L. See Comstock, D. F., Jr.
Richardson, F. D. See Kor, G. J. W.
Richardson, H. M. Changes in the usage of refractories in the iron and steel industry, (4) 103*i*.
Richardson, H. M., Lester, M., Palin, F. T., and Hodson, P. T. A. Effect of boric oxide on some properties of magnesia, (6) 214*j*.
Richardson, K. W. See Darr, D. E.
Richardson, M. Crystal structure refinements of the B 20 and monoclinic (CoGe-type) polymorphs of FeGe, (4) 130*d*.
Richardson, M. C. See Alcock, A. J.
Richardson, R. E. Method of and apparatus for press bending vertically suspended glass sheets, P (9) 307*i*.
Richardson, S. W. Staurolite stability in a part of the system Fe-Al-Si-O-H, (4) 156*a*.
Richardson, S. W., Gilbert, M. C., and Bell, P. M. Experimental determination of kyanite-andalusite and andalusite-sillimanite equilibria. Aluminum silicate triple point, (7) 265*g*.
Richter. Gyratory crushers, P (5) 190*j*.
Richman, D. Vapor phase growth and properties of aluminum phosphide, (10) 363*g*.
Richmond, J. F., Boone, J. S., and Langley, L. W. Internal ridging tool, P (2) 53*c*.
Richter, H. See Breitling, G.; Buettner, K.
Richter, H., Buettner, K. H., and Bintzek, G. Apparatus for compacting permanent magnet powders into pressings, P (4) 112*a*.
Richter, P. X-ray spectrometric determination of K_2O and CaO in mineral standards by a decomposition method, (6) 227*f*.
Rickard, D. T. Synthesis of smithite-rhombohedral FeS_4, (9) 331*i*.

Rickmann, F. Bubble structure and adherence of one-coat enamels, (5) 171*b*.
Riddel, J. W. Method of making a thermistor, P (6) 222*a*. See Schwyn, R. E.
Rideal, E. Interphase transfer, (1) 31*h*.
Rideout, D. C. Reflective markers and reflective elements therefor, P (4) 101*c*.
Rideout, V. L. See Crowell, C. R.
Ridge, C. J., Harrop, P. J., and Campbell, D. S. Amorphous Pb-Ti-O capacitors, (8) 280*h*.
Ridge, M. J. See Adami, A.; Beretka, J.; Goto, M.; Molony, B.
Ridge, M. J., Molony, B., and Boell, G. R. Transformation of finely divided cubic to trigonal iron(III) oxide, (4) 162*b*.
Ridge, M. J., and Surkevicius, H. Reactivity of calcium sulfate hemihydrate, (2) 45*f*.
Ridgway, F. Engineering helps doctors cure bedridden hospital patients, (9) 333*c*.
Riebling, E. F. Electrical conductance study of Na^+ ion mobility in silicogermanate, aluminogermanate, and aluminosilicate melts, (2) 76*j*. Palladium dichloride whiskers — preparation and properties, (4) 148*d*. Silicon dioxide dissolution in molten glass, (10) 338*g*.
Rieck, G. D. See Driessens, F. C. M.
Riedel, H. J. See Kaiser, G.; Knacke, O.
Riedel, J. Apparatus for the continuous production of a mat of glass filaments, P (8) 277*e*.
Riedl, H. R. See Schoolar, R. B.
Riegel, P. S. Equivalent value coefficients for liquid flow, (1) 21*j*.
Rieger, C. J., and Quinn, C. A. Process for producing stabilized titanium dioxide pigments, P (4) 125*a*.
Rieke, H. H., III. See Chilingarian, G. V.
Rienacker, G. See Walter, H. P.
Ries, H. B. Nomograms and graphical calculations for use in preparing ceramic bodies, (5) 186*c*.
Riess, H. See Glueck, R.
Rieve, R. W. Metal contaminant removal from solid carbonaceous materials, P (10) 342*h*.
Riewald, P. G., and Van Vlack, L. H. Slip behavior and hardness indentations in MnSe and MnSe-MnS solid solutions, (9) 329*i*.
Rigaud, J. Identification and measurement of the parameters of sintering, (6) 233*e*.
Rigby, F. See Steele, B. R.
Rigby, G. R. Ceramics in a changing world (III) refractories, (1) 40*e*.
Rigden, C. J. See Parker, R.
Rigden, S. A. R., and Whiscombe, J. B. Closure of tubes of refractory oxide material, P (6) 221*a*.
Rigdon, M. A., and Grace, R. E. Near-equilibrium kinetics of the dissociation of cupric oxide, (4) 145*j*.
Riggs, B. A. Vacuum-deposited thin films of the type PbS_xSe_{1-x}, (4) 163*c*.
Riha, J. G., Trevorrow, L. E., Ellyn, G., and Steindler, M. J. Separation of ruthenium and plutonium by a lithium fluoride sorption technique, P (11) 383*a*.
Rihak, V. See Sestak, J.
Rikagaku Kenkyusho. Method of making a woven fiber circuit element, P (9) 313*b*.
Rikhter, R. G. See Potebnya, Yu. M.
Riley, D. L. See Herzenberg, C. L.
Riley, F. L. See Popper, P.
Riley, J. E., and Williams, B. B. Method of making a capacitor by vacuum depositing manganese oxide as the electrolytic layer, P (6) 222*e*.
Riley, R. See Brecher, C.
Riley, R. E., Davidson, K. V., and Taub, J. M. Method of making solid solution carbide-graphite compositions, P (4) 106*j*.
Rimbach, H. W. Scandium-containing alkaline earth phosphate phosphor having good temperature-dependence characteristics, P (4) 116*i*.
Rimer, K. W. See Coless, T. L.
Rindner, W., and Nelson, R. F. Piezojunction device with an encapsulating *pn* junction, P (8) 283*i*.
Rindone, G. E. Effects of melting history on properties of glass, (7) 247*f*.
Rinehart, D. W. High strength fiber glass, P (11) 371*a*.
Ringwood, A. E. See Reid, A. F.
Ringwood, A. E., and Major, A. High pressure transformation in zinc germanates and silicates, (4) 138*b*.
Rinke, K. See Schafer, H.
Rioux, F. J., and Gerstein, B. C. Thermal and magnetic study of bonding in $CsCuCl_3$, (10) 362*g*.
Ripple, J. W. See Houck, J. C.
Ripple, W. M. See Arnold, A. J.
Riseman, J. See Perri, J. A.
Rishel, P. A. See Marshall, P. A., Jr.
Ristic, M. M. See Boskovic, S. B.
Ristic, M. M., and Zivanovic, B. M. Theoretical examination of the sintering process with particular reference to changes in the properties of oxides during sintering, (4) 160*f*.
Ritchey, R. A. See Hill, T. E., Jr.
Ritter, E. See Bradford, A. P.
Ritter, G. F., Jr. Oscillatory [air] spray tempering apparatus, P (10) 339*h*.
Ritter, J. C. Welding core for tubes, P (4) 109*d*.
Ritter, J. E., Jr. Deep sea submersible vehicles, (2) 47*j*. Dynamic fatigue of soda-lime-silica glass, (9) 305*b*.
Ritter Pfaudler Corp. Connection with a glass coated sealing surface, P (7) 246*e*. Glassed heat exchanger construction, P (5) 172*a*. Method and apparatus for repairing glass-coated articles, P (7) 246*f*.
Rittner, E. S. See Leventhal, E. A.
Ritzmann, H. See Weber, P.
Rivera, J., Murray, L. A., and Hoss, P. A. Growth of cuprous chloride single crystals for optical modulators, (5) 194*d*.
Rives, J. J. Method of manufacture of superwhite cement, P (5) 170*g*.
Rizhsky Elektrolampovy Zavod. Lead-in for devices with a quartz bulb, P (9) 312*e*.
Rizzo, F. E., Bidwell, L. R., and Frank, D. F. Thermodynamics of the tungsten-oxygen system, (5) 202*d*.
Robb, R. R. See Feagin, R. C.
Robba, W. A. See Turkat, M.
Robbins, C. R. Growth of strontium titanate from a silica flux, (7) 266*b*. Synthetic $CaTiSiO_5$ and its germanium analog ($CaTiGeO_5$), (2) 83*h*. See Levin, E. M.
Robbins, J. W. See Twomey, E. F., Jr.
Robbins, K. G., and Thomas, J. M. Production of epitaxial films of antimony on disordered substrates, (5) 181*f*.
Robbins, M. See Arlett, R. H.
Robbins, R. G. See Shabbir, M.
Robbins, W. B., and Kern, E. L. Method of growing thin film semiconductors using an electron beam, P (4) 114*j*.
Roberson, C. E., and Hem, J. D. Solubility of aluminum in the presence of hydroxide, fluoride, and sulfate, (9) 329*j*.
Robert, A. X-ray fluorescence analysis, (2) 71*g*.
Robert, G. See Caillet, M.
Roberts, A. L. Study of the mechanical properties of refractories at working temperatures, (5) 178*f*. See Rumsey, J. C. V.
Roberts, E. W., and Roberts, J. P. Research on the permeability of oxides to gases at Leeds University (1) 13*d*.
Roberts, G. I. Bottle forming apparatus, P (1) 10*j*.
Roberts, G. J. See Cockram, D. R.
Roberts, G. L., Hoelscher, H. E., and Cauwenberg, W. J. Apparatus for making titanium dioxide pigment, P (5) 190*e*.
Roberts, J. F. See Rand, M. J.
Roberts, J. P. See Fryer, G. M.; Heuer, A. H.; Roberts, E. W.
Roberts, L. E. J., and Markin, T. L. Thermodynamics of nonstoichiometric oxide systems, (5) 201*i*.
Roberts, R. A., Roessler, D. M., and Walker, W. C. Fine structure in the direct absorption edge of diamond, (2) 77*e*.
Roberts, R. C. Method for extracting alumina from its ores, P (4) 124*i*.
Roberts, W. G. See Cragg, D. G.
Robertson, J. A. Method of producing high temperature resistant structures, P (6) 218*d*. See Battista, O. A.
Robertson, J. A. L. Nuclear reactor fuel, P (11) 375*e*.
Robertson, J. K. See Lambert, I. B.
Robertson, J. M. See Pointon, A. J.
Robertson, J. M., and Taylor, R. G. F. Single crystal growth by a traveling isotherm technique, (5) 188*d*.
Robertson, R. S. See Wirth, L. F., Jr.
Robie, R. A., and Waldbaum, D. R. Thermodynamic Properties of Minerals and Related Substances at 298.15°K (25.0°C) and One Atmosphere (1.013 Bars) Pressure and at Higher Temperatures, B (8) 302*h*.
Robiette, A. G. E. Electric arc stabilization in electric arc melting using carbon electrodes, P (11) 374*h*.
Robin, G. See Vidal, J. P.
Robin, M. B., Andres, K., Gaballe, T. H., Kuebler, N. A., and McWhan, D. B. Metallic conductivity and superconductivity in some silver clathrate salts, (2) 80*b*.
Robinette, W. C., Jr. See Brown, G. A.
Robins, J. Process for preparing sand cores, P (6) 218*a*.
Robins, R. G. Hydrothermal precipitation of uranium dioxide from uranyl nitrate solutions, (2) 73*f*.
Robinson, B. B., and Vural, B. Double-stream interaction in a thin semiconductor layer, (4) 132*d*.
Robinson, C. C. Radiation modulator, P (4) 101*a*. See Young, R. W.
Robinson, C. G. Apparatus for melting metals by resistance heating, P (7) 252*d*.
Robinson, H. A. Physical properties and structure of silicate glasses (I) additive relations in alkali binary glasses, (9) 306*f*.
Robinson, J. G. See Aldcroft, D.; Bve, G. C.
Robinson, J. H. See Barker, J. E.; Rohl, C. W.
Robinson, K. See Oldershaw, G. A.
Robinson, L. B., Vahldiek, F. W., and Lynch, C. T. Hot-pressing zirconia method, P (1) 14*c*.
Robinson, M. L. A. See Brunner, H. R.; Emmenegger, F. P.
Robinson, M. L. A., and Roetschi, H. A.C. polarization in β-modification Nb_2O_5 single crystals, (10) 349*g*.
Robinson, M. W., Jr., Steelman, C., Jr., and Perkins, E., Jr. Process for pickling of steel strip and regeneration of the contact acid, P (8) 275*h*.
Robinson, P. H., and Dumin, D. J. Deposition of silicon on single-crystal spinel substrates, (4) 131*e*. Method of forming a crystalline semiconductor layer on an alumina substrate, P (4) 114*e*. Method of forming a semiconductor by masking and diffusing, P (4) 114*h*.
Robinson, V. J. See Baptista, J. L.
Roblin, M. J. See Grenawalt, J. J.
Robson, D., Asaabghy, F. Y. I., and Ingram, D. J. E. Determination of carbon fiber structures by electron spin resonance, (10) 351*j*.
Robson, D., and Harker, H. Partially annealed interstitial material in neutron-bombarded graphite, (9) 326*c*.
Robson, F. G. See Pearne, F. J.
Roccasecca, D. D. See Luther, L. C.
Roche, M. A., Jr. Strengthened arc carbon electrode joints, P (2) 59*g*.
Rochow, E. G. Method of employing semiconducting catalysts, P (5) 183*a*.
Rochow, H. See Nixdorf, J.
Rochte, J. E., and Martin, D. N. Sample transport system, P (4) 122*a*.
Rock, F. C. Antireflection coating and assembly having synthesized layer of index of refraction, P (6) 212*b*.
Rodbell, D. S. See Kouvel, J. S.
Rodda, P. U. See Fisher, W. L.
Rode, J. A. Production of uranium tetrafluoride, P (4) 107*f*.
Rodgers, J. T., Williams, R. M., and Larsen, R. J. [Graphite] liner for smoking pipe, P (5) 178*g*.
Rodot, H., Hruby, A., and Schneider, M. Method of synthesis and growth from solution of homogeneous single crystals of semiconductors, (7) 255*f*.
Rodriguez, A. R., and Cronin, J. Process for manufacturing a multilayer ceramic capacitor, P (10) 345*g*.
Rodriguez, E. See Montagut-Buscas, M.
Roeck, E. F. Pipet plugger, P (11) 372*c*.
Roedel, H. Waste heat boilers attached to heavy-oil-fired regenerative glass tanks with operating pressures of 10 and 30 atm, (6) 211*h*.
Roeder, E. See Frank, B.
Roeder, P. See Campbell, F. E.
Roessler, D. M. See Roberts, R. A.
Roessler, D. M., and Walker, W. C. Spin-orbit splitting of the γ-excitation in MgO, (2) 83*g*.
Roessler, M. L., and Willis, H. C. Mixing with vibrations, (5) 186*c*.
Roest, E., and Vestersjoe, E. Crystal structure of the high-temperature phase Pd_3S, (9) 319*f*.
Roetschi, H. See Brunner, H. R.; Robinson, M. L. A.
Rogers, D. B. Low pressure synthesis of electrically conductive platinum cobalt oxide from a platinum halide and an oxide containing cobalt, P (4) 113*j*.
Rogers, D. B., Gillson, J. L., and Gier, T. E. Hydrothermal crystal growth and electrical conductivity of the spinel LiV_2O_4, (4) 139*d*.
Rogers, D. T. Process of making structural elements with compacted aggregate, P (6) 214*f*.
Rogers, E. A. See Haddon, J. C.
Rogers, E. S. See Ballard, H. D., Jr.
Rogers, L. B. See Burke, M. F.
Rogers, M. T. See Manoharan, P. T.
Rogers, T. G. See Mulhern, J. F.
Rogers, W. A., Jr. So you want to make a better screen? (7) 259*c*.
Rogovoi, M. I. See Galdina, N. M.
Rohl, C. W., and Robinson, J. H. Process for producing reinforced carbon and graphite bodies, P (11) 375*b*.
Rohlfs, H. A., and Schmidt, H. Process for the manufacture of metal fluorophosphates, P (1) 24*d*.
Rohm, A. Analytical determination of toxic constituents extracted from enamels according to the proposed standard DIN 51166, (5) 171*a*.
Rohrer, K. L. Glass-to-metal seals and method for making same, P (2) 52*i*.
Rohwer, E. F. C. H. See Coetzee, C. J.
Rokhvarger, E. L. See Berenshtein, P. I.
Rola Co. (Australia) Pty., Ltd. Powdered or sintered ferrite, P (2) 66*f*.
Rolfe, J., Holzer, W., Murphy, W. F., and Bernstein, H. J. Some spectroscopic constants of O_2^- ions in alkali halide crystals, (8) 298*c*.
Rolin, M. See Staronka, A.
Rolla, M. See Sinistri, C.
Rolland, G. F., and Seipel, J. J. Coating composition and process, P (8) 275*a*.
Rolnick, J. M. See Dorschu, K. E.
Roman, H. See Marshall, P. A., Jr.
Romann, P. Industrial viscosimeter for glasses in the high viscosity range, (5) 172*i*. Measurement of dielectric loss in glass, (7) 247*h*.
Romans, J. B. See Bascom, W. D.
Ron, A. See Loewenschuss, A.
Ronceray, A. J. L. See Ronceray, R. A. M.
Ronceray, F. M. M. See Ronceray, R. A. M.
Ronceray, P. R. See Ronceray, R. A. M.
Ronceray, R. A. M., Yeomans, L. S., Ronceray, A. J. L., Ronceray, F. M. M., and Ronceray, P. R. Mixer-grinder, especially for foundry sands, P (10) 347*a*.
Ronis, D. F. Simplified calculation of the transmittance of neutral glasses, (6) 211*e*.
Roos, J. T. H., and Price, W. J. Comprehensive scheme for the analysis of cement by

atomic-absorption spectrophotometry, (7) 259*g*.
Roosild, S. A. See Dolan, R. P., Jr.
Root, J. J. Method of producing semiconductive electronegative element of a battery, P (9) 313*d*.
Root, M. R. Method for fabricating memory apparatus, P (11) 377*j*.
Rooymans, C. J. M. Structural investigation on some oxides and other chalcogenides at normal and very high pressures, (9) 330*a*.
Rooymans, C. J. M., and Langenhoff, W. F. Th. Hydrothermal growth of single crystals and phase width of tetragonal lead monoxide, (8) 293*f*.
Ropp, R. C. Method of making phosphor raw-mix materials and phosphors, P (9) 313*a*. Method of rare-earth metal recovery from orthovanadate compound, P (5) 191*d*. Phosphors based on rare earth phosphates fast decay phosphors, (5) 198*j*. Phosphors based on rare earth phosphates (I) spectral properties of some rare earth phosphates, (10) 358*f*. Spectra of some rare earth vanadates, (10) 360*i*. See Vodoklys, F. M.
Ropp, R. C., and Gruff, E. A. Efficient preparation of rare-earth metal oxalate, P (5) 190*i*.
Ropp, R. C., and Gritz, E. E. Method for preparing europium activated yttrium oxide and gadolinium oxide phosphors, P (9) 313*c*.
Roques, B. See Duval, R.
Rosa, C. See Nazaruk, S.
Rosa, C. J., and Hagel, W. C. Film-thickness determination of nitrogen diffusion in zirconium nitride, (5) 194*g*. Oxygen diffusion in hypostoichiometric zirconium oxide in the temperature range of 875° to 1050°C, (4) 148*j*. Oxygen-ion diffusivity in hypostoichiometric zirconium dioxide, (8) 295*j*.
Rose, G. Is waste disposal becoming a cost factor for the glass container industry and manufacturers of other packing materials? (9) 306*c*.
Rose, H. E., and English, J. E. Effect of particle size characteristics on the differential thermal analysis of powdered materials, (1) 21*f*.
Rosen, A. See Eylon, D.
Rosen, B. Homogeneous fatigue processes in viscoelastic polymers, B (1) 41*g*.
Rosen, J. E. See Kuenstle, J. F.
Rosen, J. J. See Tien, T. Y.
Rosenbaum, S. D. See Loro, A.
Rosenberg, D. J. See Krakauer, S.; Pall, D. B.
Rosenberg, H. M., and Wigmore, J. K. Acoustic paramagnetic resonance of Ni^{2+} in potassium magnesium fluoride, (1) 24*g*.
Rosenberg, M. A. Hermetically sealed capacitor, P (11) 376*i*.
Rosenberg, P. E. Subsolidus relations in the system $CaCO_3$-$MgCO_3$-$FeCO_3$ between 350° and 550°C, (4) 157*e*.
Rosenfeld, J. L. Stress effects around quartz inclusions in almandine and the piezothermometry of coexisting aluminum silicates, (7) 269*j*.
Rosenfield, A. R. See Hahn, G. T.
Rosenheinrich, R. See Herlet, A.
Rosenzweig, R. High frequency transistor structure with two-conductivity emitters, P (5) 183*d*. Semiconductor devices and methods of making them, P (6) 223*h*.
Roseveare, G. H. Field tests for the common mineral elements, (2) 69*f*.
Roshal, J. See Sherr, A. E.
Rosicky, J. Differential thermal analysis apparatus with interchangeable measuring heads, (7) 260*a* See Loub, J.
Rosig, H. Enameling of cast iron bath tubs and stoves, (10) 336*h*.
Rosin, S., and Isreell, J. Chemistry furnace, P (2) 72*d*.
Rosinski, E. J. See Plank, C. J.
Rosner, D. E., and Allendorf, H. D. Kinetics of the attack of high-temperature molybdenum and tungsten by atomic oxygen, (4) 141*i*.
Rosner, D. E., and Epstein, M. Condensation-enhanced vaporization rates in nonisothermal systems, (6) 231*f*.
Ross, B. Semiconductor device having improved resistance to radiation damage, P (11) 378*c*.
Ross, C. S., Bergquist, H. R., Monroe, W. H., Fahey, J. J., and Ross, M. Natroalunite in Upper Cretaceous sedimentary rocks, north-central Texas, (6) 229*e*.
Ross, D. L. Luminescent material and [liquid] laser apparatus utilizing said material, P (9) 312*f*.
Ross, F. M. Diamond reclamation—now and in the 70's, (11) 367*f*.
Ross, G. J. Structural decomposition of an orthochlorite during its acid dissolution, (1) 38*c*.
Ross, H. U. See Stangway, P. K.
Ross, J. Method for treating raw pigmentary titanium dioxide, P (8) 288*b*.
Ross, J. W. Glass electrode composition, P (4) 98*j*.
Ross, M. See Ross, C. S.
Ross, R. A., and Taylor, A. H. Sorption of ethylamine on silica and silica xerogel, (1) 37*d*.
Ross, R. E. Glass bending furnace, P (6) 212*a*.
Rossi, J. A. See Keune, D. L.
Rossi, J. A., Holonyak, N., Jr., Dapkus, P. D., Williams, F. V., and Burd, J. W. Laser transition and photon energy of GaAs in the lightly doped limit, (9) 324*d*.
Rossi, R. C. Thermal expansion of BeO-SiC composites, (7) 251*j*. Thermal-shock-resistant ceramic composites, (8) 279*h*. See Carnahan, R. D.; Cost, J. R.
Rossi, V. A. See Tarneja, K. S.
Rossiter, P. H. Slurry feeder, P (11) 379*h*.
Rossmaier, V., and Langen, J. Utilization of waste heat from glass furnaces to generate electric power, (9) 316*d*.
Rostoker, D. Method of making synthetic marble, P (4) 103*a*.
Rosu, D. P., Bujor, I., Chira, I., and Rosu, M. Magnesite and chrome-magnesite refractories production at the factory, (4) 104*h*.
Rosu, M. See Rosu, D. P.
Rosvold, W. C. Method of making semiconductor diodes, P (6) 222*i*. Multiple semiconductor device, P (10) 345*c*. See Legat, W. H.
Rosvold, W. C., and Legat, W. H. Isolated cathode array semiconductor, P (9) 312*c*.
Rosztoczy, F. E. Fabrication of solid thin film capacitor, P (7) 256*g*.
Roth, C. See Sims, S. D.
Roth, D. J. Copper base friction material with dispersed spinels, P (6) 229*d*.
Roth, H. See Steinmetz, E.
Roth, J. F. See Levy, R. M.
Roth, M. See Nitzsche, S.
Roth, R. S. See Negas, Taki.
Roth, W. L. See DeVries, R. C.
Rothe, A. See Hofmann, U.
Rothem, T. See Kedem, D.
Rothenberg, P. Crackle enamels, (6) 207*g*. Cut-out shapes for enameled wall pieces, (7) 244*e*. Enameled garden lantern, (7) 244*a*. Enameled wall panels, (6) 206*c*. Scrolled enamels, (8) 273*i*.
Rotolico, A. J. Nozzle and gas mixing arrangement for powder type flame spray gun, P (10) 337*d*.
Rotsey, W. B., Veevers, K., and McDonald, N. R. Effect of strain rate, environment, and surface condition on the modulus of rupture of beryllia, (4) 133*i*.
Rottmann, J. See Naoumidis, A.
Roubin, M. P., and Paris, J. M. Preparation of vanadium carbonitrides crystallizing in the cubic δ-V(C-N) system, (8) 296*d*.
Roubin, M. P., Paris, J. M., and Paris, R. A. Solid solutions of the transition metal nitrides and oxynitrides and methods of preparation thereof, P (4) 107*j*.
Routschka, G. Testing of refractories for construction and repair work as seen from the literature, (6) 217*b*. See Koehler, E. K.
Routschka, G., and Buttgereit, C. Bloating of clays and refractory products, especially ladle brick, (9) 308*h*.
Rovnyak, R. M. See Cook, B. C., Jr.
Rowe, G. E. Apparatus for moving newly formed glassware articles onto a continuously moving conveyor, P (1) 10*i*. Mold closing boost mechanism for glassware forming machine, P (11) 371*i*.
Rowe, G. L., and Wilson, J. R. Method of uniformly heating an annular carbonaceous body, P (2) 59*h*.
Rowe, J. J., Fournier, R. O., and Morey, G. W. System water-sodium oxide-silicon dioxide at 200°, 250°, and 300°, (11) 387*e*.
Rowe, P. E. See Copley, J. R.
Rowe, S. H., and Welford, W. T. Surface topography of nonoptical surfaces by projected interference fringes, (4) 121*j*.
Rowland, G. R. See Horak, W.
Rowland, J. F. See Iwasaki, H.
Rowlett, B. J. See Pobst, D. F., Jr.
Rowlinson, J. S. Melting at high pressure, (4) 144*c*.
Roy, C. See Evans, A. G.
Roy, D. M. See Ragone, S. E.
Roy, D. W. Method for preparing pure stable ZnSe powder, P (10) 349*c*. See Carnall, E., Jr.
Roy, D. W., and Parsons, W. F. Hot-pressing titanium dioxide, P (11) 371*a*. Method of forming zinc selenide infrared transmitting optical elements, P (10) 339*a*.
Roy, H. Electrochemical behavior of some interstratified clay minerals, (11) 384*h*.
Roy, P., and Fuerstenau, D. W. Heat of immersion of alumina into aqueous sodium dodecyl sulfonate solutions, (1) 30*b*.
Roy, R. Gel route to homogeneous glass preparation, (8) 276*a*. See Aramaki, S.; Caslavska, V.; Dachille, F.; Datta, R. K.; Joubert, J. C.; McCarthy, G. J.; Muller, O.; Sarjeant, P. T.
Roy, R., and Greer, R. T. Photon trapping in TiO_2 and simple oxides, (4) 149*h*.
Roy, R., and White, W. B. High-temperature solution (flux) and high-pressure solution (hydrothermal) crystal growth, (10) 355*b*.
Roy, S. See Mukherjee, D. K.
Roy, S. B. Suitability of talc magnesite for insulating firebrick and other brick, (1) 13*g*. See Bhadra, A. K.
Royce, E. B. See Ahrens, T. J.
Royce, M. R. Color picture display containing a red-emitting europium-activated yttrium oxysulfide phosphor, P (5) 182*j*. Rare earth activated yttrium and gadolinium oxychalcogenide phosphors, P (4) 116*e*.
Rozen, A. A. See Matyushenko, N. N.
Rozenblit, A. B. See Rastyapin, V. A.
Rozgonyi, G. A. See Polito, W. J.
Rozgonyi, G. A., and Polito, W. J. Preparation of thin films of vanadium (di-, sesqui-, and pent-) oxide, (5) 181*d*.
Rubel, P. A. Process for halogenating molten metals, P (1) 24*a*.
Ruben, S. Electrical resistor, P (2) 64*b*.
Rubenstein, C. See Fielden, J. H.
Rubenstein, M. Liquidus solubilities of CdS in a metals solvent, (9) 324*f*. Oxidation of GaP and GaAs, (1) 34*a*. Solution growth of some II-VI compounds using tin as a solvent, (8) 298*a*. See Straumanis, M. E.
Rubenstein, M. S. See Faust, J. W., Jr.
Ruberoid Co. Artificially colored mineral granules, P (5) 180*d*.
Rubin, J. J. See Smith, Richard G.; Van Uitert, L. G.
Rubin, J. J., Van Uitert, L. G., and Levinstein, H. J. Growth of single crystal niobates for electrooptic and nonlinear applications, (6) 233*d*.
Rubino, N. See Collins, J. H.
Rubisch, O. Body of industrial carbon with an oxidation inhibiting coating and method of producing such bodies, P (11) 374*f*. See Fitzer, E.
Rublevskii, I. P. See Galdina, N. M.
Ruch, H. Burner projecting into a rotary kiln, P (10) 348*c*.
Ruch, J., and Dupuy, J. Effect of fusion on the thermoelectric force of silver halides, (6) 232*d*.
Ruch, R. R. Neutron activation analysis at the Illinois State Geological Survey, (9) 315*j*.
Rud, B. M. See Samsonov, G. V.
Rudd, M. O., and Woronoff, A. M. Method for processing of ophthalmic lens, P (6) 213*e*.
Ruddlesden, K. See Jones, D. W.
Rudestedt, S. J. E. See Polasek, K. H.
Rudko, R. I. See Klein, C. A.
Rudman, P. S. Solubility limit and diffusivity of carbon in molybdenum, (1) 37*i*.
Rudnev, N. A., and Bil'kevich, I. N. Coprecipitation in the system GeS_2-InS_2, (7) 264*d*.
Rudnitskii, Yu. P. See Zhabotinskii, M. E.
Rudy, E., Brukl, C. E., and Windisch, S. Constitution of niobium(columbium)-molybdenum-carbon alloys (1) 26*j*.
Rudyak, I. N. See Karaulov, A. G.
Rue, C. Shape in extruded grain, (11) 367*g*. See Kistler, S. S.
Rueb, F. Drying plants for ceramic shapes, (7) 261*d* Screening machines for wet and dry screening, (7) 259*b*. Wet separators for dust extraction, (4) 118*i*.
Ruechardt, H. See Dorendorf, H.
Ruedorff, W. See Pausewang, G.
Ruedorff, W., Stoessel, A., and Schmidt, V. Alkali metal thio- and seleno-compounds of transition metals (IV) thio- and seleno-compounds of platinum, (5) 192*c*.
Rueter, H., Cherdron, E., and Fassle, F. Production of alpha-calcium sulfate hemihydrate, P (4) 93*a*.
Rueter, H., Haerter, M., Cherdron, E., and Scheuermann, E. Method of treating titanium ores with hydrochloric acid to produce titanium tetrachloride therefrom, P (2) 74*g*.
Ruettiger, K., and Mantey, P. G. Testing and suitability of refractory materials for lining vessels for vacuum melting of steel, (4) 105*d*.
Ruff, I. Role of water in electron transfer reactions (II,III), (6) 237*a*.
Rugg, O. I. [Bent] laminated glass assembly, P (4) 98*i*.
Ruggieri, D. J. See Sowers, H. L.
Ruggiero, E. M. Method for bonding silicon semiconductor devices, P (11) 377*g*. Ohmic contacts consisting of a first level of molybdenum-gold [and] mixture of gold and vanadium and a second level of molybdenum-gold, P (6) 223*b*.
Ruiz, J. J. Process for recovery of magnesium compounds from magnesium carbonate and calcium carbonate bearing materials, P (1) 24*c*.
Ruka, R. J., Bauerle, J. E., and Dykstra, L. Seebeck coefficient of a $(ZrO_2)_{0.85}(CaO)_{0.15}$ electrolyte thermocell, (5) 199*f*.
Rump, H. See Schrader, R.
Rumpf, H. See Pietsch, W.
Rumpf, K. Influence of firing on strains in ceramic articles, (7) 253*i*.
Rumsey, J. C. V., and Roberts, A. L. Delayed fracture and creep in silicon carbide, (4) 130*i*.
Rumyantsev, P. F. See Toropov, N. A.
Runciman, W. A. See Hughes, A. E.
Rupp, L. W., Jr. See Walsh, W. M., Jr.
Ruscoe, M. J. H. See Short, M. A.
Ruse, G. See Chernow, F.
Russ, M. J., and Kennedy, D. I. Effects of double insulating layers on the electroluminescence of evaporated ZnS:Mn films, (4) 110*d*.
Russell, K. C. Linked flux analysis of nucleation in condensed phases, (1) 31*h*.
Russell, L. K. See Leant, W. H.
Russell, R., Jr. See Bailey, J. T.; Hench, L. L.; Miller, R. J.
Russell, R. G. G. See Fleisch, H.
Russell Constructions, Ltd. Vibratory mounting for sieves and like apparatus, P (8) 288*e*.
Russi, J. N. Decorative incandescent lamp, P (11) 371*e*.
Rustambekyan, S. F. See Manvelyan, M. G.
Rusu, E. Influence of crystallization on proper-

ties of glasses in the Fe_2O_3-BaO-B_2O_3 system, (10) 337*i*.
Rutland, W. See Herinckx, C.
Rutstein, M. S., and Yund, R. A. Unit-cell parameters of synthetic diopside-hedenbergite solid solutions, (10) 363*d*.
Rutz, R. F. Solid state transformer, P (8) 283*h*. See Marinace, J. C.
Ruzdic, E. See Krleza, F.
Ruzek, J. Thermal expansion and volume stability of baddeleyite-corundum refractories, (6) 217*c*.
Ruzycki, J. See Hausen, D. M.
Ryabchenko, V. I. See Ovcharenko, F. D.
Ryabov, V. A. Role of surface in the physical and chemical properties of glass, (2) 50*j*. See Aleshin, B. N.; Derjaguin, B. V.
Ryabov, V. A., Fedoseev, D. V., Kireev, P. S., and Afonina, N. S. Flexibility of glass fibers, (2) 49*j*.
Ryabova, L. A., and Savitskaya, Y. S. Preparation of thin films of some oxides by the pyrolysis method, (2) 63*c*.
Ryan, C. E., Berman, I., Marshall, R. C., Considine, D. P., and Hawley, J. J. Vapor-liquid-solid and melt growth of silicon carbide, (5) 202*g*.
Ryan, F. M., and Miller, R. C. Photoluminescence and pair spectrum in boron phosphide, (2) 81*h*.
Ryan, J. R. See Searight, C. E.
Ryan, T. J. Tester for determining the semiconductor material type of transistors, P (11) 379*b*.
Ryan, W. E. See Hedler, R. A.
Ryba, E. History of crystallography, (1) 40*d*.
Rybaltovskii, A. O. See Evlanova, N. F.
Ryder, J. F. See Majumdar, A. J.
Ryder, P. L., and Pitsch, W. Accuracy of orientation determination by selected area electron diffraction, (9) 314*i*.
Ryder, R. J., and McMackin, J. J. Some factors affecting stack emissions from a glass container furnace (I), (10) 338*j*.
Ryder, R. J., and Taylor, E. C. X-ray analysis of glass, (10) 338*e*.
Rykalin, N. N., Kulagin, I. D., Kudinov, V. V., and Sinolitsyn, E. K. Methods of raising the quality of metallized ceramic coatings, B (5) 204*g*.
Rykken, K. J. Abrasive flap wheel, P (2) 43*f*.
Ryl'nikova, A. G. See Malkin, V. I.
Ryshkewitch, E. New problems and results in the field of beryllium oxide ceramics, (4) 108*e*.
Ryss, I. G. See Tul'chinskii, V. B.
Ryzhkova, T. P. See Vil'k, Yu. N.

Saad, O. C., and Otenbaker, J. T. Drain tile structure, P (4) 102*e*.
Saalfeld, H., Matthies, H., and Datta, S. K. New aluminum oxide hydrate with the structure of β-alumina, (2) 80*i*.
Saari, E., von Knorring, O., and Sahama, T. G. Niobian wolframite from the Nuaparra pegmatite, Zambezia, Mozambique, (8) 295*e*.
Sabastiani, C. Spraying method and apparatus to lubricate punch surfaces of tableting machines, P (11) 379*h*.
Sabel, A. H. See Watts, C. R.
Sacchi, G. See Fasano, G.
Sachenko, V. P. See Demekhin, V. F.
Sacher, I. Manufacture of foamed concrete, (7) 245*a*.
Sacher, P. A. See Heath, D. F.
Sack, H. S. See Byer, N. E.
Sackett, W. J., Sr. Twin rotor high efficiency crusher, P (4) 126*c*.
Sadek, H. See Helmy, A. K.
Sadler, A. G. Ceramics in a changing world (II) electronic and special ceramics, (1) 40*e*.
Saeger, H. See Nickel, H.
Saeman, W. C. Preparation of pure monocalcium phosphate, P (1) 24*d*.
Saenz, J. P. See Gregg, S. J.
Safford, G. J., Naumann, A. W., and Hallowell, A. L. Low-frequency vibrations of water molecules in beryl, (6) 234*e*.
Saflullin, N. Sh., and Belyaev, E. K. Alkaline decomposition of ilmenites containing chromium, (7) 261*j*.
Safonov, V. V., Korshunov, B. G., and Steblovskaya, S. N. Physicochemical study of the binary salt systems $NbCl_5$-MeCl (Me=Na,K, Rb,Cs), (8) 296*h*.
Safonov, V. V., Korshunov, B. G., and Zimina, T. N. Systems $NbCl_5$-Rb(Ca)Cl, (4) 159*a*.
Safonov, V. V., Korshunov, B. G., Zimina, T. N., and Lbevtsova, Z. N. Phase diagrams of $NbCl_5$-Na(K)Cl, (8) 296*e*.
Safronov, E. K. See Denisova, N. D.
Saga, Senzo. See Niwa, Shohei.
Saha, P. See Bandyopadhyay, T.
Saha, R. See Balian, K. S.
Sahama, T. G. See Saari, E.
Sahama, T. G., Knorring, O. V., and Lehtinen, M. Cookeite from the Muiane pegmatite, Zambezia, Mozambique, (4) 130*a*.
Sahores, J. Specimen changer for an X-ray fluorescence spectrometer, P (4) 122*a*.
Sala, F. J., and Quetsch, J. G. Surface-protected semiconductor devices and methods of manufacturing, P (7) 258*a*.
Saiki, Yoshio. See Takemoto, Kunihiro.
Sainsbury, J. J. See Ford, G. E.
St. John, D. F. See Richards, R. S.
St. Louis, R. V., Whiten, J. G., and Sprouse, N. T. Method for producing boric oxide, P (4) 124*j*.
Sainte, G. See Massart, D. L.
Saito, Fujio. Operation of a laser-pumped ruby maser at 77°K, (5) 181*j*.
Saito, H. See Hirata, Masako.
Saito, Ken. See Yoshida, Masayuki.
Saito, Koichi. See Oda, Zenjiro.
Saito, Mitsuhiro. See Tsuzuku, Takuro.
Saito, Seiichi. See Shiroki, Kenichi.
Saito, Shinroku. See Nomura, Shoichiro.
Saito, Shinroku; Somiya, Shigeyuki; and Okikawa, Shinji. Sintering of cerium oxide, (1) 36*d*.
Saito, Shinroku; Somiya, Shigeyuki; and Tanaka, Mitsuo. Sintering of mixtures in the systems ZrO_2-$MoSi_2$ and ZrO_2-SiC and their properties, (1) 36*h*.
Saito, Shunjiro. See Kuwamoto, Hidehiko.
Saito, Shuntaro, and Shoda, Yuzuru. Construction of furnace sidewalls with insulating firebrick and proper layout of metal fittings based on mechanics, (5) 176*i*.
Saito, Yukinori; Anayama, Takeshi; Yasohama, Kazuhiko; Yasukouchi, Ko; and Onodera, Yutaka. Upper critical field H_{c2} of NbN film prepared by reactive sputtering, (11) 388*c*.
Sajo, I. See Rady, G.
Sakai, Chisato. Repair of cupola using gunning material, (7) 251*j*.
Sakai, Tooru. Applications of refractory concrete in France and England, (5) 176*h*.
Sakamoto, Hitoshi. Electroluminescence of lead-containing zinc sulfide films, (4) 134*i*.
Sakamoto, Yoshimitsu. See Nakajima, Nagahisa; Yokomizo, Keiji.
Sakane, Hideo. See Okada, Kazuo.
Sakane, K. See Kubota, H.
Sakata, Kimiko, and Sakata, Tamio. Preparation and structural data of $(Ti_{1-x}V_x)O_2$, (8) 296*b*.
Sakata, Tamio. See Sakata, Kimiko.
Sakimoto, Sadanori. See Yamada, Tamotsu.
Sakka, Summio. Phototrophy of alkaline earth tungstates doped with bismuth, (4) 149*h*.
Saksaganskii, G. L. See Gagen-Torn, V. K.
Sakudo, Tunetaro. See Unoki, Hiromi.
Sakuma, Yousukou. Tile-setting frame apparatus, P (7) 254*b*.
Sakurai, Junji, and Shinjo, Teruya. Neutron diffraction of manganese ferrite prepared from aqueous solution, (2) 80*h*.
Sakurai, Shigeo. See Hayashi, Takeshi.
Sakurai, Tadashi. See Nishino, Tadashi.
Sakurai, Tai. See Nakamichi, Hiroshi; Seki, Yachiho.
Sakurai, Takemaro. See Ishigame, Mareo.
Sakurai, Takemaro, and Ishigame, Mareo. Growth of nickel oxide crystals by solar furnace fusion, (7) 266*g*.
Sakurai, Takemaro; Ishigame, Mareo; and Arashi, Haruo. Absorption spectrum of Ni^{2+} ions in spinel, (11) 383*b*.
Sakurai, Takemaro; Kamada, Osamu; and Ishigame, Mareo. Uranium dioxide crystals grown by a solar furnace, (7) 270*e*.
Sakurai, Toshio; Ueda, Toshiro; Hashimoto, Masami; and Fukunaga, Makoto. Observations on early hydration of aluminous cement, (11) 373*h*.
Saleh, J. M. Kinetics of interaction of sulfur dioxide with clean and oxidized metal films of iron, nickel, and lead, (9) 324*b*.
Sales, H. Corrosion of ceramic decoration during machine washing, (1) 15*g*.
Salgado, P. G. High temperature stress free thermocouple junction, P (7) 260*i*.
Salim, A. See Nandi, D. N.
Saller, R. See Pastoors, E.
Salmang, H., and Scholze, H. Physical and Chemical Principles of Ceramics, B (10) 365*e*.
Salomon, R. E. See Bendoraitis, J. G.; Meehan, J.
Salton, J. R. Heat-resistant [refractory core] wall, P (10) 342*e*.
Salvat, J. O. See Montagut-Buscas, M.
Salzmann, E., Plieninger, T., and Dransfeld, K. Attenuation of elastic surface waves in quartz at frequencies of 316 MHz and 1047 MHz, (7) 263*e*.
Samelson, H. See Brecher, C.; Lempicki, A.
SAMES. See Societe Anonyme de Machines Electrostatiques.
Samms, J. A. C., and Evans, B. E. Thermal dissociation of $Ca(OH)_2$ at elevated pressures, (9) 332*b*.
Sampson, J. L. See Adamski, J. A.
Sams, R. H., and McCready, N. W. Expanded silicate particles, P (9) 317*d*.
Samsonov, G. V. See Bazhenova, L. N.
Samsonov, G. V., Lapshov, Yu. K., Podchernyaeva, I. A., Fomenko, V. S., Erosov, Yu. I., and Dudnik, E. M. Preparation and physical properties of alloys of the W-LaB_6 system, (7) 268*b*.
Samsonov, G. V., Paderno, Yu. B., and Rud, B. M. Physical properties of germanides of ceric group and yttrium rare earth metals, (5) 198*c*.
Samsonov, G. V., Podchernyaeva, I. A., Fomenko, V. S., and Kondratov, I. Ya. Thermoemission of tungsten alloyed with lanthanide oxides, (9) 332*j*.
Samuel, R. L. See Butcher, J. W.
Samuelson, W. H. Piezoelectric crystal manufacturing apparatus and method [X-ray diffraction] for location of atomic planes relative to the crystal surface, P (9) 313*c*.
Samusenko, A. G. Ferroelectric control circuits, P (10) 344*h*.
Samuseva, R. G. See Plyushchev, V. E.
Samygin, V. D., Barsky, L. A., and Angelova, S. M. Mechanism of mutual flocculation of particles of different size, (7) 253*j*.
Sandbank, C. P. [Method of making] microwave generators, P (10) 345*h*.
Sandbank, C. P., and Butler, M. B. N. Scanned line radiation source using a reverse biased *pn* junction adjacent a Gunn diode, P (8) 283*a*.
Sanborn, W. E. See Colgan, J. D.
Sanborn, W. E., and Lindsley, J. F. Process for preparing a crystalline zeolite catalyst composite, P (1) 24*a*.
Sandberg, H. See Bergh, S.
Sander, L. F., and Healy, G. W. Transformation of CaO to CaS at 1400° to 1650°C, (4) 162*a*.
Sanders, D. P. Use of both silicon oxide and phosphorus oxide to mask against diffusion of indium or gallium into germanium semiconductor device, P (2) 67*c*.
Sanders, J. E. See Allen, R. C.
Sanders, R. F. See Giovanetti, A.
Sanders Associates, Inc. Thin film piezoelectric oscillator, P (5) 184*f*.
Sandmair, K. See Hofmann, U.
Sands, A. G. See Kohn, E. J.
Sandwith, C. J. Method of determining preferred orientation in metals, P (7) 261*a*.
San Fernando Electric Mfg. Co. Hermetically sealed capacitor, P (11) 376*i*.
Sanford, E. A. See Little, J. R.
Sanford, W. W. Method of manufacturing piezoelectric crystal assemblies, P (4) 115*e*.
Sanger, P. L. See Dawson, B.
Sanguigni, J. A. See Eilerman, G. E.
San Marino Electronic Corp. Empty bottle bottom and neck inspection machine using radiation sensitive means, P (4) 98*d*. Empty bottle inspection machine, P (6) 212*a*.
Sanner, G. See Schrader, R.
Sannikov, Yu. I. See Margulis, E. V.
Sano, Shiro. See Ishii, Eiichi; Kato, Shuzo.
Sansom, K. G., Smith, R. G., and White, D. Cation-exchange capacity of layer-lattice minerals (I) discrepancies between two methods of c.e.c. determinations on montmorillonite; (II) two types of cation-exchange sites on montmorillonite and their determination, (4) 127*j*.
Santillo, G. R., Jr. See Clark, K.
Sanvordenker, V. See Tien, T. Y.
Saparin, G. V. See Spivak, G. V.
Sapet, J. C. See May, P.
Sapoff, M., and Froemel, J. G. Low noise thermistor assembly and method, P (9) 312*e*.
Saponara, D. Radiant burner, P (7) 261*g*.
Sarapuu, E. Rock breaking method and apparatus, P (11) 382*j*.
Sare, E. J. See Angell, C. A.
Sargeant, H. G. Process for chlorinating titaniferous ores, P (4) 125*i*.
Sargent, J. C. See Clayton, W. A.
Sarjeant, P. T., and Roy, R. Ti^{4+} coordination in glasses in RO-TiO_2 systems, (4) 97*j*.
Sarkisov, G. G. See Moroz, I. I.
Sarkozy, F. A. Valve lever [pneumatic] and latch mounting mechanisms for glassware forming machine, P (11) 372*c*.
Sarraf, E. M. Spacer for basic refractory brick in metallurgical vessels, P (9) 309*e*.
Sarver, J. F. See Hummel, F. A.
Sarver, J. F., and Apple, E. F. Calcium halophosphate phosphors, P (6) 220*h*.
Sarver, J. F., and Louden, W. C. Calcia-magnesia-alumina seal compositions, P (7) 255*g*.
Sasagawa, Yoshiaki. See Matsuzaki, Teizo.
Sasaki, Hiromu. Process for producing butterfly twin barium titanate single crystals and barium titanate mixture used therein, P (2) 66*h*. See Matsuo, Yoshihiro.
Sasaki, Ichiemon. See Kurosawa, Toshio.
Sasamoto, Tadashi. See Torikai, Naochika.
Sasek, L. Measurement of density and volume expansion coefficient of glasses at high temperatures, (6) 210*a*. Simple apparatus for measuring viscosity of glasses in the range 10^4–$10^{2.5}$ P, (1) 8*i*. See Stanek, J.
Sastry, M. D. See Rao, K. V. S.
Satalkin, A. V., and Sointseva, V. A. Use of plastograms to select additives for lowering the freezing temperature of cement mortars, (4) 92*b*.
Satalkin, A. V., and Yasevich, A. I. Structure of gliezh-concrete, (8) 274*a*.
Satarin, V. I., Syrkin, Ya. M., and Mirak'yan, V. M. Chemistry of hydration of rapidly hardening slag portland cement, (1) 2*e*.
Satava, V. See Komrska, J.; Sestak, J.
Satava, V., and Baldrian, J. Mechanism of dehydration of gypsum and rehydration of hemihydrate, (1) 3*d*.
Satczec, Z., and Szymborski, W. Tar-bonded dolomite refractories and their behavior in oxygen converters, (4) 105*d*.
Sato, Atsushi, and Yamauchi, Masakatu. Cathode ray tube screen structure, P (2) 64*g*.
Sato, Hisanao. See Itoh, Kohji.
Sato, Katsuo. See Tsuji, Shigeru.
Sato, Katsuo, and Irie, Toshiaki. Diffusion type semiconductor device having plural protective coatings, P (5) 182*d*.
Sato, Kenro. See Murakami, Keiichi.
Sato, Sennosuke. Electric furnace having a heating element of carbon or graphite for pro-

ducing temperatures under high pressures, P (1) 23*a*.

Sato, Shuichi. See Koizumi, Haruhiko.

Sato, Tadao. See Hamada, Shuichi.

Sato, Yoshiki. Optical study of electronic structure of graphite, (2) 81*f*. See Iwata, Tadao.

Satterley, B. L. See Ballard, L. H.

Sauer, K. H. Observations concerning the effect of gases on sheet steel surfaces, (10) 336*i*.

Sauer, W. E. See Zavitsanos, P. D.

Saul, R. H. Defect structure of GaP crystals grown from gallium solutions, vapor phase and liquid phase epitaxial deposition, (10) 351*g*.

Saull, R. C. See Pointon, A. J.

Saunders, A. E., and Kubichan, R. E. Strengthening glass by multiple alkali ion exchange, P (6) 213*f*.

Saunders, G. L. See MacPherson, A. R.

Saunders, V. L., and West, W. Epitaxial growth of AgBr crystals from the melt and formation of oriented bubbles, (10) 353*c*.

Saunders Roe & Nuclear Enterprises, Ltd. Coating of the surfaces of light transparent materials associated with light sources, P (4) 98*j*, P (6) 212*i*.

Savage, E. L. Ultrasonic disaggregations of sandstones and siltstones, (8) 286*b*.

Savage, H. See Kruger, O. L.

Savage, J. See Martin, A. J.

Savage, J. T. See Trevorrow, L. E.

Savelli, G., and Wedepohl, K. H. Geochemical investigations of travertines, (9) 322*a*.

Saville, P. A. See Schneider, E. J.

Savin, L. S., Barinov, Yu. D., and Nesterova, A. I. Torsion test for the determination of the adherence of porcelain enamels to steel, (2) 71*g*.

Savinskaya, A. A. See Novokhatskii, I. A.

Savitskaya, Y. S. See Ryabova, L. A.

Savole, J. E. See Cox, D. L.

Sawamoto, Kenichi. See Ashida, Toshio.

Sawaoka, Akira, and Kawai, Naoto. Effect of hydrostatic pressure on magnetic anisotropy of ferrous and ferric ions in ferrites with spinel structure, (2) 76*b*.

Sawatari, Yuji. Tunneling characteristics of Al-Al_2O_3-Sb junctions, (8) 300*b*.

Sawatzky, E. See Kay, E.

Sawatzky, E., and Kay, E. Preparation of garnet films by sputtering, (6) 220*j*.

Sawatzky, G. A., Coey, J. M. D., and Morrish, A. H. Moessbauer study of electron hopping in the octahedral sites of Fe_3O_4, (9) 325*j*.

Sawchuk, P. Ceramic seals and bearing members, P (2) 58*a*.

Sax, N. I. Dangerous Properties of Industrial Materials, B (4) 166*j*.

Saxena, A. N. Multiplane metal-semiconductor junction device, P (9) 312*e*.

Saxena, A. N., and McDade, J. C. Distributed barrier metal-semiconductor junction device, P (9) 312*e*.

Saxena, S. C. See Mathur, S.

Saxena, S. K., and Hollander, N. B. Distribution of Fe and Mg in coexisting biotite, garnet, and cordierite, (7) 265*f*.

Sayers, P. G. See Chandler, H. H., Jr.

Sazhin, V. S., Moshkina, M. K., and Dementeva, S. D. Preparation of clay concentrate from kaolin, (7) 262*i*. Sintering of low alkaline charges, (7) 268*c*.

Sazhin, V. S., and Pankeeva, N. E. Interactions in the quaternary system Na_2O-Al_2O_3-SiO_2-H_2O at 290°C, (7) 267*f*. Properties of sodium hydroaluminosilicate of the sodalite type crystallizing at 280°C in the system Na_2O-Al_2O_3-SiO_2-H_2O, (8) 296*h*.

Sazhin, V. S., Shor, O. I., Arakelyan, O. I., and Volkovskaya, A. I. Conditions of formation and some physicochemical properties of sodium-calcium hydroaluminosilicate, (8) 289*d*.

Sazonova, M. V. Coatings made of oxygen-free high-melting silicon compounds and a silicate binder, B (5) 204*f*.

Scandellari, B. See Bizouard, M.

Scanlan, I. F. See Drake, C. F.

Scanlan, J. Elastic stiffness and the economics of fiber-reinforced plastics, (1) 6*f*.

Scardefield, J. E. See Foster, L. M.

Scaroni, A. Facilities for in-pile tests of cirene fuel rods, (7) 260*d*.

Scarpino, M. R. Power of expression, (7) 244*c*.

Scattergood, E. M., and Lightfoot, E. N. Diffusional interaction in an ion-exchange membrane, (11) 383*g*.

Schadel, J. See Arndt, H. H.

Schaefer, R. J. See Glicksman, M. E.

Schaefer, W. R. See Marino, J.

Schaeffer, B. Photoelastic study of dislocation pileup in colored LiF, (1) 34*j*. See Dupuy, C.

Schaeffer, H., and Maywald, H. Na^+ diffusion in Na_2O-$2SiO_2$ glass containing NaCl and $NaSO_4$, (9) 306*j*.

Schafer, F. W. Two pragmatic views on vasa diatreta (I), (4) 90*j*.

Schafer, H. See Spear, K. E.

Schafer, H., Giegling, D., and Rinke, K. Tungsten-oxygen-iodine system (III) thermal behavior of tungsten dioxide diiodide, (5) 202*b*.

Schafer, W., and Blass, R. Binders for sheet glass, P (5) 174*j*.

Schaffer, H. J. See Peterson, G. D.

Schaffer, P. S. See Campbell, W. B.

Schaffner, H. J. Rheological behavior of sand vibrating in rotary viscometer, (5) 188*b*.

Schafft, H. W. Method for polarizing piezoelectric material, P (6) 222*e*.

Schara, M. See Cevc, P.

Scharfetter, D. L. See De Loach, B. C., Jr.

Schatz, M. See Hofmann, U.

Schatzer, L. Dutch East India Company as an importer of Chinese porcelain, (11) 367*i*. Rational analysis of feldspar, clays, kaolins, and fine ceramic bodies, (4) 121*b*.

Schaub, P. W. See Goodwin, R. J.

Schaudinn, K. New 20 kV open-air insulator guaranteed to withstand fog and salt, (7) 254*a*.

Schauer, V. See Jakes, D.

Schawlow, A. L. See Greene, R. L.; Wong, J. Y.

Schechter, M. Preparation of crystalline UO_2 by thermal decomposition of $UOCl_2$ dissolved in molten UCl_4, (10) 359*e*.

Schechter, R. S. See Mannheimer, R. J.

Schedin, U., and Frydman, M. Studies on the hydrolysis of metal ions (LIX) uranyl ion in magnesium nitrate medium, (10) 361*i*.

Scheel, H. J. Crystal growth of metastable quartz solid solutions in MgO-Al_2O_3-SiO_2 glasses, (7) 264*h*.

Scheffler, P. H. Controllable flow pump, P (11) 374*g*.

Scheidegger, R. See Baukal, W.

Scheidt, P. See Zettlemoyer, A. C.

Scheller, W. See Neuenschwander, E.

Schellinger, A. K. See Spedden, H. R.

Scheludko, A., Radoev, B., and Kolarov, T. Tension of liquid films and contact angles between film and bulk liquid, (10) 362*i*.

Schembra, F. W. See Hofmann, U.

Schembs, W. See Meer, W.

Schempf, J. M. See Freeberg, F. E.

Schenk, G. H., Dilloway, K. P., and Coulter, J. S. Determination of nickel(II) by quenching of the fluorescence of aluminum-1-(2-pyridylazo)-2-naphthol and direct fluorometric determination of cobalt, (8) 284*j*.

Scherzberg, H. See Hoppe, H.

Scherzer, O. See Heimann, W.

Scheuermann, E. See Rueter, H.

Scheurlen, D. See Hofmann, U.

Scheve, J. See Walter, H. P.

Schicht, R. See Paulitsch, P.

Schickell, W. D. See Gerstein, B. C.

Schieber, M. Effects of high magnetic fields on the isothermal dissolution and growth rates of $Fe(NH_4)_2{\cdot}6H_2O$ and $KAl(SO_4)_2{\cdot}12H_2O$ seed crystals, (4) 133*g*.

Schieber, M., Grill, A., and Shidlovsky, I. Growth of mixed cation iron garnets in the ytterbium-gallium and yttrium-calcium silicate systems, (10) 354*i*.

Schier, H. See Lehovec, K.

Schier, K. H., Bauer, W., and Ehrig, R. Dependence of gas bubble formation in glass melts on the furnace atmosphere, (4) 95*h*.

Schile, R. D. Process for making filamentary materials, P (11) 375*a*.

Schiller, C., and Jarrouse, B. Anomalous diffusion of X rays in semiconductors of the blende type, (9) 318*d*.

Schiller, K. K. See Fowler, A.

Schiller, S., Foerster, H., and Lenk, P. Lanthanum hexaboride cathode system for an electron beam generator, P (7) 256*g*.

Schilt, A. A., and Hoyle, W. C. Spectrophotometric determination of copper in alkali metals and hydroxides with 4,4′-dihydroxy-2,2′-biquinoline, (8) 285*e*.

Schimitschek, E. J., and Schumacher, E. R. Liquid laser cell [quartz tube], P (9) 307*g*.

Schindehette, D. J. See Ammerman, F. E.

Schinnerling, F. See Schwiete, H. E.

Schippel, E. Replication procedures for electron microscope photographs of rough ceramic surfaces, (4) 121*d*.

Schirmer, D. See Hueter, L.

Schirmer, O. F. Structure of the paramagnetic lithium center in zinc oxide and beryllium oxide, (9) 330*c*.

Schjeldahl, G. T., Co. Glass fabric structure and method of making the same, P (8) 277*a*.

Schlabach, T. D. See Swisher, J. H.

Schlapp, W. Thin sheets [of alumina] without impurities as the binder, (11) 374*c*.

Schlaudt, C. M. See Overcashier, R. H.

Schlegel, E. CaO-MgO-CaF_2 system, (4) 127*c*. Relations between shrinkage and green density, (9) 314*f*. Thermal decomposition of fluorspar by water vapor, (6) 239*b*.

Schlegel, E., and Schwab, T. Slip casting of magnesium oxide with ethanol, (4) 105*i*.

Schleifer, P., Jarzmik, B., and Kucharski, J. Transparent glass-ceramics—Silital, (10) 338*b*.

Schleifer, P., and Tarczon, T. Synthesized pyroxene and its properties, (4) 124*a*.

Schlesiger, K. Diaphragm-piston pump—ideal for spray-drying plants, (7) 258*i*.

Schleusener, S. A. Laser small-particle detector and method, P (2) 71*j*.

Schlientz, W. J. See Bruss, H. G., Jr.

Schlientz, W. J., and Wiens, B. E. Method of rendering glass surfaces abrasion resistant and glass articles produced thereby, P (7) 249*i*.

Schlinkert, Cl. Experiences during kiln research, especially tunnel kilns, (5) 188*j*.

Schlip, W. H., Jr. See Stoller, A. I.

Schlitter, W. See Pink, P.

Schloemann Akt.-Ges. Apparatus for pouring molten metal, P (11) 374*e*.

Schloemer, H., and Mueller, F. Effect of etching on dislocations in oriented basal flakes of corundum crystals, (1) 27*h*.

Schlosshauer, H., and Wahl, H. Semiconductor device, P (6) 223*f*.

Schluessler, H. See Hennicke, H. W.

Schlueter, H. Domestic dishwashing machines, (1) 15*h*.

Schlueter, K. See Steggewentz, H.

Schmalz, R. F. See Weber, J. N.

Schmalzried, H. See Hohmann, H. H.; Holt, J. B.

Schmeiser, K., Lehmann, K., Ziegler, H. W., and Kowalski, W. Apparatus for monitoring the temperature prevailing in a grate of the type used for drying and calcining shapes, P (1) 22*a*.

Schmeling, G. Method and apparatus for successively metering identical quantities of particulate material, P (4) 118*f*.

Schmersahl, G. W. See Dews, J. N.

Schmets, J. J. See Camozzo, G.

Schmid, A. P. Evidence for the small polaron as the charge carrier in glasses containing transition metal oxides, (2) 49*b*.

Schmid, B. C. Electrostatic separation of dry materials, P (11) 382*a*.

Schmid, F. See Viechnicki, D.

Schmidt, A. See Gugel, E.

Schmidt, A. J. See Greenhow, R. C.

Schmidt, B. L. Glass furnace with two separate throat passages, P (5) 174*g*.

Schmidt, D. L. Ablative antenna window compositions, P (5) 178*i*. See Pirrung, P. F.

Schmidt, E. D. D. See Vedam, K.

Schmidt, E. D. D., Kirk, J. L., and Vedam, K. Variation of the refractive index of diamond with hydrostatic pressure to 7 kilobars, (9) 332*i*.

Schmidt, E. R. See Tauber, K. A. G.

Schmidt, E. W. Dry-pressing in the brick industry, (7) 249*j*.

Schmidt, F. J. Fast warmup cathode, P (6) 221j.

Schmidt, H. See Ilschner, B.; Rohlfs, H. A.

Schmidt, K., and Staude, H. Fluorometric microdetermination of thallium [down to 0.05 μg of Tl^+/ml] in alkali halide single crystals (I) determination in sodium iodide, (6) 226*h*.

Schmidt, N. E. Specific heat and heat of fusion of crystalline boron oxide, (4) 155*d*.

Schmidt, O. See Keller, W.

Schmidt, P. F., van Gelder, W., and Drobek, J. Phosphorus concentration profile and phase segregation in phosphosilicate glass on SiO_2 films, (4) 149*d*.

Schmidt, P. W. Small angle X-ray scattering study of colloidal thorium oxide, (2) 83*d*. See Brill, O. L.

Schmidt, R. See Hauffe, K.

Schmidt, R., and Wernick, J. H. Aluminum-gold contact to silicon and germanium, P (1) 17*h*.

Schmidt, R. L., and Morgan, J. F. Viscosity reduction of alumina hydrate filter cake, P (2) 74*h*.

Schmidt, V. See Ruedorff, W.

Schmidt-Holthausen, H. J., and Backsen, H. Method and apparatus for blending bulk solids, P (11) 379*f*.

Schmier, A. Process of producing ramsdellit, a type of manganese dioxide, P (5) 191*g*.

Schminke, O. W. Forty years of U-type enameling kilns, (1) 4*c*.

Schmit, F. M. Semiconductor method and apparatus, P (11) 378*g*.

Schmitz, H. See Deussner, H.

Schnabel, A. Manufacture of plasterboard from synthetic gypsum, P (8) 274*c*.

Schnabel, H. W. Coated abrasive products, P (1) 1*g*.

Schneider, E., and Wegener, E. Process for the manufacture of white quartz powder, P (7) 263*a*.

Schneider, E. E. See Heilmann, G.; Patankar, A. V.

Schneider, E. J., and Saville, P. A. [Contoured] abrasive cutting tools, P (7) 243*i*.

Schneider, H. See Hein, W.; Poeschmann, H.

Schneider, I. Sodium and lithium M_A centers in KCl, (4) 155*d*.

Schneider, M. See Rodot, H.

Schneider, N. F. See Purviance, L.

Schneider, R. F. See Mackay, R. A.

Schneider, R. R. Rotary kiln construction, P (5) 189*f*.

Schneider, S. J. See McDaniel, C. L.

Schneider, S. J., and McDaniel, C. L. BaO-Pt system in air, (11) 383*c*.

Schneider, W. C. See Busen, K. M.

Schneider, Jos., & Co. Fiber-optic cable comprising a plurality of ribbons, each having a plurality of light conductive fibers, P (4) 98*e*. Fiber-optic cable comprising rows of interleaved light-conducting fibers with masking of fiber portions in zones common to fibers of adjacent rows, P (4) 98*f*.

Schneidner, K. A. G., Jr. Interrelations of the physical properties of lanthanide compounds—melting point, heat of formation, and lattice parameters, (10) 355*i*. Valences of europium and ytterbium in compounds, (10) 363*e*.

Schnell, M. D. Standard cost accounting system for the porcelain enamel industry, (1) 5*b*.

Schnell, W. Drying techniques, (4) 122*f*.

Schnepp, O. See Loewenschuss, A.

Schock, R. N., and Katz, S. Pressure dependence of the infrared absorption of calcite, (10) 359*i*.

Schoeffler, P. W. See Arnold, A. J.

Schoeman, B. J. K. See Preller, G. S.

Schoenbrunn, G., and Schulmeister, R. Destruction of glass by cavitation, (9) 305*j*.

Schoenherr, E. Dislocations and grain boundaries in melt-grown potassium chloride, (7) 265*e*.

Schoenlaub, R. A. Furnace apparatus with a series of hearths, P (6) 228*f*. Oxidation of pyrite, (4) 148*i*.
Schoenthaler, D. Bonding leads to quartz crystals, P (11) 376*g*.
Scholder, R., Rade, D., and Schwarz, H. Lithium plumbates(IV) and stannates(IV), (10) 356*j*.
Scholer, H. G. Method of manufacturing semiconductor devices, P (8) 283*d*.
Scholes, A. B., and Pickard, J. E. Glass having dual protective coatings thereon and a method for forming such coatings, P (5) 174*g*.
Scholes, S. R. Opportunities in Ceramic Engineering, B (6) 241*e*.
Scholl'mayer, K. Museum for glass and jewelry (bijouterie) in Jablonec, Czechoslovakia, (5) 169*j*.
Scholz, S. See Frank, B.
Scholze, H. Explanation of the different effects of water content on the refraction and densities of glasses of various compositions, (6) 209*j*. See Corbach, R.; Grosskopf, K.; Herr, A. M.; Salmang, H.
Scholze, H., and Lowsky, W. Distribution of bubbles in porcelain glazes, (7) 253*j*.
Schoolar, R. B., Riedl, H. R., and Dixon, J. R. Burnstein shift of the fundamental absorption edge of tin telluride, (4) 127*g*.
Schooley, J. F. See Ambler, E.; Pfeiffer, E. R.
Schoonover, R. J. See Nellessen, A. H.
Schoppe, F. Burner for firing a combustion chamber, P (4) 122*i*.
Schorr, J. R., and Everhart, J. O. Thermal behavior of pyrite and its relation to carbon and sulfur oxidation in clays, (9) 308*g*.
Schott, F. W. See Tao, T. F.
Schott, H. Deflocculation of swelling clays by nonionic and anionic detergents, (5) 189*i*. Interaction of anionic detergent and montmorillonite, (4) 123*f*.
Schottmiller, J. See Knox, B. E.
Schrader, M. E. Method of improving the bonding characteristics of glass surfaces, P (4) 100*a*.
Schrader, M. E., and Lerner, I. Method of improving the strength characteristics of glass reinfroced laminates, P (2) 53*d*. Organophosphorus coupling agents for epoxy to glass laminates, P (5) 176*b*.
Schrader, R. See Kneschke, G.
Schrader, R., Arnold, M., and Rump, H. Behavior of bauxite and its phases after mechanical activation (I) mechanical activation of boehmite, (4) 126*j*.
Schrader, R., and Rump, H. Behavior of bauxite and its phases after mechanical activation (III) mechanical activation of corundum, (4) 127*c*.
Schrader, R., Rump, H., and Sanner, G. Behavior of bauxite and its phases after mechanical activation (II) mechanical activation of gibbsite, (4) 127*a*.
Schrage, M. See Iken, H.
Schrager, M. See Collins, F. C.
Schrama, A. H. M. See De Wijn, H. W.
Schrey, F. See O'Bryan, H. M., Jr.
Schreyer, W., and Seifert, F. Compatibility relations of aluminum silicate in the systems MgO-Al_2O_3-SiO_2-H_2O and K_2O-MgO-Al_2O_3-SiO_2-H_2O at high pressure, (7) 264*h*. High pressure phases in the system MgO-Al_2O_3-SiO_2-H_2O, (10) 354*j*.
Schroeder, J. Problems of automatic control of glass tanks, (5) 173*j*.
Schroeder, J. B., and Linares, R. C. Growth of single crystals from nonstoichiometric melts, B (7) 272*g*.
Schroeder, J. W. See Garland, J. K.
Schroeer, D., and Nininger, R. C., Jr. Morin transition in α-Fe_2O_3 microcrystals, (4) 145*c*.
Schubert, P. Energy supply for an average sized container plant with particular emphasis on high pressure waste heat boilers, (6) 209*h*.
Schuele, D. E. See Wong, C.
Schueler, W. A. Method for producing semiconductor nuclear particle detectors by diffusing, P (4) 115*h*.
Schuelke, W. J. See Clark, K.
Schuett, H. W. Isocapillary membranes of bentonite, (6) 234*a*.
Schuett, K. See Neuenschwander, E.
Schuetz, A. Discussion of "Problem of dust measurement in the ceramic industry," (6) 227*c*. Dust measurements in ceramic works—methods and results, (6) 226*d*.
Schuetz, E., Hastik, W., and Nievelstein, M. J. W. E. Method and apparatus for controlling sintering processes in conveyor type sintering machines, P (1) 23*b*.
Schuetz, H. Hints on the selection of the most suitable dust extractor, (4) 117*i*.
Schuetz, W. Practical determination of micro particle size distribution of abrasives by sedimentation, (10) 347*d*.
Schuetze, H. J. See Hennings, K.
Schuetze, H. J., and Hennings, K. Production of circuit devices, P (6) 223*j*. Semiconductor, P (6) 223*d*. Semiconductor fabrication, P (5) 185*h*.
Schuez, W. Study of synthetic spinel crystals with the scanning electron microscope, (8) 298*j*.
Schuh, A. E. Centrifugal casting method, P (10) 342*b*.
Schuler, C. C. Method [vapor deposition] for producing thin films of rare earth chalcogenides, P (9) 313*e*.
Schuler, F. W. Flameworking: Glassmaking for the Craftsman, B (9) 333*j*.
Schuller, W., and Hohlfeld, H. Method and apparatus for manufacturing twisted fiber strands from staple fibers, especially from glass staple fibers, P (5) 175*b*.
Schuller, W. H. W. Method and apparatus for manufacturing twisted fiber strands from staple fibers, especially from glass staple fibers, P (5) 175*b*.
Schulmeister, R. See Schoenbrunn, G.
Schulten, R., Bohn, T., Hecker, R., and Baurmann, K. W. Method of and apparatus for the treatment of graphite-coated particles for nuclear reactors and the like, P (10) 342*j*.
Schultz, A. B., and Tsai, S. W. Dynamic moduli and damping ratios in fiber-reinforced composites, (2) 48*h*.
Schultz, A. H., and Stubican, V. S. Modulated structures in the system TiO_2-SnO_2, (5) 197*e*.
Schultz, A. W. Correlation and analysis of ultrasonic test results in evaluating reinforced resin laminates, (11) 380*b*.
Schultz, D. C. See West, R. R.
Schultz, L. K. See Nyman, G. E.
Schultze, D., Wilke, K. Th., and Waligora, Ch. Chemistry of molten solutions (III) preparation of crystalline tungstates $M^{2+}WO_4$, (6) 231*a*.
Schultze-Frentzel, U. Investigation of the macrostructure of ceramic antiquities by X rays, (6) 206*d*.
Schulz, B. See Ondracek, G.
Schulz, E., and Hehnen, J. Multiple emitter transistor with improved frequency and power characteristics, P (10) 345*b*.
Schulz, E. O. Process for making foam glass, P (2) 54*b*. Process for manufacturing glass in fine granular form, P (2) 54*c*.
Schulz, Hans. "Glass," (11) 370*c*.
Schulz, Heinz. Interpretation of the superlattice of noselite $[Na_8SO_4Al_6Si_6O_{24}]$ single crystals, (9) 323*d*.
Schulz, I. See Walter, H. P.
Schulz, P. R. Method for adjusting contacts in reed switches, P (6) 212*j*.
Schulz, W. W. See Burns, R. E.
Schumacher, E. R. See Schimitschek, E. J.
Schumacher, J. C., Rado, T. A., and Fairchild, J. L. Process for producing boric oxide, P (9) 317*d*.
Schumann, H. See Hein, W.
Schuster, H. U. See Juza, R.
Schuster, L. K., and Tongyai, Singkata. Coating cementitious articles with hexavalent chromium-resinous dispersions, P (5) 170*f*.
Schuster, M. A., List, W. F., and Reinitz, K. Mosaic of semiconductor elements interconnected in an XY matrix, P (9) 313*g*.
Schuster, P. See Gugel, E.
Schutt, J. B., and Shai, C. M. Alkali-metal silicate protective coating, P (4) 93*j*, P (10) 337*d*.
Schutte, H. See Geus, J. W.
Schwab, G. M. Chemical processes in phase boundaries, (6) 231*d*.
Schwab, T. See Schlegel, E.
Schwartz, A. S. See Bokros, J. C.
Schwartz, B. Method of manufacturing recording heads, P (4) 115*g*.
Schwartz, R. W. See Banks, E.
Schwartz, H. S. Method for the manufacture of pyrolytically coated filaments, P (5) 179*d*.
Schwartz, J. Cermet resistance module, P (7) 256*a*.
Schwartz, J. W. Magnetic shielding means [coating] for cathode ray tube, P (8) 282*d*.
Schwartz, M. A. See Li, P. C.
Schwartz, R. T. See Hough, R. L.
Schwartz, W. See Thiele, K. H.
Schwartzwalder, K. See Kesten, P. N.
Schwartzwalder, K., and Berg, M. Thermocouple with reducing atmosphere producing sheath, P (9) 316*a*.
Schwarz, H. See Scholder, R.
Schwarzbach, J. See Balcar, O.; Koller, A.
Schwarzbach, J., and Plocek, L. System BaO-TiO_2 in the region of barium polytitanates, (8) 299*j*.
Schwarzkopf Development Co. Glassmelting electrodes for glassmelting furnaces, P (4) 123*a*. Shaped bodies with high temperature strength and corrosion resistance against molten metals, particularly molten iron and steels, P (1) 14*h*.
Schwarzler, G. Building ceramics from the Muehlendyck pottery center, (7) 244*b*. Ceramic artists and their work—Rudolf Lunghard, (1) 2*a*; Celine von Eichborn; Ernst Loesche, (6) 205*j*.
Schwiete, H. E., and Boehme, H. J. Experimental and theoretical study on the determination of thermal conductivity of refractory building materials under thermal and structural stress, (4) 119*f*.
Schwiete, H. E., Pohl, K. D., and Herzhoff, P. H. Investigations of the Structure and of the Influence of Organic Matter on the Use of Raw Materials in the Area of Mineralogy and Metallurgy, B (11) 389*b*.
Schwiete, H. E., and Rehfeld, G. Studies of the textures of refractories with a scanning electron microscope, (4) 105*b*.
Schwiete, H. E., and Schinnerling, F. Technological investigations, thermal expansion, and life tests of high and low iron containing magnesite brick, (9) 309*c*.
Schwiete, H. E., and Wierich, H. Influence of furnace atmosphere on the hot crushing strength of various refractories, (6) 215*g*.
Schwyn, R. E., and Riddel, J. W. Thermoprobe assembly, P (4) 122*c*.
Scibona, G. See Cogliati, G.
Sciola, J. See Wang, P.
SCM Corp. High-temperature temporary protective ceramic coating compositions for metals and resulting coated metal articles, P (11) 369*c*. Iron powder for forming sintered articles of improved strength, P (4) 106*c*. Low temperature temporary protective ceramic coating compositions for metals and resulting coated metal articles, P (10) 337*a*. Process for grinding portland cement clinker, P (5) 170*h*. Process for preparing nucleated frit and white-enameled cast iron bodies prepared from the frit, P (2) 46*a*.
Scola, D. A. See Brooks, C. S.
Scoledge, R. F. See Palermo, J. J.
Scory, M. See Lauegt, M.
Scott, A. A., and Hartman, R. A. Compression assembled semiconductor device using spherical force transmitting member, P (1) 18*c*.
Scott, A. B. See Hamby, D. C.
Scott, B. See Carruthers, T. G.
Scott, B. A. See Giess, E. A.; O'Kane, D. F.
Scott, B. A., Giess, E. A., Burns, G., and O'Kane, D. F. Alkali-rare earth niobates with the tungsten bronze-type structure, (8) 288*f*.
Scott, B. A., Giess, E. A., and O'Kane, D. F. Phase equilibria in the $NaNbO_3$-$BaNb_2O_6$ system, (10) 358*i*.
Scott, C. E. Method of treating fluidizable particles, P (9) 317*h*.
Scott, C. J. Transient temperature response of a thin-walled, transpiration-cooled porous surface, (4) 162*c*.
Scott, F. P. Quick flash high yield getter with means to restrain warping and breaking of the getter material, P (10) 345*i*.
Scott, J. E. See Carter, J.
Scott, J. F. Dipole-dipole interactions in tungstates, (6) 231*g*. Lattice perturbations in $CaWO_4$ and $CaMoO_4$, (2) 79*e*. Raman spectra of BaClF, BaBrF, and SrClF, (8) 297*d*.
Scott, J. H., Jr. Method of forming aligned oxide patterns on opposite surfaces of a wafer of semiconductor material, P (2) 65*c*. Semiconductor junction device, P (11) 378*f*. See Fisher, A. W.
Scott, J. H., Jr., and Olmstead, J. A. Remote cutoff junction gate field-effect transistor, P (9) 313*f*.
Scott, J. J., and Turnbull, N. C. Electric fusion crystallization of magnesium, zirconium, and calcium oxides, P (4) 106*d*.
Scott, J. N. See Geib, C. B., Jr.
Scott, K. J. Experimental study of continuous thickening of a flocculated silica slurry, (2) 67*e*.
Scott, K. T., and Wassell, L. L. Diffusional release of tritium from irradiated BeO, (4) 131*f*. Release of gas from irradiated nonfissile ceramics, (1) 13*b*.
Scott, P. L. See Stokowski, S. E.
Scott, R. K. Precision casting, P (1) 14*b*. See Henry, G. R.
Scott, T. R., and Dyson, N. F. Catalyzed oxidation of zinc sulfide under acid pressure leaching conditions, (4) 127*g*.
Scott, W. D. Ceramic materials for structural components, (1) 40*d*. Impurity deposits on alumina crystals, (10) 355*i*. See Shackelford, J. F.
Scott, W. Z. See Malakoff, J. L.
Searcy, A. W. See Blank, B. A. H.; Hart, P. E.; Lim, M.; Newbury, R. S.; Skinner, H. B.
Searight, C. E., Alexander, E. M., and Ryan, J. R. High index of refraction glass compositions, P (4) 99*h*.
Searle, T. M. See Glass, A. M.
Searle, T. M., and Glass, A. M. Thermal decay of the V' center in magnesium oxide, (9) 331*g*.
Sebenik, R. F., and Smutz, M. Optimization of a solvent extraction plant to process monazite rare-earth nitrates, (8) 286*i*.
Secrist, D. R. Measurement of surface tension of glasses by a capillary flow technique, (6) 226*c*.
Secrist, D. R., and Mackenzie, J. D. Deposition of silica films by the glow discharge technique, (2) 75*c*.
Sedlatschek, K. See Pipitz, E.
Sedov, N. N. See Spivak, G. V.
Sedykh, E. M., and Ivanov, N. P. Determination of zinc and magnesium in glasses by the atomic absorption method, (2) 48*e*.
Seeger, A. (editor). Modern Problems of Metal Physics (Vol. II) Chemical Bonds in Crystals and Ferromagnetism, B (4) 166*h*.
Seelandt, K. H., and Twine, C. J. Hearth for a heat-treating furnace, P (5) 189*b*.
Seeley, G. See Ernst, E. O.
Segal, B. B. See Kriek, H. J. S.
Segalova, E. E., Tulovskaya, Z. D., Brutskus, T. K., and Lyubarskaya, G. V. Effect of polyacrylamide on the filtration properties of aqueous asbestos suspensions, (1) 23*e*.
Segmueller, A. See Giess, E. A.
Segnit, E. R. Corrosion of firebrick by brown coal ash, (5) 176*j*. Microstructure of ceramic materials (V) aluminosilicate refractories (4), (5) corrosion under service conditions, (7) 251*a*.
Segura, M. A., and Hunter, E. A. Novel lith-

ium silicate compositions and process for producing, P (11) 382*g*.
Schlke, K. H. L., and Tauber, A. High-temperature X-ray diffraction study of zircon-containing glaze frits, (10) 343*d*.
Seidel, H. See Juza, R.
Seidel, J., and Eaves, C. A. High temperature magnetic cores and process for producing, P (4) 113*a*.
Seidel-Stoicescu, D. See Szabo, A.
Seidl, J. See Ralkova, J.
Seifert, F. See Schreyer, W.
Seiler, H., Reimers, P., and Indradev. Epitaxial growth of CdS single crystal layers on ZnS platelets, (10) 353*c*.
Seipel, J. J. See Rolland, G. F.
Seipt, W. R. See Jackson, J. C.
Seiter, G. See Michel, H.
Seiter, H., and Zaminer, C. Method for epitaxial precipitation of semiconductor material on a spinel-type lattice substrate, P (5) 183*b*.
Seitz, M. A., and Whitmore, D. H. Electronic drift mobilities and space-charge-limited currents in lithium-doped zinc oxide, (9) 321*i*.
Seitz, R. Method for producing yttrium aluminate crystals, P (4) 125*a*. Method for producing yttrium aluminum oxide garnet crystals, P (6) 222*g*. Method [solution etching] for machining fragile crystals, P (9) 314*h*.
Seiwatz, H., and Groom, C. M. Method utilizing an electron beam for nondestructively measuring the dielectric properties of a sample, P (9) 315*i*.
Sekerka, R. F. Morphological stability, (10) 357*b*. See James, D. W.
Seki, Hajime. See D'Heurle, F. M.
Seki, Koshi. See Fujii, Satoshi.
Seki, Shingo; Kasahara, Kiyoshi; Kuriyama, Takeo; and Kawasumi, Makoto. Relation between compressive strength of concrete and the effective cement-water ratio calculated from the hydration rate of cement, (7) 245*a*.
Seki, Syuzo. See Sorai, Michio.
Seki, T. See Hariu, Takashi.
Seki, Yachiho, and Sakurai, Tai. Factors influencing physical properties of glass-pot material, (2) 55*i*.
Sekiya, Hitoshi. See Hibino, Taizo.
Sekiya, Michio, and Setoyama, Katsumi. Heat of hydration of various calcium sulfate hemihydrates measured by the method of dissolution in HCl, (5) 170*e*.
Selas Corp. of America. Method of making ceramic shapes, P (5) 180*c*.
Seleznev, I. P. See Kabanov, A. N.
Selikson, B. Diffusion anomalies in thin metallic films, (10) 343*h*.
Seliverstov, V. T. See Mazurov, D. J.
Sell, H. G. Refractory oxide incandescent lamp, P (9) 313*e*. See Atkinson, R. H.
Sellers, D. J. See Heuer, A. H.
Sellers, T. (editor). Potter's Wheel Projects, B (2) 85*g*.
Selph, C. C. See Ko, Hon Chung.
Seltzer, M. S. Correlation between the activation energies for steady-state creep and self-diffusion in beryllium oxide, (8) 289*f*. See Contin, M. R.
Semba, Kimio. See Miyatake, Kazumi.
Semenov, E. I. See Perrault, G.
Semenov, V. See Bertaut, E. F.
Semenova, N. N. See Vinnik, M. A.
Sementsova, D. V. See Bukhalova, G. A.
Sementsova, D. V., and Bukhalova, G. A. System of the chlorides of sodium, potassium, calcium, and barium, (4) 158*j*.
Semikron Gesellschaft fuer Gleichrichterbau und Elektronik m.b.H. Method and article for making switchable semiconductor elements, P (6) 222*c*.
Semirikov, I. S. See Loshkarev, B. A.
Semlyen, J. A. Rotational isometric state models of sulfur and selenium chains (III) large rings in liquid sulfur and the nature of $S\pi$, (9) 329*b*.
Semmelman, J. O. Composite artificial tooth, P (5) 180*b*. See Halpern, B. D.
Semmens, B. Reaction of kaolin with fluorides (III) hydrolysis of silicon tetrafluoride by kaolinite at elevated temperatures, (8) 287*a*.
Semmens, B., and Meggy, A. B. Reaction of kaolin with fluorides (I) effect of neutral and acid sodium fluoride solutions; (II) effect of aqueous hydrofluoric acid, (2) 73*e*.
Semov, M. P. See Zil'bershtein, Kh. I.
Semroc, C. V. Alkyd resin-aminoplast resin coating composition for glass, P (5) 174*f*.
Sen, S. See Bhattacharyya, B. N.; Guha, S. K.
Sen, S. K. See Aggarwal, P. S.
Sen, Tin Kun. See Hlavac, J.
Sendeckyj, G. P. See Chamis, C. C.
Seng, E. J. Method of fabricating integrated circuits by controlled process, P (7) 257*b*.
Sen Gupta, P. K. See Johns, W. D.
Sennett, P., and Olivier, J. P. Process for treating clay, P (8) 288*b*.
Senno, Harufumi, and Tawara, Yoshio. Exchange anisotropy in the mixed phase of γ-Fe_2O_3 and α-Fe_2O_3, (9) 321*b*.
Sensi, J. E. Manufacture of float glass using enclosed bath zones, P (11) 371*c*.
Sensui, Y. See Takaishi, T.
Sentjure, M. See Blinc, R.
Seo, Hirokichi. See Takamori, Takeshi.
SEPAC. See Societe d'Etudes et de Participations Couquelet S.A.
Septla, Z. See Kadlecek, V.
Serafin, F. G. Amide grinding aid, P (11) 382*h*. Aromatic acetates as grinding aids, P (5) 170*d*. Method of increasing the grinding efficiencies of minerals and cement, P (5) 191*b*. Mineral grinding aids, P (8) 274*e*. Vinyl acetate grinding aid, P (8) 288*e*. See Dodson, V. H.
Serdean, A. See Marino, D.
Serebryakova, T. I. See Kuz'ma, Yu. B.
Sereda, P. J. See Hosek, J.; Swenson, E. G.
Serindat, J. See Monneraye, M.
Seris, G. See Perraudin, R.
Serisawa, Yoshikiyo. See Murakami, Keiichi.
Serpinskii, V. V. See Bering, B. P.
Service (Engineers), Ltd. Manufacture of pottery, P (4) 123*c*, P (7) 254*b*.
Servomic Instruments, Inc. Method of making molded ceramic articles [pressure sintering], P (7) 257*g*.
Serway, R. A. See Hodges, J. A.; Marshall, S. A.
Sestak, J., Satava, V., and Rihak, V. Algorithm for evaluating kinetics data from a nonisothermic thermogravimetric curve, (2) 68*e*.
Setaka, Nobuo, and Ejiri, Koichi. Evidence for 2H-SiC whisker growth by a screw dislocation process, (9) 308*i*. Influence of oxygen on growth of 2H-SiC whiskers, (4) 140*d*.
Sethi, R. S. See Gaur, H. C.
Setkina, O. N. See Shteinberg, Yu. G.
Seto, D. K. See Kren, J. G.
Setoyama, Katsumi. See Sekiya, Michio.
Settineri, W. J. See Gillespie, T.
Settino, F. A. Float glass takeout roll, P (8) 277*j*.
Seufert, J. L. See Fleming, G. S.
Seufert, L. E. Alumina-spinel composite material, P (7) 243*h*.
Sevick, D. J. See West, R. R.
Sevigny, A. J., Jr. See Mandonas, N. J.
Seward, T. P., III, Uhlmann, D. R., and Turnbull, D. Development of two-phase structure in glasses, with special reference to the system BaO-SiO_2, (1) 6*f*.
Sewell, F. A., Jr., Wegener, H. A. R., and Lewis, E. T. Charge storage model for variable threshold FET memory element, (9) 310*b*.
Sewell, P. A. Porous layers at glass surfaces, (4) 97*b*. Surface area estimations of grains used in glass durability testing, (7) 248*d*.
Sewell, P. A., and Morgan, A. M. Methanol vapor adsorption on silica and soda-lime-silica glass, (6) 210*c*. Physical adsorption on porous glass beads, (4) 96*h*.
Sewell, P. B. See Ramasubramanian, N.
Seymour, S. L. Mold cover for bending glass sheets, P (5) 176*b*.
Shabanov, A. G., Churikov, V. D., Tyurin, Yu. M., Gorokhovskii, V. A., Kuleshov, F. P., and Kachalov, N. N. Production of toughened enameled sheet glass, (6) 211*b*.
Shabbir, M., and Robbins, R. G. Effect of crystallographic orientation on the dissolution of uranium dioxide in nitric acid, (5) 193*g*.
Shackelford, J. F., and Scott, W. D. Relative energies of [1100] tilt boundaries in aluminum oxide. (1) 36*c*.
Shadek, E. G. See Gushchina, I. I.
Shaffer, J. W., and Hartman, D. W. Photoflash lamp, P (7) 249*b*.
Shaffer, P. T. B. Comments regarding the structure of beta SiC whiskers, (4) 129*c*. SiC phase in the system SiC-B_4C-C, (10) 360*h*. See Hannam, A. L.
Shah, M. J. See Mehta, P. K.
Shai, C. M. See Schutt, J. B.
Shaikh, M. S. Method of fabricating a semiconductor by diffusion, P (7) 257*c*. See Amsterdam, M. F.
Shain, S. A. See Overcashier, R. H.
Shakhtakhtinskii, T. I. See Verenkova, E. M.
Shakmanov, V. V., and Spivak, G. V. Domain structure of barium titanate films in the rhombic phase, (2) 61*j*.
Shalaginov, V. N. See Bessonov, A. F.
Shalek, P. D. See Baskin, Y.
Shalimo, Z. N. Change in structure and mechanical properties of glasses during crystallization, (2) 47*d*.
Shaltiel, D. See Beeman, D. E.
Shamrai, F. I. See Dokukina, N. V.
Shand, E. B. Fracture of glass by impact, (1) 7*d*.
Shand, W. A. Detection of rare earth impurities in ionic materials by X-ray-stimulated luminescence, (1) 21*b*. See Jones, D. A.
Shanefield, D. J., Battle, J. H., and Currier, E. W. Nonrectifying solid state element, P (10) 339*d*.
Shanefield, D. J., Battle, J. H., and Lighty, P. E. Solid state element comprising semiconductive glass composition exhibiting negative incremental resistance, P (9) 314*c*.
Shanefield, D. J., and Currier, E. W. Method of shaping a crystal by acid cutting, P (2) 68*b*.
Shankland, T. J. Pressure shift of absorption bands in MgO:Fe^{2+} and the dynamic Jahn-Teller effect, (10) 359*a*.
Shanks, B. E. Electric incandescent lamp and method of manufacture, P (9) 307*c*.
Shanks, H. R. See Wechter, M. A.
Shannon, R. D. New high pressure phases having the corundum structure, (4) 146*f*. Synthesis of some new perovskites containing indium and thallium, (11) 387*i*.
Shannon, R. D., and Prewitt, C. T. Coordination and volume changes accompanying high-pressure phase transformation of oxides, (10) 351*e*.
Shannon, R. F. Reinforced hydraulic cements and casts therefrom, P (11) 368*f*. Slurry pouring means and mold, P (11) 375*d*.
Shapiro, L., and Offenbacher, E. L. Microscopic effects of electric breakdown in MgO, (9) 324*f*.
Shapiro, S. L. Second harmonic generation in $LiNbO_3$ by picosecond pulses, (7) 268*j*.
Shapiro, S. M., O'Shea, D. C., and Cummins, H. Z. Raman scattering study of the alpha-beta phase transition in quartz, (4) 152*c*.
Shapiro, Z. I., Fedulov, S. A., and Venevtsev, Yu. N. Determination of the Curie point of the ferroelectric $LiNbO_3$, (2) 61*d*.
Shapiro, Z. M. Apparatus for producing vapor coated particles, P (6) 217*h*.
Shaplygin, I. S. See Komissarova, L. N.
Sharkina, E. V. See Tarasevich, Yu. I.
Sharma, K. K., and Artman, J. O. Energy-level scheme for Np^{4+} in $PbMoO_4$, (10) 353*b*.
Sharma, M. R., and Krishnaswami, S. P. Modified centrifuge apparatus for heavy liquid separations, (1) 21*e*.
Sharma, S. See Sodha, M. S.
Sharma, T. N. Technical Faults in Porcelain Manufacture and Their Elimination, B (1) 42*j*.
Sharp, J. D. Nozzle and stopper assemblies for teeming liquid metal, P (4) 107*i*.
Sharp, J. H. See Brindley, G. W.
Sharpe, R. M. See Bramman, J. I.
Sharpe, T. F., and Meibuhr, S. G. Simple method for preparing spherical metal electrodes, (10) 344*j*.
Shatas, R. A. See Tanton, G. A.
Shatunova, A. V. See Batvrev, V. A.
Shaunfield, W. N. See Pollock, L. J.
Shaver, R. G. See Alexander, J. A.
Shaw, A. M. B. See Booker, G. R.
Shaw, D., Goldsmith, L. A., and Little, A. Suitability of the flash method for measuring the thermal diffusivity of cracked specimens, (9) 315*d*.
Shaw, D. W. Effects of vapor composition on the growth rates of faceted gallium arsenide hole deposits, (10) 352*j*. Selective epitaxial deposition of gallium arsenide in holes, (2) 82*j*.
Shaw, D. W., and Mehal, E. W. Method of making shaped epitaxial deposits, P (5) 183*h*.
Shaw, F. M. Apparatus for milling foundry sand, P (5) 178*a*.
Shaw, H. E., Jr. Radiation sensitive apparatus for severing [moving] glass [sheet] along a score mark, P (4) 101*c*.
Shaw, J. T. See Bethell, K. D.
Shaw, K. Ceramic Colors and Pottery Decoration, B (10) 364*h*. Ceramics coloring materials, (10) 348*g*. How channel width affects tunnel kiln performance, (1) 22*j*.
Shay, G. C. See Wosinski, J. F.
Shcherbak, B. I. See Babich, V. I.
Shcherban, N. I. See Beloivan, A. F.
Shcherbov, D. P. Fluorescence analysis of inorganic substances, (2) 69*f*.
Shchetnev, Yu. F. See Vertsner, V. N.
Shchukarev, S. A., Perfilova, I. L., and Garin, L. N. System VCl_3-CsCl, (7) 270*c*.
Shchukarev, S. A., Vasil'kova, I. V., Efimov, A. I., and Pitirimov, B. Z. Enthalpy of formation of chromium trichloride, (4) 135*a*.
Sheasby, J. S., Smeltzer, W. W., and Jenkins, A. E. Diffusional properties of oxygen in niobium pentoxide crystals and scales formed on niobium, (5) 193*e*.
Sheasby, J. S., and Wallwork, G. R. Parabolic oxidation kinetics of niobium, (2) 81*j*.
Sheatsley, L. L. See Hauth, C. R.
Sheer, R. E., Jr. See Cary, K. H.
Sheftal, N. N. (editor). Growth of Crystals (Vol. 6, Parts A and B), B (9) 334*c*.
Sheinin, E. I. See Belostotskaya, N. S.
Sheinina, M. E. See Yurchak, I. Ya.
Shekhawat, V. S. See Balian, K. S.
Shelamov, V. A. See Gladneva, L. I.
Shelby, J. E., Jr., and Day, D. E. Mechanical relaxations in mixed-alkali silicate glasses (I) results, (6) 210*b*.
Sheldahl, D. B. See Teeter, F. C.
Sheldon, W. M. Fine granulator, P (7) 259*a*.
Shell, H. R. See Nichols, E. F.
Shell, H. R., and Ivey, K. H. Fluorine micas, (10) 348*h*.
Shelley, D. P. Recent developments in kilns for the ceramic industry, (7) 261*e*.
Shell Oil Co. Manufacturing diamond bits, P (10) 335*f*. Method of producing foamed glass having uniform cell size, P (8) 278*a*. Process for sealing cement concrete surfaces, P (9) 304*d*.
Shelyubskii, V. I. Calculation of the concentration distribution in binary powder mixtures of variable composition, (2) 67*d*.
Shen, Chung Yu. Process for manufacture of crystalline pyrophosphoric acid, P (10) 349*f*. Production of alkaline earth metal pyrophosphates, P (2) 74*e*.
Shendalman, L. H., and O'Toole, J. T. Nucleation and coarsening in binary condensed phases, (5) 197*i*.
Shenker, H., Moore, W. J., and Swiggard, E. M.

Beryllium doped germanium photoconductive detector, P (10) 344*b*.

Shenoy, G. K., Kalvius, G. M., and Hafner, S. S. Magnetic behavior of the $FeSiO_3$-$MgSiO_3$ orthopyroxene system from NGR [nuclear gamma-ray resonance] in ^{57}Fe, (9) 324*h*.

Shenyaskaya, L. A. See Distler, G. I.

Shepard, A. O., and Starkey, H. C. Effects of exchanged cations on the thermal behavior of heulandite and clinoptilolite, B (4) 167*h*.

Sheppard, M. A. See Glasson, D. R.

Sher, E. S. See Toropov, N. A.

Sherer, J. B. See Gleim, P. S.

Sherk, L. See Caron, A. P.; Huettner, D. J.

Sherman, A. B. See Judin, V. M.

Sherman, I. L. Making a slip trailer from moisture-proof paper, (10) 335*j*.

Sherr, A. E., and Roshal, J. Plaster compositions, (10) 336*a*.

Sherrington, L. G., and Hewitt, J. M. Separation of rare earth elements, P (10) 349*e*.

Shershebytova, L. A. See Yarosh, P. Ya.

Sherwin, E. J. See Weinstein, M.

Sherwood, E. M. See Campbell, I. E.

Sherwood, J. N. Imperfections in molecular solids, (8) 293*i*.

Sherwood, R. C. See Gallagher, P. K.

Shevchenko, A. V. See Tresvyatskii, S. G.

She chenko, V. K. See Nesanelis, M. Z.

Shevtsova, Z. N. See Korshunov, B. G.; Safonov, V. V.

Sheybany, H. A. Alchemistical recipes from Persia for the manufacture of colored silicate glasses, (9) 303*f*.

Shiba, Hiroshi. See Kurosawa, Toshio; Yawata, Keisuke.

Shiba Electric Co., Ltd. See Nippon Telegraph & Telephone Public Corp.

Shibala, S., Goto, K., and Nakashima, R. Spectrophotometric determination of Fe in high purity Y_2O_3 with 1-(2-pyridylazo)-2-naphthol, (10) 347*g*.

Shibata, Goro. See Komatsu, Teruhiko.

Shibata, Noboru. See Iwanaga, Hiroshi.

Shibata, Shinichi; Mori, Hideo; and Owada, Atsushi. Semiconductive electromechanical transducers, P (6) 223*c*.

Shibata, Yukio. See Kumagai, Yasuji.

Shibuno, Masao. See Hayashi, Takeshi.

Shidlovsky, I. See Mayer, I.; Schieber, M.

Shield, W. A. See Kerr, J. M.

Shiever, J. W. See Nassau, K.; Wehmeier, F. H.

Shikano, Hiroshi. See Miyatake, Kazumi.

Shiloff, J. C. See Morley, H. B.

Shilov, A. V. See Telyatnikov, G. V.

Shimada, Kinji; Kawasaki, Junko; and Kono, Masae. Coral limestone from Tokunoshima and Okierabushima, (4) 123*h*.

Shimada, Kohei. See Ohba, Hiroshi.

Shimada, Kohichi. See Kojima, Kojiro.

Shimada, M., Kume, S., and Koizumi, M. Possible existence of dense ferrimagnetic perovskite allotropic form of yttrium iron garnet, (1) 17*h*.

Shimada, Nobuo. Relations between characteristics of plastic chrome refractories and conditions for their use, (5) 178*e*.

Shimada, Nobuo, and Oyama, Hoiiro. Erosion velocity of steelmaking ladle brick, (7) 250*h*.

Shimada, Nobuo; Takahashi, Tadaki; and Nakagawa, Hideo. Results of service tests on direct-bonded basic brick in open hearth roof, (7) 251*b*.

Shimada, Sadakuni. TE_{02} mode filter for TE_{01} mode circular waveguide at millimeter wavelengths, (4) 111*c*.

Shimada, Shinro, and Kojima, Yasuiiro. Drying problems relating to laying of blast furnace bottom brick, (2) 55*d*.

Shimanouchi, Takehiko. See Nakagawa, Ichiro.

Shimizu, Kelichi; Takekawa, Tatsuya; Tamaki, Nobuo; Takasue, Takashi; Suemoto, Toshio; and Mase, Kazuo. Electrolytic method for preparing manganese dioxide, P (7) 262*h*.

Shimizu, Satoshi. See Terada, Kiyoshi.

Shimizu, Satoshi; Nishida, Toshihiko; and Terada, Kiyoshi. Influence of burning atmosphere on the behavior of alite mixture during firing, (4) 91*i*.

Shimizu, Shokichi. See Matsuzaki, Hiroyuki.

Shimoda, Koichi. See Kasuva, Takahiro.

Shimoda, R. Y., Hsieh, E. J., and Mayeda, K. Comparison of some physical properties of resistance-heated and electron-gun evaporated SiO films, (1) 16*d*.

Shimoda, Susumu. See Sudo, Toshio.

Shimoda, Takeshi. See Futaki, Hisao.

Shimoji, M. See Emi, T.

Shimpo, Yoshiro. Effect of methods of casting on physical properties of castable refractories, (11) 373*c*.

Shinada, Masaki, and Sugano, Satoru. Interband optical transitions in extremely anisotropic semiconductors (I) bound and unbound exciton absorption, (5) 195*f*.

Shinal, J. B. See Glovatsky, A.

Shinde, V. M., and Knopkar, S. M. Rapid extraction and direct spectrophotometric determination of copper with thiothenoyltrifluoroacetone, (8) 285*b*.

Shindo, Akio; Fujii, Rokuro; and Souma, Isao. Producing method of carbon or carbonaceous material, P (5) 179*c*.

Shinmei, M. See Huffman, D. R.

Shinnippon Denki Kabushiki Kaisha. Treatment of a phosphor screen in a cathode ray tube, P (2) 67*b*.

Shinoda, Masaichi. Method of producing a variable capacitance diode, P (7) 257*c*.

Shiokawa, Jiro. See Adachi, Gin-ya.

Shionogi & Co., Ltd. Apparatus for fluidized drying and separation, P (10) 348*b*.

Shionoya, Shigeo. See Nagasawa, Masahiro; Shinjo, Teruya. See Sakurai, Junji; Yasuoka, Hiroshi.
Nakazawa, Ehchiro; Yamamoto, Hajime.

Shiota, P. S. See Lin, H. C.

Shiozawa, L. R. Piezoelectric materials, P (2) 66*c*.

Shipley, L. E. Toby jugs, (7) 244*e*.

Shiragaki, Hajime. Method of making electric bulbs, P (11) 371*g*.

Shirai, Toshiaki. See Hamada, Shuichi.

Shiraishi, Takashi. See Yamaguchi, Takashi.

Shiraiwa, Takao. See Fujiwara, Shinobu.

Shirakashi, Shigeru, and Kowaki, Hirokazu. Results of service test on electric furnace whose hearth was rammed with MgO clinker, (11) 373*i*.

Shirane, G. See Gonzalo, J. A.

Shirane, G., Frazer, B. C., Minkiewicz, V. J., Leake, J. A., and Linz, A. Soft optic modes in barium titanate, (4) 155*d*.

Shirato, Yoshiaki. See Hijikata, Kenzo.

Shirk, T. See Joubert, J. C.

Shirkevich, T. L., Gorokhovskii, V. A., and Khripunova, T. P. Production of foam glass from volcanic glasses, (1) 8*i*.

Shirkevich, T. L., and Khripunova, T. P. Production of foam glass from volcanic glasses with preliminary melting, (1) 8*j*.

Shiroki, Kenichi, and Saito, Selichi. Flame fusion crystal growing employing vertically displaceable pedestal responsive to temperature, P (8) 282*g*. Method for growing high-melting-point single crystals and an apparatus therefor, P (4) 114*j*.

Shirokova, G. A. See Belyakova, E. P.

Shirvinskaya, A. K. See Grebenshchikov, R. G.

Shirvinskaya, A. K., Grebenshchikov, R. G., Shitova, V. I., and Toropov, N. A. Solid solutions in the system $CaSiO_3$-$CaGeO_3$, (7) 269*a*.

Shishakova, T. N. See Fedorova, G. M.

Shishkov, N. V. See Budnikov, P. P.

Shitaya, Takao. See Yamamoto, Ryoichi.

Shitova, V. I. See Grebenshchikov, R. G.; Shirvinskaya, A. K.

Shiun, C. H. Method for separating asbestos fibers from foreign solids, P (5) 191*d*.

Shklyarenko, N. G. See Ostrovskii, O. P.

Shlyakov, O. N. See Il'in, M. A.

Shockey, D. A., and Groves, G. W. Origin of water-induced toughening in MgO crystals, (4) 148*a*.

Shockley, W. L. Selective sputtering rate circuit forming process, P (7) 258*a*.

Shoda, Koichiro. Method of manufacturing semiconductor devices [masking], P (7) 257*j*.

Shoda, Yuzuru. See Saito, Shuntaro.

Shoemaker, F. O. Abrasive disk, P (1) 1*j*.

Shor, O. I. See Sazhin, V. S.

Shorb, A. M. See Wiederhorn, S. M.

Shore, R. G., and Wanklyn, B. M. Systems PbF_2-AlF_3 and CaF_2-AlF_3, (4) 159*a*.

Short, M. A., and Ruscoe, M. J. H. Demountable tube in light element fluorescence analysis, B (1) 41*a*.

Short, O. A. Compositions, P (4) 112*j*. Thermistors made therefrom, P (2) 66*i*.

Shortes, S. R. Formation of electron barriers on phosphor particles, P (9) 312*j*. Increasing the electron energization threshold of phosphor particles, P (2) 65*c*. Method of making electrical contact to a semiconductor body, P (2) 65*f*. Process of coating a semiconductor with a mask and diffusing an impurity therein, P (9) 313*d*.

Shoulders, K. R. Thin wafer-channel multiplier, P (11) 379*a*.

Shoup, R. D. See Fitch, F. T.

Shrader, R. E. See Larach, S.

Shropshire, J. A. Crystal structure effects in the adsorption of calcium sulfonate on $CaCO_3$, (1) 26*e*.

Shteinberg, Yu. G., Belova, A. N., and Bochkareva, I. V. Crystallization in strontium-zinc glazes, (8) 280*b*.

Shteinberg, Yu. G., and Setkina, O. N. Glasses in the system SrO-SiO_2-CaO-SiO_2 (II) structure of strontium silicate glasses studied by infrared absorption spectra, (7) 247*d*.

Shtrikman, S. See Eibschuetz, M.

Shubin, V. I. See Budnikov, P. P.

Shubina, N. V. See Budnikov, P. P.

Shubina, T. N. See Zaitsev, L. M.

Shudo, Akio. See Torikai, Naochika.

Shul'man, I. G. See Boiko, D. Ya.

Shul'ts, M. M. See Bobrov, V. S.

Shultz, R. M. See Wanlass, F. M.

Shumate, M. S. Interferometric measurement of large indices of refraction, (1) 31*h*.

Shuron/Continental Div. of Textron, Inc. Method of generating a lens, P (9) 307*j*.

Shuvaev, A. T., Blokhin, M. A., and Izrialevich, E. A. X-ray spectroscopic determination of the valence of titanium and the coordination number of aluminum in special glasses, (2) 52*g*.

Shveikin, G. P. See Alyamovskii, S. I.

Shwayder, W. M. Method of disintegrating sintered hard carbide masses, P (7) 243*g*.

Shyam, M. See Allen, J. W.

Shyne, J. J., and Milewski, J. V. Method of growing alpha alumina and beta silicon carbide whiskers, P (2) 59*c*. Method of growing alpha alumina single crystal ribbons, P (5) 186*d*.

Shyne, J. J., Milewski, J. V., and Smith, C. B. High strength whisker composite article, P (5) 178*i*.

Sibert, F. J. Process for separation of red mud from dissolved alumina, P (8) 288*b*.

Sibley, F. S., and Spooner, N. F. Nickel alloy thermocouple, P (10) 348*a*.

Sibley, W. A. See Chen, Y.

Sibley, W. A., Nelson, C. M., and Chen, Y. Luminescence in MgO, (6) 234*e*.

Sickafus, E. N., and Barker, D. B. Surface-spike growth on $NiBr_2$ crystals—a VLS mode of crystal growth, (4) 158*g*.

Siddiqui, M. K. H. Bleaching Earths, B (9) 333*i*.

Sidhu, G. S., and Singh, D. Improved die for making glass headers, (5) 172*i*.

Sidorov, A. B. See Bartenev, G. M.

Sidorov, T. A., and Tyul'kin, V. A. Nature of hole centers in irradiated alkali silicate glasses, (8) 276*e*. Study of sitalls in the system Li_2O-Al_2O_3-SiO_2 by electron paramagnetic resonance, (7) 269*g*.

Sidorov, T. A., Tyul'kin, V. A., and Aksenov, V. S. Thermoluminescence, EPR, and electron absorption spectra of irradiated silicate glasses, (8) 277*a*.

Siegel, F. R. See Pierce, J. W.

Siegmund, W. P., and Williams, N. S. Fiber optical image-conducting devices embodying varying controlled stray light absorbing means, P (7) 248*f*.

Siemens, Akt.-Ges. Apparatus for crucible-free floating zone melting of crystalline rods, P (10) 344*a*. Apparatus for producing striationless bodies of metal and semiconductor substances containing impurities, P (4) 112*d*. Ceramic bodies of ferroelectric material with perovskite structure which is partially *p*-conducting and partially *n*-conducting, P (7) 255*i*. Device for inductively heating semiconductor material, P (7) 256*d*. Electrical structural element having closely neighboring terminal contacts and method of making, P (4) 112*f*. Epitactic vapor coating apparatus, P (11) 376*e*. Field-effect transistor with a ferroelectric control gate layer, P (5) 183*b*. Fused junction between a germanium-silicon semiconductor member and a junction element and method of producing, P (7) 256*i*. Galvanomagnetic resistor with semiconductor top layer, P (4) 113*h*. Gas etching followed by gas plating, P (11) 376*g*. High frequency transistor with sloping emitter junction, P (6) 221*e*. Indirectly heated dispenser cathode for electric discharge tubes, P (10) 345*b*. Integrated complementary transistor circuit, P (10) 345*c*. Mechanical to electrical semiconductor transducer, P (11) 377*e*. Memory element with stacked magnetic layers, P (11) 377*e*. Mesa transistor with an asymmetrical U-shape base electrode, P (9) 312*g*. Method and apparatus for increasing the cross section of a crystalline rod during crucible-free zone melting, P (4) 114*g*. Method and apparatus for thermally bonding semiconductor components to carriers, P (7) 256*j*. Method of crucible-free zone melting of semiconductor material, particularly silicon, P (10) 345*f*. Method of epitaxial deposition wherein spent reaction gases are added to fresh reaction gas as a viscosity-increasing component, P (8) 282*f*. Method for epitaxial precipitation of semiconductor material on a spinel-type lattice substrate, P (5) 183*b*. Method of epitaxially growing layers of semiconducting compounds, P (11) 377*i*. Method of epitaxially producing *pn* junctions in silicon, P (2) 65*a*. Method of etching a semiconductor material, P (5) 183*c*. Method of influencing the surface profile of semiconductor layers precipitated from the gas phase, P (4) 115*a*. Method of inserting manganese into semiconductors serving to produce electronic semiconductor structural components, P (9) 312*i*. Method of making a *pnpn* thyristor [indiffusing], P (8) 283*b*. Method of manufacturing [doped] integrated semiconductor circuit device, P (8) 283*d*. Method [precipitation] of producing semiconductor members, P (9) 313*c*. Method of producing highly pure halogen compounds of gallium and indium, P (5) 184*c*. Method of producing intermetallic superconducting compounds of niobium and gallium, P (5) 184*c*. Polishing method for the removal of material from monocrystalline semiconductor bodies, P (7) 257*h*. Pressure-responsive semiconductor device, P (5) 184*j*. Process of attaching electric connections to a semiconductor body, P (4) 115*h*. Process of epitaxial growth wherein the distance between the carrier and the transfer material is adjusted to effect either material removal from the carrier surface or deposition thereon, P (5) 185*b*. Radiation sensor utilizing semiconductor body having photoelectromagnetic effect, P (2) 66*j*. Seal for enclosures subjected to high pressures and temperatures, P (11) 379*g*. Semiconductor crystals of fibrous structure and method of their manufacture, P (8) 283*c*. Semiconductor device with interelectrode capacitance compensation, P (1) 19*i*. Semiconductor device, particularly for response to variable pressure, P (4) 116*d*. Semiconductor rectifier diode for power current with

a particular doping, P (7) 258*e*. Semiconductor structural component, P (11) 378*g*. Tunnel diodes wherein the height of the reduced cross section of the mesa is minimized and process of making, P (2) 67*b*. Voltage-sensitive variable *pn* junction capacitor with intermediate control zone, P (4) 117*c*.

Siemens-Planiawerke Akt.-Ges. fuer Kohlefabrikate. Method of protectively treating an electrically and thermally conducting refractory body of sintered silicon carbide, P (4) 107*c*.

Sienko, M. J. See Berger, M.; Bouchard, G. H., Jr.; Kudrak, D. R.; Perlstein, J. H.; Reid, A. F.

Sierro, J. See Bill, H.

Sievers, A. J., Alexander, R. W., Jr., and Takeno, S. Resonant impurity mode and the Moessbauer effect for europium-doped MnF_2, (4) 153*c*.

Sievers, R. E. See Eisentraut, K. J.

Sigel, G. H., Jr., and Ginther, R. J. Effect of iron on the ultraviolet absorption of high purity soda-silica glass, (1) 6*b*.

Sigety, E. A. See Kurkjian, C. R.

Sigmund, P. Number of atoms displaced by implanted ions or energetic recoil atoms, (10) 357*h*.

Signetics Corp. Method for making field effect transistor, P (5) 183*f*.

Sigri Elektrographit G.m.b.H. Body of industrial carbon with an oxidation inhibiting coating and method of producing such bodies, P (11) 374*f*.

Sigsway, R. L. See Linares, R. C.

Sihvonen, Y. T., Boyd, D. R., and Kitts, E. L., Jr. Light responsive variable capacitor, P (5) 183*h*.

Sikirica, M. See Ban, Z.

Sikora, W., and Stoch, L. Effect of iron content on the whiteness of kaolins from Lower Silesia, (9) 316*i*.

Sikora, W., Stoch, L., and Jablonska, B. Occurrence of iron in kaolins of Lower Silesia, (9) 326*d*.

Silberstein, A. See Hoch, M.

Silcox, N. W. See McGrath, R. S.

Sileika, A. See Babonas, G.

Siliconix, Inc. Unipolar transistor, P (10) 346*b*.

Sillen, L. G. See Hietanen, S.

Sillwood, J. M. See Champion, J. A.

Sil'vanovich, Yu. A. See Artyukhin, P. I.

Silver, G. L. See Lonadier, F. D.

Silver, R. S. See Perlman, S. S.

Silverman, B. A., Thompson, B. J., and Parrent, G. B., Jr. Particle size and distribution analysis using spatial filtering techniques, P (9) 315*j*.

Silverman, M. S. Method of preparing rhombohedral crystalline tungsten disulfide, P (1) 14*i*.

Silverman, R. Effect of moisture on the aluminum-silica reaction, (9) 320*i*.

Silvernail, W. L. Process for rejuvenating spent glass polishing agents [by flocculation], P (7) 249*d*.

Silverstone, C. E. See Kear, B. H.

Silvey, G. A. See Doo, V. Y.; Regh, J.

Silvidi, A. A. Proton magnetic resonance study of lithium trihydrogen selenite, (4) 151*d*.

Simanek, E., and Huang, N. L. Covalency and temperature dependence of hyperfine coupling: Mn^{2+} in MgO, (2) 75*e*.

Simkovich, A., Li, Kun, and McCabe, C. L. Dissolution of alumina in carbon-saturated liquid iron, (10) 340*h*.

Simmons, G. See Chung, D. H.

Simmons, G. A., Jr. See Gould, R. E.

Simmons, J. G. See Verderber, R. R.

Simmons, J. H. See Macedo, P. B.

Simms, B. B. See Block, A.

Simon, E. High-voltage planar semiconductor devices, P (11) 376*i*.

Simon, I. See Obst, M.

Simon, J., Gal, S., and Erdey, L. Thermal reactions of sodium halides, (5) 201*i*.

Simon, R. A. Sheet glass edge control device, P (9) 308*c*.

Simon, R. E. See Williams, B. F.

Simons, C. C. See Carlson, R. J.

Simons, P. Y. See Dachille, F.

Simons, W. H. See Feidmann, H. F.

Simplicity Engineering Co. Combined crushing [gyratory] and attrition apparatus and method, P (10) 349*c*.

Simpson, D. R. Substitutions in apatite (I) potassium-bearing apatite, (8) 299*b*.

Simpson, H. E. Glass industry 1968 (I), (7) 247*b*.

Sims, S. D., Stein, A., and Roth, C. Dynamic optical path distortions in laser rods, (1) 27*c*.

Simsa, Z. Influence of Mn^{3+} ion clustering on electrical properties of manganese ferrites, (10) 355*c*.

Simurov, V. V. See Kruglitskii, N. N.

Sinclair Research, Inc. Crystalline aluminosilicate-containing catalyst and methods of treating and using, P (6) 229*d*. Disproportionation of alkyl aromatics with a crystalline aluminosilicate and oxygen, P (7) 262*g*. Fuel block heater, P (4) 102*f*. Method of crystallizing aluminosilicates, P (5) 191*a*. Process for grinding glass with diamond grinding surface and alkali metal soap emulsifiable composition, P (11) 372*a*. Production of alumina from dawsonite, P (11) 382*j*.

Sinclair Research, Inc., and Engelhard Hanovia, Inc. Process for grinding glass with diamond grinding surface and an emulsifiable composition, P (10) 339*j*.

Sing, K. S. W. Assessment of microporosity, (2) 68*g*. See Aldcroft, D.; Bye, G. C.; Carruthers, J. D.; Harris, M. R.; Payne, D. A.

Sing, K. S. W., and Swallow, D. Determination of specific surface area by low-temperature krypton adsorption, (1) 27*f*.

Singer, E. Cristobalite as a separation phase in porcelain glazes containing spinel, (7) 253*h*. Preparation of raw materials for technical ceramics, (5) 190*i*.

Singer-General Precision, Inc. Method of making a moisture sensitive capacitor, P (10) 345*i*. [Method of making] photoconductive thin film cell responding to a broad spectral range of light input, P (9) 313*b*.

Singh, A. See Balian, K. S.

Singh, B. Determination of the strength of rocks, (4) 123*j*. See Narain, J.

Singh, D. See Sidhu, G. S.

Singh, G. See Kar, K. R.

Singh, R., Witt, A. F., and Gatos, H. C. Application of the Peltier effect for the determination of crystal growth rates, (4) 126*i*.

Singh, R. P. See Patel, A. R.

Singh, R. P., Chickerur, N. S., and Narasaraju, T. S. B. Complexometric determination of calcium and phosphorus in synthetic hydroxiapatite, (6) 225*i*.

Singh, S. See Chen, F. S.; Geusic, J. E.; Gupta, K. P.; Smith, Richard G.

Singh, S., and Geusic, J. E. Observation and saturation of a multiphoton process in $NdCl_3$, (2) 81*c*.

Singh, S. P. See Mathur, V. K.

Singh, S. S. See Brydon, J. E.

Sinha, A. P. B. See Ghare, D. B.

Sinistri, C., Franzosini, P., and Rolla, M. Atlas of Miscibility Gaps in Molten Salt Systems, B (8) 301*j*.

Sinke, G. C., Walker, L. C., Oetting, F. L., and Stull, D. R. Thermodynamic properties of aluminum hydride, (4) 161*j*.

Sinollitsyn, E. K. See Rykalin, N. N.

Sintermetallwerk Krebsoge G.m.b.H. Process for the production of sintered articles, P (4) 107*c*.

Sintsova, I. T. See Avgustinik, A. I.

Sippel, R. F. Sandstone petrology, evidence from luminescence petrography, (1) 36*i*.

Sippel, R. J. Preparation of silica sols of minimum turbidity, P (7) 263*c*.

Siratori, Kiiti. Effect of crystal deformation on lattice vibration of oxide spinels, (1) 27*f*.

Siratori, Kiiti, and Kohn, K. Frequency of the magnetic resonance of $MnCr_2O_4$, (2) 77*i*.

Sircar, N. R. See Banerjee, J. C.

Sironi, G. See Colombo, U.

Sirtl, E. Gas etching followed by gas plating, P (11) 376*g*. Method of epitaxial deposition wherein spent reaction gases are added to fresh reaction gas as a viscosity-increasing component, P (8) 282*f*. Method [precipitation] of producing semiconductor members, P (9) 313*c*.

Sisson, C. G., Foster, J. L., and Myers, C. B. Process for the production of calcium carbonate, P (8) 288*b*.

Sivyer Steel Casting Co. Material [endothermic] for making shell molds, P (10) 342*h*.

Sizelove, J. R. See Love, J. A., III.

Sizikova, N. G. See Krokhina, A. I.

Sjodahl, L. H. X-ray measurement of strain in TaC due to composition gradients, (6) 239*g*. See Bittel, J. T.; Hein, R. A.

Skaggs, C. W. See Heath, H. E.

Skaggs, R. L. See Peterson, D. T.

Skalla, N. See Maier, K. M.; Moertl, G.

Skalskaya, U. L. See Kruglitskii, N. N.

Skalski, J. F., and Petree, M. C. Insulated-gate field-effect transistor using lead salt, P (2) 65*d*.

Skapski, A. C. See Brandt, B. G.; Keve, E. T.

Skeen, C. H., and York, C. M. Laser-induced "blow-off" phenomena, (6) 234*e*.

Skelly, D. C. See Garber, J. A.

Skinner, H. B., and Searcy, A. W. Vapor pressure, the heat of sublimation, and the evaporation coefficient of praseodymium trifluoride, (10) 363*h*.

Skinner, J. G. See Nilsen, W. G.

Skinner, R. H. Analog for non-Newtonian flow, (4) 118*j*.

Sklar, N., and Post, B. Crystal structure of lithium aluminum hydride, (4) 130*h*.

Skolnick, L. P. See Locker, L. D.

Skolozdra, R. V. See Gladyshevskii, E. I.

Skopa, D. D. See Telvatnikov, G. V.

Skorikov, V. M. See Speranskaya, E. I.

Skripak, V. N. See Vishnevskii, I. I.

Skrzec, A. E. See Morley, H. B.

Skrzypczak, J. See Wolski, W.

Skudelny, D. Dust removal at a quartz grinding works, (6) 224*h*.

Skudera, W. J., Jr., and Wade, W. L., Jr. Method of forming magnetic ferrite films, P (2) 65*c*.

Skvara, F. Study of dissolution of α-$CaSO_4 \cdot 1/2H_2O$ in water (I), (2) 83*b*; (II), (7) 245*d*.

Skvor, J. See Bezouska, V.

Slabaugh, W. H., and Carter, L. S. Hydrophilic-hydrophobic character of organomontmorillonites, (5) 195*h*.

Slack, G. A., Ham, F. S., and Chrenko, R. M. Optical absorption of tetrahedral $Fe^{2+}(3d^6)$ in cubic ZnS, CdTe, and $MgAl_2O_4$, (4) 147*h*.

Slagle, O. D. Comments on "Effect of porosity and crystalline orientation on Young's modulus of artificial graphite," (4) 129*a*.

Slater, D. N. See Aspinall, A.

Slavik, J. Gypsum and anhydrite in the salt bearing formations of Moizons in the Ostolowaker, (4) 138*c*.

Sleight, A. W. New ternary oxides of tetravalent platinum and palladium with the pyrochlore structure, (2) 80*j*. See Longo, J. M.; Prewitt, C. T.; Sleight, T. P.

Sleight, A. W., Chamberland, B. L., and Weiher, J. F. Magnetic, Moessbauer, and structural studies on three modifications of $FeMoO_4$, (11) 385*h*.

Sleight, A. W., and Gillson, J. L. Preparation and properties of alkali rhenium bronzes and a WO_3-ReO_3 solid solution, (4) 150*d*.

Sleight, T. P., Hare, C. R., and Sleight, A. W. Metal-metal bonding in $La_4Re_6O_{19}$ and rutile-related dioxides, (6) 235*d*.

Slessor, R. P. See Hill, R. A. W.

Sliepcevich, C. M. See Rein, R. G., Jr.

Sliney, H. E. Self-lubricating fluoride-metal composite materials, P (4) 94*f*.

Slipchenko, V. A., and Kul'skii, L. A. Effect of preparation conditions on the flocculating properties of silica sols, (7) 262*c*.

Slobbe, W. W. See Glovatsky, A.

Slobodnik, A. J., Jr. Microwave frequency acoustic surface wave propagation losses in $LiNbO_3$, (9) 311*a*.

Slocombe, J. W., Parkinson, J. R., and Wilma, D. D. Capacitative moisture measurement, (7) 259*j*.

Slodzian, G. See Castaing, R.

Slosiar, J. See Harman, R.

Slunecko, M., and Kyncl, M. Theoretical analysis of the combustion process in the atomizing jet burner for superfine glass fiber manufacture, (7) 261*f*.

Slutsky, L. J. See Craft, W. L.

Sly, F. A. W. See Brown, D. J.

Slyshankova, V. A. See Bazhenova, L. N.

Smagunova, A. N. See Losev, N. F.

Smailos, E. See Holleck, H.

Small, A. B., and Babcock, H. N. Cementitious systems, P (9) 304*a*.

Small, E. A., Jr. See Berning, P. H.

Small Business Administration. Rock breaking method and apparatus, P (11) 382*j*.

Smalley, I. J., and Cabrera, J. G. Particle association in compacted kaolinite, (10) 358*g*.

Smalley, W. Solids-mixing techniques, (4) 118*c*.

Smallman, R. E. See Hollox, G. E.

Smart, W. L. Fundamentals of electrostatic finishing, (7) 246*b*.

Smeelen, T. J. H. See Hinssen, A. P. P.

Smeltzer, W. W. See Cowgill, M. G.; Madeyski, A.; Perrow, J. M.; Sheasby, J. S.

Smidth, F. L., & Co. Apparatus and method for making a slurry, P (11) 382*h*. Drum sieves, P (11) 382*j*. Grate cooler control method and apparatus, P (1) 3*g*.

Smirnov, M. P. See Bibenina, G. A.

Smirnov, N. S. Determination of the adhesion between a protective coating and a metal, B (5) 204*e*.

Smirnov, P. V. See Obukhovskii, V. V.

Smirnov, V. V. See Kulevskii, L. A.

Smirnova, E. P. See Tumanov, S. G.

Smirnova, E. V. Study of the crystallization of lead-silicate glass of $2PbO \cdot SiO_2$ composition by infrared spectroscopy, (7) 269*c*.

Smirnova, K. A. Synthesis of porous ceramic [silicate] materials for filtration and aeration, (11) 374*b*.

Smirnova, M. F., Dushina, A. P., and Aleskovskii, V. B. Synthesis and chemical properties of aluminosilica gels (I), (1) 39*b*; (II) Sorption properties of aluminosilica gels, (1) 37*h*.

Smirnova, R. I., and Pron, G. F. Interactions of the sulfides of zinc, cadmium, and mercury with telluric anhydride, (7) 267*f*.

Smisko, J. See Conaway, W. A.

Smith, A. B. See Fessler, T. E.

Smith, A. L. Method of staining glass and glass staining compositions, P (5) 175*h*, *i*.

Smith, B. A., and Austin, I. G. Growth of single crystals of transition metal oxides by the arc-transfer method, (4) 138*a*.

Smith, C. B. See Shyne, J. J.

Smith, C. C., and Ely, E. E. Apparatus for adhesively bonding a metal plate to a refractory brick, P (8) 279*i*.

Smith, David. See Stephenson, C. C.

Smith, Don. See Bruns, R.

Smith, D. C. Arc welding electrode, P (4) 93*c*. See Combe, E. C.

Smith, D. E., Tien, T. Y., and Van Vlack, L. H. System NiO-CaO, (11) 387*e*.

Smith, D. G. W. Pyrometamorphism of phyllites by a dolerite plug, (8) 297*c*.

Smith, D. H. See Olsen, K. M.

Smith, D. J. Acid-reacting ceramic grade anatase (TiO_2) pigment, P (11) 382*g*.

Smith, D. K. See Borg, I. Y.

Smith, D. K., and Leider, H. R. Low-temp. thermal expansion of lithium hydride, magnesium oxide, and calcium oxide, (10) 356*b*.

Smith, D. L. See Stark, F. B.

Smith, D. L., and Downie, P. M. Nozzle having interior guide, P (4) 100*d*.

Smith, D. L., Milford, M. H., and Zuckerman, J. L. Mechanism for intercalation of kaolinite by alkali acetates, (4) 143*j*.

Smith, D. M. Evaluation—inorganic vs organic for glass decorating colors, (1) 7*c*.

Smith, D. M., and Elschens, R. P. Infrared study of oxygen adsorption on impure zinc oxide, (10) 355 *g*.
Smith, D. P. See Strehlow, W. H.
Smith, E. Crack bifurcation in brittle solids, (11) 383*h*. Piling up of screw dislocations against a circular cylindrical rigid inclusion, (11) 386*g*.
Smith, G. F. See Margerum, D. W.
Smith, G. P. See Boston, C. R.
Smith, H., and Wootton-Davies, J. W. Treatment [conveying] of granular, crushed, powdered, or like materials, P (7) 263*d*.
Smith, H. F. See McKinney, C. N.
Smith, Herbert J. See Arnold, A. J.
Smith, Howard J. See Spencer-Strong, G. H.
Smith, H. T. See Franks, F.
Smith, I. L. Method for producing electroluminescent zinc-cadmium sulfide-oxide phosphors, P (11) 377*g*.
Smith, J. Another artificial heart ready for human implant any day now, (10) 336*e*.
Smith, J. A. G. See Wilks, R. S.
Smith, J. F. Attachment of leads to semiconductors, P (1) 17*i*.
Smith, J. G. See Fitch, F. T.
Smith, J. L. Dielectric relaxation and dc temperature measurements in evaporated CaF_2 films, (8) 281*b*.
Smith, J. P. See Kraus, H.
Smith, J. P., and Tenny, R. F. Automatic stepping shuttler system for preparing standard thin films for electron microprobe analysis, (9) 314*i*.
Smith, J. S., II. See Mazdiyasni, K. S.
Smith, J. T. See Hull, G. F.
Smith, Jack V. See McVey, C. I.
Smith, Joseph V. Crystal structure of staurolite, (9) 319*h*. Mg pyroxenes at high temps. —inversion in clinoenstatite, (10) 356*e*. See Bennett, J. M.; Birle, J. D.; Chinnor, G. A.; Moore, P. B.; Newton, R. C.
Smith, J. W. See Cross, L. E.
Smith, M. A. See Gutt, W.
Smith, M. F. See Ermenc, E. D.
Smith, M. H. See Miller, K. F.
Smith, M. J. Extruded graphite matrix containing coated particles, P (4) 106*f*.
Smith, N. F. See Anderson, A. R.; Mandonas, N. J.
Smith, P. C. See Genser, M.
Smith, P. H. S. See Stoneham, A. M.
Smith, P. K., and Cathey, L. Preparation and electrical resistance of single crystals of β-US_2, (4) 150*j*.
Smith, R. See Loukes, D. G.
Smith, R., Stafford, C. M., and Winefordner, J. D. Interference effects in the hydrogen/argon/entrained-air flame, (1) 21*c*.
Smith, R. E. Petrography-porosity relations in carbonate-quartz systems, Gatesburg formation (late Cambrian), Pennsylvania, (9) 326*g*.
Smith, R. E., Holmes, C. D., and Henkel, C. E. Fused projector lamp, P (4) 113*g*.
Smith, Richard G. See Bergman, J. G.; Geusic, J. E.
Smith, Richard G., Geusic, J. E., Levinstein, H. J., Rubin, J. J., Singh, S., and Van Uitert, L. G. Continuous optical parametric oscillation in $Ba_2NaNb_5O_{15}$, (4) 129*h*.
Smith, Roger G. See Sansom, K. G.
Smith, S. H., and Elwell, D. Growth of nickel ferrite crystals from barium borate by a pulling method, (7) 254*j*.
Smith, S. T. See West, R. R.
Smith, S. V., and Utley, R. W. Froth flotation for impure carbonate sediments, (1) 23*g*.
Smith, Tennyson. Controlled atm Langmuir trough with simultaneous automatic recording of ellipsometric, contact potential, and surface tension measurements, (5) 187*d*.
Smith, Thomas. See Buyers, W. J. L.
Smith, V. C. See Dodge, F. C. W.
Smith, W. C. See Martin, F. W.
Smith, W. D., and Liebmann, H. J. Material distributing device in a vertical kiln, P (4) 123*c*.
Smith, W. E. See Rhodes, E.
Smith, W. H., Whitley, D. M., and Eaton, E. P., Jr. Anisotropic continuous casting mold, P (7) 252*c*.
Smith, W. L. Acoustical panels, P (9) 307*j*.
Smith, W. M., and Gladrow, E. M. Zeolitic materials, P (4) 126*b*.
Smith, W. N., Jr. Method for preparing lithium peroxide, P (8) 288*b*. See Beumel, O. F., Jr.
Smith, W. S. Glassware forming apparatus with blowhead control, P (1) 10*h*.
Smoes, S. See Coppens, P.; Drowart, J.; Patteret, A.
Smolczyk, H. G. X-ray fine-structure diffraction as mineralogical-analytical method, (2) 71*f*.
Smolders, A. See Mestdagh, G.
Smolinsky, G. See Burgiel, J. C.
Smolski, A. Method of drying ceramic products, P (10) 348*e*. [Zone controlled] tunnel dryer, P (10) 348*e*.
Smolyaninov, N. P. Dilatometry of the system Bi_2O_3-MoO_3, (8) 290*h*.
Smoot, T. W. See Cope, G. R.
Smothers, W. J. See Herron, R. H.
Smrcek, A. Laws of heat transmission during hot-forming of molten-glass (I), (10) 338*b*.
Smulikowski, K. Differentiation of eclogites and its possible causes, (5) 193*d*.
Smull, E. R. Ladle stopper head assembly, P (11) 375*b*.
Smutz, M. See Sebenik, R. F.
Smyth, D. M. Donor ion modified $BaTiO_3$ capacitor and process, P (5) 182*g*. Heat treatment of anodic oxide films on tantalum (V) thermal redistribution of incorporated phosphorus, (2) 78*a*.
Smyth, D. M., and Tripp, T. B. Heat treatment of anodic oxide films on niobium, (2) 77*j*.
Smyth, J. R. See Moore, P. B.
Smyth, R. L. Marketing for profit, (6) 240*d*.
SNAM S.p.A. Method for preparing spheroidal alumina, P (4) 124*i*.
Snaper, A. A. Electrooptical device with concentric arrangement of layers, P (8) 282*f*.
Snavely, B. B. Electroabsorption of CdS, (4) 134*g*.
Snell, P. O. See Lundstrom, T.
Snitzer, E. Plural fiber optic laser construction, P (4) 100*g*. See Koester, C. J.
Snitzer, E., Bazinet, W. P., Jr., and Hwalek, D. C. Method of making optical couplers, P (10) 339*b*.
Snitzer, E., Young, R. W., and Woodcock, R. F. Glass laserable material, P (5) 174*h*.
Snogren, R. C. Systematic approach to selection of surface preparation process (I); (II) selection of surface preparation processes, (8) 284*g*.
Snow, E. H. Variable threshold insulated-gate field-effect device, P (6) 224*c*. See Cagnina, S. F.; Lenzlinger, M.
Snow, G. S. Thermally activated diffusion of electronic carriers in iron phosphate glasses, (5) 173*h*.
Snow, R. H. Size reduction, (4) 118*c*.
Snow, R. H., and Work, L. T. Size reduction, (1) 20*c*.
Snow, R. J. See Welch, B. J.
Snow, W. E. Ladle for use in treatment of molten metal, P (4) 106*c*.
Snowden, B. S., Jr. See Woessner, D. E.
Snyder, A. W., and Pick, G. G. Ferrite core having different regions of varying permeability, P (4) 113*c*.
Snyder, R. P. Flexible abrasive wheel and method of making, P (4) 89*i*.
So, J. J. Method of manufacturing semiconductor devices, P (2) 65*g*.
Sobel, I. J., and Didyk, . Miniature ceramic microphone, P (7) 257*d*.
Sobel'man, E. I., Tyulyaeva, N. G., and Kashirin, V. F. Regularity in sectorial structures of crystals grown from a melt, (4) 153*h*.
Sobol, N. P. See Svirskii, L. D.
Soboleev, Ch. S. See Gendelev, S. Sh.
Sobolev, G. P., Levitskii, V. K., Nikitina, K. T., and Sorokin, N. F. Gas chamber kiln with mobile hearth tor firing technical ceramic bodies and articles, (6) 228*h*.
Sobolev, N. V., Jr. Eclogite clinopyroxenes from the kimberlite pipes ot Yakutia, (4) 132*f*.
Sobolev, N. V., Jr., Kuznetsova, I. K., and Zyuzin, N. I. Petrology of grospydite zenoliths from the Zagadochnaya kimberlite pipe in Yakutia, (1) 34*f*.
Societa Ceramica Italiana Richard-Ginori S.p.A. Abrading apparatus for finishing plates, P (1) 15*i*. Equipment for varnishing ceramic stock semifinished products, in particular crockery, P (5) 180*b*.
Societe Alsacienne de Constructions Atomiques de Telecommunications et d'Electronique Alcatel S.A. Ferroelectric ceramics, P (7) 256*h*. Manufacture of ferroelectric parts, more particularly of transducers, P (10) 345*d*. Method of manufacturing ferroelectric ceramics, P (5) 183*j*.
Societe Anonyme Glaverbel. Apparatus for the production of ribbed glass sheets, P (11) 370*j*. Apparatus for supporting and conveying glass sheets on a gas support bed, P (5) 174*h*. Furnace arrangement and method, P (11) 371*g*. Glass furnace wall arrangement, P (8) 277*e*. Glassmelting furnace with vacuum feed means, P (6) 212*e*. Melting furnace for manufacturing flat glass, P (1) 11*b*. Method and apparatus for manufacturing float glass with internal circulatory bath heat exchange, P (7) 249*b*. Multipane glazing unit, P (11) 372*a*. Process for agglomerating vitrifiable masses and the products thereof, P (9) 308*b*. Process for homogenizing glass by gas injection, P (4) 100*h*. Refractory composition and process for producing, P (5) 179*e*.
Societe Anonyme de Machines Electrostatiques. Method and apparatus for the electrostatic sorting of granular materials, P (1) 20*e*, P (2) 74*d*.
Societe le Carbone-Lorraine. Process for the manufacture of macroporous vitreous carbon, P (8) 273*j*.
Societe des Ciments Francais. Method and arrangement for producing white cement, P (9) 304*c*.
Societe des Ciments Portland de Saint-Maurice S. A. Cooling and suction device of an installation comprising a [rotary] furnace having at one side a burner producing a flow of hot gases and at the other side a distributor of material to be boiled, P (8) 286*f*.
Societe d'Electronique et d'Automatisme. Electrical film resistors, P (7) 256*e*. Preparation of tin oxide resistances, P (1) 19*b*.
Societe d'Etudes et de Participations Couquelet S. A. Apparatus for controlled heat softening of glass tubing, P (11) 370*i*.
Societe Generale de Constructions Electriques et Mecaniques (Alsthom). Apparatus for continuous weighing of powdered or granular materials with weight regulation of the flow, P (2) 67*f*.
Societe Generale des Produits Refractaires. Prefiring of refractory materials, P (5) 179*a*.
Societe Lignes Telegraphiques et Telephoniques. Process for manufacturing high porosity sintered parts, P (10) 347*a*. Solid electrolytic capacitor having mixed dioxide semiconductor layer, P (11) 378*j*.
Societe des Lunetiers, Cottet, Poichet, Temkine & Cie. Lens trimming machines, P (10) 399*h*.
Societe Nationale des Petroles d'Aquitaine. Specimen changer for an X-ray fluorescence spectrometer, P (4) 122*a*.
Societe a Responsabilite Limitee Doittau Produits Metallurgie. Insulating and refractory composition and elements for the lining of metal casting molds incorporating such compositions, P (2) 58*h*.
Societe Rhodiaceta. Process for rendering glass and polyesters adhesive to rubber, P (11) 372*a*.
Society of Glass Technology, Chemical Analysis Committee. Determination of potassium oxide in soda-lime-magnesia-silica glasses—a comparison of flame photometric and gravimetric methods, (7) 259*i*. Investigation into the use of EDTA for the determination of alumina in soda-lime-silica glasses, (7) 260*g*.
Socino, G., De Batist, R., and Gevers, R. Relaxation processes in single-crystal UO_2, (8) 297*j*.
Sockel, H. G. See Holt, J. B.
Sodell Research & Development Co. Method for preparing a slide for viewing, P (9) 315*i*.
Soderling, L. A. Electrical conductivity test method for determining active clay content in molding sand compositions, P (4) 121*f*.
Sodha, M. S., Gupta, G. P., and Sharma, S. Generation of microwave second harmonic and sum and difference frequency in semiconductors at low temperatures, (5) 181*e*.
Sodi, J., and Elliott, John F. Free energy of formation of ReS_2, (4) 136*g*.
Soeya, Teruko. Transient phenomena in dc electroluminescence in thin films of zinc sulfide, (8) 300*j*.
Soffer, B. H. See Hoskins, R. H.
Sofronova, A. V. See Pechkovskii, V. V.
Soga, Minoru; Imaizumi, Rikizo; Kondo, Yoshihiro; and Okabe, Takahiro. Method of growing CuCl single crystals with flux, (4) 144*h*.
Soga, Naohiro. Elastic constants of polycrystalline BeO as a function of pressure and temperature, (7) 265*a*.
Sogawa, Satori, and Ozaki, Hiroshi. Convenient method of calculating viscosity by means of fusion flow test for frits, (6) 225*i*.
Sokolov, V. I., and Hien, T. D. Magnetostriction of single crystals of terbium and holmium ferrite garnets at low temperatures, (2) 80*h*.
Sokolova, A. A., and Mukhina, Z. S. Amperometric determination of molybdenum in [enamel] frits, (2) 68*f*.
Sokolova, I. D. See Krivovyazov, E. L.
Sola Basic Industries. Apparatus for effecting bonding of semiconductor parts, P (9) 312*a*. Apparatus to sever [gold] wire bonded to semiconductor devices, P (9) 312*b*.
Solar Engineering & Equipment Co. Glass bottle handling apparatus, P (5) 174*e*.
Solaronics, Inc. Tile assembly for radiant gas burners, P (7) 253*b*.
Solbu, A. See Thonstad, J.
Soldani, G. See Bertozzi, G.
Sole, M. J. See Van Der Walt, C. M.
Sole, M. J., and Van Der Walt, C. M. Oxidation and deformation studies of uranium nitride by electron microscopy, (1) 33*j*.
Sole, M. J., Van Der Walt, C. M., and Truzenberger, M. Electron microscope studies of uranium sulfide single crystals (I) slip behavior; (II) precipitation phenomena, (1) 28*f*.
Solf, A. See Ohnemueller, W.
Solitron Devices, Inc. Connection arrangement for three-element component to a microelectronics circuit, P (4) 112*b*. Method of assembly of power transistors, P (4) 114*i*.
Solntsev, S. S., and Fridman, Ya. B. Analysis of cracks and fracture in glass, (4) 94*h*.
Solntseva, V. A. See Satalkin, A. V.
Solomon, P. R. Relaxation of Mn^{2+} and Fe^{3+} ions in magnesium oxide, (4) 153*i*.
Solomons, C., Clarke, J. H. R., and Bockris, J. O'M. Identification of the complex ions in liquid cryolite, (6) 233*d*.
Solomons, C., and White, M. S. Oscillating plate viscometry (I) theoretical principles, (9) 315*b*.
Solov'ev, S. P. See Dem'yanov, V. V.
Solovova, I. P. See Lapin, V. V.
Soltis, D. G. See Arrance, F. C.
Soltz, D. J. Apparatus [glass electrode] for measuring pH with temperature compensating diode means, P (2) 71*i*.
Solymar, K. See Dobos, G.
Solymosi, F., and Bansagi, T. Thermal stability of chlorine oxysalts in the solid state (I) kinetic study of the disproportionation and explosion of some chlorites; (II) kinetic and derivatographic study of the thermal de-

composition of some metal chlorates, (5) 201*i*.
Somasundaran, P. Zeta potential of apatite in aqueous solutions and its change during equilibration, (5) 203*e*.
Somasundaran, P., and Agar, G. E. Zero point charge of calcite, (5) 203*d*.
Somasundaran, P., Healy, T. W., and Fuerstenau, D. W. Aggregation of colloidal alumina dispersions by adsorbed surfactant ions, (1) 25*a*.
Someno, Mayumi. See Kashida, Koichi.
Somers, A. V. Method of making a ceramic core, P (5) 178*j*. See Fenerty, M. J.
Someya, Akira. See Hashimoto, Tsunekazu.
Somiya, Shigeyuki. See Saito, Shinroku; Tagai, Hideo.
Sommelet, P. See Lichter, B. D.
Sommer, E. Fracture behavior of glass rods in oil jacket pressure tests with superimposed tensile stress, (9) 305*f*.
Sommer, J. G. See Daly, J. H.
Sommer & Maca Glass Machinery Co. Glass [sheet] washing apparatus, P (9) 307*f*.
Sommerfeld, R. A. Critical evaluation of the heats of formation of zoisite, muscovite, anorthite, and orthoclase, (4) 130*b*.
Somody, A. See Paulik, I.
Somorjai, G. A. See Lester, J. E.
Sonnenberg, H. Low-work-function surfaces for negative-electron-affinity photoemitters, (11) 385*e*.
Sonnino, T. See Pasternak, M.
Sonnleitner, D. See Hazdra, J. J.
Sonoco Products Co. Forming tube for glass fibers, P (9) 307*e*, P (10) 338*j*.
Sonoda, T. See Ohtsuki, T.
Sonomura, Hajimu. See Miyauchi, Takeshi.
Sonsthagen, L. A. Process for dispersing pigments in liquid media, P (11) 379*g*.
Sony Corp. Cathode ray tube color screen and method of producing, P (7) 255*i*. Method of making color screen for cathode ray tube, P (9) 312*j*. Method of making a semiconductor junction by diffusion, P (8) 283*b*. Semiconductor having reinforced lead structure, P (9) 314*a*.
Sopher, R. P. See Napier, J.
Soppet, F. E. See Ayer, J. E.
Sorai, Michio; Kosaki, Akio; Suga, Hiroshi; and Seki, Syuzo. Particle size dependence of the magnetic heat capacity of $Ni(OH)_2$ crystals at low temperatures, (4) 148*f*.
Sorai, Michio; Suga, Hiroshi; and Seki, Syuzo. Thermal properties of alkali halide crystals with the CsCl-type structure (I) construction of a calorimeter for the temperature region 1°–20°K and heat capacities of cesium bromide and cesium iodide between 1.5° and 300°K, (4) 160*g*.
Sorbie, T. B. Bottle gaging, P (5) 174*a*. Method and apparatus for inspecting glass containers, P (4) 99*d*.
Soria-Ruiz, J. See Bowden, F. P.
Sorocopud, L. See Deica, N.
Sorokin, I. P., Dmitrevskii, G. E., Kol'tsov, Yu. I., Blinov, B. S., and Belitskaya, A. A. Thermal decomposition of potassium hexafluorotitanate, (8) 300*e*.
Sorokin, N. F. See Sobolev, G. P.
Sorrell, C. A. Fusion and vaporization characteristics of $ZrTe_2O_5$, (1) 30*e*. See Negas, Taki.
Sosin, A., and Bauer, W. Impurity-delayed diffusion, (1) 30*i*.
Soskin, M. S. See Broude, V. L.
Soucy, P. L. See Jarboe, E. D.
Soudain, G. See Carpentier, S.
Souma, Isao. See Shindo, Akio.
Souquet, J. L., Deportes, C., and Besson, J. Electrochemical study of the diffusion of silica in a molten sodium silicate (I), (4) 134*h*.
South African Inventions Development Corp., Council for Scientific & Industrial Research. Recovery of cesium and nitrous oxide from fission product solutions containing ammonium nitrate, P (4) 125*g*.
South African Iron & Steel Industrial Corp., Ltd. Zone refining, P (6) 228*a*.
South Eastern Gas Board. Control of gas flame characteristics, P (2) 72*f*.
Southgate, P. D. Laser action in field-ionized bulk GaAs, (1) 31*g*.
Southington Mfg., Inc. Continuous operation [gravity fed] mulling apparatus and method for accurately proportioning foundry sand ingredients, P (6) 217*i*.
Southwestern Engineering Co. Means for improving performance of separator screens, P (5) 186*b*. Self-discharging finishing mill, P (5) 186*f*. Vibratory separator, P (5) 186*g*.
Sovers, O. J. See Avella, F. J.
Sowers, H. L., Ruggieri, D. J., and Balkwill, J. T. Electrooptic image intensifier and method of making same, P (11) 376*e*.
Sowman, H. G. See Johnson, J. R.
Space Age Materials Corp. Grain-oriented pyrolytic graphite forms and method [vapor deposited] of making, P (4) 106*i*.
Spacil, H. S. Solid stabilized zirconia or thoria having a layer of tantalum pentoxide and titanium oxide thereon, P (1) 19*a*.
Spaite, P. W. See Potter, A. E.
Sparkler Mfg. Co. Means for detecting filter cake buildup, P (6) 225*b*.
Speakman, J. C. See Kennard, O.
Speakman, K. Properties of compacted synthetic kilchoanite material, (2) 73*c*.
Speakman, K., Taylor, H. F. W., Bennett, J. M., and Gard, J. A. Hydrothermal reactions of γ-dicalcium silicate, (4) 139*j*.
Spear, B. W. See Powell, D. E.
Spear, K. E., Gilles, P. W., and Schafer, H. Chemical transport reactions in the vanadium-silicate-oxygen system and the ternary phase diagram, (5) 192*f*.
Spear, K. E., and Leitnaker, J. M. Consistent set of thermodynamic values for plutonium mononitride, (1) 26*i*. Formation of active carbon in twin-crucible studies of vanadium carbonitride solutions, (7) 265*j*.
Spear, K. E., Schafer, H., and Gilles, P. W. Vanadium-boron-nitrogen system, (8) 300*c*.
Spears, D. L., and Bray, R. Modulation by optical absorption at the intrinsic edge of acoustoelectric domains in *n*-GaAs, (1) 33*b*.
Spedden, H. R., and Schellinger, A. K. Process of producing high purity alumina from aluminum-bearing acidic sulfate solutions, P (7) 263*a*.
Spedding, P. L., and Mills, R. Tracer diffusion measurements in mixtures of molten alkali carbonates, (1) 39*h*.
Speicher, C. A. See Potts, H. R.
Speidel, D. H. See Lindsley, D. H.
Speidel, D. H., and Nafziger, R. H. *P-T-*f_{O_2} relationships in the system FeO-MgO-SiO_2, (6) 236*e*.
Speidel, D. H., and Osborn, E. F. Element distribution among coexisting phases in the system MgO-FeO-Fe_2O_3-SiO_2 as a function of temperature and oxygen fugacity, (4) 135*e*.
Speight, M. V. Growth kinetics of grain-boundary precipitates, (1) 30*i*.
Spell, S. See Konrad, H. E.
Spektor, A. N. See Menkovskii, M. A.
Speliotis, D. E. See Bate, G.
Spencer, A. J. M. See Mulhern, J. F.
Spencer, D. H. T. See Napier, B. A.
Spencer, D. R. F., and Coleman, D. S. Densities of silicates in the CaO-MgO-SiO_2 system, (10) 351*h*.
Spencer, E. G. See Lenzo, P. V.
Spencer-Strong, G. H. See Eppler, R. A.
Spencer-Strong, G. H., and Smith, Howard J. Process for preparing nucleated frit and white-enameled cast iron bodies prepared from the frit, P (2) 46*a*.
Speranskaya, E. I., and Skorikov, V. M. Bismuth titanates and ferrites, (2) 61*e*. Problem of the sillenite phase, (8) 296*g*.
Sperber, H. See Rebhun, M.
Speros, D. M. See Hanneman, R. E.
Speros, D. M., and Woodhouse, R. L. Realization of quantitative differential thermal analysis (II) solid-gas reaction, (8) 297*g*.
Sperry, D. R., & Co. Device for separating plates and frames of filter presses, P (8) 284*e*.
Sperry, L. L., and Mackenzie, J. D. High-pressure, high-temperature viscometer, (9) 315*f*. Pressure dependence of viscosity of B_2O_3, (1) 8*d*.
Sperry Rand Corp. Broadband reciprocal dual meander line ferrite phase shifter, P (9) 312*c*. Laser fluid flow sensor insensitive to rotation, P (9) 312*d*. Method for fabricating memory apparatus, P (11) 377*j*. Optical computer comprising semiconductor *pn* junction components, P (6) 223*c*. Optical inspection system, P (7) 259*d*. Oxygenated silicon nitride semiconductor devices and silane method for making, P (5) 184*e*. Sharp thin ferromagnetic film, P (6) 223*j*.
Speyer, D. M. See Blank, Z.
Spicak, K., Hanykyr, V., and Esner, M. Wear of porcelain balls during dry milling, (10) 346*i*.
Spicak, K., Tyrolerova, P., and Chaloupka, J. Thixotropy control of porcelain bodies with higher alumina content, (10) 343*f*.
Spicar, E. See Svedberg, P.
Spicer, W. E. See Liu, Y-Z.
Spickenreuther, D. See Eugster, E.; Weisshaar, E.
Spiegler, J. High strength resistor, P (7) 256*a*.
Spielberger, R. K. See Miller, L. F.
Spielman, L., and Goren, S. L. Improving resolution in Coulter counting by hydrodynamic focusing, (5) 187*a*.
Spielman, L. S., and Moore, E. E. Nozzle mixing gas burner, P (4) 123*b*.
Spielmann, H. Ceramic artists and their work —Jan Bontjes van Beek, (1) 2*b*.
Spielmann, W. K. See Ebert, E.; Immendorfer, M.
Spiering, G. A. See Revolinsky, E.
Spiers, H. R. Porcelain enameled parts from precoated coils, (5) 171*i*. Porcelain enameling by coil coating—a status report, (7) 246*f*. Progress report—ceramic coil coating, (8) 275*c*.
Spindel-, Motoren-, und Maschinenfabrik A. G. Apparatus for analyzing fresh concrete, P (4) 121*d*.
Spink, J. A. Thermal desorption of stearic acid monolayers from mica and silver, (1) 39*b*.
Spinks, J. L. Mineral wool furnaces, (4) 122*j*.
Spinulescu-Carnaru, I., Draghici, I., and Petrescu, M. Crystalline structure of PbTe thin films, (8) 280*i*.
Spiridinov, F. M., Stepanov, V. A., Komissarova, L. N., and Spitsyn, V. I. Binary system HfO_2-Gd_2O_3, (7) 263*i*.
Spirko, E. J. See Komac, T.
Spit, B. J., and de Jong, J. Examples of investigations on glass with the electron microscope, (11) 370*b*.
Spitsyn, V. I. See Bkhargava, Kh. D.; Spiridinov, F. M.
Spitz, J. See Chevallier, J.
Spitzer, R. H., Manning, F. S., and Philbrook, W. O. Simulation of topochemical reduction of hematite via intermediate oxides in an isothermal countercurrent reactor, (2) 83*b*.
Spitzer, W. G., and Allred, W. Site transfer of Si in GaAs, (1) 37*a*.
Spitzin, B. V. See Derjaguin, B. V.
Spivak, G. V. See Gladneva, L. I.; Shakmanov, V. V.
Spivak, G. V., Dubinina, E. M., Dyukov, V. G., Luk'yanov, A. E., Sedov, N. N., Petrov, V. I., Pavlyuchenko, O. P., Saparin, G. V., and Nevzorov, A. N. Stroboscopic electron microscopy, (2) 71*a*.
Spohr, H. See Bredsdorff, P.
Spooner, N. F. See Sibley, F. S.
Sprackling, M. T. Annealing of slightly bent AgCl single crystals, (9) 318*c*.
Sprague, L. G. Method of making electric heating units, P (7) 249*f*. See Bennett, R. W.
Sprague Electric Co. Capacitance-adjusted ceramic capacitor, P (10) 344*c*. Controlled reduction and reoxidation of $BaTiO_3$ capacitors and resulting capacitor, P (5) 182*a*. Distributed barrier metal-semiconductor junction device, P (9) 312*e*. Donor-acceptor ion-modified barium titanate capacitor and process, P (5) 182*g*. Donor ion-modified $BaTiO_3$ capacitor and process, P (5) 182*g*. *LA* junction lateral transistor, P (8) 282*b*. Method [epitaxial growth] of making a narrow base transistor, P (10) 345*f*. Method for inspecting semiconductor devices using electron mirror microscopy, P (2) 65*e*. Method of making a capacitor with an oxygen-pervasive and an oxygen-impervious electrode, P (6) 222*f*. Method of making a transistor with a very thin diffused base and an epitaxially grown emitter, P (2) 65*h*. Method of preparing +2 valent metal yttrium and rare earth ferrites, P (7) 257*b*. Monolithic structure with three-region complementary transistors, P (4) 115*j*. Monolithic structure with three-region or field-effect complementary transistors, P (4) 115*j*. Multiplane metal-semiconductor junction device, P (9) 312*e*. Narrow emitter lateral transistor, P (8) 283*f*. Negative resistance diode, P (2) 66*c*. Resistance element utilizing group III or VB metal, P (4) 116*h*. Silicon nitride coating on semiconductor and method, P (5) 185*j*. Stacked mica capacitor having a multiple value mica film, P (1) 19*b*. Transistors and method of manufacturing, P (5) 185*h*.
Sprenger, H., and Nickl, J. New titanium silicide—$TiSi_4$, (6) 235*h*.
Spriggs, R. M. See Vasilos, T.
Springthorpe, A. J. Preparation of single crystal orthorhombic SiP_2, (10) 359*i*.
Springthorpe, A. J., and Harrison, J. G. Mg-SiP_2—a new member of the II-IV-V_2 family of semiconducting compounds, (10) 357*f*.
Springthorpe, A. J., and Pamplin, B. R. Growth of some single crystal II-IV-V_2 semiconducting compounds, (7) 255*a*.
Sproles, J. D. See Pirrello, A.
Sproul, J. D., Jr. Abrasion resistant glass bead with sharp softening range and process for making, P (4) 98*b*. High melting point glass beads with sharp melting range and process for making, P (6) 212*f*.
Sprouse, N. T. See St. Louis, R. V.
Spruiell, J. E. See Venard, J. T.
Spry, A., Turner, R. G., and Tobin, R. C. Optical phenomena associated with Brazil-twin boundaries in quartz, (10) 358*c*.
Spry, W. J. Process for producing fibrous graphite, P (10) 343*b*.
Spurr, R. Container inspection machine, P (5) 174*b*.
Squier, C. A. See Hughes, J. V., Jr.
Squire, C. F., and Zamecki, E. R. Optical birefringence in alkali halides, (4) 147*h*.
Squire, G. L. See Ward, J. M.
Srinivasagopalan, C. See Henisch, H. K.
Srivastava, J. P. Absorption spectrum of Co^{2+}-doped NaF, (6) 230*f*.
Srivastava, K. P. See Prasad, S. N.; Ram, A.
Srivastava, R. C., and Abrol, Y. P. Time of coagulation as a function of electrolyte concentration—a modified empirical relationship, (6) 239*b*.
Srivastava, R. S. See Ramachandran, V. S.
Srivastava, S. N. See Daluja, K. L.
Srivastava, S. P., and Madan, M. P. Infrared absorption frequency and characteristic Debye temperature of some halides and oxides of heavier salts, (2) 79*a*.
Srygley, F. D. See Chen, Y.
Stablein, H., and May, W. Phase investigations of the system BaO-Fe_2O_3-Fe_2O_3, (11) 376*b*.
Stacey, M. H. See Ray, N. H.
Stadelmaier, H. H. See Fraker, A. C.
Stadler, H. L. Transducer utilizing electrically polarizable material, P (9) 314*c*.
Stadnyk, B. I. See Kuz'ma, Yu. B.
Staebler, D. L., and Kiss, Z. J. Photoreversible charge transfer in rare-earth-doped CaF_2, (10) 358*g*.
Stafford, C. M. See Smith, R.
Stafford, F. E. See Steck, S. J.
Stafsudd, O. M. See Gentile, A. L.
Stager, C. V. See Calvo, C.; Gornostansky, S. D.

Stahl, E. A., Jr. See Tipsword, R. F.
Stahl, N. See Bergh, S.
Stahl, R. See Jacobi, R.
Stakheeva, S. A. See Khazanov, E. I.
Stalego, C. J. Internal combustion burner nozzle construction, P (2) 53*c*. Method and apparatus for processing heat-softened material, P (2) 53*a*. Opalescent glass fibers, P (4) 100*e*.
Stamicarbon N. V. Process for determining the free-oxygen content of a gas or dust mixture, P (4) 122*e*.
Standard Electrik Lorenz AG. Method and apparatus for making video tubes implosion-proof, P (11) 371*d*.
Standard Oil Co. Acid-resistant cement products, P (9) 304*f*.
Stanek, J. Electric glassmelting, (2) 48*f*. See Goetz, J.
Stanek, J., Sasek, L., and Meissnerova, H. Flow of glass in furnaces heated by electricity, (8) 276*i*.
Stanford Research Institute. Luminescent films containing rare earth oxides, P (6) 221*j*. Thin wafer-channel multiplier, P (11) 378*a*.
Stanicic, N. See Krleza, F.
Stanton, N. B. Determination of zirconium in mineral rutile with Alizarin Red S, (6) 226*c*.
Stanton, R. L., and Gorman, H. Annealing of single phase polycrystalline sulfide ores, (8) 288*i*.
Stanway, V. M. See Pitt, E. E. H.
Stapf, V. M., and Babunovic, M. Light transparent container inspecting apparatus, P (10) 339*h*.
Staples, B. G. See Warren, G.
Staples, B. R., and Bates, R. G. Two new standards for the pH scale, (6) 227*f*.
Stapley, A. J., and Beevers, C. J. Some electron microscope observations of alumina whisker/nickel composites, (8) 279*f*.
Starbuck, C. L. See Ashburn, L. L.
Starck, H. C. Composite powders and apparatus for production, P (6) 208*a*.
Stark, F. B., and Smith, D. L. Ceramic insulator in cable connections, P (7) 255*j*.
Stark, K. See Eckert, O.
Stark, S. O. S. See Tornqvist, N. E.
Stark Ceramics, Inc. Interlocking building block, P (5) 176*g*.
Starkey, H. C. See Shepard, A. O.
Starnes, P. E. Radiometric analysis of powdered sample material, P (8) 286*b*.
Staronka, A., Pham, H., and Rolin, M. Study of the system SiO_2-Al_2O_3 by the cooling curve method, (5) 200*d*.
Starzacher, A. Hot modulus of rupture at high temperatures, (4) 104*e*.
Statman, M. See Hagemeyer, H. J., Jr.
Staude, H. See Schmidt, K.
Stauffer, J. L. See Blackburn, P. E.
Stauffer Chemical Co. Cleaning compositions and method of using the same, P (4) 164*j*. Increasing the bulk density of soda ash by adding calcium and magnesium ions prior to precipitation, P (11) 382*b*. Preparation of molds, P (6) 218*g*. Process for producing boric acid from alkali metal borates, P (10) 349*c*.
Staunton, J. J. Monochromator system with selective diffraction grating system, P (4) 122*b*. Optical prism unit and manufacture thereof, P (9) 308*e*.
Staveley, L. A. K. See Waterfield, C. G.
Steatit-Magnesia Akt.-Ges. Electroless formation of electrical resistance films, P (1) 18*e*.
Steblovskaya, S. N. See Safonov, V. V.
Steck, A. B. Material [endothermic] for making shell molds, P (10) 342*h*.
Steck, S. J., Pressley, G. A., Jr., Lin, Sin-Shong, and Stafford, F. E. Mass-spectrometric investigation of the reaction of hydrogen with graphite at 1900°-2400°K, (11) 386*a*.
Stedman, D. F. Production of amorphous ferric oxide, P (4) 125*d*.
Stedman, G. E. Crystal field of ruby and stressed MgO:Cr^{3+}, (10) 351*h*.
Steele, B. C. H. See Alcock, C. B.
Steele, B. C. H., Powell, B. E., and Moody, P. M. R. Anionic conduction in refractory oxide solid solutions possessing the fluorite, pyrochlore, and perovskite structures, (10) 349*h*.
Steele, B. R., Rigby, F., and Hesketh, M. C. Investigations on the modulus of rupture of sintered alumina bodies, (2) 56*j*.
Steele, J. L., and McCartney, E. R. Anisotropy of diffusion in rutile, (10) 349*j*.
Steele, T. W. See Pearton, D. C. G.
Steelman, C., Jr. See Robinson, M. W., Jr.
Stefanovskii, E. E. Economic tendencies in the silicate materials industry in the United States, (2) 85*a*.
Steggewentz, H., and Schlueter, K. Method of influencing the surface profile of semiconductor layers precipitated from the gas phase, P (4) 115*a*.
Steidl, D. V. See Trevorrow, L. E.
Steigelman, H. A. Glass surfaces having dual protective label accepting coatings and method, P (5) 174*j*.
Steimke, F., and Charbonnier, W. P. Advances in glass tank refractories, (1) 5*i*.
Stein, A. See Sims, S. D.
Stein, F. Temperature control of large [oil-fired] container glass tanks, (9) 307*g*.
Stein, H. N. Calcium silicates and their surface layers in aqueous electrolyte solutions, (6) 230*j*. See De Jong, J. G. M.
Stein, J. L. Refractory brick suspension arrangement, P (2) 59*e*. See Farrington, G. M.
Stein, K. U. See Feldtkeller, E.
Steinbach, F. Photosensitized oxidation of carbon monoxide on semiconductors supported by silver, (5) 181*a*.
Steinbach, H. See Hitzemann, G.; Kulling, A.
Steinbacher, J. T. Method and apparatus for cleaning foundry cores, P (10) 342*i*.
Steinberg, D. R. System for measuring temperature, P (6) 228*c*.
Steinberg, I. V. Method of treating alumina abrasive grains with iron nitrate and products made thereby, P (5) 169*h*.
Steinbruegge, K. See Mazelsky, R.
Steindler, M. J. See Riha, J. G.; Trevorrow, L. E.; Vissers, D. R.
Steiner, D. F. Ultrasonic cleaning (I) how and why it works, (2) 67*d*; (II), (4) 118*f*.
Steingroever, E. Magnetic thickness gage having shielded magnet, P (7) 260*j*.
Steinhauser, O., von Fragstein, P., and Harzdorf, C. Analysis of fluorspar, (5) 186*j*.
Steininger, J. Growth of CdSe single crystals by temperature gradient solution zoning in excess Se, (7) 266*f*.
Steininger, J., and England, R. E. Growth of single crystals of ZnTe and $ZnTe_{1-x}Se_x$ by temperature gradient solution zoning, (2) 77*h*.
Steinitz, R. Elements [TaC] for incandescent devices, P (7) 248*f*.
Steinmetz, E., and Roth, H. Free energy of formation of chlorides and fluorides, (9) 321*i*.
Stejskal, E. O. See Boss, B. D.
Stengle, E. J., Jr. Method of assembling a composite container, P (7) 249*c*.
Stengle, T. R. See Caron, A. P.; Huettner, D. J.
Stepanov, V. A. See Spiridinov, F. M.
Stephanoff, N. N. Apparatus [fluid impact] for treating solid granular material, P (10) 346*j*. Method for drying or treating wet solid and semisolid materials, P (2) 68*c*.
Stephans, R. W. See Zysk, E. D.
Stephen, F. M. See Ozenne, G. J.
Stephens, R. C. Elements for the support of refractory anchors, P (4) 106*f*.
Stephens, R. E. See Reitmeier, R. E.
Stephenson, C. C., and Smith, David. Heat capacity of manganese titanate from 30° to 300°K, (8) 292*i*.
Stephenson, D. A. Improved flux-fusion technique for X-ray emission analysis, (10) 347*g*.
Stephenson, J. B. See Donaldson, J. G.
Stepinac, M., and Karsulin, M. Function of pH of glasses in the system Li_2O-BaO-$(Pr,Nd)_2O_3$-SiO_2, (4) 95*i*.
Stepisnik, J. See Blinc, R.
Stepkowska-Paszyc, E. Physicochemical interpretation of the shearing process in montmorillonite clays, (5) 198*e*.
Sterman, S. See Marsden, J. G.
Sterman, S., and Marsden, J. G. Glass fiber reinforced thermoplastic polyarylene polyether resin article and process for making same, P (6) 212*d*.
Stern, E. See Caswell, H. L.
Stern, K. H. Ion diffusion into fused silica from molten salts, (5) 195*j*. Membrane potentials and ion selectivity of used silica in molten salts, (5) 197*a*.
Sternstein, S. S. See Cessna, L. C., Jr.
Sterzer, F. Cubic crystal light modulator, P (10) 344*e*.
Stetson, A. R. See Wimber, R. T.
Stevanovic, M., and Elston, J. Effect of fast neutron irradiation in sintered alumina and magnesia, (4) 132*e*.
Stevels, J. M. Effect of electromagnetic radiation on vitreous systems, (6) 208*j*. Structure and electrical properties of glasses, (9) 307*e*. See Beekenkamp, P.; de Jong, J. G. M.
Stevens, K. W. H., and Walsh, D. Ground state of the ferrous ion in alumina and calculation of spin-lattice relaxation, (6) 232*j*.
Stevens, R. H. See Anderson, N. G.
Stevenson, C. L. High screening efficiency achieved through probability sizing, (8) 284*e*.
Stevenson, D. A. See Burmeister, R. A., Jr.; Reynolds, R. A.
Stevenson, R. Fine structure in the absorption spectra of $KMnF_3$ and $RbMnF_3$, (4) 136*h*.
Steventon, B. R. See Edwards, A. J.
Steverding, B. Brittleness and impact resistance, (6) 230*i*.
Stewart, A. K., and Hepworth, M. T. Oxygen diffusivity in bcc iron stabilized by phosphorus, (2) 81*j*.
Stewart, D. B. See Wright, T. L.
Stewart, D. J. See Duncan, J. F.
Stewart, G. H. (editor). Science of Ceramics (Vol. 4) Proceedings of the Fourth International Conference Held Under the Auspices of the European Ceramic Association at Maastricht, Netherlands, April 1967, B (10) 366*b*.
Stewart, J. H., Jr. Interlocking building block, P (5) 176*g*.
Stewart, J. M. See Petruk, W.
Stewart, S. W. Tundish nozzle construction, P (9) 309*f*.
Stewarts & Lloyds, Ltd. Weld backing member and method of forming welded joins in metallic members or between metallic members, P (6) 208*c*.
Sticher, H. See Barrer, R. M.
Stickel, A., and Hagedorn, F. T. Apparatus for bending glass sheets with aligning means, P (11) 370*h*.
Stigger, E. K. See Brown, L. H.
Stiles, P. J. See Esaki, L.
Stillman, G. E., Wolfe, C. M., Melngailis, I., Parker, C. D., Tannenwald, P. E., and Dimmock, J. O. Far-infrared photoconductivity in high-purity epitaxial GaAs, (8) 292*f*.
Stine, C. K., and Dugge, R. H. Outlet structure for unloading bulk materials either by gravity or pneumatically, P (2) 74*h*.
Stirland, D. J. See Brown, A. S.; Lewis, B.
Stirling, J. F., and Hardy, L. E. Method for the simultaneous measurement of thermal expansion, setting temperature, and Young's modulus of a vitreous enamel in the form of a thin layer, (10) 336*g*.
Stirling, J. F., and Miselbach, R. G. Technique for improving the homogeneity of laboratory melts, (6) 211*d*.
Stitt, D. M. See Anthony, R. G.
Stober, W., Fink, A., and Bohn, E. Controlled growth of monodisperse silica spheres in the micron size range, (1) 26*c*.
Stoch, L. See Sikora, W.
Stochl, V. Apparatus for evolving gases from minerals and rocks; their measuring and sampling into the gas chromatograph, (2) 68*g*.
Stock, D. F. See Cobaugh, G. D.; Hart, H. G.
Stockard, R. R. See Wortman, J. J.
Stockbridge, C. D. G. See Olsen, K. M.
Stoebe, T. G., and Pratt, P. L. Ionic conductivity and diffusivity in lithium fluoride, (8) 293*i*.
Stoecker, H. J. See Naoumidis, A.
Stoeffler, D. See Arndt, J.
Stoeffler, D., and Arndt, J. Coesite and stishovite, high-pressure modifications of silicon dioxide, (9) 316*h*.
Stoessel, A. See Ruedorff, W.
Stoev, S. M., and Watson, D. Pelletizing on a flat surface using three-dimensional vibrations, (8) 284*f*.
Stohldrier, O. H. Method and means for sampling pulverulent material, P (8) 286*a*.
Stokes, R. J. Fracture of ceramics, B (1) 41*g*. Mechanical properties of polycrystalline sodium chloride, (2) 80*j*.
Stokowski, S. E., Johnson, S. A., and Scott, P. L. Vibronic transitions in ruby and MgO:V^{2+}, (1) 40*c*.
Stolba, G. See Bildstein, H.
Stolen, R. See Bagdade, W.
Stollar, W. P. See Moss, H. I.
Stollar, W. P., and Moss, H. I. Pressure sintering of gallium arsenide, (6) 236*j*.
Stoller, A. I., and Schlip, W. H., Jr. Isolation techniques for fabricating integrated circuits (II) dielectric refill techniques and decal air isolation, (8) 281*j*.
Stoloff, N. S. Effects of solutes on the fracture behavior of metals, B (1) 41*g*.
Stolz, H. See Knozinger, H.
Stone, G. D. See Gilles, P. W.
Stone, H. E. N. Electrical conductivity and sintering in iron oxides at high temperatures, (8) 291*b*.
Stone, J. N., and Eick, G. H. Process for grinding portland cement clinker, P (5) 170*h*.
Stone, L. R., Reim, T. E., Muskovac, N. G., and Cook, J. E. Nuclear gaging system for moisture content of irregular stream of bulk material, P (6) 228*b*.
Stone, M. L., and Danko, G. K. Halogen-cycle incandescent lamp with planar filament, P (7) 248*i*.
Stoneham, A. M. See Henderson, B.; Lannoo, M.
Stoneham, A. M., Hayes, W., Smith, P. H. S., and Stott, J. P. Hyperfine interactions of *F* centers in alkaline earth fluorides, (5) 195*i*.
Stonehouse, A. J. See Booker, J.
Stong, C. L. See Hammesfahr, J. E.
Stong, G. E. Transparent glass-ceramic articles and method for producing, P (9) 308*d*.
Stookey, S. D. Photochromic glass making, P (9) 308*a*.
Stoops, R. F. Liquid-phase-extrusion hot-pressing, (5) 177*e*.
Stora, J. P. See Francois, B.
Stormont, R. W. See Wald, F.
Storms, E. K., and Huber, E. J., Jr. Heat of formation of uranium carbide, (4) 138*h*.
Stott, J. P. See Hayes, W.; Stoneham, A. M.
Stout, N. D., Hoenig, C. L., and Nordine, P. C. Knudsen cell studies of the vaporization of samarium dicarbide, (6) 234*e*.
Stoute, R. L. See MacEwan, J. R.
Strabag Bau-A. G. Process and apparatus for the determination of particle size distribution, P (6) 228*b*.
Stradtmann, J. See Obst, K. H.
Strafford, K. N., and Gartside, H. Effect of stoichiometry on the lattice deformation of cobalt monoxide scales, (9) 320*b*.
Strain, F. See Wilson, W. L.
Strangway, P. K., and Ross, H. U. Study of the factors which influence the rate minimum phenomenon during magnetite reduction, (4) 157*h*.
Stranzl, P. Refractory construction materials in the brick and tile industry, (10) 340*e*.
Strasheim, A., and Brandt, M. P. Quantitative X-ray fluorescence method of analysis for geological samples using a correction technique for the matrix effects, (4) 121*a*.

Strategic Materials Corp. Heating apparatus and process, P (5) 189*c*.
Strater, K. Controlled oxidation of silane, (8) 289*e*.
Straughan, B. W. See Mullin, J. B.
Straumanis, M. E., Krumme, J. P., and Rubenstein, M. Thermal expansion coefficients and lattice parameters between 10° and 65°C in the system GaP-GaAs, (4) 160*e*.
Strauss, A. J. Metallurgical and electronic properties of $Pb_{1-x}Sn_xTe$, $Pb_{1-x}Sn_xSe$, and other IV-VI alloys, (2) 80*c*.
Strauss, A. J., Banus, M. S., and Finn, M. C. Pseudobinary InSb-InTe system, (1) 35*c*.
Strauss, H. S. See Thouret, W. E.
Strauss, K. Old Saxony stoneware, (1) 2*b*.
Strauss, W. See Angell, C. A.
Strayer, R. W. See Swanson, L. W.
Strehlow, W. H., and Smith, D. P. Determination of the crystallographic polarity of CdS by ion scattering, (7) 265*c*.
Streib, H., and Hechelhammer, W. Glass fibers sized with polycarbonate, P (2) 52*i*.
Streiff, R. Study of calcium oxidation—reaction mechanisms, (4) 157*b*.
Streltsina, M. V. See Mazurin, O. V.
Stresino, E. F. See Eschenbach, R. C.
Streus, R. G. J. Symmetry-entropy-volume relations in polymorphs, (1) 39*a*.
Stribling, M. L. Glazed clay cutouts, (10) 335*i*.
Strick, G. See Hahn, H.
Strickland, G. See Tuthill, E. J.
Strickler, D. W. See Caslavska, V.
Strief, M. J. See Kelly, W. T.
Strier, M. P. See Berger, C.
Strieter, F. J. Method for isolating individual devices in an integrated circuit monolithic bar, P (8) 282*j*.
Stringer, J. Rate-controlling processes in the high-temperature oxidation of tantalum, (4) 152*g*.
Strnad, P., and Pribik, R. Simple temperature indicator, (7) 260*c*.
Strnat, K. J., Hoffer, G. I., Olson, J. C., and Ostertag, W. Method of producing permanent magnets of rare earth metals containing Co or mixtures of Co, Fe, and Mn, P (5) 184*d*.
Strohmeier, G. See Pipitz, E.
Stromberg Carlson Corp. Cathode ray tube display device having a hemispherical display area, P (2) 64*g*.
Strong, F. C., III. Improving the potassium flame test, (8) 285*e*.
Strong, H. M. High pressure reaction vessel for the preparation of diamond, P (2) 67*j*.
Strongin, O., and Goldman, W. Phosphorescent porcelain enamels, (1) 4*i*.
Stroud, D. G. See Reynolds, R. A.
Stroup, R. F. See Bracken, R. C.
Struk, L. I. See Dubovik, T. V.
Strull, G. Semiconductor integrated circuits with improved isolation, P (11) 378*e*.
Struthers, J. D. See Buck, T. M.
Stuart, M. Electrical properties of evaporated cerium oxide films, (7) 254*f*.
Stuart, M. C. See Gross, P.
Stuart, P. R. See Gleed, W. L.
Stubican, V. S. See Schultz, A. H.; Tressler, R. E.
Stubican, V. S., Greskovich, C., and McKinstry, H. A. Kinetics of precipitation and measurements of strain in the system MgO-Al_2O_3-Cr_2O_3, (6) 234*d*.
Stucki, F. F. Ferrimagnetic pressure transducer, P (6) 221*a*.
Stuermer, W. Porcelain reliefs, (7) 244*c*.
Stuetz, D. E. Direct production of graphite fibers, P (9) 309*e*.
Stull, C. W. Organic decorating today and tomorrow, (2) 50*j*.
Stull, D. R. See Sinke, G. C.
Stumm, W. See O'Melia, C. R.
Stump, N. W. See Gray, N. B.
Sturgeon, G. D., and Eick, H. A. Samarium borides — tetraboride-hexaboride conversion, (2) 82*g*.
Sturgill, D. T. Method of forming a glass-ceramic article having an internal cavity, P (7) 249*e*.
Sturgis, D. H., and Nelson, J. A. Effects of gaseous adsorbates on the compaction of ultrafine active alumina powder, (7) 253*g*. Silicone resins simplify fused silica processing, (2) 57*f*.
Sturhahn, H. H. See Hennicke, H. W.
Sturm, J. See Barson, F.
Sturtevant Mill Co. Methods and apparatus for air classifying and screening of finely divided material, P (6) 225*d*.
Stutsman, P. W. Gas-filled discharge device having a grid with an element particularly spaced from the cathode, P (2) 64*i*.
Styblo, R. See Carniol, B.
Stynen, A. See Camozzo, G.
Stynes, J. A. Boratozirconium chloride, P (5) 190*g*.
Stynes, J. A., and Clearfield, A. Crystalline zirconium phosphates, P (4) 124*a*.
Subrahmanyam, A. V., and Murthy, H. P. S. Laboratory study of Indian and foreign nozzles for pouring steel, (11) 373*g*.
Suckow, A., and Degen, K. Hot bending strength of basic brick, (4) 104*b*.
Suda, Kyo. See Takami, Katsumi.
Sudakas, L. G. See Golynko-Vol'fson, S. I.
Sudakova, L. P. See Ust'yantsev, V. M.
Sudo, T. See Tomida, K.
Sudo, Toshio; Shimoda, Susumu; Nishigaki, Shigeru; and Aoki, Masaharu. Energy changes in dehydration processes of clay minerals, (7) 265*c*.
Suemoto, Toshio. See Shimizu, Keiichi.
Suemune, Yasutaka. Thermal conductivity of some ferroelectric crystals with hydrogen bonds, (8) 300*a*.
Suesse, P. Crystal structure of amarantite, (6) 231*g*.
Suga, Hiroshi. See Sorai, Michio.
Sugano, Satoru. See Shinada, Masaki.
Sugawara, Akira. Precise determination of thermal conductivity of pure fused quartz, (9) 306*h*.
Sugawara, Fuyuhiko; Iida, Shuichi; Syono, Yasuhiko; and Akimoto, Syun-iti. Magnetic properties and crystal distortions of $BiMnO_3$ and $BiCrO_3$, (8) 294*j*.
Sugawara, Fuyuhiko; Syono, Yasuhiko; and Akimoto, Syun-iti. High-pressure synthesis of a new perovskite, $PbSnO_3$, (7) 266*d*.
Sugibuchi, Kiyoshi; Tsuya, Hideki; and Fujino, Yoshio. Light extinction of lithium tantalate in light modulation, (8) 294*f*.
Sugihara, Ko. See Ono, Shusuke.
Sugimoto, Mitsuo. See Takeda, Takayoshi; Watanabe, Hiroshi.
Sugioka, Yasoichi. See Okada, Kazuo.
Sugita, Kiyoshi. See Ohba, Hiroshi.
Sugita, Tadaaki; Furukawa, Mitsuhiko; and Yasui, Heiji. Friction and wear behavior of ceramic-cemented carbide couples (I, II), (5) 177*j*.
Sugito, Yoshihiko. Results of service test on unfired brick used in cupola lining (I), (11) 374*a*. Results of tests on tar dipped brick for cupola lining, (10) 342*g*.
Sugiyama, Jukichi. Results of service test on cased brick and improved masonry in front wall of open-hearth furnace, (11) 373*i*.
Sugiyama, Kohzoh. See Takahashi, Takehiko.
Sugiyama, Sachio; Hasatani, Masanobu; and Kondo, Takayoshi. Two-stage thermal decomposition of solids (II) effects of inert materials, (5) 170*i*.
Sults, J. C. See Grant, P. M.
Suk, V. See Neumann, J.
Sukharevsky, B. Ya., Alapin, B. G., and Aksel'rod, E. I. Structural vacancies and solid solution decay in ferrospinels, (10) 361*c*.
Sullivan, C. P. See Leverant, G. R.
Sullivan, D. J. Methods and apparatus for air classifying and screening of finely divided material, P (6) 225*d*.
Sullivan, D. L. Thin-film cold cathode, P (8) 284*a*.
Sullivan, K. M. Direct drying of vitrified clay pipes, (7) 249*j*.
Sullivan, R. E. See Holderreed, F. L.
Sullivan, T. A., and King, B. W., Jr. Effects of moist furnace atmosphere on a white porcelain enamel, (8) 274*j*.
Sumita, Minoru. Photoconductive effect of ZnO-Cu crystals, (9) 327*e*.
Sumitomo Electric Industries, Ltd. Constant current semiconductor device, P (6) 221*e*.
Summers, J. G. See Foxell, C. A. P.
Summitt, R. See Luxon, J. T.
Sumner, D. H. See Kelley, J. E.
Sumner, G. G. Microcontact Schottky barrier semiconductor device, P (9) 313*g*.
Samson, H. T. See Crooks, D. D.; Kelsey, R. W.
Sumski, S. See Panish, M. B.
Sun Oil Co. Preparation of amorphous alumina, P (2) 74*a*.
Sunagawa, Ichiro. Mechanism of crystal growth and surface structures of crystal faces, (1) 32*d*. Surface microstructures of crystals grown from molten salts, (4) 158*c*.
Sunbeam Corp. Shuttle hearth furnaces, P (1) 23*b*.
Sunderland, P. W., and Chaklader, A. C. D. Creep during dehydroxylation of magnesium hydroxide, (10) 351*f*.
Sunderman, J. A. Geology and mineral resources of Washington County, Indiana, (9) 316*j*.
Sung, P., and Turnbaugh, J. E. Calculation of the temperature-dependent shear modulus of UO_2, (4) 127*b*.
Sunners, B. Control of photoconductive properties in cadmium selenide, (4) 129*j*.
Surkevicius, H. See Ridge, M. J.
Surplice, N. A. Unified model of the oxide cathode which gives prominence to the role of localized surface states on small crystals, (4) 111*h*.
Surty, R. J. See Dietsch, H. E.
Susman, S. Zone purification of potassium chloride, (4) 164*e*.
Susquehanna Corp. Methods of making sources of radioactive energy, P (10) 345*a*.
Susse, C. See Bocquillon, G.
Sussmann, E. See Ullrich, H.
Sutherland, D. N. Theoretical model of floc structure, (1) 39*h*.
Sutherland, G. E. See Bergstrom, J. W.
Sutherland, H. B., and Neale, D. F. Determination of shape factor of sands, (5) 190*b*.
Sutherland, J. P. See Coleman, R. D.
Suttner, L. J. Stratigraphic and petrographic analysis of Upper Jurassic-Lower Cretaceous Morrison and Kootenai formations, southwest Montana, (11) 387*f*.
Suzuishi, Masatsugu, and Ito, Hiroo. Growth of single crystals of yttrium iron garnet, (10) 354*j*.
Suzukawa, Yuichi, and Kobayashi, Waichi. Relation of grinding temperature to cement quality, (4) 92*d*.
Suzuki, Hiroshige. Some problems of refractoriness-under-load test, (10) 342*g*. Transport processes in refractories—spalling of basic refractories, (2) 58*g*. See Tagai, Hideo.
Suzuki, Hiroshige, and Hosaka, Takao. Nitriding reactions of the silicon-silica system, (4) 146*d*.
Suzuki, Hiroyoshi, and Kadokura, Toshio. Calcination of limestone in a fluidized bed, (4) 123*g*.
Suzuki, Hisashi, and Hayashi, Kozi. Effect of annealing on the properties of sintered WC-TiC-10%Co alloys, (4) 103*h*.
Suzuki, Hisashi; Yamamoto, Takaharu; and Chujo, Nobuyoshi. Properties of WC-10% (Ni-Fe) alloys, (4) 151*j*.
Suzuki, Kanae. See Mori, Kazumi.
Suzuki, Kazuo, and Hiraiwa, Osamu. Runner brick (V) protection of runner brick from spalling and erosion, (2) 57*e*.
Suzuki, Kazutaka. See Yamaguchi, Goro.
Suzuki, Kazutaka; Kido, Tsuyoshi; Fujitani, Masataka; Fujiwara, Akinobu; and Nagai, Shoichiro. Studies on the strength development by autoclaved treatment of slaked lime, siliceous materials, and blast-furnace slag mixtures, (4) 92*i*.
Suzuki, Makoto. See Arai, Yuzo.
Suzuki, Osamu; Takahashi, Masao; Fukunaga, Tomio; and Kuboyama, Jun. Novel cobalt oxide and an electrode having the cobalt oxide coating, P (1) 18*h*.
Suzuki, Takashi, and Watanabe, Takahide. Constant current semiconductor device, P (6) 221*e*.
Svec, J. J. Arvida—$100 million spent to improve alumina production facilities, (4) 123*d*. Brick plant exports to 40 countries, (4) 101*g*. Can European manufacturers show the U.S. a new market? (6) 213*j*. Conveyor system automates tile production, (2) 59*j*. Denver Brick installs a one-man grinding plant, (8) 278*f*. Kinader automates small plant, (4) 104*g*. Modern brick plant built in old Swiss village, (4) 102*a*. Nassau Brick modernizes soft mud operation, (4) 102*a*. Rotary table press featured at Danish soft mud plant, (8) 278*f*.
Svedberg, P. See Edqvist, O.
Svedberg, P., and Spicar, E. Semiconductor device with increased reverse and forward blocking voltages, P (2) 66*e*.
Svensson, O. See Raunie, G.
Svetina, S. See Blinc, R.
Svikis, V. D. Dead-burned magnesia from an Ontario magnesite concentrate, (8) 278*j*.
Svirskii, L. D., and Pirogov, Yu. A. Formation processes of coatings deposited by gas-flame dusting, B (5) 204*h*. Peculiarities of the heat-resistant coatings deposited by the gas-flame process, B (5) 204*h*.
Svirskii, L. D., and Sobol, N. P. Formation of heat-resistant enamel coatings, B (5) 204*h*.
Svoboda, V. Program-controlled machine tools for production of ceramic whiteware, (2) 60*a*.
Swaan, E. Measurements at high temperatures on reacting mixtures of barium carbonate and titanium(IV) oxide (anatase), (6) 235*a*.
Swalin, R. A. See Copeland, W. D.
Swallow, D. See Sing, K. S. W.
Swallow, D. M. Means for improving performance of separator screens, P (5) 186*b*.
Swallow, H. T. S. Radiant ceramic tubes, (7) 251*d*.
Swamy, A., and Thiemann, R. Method for the surface treatment of semiconductor devices, P (4) 115*i*.
Swank, T. F., and Lawless, K. R. Expansion on cooling of thick Cu_2O films grown on copper substrates, B (1) 40*i*.
Swann, J. D. Shade variations in ceramic glazes resulting from processing variables, (10) 343*e*.
Swann, R. C. G., Mehta, R. R., and Cauge, T. P. Preparation and properties of thin film silicon-nitrogen compounds produced by a radio frequency glow discharge reaction, (4) 150*f*.
Swanson, L. W., and Strayer, R. W. Field-electron-microscopy studies of cesium layers on various refractory metals—work function change, (4) 136*g*.
Swanson, T. B. Electron magnetic resonance spectra of $MnCl_2$-LiCl-KCl eutectic mixtures, (10) 352*i*.
Swaroop, B., and Wagner, J. B., Jr. Anomalous diffusion of nickel in single crystals of lead selenide at 700°C, (4) 126*f*. Oxidation of copper and copper-gold alloys in CO_2 at 1000°C (I) linear kinetics, (4) 148*b*.
Swartz, G. A. Grooved bulk semiconductor oscillator, P (10) 345*a*.
Swartz, J. C. Experience with combination drawing compounds and rust preventives—mill applied, (8) 275*a*. Protective linings for pickle tanks, (8) 275*d*.
Swartz, W. See Hoffmann, B. J.
Sweatman, T. R., and Long, J. V. P. Quantitative electron-probe microanalysis of rock-forming minerals, (11) 380*f*.
Sweet, R. C. See Bronnes, R. L.
Swenson, E. G. Admixtures in portland cement concrete, (5) 170*c*.
Swenson, E. G., and Sereda, P. J. Mechanism of the carbonatation shrinkage of lime and

hydrated cement, (9) 303*j*. Some aging characteristics of lime, (8) 287*a*.

Sweo, B. J. Basic approach to progress in porcelain enameling, (1) 4*a*.

Swiggard, E. M. Liquid encapsulation zone refining (LEZOR), (4) 110*c*. See Shenker, H.

Swihart, D. E. Thermoelectric body including pyrolyzed reaction product of pyromellitonitrile and alkanol and with comminuted metal, P (1) 19*f*.

Swillinger, F. L. Apparatus for minimizing open bottom blisters on float glass, P (6) 212*e*.

Swindells, J. F. (editor). Precise measurement and calibration — temperature, (7) 260*j*.

Swisher, J. H. Internal oxidation of iron-manganese alloys, (4) 140*h*. Thermodynamics of carbide formation and graphite solubility in the CaO-SiO_2-Al_2O_3 system, (4) 161*h*.

Swisher, J. H., Fuchs, E. O., and Schlabach, T. D. Mechanical and electrical properties of Cu-Cu_2O eutectic alloys, (9) 324*j*.

Swiss Aluminium, Ltd. Methods of and means for producing anhydrous alumina, P (2) 74*c*. Process for purifying solutions containing aluminates, P (10) 349*e*.

Sybron Corp. Composite spheroidal phosphorescent organic polymer article and process, P (11) 376*j*. Semicrystallized ground coats and enameled articles manufactured therefrom, P (11) 369*c*.

Sychra, V. See Matousek, J.

Sylvania Electric Products, Inc. Apertured fluorescent lamp with lens along the aperture, P (10) 344*a*. Arc discharge tube having an electrode which contains a light-emitting metal, P (2) 52*j*. Arc tubes and process for their fabrication, P (5) 182*f*. Decorative incandescent lamp, P (11) 371*e*. Electric discharge lamp with the starting resistor impedance twice that of the lamp impedance, P (8) 282*e*. Electric lamps and method of detecting leaks in such lamps, P (2) 52*h*. Europium activated barium and strontium haloaluminate phosphors, P (9) 312*g*. Europium activated strontium fluoroborate phosphor, P (6) 221*i*. Europium activated strontium haloborate phosphor, P (6) 221*j*. Ferrite core having different regions of varying permeability, P (4) 113*c*. Film thickness monitoring apparatus, P (1) 22*b*. Fluorescent manganese activated magnesium digallate phosphor composition, P (2) 64*g*. Fluorescent manganese activated magnesium gallate phosphor and lamp, P (2) 64*h*. Four-layer semiconductor switching devices in integrated circuitry, P (9) 312*a*. Fused projector lamp, P (4) 113*g*. Harness construction for metal arc type lamp, P (5) 183*c*. High pressure electric discharge device containing mercury, halogen, scandium, and alkali metal, P (2) 65*a*. Incandescent lamp, P (4) 99*i*. Infrared incandescent [quartz] lamp, P (8) 282*j*. Method of coating [insulating oxide] heater coils, P (9) 304*h*. Method [etching] of forming leads on semiconductor devices, P (5) 183*c*. Method of fabricating a color cathode ray tube screen, P (7) 257*a*. Method of fabricating an incandescent lamp and its construction, P (4) 99*i*. Method for the fabrication of image display screens, P (7) 257*d*. Method for preparing vanadate phosphors, P (5) 184*a*. Method of producing an array of semiconductor elements, P (10) 345*j*. Method of producing semiconductor devices, P (5) 184*d*. Method of producing semiconductor devices having connecting leads attached thereto, P (5) 184*e*. Method of separating frit-sealed glass bodies, P (4) 100*j*. Method for separating phosphors, P (9) 313*e*. Photoflash lamp, P (7) 249*b*. Process for removing alkali contamination from electric lamps, P (5) 176*d*. Process for sealing connectors in a planar structure, P (8) 278*b*. Semiconductor device employing punch-through, P (11) 378*c*.

Symons, M. C. R. See Brivati, J. A.

Synfibrit, G.m.b.H. & Co. Method and means for producing foamed silicate articles, P (6) 213*d*.

Synge-Hutchinson, P. Masterpiece of an unknown craftsman, (4) 90*j*.

Syono, Yasuhiko. See Akimoto, Shunichi; Sugawara, Fuyuhiko.

Syrkin, Ya. M. See Satarin, V. I.

Sysoev, L. A., Konvisar, L. V., and Raiskin, E. K. Process for growing single crystals of sulfides, selenides, and tellurides of metals of groups II and III of periodic system, P (4) 115*h*.

Szabo, A. See Barbulescu, E.; Catana, V.; Corneanu, A.; Petri, L.; Veiser, I.

Szabo, A., Barbulescu, E., and Seidel-Stoicescu, D. Improving refractory clay quality by microplex pneumatic classification, (10) 348*i*.

Szabo, E. See Poko, Z.

Szabo, E., and Rausch, H. Activation analysis of trace contaminants in GaAs semiconductor materials, (5) 186*h*.

Szai, A. P. See Gasparac, R. J.

Szalek, G. See Lichtner, E.

Szasz, P. R. See Zanger, E. A.

Sze, M. C., and Gessner, A. W. Process for producing a mixed oxide oxidation catalyst having improved selectivity, P (1) 24*b*.

Szedon, J. R. See Chu, T. L.

Szekely, J., and Carr, R. G. Nonisothermal flow of gases through packed beds, (4) 146*f*.

Szekely, J., and Fisher, R. J. Transient heating or cooling of spheres by thermal radiation at the bounding surface, (2) 84*b*.

Szekely, J., and Lee, R. G. Effect of slag thickness on heat loss from ladles holding molten steel, (1) 12*b*.

Szendy, K. See Halasz, D.

Szepesi, Z. Image intensifier comprising perforated glass substrate and method of making, P (2) 65*b*.

Szerdahelyi, D. See Zenobi, G. V.

Szklarz, E. G. See Giorgi, A. L.; Krupka, M. C.

Szulakowski, W. Processes occurring during the fine grinding of silica, (4) 151*c*.

Szware, R. See Fryxell, R. E.; Hein, R. A.

Szymborski, W. See Satczec, Z.

Tabak, M. D., and Warter, P. J., Jr. Sublinear photocurrents and surface recombination in cadmium sulfide crystals, (2) 83*c*.

Tabata, Hideyo. See Nakano, Kikuo.

Tabata, Katsuhiro. See Hayashi, Takeshi.

Tabor, D., and Winterton, R. H. S. Surface forces — direct measurement of normal and retarded van der Waals forces, (4) 157*j*.

Tabor, J. B., and Li, Che-Yu. Effect of an aqueous environment on the surface hardening of silver chloride, (1) 27*d*.

Tada, Takaharu. See Otsubo, Katsuhiko.

Tada, Takaharu; Kawamura, Junichi; and Hayasoko, K. Results of service test on ramming material for electric furnace cover, (7) 251*i*.

Taebel, W. A. See Allen, W. C.

Taft, E. A. See Brown, D. M.

Taft, E. A., Jr., and Gray, P. V. Processes of epitaxial deposition or diffusion employing a silicon carbide masking layer, P (9) 313*e*.

Taft, E. M. Flame ionization detector, P (1) 22*b*.

Taft, L. G. See Marchese, M. A.

Tagai, Hideo; Iwai, Shinichi; and Iseki, Takayoshi. Diffusion of iron oxide into single crystals of magnesia in reducing atmosphere, (1) 27*j*.

Tagai, Hideo; Suzuki, Hiroshige; and Iseki, Takayoshi. Application of X-ray microanalyzer to study of refractories, (7) 250*e*.

Tagai, Hideo; Suzuki, Hiroshige; and Somiya, Shigeyuki. Testing method for refractoriness under load of magnesia clinker (tentative), (11) 374*c*.

Tagai, Hideo; Zisner, T.; and Yasuda, Eiichi. Agglomeration and sintering of high purity magnesia, (11) 372*h*. Effect of minor additives on high temperature creep of magnesia, (11) 373*c*.

Tagawa, Hiroaki, and Ishii, Kikuo. Formation of boron nitride by the reaction of boron trichloride with ammonia and its crystallization by heat treatment, (5) 177*i*.

Tait, H. "Wolff" glasses in an English private collection, (4) 91*b*.

Tait, J. S. See Ketterson, J. B.

Taiyo Yuden Co., Ltd. Ceramic dielectric for temperature compensating electric condensers, P (1) 17*j*.

Tajima, Kozo. Results of service test on tar-soaked brick used in cupola lining, (11) 373*j*.

Takabayashi, Toshiaki. Method of producing cement mortar or concrete, P (6) 207*a*.

Takada, Toshio. See Yasuoka, Hiroshi.

Takagi, Hiroyoshi, and Hayashi, Hiroshi. Reactions between montmorillonite and a few aliphatic amines, (9) 328*c*.

Takagi, Katushiro. See Kojima, Kojiro.

Takagi, Kiyoshi, and Wada, Masamichi. Glass-ceramic product and method for making same, P (10) 339*a*.

Takagi, Takeshi. See Okutsu, Shinkichi.

Takahashi, Akira. See Nobuoka, Soichiro.

Takahashi, Katsuaki. See Hirai, Taketsugu.

Takahashi, Katsuaki; Kambara, Ginjiro; and Okahara, Masamichi. Spectrophotometric studies on high iron content silicate glasses, (1) 8*j*.

Takahashi, Katsuaki; Yoshio, Tetsuo; Miura, Yoshinari; and Hirai, Taketsugu. Measurement of high temperature thermodynamic properties of several binary alkali silicate glasses, (1) 7*d*.

Takahashi, Masao. See Akashi, Tsuneo; Suzuki, Osamu.

Takahashi, Tadaki. See Shimada, Nobuo.

Takahashi, Takehiko; Sugiyama, Kohzoh; and Tomita, Kensuke. Chemical vapor deposition of titanium carbide coatings on iron, (4) 93*c*.

Takai, Kiyoshi. Changes in method of lining LD converter ladle and improvement on intermediate repair method. (7) 250*e*.

Takaishi, T., and Sensui, Y. Exchange reaction between chlorine gas and potassium chloride crystal, (4) 136*a*.

Takami, Katsumi; Yamada, Yahiko; Suda, Kyo; and Koga, Masashi. Infrared ray detector utilizing ferroelectric single crystal, P (10) 345*b*.

Takamiya, Yoichi; Taniguchi, Teiichi; and Ohda, T. Sintering properties of magnesia-dolomite clinker, (7) 251*g*.

Takamori, Takeshi, and Akanuma, Masanobu. Dilatometry of tubular pyrolytic graphite, (1) 11*j*. Possible braze compositions for pyrolytic graphite, (8) 279*c*.

Takamori, Takeshi; Seo, Hirokichi; and Tashiro, Minoru. Polarization effects in semiconducting oxide glasses containing Na_2O, (11) 370*b*.

Takamura, Tohru. See Kobayashi, Yoshichika.

Takano, Shuji. See Hibino, Taizo.

Takano, Sumio. See Nakajima, Nagahisa; Yokomizo, Keiji.

Takase, Seikichi. Silicon nitride as refractory materials, (7) 251*g*.

Takashima, Yoshimasa, and Ohashi, Shigeru. Moessbauer spectra of various natural minerals, (4) 145*e*.

Takasu, Shinichiro. See Wakatsuki, Masao.

Takasue, Takashi. See Shimizu, Keiichi.

Takayanagi, Shigetoshi. See Yoshioka, Satoshi.

Takeda, Seiji. See Hirose, Yasuo.

Takeda, Shigeru. See Chisaka, Haruo.

Takeda, Tadao. See Uchida, Enji.

Takeda, Takayoshi; Yamaguchi, Yasuo; Tomoyoshi, Shoichi; Fukase, Masahiro; Sugimoto, Mitsuo; and Watanabe, Hiroshi. Magnetic structure of $Ca_2Fe_2O_5$, (2) 80*e*.

Takeda, Takeshi. Electron spin resonance of Gd^{3+} in orthorhombic and rhombohedral phases of $BaTiO_3$, (2) 76*d*.

Takeda, Takeshi, and Watanabe, Akinori. Electron spin resonance of Eu^{3+} in cubic and tetragonal phases of $BaTiO_3$, (2) 76*d*. Observation of the ^{47}Ti and ^{49}Ti *hf* structure in the *F*-center ESR line in $BaTiO_3$, (1) 33*f*.

Takeda, Tsuneo. See Murakami, Kazo.

Takei, Humihiko. See Koide, Shigenao.

Takei, Humihiko, and Koide, Shigenao. Epitaxial growth of VO single crystals and their electrical properties, (2) 76*i*.

Takei, Takeshi. See Kuwamoto, Hidehiko; Ueoka, Hisayoshi.

Takekawa, Tatsuya. See Shimizu, Keiichi.

Takemoto, Kunihiro, and Saiki, Yoshio. Forms of calcium carbonate and sulfate in aerated portland cement, (4) 91*f*.

Takeno, S. See Sievers, A. J.

Taki, Hiromitsu. See Hayakawa, Shigeru.

Takigawa, Hideaki. See Itakura, Kiyoshi.

Takiguchi, Toshimichi, and Asada, Eiichi. Mn$K\beta_5$ spectra and Mn*K* absorption edges of manganese oxides in various valence states, (9) 325*h*.

Taksis, G. A. See Bessonov, A. F.

Talaber, J. Long-time performance of alumina cements, (8) 274*b*.

Talalaeva, E. V. See Belov, K. P.

Talian, N. M. See Bransky, I.

Tallman, R. L., and Gulbransen, E. A. Crystal morphology and mechanisms of growth of alpha-Fe_2O_3 whiskers on iron, (4) 130*e*. Dislocation and grain boundary diffusion in the growth of α-Fe_2O_3 whiskers and twinned platelets peculiar to gaseous oxidation, (9) 320*f*. Selected area electron diffraction study of twinned α-Fe_2O_3 bladelike platelet growths on iron, (10) 360*d*.

Tamaki, Nobuo. See Shimizu, Keiichi.

Tamaru, Kenzi. See Fukuda, Kenzo; Noto, Yuko.

Tamas, F. (editor). Proceedings of the Ninth Conference on the Silicate Industry, Budapest, 1967, B (7) 272*h*. Rate equation of cement hydration, (11) 368*b*.

Tamosauskas, A. E. See Marzocchi, A.

Tamura, Michio. Method of making color screen for cathode ray tube. P (9) 312*j*.

Tamura, Michio, and Nakamura, Mitsuyoshi. Cathode ray tube color screen and method of producing same. P (7) 255*i*.

Tanabe, I. See Oi, N.

Tanaka, Hirobumi. See Murakami, Keiichi.

Tanaka, Hirokichi. See Tanigawa, Hideo.

Tanaka, Isamu. See Inoue, Toshio.

Tanaka, Kenzo. See Mannami, Michi-hiko.

Tanaka, M. See Mihama, K.

Tanaka, Masami. See Hattori, Makoto; Tsubaki, Takayuki.

Tanaka, Masaru. See Yamashita, Akio.

Tanaka, Masayoshi. See Ohba, Hiroshi.

Tanaka, Mitsuo. See Saito, Shinroku.

Tanaka, Shigezo, and Chiba, Kozo. Semiconductor device [Ge,Si] utilizing an $AuAl_2$ layer as a diffusion barrier that prevents "purple plague," P (1) 19*h*.

Tanaka, Tadayoshi. See Ando, Yoshio.

Tanaka, Takeshi. See Asamura, Hitoshi.

Tananaev, I. V., Dzhurinskii, B. F., and Belyakov, I. M. Rare earth borates in the systems Na_2O-B_2O_3-Ln_2O_3, (6) 236*i*.

Tandon, D. See Anderson, S.

Tanei, Tadayoshi. Electron spin resonance study on ultraviolet light irradiated benzene adsorbed on silica gel and alumina, (8) 291*i*.

Tanemura, Fumikazu; Adachi, Shozo; and Ogawa, Kazuya. Spalling test for casting pit refractories. (2) 57*j*.

Tani, A. See Fujii, I.

Tani, Tetsuro; Hayashi, Takeshi; and Okuda, Shigeru. Deterioration of magnesia brick used in converter outlet, (10) 340*g*.

Tanigawa, Hideo, and Tanaka, Hirokichi. Studies on crystallization of glasses in the BaO-SiO_2 system, (2) 51*h*.

Taniguchi, Ichirou. See Yamazaki, Syunpei.

Taniguchi, Masao. See Kato, Masanori.

Taniguchi, Teiichi. See Takamiya, Yoichi.

Taniyama, Mitsuya. See Ohba, Hiroshi.

Tannenwald, P. E. See Stillman, G. E.

Tanner, W. F. Particle size scale, (11) 380*b*.

Tannhauser, D. S. See Hed. A. Z.

Tansley, D. R. Stress inspection apparatus with sine wave modulation of the photomultiplier tube output, P (7) 261*b*.

Tansuriwongs, P. See Lundstrom, T.

Tanton, G. A., Shatas, R. A., Williams, J. E., and Mukerji, A. H and F bands in alkaline-earth fluorides, (10) 354*h*.
Tanzilli, R. A., and Heckel, R. W. Numerical solutions to the finite, diffusion-controlled, two-phase, moving-interface problem (with planar, cylindrical, and spherical interfaces), (6) 235*a*.
Tao, T. F., Tully, J. W., and Schott, F. W. Dynamic mode surface waves on magnetized YIG and ferrite rods, (9) 310*h*.
Tappin, G. See Clarke, F. J. P.; Davidge, R. W.
Taramasso, M., and Veniale, F. Gas-chromatographic investigations on dimethyldioctadecyl ammonium derivatives of different clay minerals, (9) 321*j*.
Tarasevich, Yu. I. Determination of the infrared spectra of clay minerals and adsorbed substances, (7) 259*g*. See Brekhunets, A. G.; Ovcharenko, F. D.; Polyakov, V. E.
Tarasevich, Yu. I., and Ovcharenko, F. D. Nature of the interaction of montmorillonite surface with water (III) applicability of BET equation on the sorption isotherm of water vapor by montmorilionite, (7) 267*e*.
Tarasevich, Yu. I., Sharkina, E. V., Polyakov, V. E., and Ovcharenko, F. D. X-ray studies of cation-exchanged vermiculite, (7) 270*g*.
Turcza, W. H. See Asher, J. W.
Tarczon, T. See Schleifer, P.
Tardiff, M. A. Two approaches to automating porcelain pretreatments, (7) 246*i*.
Tarneja, K. S. See Amsterdam, M. F.
Tarneja, K. S., Ernick, F. G., and Rossi, V. A. Manufacture of semiconductor solar cells, P (11) 377*d*.
Tarte, P. Structural research into the constitution of cements (II) isomorphic substitution phenomena in tricalcium aluminates, (9) 304*c*.
Tarui, Yasuo; Komiya, Yoshio; and Teshima, Hiroo. Built-in voltage and charge distributions in an oxide of MOS structure, (8) 289*a*.
Tasaki, Sueo. See Miyatake, Kazumi.
Tasca, A., and Bucci, F. Mario Mascarin, (6) 206*a*.
Tashima, Norio. See Ueoka, Hisayoshi.
Tashiro, Minoru. See Takamori, Takeshi.
Tata Iron & Steel Co. Composition and process for making floor tiles, P (4) 109*b*.
Tate, J. R. See Clunie, J. S.
Tatem, W. A. Method of making a capacitor with an oxygen-pervasive and an oxygen-impervious electrode, P (6) 222*f*.
Tatnall, R. F. Engineered brick masonry, (4) 101*h*. New plant grades SiC grain at Electro, (4) 104*h*. Roller hearth kiln fires alumina, (4) 105*h*. Tunnel kiln holds ±10°F throughout load, (8) 286*d*. Westinghouse mechanizes insulator production—sales value per employee up 28%, (6) 219*j*.
Tatom, E. Structure and method for production of narrow doped region semiconductor devices, P (10) 346*d*.
Tatsak, J. E. Glass forming machine having molds with movable bottom sections, P (4) 99*a*.
Tatsumoto, Eiji. See Okamoto, Tetsuhiko.
Tattersall, H. G. See Clarke, F. J. P.
Taub, J. M. See Riley, R. E.
Tauber, A. See Sehlke, K. H. L.
Tauber, E., and Hill, R. K. Investigation of the drying process of clays and ceramic bodies with a barelattograph, (10) 346*f*.
Tauber, K. A. G., and Schmidt, E. R. Electrical potential measurements in clays, (9) 321*d*.
Tauber, R. N. See Levine, E.
Tausheck, R. W. See Pector, H.
Tauveron, P. See Morel, R. C. M.
Tawara, Yoshio. See Mizuno, Hideo; Senno, Harufumi; Yanase, Akira.
Taxil, A. Process for filling an electric discharge lamp having an ionizable atmosphere, P (5) 176*d*.
Taylor, A. See Barsis, E.
Taylor, A., and Doyle, N. J. Solid solubility of oxygen in niobium and niobium-rich niobium-hafnium, niobium-molybdenum, and niobium-tungsten alloys, (4) 155*e*.
Taylor, A. H. See Ross, R. A.
Taylor, A. M., and Terrell, B. C. Synthetic tourmalines containing elements of the first transition series, (5) 200*i*.
Taylor, B. N. Device applications of superconductive tunneling, (1) 16*h*.
Taylor, D., and Henderson, C. M. B. Thermal expansion of the leucite group of minerals, (10) 362*d*.
Taylor, D. W. See Carnes, R. A.
Taylor, D. W., and Hart, A. B. Creative Ceramics for the Beginner Step by Step, B (9) 333*i*.
Taylor, E. C. See Ryder, R. J.
Taylor, E. D., and Hecht, H. G. Thermoluminescent study of X-irradiated polycrystalline CaO, SrO, and BaO, (9) 332*a*.
Taylor, H. F. W. See Ahmed, S. J.; Speakman, K.
Taylor, H. F. W., and Moore, A. Crystal structure of ettringite, (9) 319*e*.
Taylor, H. P., Jr. See O'Neil, J. R.
Taylor, J. Thermodynamic relationships in partially liquid oxide systems, (5) 201*e*.
Taylor, J. A. G., Hockey, J. A., and Pethica, B. A. Silica-water interface, (1) 36*b*.
Taylor, J. D. See Pearton, D. C. G.
Taylor, J. J., and Newport, J. B. Method for measuring toughness of ceramic materials, (6) 226*e*.
Taylor, N. See Hayward, D. O.
Taylor, P. C. See Griscom, D. L.
Taylor, R. C. Epitaxial deposition of GaAs in an argon atmosphere, (4) 135*c*.
Taylor, R. G. F. See Robertson, J. M.
Taylor, S. G., Chain Co., Inc. Heat transfer elements for rotary kilns, P (8) 286*e*.
Taylor, S. R., Ewart, A., and Capp, A. C. Leucogranites and rhyolites—trace element evidence for fractional crystallization and partial melting, (8) 294*e*.
Taylor, W. C. See Hansen, K. W.
Taylor, W. C., and Nale, R. F. Electric furnace having refractory brick of specific composition in the critical wear areas, P (1) 13*j*.
Taylor-Smith, E. J. Building unit casting and facing method and apparatus, P (5) 170*e*.
Tazairt, A. See Wollast, R.
TDK Electronics Co., Ltd. Ceramic dielectrics, P (4) 112*g*, P (5) 182*j*, P (6) 220*j*, P (7) 255*j*.
Tebenikhin, E. F., and Gusev, B. T. Crystallization modifications of calcium carbonate, (7) 264*i*.
Technicon Corp. Chemistry furnace, P (2) 72*d*.
Tedeschi, W. R. See Freedman, B. J.
Tedmon, C. S., Jr. Effect of oxide volatilization on the oxidation kinetics of Cr and Fe-Cr alloys, (1) 28*b*. High-temperature oxidation of ductile Cr-Re alloys, (1) 30*f*.
Teeg, R. O. High strength glass and method for making the same, P (6) 212*g*.
Teeg, R. O., and Hallman, R. W. Processes of preparing vanadium suboxide coatings, P (10) 345*h*.
Teeg Research, Inc. High strength glass and method for making the same, P (6) 212*g*. Processes of preparing vanadium suboxide coatings, P (10) 345*h*.
Teeling, G. A. M. See Jacobs, J. M. H.
Teeter, F. C. Process for grinding glass with diamond grinding surface and alkali metal soap emulsifiable composition, P (11) 372*a*.
Teeter, F. C., Sheldahl, D. B., and Highberg, C. W. Process for grinding glass with diamond grinding surface and an emulsifiable composition, P (10) 339*j*.
Te Grootenhuis, W. D. See Dapolito, J. J.
Teichner, S. J. See Juillet, F.
Teichner, S. J., Thomas, C. L., and Hoang, V. C. Preparation of amorphous alumina, P (2) 74*a*.
Tektronix, Inc. Mesa type combined direct viewing storage target and fluorescent screen for cathode ray tube, P (1) 18*a*.
Teledyne, Inc. Isolated resistor for integrated circuit, P (6) 221*h*. Junction capacitor, P (10) 345*d*. Method of forming a flip-chip integrated circuit, P (8) 282*i*. Semiconductive field-controlled diode device, P (10) 346*a*. Thermoelectric device comprising an oxide base thermoelectric element, P (11) 379*c*.
Telefonaktiebolaget L M Ericsson. Procedure for producing a ferrite, especially adequate for use in pulse relay cores, P (5) 184*j*. Semiconductor bidirectional component, P (7) 258*b*.
Telefunken Akt.-Ges. [*Pn*] junction transistor, P (7) 257*g*. Semiconductor device, P (6) 223*f*.
Telefunken Patentverwertungs-G.m.b.H. Aligning [mask] method and apparatus, P (11) 376*e*. Barium titanate compositions containing cerium and bismuth, P (8) 282*c*. Contacting arrangement for solid-state components, P (10) 344*c*. Controllable electrical resistance, P (4) 112*b*. Controllable tunnel diode, P (11) 376*b*. Electrical circuit manufacture, P (11) 376*c*. Manufacture of semiconductor arrangements using a masking step, P (8) 282*d*. Method [epitaxial growth] of fabricating electrical devices, P (11) 377*i*. Process of fabricating a metal base transistor, P (5) 185*c*. Production of circuit device, P (6) 223*j*. Semiconductor, P (6) 223*d*. Semiconductor arrangement with capacitative shielding means between conductive strips and semiconductor body, P (2) 66*d*. Semiconductor device with an emitter, base, and collector region, P (11) 378*d*. Semiconductor fabrication, P (5) 185*h*. Separation [scoring] of individual wafers of a semiconductor disk, P (11) 378*h*.
Telyatnikov, G. V., Khodorov, E. I., Evtjutov, A. A., Škopa, D. D., Chervinsky, A. A., Shilov, A. V., and Kazantseva, N. M. Heat exchanger for powdered materials suspended in gases, P (8) 284*f*.
Tempel, G. W. Electromechanical transducer material [colloidal graphite], P (9) 312*f*.
Temperley, H. N. V., and Blythe, G. K. E. Mills which grind to micron size without moving parts, (4) 117*h*.
Templeton Coal Co. Method for making electric resistance heaters, P (5) 183*f*.
Tench, A. J. See Nelson, R. L.
Tench, A. J., and Nelson, R. L. Adsorbed nitro-compounds and electron donor properties of magnesium oxide, (5) 191*j*. Paramagnetic defects associated with hydrogen adsorbed on the surface of magnesium and calcium oxides, (5) 198*e*.
Tennenhouse, G. J. Method of making a solid ionic conductor, P (8) 283*c*.
Tennery, V. J., and Hang, K. W. Role of certain impurities in heats of transition of $PbZrO_3$, (1) 36*g*.
Tennery, V. J., Hang, K. W., and Novak, R. E. Ferroelectric and structural properties of the $Pb(Sc_{1/2}Nb_{1/2})_{1-x}$-$Ti_xO_3$ system, (1) 16*g*.
Tennessee Corp. Process for producing fluosilicates, P (11) 382*i*.
Tenny, R. F. See Smith, J. P.
Terada, Kiyoshi. See Shimizu, Satoshi; Wakamatsu, Mitsuru.
Terada, Kiyoshi; Shimizu, Satoshi; and Fujiwara, Toshiaki. Effect of reducing atmospheres on the combination of constituent oxides in portland cement burning, (4) 91*c*.
Terai, Shoji. Service tests on some kinds of zircon-containing nozzles installed on 50-ton ladle, (11) 374*d*.
Terajima, Makoto. Process for producing a ferromagnetic thin film, P (5) 185*d*.
Terakawa, Haruyuki. Apparatus for fluidized drying and separation, P (10) 348*b*.
Terao, Noburo. Structure of tantalum oxides, (10) 361*g*.
Terao, Takehiko. See Kunitomo, Masakazu; Tsutsumi, Yoshitaka.
Terasaki, O. See Watanabe, D.
Terasaki, Takeshi. See Onuma, Takeshi.
Terasawa, Michitaka. Anomalous X-ray emission from electrical insulators, (10) 350*e*.
Terekhova, N. B. See Troitskii, O. A.
Termain, J. D. See Fleisch, H.
Terminassian-saraga, L. Free energy of adhesion and equilibrium of contact reactions at solid-fluid interfaces (I) perfect solid and fluid, (1) 30*d*.
Terrell, B. C. See Taylor, A. M.
Terrell, M. P. See Johnson, L. R.
Tervo, R. O. Granular electrically insulating material of magnesia and fused zircon, P (10) 342*e*.
Ter Vrugt, J. W. See Blasse, G.; Bril, A.; Wanmaker, W. L.
Terwilliger, G. R., and Gordon, R. S. Correlations between models for time-dependent creep with concurrent grain growth, (6) 231*g*.
Teshima, Hiroo. See Tarui, Yasuo.
Tesla, Narodni Podnik. Circuit arrangement for temperature measurement, P (1) 22*a*. Passive electric network, P (1) 18*h*.
Testardi, L. R., Levinstein, H. J., and Guggenheim, H. J. Magnetic and structural transformations in $RbFeF_3$, (4) 143*h*.
Teszner, S. Integral grid and multichannel field effect devices, P (2) 65*e*.
Tetenbaum, M., and Hunt, P. D. High-temperature thermodynamic properties of oxygen-deficient urania, (10) 355*c*.
Tettenhorst, R., Levinson, A. A., and McGuire, R. C. X-ray data on a fractionated regularly interstratified clay, (8) 300*j*.
Texaco, Inc. Hydrocarbon separation process employing crystalline aluminosilicates, P (11) 382*a*.
Texaco Experiment, Inc. Method of making high strength refractory filaments, P (8) 279*h*.
Texas Gulf Sulphur Co. Process for producing sodium sesquicarbonate and soda ash from trona, P (10) 349*d*.
Texas Instruments, Inc. Aluminum oxide humidity sensor, P (7) 260*f*. Amorphous glass compositions, P (7) 248*h*. Apparatus for holding silicon slices, P (10) 344*b*. Apparatus and process for growing noncontaminated thermal oxide on silicon, P (8) 282*b*. Braze grounded lead header, P (7) 255*g*. Capacitor for miniature electronic circuits or the like, P (6) 220*i*. Cermet material and method of making same, P (5) 178*d*. Color TV tube structure, P (2) 64*i*. Compound channel insulated gate triode, P (7) 256*b*. Electrical isolation of circuit components of monolithic integrated circuits, P (2) 64*a*. Electron beam techniques in integrated circuits, P (10) 344*g*. Electrooptical transistor switching device, P (4) 112*i*. Field-effect transistors, P (7) 256*i*. Formation of carbide compounds by vapor deposition on graphite bodies, P (11) 374*i*. Formation of electron barriers on phosphor particles, P (9) 312*j*. Gold alloy for attaching a lead to a semiconductor body, P (6) 221*c*. Increasing the electron energization threshold of phosphor particles, P (2) 65*c*. Integrated circuits and fabrication thereof, P (11) 377*a*. Light responsive variable capacitor, P (5) 183*h*. Method and apparatus for producing crystalline semiconductor ribbon, P (10) 346*i*. Method and apparatus for testing hermetically sealed transistor devices, P (4) 114*h*. Method for the fabrication of integrated circuits, P (10) 345*g*. Method for isolating individual devices in an integrated circuit monolithic bar, P (8) 282*j*. Method of making a capacitor by vacuum depositing manganese oxide as the electrolytic layer, P (6) 222*e*. Method of making diffused semiconductor devices, P (6) 222*g*. Method of making electrical contact to a semiconductor body, P (2) 65*f*. Method for making graded composition mixed compound semiconductor materials, P (7) 257*f*. Method of making high resistivity group III-V compounds and alloys doped with iron from

an iron-arsenide source, P (5) 183*f*. Method of making shaped epitaxial deposits, P (5) 183*h*. Method for melt-casting infrared transmitting glasses, P (9) 308*b*. Method of preparing a silicon carbide whisker reinforced silicon composite material, P (11) 375*d*. Microcontact Schottky barrier semiconductor device, P (9) 313*g*. Ohmic contacts consisting of a first level of molybdenum-gold [and] mixture of gold and vanadium and a second level of molybdenum-gold, P (6) 223*b*. Ohmic contact to semiconductor devices, P (4) 115*d*. Photoconductive electrooptic image intensifier utilizing polarized light, P (9) 313*b*. *Pn* photocell epitaxially deposited on transparent substrate and method for making same, P (7) 257*g*. Process of coating a semiconductor with a mask and diffusing an impurity therein, P (9) 313*d*. Process for making boron nitride film capacitors, P (4) 115*j*. Process for making thin film circuit devices, P (1) 19*c*. Selective deposition of semiconductor materials, P (2) 66*b*. Selective gold doping for high resistivity regions in silicon, P (7) 257*j*. Semiconductor devices and process for embedding same in plastic, P (7) 258*c*. Semiconductor junction device for generating optical radiation, P (2) 66*f*. Semiconductor optical radiation device, P (10) 346*d*. Solid-state crystal optical modulator, P (7) 258*a*. Solid state microstripline attenuator, P (6) 224*b*. Structure and fabrication of microwave oscillators, P (6) 224*b*. Structure and method for preventing spurious growths during epitaxial deposition of semiconductor material, P (5) 186*c*. Suction box cover, P (7) 253*b*. Transistor with an isolated region having a *pn* junction extending from the isolation wall to a surface, P (4) 117*a*. Use of both silicon oxide and phosphorus oxide to mask against diffusion of indium or gallium into germanium semiconductor device, P (2) 67*c*. Vapor deposition apparatus including orbital substrate support, P (10) 346*c*.

Textron, Inc. Edge-grinding machine for lenses, P (11) 371*e*. Method for blocking and deblocking lenses, P (2) 53*c*.

Thacher, P. D. Electrocaloric effects in some ferroelectric and antiferroelectric $Pb(Zr,Ti)O_3$ compounds, (1) 16*c*.

Thakar, D. H., and Nagel, G. A. Ladle and cover, P (1) 14*d*.

Thakur, R. L. See Banerjee, A. K.

Thakur, R. L., and Thingarajan, S. Kinetics of bulk crystallization of glasses, (10) 338*a*.

Thaler, W. J. See Auth, D. C.

Thatcher, C. R. See Probst, R. O.

Thayer, A. G. See Grosskopf, J. W., Jr.

Theisen, L. See Emons, H. H.

Theissing, H. H., Ewantzky, T. F., Caplan, P. J., and Grosse, D. W. Y^{3+} as a color center in irradiated CaF_2, (11) 388*e*.

Theng, B. K. G., Greenland, D. J., and Quirk, J. P. Adsorption of alkylammonium cations by montmorillonite, (7) 263*f*.

Theodore, F. W. Alkali metal salt separation, P (4) 124*f*.

Theodosopoulos, J., and Mackay, S. Method of coating [insulating oxide] heater coils, P (9) 304*h*.

Thermo Electron Engineering Corp. Method of preparing a single crystal for improved electron emission, P (6) 222*f*.

Thery, J. See Collongues, R.; Harari, A.

Theuerkauff-Liederwald, A. E. Romer (I) studies of a glass form, (4) 90*h*. Shape of glass cups with a low baluster type foot from the 17th century with special consideration of the Netherlands, (9) 303*g*.

Thiagarajan, S. See Thakur, R. L.

Thiele, K. H., Schwartz, W., and Dettmann, L. Preparation of very pure finely dispersed aluminum oxide from triethylaluminum, (6) 236*j*.

Thiele, T. N., and Gerlach, L. O. Gyratory crusher clearance measuring means having resonant coupling circuits, P (7) 262*i*.

Thiele, T. N., and Ting, L. J. Capacitance measuring means for indicating clearance in gyratory crusher and having means to compensate for stray capacitance, P (7) 262*e*.

Thiem, F. C. Surface preparation and electrostatic coating, (10) 337*b*.

Thiemann, H. Ceramic artists and their work—Ruth Koppenhoefer, (4) 90*e*; Elisabeth Pluquet-Ulrich, (11) 367*h*.

Thiemann, R. See Swamy, A.

Thilo, E. See Jost, K. H.

Thiokol Chemical Corp. Noneroding rocket nozzle, P (7) 252*j*. Tungsten oxide coated rocket motor throat insert, P (4) 108*a*.

Thire, J. Metal-oxide-semiconductor capacitor using genetic semiconductor compound as dielectric, P (1) 18*a*.

Thirsk, H. R. See Fleischmann, M.; Lown, D. A.

Thom, D. See Bramman, J. I.

Thoma, P. E. Cross-linked electrical resistance humidity sensing element, P (11) 381*e*.

Thomas, A. C. See Bethell, K. D.

Thomas, C. L. See Teichner, S. J.

Thomas, D. G. See Cuthbert, J. D.; Gershenzon, M.; Lynch, R. T.

Thomas, D. W. Small-Scale Manufacture of Burned Building Brick, B (4) 168*g*.

Thomas, E. C. Graphite heating element assembly and furnaces containing same, P (1) 23*b*.

Thomas, E. E. See Vural, B.

Thomas, G. See Midkiff, L. J., Jr.

Thomas, H. C. See Cremers, A.

Thomas, I. M. See Levene, L.

Thomas, J. E. C. See Dickinson, G. A.

Thomas, J. M. See Bahl, O. P.; Robbins, K. G.

Thomas, J. M., and Evans, E. L. Enhanced reactivity at dislocations in layer structures, (4) 135*j*.

Thomas, J. M., and Renshaw, G. D. Influence of dislocations on the thermal decomposition of calcium carbonate, (4) 139*i*.

Thomas, P. M., Neill, R. H., Wright, L. W., Crile, E. E., and Burge, R. W. Brick stacking machine, P (2) 54*e*.

Thomas, R. L. Relations of grain size, clay content, quartz, and organic carbon in some Lake Erie and Lake Ontario sediments, (11) 382*f*.

Thomas, R. T., Tredgold, R. H., and Williams, R. H. Influence of gaseous adsorption on the metal-$BaTiO_3$ contact, (4) 140*a*.

Thomas, S. H. Air pollution and glass manufacturing, (10) 337*f*.

Thomas, W. J., Sr. Apparatus for making perforated bricks, P (4) 102*d*.

Thomas Electronics, Inc. Vacuum seal for a thin beryllium X-ray window, P (4) 122*c*.

Thompsen, R. S. See Bruce, B. D.

Thompson, B. J. See Silverman, B. A.

Thompson, D. S., and Pratt, P. L. Mechanical properties of reaction-sintered silicon nitride, (2) 56*b*.

Thompson, D. W. See Barclay, L. M.

Thompson, G., and Bowen, V. T. Lithified carbonates from the deep sea of the equatorial Atlantic, (6) 229*c*.

Thompson, G. G. See Henry, J. L.

Thompson, I. M., and Maskal, J. Method of preparing magnesium hydroxide, P (9) 317*e*. Method of separating magnesium and calcium values from calcium and magnesium carbonates, P (4) 125*b*.

Thompson, J. B., Jr., and Waldbaum, D. R. Analysis of the two-phase region halite-sylvite in the system NaCl-KCl, (10) 349*h*. Mixing properties of sanidine crystalline solutions (III) calculations based on two-phase data, (11) 386*b*.

Thompson, R. J., Boaz, P. T., Cholger, H. W., Gray, D. R., and Meyer, J. H. Process using gas inlets to laterally stretch glass during float glass manufacturing, P (7) 249*d*.

Thompson, S. P. Ceramic-metal seals, P (1) 18*b*.

Thompson, S. P., and Delroy, W. Ceramic-metal seals, P (6) 220*j*.

Thompson, T. D., Wentworth, S. A., and Brindley, G. W. Hydration states of an expanded phlogopite in relation to interlayer cations, (7) 266*h*.

Thompson, W. K. Infrared study of water adsorbed on silica, (1) 31*d*.

Thomsett, M. F., Heritage, M. B., and Grigson, C. W. B. Small angle filtered electron diffraction from growing films, (4) 121*h*.

Thonstad, J. Chronopotentiometric measurements on graphite anodes in cryolite-alumina melts, (6) 214*i*.

Thonstad, J., and Solbu, A. Metal reoxidation in aluminum electrolysis, (1) 32*e*.

Thorium, Ltd. Separation of rare earth elements, P (10) 349*e*.

Thormann, P. See Rauschenfels, E.

Thorn, R. J. See Cater, E. D.

Thorn-AEI Radio Valves & Tubes, Ltd. Cathode ray tubes [evacuation], P (11) 371*b*.

Thorne, D. J. See Watt, J. D.

Thorne, R. P., and Howard, V. C. Changes induced in polycrystalline alumina by fast neutron irradiation, (4) 128*f*.

Thorne, R. P., Howard, V. C., and Hope, B. Radiation-induced changes in porous cubic silicon carbide, (4) 151*i*.

Thornton, W. A., Jr. Method of activation of phosphor, P (6) 222*a*. Polychromatic luminescent devices and method of manufacture, P (11) 378*e*. Preparation of electroluminescent phosphors, P (4) 115*g*. Process for manufacturing an electroluminescent device, P (4) 116*a*.

Thorp, J. M., and Woolf, J. B. Modification of the porous structure of silica gel on purification and the associated change in the dielectric behavior of adsorbed benzene, (4) 144*j*. Sorption and dielectric behavior of benzene on silica gel, (10) 360*f*.

Thorp, T. L. See Cashion, J. D.

Thouret, W. E. Incandescent lamp with addition of fluorine compounds to the operating gas filling, P (4) 99*j*.

Thouret, W. E., and Strauss, H. S. Metal vapor lamp with metal additive for improved color rendition and internal self-ballasting filament used to heat arc tube, P (8) 282*e*.

Thring, M. W. Application of our knowledge of flames and heat transfer to the future design of glassmelting furnaces, B (4) 168*j*.

Throne, J. L. See Progelhof, R. C.

Thrower, P. A. Thermal annealing studies of irradiation defects in graphite and the self-diffusion mechanism, (9) 331*c*.

Thuemmler, F. See Bumm, H.; Holleck, H.

Thumm, H. See Kulling, A.

Tibol, G. J. Process and apparatus for making thin film capacitors [vacuum deposition], P (11) 378*g*.

Tichelaar, G. W. See Essers, W. G.

Tichy, J. See Zelenka, J.

Tichy, O. Problems of firing at high temperatures, (10) 348*d*.

Tiede, R. L. Glass fibers and treatment therefor, P (8) 277*b*.

Tiemann, J. J. See Hall, R. N.

Tien, P. K. See Buchsbaum, S. J.

Tien, P. K., Ulrich, R., and Martin, R. J. Modes of propagating light waves in thin deposited semiconductor films, (10) 344*h*.

Tien, Pei-Lin, Waugh, T. C., and Dilts, R. L. Vivianite in Graneros shale (Upper Cretaceous), central Kansas, (9) 317*b*.

Tien, R. H., and Geiger, G. E. Heat transfer analysis of the solidification of a binary eutectic system, (4) 138*i*. Unidimensional solidification of a binary eutectic system with a time-dependent surface temperature, (4) 163*a*.

Tien, T. Y. See Smith, D. E.

Tien, T. Y., and Cross, L. E. Dielectric relaxation in strontium titanate solid solutions containing lanthana, (9) 320*a*.

Tien, T. Y., Rosen, J. J., Bigelow, W. C., and Sanvordenker, V. Microhardness of TiO_2-Nb_2O_5 solid solutions, (11) 386*b*.

Tietjen, J. J., and Amick, J. A. Preparation and properties of vapor-deposited epitaxial $GaAs_{1-x}P_x$ using arsine and phosphine, (1) 35*h*.

Tighe, N. J. See Barber, D. J.

Tikhonov, V. N., Kuznetsov, S. I., and Myuller, A. M. Induction period during the decomposition of aluminate solutions, (1) 30*j*.

Tillack, J. Tungsten-oxygen-iodine system (II) preparation and properties of tungsten dioxide iodide, (5) 202*b*.

Tiller, W. A. Theoretical analysis of requirements for crystal growth from solution, (7) 270*g*.

Tiller, W. A., and Kang, C. Growth rate of crystals from solution, (7) 266*h*.

Tillett, P. I. See Grigson, C. W. B.

Tillett, P. I., and Grigson, C. W. B. Reflection scanning electron diffraction from growing films, (4) 153*f*.

Tilling, R. I. Zonal distribution of variations in structural state of alkali feldspar within the Rader Creek pluton, Boulder batholith, Montana, (4) 164*d*.

Tilton, A. E. See Patterson, R. J.

Timashev, V. V. See Butt, Yu. M.

Timidei, A., and Janz, G. J. Transport processes in low melting salts—thallous nitrate, (8) 300*a*.

Timmons, G. A. Molybdenum powder for use in spray coating, P (2) 46*e*.

Timofeev, V. A., and Timofeeva, E. N. Standard heats of formation of oxides and hexaborides of the rare-earth elements, (7) 269*h*.

Timofeeva, E. N. See Timofeev, V. A.

Timofeeva, N. I. See Mordovin, O. A.

Timofeeva, V. A. Isomorphic impurity distribution in garnets as a function of the solubility of the trivalent oxides in molten salts and of the method of crystal growth, (10) 356*d*.

Timonova, R. I. See Ivashentsev, Ya. I.

Ting, L. J. See Thiele, T. N.

Tingquist, S. C., and Trench, W. H. Method for manufacture of refractory shell molds, P (6) 217*j*.

Tinkle, M. C. See Benz, R.

Tinling, D. J. A. See Brivati, J. A.

Tinnes, B. Molten metal pouring spout, P (11) 375*d*.

Tinsley, C. J. See Parker, R.

Tipotsch, D. G. Wavelength programed monochromator device with adjustable entrance and exit cam operated slit means for providing a variable proportionality factor between their widths, P (11) 381*e*.

Tipsword, R. F. See Whidden, C. J.

Tipsword, R. F., Allender, J. T., Stahl, E. A., Jr., and Williams, C. D. Temperature dependence of the nuclear quadrupole resonance frequency of ^{79}Br in $NaBrO_3$ and $KBrO_3$, (8) 299*j*.

Tischer, R. E. Effect of compression and compositional changes on the nature of chromium sites in simple glasses. (2) 48*j*. Heat of annealing in simple alkali glasses, (11) 370*f*.

Tishura, T. A. Phase composition of binary and ternary systems composed of SiO_2, CaO, Na_2O, and B_2O_3, (9) 326*i*.

Titan Abrasives Co. Abrasive disk, P (1) 1*j*.

Titangesellschaft m.b.H. Process and apparatus for the manufacture of fine particle size titanium dioxide by reacting titanium tetrachloride with oxygen, P (4) 125*g*. Process for the manufacture of a rutile pigment by reacting titanium tetrachloride with oxygen or gases containing oxygen, P (10) 349*f*.

Tite, M. S. Determination of the firing temperature of ancient ceramics by measurement of thermal expansion, (10) 347*e*.

Title, R. S., and Plaskett, T. S. EPR detection of triple Li ion centers in lithium-diffused Mn-doped GaP crystals, (10) 353*f*.

T'Jampens, G. R., Meijer, R. A. J. M., and van de Weijer, M. H. A. Regenerative cycle electric incandescent lamp, P (4) 116*h*.

Tobin, R. C. See Spry, A.
Tobolov, P. N., Kriger, J. A., Litvinov, I. P., Bashirov, I. G., and Fildshtein, M. V. Plant for conditioning free-flowing hardening mixture [casting cores], P (9) 309*b*.
Tocu, P. See Avram, C.
Toda, Masumi. See Kinuta, Tsunekazu.
Togashi, Hiromitsu. See Hamano, Kenya.
Toibana, Yasuo. See Hashimoto, Hachiro.
Toibana, Yasuo, and Hashimoto, Hachiro. Hot-pressed titanium and zirconium diborides, (2) 56*c*.
Tokar, M. Microstructure and magnetic properties of lead ferrite, (8) 281*a*.
Tokiwano, Kazuo, and Hayashi, Masakazu. Absorption line ($n = 1$) of Cu_2O, (1) 24*g*.
Tokonami, Masayasu. See Morimoto, Nobuo; Yuasa, Takaaki.
Tokuda, Toshio. See Yamaguchi, Goro.
Tokue, Tetsuo; Ishino, Ken; and Makino, Motohiko. Relation between magnetic properties and powder characteristics in Ni-Zn ferrite, (5) 181*g*.
Tokumaru, Yozo. Current oscillations by two bulk negative-resistance effects in photo-excited GaAs, (9) 310*e*.
Tokumoto, Yukitaka. See Hoshino, Masahiro.
Tokutaka, H. See Gallon, T. E.
Tokuyama, Takashi, and Uehara, Keijiro. Surface treatment of semiconductor device, P (8) 283*j*, P (9) 314*e*.
Tokuyama, Takashi; Uehara, Keijiro; and Adachi, Yuko. Method of forming a glass coating on semiconductor, P (4) 114*f*.
Tokyo Kakin Kogyo Co., Ltd. Additive for production of spheroidal graphite cast iron consisting mostly of calcium-silicon, P (4) 93*i*.
Tokyo Shibaura Electric Co., Ltd. Fluorescent lamps, P (11) 371*f*. Method of converting carbonaceous material to diamond, P (10) 335*f*. Method of making baseless lamp bulb, P (2) 53*f*. Method of making synthetic diamond crystals, P (8) 273*g*. Method for the manufacture of alumina refractories having an aluminum nitride coating, P (5) 179*c*. Method for preparing diamond crystals, P (7) 243*h*. Method of preparing sintered masses of aluminum nitride, P (7) 252*h*. Semiconductive electromechanical transducers, P (6) 223*c*.
Toland, D. A., and Conaway, H. L. Improved steel for direct-white enameling applications, (1) 4*d*.
Tolksdorf, W. Growth of yttrium iron garnet single crystals, (7) 258*h*.
Tolmachev, A. F. See Perelman, S. M.
Tolman, E. M. See Olsen, K. M.
Tolutis, V. Selenium memory cell containing silver up to 2 at.% adjacent the rectifying contact, P (9) 313*h*. See Lautsyus, A. S.; Meshkuotis, Yu. A.
Tolutis, V., Deksnys, A., and Paukste, J. Characteristics of physical properties of thin tetragonal InTe films, (5) 192*b*.
Tolutis, V., Jasutis, V., and Bertulis, K. Properties of CdTe film growth at the substrate temperatures at which the coefficient of CdTe condensation $\alpha<1$, (5) 199*d*.
Toma, S. Z., Mathers, J. E., and Mikus, F. F. Method for preparing vanadate phosphors, P (5) 184*a*.
Toma, S. Z., Mikus, F. F., and Mathers, J. E. Energy transfer and fluorescence processes in Bi^{3+} and Eu^{3+} activated YVO_4, (4) 135*i*.
Tomandl, G., Frischat, G. H., and Oel, H. J. Moessbauer effect in iron-alkali-silicate glasses, (9) 306*i*.
Tomasek, M., and Koutecky, J. Nature of the chemisorption bond on semiconductor surfaces, (10) 357*e*.
Tomb, W. H., Wesel, P. E., and Zine, A. R., Jr. [Glass] pipe coupling, P (4) 99*b*.
Tombak, M. I. See Gurvich, A. M.
Tombs, N. C. Oxygenated silicon nitride semiconductor devices and silane method for making same, P (5) 184*e*.
Tomida, K., and Sudo, T. Interstratification structure formed from a preheated mica by acid treatments, (8) 293*h*.
Tomita, Kensuke. See Takahashi, Takehiko.
Tomita, Takanori. See Yuasa, Takaaki.
Tomita, Takanori, and Yuasa, Takaaki. Polymorphism of silicon carbide crystals, (1) 35*a*.
Tomizawa, Toshiaki; Hashimoto, Hidehisa; and Moteki, Kesakichi. Effects of calcining conditions on the properties of MgO particles, (8) 291*i*.
Tomkins, R. P. T. See Janz, G. J.
Tomkus, M. R. See Palilla, F. C.
Tomono, Yuzo. See Nagata, Kazukiyo.
Tomotika, Tosiro. See Inoue, Toshiharu.
Tomoyoshi, Shoichi. See Takeda, Takayoshi.
Tompkins, F. C. See Delchar, T. A.
Tomura, Kenji; Higuchi, Hideo; Onuma, Naoki; and Hamaguchi, Hiroshi. Rapid determination of dysprosium in rock samples by neutron activation analysis with a Ge(Li) detector after chemical separation, (1) 21*i*.
Tongyai, Singkata. See Schuster, L. K.
Tonjes, B. D. Aggregate size testing apparatus and process, P (7) 262*d*. Pulsatory screening device, P (4) 118*i*.
Tonozzi, S. A. Method [etching] of manufacturing printed circuit boards, P (9) 312*h*.
Toolmasters, Ltd. Method of making a grinding member, P (4) 89*j*.
Toombs, P. A. B. Thin films of barium lanthanum titanate, (2) 64*a*.
Toop, G. W. See Olson, N. J.
Toothacker, W. S., Preuss, L. E., and Bugenis, C. K. Debye-Scherrer powder photographs obtained using ^{55}Fe K X-rays on lithium fluoride, (5) 193*a*.
Topas, B. Apparatus for [acid] dicing semiconductor wafers, P (5) 182*f*. Method of etching a semiconductor material, P (5) 183*c*.
Topol, L. E., and Owens, B. B. Thermodynamic studies in the high-conducting solid systems RbI-AgI, KI-AgI, and NH_4I-AgI, (5) 201*g*.
Topping, J. A. See Gough, E.
Torii, Michihiro. See Kobayashi, Nariaka.
Torikai, Naochika; Sasamoto, Tadashi; and Komine, Yoshiharu. Reactivity of carbon in the formation of calcium carbide in the molten phase, (9) 328*e*.
Torikai, Naochika; Sasamoto, Tadashi; and Shudo, Akio. Reactivity of quicklime for formation of calcium carbide in molten phase, (4) 123*h*.
Tornqvist, N. E., and Stark, S. O. S. Method of applying preferably band-shaped metal parts with good mechanical adhesion to a metal frame coated with insulating, preferably ceramic, material, P (5) 183*j*.
Torok, A. Modified montmorillonite containing exchangeable ammonium cations and preparation thereof, P (2) 74*h*.
Torok, E. J. See Barker, P. D.
Torok, F. See Foldesi, I.; Fogarasi, G.
Toropov, N. A. Activity of the Institute (of Silicate Chemistry) related to the design of protective coatings for different materials, B (5) 204*d*. See Boikova, A. I.; Grebenshchikov, R. G.; Shirvinskaya, A. K.
Toropov, N. A., and Babayan, S. A. Synthesis and study of the properties of the orthosilicates of nickel and cobalt, (4) 158*e*.
Toropov, N. A., and Degen, M. G. New microstructures of inorganic materials, (2) 50*g*.
Toropov, N. A., and Rumyantsev, P. F. Solution kinetics of dicalcium silicate in liquid phase of cement clinker; Tricalcium silicate, (8) 274*g*. Study of kinetics of solution of calcium oxide in the liquid phase of cement clinker, (7) 245*a*.
Toropov, N. A., Sher, E. S., and Degen, M. G. Microstructure of organosilicate materials, B (5) 204*i*.
Torres-Acuna, N. See Habashi, Fathi.
Toshev, A. See Peshev, P.
Tosser, M. Effects of disturbance of the transfer of electrons in electroluminescent diodes by electrode transparency, (8) 281*e*.
Totani, A., Okazaki, H., and Nakajima, S. Phase relations in the system SnTe-SnSe, (2) 81*c*.
Totesh, A. S. See Mazurin, O. V.
Toth, I. See Boucraut, M.
Toth, L., and Collins, S. A., Jr. Reconstruction of a three-dimensional microscopic sample using holographic techniques, (4) 121*c*.
Toth, R. S., and Cicotte, L. J. Epitaxy of Ag and Au on doped NaCl substrates, (2) 62*j*.
Totta, P. A. See Mutter, W. E.; Napier, J.
Touchy, W. Pressure-responsive semiconductor device, P (5) 184*j*. See Zerbst, M.
Toulouse, J. H. Empontilling—a hisory (I-II), (1) 7*a*.
Touray, J. C., and Lantelme, F. Analysis of gas inclusions in minerals—method of progressive heating, (1) 25*g*.
Touray, J. C., and Yalims, J. Study of inclusions of liquid CO_2 in quartz veins, (1) 38*f*.
Touron, L. See Makram, H.
Toussaint, C. J., and Vos, G. Variations in the lattice parameter of the solid solution of lithium oxide in nickel oxide, (9) 332*j*.
Towe, K. M., and Bradley, W. F. Mineralogical constitution of colloidal "hydrous ferric oxides," (1) 32*f*.
Towles, R. J. See Naughton, T. J.
Town, J. W. Crystallization of tungsten disulfide from molten slags, P (1) 13*h*.
Townsend, M. G. See Ralph, J. E.
Townsend, P. D. Spectral emission from LiF during thermoluminescence, (8) 298*e*.
Townsend, R. L., Jr. See Phillips, T. G.
Toyoda, Hiroo. See Ashida, Toshio; Itakura, Masajuki; Iwasaki, Hiroshi; Niizeki, Nobukazu; Yamada, Tomoaki.
Toyoshima, Satoshi. See Nakaido, Yasuaki.
Toyoshima, Y., Kobatake, Y., and Fujita, H. Studies of membrane phenomena (IV) membrane potential and permeability; (V) bulk flow through membrane, (8) 298*f*.
Toyoshima, Y., Yuasa, M., Kobatake, Y., and Fujita, H. Studies of membrane phenomena (III) electric resistance of membranes, (8) 298*e*.
Toyota, Yukio. See Miyatani, Shinya.
Tozer, D. C. (editor). Non-Elastic Processes in the Mantle—Proceedings of the International Upper Mantle Committee Symposium Held at Newcastle upon Tyne, Feb. 21-25, 1966, B (6) 241*c*.
Traber, W. F. See Oron, M.
Trachte, K. See Wambach, A.
Tragert, W. E. See Mitoff, S. P.
Trambouze, Y. See Bressat, R.
Trampier, C. R., Jr. See Heywood, K. W.
Trancoa Chemical Corp. Radiation resistant semiconductor grade silicon containing a metal oxide, P (8) 283*j*.
Transitron Electronic Corp. Matrix-type permanent memory device, P (11) 377*d*. Semiconductor device doped with gold just to the point of no excess and method of making, P (8) 283*e*.
Trap, H. J. L. Electronically conducting glasses, their properties and possible applications in electronics, (7) 247*j*.
Trapp, H. D. See Juza, R.
Trautweiler, F., Moser, F., and Khosla, R. P. Optical and electrical properties of CdF_2:In and CdF_2:Eu, (10) 358*a*.
Traverse, J. P. See Foex, M.
Treacy, E. B. Measurement of picosecond pulse substructure using compression techniques, (10) 357*a*.
Tredennick, W. T., and Miller, J. R. Refractory floor construction, P (6) 218*d*.
Tredgold, R. H. See Thomas, R. T.
Trees, J. S. See Edgecombe, D. A.
Treffner, W. S. See Farrington, G. M.
Treichler, W. See Witzmann, H.
Treinin, A. See Feldmann, T.
Trench, W. H. See Tinguist, S. C.
Tress, J. E. See Good, P. C.
Tressaud, A. See de Pape, R.; Portier, J.
Tressler, R. E., Hummel, F. A., and Stubican, V. S. Pressure-temperature study of sulfospinels, (1) 35*i*.
Tresvyatskii, S. G. See Panasevich, V. M.; Pavlikov, V. N.
Tresvyatskii, S. G., Isakhanov, G. V., Grosheva, V. M., and Donets, I. G. Resilience of silicates and oxides—preparation of the products, (9) 328*j*.
Tresvyatskii, S. G., Lopato, L. M., Pavlikov, V. N., and Shevchenko, A. V. Phase correlation in systems formed by the oxides of rare earths and chromium, (1) 34*g*.
Tretinnik, V. Yu. See Kruglitskii, N. N.; Ovcharenko, F. D.
Tretjakow, J. D. See Hohmann, H. H.
Treusch, A. L. See Farr, A. E.
Trevorrow, L. E. See Riha, J. G.
Trevorrow, L. E., Steindler, M. J., Steidl, D. V., and Savage, J. T. Melting-point diagram for the system uranium hexafluoride-plutonium hexafluoride, (11) 386*b*.
Trier, W. See Giegerich, W.
Trigunayat, G. C. See Jain, R. K.
Triplex Safety Glass Co., Ltd. Laminated transparent panels incorporating heating wires, P (7) 248*j*. Methods and apparatus for treating glass sheets, P (6) 213*g*. Tubular cutting tools, P (9) 308*d*.
Tripp, T. B. See Smyth, D. M.
Trivich, D. See Balkanski, M.
Troell, P. T. See Renkey, A. L.
Troemel, C. P., and Weber, E. H., Jr. Temperature measuring apparatus using semiconductor junction, P (5) 188*h*.
Troemel, G., Fix, W., and Heinke, R. High temperature studies up to 1900°C on calcium orthosilicate and tricalcium silicate, (7) 266*e*.
Trofimov, M. G. See Verenkova, E. M.; Zakharov, B. M.
Troitskii, O. A., and Terekhova, N. B. Effect of α-radiation on the microplasticity of quartz glass, (2) 48*j*.
Trojer, F. J. Crystal structure of parawollastonite, (6) 231*i*.
Trostel, L. J., Jr. Compressive creep of high purity aluminum oxide refractories, (8) 278*j*.
Trott, W. J., and Radford, W. E. Method [fluid amalgam] for joining piezoelectric elements, P (9) 312*h*.
Trotter, J. See Bartlett, N.
Trout, H. E., Jr. Stabilized zirconia—a coming tool for metallurgists, (9) 311*c*.
Trudeau, U. P. Parison transfer and invert mechanism, P (8) 278*a*.
Truhlarova, M., and Veprek, O. Solution of fused quartz in Na_2O-SiO_2 melts, (9) 307*d*.
Truitt, J. D. See Bawa, M. S.
Tru-Lay Masonry Products Corp. Grooved brick construction and composite thereof, P (6) 214*d*.
Trulson, O. C., and Goldstein, H. W. Mass spectrometric study of zirconium diboride, (1) 32*a*.
Trumbore, F. A. See Gershenzon, M.
Trunov, V. K. See Lykova, L. N.
Trunov, V. K., and Kovba, L. M. Roentgenography of the double oxide La_2O_3·$5Nb_2O_5$, (8) 297*a*.
Trurumi Soda Co., Ltd. Novel cobalt oxide and an electrode having the cobalt oxide coating, P (1) 18*h*.
Trutner, D. G., and Olsen, A. H. Machine for forming helical grooves in thin wall glass tubing, P (1) 11*b*.
Truzenberger, M. See Sole, M. J.
TRW, Inc. Coating of refractory metals with metal modified oxides, P (4) 93*h*. Information storage devices, P (7) 256*c*. Liner for crucibles, P (1) 14*e*. Method and apparatus for improving grain structures and soundness of castings, P (7) 252*c*. Ultrasonic transducer, P (10) 346*a*. Vitreous enamel resistor composition and resistor made therefrom, P (7) 246*i*.
Tsai, J. C. Field-effect semiconductor devices of the junction type and method of making, P (9) 312*j*. Semiconductor devices [MOS] with a region having portions of differing depth and concentration, P (9) 314*a*.
Tsai, S. W. See Schultz, A. B.
Tsai, S. W., Halpin, J. C., and Pagano, N. J. (editors). Composite Materials Workshop

—Proceedings of the Summer Workshop, Physical Aspects of Composite Materials, Held at Washington University, St. Louis, Mo., July 1967, B (4) 166*f*.

Tsang, Tung, and Farrar, T. C. Nuclear magnetic relaxation studies of internal rotations and phase transitions in borohydrides of lithium, sodium, and potassium, (11) 386*j*.

Tsang, Wei K. See Busen, K. M.

Tsang, Wei K., and Busen, K. M. Narrow emitter lateral transistor, P (8) 283*f*.

Tsapkin, V. V. See Zhabotinskii, M. E.

Tsapkina, I. V. See Zhabotinskii, M. E.

Tsirlin, Yu. A. See Gel'fman, A. Ya.

Tsoucaris, G. See de Rango, C.

Tsubaki, Takayuki; Hattori, Makoto; and Tanaka, Masa.ni. Thermal conductivity of vitreous sodium phosphates, (4) 97*f*.

Tsuboi, Masamichi, and Wada, Akiyoshi. Optically active lattice vibrations in wurtzite-type crystals of zinc oxide and cadmium sulfide, (4) 147*d*.

Tsubouchi, Norio. See Akashi, Tsuneo.

Tsuboya, Ichiro. See Hasegawa, Masashiko.

Tsuchida, Atsushi. See Nakagawa, Ichiro.

Tsuchihashi, Shoji. Corrosion of polished surfaces of optical glass by small droplet of etchant solution, (6) 208*j*.

Tsuchihira, Hisao. See Nakai, Tsuneo.

Tsuchiya, Nobujiro. See Murakami, Kazo.

Tsuchiya, Yoshimi. See Kabashima, Shigeharu.

Tsuda, Isunekazu. See Hashimoto, Tsunekazu.

Tsuda, Toshinobu. See Kubo, Takeji.

Tsuji, Shigeru. See Ikeda, Koichi.

Tsuji, Shigeru, and Anazawa, Shinzo. Semiconductor device, P (2) 66*d*.

Tsuji, Shigeru; Hayashi, Kazutami; Kadowaki, Kouichi; and Sato Katsuo. Device for glass glazing electronic housing members, P (7) 248*e*.

Tsujimoto, Hiroshi. See Kaname, Yuichi.

Tsukiyama, Koichi. See Uchikawa, Hiroshi.

Tsukuda, Noboru. See Okazaki, Atsushi.

Tsunashima, Yutaka. See Kato, Chuzo.

Tsurumi, Takematsu. See Nakazawa, Michihiko.

Tsutsumi, Kenjiro, and Nakamori, Hiroo. X-ray *K* emission spectra of chromium in various chromium compounds, (10) 363*f*.

Tsutsumi, Nobuhisa. Cupola, (2) 54*j*.

Tsutsumi, Yoshitaka. See Kunitomo, Masakazu.

Tsutsumi, Yoshitaka; Kunitomo, Masakazu; Terao, Takehiko; and Hashi, Tsuneo. NMR of ^{39}K in KH_2PO_4 in the ferroelectric phase, (2) 81*b*.

Tsuya, Hideki. See Sugibuchi, Kiyoshi.

Tsuzuku, Takuro, and Saito, Mitsuhiro. Impurity-dope effects on the anelasticity of graphite, (8) 293*j*.

Tsuzuku, Takuro; Yugo, Shigemi; and Fukui, Tsunenori. Annealing study of radiation damage in graphite by ESR, (2) 74*i*.

Tsygankova, M. S. See Fedorov, P. I.

Tsykunova, S. V. See Kuz'min, N. M.

Tucker, W. F. Methods and apparatus for zone melting, P (6) 227*j*.

Tul'chinskii, V. B., Ryss, I. G., and Zubov, V. I. Synthesis and some properties of potassium difluorophosphate KPO_2F_2, (8) 299*i*.

Tuleff, J. Sintering from its macroscopic aspect, (6) 237*f*.

Tully, G. R., Jr., and Goeddel, W. V. Method of fabricating low permeability nuclear fuel bodies, P (2) 59*b*.

Tully, J. W. See Tao, T. F.

Tulovskaya, Z. D. See Segalova, E. E.

Tuluzov, G. N. See Vatman, A. P.

Tuma, G. See Rein, R. G., Jr.

Tumanov, A. D. See Bash, S. M.

Tumanov, S. G., Petrov, Yu. F., and Bystrikov, A. S. Synthesizing ceramic pigments in the $R_2^{3+}R_2^{3+}(PO_4)_4$ system, (6) 219*g*.

Tumanov, S. G., and Smirnova, E. P. Role of a gas medium in firing of porcelain, (10) 343*d*.

Tummala, R. R., and Friedberg, A. L. Strength of glass-crystal composites, (6) 211*i*.

Tung, S. E., and McInnch, E. Process [and catalyst] for reducing the pour point of crude oil and the like, P (1) 24*f*.

Turco, J. F. See Petrocelli, A. W.

Turkat, M., and Robba, W. A. Grain-oriented pyrolytic graphite forms and method [vapor deposited] of making same, P (4) 106*i*. Method for depositing pyrolytic graphite, P (8) 279*e*.

Turkdogan, E. T. Iron-sulfur system (I) growth rate of ferrous sulfide on iron and diffusivities of iron in ferrous sulfide, (4) 141*g*. See Worrell, W. L.

Turkov, S. K. See Postnikov, V. S.

Turnbaugh, J. E. See Sung, P.

Turnbull, D. See Seward, T. P., III.

Turnbull, N. C. See Scott, J. J.

Turner, D. W. Photoelectron spectroscopy, (4) 120*c*.

Turner, E. H. See Kaminow, I. P.

Turner, P. P., and Bartram, S. F. Tentative phase diagram of beryllia-lithia system, (4) 159*h*.

Turner, R. See Riccius, H. D.

Turner, R. G. See Spry, A.

Turner, R. M., and Whitworth, R. W. Movement of dislocations in sodium chloride crystals in an electric field, (5) 197*h*.

Turner, W. H. See Albinak, M. J.

Turner Brothers Asbestos Co., Ltd. Manufacture of asbestos products, P (9) 317*e*.

Tuszynski, W., and Chojnicka, G. Problem of inhibitors in the process of etching the glass-ceramics "Quasicerams," (4) 97*c*.

Tuthill, E. J., Strickland, G., and Weth, G. G. Platinum for high temperature crucibles used in processing radioactive wastes, (5) 178*a*.

Tuttle, O. F. See Ragone, S. E.

Tvarusko, A. Electric resistivity of AgO, (5) 180*j*.

Tweed, R. E. Method of testing the porosity of coated articles, P (11) 381*a*.

Twine, C. J. Burner tube assembly for heat-treating furnace, P (5) 189*g*. See Seelandt, K. H.

Twomey, E. F., Jr., and Robbins, J. W. Radiant energy reflective and translucent structures of fiber-reinforced plastics, P (4) 101*a*.

Twomey, E. F., Co., Inc. Radiant energy reflective and translucent structures of fiber-reinforced plastics, P (4) 101*a*.

Tyco Laboratories, Inc. Method of growing [piezoelectric] crystals, P (6) 225*c*.

Tykachinskii, I. D. See Boguslavskii, I. A.

Tyler, L. W. Carbonaceous cement, P (7) 252*d*.

Tyler, W. S., Inc. Method and apparatus for sizing of discrete particles in a fluid medium, P (10) 346*j*. Method and apparatus for wet sizing finely divided solid materials, P (7) 259*b*.

Tyrolerova, P. See Hanvkyr, V.; Spicak, K.

Tyrolerova, P., and Lu, W-K. Volume change on freezing of Al_2O_3, (4) 163*i*. Volume change of mullite on solidification, (7) 270*e*.

Tyrrell, M. E. See Hollenbeck, R. P.

Tyul'kin, V. A. See Sidorov, T. A.

Tyulyaeva, N. G. See Sobel'man, E. I.

Tyurin, Yu. M. See Shabanov, A. G.

Ubank, R. G. See Llewelyn, G.

Ubbelohde, A. R. See Rhodes, E.

Uchida, Enji; Fukuoka, Nobuo; Kondoh, Hisamoto; Takeda, Tadao; Nakazumi, Yoshihide; and Nagamiya, Takeo. Magnetic anisotropy of single crystals of NiO and MnO, (2) 79*f*.

Uchida, Ichizo. Photoconductivity of pure cadmium sulfide single crystal near the band edge, (8) 296*h*.

Uchida, Naoya. Calculation of electrostriction and polarization in perovskite-type ferroelectric ceramics, (1) 16*b*.

Uchikawa, Hiroshi, and Tsukiyama, Koichi. Precise determination of $BaAl_2O_4$ ceil and certification of the formation of iron-bearing solid solution, (1) 35*f*. Structural change and mechanical strength of hydrated barium aluminate at elevated temperature, (5) 170*h*.

Udagawa, S. See Williams, E. G.

Udvardi, M. Determination of carbon in flue dust, fly ash, and cement clinker, (2) 69*f*.

Uebbing, J. J. See Bell, R. L.

Ueda, Ichiro. See Ikegami, Seiji.

Ueda, Masao. See Miyatake, Kazumi.

Ueda, Masao, and Iwamoto, Yoshimi. Effect of water on crushed quantity and grain size of raw material during crushing process (I) crushing in dry pan mill, (10) 341*d*.

Ueda, Ryuzo. See Inuzuka, Tadao.

Ueda, Toshiro. See Sakurai, Toshio.

Uehara, Keijiro. See Okutsu, Shinkichi; Tokuyama, Takashi.

Uei, Isao. See Nakazawa, Yasuro.

Uei, Isao, and Fukui, Masao. Rapid determination of thermal conductivity of refractories by the hot-wire method, (11) 373*g*.

Uei, Isao; Inoue, Keikichi; and Fukui, Masao. Sintering and crystallization processes of glass powder having cordierite composition, (1) 36*h*.

Uemura, Yukikazu. See Nakagawa, Masuo.

Ueno, Tokihiro, and Hayashi, Masakazu. Fine structures in the absorption spectrum of NiO, (1) 29*g*.

Ueoka, Hisayoshi; Tashima, Norio; and Takei, Takeshi. Nature of manganese-bearing sintered wustite (II) semiconductive and thermomagnetic properties, (4) 145*g*.

Uesugi, Mitsuo. See Aoyagi, Kiyoshi.

Uetani, Keiji; Ogimura, Yoshiko; Kato, Akira; and Nagashima, Kozo. Chemical studies of minerals containing rarer elements from the Far East district (LXI) yttrofluorite from Suishoyama, Kawamatamachi, Fukushima Prefecture, Japan, (8) 289*f*.

Uetsuki, Toru. See Nakazawa, Yasuro.

Ugine Kuhlman (Societe Anonyme). Manufacture of molybdenum trioxide, P (2) 74*b*.

Uhlmann, D. R. See Kimmel, R. M.; Seward, T. P., III.

Uhrich, D. L., and Barnes, R. G. Moessbauer effect determination of Tm^{3+} crystalline electric field parameters in thulium-doped soda-silica glasses, (6) 210*i*.

Ukrainskii, L. Z., and Obnovlenskii, P. A. Ultrasonic measurement of the degree of dispersion of suspended particles, (2) 71*h*.

Ukshe, E. A., and Kachina-Pullo, E. B. Electrical conductivity in the system KCl-$MgCl_2$, (7) 265*b*.

Ulbricht, G. See Hennings, K.

Ullman, W. L., Baxter, J. C., Pearson, A. J., Davis, R. E., and Hullhorst, W. B. Method for production of tubular fibrous bodies, P (2) 53*h*.

Ullrich, H., and Sussmann, E. Method of manufacturing [doped] integrated semiconductor circuit device, P (8) 283*d*.

Ulrich, R. See Tien, P. K.

Ulrich, R. J. See Cawthon, W. C.

Ultra Carbon Corp. Method of purifying graphite, P (4) 107*d*.

Umblia, E. J. See Polasek, K. H.

Umeno, Masayoshi. See Arizumi, Tetsuya.

Underwood, P. J. See Martyny, W. C.

Ungureanu, G. See Comsulea, D.

Union Carbide Corp. Abrasive wheels comprising a novolak resin and a thermoplastic polyhydroxyether, P (2) 43*g*. Antistatic agents for glass fiber materials, P (4) 98*c*. Carbonaceous cement, P (7) 252*d*. Chrysotile asbestos fiber dispersion including monocarboxylic acid, P (2) 74*a*. Coating composition and method of applying, P (7) 246*e*. Crystalline zeolite containing singly charged nickel cations, P (4) 124*j*. Densification of boride compositions, P (7) 252*j*. Desiccant bodies, P (8) 287*i*. Fuel nozzles for high temperature furnace and method of operating, P (11) 381*i*. Glass fiber reinforced thermoplastic polyarylene polyether resin article and process for making same, P (6) 212*d*. High temperature cement, P (6) 217*a*. Iridium coated graphite, P (8) 279*d*. Low silica welding composition, P (5) 172*a*. Metallic carbides and a process of producing the same, P (1) 14*f*. Method of making bonded welding flux, P (6) 208*b*. Method of making refractory shapes, P (1) 14*g*. Method of manufacturing fuel elements [for nuclear reactors], P (7) 252*g*. Method and material for hard-surfacing, P (5) 172*a*. Method of providing electrical contacts by sputtering a film of gold on a layer of sputtered molybdenum, P (7) 257*c*. Method of uniformly heating an annular carbonaceous body, P (2) 59*h*. Passivation of semiconductor devices, P (10) 345*e*. Polycrystalline oxide bodies, P (8) 274*e*. Process for preparing chromates, P (2) 74*c*. Process for producing fibrous graphite, P (10) 343*b*. Process for producing metal carbide fibers, textiles, and shapes, P (1) 14*f*. Process for producing metal fibers, textiles, and shapes, P (2) 59*d*. Process for producing metal nitride fibers, textiles, and shapes, P (1) 14*g*. Production of vanadium trioxide, P (4) 125*f*. Refractory composites and method of making the same, P (2) 59*e*. Reversible flocculation and redispersion of chrysotile asbestos, P (5) 191*d*. Solid solution cement, P (8) 274*f*. Solid state laser device using gadolinium oxide as the host material, P (5) 185*b*. Shredded carbonaceous fiber compactions and method of making the same, P (2) 59*f*. Strengthened arc carbon electrode joints, P (2) 59*g*. Treatment of oxidatively regenerated molecular sieve catalysts, P (9) 317*g*. Tube wire electrode, P (2) 46*c*. Zeolite N and process for preparing same, P (4) 126*b*.

Union Oil Co. of California. Process for the manufacture of metal-cation-deficient zeolites, P (11) 382*g*.

Union Scientifique Continentale du Verre, Belgium. Symposium on the Surface of Glass and Its Modern Treatments, Luxembourg, June 1967, (5) 204*h*.

United Aircraft Corp. Coated nickel base engine alloys, P (9) 304*h*. Coating composition comprising aluminum and metal fluorides, P (4) 93*g*. Composite structural material incorporating metallic filaments in a matrix and method of manufacture, P (5) 178*e*. Method of applying oxidation protective coatings to niobium, P (6) 208*c*. Method for bonding silicon semiconductor devices, P (11) 377*g*. Method of forming Ti-modified silicide coatings on Nb-base substrates and resulting articles, P (8) 275*f*. MOS field-effect transistor with a 1 μm vertical channel, P (4) 115*a*. Monocrystalline directional sonic transducer, P (5) 184*i*. Process for making filamentary materials, P (11) 375*a*. Process of making a glass fiber vessel having a clevis joint, P (5) 176*d*. Process for making and testing semiconductive devices, P (11) 378*i*. Refractory metal articles having oxidation-resistant coating, P (8) 275*i*. Structure and method for production of narrow doped region semiconductor devices, P (10) 346*d*.

United-Carr, Inc. Method of testing the porosity of coated articles, P (11) 381*a*.

United Ceramics, Ltd. Decorative bricks, tiles, or the like and methods of manufacturing the same, P (1) 11*h*.

United Glass, Ltd. Process for strengthening glass containers, P (9) 308*c*.

United Glassworks. See N. V. Vereenigde Glasfabrieken.

United Kingdom Atomic Energy Authority. Ceramic fuel materials, P (8) 279*a*. Electrical resistance furnaces, P (2) 72*g*. Fast nuclear reactor cooled by supercritical steam, P (2) 58*e*. Fuel element fabrication, P (4) 106*g*. Hot-pressing of metal powders having inert solid surface films by adding activator elements, P (2) 68*b*. Manufacture of nuclear fuel, P (10) 342*g*. Methods and apparatus for differential thermal analysis, P (4) 122*b*. Nuclear reactor fuel elements, P (2) 59*b*, P (5) 179*g*. P (6) 218*f*. Processes for producing fiber-reinforced materials, P (9) 309*c*. Welding thermocouples, P (5) 188*i*. X-ray source and measuring means for backscatter analysis of samples, P (9) 316*a*.

United Nuclear Corp. Production of uranium tetrafluoride, P (4) 107*f*.

United States of America. Temperature sensor probe, P (9) 316*a*.
United States of America, Administrator of the National Aeronautics and Space Administration. Alkali-metal silicate protective coating, P (4) 93*j*, P (10) 337*d*. Automatic fatigue test temperature programer, P (2) 71*i*. Electronic cathode having a brushlike structure and a relatively thick oxide emissive coating, P (4) 112*i*. Gd or Sm doped silicon semiconductor composition, P (2) 64*j*. Method of making electrical contact on silicon solar cell and resultant product, P (6) 222*h*. [Rocket] combustion chamber, P (11) 375*c*. Self-lubricating fluoride-metal composite materials, P (4) 94*f*. Thin window drifted silicon charged particle detector, P (5) 185*g*.
United States of America, Director of the National Science Foundation. Apparatus for acoustically detecting minute particles suspended in a gaseous atmosphere, P (6) 227*g*.
United States of America, Secretary of the Air Force. Ablative antenna window compositions, P (5) 178*i*. Ablative product and method for its manufacture, P (4) 105*j*. Apparatus for the continuous formation of filaments, P (1) 13*f*. Fiber-containing pyrolytic composite material, P (11) 374*i*. Hot-pressing zirconia method, P (1) 14*c*. Low ohmic semiconductor tuned narrow bandpass barrier photodiode, P (9) 312*f*. Metal surfaced with boron and coating of silicon, silicon carbide, or titanium nitride. P (7) 246*f*. Method and apparatus for manufacture of high strength and high modulus carbon filaments, P (1) 14*g*. Method and apparatus for the manufacture of pyrolytic fibers, P (4) 106*f*. Method of eliminating magnetocrystalline anisotropy effect on spin resonance of ferrimagnetic materials, P (2) 65*i*. Method of making metal or metalloid carbide yarn by decomposing the respective chloride in the presence of carbon yarn, P (6) 217*i*. Method of making [photovoltaic] solar cell, P (7) 257*g*. Method for the manufacture of pyrolytically coated filaments, P (5) 179*d*. Method for preparing electroluminescent light sources, P (11) 377*f*. Method of producing permanent magnets of rare earth metals containing Co or mixtures of Co, Fe, and Mn, P (5) 184*d*. Method for the pyrolytic deposition of silicon carbide, P (4) 107*e*. Particle size and distribution analysis using spatial filtering techniques, P (9) 315*j*. Process for implanting buried layers in semiconductor devices, P (11) 378*h*. Process for implanting grids in semiconductor devices, P (6) 223*i*. Process for metal finishing boron and tungsten filaments, P (4) 118*h*. Production of a cooling module for microelectronic circuits by cathodic sputtering, P (7) 257*i*. Solar cell panels from nonuniform dendrites, P (4) 117*a*. Transparent zirconia composition and process for making same, P (6) 218*h*. Vapor depositing infrasensitive antimony tritelluride, P (5) 185*i*. Wire coated with boron nitride and boron, P (9) 304*j*.
United States of America, Secretary of the Army. Ceramic [piezoelectric] memory device, P (9) 312*c*. Fast warmup cathode, P (6) 221*j*. Field-enhanced thermionic emitter, P (11) 376*g*. High temperature thermocouple, P (1) 22*c*. High voltage low temperature resistance device, P (4) 113*b*. Laboratory aerosol device, P (5) 188*g*. Method of forming magnetic ferrite films, P (2) 65*c*. Method of making a barium titanate body, P (6) 222*e*. Method of processing ferroelectric powders, P (10) 345*j*. Method for producing predetermined crystal structures, P (10) 347*a*. Method of treating alumina, P (1) 14*a*. Method of treating monolithic ceramic capacitors, P (5) 184*f*. Microwave power limiter comprising abutting semiconductor and ferrite elements, P (5) 184*i*. Nondispersive electrically variable microwave acoustic delay line comprising a ferrite Faraday rotator coupled to an anisotropic piezoelectric crystal, P (6) 223*b*. Plurality of ceramic spacers for separating planar grids, P (6) 223*f*. Reciprocal ferrite attenuator, P (4) 116*f*. Reciprocal microwave ferrite phase shifter, P (6) 223*a*. Solid state device with reduced leakage current at *np* junctions over which electrodes pass, P (5) 185*b*. Spectrophotometric apparatus for rapid analysis having deflection means to prevent vortex formation, P (4) 122*a*. Vapor deposition apparatus, P (9) 314*d*
United States of America, Secretary of the Interior. Apparatus for forming spherical pellets, P (6) 225*e*. Crystallization of tungsten disulfide from molten slags, P (1) 13*h*. Method and apparatus for growing large monocrystals of nonmetallics, P (8) 287*j*. Method of determining preferred orientation in metals, P (7) 261*a*. Process for fractionating lanthanide mixtures containing cerium, P (5) 191*f*.
United States of America, Secretary of the Navy. Alloys for improving properties of graphite, P (7) 252*b*. Apparatus for producing small holes, P (7) 248*j*. Beryllium doped germanium photoconductive detector, P (10) 344*b*. Brazing method, P (5) 178*c*. Ceramic plastic composite material for radomes, P (7) 252*f*. Field effect transistor in an integrated circuit having an embedded grid, P (6) 221*a*. Image intensifier comprising perforated glass substrate and method of making same, P (2) 65*b*. Instrument for measuring absolute reflectance and transmittance at cryogenic temperatures, P (1) 22*c*. Insulated-gate field-effect transistor using lead salt, P (2) 65*d*. Measuring thin film thickness using interferometric-capacitance technique, P (5) 183*i*. Method of connecting a fiber glass rodlike member to a metallic terminal, P (11) 377*h*. Method [fluid amalgam] for joining piezoelectric elements, P (9) 312*h*. Method of heat-treating thin magnetic films in a transverse magnetic field, P (2) 65*d*. Method of improving the bonding characteristics of glass surfaces, P (4) 100*a*. Method of improving the strength characteristics of glass reinforced laminates, P (2) 53*d*. Method for treating, working, and bonding refractory metals and alloys, P (4) 107*g*. Movable substrate method of vaporizing and depositing electrode material layers on the substrate, P (9) 313*h*. Organophosphorus coupling agents for epoxy to glass laminates, P (5) 176*b*. Welding core for tubes, P (4) 109*d*.
United States of America, U. S. Atomic Energy Commission. Apparatus for vacuum deposition on a negatively biased substrate, P (6) 220*h*. Controlled defect [fused quartz] coloration dosimeter, P (10) 344*e*. Detection, identification, and analysis of fissionable isotopes, P (10) 347*i*. Extraction of berkelium values in the tetravalent state using 2-thenoyltrifluoroacetone, P (2) 67*i*. Flame ionization detector, P (4) 121*g*. Glass fibers and treatment therefor, P (8) 277*b*. High loaded UO_2-niobium cermets, P (6) 217*a*. High speed temperature monitor, P (11) 381*e*. High temperature stress free thermocouple junction, P (7) 260*i*. Hot-isostatic-pressing apparatus, P (5) 186*g*. Ion exchange method for preparing metal oxide microspheres, P (7) 262*i*. Lithium drifted semiconductor radiation detector, P (4) 113*i*. Method of chlorinating metals with carbon tetrachloride and carbon dioxide, P (11) 382*c*. Method of dissolving aluminum-clad thoria target elements, P (2) 59*a*. Method of extracting soluble metal complexes using amine solvents, P (2) 68*b*. Method of fluorinating nuclear fuel with recovery of plutonium tetrafluoride and uranium hexafluoride, P (6) 217*g*. Method of making solid solution carbide-graphite compositions, P (4) 106*j*. Method of preparing a cermet nuclear fuel, P (2) 59*f*. Method of preparing a fuel material for use in a nuclear reactor, P (6) 218*b*. Method for preparing metal oxide microspheres, P (5) 179*e*. Method of preparing spherical uranium nitride particles having a porous interior, P (4) 106*j*. Method of processing nuclear fuel by selective ClF fluorination with separation of UF_6 and PuF_4, P (6) 218*c*. Method of separating berkelium from cerium, P (1) 24*a*. Method utilizing an electron beam for nondestructively measuring the dielectric properties of a sample, P (9) 315*i*. Metrology method for crystal defect detection, P (1) 22*g*. Multiremanence ferroelectric ceramic memory element, P (6) 222*j*. *P*-contact for compensated *p*-germanium crystal, P (11) 378*c*. Preparation of the carbonates of the rare earths, P (1) 24*d*. Process of making high loaded UO_2-niobium cermets, P (4) 107*b*. Process for preparing plutonia aquasols, P (11) 382*h*. Recovery of plutonium from refractory siliceous materials, P (4) 125*i*. Semiconductor detector having a lithium compensated shelf region between opposite conductivity type regions, P (4) 116*b*. Separation of ruthenium and plutonium by a lithium fluoride sorption technique, P (11) 383*a*. Thermoluminescent radiation dosimetric material, P (4) 117*e*. Zirconia-based thermoelectric compositions, P (9) 314*e*.
U. S. Automatics Corp. Semiconductor controlled switch circuit component. P (9) 313*i*.
United States Borax & Chemical Corp. Method and means for beneficiating ores, P (5) 191*c*. Method for producing boric oxide, P (4) 124*j*.
United States Ceramic Tile Co. Pregrouted ceramic tile assemblies, P (8) 280*d*.
United States Gypsum Co. Apparatus for producing cast gypsum articles, P (11) 368*e*. Calcined gypsum and a method for its preparation, P (4) 92*e*. Fire resistant plaster products, P (10) 336*b*.
U.S. Philips Corp. Dispenser cathode made of tungsten powder having a grain size <3 μm, P (11) 376*c*. Electroluminescent screen composition, P (9) 312*f*. Ferrimagnetic material for use at frequencies higher than 50 MHz having reduced loss factor and higher quality factor, P (11) 376*f*. Formation of coating on germanium bodies, P (8) 282*h*. Glow-discharge tubes containing a radioactive primer, P (11) 376*h*. High-voltage transistor with controlled base and collector doping and geometry, P (9) 312*b*. IGFET with interdigital source and drain and gate with limited overlap, P (9) 312*b*. Incandescent lamp having a filament surrounded by a wire screen, P (10) 345*a*. Integrated circuits using heavily doped surface region to prevent channels and methods for making, P (10) 345*c*. Method of manufacturing a magnetic head with a substantially bubble-free [glass] gap, P (10) 345*i*. Method of manufacturing semiconductor devices [printed circuits] and semiconductor devices manufactured by such methods, P (8) 283*e*. Method of manufacturing a target plate for use in a camera tube, P (10) 345*f*. Method of producing pure red lead monoxide, P (9) 317*g*. Method of treating objects of oxidic ceramic polycrystalline materials, P (11) 377*h*. *Pn* junction injection laser using a refractive index gradient to confine the laser beam, P (10) 345*e*. Projection lamp with a wire screen for blackening prevention, P (11) 378*j*. Radiation detectors having a semiconductor body, P (10) 345*i*. Semiconductor device with inversion layer, underneath an oxide coating, compensated by gold dopant, P (9) 313*j*. Semiconductor device for producing and amplifying electrical signals of very high frequencies, P (11) 378*d*. Ultrasonic welding method and apparatus, P (10) 340*b*.
United States Pipe & Foundry Co. Centrifugal casting method, P (10) 342*b*.
United States Radium Corp. Self-luminous light-emitting units, P (2) 66*c*.
United States Steel Corp. Apparatus and method for measuring temperatures, P (5) 188*e*. Blast furnace stock line wall and method of constructing the same, P (4) 106*a*. Metal vaporization crucible with upstanding walls for confining and condensing vapor, P (4) 106*e*. Method of enameling steel, P (7) 246*g*. Oil well cement and method of making the same, P (4) 93*a*. Refractory composition and method of making refractory shapes, P (4) 107*g*.
United States Stoneware, Inc. Ball mill drum [design], P (10) 346*h*. Method and apparatus for comminution, P (5) 186*c*. Vibratory mill and its operation, P (6) 225*e*.
United Steel Co., Ltd. Nozzle and stopper assemblies for teeming liquid metals, P (4) 107*i*.
Unitrode Corp. High-voltage planar semiconductor devices, P (11) 376*i*.
Universal Oil Products Co. Crystalline zeolite, P (6) 229*f*. High surface area alumina and catalyst composite, P (4) 124*b*. Inertial type pneumatic separator, P (2) 68*b*. Manufacture of spheroidal silica-alumina particles, P (7) 262*j*. Semicatalytic infrared heat producing unit, P (2) 72*g*.
Universal Rundle Corp. Method and means for casting syphon-jet type toilet bowls, P (11) 376*a*.
Univis, Inc. Method for processing of ophthalmic lens, P (6) 213*e*.
Uno, R. Electrical conduction of NiO at high temperature, (1) 28*j*.
Unoki, Hiromi, and Sakudo, Tunetaro. Electron spin resonance of Fe^{3+} in $SrTiO_3$ with special reference to the 110°K phase transition, (1) 29*a*.
Uoda, Hidetaka. See Osaka, Matajiro.
Upadhyaya, V. G., Mulfinger, H. O., and Dietzel, A. Effect of gases on enameling of cast iron and determination of gases developed during enameling, (5) 171*g*.
Upor, E., and Nagy, G. Separation of traces of elements by precipitation (IV) separation through the carbonates—its use in determining trace contaminants in uranium compounds, (10) 347*e*.
Upton, L. O. Method for treating molten glass with a laser beam, P (4) 100*b*.
Urban, C. See Bentz, G.
Urban, W. Direct determination of the parameters for Gd^{3+} in YVO_4 and YPO_4 from variable-frequency EPR, (8) 290*j*. See Kahle, H. G.
Ure, R. W., Jr. See McAvoy, B. R.
Urnes, S. Studies of the sodium distribution in sodium silicate glasses by the chemical difference method, (8) 276*j*.
Ursu, G. Rapid methods for determining sulfur in molybdenite concentrates, minerals, etc., (1) 21*j*.
Urusov, V. S. Chemical bonding in silica and the silicates. (4) 128*j*.
Usami, Katsuhisa. See Kato, Norio.
Ushakov, D. F. See Zorina, M. L.
Ushakovskii, V. T. See Kashkurov, K. F.
Ushii, Eiichi; Kato, Shuzo; Sano, Shiro; and Iga, Takeo. Sintering of magnesium oxide (I) calcination of magnesium carbonate and magnesite containing ZnO. (4) 154*c*.
Ushio, Masun. See Noda, Tokiti.
Uskov, I. A. See Uskova, E. T.
Uskova, E. T., Emel'yanov, V. B., and Uskov, I. A. Acidity nature of palygorskite clays, (5) 191*h*.
Usner, L. See Jangg, G.
Ust'yantsev, V. M., Sudakova, L. P., and Bessonov, A. F. X-ray study of systems CuO-SiO_2 and Cu_2O-SiO_2, (7) 270*g*.
Usvitskii, M. B. Automatic temperature control in glass lehrs, (6) 208*g*.
Utley, R. W. See Smith, S. V.
Utsu, Shigetoshi. See Nameishi, Naoyuki.
Uytterhoeven, J. B. See Fripiat, J. J.
Uzuki, Takao. See Nishino, Tadashi.
Vacz, I., and Kerenyi, I. Electronic (initial current) measurement of the cathode temperature, (6) 226*f*.

Vagh, A. S. See Joshi, M. S.
Vahldiek, F. W. Growth and microstructure of molybdenum oxide crystals, (9) 322*g*. High pressure electrical resistance, compressive strength, and nonstoichiometry of titanium dioxide, (5) 194*j*. Translucent ZrO_2 prepared at high pressures, (4) 162*d*. See Robinson, L. B.
Vahldiek, F. W., and Lynch, C. T. Cyclic high-pressure hot-pressing of oxides, P (2) 58*a*.
Vahldiek, F. W., and Mersol, S. A. (editors). Anisotropy in Single-Crystal Compounds (Vols. 1, 2), B (7) 270*i*.
Vaidya, M. D. See Bhide, G. K.
Vainshtein, A. L. See Oblival'nyi, F. A.
Vakhrameev, V. I., Lesnikov, A. K., and Evstrop'ev, K. S. Increasing the heat resistance of glasses by treatment in alkaline solutions, (6) 209*e*.
Val, C. See Dogu, A.
Valdes, L. B. See Dixon, A. F.
Valentine, C. K. See Pfeiler, W. A.
Valenziano, F. P. Pipe joint, P (6) 214*e*.
Valigi, M. See O'Keeffe, M.
Valignat, N., and Bonnier, E. Computer calculation applied to exchange equilibria between condensed and gas phases, (1) 26*i*.
Val'kovskaya, M. I. See Boyarskaya, Yu. S.
Valla, O., Grjotheim, K., and Muan, A. Solid-liquid equilibria in the system CaO-"FeO"-MnO in contact with metallic iron, (6) 237*g*.
Valletta, R. M., and Pliskin, W. A. Preparation and characterization of manganese oxide thin films (4) 111*c*.
Valley, R. B., and Morse, T. H. Particle length measuring apparatus, P (7) 261*a*.
Vallier, G. See Caillet, M.
Value Engineering Co. Method of etching refractory metal based materials uniformly along a surface, P (4) 106*h*.
Van Alstine, R. E. See Lipman, P. W.
Van Arkel, A. E. Compound and solution characteristics in vitreous phases, B (4) 168*j*.
Van Atta, L. B. See Picus, G. S.
Van Atta, L. B., Picus, G. S., and Yariv, A. Evidence for superradiance in the recombination radiation from CdTe, (1) 29*c*.
Van Bladel, R. See Laudelout, H.
Van Caulweiaert, F. See Leonard, A. J.
Vance, N. J. Metal silicate coating utilizing electrostatic field, P (7) 256*i*.
Vancil, D. O., and Harrison, M. C. Beneficiation of cryolite material, P (10) 349*a*.
Van Craeynest, J. C., and Weilbacher, J. C. Thermal conductivity study of the mixed oxides of uranium and plutonium, (8) 300*c*.
Vand, V. See Johnson, G. G., Jr.
Van den Boomgaard, J. System Cr-SiC, (9) 331*b*.
Van Den Steen, A. J., Vanlaer, M., and Joly, F. H. E. Manufacture of molybdenum trioxide, P (2) 74*b*.
Van Der Beck, R. R. Refractory properties of a Florida kyanite-sillimanite concentrate, (8) 279*c*.
Van der Elsken, J. See Bonn, R.
Van der Giessen, A. A. Chemical and physical properties of iron(III) oxide hydrate, (9) 318*b*.
VanderHart, D. L., Gutowsky, H. S., and Farrer, T. C. NMR study of $BaFPO_3$—^{31}P and ^{19}F chemical-shift anisotropies and the absolute sign of the F-P coupling constant, (10) 357*g*.
Vanderheiden, D. B., Dumler, J. T., Allen, D. R., and Allen, A. S. Electrolytic preparation of pure basic aluminum fluorides, (1) 23*f*.
Van der Heijden, C. W. M. See Lieth, R. M. A.
Van der Hoeven, B. J. C., Jr., and Keesom, P. H. Low-temperature specific heat and density of states of boronated graphite, (4) 143*c*.
Van der Maesen, F. See Diemer, G.
Van der Plas, L. Zeolites, (6) 229*a*.
Van der Veen, A. H. Quantitative analysis of the available alumina content (by DTA) in bauxite from "Onverdacht" Surinam, (6) 227*e*.
Van Der Walt, C. M. See Sole, M. J.
Van Der Walt, C. M., and Louw, H. N. J. Precipitates in arc-melted thoria, (1) 35*d*.
Van Der Walt, C. M., and Sole, M. J. Plastic behavior of crystals with the NaCl-structure, (1) 34*g*.
Van der Ziel, J. P. Davydov splitting of the ^2E lines in antiferromagnetic Cr_2O_3, (4) 130*g*. Magnon sidebands and local order in Co-doped MnF_2, (1) 32*i*.
Van der Ziel, J. P., Merritt, F. R., and Van Uitert, L. G. Paramagnetic resonance of Cr^{3+} in $EuAlO_3$, (11) 386*b*.
Van de Weijer, M. H. A. See T'Jampens, G. R.
Vandor, M. Rheological examination of ceramic casting slips, (8) 280*c*.
Van Drunen, C. J. See Levitan, J.
Van Dyke, B. See Arnold, A. J.
Van Dyke, D. See Arnold, A. J.
Van Gelder, W. See Schmidt, P. F.
Van Hove, R., and Luryckx, A. Photoconductivity decay of ZnO crystals in oxygen, (4) 149*f*.
Van Laar, K. See Booster, P.
Vanlaer, M. See Van Den Steen, A. J.
Van Landuyt, J., Hatwell, H., and Amelinckx, S. Domain structure of β-In_2S_3 "single crystals" due to the ordering of indium vacancies, (7) 265*g*.
Van Langen, J. O. M., and Bastiaanssen, J. W. Method of manufacturing a magnetic head with a substantially bubble-free [glass] gap, P (10) 345*i*.
Van Leemput, H. See Witkin, D. E.
Van Loan, P. R. Study of polytypism in silicon carbide, (4) 157*b*.
Vannerberg, N. G. See Hedvall, J. A.
Van Nordstrand, R. A. Production of alumina from dawsonite, P (11) 382*j*.
Vannotti, L. E. See Brailsford, J. R.
Van Pul, B. Methods for making semiconductor structures having glass insulated islands, P (10) 345*a*. See Fordemwalt, J. N.
Van Rooyen, T. H. See De Villiers, J. M.
Van Rouendal Smit, J. Recovery of cesium and nitrous oxide from fission product solutions containing ammonium nitrate, P (4) 125*g*.
Van Ruyven, L. J. Method of bonding two different materials by electromagnetic radiation, P (5) 183*a*.
Van Ruyven, L. J., and Chase, J. D. Time-dependent electrical conduction in rutile single crystals, (2) 84*a*.
Van Sickler, R. H., and Dagley, J. F. Method of assembling lamp filament and support structure, P (2) 53*b*.
Van Someren, L. O. Method of preparing a single crystal for improved electron emission, P (6) 222*f*.
Van Stapele, R. P. See Lotgering, F. K.
Van Stratum, A. J. A., Zalm, P., Verest, F. J., and Henkes, H. Dispenser cathode made of tungsten powder having a grain size <3 μm, P (11) 376*c*.
Van Tassel, J. H. See Clark, J. H.; Ramsey, T. H., Jr.
Vantini, N. See Donati, E.
Van Tkhien, N. See Ved, E. I.
Van Tuyl, T. O. Suspension insulator having a cap with internal load transmitting surfaces, P (8) 280*e*.
Van Uitert, L. G. See Ballman, A. A.; Bonner, W. A.; Geusic, J. E.; Johnson, L. F.; Rubin, J. J.; Smith, Richard G.; van der Ziel, J. P.
Van Uitert, L. G., Dearborn, E. F., and Grodkiewicz, W. H. Quenching interactions involving the first excited states of Gd, Yb, Er, Tm, and Ho in sodium rare-earth tungstates, (10) 359*e*.
Van Uitert, L. G., Dearborn, E. F., and Rubin, J. J. Mechanisms of energy transfer involving trivalent Er and Tb or Tm in sodium rare-earth tungstates; Tb and Nd in sodium rare-earth tungstates, (4) 144*a*.
Van Uitert, L. G., Rubin, J. J., Grodkiewicz, W. H., and Bonner, W. A. Some characteristics of Ba,Sr,Na niobates, (10) 360*c*.
Van Velzen, H. C. See Burggraaf, A. J.
Van Vijfeijken, A. G. Theory of vortices in type II superconductors, (9) 331*b*.
Van Vlack, L. H. See Riewald, P. G.; Smith, D. E.
Van Vorous, T. See Baum, G. A.
Vargin, V. V. Technology of Enamels, B (4) 168*i*.
Varian Associates. Ceramic-to-metal seal and method of making same, P (4) 93*e*. Flame ionization detector, P (1) 22*b*. Heterojunction semiconductor devices employing carrier multiplication in a high gap ratio emitter-base heterojunction, P (4) 113*i*. Ridged dielectric window with titanium suboxide solely on ridges, P (7) 249*e*.
Varick, L. See Carpenter, W. E.
Varlamova, L. S. See Pankova, N. A.
Varma, C. K. R. Evidence of nucleation in diamond growth, (2) 77*c*. Studies on the structure of natural diamond crystals of the cube form, (1) 38*c*. Trigons on diamond, (1) 40*c*.
Varnakov, S. V. See Ivanovskii, G. F.
Vart, P. Brick chimney for brick kiln, P (1) 23*a*.
Varta Petrix-Union G.m.b.H. Process of producing ramsdellit, a type of manganese dioxide, P (5) 191*g*.
Varuzhanyan, A. A. See Oganesyan, R. B.
Vasil'eva, N. V. See Krokhina, A. I.
Vasil'kova, L. V. See Shchukarev, S. A.
Vasilos, T., and Spriggs, R. M. Pressure sintering of ceramics, B (7) 272*h*.
Vassamillet, L. F., and Caldwell, V. E. Electron-probe microanalysis of alkali metals in glasses, (11) 369*j*.
Vassell, W. C. See Lambe, J. J.
Vassilevsky, A. N. Lightweight high-strength cement compositions, P (9) 304*c*.
Vassiliev, A., Nicolas, J., and Hildebrandt, M. Garnet compositions, P (4) 113*h*.
Vaszko, B. See Wood, G. C.
Vatman, A. P., Kobliyatskii, V. G., Petrichenko, A. M., Tuluzov, G. N., and Khrestin, V. A. Apparatus for measurement of thermal fatigue of solids in a liquid metal, (2) 68*e*.
Vaughan, D. E. W. See Barrer, R. M.
Vaughan, R. W., and Drickamer, H. G. High-pressure Moessbauer studies on α-Fe_2O_3, $FeTiO_3$, and FeO, (4) 138*a*.
Vaughan, T. B., and Whitehouse, R. Electrostatic spraying of vitreous enamels, (1) 4*i*.
Vaupel, H. See Hennicke, H. W.
Vavilonova, V. T. See Boikova, A. I.
Vavrina, K. See Balcar, O.
Vdovin, V. M. See Fogarasi, G.
Veatch, F. See Alford, H. E.
VEB Carl Zeiss Jena. Radiation source for reducing specimen contamination in electron microscopes, P (4) 122*d*.
VEB Lokomotivbau-Elektrotechnische Werke "Hans Beimler." Lanthanum hexaboride cathode system for an electron beam generator, P (7) 256*g*.
VEB Schaumglaswerk Taubenbach. Process for making foam glass, P (2) 54*b*. Process for manufacturing glass in fine granular form, P (2) 54*c*.
Ved, E. I., and Van Tkhien, N. Influence of inorganic salts and their combinations on the kinetics of hardening of portland cement, (2) 44*e*.
Ved, E. I., Zharov, E. F., Litvinova, Z. S., and Bludov, B. F. Study of the hardening of MgO-Al_2O_3-H_2O, MgO-SiO_2-H_2O, and Al_2O_3-SiO_2-H_2O systems under hydrothermal conditions, (2) 58*e*.
Vedam, K. See Knausenberger, W. H.; Schmidt, E. D. D.
Vedam, K., and Davis, T. A. Piezo- and thermooptic behavior of $LiNbO_3$, (1) 34*f*.
Vedam, K., and Schmidt, E. D. D. Nonlinear piezo-optic behavior of sphalerite (α-ZnS), (4) 146*g*.
Vedder, W. See Breiter, M. W.
Vedin, B. A. See Edqvist, O.
Veen, A. W. I., and Wiersma, J. Low-angle X-ray diffraction maximum due to textural periodicity in heated gibbsite, (8) 294*h*.
Veevers, K. Recrystallization of machined surfaces of beryllium oxide, (10) 342*a*. See Rotsey, W. B.
Veilex, R. Semiconductor device for producing and amplifying electrical signals of very high frequencies, P (11) 378*d*.
Veiser, I., and Szabo, A. Determining the thermochemical resistance of refractories to the effect of slags, (10) 340*g*.
Veiser, I., Szabo, A., Moldovan, T., and Alexinschi, T. Manufacture of silica insulating refractories, (1) 12*a*.
Veiser, I., Szabo, A., and Petri, L. Studies on the possibilities of improving the quality of teeming ladle refractory brick, (10) 342*i*.
Veitscher Magnesitwerke-Akt.-Ges. Method of molding shaped refractory bodies having an attached spacer of nonmetallic sheet material, P (2) 59*d*.
Vektaris, B., Gumulyauskas, A., and Nenorta, A. (Editorial Board). Research on Silicate Concretes—Collected Papers, B (4) 168*e*.
Velde, B., and Kornprobst, J. Stability of hydrated aluminum silicates, (9) 329*j*.
Venables, J. D. Nature of precipitates in boron-doped TiC, (1) 33*g*.
Venables, J. D., Kann, D., and Lye, R. G. Structure of the ordered compound V_6C_5, (4) 156*j*.
Venard, J. T., and Spruiell, J. E. Phase relations in the thorium-uranium-nitrogen ternary system at 1000°C, (9) 327*f*.
Vene, N. See Blinc, R.
Venevtsev, Yu. N. See Shapiro, Z. I.
Venghiattis, A. New method for the atomization of solid samples for atomic absorption spectroscopy, (2) 70*i*.
Veniale, F. See Taramasso, M.
Venkateswarlu, P. See Rao, K. V. S.
Venzel, L. I. Glass-crystalline enamel based on lithium metasilicate, (6) 207*i*.
Veprek, O. See Truhlarova, M.
Veprek, S., and Arend, H. Reduction of $BaTiO_3$ in nonisothermal hydrogen plasma, (7) 255*a*.
Verderber, R. R., Simmons, J. G., and Eales, B. Forming process in evaporated SiO thin films, (1) 30*c*.
Verduin, F. C. See Farrington, G. M.
Vere, A. W. Mechanical twinning and crack nucleation in lithium niobate, (9) 324*b*.
Vereinigte Glaswerke Zweigniederlassung der Compagnie de Saint-Gobain. Binders for sheet glass, P (5) 174*j*.
Vereinigte Kesselwerke Akt.-Ges. Ball mill, P (10) 346*g*.
Verenkova, E. M., Trofimov, M. G., Frolov, A. S., and Shakhtakhtinskii, T. I. Heat-resistant insulating ceramic materials and coatings, B (5) 204*g*.
Veres, F. Crystalline luminescent ceramic materials, P (11) 371*d*. Method of forming a glass body of devitrifiable glass and devitrifying the same, P (11) 371*f*.
Vereshchagin, L. F. See Bendeliani, N. A.
Vereshchagin, L. F., Kalashnikov, Ya. A., and Nikol'skaya, I. V. Carbon formation in the $CaCO_3$-SiO_2 system at high pressures and temperatures, (4) 127*e*.
Verest, F. J. See van Stratum, A. J. A.
Vergnon, P. See Juillet, F.
Vernagen, J. G. See Essers, W. G.
Verhine, C. J. See Lewis, J. M.
Verleur, H. W. See Barker, A. S., Jr.; Boyle, W. S.
Verlijsdonk, J. G. See Wanmaker, W. L.
Verlotskii, A. A. See Galdina, N. M.
Verma, J. K. D. See Nayar, P. S.
Verma, O. P. Role of industrial minerals in the economic development of Rajasthan, (4) 123*j*.
Verma, R. L. See Bhide, G. K.
Vermilyea, D. A. See Bubar, S. F.
Ver Planck, W. E. Quartzite in California, (2) 73*e*.

Verrando, M. G., and Kelchner, J. R. Swing mounted thermocouple assembly, P (11) 381*b*.
Verrerie Souchon-Neuvesel, Soc. Anon. Method and apparatus for measuring the thickness of an insulating layer by variation of the dielectric of a condenser using a contacting electrode, P (5) 183*i*.
Vertes, P. See Delange, M.
Vertsner, V. N. See Zhdanov, G. S.
Vertsner, V. N., and Shchetnev, Yu. F. Use of slow electrons in transmission electron microscopy, (2) 71*d*.
Veselov, P. A. See Krivtsov, V. A.
Vesterasjoe, E. See Roest, E.
Vesuvius Crucible Co. Composite sleeve for ladle stopper rods, P (10) 342*c*. Ladle stopper head assembly, P (11) 375*b*.
Vetere, J. J. See Richards, E. A.
Vian-Ortuno, A., and Diez-Vilches, A. Method of producing oxide and hydroxide of zinc, P (10) 349*d*.
Vicat, J. See Aleonard, S.
Vicat, J., and Aleonard, S. Borates, $MeMe'(BO_3)_2$, with the dolomite structure, (7) 263*j*.
Victoria, R. O. See Iles, P. A.
Victory Engineering Corp. Low noise thermistor assembly and method, P (9) 312*e*.
Vidal, J. P., Broquet, C., and Robin, G. Application of radioactive tracers in the use of refractories, (2) 54*h*.
Vidavskii, L. M., Reshetov, K. V., Koval'chuk, V. Yu., and Kovba, L. M. Quantitative X-ray phase analysis of mixtures of α-UO_2 with an amorphous modification of UO_3, (4) 151*h*.
Viechnicki, D., and Schmid, F. Investigation of the eutectic point in the system Al_2O_3-$Y_3Al_5O_{12}$, (10) 356*a*.
Viehmann, W. Current oscillations in photo-excited gallium-arsenide, (9) 310*f*. See Mahootian, N.
Viernickel, K. Barium titanate compositions containing cerium and bismuth, P (8) 282*c*.
Vierow, W. F. Powder on wire capacitor, P (5) 184*h*.
Vijh, A. K. Electrochemical oxidation of semiconducting ceramic barium titanate, (6) 220*g*.
Vijh, A. K., and Alwitt, R. S. Convenient method for sealing metallic wires into glass tubing, (10) 337*g*.
Vilches, O. E., and Wheatley, J. C. Measurements of the specific heats of three magnetic salts at low temperatures, (2) 80*j*.
Vil'k, Yu. N., Ordan'yan, S. S., Avarbe, R. G., Avgustinik, A. I., Ryzhkova, T. P., and Omel'chenko, Yu. A. Phase diagram of the Zr-ZrC system, (7) 267*i*.
Villaume, H. F., and Collins, D. S. Cryogenic refrigeration for crystal X-ray diffraction studies, P (4) 121*f*.
Villwock, R. Geological field methods for the exploration and opening of raw material deposits for the clay, glass, and ceramic industries, (5) 190*e*.
Vilnat, J. See Pagano, M.
Vinal, A. W. Method for processing ferrite cores, P (5) 184*b*.
Vincent, C. A. See Purdie, N.
Vincent, G. L. Glass-ceramic coatings expand into commercial field, (2) 45*i*.
Vincent, J. S. See Fessler, T. E.
Vincent, R. T. Bottle gaging apparatus, P (2) 52*b*.
Vinetskii, V. L., and Eritsyan, G. N. Self-compensation of conductivity in silica, (7) 268*a*.
Vingas, G. J. See Zrimsek, A. H.
Vinnik, M. A., Agranovskaya, A. I., and Semenova, N. N. X-ray and microstructural study of the phase relations during the formation of the barium-cobalt hexagonal ferrite $BaCo_2Fe_{16}O_{27}$, (9) 333*a*.
Vinogradov, A. P. Geochemical problems in the evolution of the ocean, (8) 292*d*.
Vinz, O. Glass in electronics, (5) 172*f*.
Vinzelberg, B., and Bunge, K. Radiation sensitive ampoule testing apparatus and method, P (4) 101*b*.
Viscakas, J., Gaidelis, V., and Pocius, Z. Effect of electric field on the space charge density of ZnO electrophotographic layers, (5) 180*i*.
Viscrian, I., and Georgescu, V. Contributions to the study of tin oxide films, (8) 280*h*.
Vishnevskii, I. I., and Skripak, V. N. Temperature and concentration dependence of thermal conductivity of solid solutions of MgO-$MgCr_2O_4$ and Al_2O_3-Cr_2O_3, (6) 238*h*.
Vislocky, N. Laser structure with laser element inserted concentrically within cylindrical light pump tube, P (9) 312*d*.
Visser, B. F. Method and device for determining the oxygen and carbonic acid content in a gas mixture, P (1) 22*f*.
Visser, R. See Booster, P.
Vissers, D. R., and Steindler, M. J. Removal of tellurium hexafluoride from gaseous systems by solid reagents, (4) 153*c*.
Viswanathan, C. R., and Ogura, Seiki. Effect of heating under bias on photoelectric threshold in MOS structure, (2) 76*b*.
Viswanathan, S. See Aravamuthan, V.
Vita Zahnfabrik H. Rauter K. G. Artificial tooth, P (8) 280*e*.
Vitkus, P. L. Process of epitaxial growth of silicon carbide, P (11) 378*h*.
Vitman, F. F., Volovets, L. D., Ivanov, M. I., and Pugachev, G. S. Influence of loading time on the impact resistance of high-strength sheet glass, (2) 49*e*.
Vitro Corp. of America. Sulfidation corrosion-resistant coating containing rare-earth metal aluminides, P (9) 304*j*.
Vitter, G. See Caillet, M.; Duclot, M.
Vitzthum, D. See Hoffmann, H.
Vivante, C. Coated fuel particles for high-temperature reactors, (4) 103*j*.
Vlasov, V. A. See Krogius, E. A.
Vlasse, M. See Kershaw, R.
Vobornik, K. Solarization of soda-potash crystal glass by sunshine and its stabilization, (8) 276*g*.
Vodar, B. See Bocquillon, G.
Vodicka, V. Method of manufacturing electroluminescent display devices, P (11) 377*e*.
Vodoklys, F. M. Discharge lamp incorporating phosphor which is normally sensitive to lehring and method, P (6) 221*h*.
Vodoklys, F. M., and Ropp, R. C. Antimony activated halophosphate phosphor with rare earth additive, P (6) 220*h*.
Voelker, U., and Gerloff, G. Sintered friction material, P (7) 253*c*.
Voeller, H. See Buettner, K.
Voelling, A. See Juza, R.
Vogel, A. C. See Belfield, R. E.; Pall, D. B.
Vogel, F. L., Jr. Silicon nitride coating on semiconductor and method, P (5) 185*j*.
Vogel, R. W. Form grinding ceramic materials, (8) 284*d*.
Vogler, S. See Nelson, P. A.
Voigt, A. F. See Wechter, M. A.
Voisinet, W. E. Impregnation of asbestos-cement products with thermosetting formaldehyde resin, P (4) 92*i*.
Vojnovich, T., and McGee, T. D. Determination of donor gradients within surface barriers formed on dense Gd-doped barium titanates, (9) 310*g*.
Volf, M. B. Viscosity of the Czechoslovak technical glasses, (1) 9*j*.
Volk, H. F., and Mercuri, R. A. Iridium coated graphite, P (8) 279*d*.
Volkova, N. M. See Alyamovskii, S. I.
Volkovskaya, A. I. See Sazhin, V. S.
Vollhardt, F. Waste heat boilers for continuously operating glass tanks, (6) 211*i*.
Volovets, L. D. See Vitman, F. F.
Von Bichowsky, F. Process for converting alkali metal titanates into their pure titanium dioxide pseudomorphs, P (5) 191*e*.
Von Bock, G. Ceramic artists and their work—Kurt Derckum, (1) 2*a*.
Von Der Decken, C. B. See Huehndorf-Richter, B.
Von Doenhoff, C. See Wilson, B. S., Jr.
Von Dreusche, C. F., Jr. High temperature multiple hearth furnace structures, P (4) 123*b*.
Von Eckermann, H. Mineral from Norra Karr, Addendum, (8) 295*g*. New contributions to the interpretation of the genesis of the Norra Karr alkaline body in southern Sweden, (4) 146*a*.
Von Fragstein, P. See Steinhauser, O.
Von Gutfeld, R. J., and Nethercot, A. H., Jr. Temperature dependence of heat-pulse propagation in sapphire, (2) 84*c*.
Von Heidenstam, O., Johansson, A., and Westman, S. Redetermination of the distribution of atoms in Cu_5Zn_8, Cu_5Cd_8, and Cu_9Al_4, (8) 297*h*.
Von Kahler, U., Wohlleben, K., and Konopicky, K. Possible use of a portable X-ray fluorescence apparatus, (11) 380*b*.
Von Knorring, O. See Saari, E.
Von Saldern, A. "Breathing spells" in the history of glass, (9) 303*g*.
Von Tress, W. R., and Enos, J. H. Method for making porous structures, P (7) 252*f*.
Vook, F. L. Anisotropic thermal conductivity of electron-irradiated CdS, (7) 263*i*.
Vook, R. W. See Witt, F.
Voroshilov, Yu. V. See Kuz'ma, Yu. B.
Vos, G. See Toussaint, C. J.
Voskoboinikov, G. I. See Bartenev, G. M.
Voskresenskaya, N. K. Analytical study of the law of Kablukov, (8) 288*h*. See Berul, S. I.; Budova, G. P.; Krivovyazov, E. L.
Voskull, J. Flow studies on water models for kilns and dryers, (4) 119*g*.
Voss, B. See Irmler, H.
Voss, W. G. Method and material for making joints between refractory panels, P (6) 218*a*.
Vossen, J. L., and O'Neill, J. J., Jr. Rf sputtering processes, (4) 153*e*.
Vozzella, P. A., Miller, A. D., and DeCrescente, M. A. Dissociation behavior of uranium monocarbide, (8) 290*f*.
Vrabel, M. J., and Atwater, H. A. EPR observation of the Eu^{3+} to Eu^{2+} transformation in CdF_2:Eu, (2) 77*a*.
Vranka, L., and Dojiva, C. Is it possible to make mining for brickworks more effective? (7) 250*a*.
Vratny, F. Cathodic sputtering from a cathodically biased target electrode having an rf potential superimposed on the cathodic bias, P (11) 376*h*. Deposition of tantalum and tantalum oxide by superimposed rf and dc sputtering, (4) 131*e*. Electrostatic control of electron movement in cathode sputtering, P (4) 112*j*. See Burgiel, J. C.
V.R.B. Associates, Inc. Lightweight high-strength cement compositions, P (9) 304*c*.
Vredevoe, L. A. Low-temperature electric dipole vibronic transitions in rock-salt- and zinc-blende-type structures, (1) 31*j*.
Vromans, P. H. G. M. See Kwestroo, W.
Vrzalova, D. See Budesinsky, B.
Vsesvyatskaya, L. M. See Antonova, E. A.
Vural, B. See Robinson, B. B.
Vural, B., and Thomas, E. E. Helicon-spin wave interaction in the magnetic semiconductor $Ag_xCd_{1-x}Cr_2Se_4$, (1) 30*f*.
Vyas, B. R. See Kulkarni, A. K.
Vyse, J. See Clements, J. F.
Vyzkumny Ustav Matematickych Stroju. Apparatus for automatically measuring the reverse recovery transient of a semiconductor diode, P (11) 376*f*.

Waasdorp, A. See Booster, P.
Wabash Smelting, Inc. Ladle and cover, P (1) 14*d*.
Wachtman, J. B., Jr. (editor). Mechanical and Thermal Properties of Ceramics—Proceedings of a Symposium Held at Gaithersburg, Md., April 1968, B (11) 389*h*.
Wachtman, J. B., Jr., and Franklin, A. D. (editors). Mass Transport in Oxides—Proceedings of a Symposium Held at Gaithersburg, Md., October 1967, B (5) 204*a*.
Wacker-Chemie G.m.b.H. Water repellent masonry articles, P (10) 336*d*.
Wada, Akiyoshi. See Tsuboi, Masamichi.
Wada, Harue. See Yamaguchi, Shigeto.
Wada, Koji. Study of hydroxyl groups in kaolin minerals utilizing selective deuteration and infrared spectroscopy, (7) 269*e*.
Wada, Masamichi. See Takagi, Kiyoshi.
Wada, Masanobu. See Hariu, Takashi.
Waddington, J. S. Conditions affecting the mechanism of fracture at high temperatures, (2) 75*e*.
Waddington, T. C. Free-electron molecular-orbital calculations for inorganic systems (II) tetrahedral, square, octahedral, trigonal prismatic, hexagonal, cubic, Archimedean antiprismatic, and icosahedral free-electron networks, (4) 136*d*.
Wade, R. C. See Genzabella, C. F.
Wade, W. H. See Barto, J.
Wade, W. L., Jr. See Skudera, W. J., Jr.
Wadhwa, S. S. Recent trends in auger designs for clay extrusion, (4) 102*f*.
Wadia, W., and Balloomal, L. S. Interpretation of the vibrational spectra of fused silica, (4) 140*i*.
Wadlin, W. H. See Harrison, W. W.
Wadsley, A. D. See Reid, A. F.
Wadsoe, I. Design and testing of a micro reaction calorimeter, (4) 119*i*.
Wadsten, T. Synthesis of a pyrite-type modification of SiP_2, (4) 158*e*.
Wagendristel, A. See Ebel, H.
Waggener, H. A. Process for preparation of stabilized metal film resistors, P (10) 345*g*.
Waghorne, R. H. See Landrum, T. C.
Wagner, B. C. Method of forming metal boride coating on wire, P (6) 208*a*.
Wagner, C. Diffusion processes during the uptake of excess calcium by calcium fluoride, (10) 352*i*. See Douglass, D. L.
Wagner, C. N. J. See Light, T. B.
Wagner, E., and Pralow, W. E. L. Noble metal alloy adapted to receive porcelain cladding, artificial dental constructions, and method of preparing the same, P (4) 109*b*.
Wagner, G. See Mueller, A.
Wagner, H. See Knotik, K.
Wagner, J., and Zinko, H. Microelastic behavior during scratching of glass and Plexiglas, (6) 210*e*.
Wagner, J. B., Jr. See Eror, N. G.; George, T. D.; Swaroop, B.
Wagner, J. W., and Willardson, R. K. Growth and characterization of single crystals of PbTe-SnTe, (2) 77*d*. Growth of $Pb_{1-x}Sn_xTe$ single crystals from nonstoichiometric melts, (9) 322*i*.
Wagner, K. A. Practical testing of grinding wheels, (7) 243*g*.
Wagner, R. S., and Doherty, C. J. Mechanism of branching and kinking during VLS crystal growth, (4) 143*h*.
Wagner Electric Corp. Lamp lead wire terminal, P (5) 175*c*. Mechanically based rear loading panel lamp, P (1) 11*b*. Method for gettering completed gas filled lamps and the product resulting therefrom, P (7) 249*e*. Tungsten filament iodine cycle incandescent lamp with alkali metal getter, P (4) 117*b*.
Wagstaff, F. E. Metastability of high cristobalite in vitreous silica, (8) 295*b*. See Richards, K. J.
Wahl, H. See Muatacchi, C.; Schlosshauer, H.
Wahlbeck, P. G. See Gilles, P. W.
Wahlin, L. See Chernow, F.
Wahlstrom, E. E. Optical Crystallography, B (10) 365*b*.
Waidelich, W. See Peisl, H.
Waits, R. K. Thin-film resistors, P (11) 379*a*.
Wajda, E. S. See Kontrimas, R.; Krohl, R. J.
Wakabayashi, Akira. Vacuum degassing process for steel and refractories used, (7) 252*a*.
Wakamatsu, Mitsuru, and Terada, Kiyoshi. Fundamental studies on ceramic tunnel kilns (I) studies on the flow patterns of gases in ceramic tunnel kilns by model techniques, (4) 122*g*.

Wakamatsu, Nobuyuki. See Wakatsuki, Masao.
Wakamiya, Kinji. Method of making a semiconductor junction by diffusion, P (8) 283*b*.
Wakatsuki, Masao. See Inuzuka, Hideo.
Wakatsuki, Masao; Aoki, Toshio; and Hayashi, Hiroaki. Method of making synthetic diamond crystals, P (8) 273*g*.
Wakatsuki, Masao; Aoki, Toshio; Takasu, Shinichiro; and Wakamatsu, Nobuyuki. Method of making synthetic diamond crystals, P (8) 273*g*.
Wakatsuki, Masao; Aoki, Toshio; and Wakamatsu, Nobuyuki. Method of converting carbonaceous material to diamond, P (10) 335*f*.
Wakatsuki, Masao; Aoki, Toshio; Wakamatsu, Nobuyuki; and Takasu, Shinichiro. Method for preparing diamond crystals, P (7) 243*h*.
Wakefield, G. F. Method of preparing a silicon carbide whisker reinforced silicon composite material, P (11) 375*d*.
Wakefield, G. F. See Bracken, R. C.
Wakim, F. G. Hydrogen and deuterium in $SrTiO_3$ single crystals, (9) 322*h*. See Addiss, R. R., Jr.
Walbridge, L. H. Ignition and flame monitoring control apparatus for fuel burners, P (2) 72*e*.
Wald, F. See Bates, H. E.
Wald, F., and Stormont, R. W. Constitution of the pseudobinary section lead telluride-iron, (1) 26*a*.
Waldbaum, D. R. See Klein, C., Jr.; Robie, R. A.; Thompson, J. B., Jr.
Waldow, P. See Jackson, D. M., Jr.
Waligora, Ch. See Schultze, D.
Walker, B. E., Jr., Ewing, C. T., and Miller, R. R. Nondestructive testing for void content in glass-filament-wound composites, (10) 338*c*.
Walker, B. F., Johnson, V. A., Hahn, W. C., Jr., and Wood, J. D. Study of the effects of ultrasonics on diffusion, (4) 157*f*.
Walker, D. G. See Hickman, B. S.
Walker, D. G., and Hickman, B. S. X-ray studies of radiation damage in beryllium oxide dispersion fuels, (4) 164*g*.
Walker, E. G. See Holdridge, D. A.
Walker, E. J. See Fang, F. F.
Walker, J., and Westwood, G. W. Process for the production of foundry cores and molds, P (6) 218*c*.
Walker, L. C. See Sinke, G. C.
Walker, M. J. See Ainscough, J. B.
Walker, P. L., Jr. (editor). Chemistry and Physics of Carbon (Vols. 1, 2), B (5) 203*i*; (Vol. 3), B (6) 240*g*.
Walker, W. C. See Roberts, R. A.; Roessler, D. M.
Wallace, C. A. See Isherwood, B. J.
Wallace, G. C., and Keller, L. D. Filtration process with scraping and blowback cake removal, P (2) 74*a*.
Wallace, M. W. Tunnel cathode in matrix form with integral storage feature, P (8) 284*b*.
Wallace, P. R. Configuration of interstitial atoms in irradiated graphite, (4) 129*c*.
Wallace, R. W. See Reardon, D. E.
Wallace, T. C. See Giorgi, A. L.
Wallace, W. E. See Mader, K. H.
Wallace, W. E., and Mader, K. H. Magnetic and crystallographic characteristics of praseodymium hydrides, (2) 79*h*.
Wallace-Murray Corp. Abrasive tool, P (5) 169*f*.
Walley, P. A. Electrical conduction in amorphous silicon and germanium, (8) 281*f*.
Wallis, G. See Pomerantz, D. I.
Wallis, R. F. See Maradudin, A. A.
Wallis, R. F., and Maradudin, A. A. Theory of surface effects on the thermal diffuse scattering of X rays or electrons from crystal lattices, (2) 84*e*.
Wallmark, J. T. See Boesenberg, W. A.
Walls, R. See Keen, I. M.
Wallwork, G. R. See Sheasby, J. S.
Walpole, A. O. Molten material furnace hole closures, P (1) 14*b*.
Walsh, D. See Stevens, K. W. H.
Walsh, E. N. Cleaning compositions and method of using the same, P (4) 164*j*.
Walsh, J. M., III. Compact radiation detector with superimposed filter, phosphor, glass, and photosensitive layers, P (5) 182*a*.
Walsh, J. N. See Hall, A.
Walsh, T. Gravity separation of particulate material, P (7) 262*h*. See Douglas, E.
Walsh, W. M., Jr., Remeika, J. P., and Rupp, L. W., Jr. Conduction-electron spin resonance in degenerate indium sesquioxide, (4) 129*b*.
Walter, H. P., Scheve, J., and Rienacker, G. Magnetic studies on aluminum oxide-chromium oxide catalysts, (6) 234*f*.
Walter, H. P., Schulz, I., and Scheve, J. Magnetic studies on $CuCr_2O_4$ catalysts, (6) 234*h*.
Walter, L. S., and Giutronich, J. E. Vapor fractionation of silicate melts at high temperatures and atmospheric pressures, (5) 202*f*.
Walters, R. R. See Westrum, E. F., Jr.
Walters, S. S. Stretch your capabilities, (10) 335*i*.
Walther, C. K. Abrasive article, P (10) 335*g*.
Waltke, R. W. [Tapered hollow] dowels for fireable ceramic dies and method for their use, P (10) 343*g*.
Walton, C. F. What is cast iron today? (8) 275*g*.
Waltz, A. R. Automatic classifying device [semiconductors], P (9) 312*b*.
Wambach, A., Trachte, K., and DiBenedetto, A. Fracture properties of glass filled polyphenylene oxide composites, (2) 49*g*.
Wampler, D. M. See Leflet, H. A., Jr.
Wampler, D. M., and Leflet, H. A., Jr. Apparatus for bending glass sheets, P (6) 212*b*.
Wang, C. C., Gottlieb, G. E., Cullen, G. W., McFarlane, S. H., III, and Zaininger, K. H. Heteroepitaxy of silicon on stoichiometric spinel, (10) 354*e*.
Wang, C. C., and McFarlane, S. H., III. Growth and characterization of large stoichiometric magnesium aluminate spinel single crystals, (10) 354*i*.
Wang, P., Pink, F., and Sciola, J. Propagation of growth striae in GaAs epitaxial films, (4) 151*d*.
Wang, R., and Yerouchalmi, D. Fluid fuel burner, P (5) 189*c*.
Wang, S., and Chang, C. C. Coherent fluorescence from zinc sulfide excited by two-photon absorption, (2) 75*c*.
Wang, Wen-Chung. See White, D. L.
Wang, Wen-Chung, and Das, P. Focusing of a laser beam by an active CdS oscillator, (2) 77*f*.
Wanie, W. Colored bodies, engobes, and glazes (I,II), (4) 108*d*. Firing in reducing atmosphere, (4) 101*i*. Pinholes in glazes, (6) 219*b*.
Wanie, W. E. Dryers and kilns for the manufacture of hard-fired brick, (5) 188*j*.
Wanklyn, B. M. Vapor growth of single crystals of WO_3 and MoO_3, (8) 300*e*. See Garton, G.; Hill, G. J.; Leask, M. J. M.; Shore, R. G.
Wanklyn, J. N. See Harrop, P. J.
Wanlass, F. M., and Shultz, R. M. Method of making a phosphorus-protected semiconductor device, P (7) 257*g*.
Wanmaker, W. L. See Blasse, G.; Bril, A.
Wanmaker, W. L., and Bril, A. Fluoro-substituted europium activated gadolinium, yttrium, and lanthanum oxides, P (4) 113*e*.
Wanmaker, W. L., Bril, A., and Verlijsdonk, J. G. X-ray converter having terbium activated lanthanum compound phosphor, P (1) 19*h*.
Wanmaker, W. L., Hoekstra, A. H., and Ouweltjes, J. L. Solubility of Sb(III) in chlorapatite, (10) 360*a*.
Wanmaker, W. L., and ter Vrugt, J. W. Luminescence of calcium orthophosphates activated by divalent europium, (10) 356*c*.
Wanmaker, W. L., and Verlijsdonk, J. G. Europium activated yttrium and gadolinium vanadate-phosphate and vanadate-arsenate phosphors, P (4) 112*j*. Terbium or terbium and gadolinium activated mixed alkaline earth alkali metal borate luminescent substance, P (5) 185*f*.
Warble, C. E. See Moodie, A. F.
Warburton, J. B. See Antill, J. E.
Ward, J. M., and Squire, G. L. Sodium carbonate treatment of high silica fiber products, P (10) 340*b*.
Ward, T. J. Effect of clay cation exchange on foundry sand characteristics, (10) 341*a*.
Ward, W. T. See Cantor, S.
Wardale, H. W. See Brivati, J. A.
Ware, D. A. See Griscom, D. L.
Wargo, J. Tough windshield glass breaks into blunt shards, (5) 173*j*.
Wariyar, N. S. See Iyer, K. P. D.
Warmkessel, B. M., and Kevane, C. J. Platinum contamination and reduction of cerium oxide, (1) 34*h*.
Warner, A. W., Coquin, G. A., Meitzler, A. H., and Fink, J. L. Piezoelectric properties of $Ba_2NaNb_5O_{15}$, (7) 255*i*.
Warner, A. W., Jr. See Onoe, Morio.
Warner, J. Photomultiplier detection of 10.6 μm radiation using optical up-conversion in proustite, (2) 81*h*.
Warner, J. S. Free energy of formation of palladium oxide, (4) 136*f*.
Warner, R. M., Jr. Compound channel insulated gate triode, P (7) 256*b*.
Warren, G., and Staples, B. G. Method and apparatus for repairing glass-coated articles, P (7) 246*f*.
Warren, J. W., Jr. Anisotropic [pyrolytic graphite] mold liner for continuous casting of metals, P (5) 178*j*.
Warren, R. Carbide grain growth during the liquid-phase sintering of the alloys NbC-Fe, NbC-Ni, and NbC-Co, (10) 350*j*. Interaction between liquid platinum and some transition metal carbides, (5) 195*d*. Microstructural development during the liquid-phase sintering of two-phase alloys, with special reference to the NbC-Co system, (8) 295*d*.
Warrington, D. H. See Moriya, Y.
Warshaw, S., Loveland, W., and Denchick, F. A. Marble sorter selectively rejectable of misshapen marbles and fragments thereof, P (4) 99*b*.
Warter, P. J., Jr. See Tabak, M. D.
Washburn, J. See Cass, T. R.
Wasko, J. H. See Zemon, S.
Wassell, L. L. See Scott, K. T.
Wasser, R. E. Method of making molded ceramic articles [pressure sintering], P (7) 257*g*.
Wasyluk, R. Passive electric network, P (1) 18*h*.
Watanabe, Akinori. See Takeda, Takeshi.
Watanabe, D., Terasaki, O., Jostsons, A., and Castles, J. R. Ordered structure of $TiO_{1.25}$, (2) 81*h*.
Watanabe, Hideo. Brick for LD converter, (10) 340*f*.
Watanabe, Hideo, and Masuda, Satoru. Studies conducted at Hirohata plant to improve quality and shape of ladle brick and mode of lining ladle to reduce quantity of ladle brick required to produce a ton of steel, (11) 374*i*.
Watanabe, Hiroshi. See Takeda, Takayoshi; Yamamoto, Hisao.
Watanabe, Hiroshi; Yamauchi, Hiroshi; Ohashi, Masayoshi; Sugimoto, Mitsuo; Okada, Takuya; and Fukase, Masahiro. Neutron diffraction study of $CaFe_2O_4$, (8) 295*j*.
Watanabe, K. See Ohtsuki, T.
Watanabe, Shiro. See Horibe, Toshiyasu.
Watanabe, Takahide. See Suzuki, Takashi.
Watanabe, Takashi. Study of clay minerals [*e.g.* allophane, halloysite, and kaolinite] by small-angle X-ray scattering, (8) 298*h*.
Watanabe, Yoshio, and Yoshida, Masayuki. Measurement of the distribution of phosphorus diffused in silicon dioxide film using ^{32}P as a tracer, (8) 294*g*.
Water, P. L. See Bowling, K. McG.
Waterfield, C. G., Linford, R. G., Goalby, B. B., Bates, T. R., Elyard, C. A., and Staveley, L. A. K. Thermodynamic investigation of disorder in the hydrates of sodium carbonate, (9) 332*h*.
Waterfield, C. G., and Staveley, L. A. K. Thermodynamic investigation of disorder in the hydrates of disodium hydrogen phosphate, (5) 201*c*.
Waters, A. See Blake, W. E.
Waters, J. See Grimes, N. W.
Waterworth, T. H. See Gell, P. A. M.
Watkins, D. A. M., and Parsons, D. S. Novel all-glass circulating system, (11) 370*a*.
Watkins, J. See Allam, D. S.
Watson, A. I. See Parke, S.
Watson, D. See Stoev, S. M.
Watson, D. D. See Brown, L. H.
Watson, G. R., and Matchen, B. High temperature [electric] tunnel kiln for production of crystalline refractory and abrasive materials, P (6) 228*f*.
Watson, J. D., Sr. See Olstowski, F.
Watson, J. F. Selective deposition of semiconductor materials, P (2) 66*b*.
Watt, J. D., and Thorne, D. J. Composition and pozzolanic properties of pulverized fuel ashes, (2) 43*i*.
Watt, W. See Johnson, W.
Watts, C. H., and Horton, R. A. Ceramic shell molds and methods of production, P (4) 106*b*.
Watts, C. R., and Sabel, A. H. Tension test method for high-modulus, high-strength filaments, (11) 381*a*.
Watts, J. F. See English, J.
Watts, R. K. Host crystal effects on the electron paramagnetic resonance of Er^{3+} and Yb^{3+} in II-VI compounds, (4) 138*i*.
Waugh, A. Process for manufacture of porous abrasive articles, P (4) 90*a*.
Waugh, J. A. See Marzocchi, A.
Waugh, T. C. See Tien, Pei-Lin.
Wawner, F. E., Jr. Method of making high strength refractory filaments, P (8) 279*h*.
Waxman, A., and Zaininger, K. H. Al_2O_3-silicon insulated-gate field-effect transistors, (1) 25*c*.
Waymouth, J. F. Electric discharge lamp with the starting resistor impedance twice that of the lamp impedance, P (8) 282*e*. Process for removing alkali contamination from electric lamps, P (5) 176*d*. See Gungle, W. C.; Koury, F.
Waymouth, J. F., and Koury, F. Arc tubes and process for their fabrication, P (5) 182*f*.
Weagley, R. J. See Carnall, E., Jr.
Weaver, C. See Macfarlane, J. C.
Weaver, C. W., and Paterson, M. S. Deformation of cube-oriented MgO crystals under pressure, (8) 290*i*.
Weaver, E. A. High silica content glasses, P (11) 371*j*. Vapor phase growth of ZnO single crystals, (6) 239*d*.
Weaver, E. A., and Li, C. T. Growth of complex oxide single crystals from fluoride melts, (8) 292*e*.
Weaver, E. A., Merchant, H. D., and Poplawsky, R. P. Growth of Fe-Ni oxide spinel single crystals by arc image techniques, (6) 220*h*.
Weaver, E. P. Refractory shapes coated with organic material, P (10) 343*b*.
Webb, J. E. Bonding graphite with fused silver chloride, P (10) 342*b*. Bonding thermoelectric elements to nonmagnetic refractory metal electrodes, P (9) 312*b*. Catalyst for growth of boron carbide crystal whiskers, P (5) 178*d*. Depositing semiconductor films utilizing a thermal gradient, P (5) 182*b*. Extended area semiconductor radiation detectors and a novel readout arrangement, P (4) 113*a*. Inorganic thermal control pigment, P (6) 208*b*. Method of making membranes, P (5) 179*b*. Method for processing ferrite cores, P (5) 184*b*. Method for producing a solar cell having an integral protective covering, P (7) 257*b*. Segmenting lead telluride-silicon germanium thermoelements, P (10) 345*j*. Semiconductor *pn* junction stress and strain sensor, P (6) 223*i*. Tensile strength testing device, P (11) 381*c*.

Webb, J. M. See Mellen, E. J., Jr.
Webb, W. M. See Ault, C. H.
Webber, H. M., and Wilson, A. L. Absorptiometric determination of silicon in water (VII) improved method for determining the total silicon content of high-purity water, (7) 259*g*. Determination of sodium in high purity water with sodium-responsive glass electrodes, (9) 315*c*.
Weber, E. H., Jr. See Troemel, C. P.
Weber, J. See Weinstein, A. B.
Weber, J. B. See Weed, S. B.
Weber, J. N., and Schmalz, R. F. Factors affecting carbon and oxygen isotopic composition of marine carbonate sediments (III) Eniwetok Atoll, (6) 229*a*.
Weber, P., Ritzmann, H., and Mollenkopf, H. Method of and apparatus for making porous clay, P (2) 54*e*.
Weber, T. Composite powders and apparatus for the production of the same, P (6) 208*a*.
Webster, A. H. See Weston, T. B.
Webster, A. V., and Dinsdale, A. Calcining and grinding of bone, (10) 348*f*.
Webster, L. P. See Worcester, L. E.
Webster, R. K., Jones, T. L., and Anderson, P. J. Proton magnetic resonance studies of adsorbed water on magnesium oxide, (1) 35*a*.
Wechter, M. A., Shanks, H. R., and Voigt, A. F. Relations between lattice parameter and x value for some cubic tungsten bronzes, (11) 387*c*.
Wedding, B. See Klein, M. V.
Wedell, H. Washing and rinsing agents for machine washing, (1) 15*g*.
Wedepohl, K. H. See Savelli, G.
Wedepohl, P. T. See Comins, J. D.
Wedgwood, F. A. See Fender, B. E. F.
Wedin, J. A. Method for manufacturing glass fiber reinforced resin impregnated mats, P (2) 53*g*.
Wedler, G., and Wissmann, P. X-ray diffraction study of the structure of vapor deposited nickel films on quartz glass, (8) 281*j*.
Weed, S. B., and Weber, J. B. Effect of adsorbent charge on the competitive adsorption of divalent organic cations by layer-silicate minerals, (8) 290*j*.
Weed, S. E. Composite sleeve for ladle stopper rods, P (10) 342*c*.
Weedy, R. C. How air pollution can be controlled in a plant, (4) 117*f*.
Weeks, R. A. See Abraham, M. M.; Chen, Y.
Weeks, R. A., and Bray, P. J. Electron spin resonance spectra of gamma-ray-irradiated phosphate glasses and compounds—oxygen vacancies, (1) 7*a*.
Wegdam, G. H. See Bonn, R.
Wegener, E. See Schneider, E.
Wegener, H. A. R. See Sewell, F. A., Jr.
Wegner, E. Advances in the development of acid and alkali resistant enamels for chemical industry apparatus, (5) 171*a*.
Wehmeier, F. H., Laudise, R. A., and Shiever, J. W. System Ag_2S-As_2S_3 and the growth of crystals of proustite, smithite, and pyrargyrite, (2) 83*i*.
Wehner, G. O. See Curtze, E. W.
Wehren, P. H. A. Apparatus for filling valve bags with pulverous material, P (8) 284*e*.
Weidmann, W. See Zirngibl, H.
Weidner, A. See Moertl, G.
Weigel, R. V. Lamp bridge making method and apparatus, P (5) 175*c*.
Weightman, H. L. See Darling, A. H.
Weiher, J. See Greenbaum, M. A.
Weiher, J. F. See Sleight, A. W.
Weiher, R. L. Optical properties of free electrons in ZnO, (4) 147*b*.
Weil, C. G. See Brill, O. L.
Weiland, W. Review of the development of ceramic production in India, (6) 206*b*.
Weilbacher, J. C. See van Craeynest, J. C.
Weimar, P. See Bumm, H.
Weinberg, F. J., Howden, D., and Cleaver, D. Process for producing metal oxide particles of reduced particle size, P (6) 230*d*.
Weinberg, H. P. Method of etching refractory metal based materials uniformly along a surface, P (4) 106*h*.
Weininger, J. L. See Garfinkel, M.
Weinmann, K. See Glueck, R.
Weinreich, O. A., and Ribner, A. Optical and electrical properties of SiC films prepared in a microwave discharge, (5) 181*j*.
Weinryb, E. See Hazart, J. P.
Weinstein, A. B., Erdman, S., and Weber, J. Cast porcelain prosthesis and method of making the same, P (1) 15*j*.
Weinstein, H. Adjustable variable voltage responsive two-terminal semiconductor switch device, P (8) 282*a*. Electrically insulating-heat conductive mass for semiconductor wafers, P (11) 376*c*. Pinch-off shunt for controlled rectifiers, P (10) 345*e*. Semiconductor wafer having low field junction surface, P (7) 258*f*.
Weinstein, M. See Bates, H. E.; Hemmat, N.
Weinstein, M., Bates, H. E., and Epstein, J. Segmenting lead telluride-silicon germanium thermoelements, P (10) 345*j*.
Weinstein, M., and Sherwin, E. J. Bonding thermoelectric elements to nonmagnetic refractory metal electrodes, P (9) 312*b*.
Weir, C. E., Piermarini, G. J., and Block, S. Crystallography of some high-pressure forms of C_6H_6, CS_2, Br_2, CCl_4, and KNO_3, (11) 383*d*.
Weis, J. H. Process for making aluminum-containing ferrites, P (4) 115*j*.
Weisberg, H. See Desmond, T. J.
Weisberg, L. R., and Fischer, A. G. Method for preparing electroluminescent light sources, P (11) 377*f*.
Weise, C. H. See Copeland, L. E.
Weiser, K. See Keyes, R. W.
Weisgerber, P. See Fiegna, A.
Weiss, A. See Heller, L.
Weiss, A., and Lagaly, G. Simple method for the estimation of the layer charge in swelling mica-like layer silicates, (4) 154*i*.
Weiss, H. Radiation sensor utilizing semiconductor body having photoelectromagnetic effect, P (2) 66*j*.
Weiss, M. P. See Ali, S. A.
Weiss, V. See Burke, J. J.
Weisshaar, E., and Spickenreuther, D. Semiconductor rectifier structure having semiconductor element assembly screwed into place on support base, P (10) 346*d*.
Weissmantel, C. See Hecht, G.
Weitzel, H. See Dachs, H.
Welch, B. J. See Anthony, R. G.
Welch, B. J., and Snow, R. J. Repeatability of the anode effect in cryolite-alumina melts, (2) 82*c*.
Weldes, H. H., Boyle, F. A., and Bobb, J. S. S. Continuous process for making silica sols, P (7) 262*g*.
Weldes, H. H., and Netting, D. I. Expanded silica insulation material, P (4) 106*j*.
Welding Engineers, Inc. Slurry feeder, P (11) 379*h*.
Welford, W. T. See Rowe, S. H.
Welker, R. H. See Ferguson, C. W.; Grosskopf, J. W., Jr.
Weller, C. W. Method for alignment of microcircuit devices on substrate, P (11) 377*g*.
Weller, P. F. Optical spectra of ytterbium in CdF_2, (4) 147*c*.
Wellmann, B. See Hahn, H.
Wells, J. E. See Meyer, D. E.
Wells, J. S. See Matarrese, L. M.
Wells, L. M. See McAtee, J. L., Jr.
Wells, M. R. See Cashion, J. D.
Wells, O. C. Irradiation effect in thermally grown SiO_2, (9) 323*i*.
Wells, P. E., and Davis, J. S. Information storage devices, P (7) 256*c*.
Wells, S. T. See Ashpole, R. S.
Welty, J. M. Junction capacitor, P (10) 345*d*.
Wemple, S. H. See DiDomenico, M., Jr.; Kahng, D.
Wemple, S. H., DiDomenico, M., Jr., and Camlibel, I. Dielectric and optical properties of melt-grown $BaTiO_3$, (10) 352*b*. Relation between linear and quadratic electrooptic coefficients in $LiNbO_3$, $LiTaO_3$, and other oxygen-octahedra ferroelectrics based on direct measurement of spontaneous polarization, (2) 82*a*.
Wenckus, J. F. See Haggerty, J. S.
Wendler, L. Calculation of glazes, (1) 15*c*. Influence of drying degree on the dry strength of porcelain bodies, (2) 60*e*.
Wenk, H. R. Annealing of oligoclase at high pressure, (10) 350*a*.
Wentorf, R. H., Jr. Behavior of some carbonaceous materials at very high pressures and high temperatures, (1) 25*a*.
Wentworth, S. A. See Thompson, T. D.
Werner, A. J. Titanium dioxide pigment coated with silica and alumina, P (7) 263*d*.
Werner, T. See Greaves, M. J.
Werner, Th. (compiler). Natural Gas Firing in Glass Melting Furnaces, B (11) 389*j*.
Wernick, J. H. See Schmidt, R.
Werno, M., and Najder, J. Measurements of the volume change zone in a clay layer in situ, (5) 190*f*.
Wertheim, G. K. See Wickman, H. H.
Wesche, K. Influence of the pore volume of hardened cement paste on the resistance of concrete exposed to seawater, (1) 3*a*.
Wesel, J. R., and Olds, L. E. Heating apparatus and process, P (5) 189*c*.
Wesel, P. E. See Reese, R. C.; Tomb, W. H.
Wesel, P. E., and Zine, A. R., Jr. Method for cutting glass tubing, P (2) 53*c*.
Wesemeyer, H. H. K. Semiconductor bidirectional component, P (7) 258*b*.
Wesolowski, W. E. See Hazdra, J. J.
West, H. W. H. American Brick Industry, B (6) 240*e*. Future of brick—1968, (9) 308*g*. Performance of walls built of wire-cut bricks with and without perforations (I) basis of experimentation, (6) 214*g*.
West, H. W. H., and Hodgkinson, H. R. Performance of walls built of wire-cut bricks with and without perforations (III) tests of rain penetration, (6) 214*a*.
West, H. W. H., Hodgkinson, H. R., Beech, D. G., and Davenport, S. T. E. Performance of walls built of wire-cut bricks with and without perforations (II) strength tests, (6) 214*g*.
West, I. M. See Curry, D.
West, R. R., Czapliński, W. J., Frankson, R. W., Schultz, D. C., Sevick, D. J., and Smith, S. T. Characteristics of clays related to dry strength, (5) 179*h*.
West, T. S. See Fleet, B.
West, W. See Saunders, V. I.
West Midlands Gas Board and Johnson Brothers (Hanley), Ltd. Continuous [fast fire] pottery kiln with slidable stretchers, P (10) 348*c*.
Westbrook, J. H. See Hanneman, R. E.
Westbrook, J. H., and Jorgensen, P. J. Effects of water desorption on indentation microhardness anisotropy in minerals, (8) 285*a*.
Westerman, A. See Hancock, J.
Western Electric Co., Inc. Apparatus for helixing a path in a carbon film deposited on a ceramic core, P (2) 64*f*. Apparatus for helixing and sorting filmed resistors, P (8) 282*b*. Apparatus for making slab cuts in resistor films, P (4) 112*c*. Apparatus for polishing, P (7) 255*f*. Bonding leads to quartz crystals, P (11) 376*g*. Integrated circuit containing multilayer tantalum compounds, P (2) 65*e*. Metallization of selected regions of surfaces and products so formed, P (4) 114*d*. Method for fabricating double-diffused semiconductive devices, P (8) 282*g*. Methods and apparatus for separating articles initially in a compact array, and composite assemblies so formed, P (9) 313*e*. Methods and apparatus for treating semiconductive materials with gases, P (5) 184*h*. Methods of manufacturing thin film components, P (1) 18*f*.
Westerveld, W. See Janssens, H. H.
Westfalia Dinnendahl Groppel Akt.-Ges. Apparatus for drying and preheating of pulverulent material, particularly raw cement material, P (5) 170*c*.
Westgate, C. R. See Apel, J. R.
Westinghouse Electric Corp. Activation of phosphor films, P (11) 376*e*. Antimony activated halophosphate phosphor with rare earth additive, P (6) 220*h*. Apparatus for epitaxially producing a layer on a substrate, P (11) 376*g*. Apparatus and process for forming or molding magnetic substances, P (9) 312*a*. Apparatus for sealing off glass vessels, P (6) 212*h*. Attachment of leads to semiconductors, P (1) 17*i*. Attachment of leads to semiconductor devices, P (4) 112*d*. Cast electrical bushing, P (6) 220*i*. Ceramic arc tube and closure member construction, P (5) 182*i*. Ceramic discharge lamp, P (11) 376*i*. Compression bonded semiconductor device, P (4) 112*a*. Constant gain power transistor, P (11) 376*b*. Controllable flow pump, P (11) 374*g*. Discharge lamp incorporating phosphor which is normally sensitive to lehring and method, P (6) 221*h*. Efficient preparation of rare-earth metal oxalate, P (5) 190*i*. Fabrication of semiconductor integrated circuits, P (4) 113*a*. Fabrication of structures for semiconductor integrated circuits, P (5) 182*j*. Field-effect semiconductor devices of the junction type and method of making, P (9) 312*j*. Formation of heterojunction devices by epitaxial growth from solution, P (9) 312*j*. Glass-to-metal seals and method for making same, P (2) 52*i*. Heterojunction solar cell with shorted substrate, P (10) 345*a*. High concentration doping of silicon using ammonium phosphate, P (4) 113*j*. High-pressure electric discharge lamp having magnetically actuable arc ignition means, and apparatus for starting such a lamp, P (9) 312*b*. High-pressure metallic vapor discharge lamp including mercury and thallium iodide, P (6) 221*f*. High-speed semiconductor switch, P (1) 18*h*. High temperature magnetic cores and process for producing the same, P (4) 113*a*. Incandescent lamp with a refractory metal carbide filament, P (2) 65*b*. Insulated-gate field-effect transistor structure with reduced current leakage, P (7) 256*d*. Integrated complementary MOS-type transistor structure and method of making same, P (7) 256*e*, P (8) 282*a*. Integrated complementary transistor structure with equivalent performance characteristics, P (5) 183*f*. Lamp monogram and monogram ink, P (8) 277*d*. Manufacture of semiconductor solar cells, P (11) 377*d*. Metal vapor discharge lamp, P (9) 312*g*. Method of activation of phosphor, P (6) 222*a*. Method of fabricating an integrated circuit structure including unipolar transistor and bipolar transistor portions, P (2) 65*b*. Method of fabricating a semiconductor by diffusion, P (7) 257*c*. Method [flame spray] of coating with glass, P (10) 337*b*. Method [float glass] and apparatus for the manufacture of glass envelopes, P (11) 371*f*. Method of making complementary transistor structure, P (4) 115*a*. Method for making ferrite magnets, P (4) 115*b*. Method of making phosphor raw-mix materials and phosphors, P (9) 313*a*. Method for preparing europium activated yttrium oxide and gadolinium oxide phosphors, P (9) 313*c*. Method for producing tantalum carbide and tantalum-alloy carbide filaments, P (4) 107*b*. Method of rare-earth metal recovery from orthovanadate compound, P (5) 191*d*. Method of removing carbon from mixtures of tungsten powder and thoria and insuring a uniform dispersion of thoria, P (9) 317*g*. Mosaic of semiconductor elements interconnected in an XY matrix, P (9) 313*g*. MOS field-effect transistor Hall effect devices, P (9) 313*g*. Polychromatic luminescent devices and method of manufacture, P (11) 378*e*. Preparation of electroluminescent phosphors, P (4) 115*g*. Process for diffusing gold into semiconductor material, P (7) 257*h*. Process for manufacturing an electrolumines-

cent device, P (4) 116*a*. Process for producing thermoelectric elements, P (1) 19*d*. Rare earth activated strontium lithium germanate phosphors, P (5) 185*f*. Refractory-oxide incandescent lamp, P (9) 313*e*. Refractory-oxide incandescent lamp with preheater, P (4) 116*g*. Scandium-containing alkaline earth phosphate phosphor having good temperature-dependence characteristics, P (4) 116*i*. Sealed-beam type electric lamp with noncircular lens component, P (4) 101*d*. Sealing means for refractory ceramic discharge device envelopes [Al_2O_3], P (9) 313*g*. Semiconductor device contact structure, P (4) 116*c*. Semiconductor devices [MOS] with a region having portions of differing depth and concentration, P (9) 314*a*. Semiconductor integrated circuits with improved isolation, P (11) 378*e*. Semiconductor integrated circuits and method of making the same, P (5) 185*i*. Semiconductor structure particularly for performing unipolar transistor functions in integrated circuits, P (4) 116*i*. Semiconductor structures for integrated circuitry and method of making the same, P (7) 258*j*. Solid lubricant composites, P (5) 191*f*. Strontium and barium substituted lanthanum phosphate phosphors, P (5) 185*c*. Terbium activated calcium and magnesium germanate phosphors, P (9) 314*a*. Wide bandwidth millimeter maser, P (7) 258*d*.

Westman, S. See von Heidenstam, O.

Weston, D. Simultaneous flotation of silica phosphates and carbonate minerals, P (6) 230*c*. Slow magnetic drum ore separator control device, P (6) 230*d*.

Weston, T. B., Webster, A. H., and McNamara, V. M. Lead zirconate-lead titanate piezoelectric ceramics with iron oxide additions, (7) 255*c*.

Weston Instruments, Inc. Method of forming films of compounds having at least two anions by cathode sputtering, P (4) 114*f*. Photoconductive cell having high stability and dark resistance, P (8) 283*g*.

Westrum, E. F., Jr. High temperature adiabatic calorimetry, B (4) 165*b*. See Lyon, W. G.

Westrum, E. F., Jr., Walters, R. R., Flotow, H. E., and Osborne, D. W. Uranium monosulfide. Ferromagnetic transition. Heat capacity and thermodynamic properties from 1.5° to 350°K, (2) 84*d*.

Westwood, A. R. C., Goldheim, D. L., and Lye, R. G. Further observations on Rebinder effects in MgO, (4) 136*j*.

Westwood, G. W. See Walker, J.

Westwood, W. D. See Lewis, D. C.

Weth, G. G. See Luthill, E. J.

Weyl, W. A. Effect of disorder on some properties of solids, (1) 6*a*. Effects of anharmonicity of thermal vibrations on properties of crystals and glasses, B (4) 168*i*.

Whalley, E. See Kuriakose, A. K.

Whateley, T. L. See Evans, J. V.

Wheatley, J. C. See Vilches, O. E.

Wheeler, B. R. See Jones, K. A.

Wheeler, J. See Edmeades, R. M.

Wheeler, M. J. See Hazelden, D. W. J.

Wheeler, V. J. See Dell, R. M.; Markin, T. L.

Wheeler, W. C. See McRae, T. F.

Wheildon, W. M., Jr. See Ault, N. N.

Whelan, M. J. See Booker, G. R.

Whidden, C. J., Williams, C. D., and Tipsword, R. F. Pressure and temperature dependence of the nuclear quadrupole frequency of ^{23}Na in $NaBrO_3$, (10) 359*a*.

Whigham, D. M. See Amsterdam, M. F.

Whilems, C. J. Optical windows for lasers, P (5) 176*b*.

Whiscombe, J. B. See Rigden, S. A. R.

Whistler, L. Some engraved glasses by David Peace, (4) 90*i*.

Whitaker, H. L. See Narken, B.

White, A. E. S., and Norcott, A. Preliminary comparison of oxidation aging and electrical aging of sintered silicon carbide heater elements, (2) 57*a*.

White, D. See Sansom, K. G.

White, D. E., and Beals, R. J. Dry-pressing of a urania pycnometer, (1) 12*a*.

White, D. L., and Wang, Wen-Chung. Active CdS ultrasonic oscillator, (4) 126*d*.

White, E. A. D. See Cloete, F. L. D.; Wood, J. D. C.

White, E. W. See Baun, W. L.; Knausenberger, W. H.

White, E. W., and Gibbs, G. V. Structural and chemical effects on the Al$K\beta$ X-ray emission band among aluminum containing silicates and aluminum oxides, (11) 387*g*. Structural and chemical effects on the Si$K\beta$ X-ray line for silicates, (4) 156*d*.

White, G. D., and Handwerk, J. H. Method of preparing a fuel material for use in a nuclear reactor, P (6) 218*b*.

White, G. K., and Birch, J. A. Thermal properties of silica at low temperatures—correction, (4) 160*i*.

White, H. G. See Logan, R. A.

White, J. See Dutta, S. K.; Willshee, J. C.

White, J. F. See Bittel, J. T.

White, J. G., Yocom, P. N., and Lerner, S. Structure determination and crystal preparation of monoclinic rare-earth sesquisulfides, (11) 387*h*.

White, M. H. See Cricchi, J. R.

White, M. S. See Solomons, C.

White, R. See McLaughlin, R.

White, R. L. See Lefever, R. A.; Phillips, T. G.

White, R. M. See Lee, R. E.

White, R. W. See Chiotti, P.

White, S. Decorated diffusion paths in quartz, (9) 319*d*.

White, T. E. See Evans, B.

White, W. B. See Berkes, J. S.; Joubert, J. C.; McCarthy, G. J.; Muller, O.; Roy, R.

White Consolidated Industries, Inc. Method for the production of amorphous cadmium sulfide, P (6) 222*h*.

Whitehead, R. C. See O'Hara, C.

Whitehouse, R. See Vaughan, T. B.

Whiten, J. G. See St. Louis, R. V.

Whitfield, H. J. See Hudson, A.

Whiting, F. L. See Young, J. P.

Whiting, G. H. Recent advances in clay brickmaking, brick testing, and brick building, (2) 54*f*.

Whitley, D. M. See Smith, W. H.

Whitley, J. B. See Balentine, J. W.; Iannicelli, J.

Whitlow, T. E. What you should know about grain sizes, (10) 335*f*.

Whitmore, D. H. See Seitz, M. A.

Whitney, E. D. See Murata, Yorihiro.

Whitney, J. B. Bonded article comprising two metallic members joined by an intermediate layer, P (1) 5*e*.

Whittaker, A. G., and Kintner, P. L. Carbon—observations on the new allotropic form, (11) 382*a*.

Whittaker Corp. Ceramic structural composite, P (11) 374*f*. Filament reinforced metal composites for gas turbine blades, P (11) 374*i*. Filamentary thermal cell with ionically conductive glass coating, P (4) 94*a*.

Whittemore, O. J., Jr. Process for producing shaped mordenite bodies, P (8) 288*a*. Ultrarefractory ceramics—carbides, nitrides, and borides, (1) 13*b*.

Whittier, R. J. Planar high voltage four layer structures, P (6) 223*e*.

Whittingham, M. S. See Dickens, P. G.

Whittle, D. P. See Wood, C. G.

Whitworth, C. R., and Cutler, I. B. Thermoluminescence of sintered alumina, (10) 363*a*.

Whitworth, R. W. Theory of the thermal equilibrium charge on edge dislocations in alkali halide crystals, (4) 160*g*. See Turner, R. M.

Whoriskey, P. J. Five-layer light-actuated semiconductor device having beveled sides, P (5) 183*c*.

Whyte, J. N. See Baker, L. R.

Wiater, K. Refractories for glass furnace generators, (4) 105*f*.

Wickens, A. A. See Laird, R. T.

Wickersheim, K. A. See Lefever, R. A.

Wickert, H. See Pfrunder, V. R.

Wickman, H. H. See Nowik, I.

Wickman, H. H., and Wertheim, G. K. Moessbauer hyperfine spectra of Fe^{3+} in corundum—magnetic- and crystal-field effects, (2) 80*e*.

Widmer, A. E. See McCaldin, J. O.

Widmer, R. See Kaldis, E.

Wiechec, W. J. Method for improving the switching coefficient of ferrites with hysteresis loops of rectangular shape, P (11) 377*b*.

Wiedemeier, H., and Khan, A. Phase studies in the system manganese sulfide-cadmium sulfide, (4) 149*j*.

Wiederhorn, S. M. Fracture of sapphire, (11) 385*b*. Fracture surface energy of glass, (4) 95*i*.

Wiederhorn, S. M., Shorb, A. M., and Moses, R. L. Critical analysis of the theory of the double cantilever method of measuring fracture-surface energies, (2) 47*f*.

Wiedmann, T. High-strength porcelains, (II–V), (7) 253*h*.

Wiegmann, W. See Logan, R. A.

Wieker, W. Chemical studies of silicates (XXXIV) structure of the silicate anions of the 14 Å tobermorite of Crestmore and its dehydration products, (5) 192*d*.

Wiens, B. E. See Braddy, J. E.; Bruss, H. G., Jr.; Schlientz, W. J.

Wiensz, K. See Wuhrer, J.

Wierich, H. See Schwiete, H. E.

Wiersma, J. See Veen, A. W. L.

Wiesner, R. Voltage-sensitive variable *pn* junction capacitor with intermediate control zone, P (4) 117*c*.

Wiff, D. R., and Keown, R. Energy bands in cubic boron nitride, (4) 135*h*.

Wiggins, C. S. See Avella, F. J.

Wigginton, R. J., Dear, W. N., and Culfeather, W. R. Manufacture of titanium dioxide, P (4) 124*d*.

Wigmore, J. K. See Rosenberg, H. M.

Wijn, H. P. J. See Neumann, H.

Wikdahl, N. A. L. Method and apparatus for vortical separation of solids, P (4) 124*f*.

Wilchinsky, Z. W. Apparatus and process for eliminating preferred orientation in X-ray diffraction in crystals, P (4) 121*d*.

Wilcock, J. E. Apparatus for molding of glass articles, P (4) 98*e*.

Wilcox, B. A. See Contin, M. R.

Wilcox, B. A., Clauer, A. H., and McCain, W. S. Creep and creep fracture of an Ni-20Cr-2ThO_2 alloy, (1) 26*d*.

Wilcox, D. L. See Maissel, L. I.

Wilcox, F. L. See Keenan, A. G.

Wilcox, R. L. Image translation system employing optical fibers, P (11) 376*j*.

Wild, P. See Gnehm, C.; Nitsche, R.

Wild, R. L. See Huffman, D. R.

Wilde, D. K. See Dingwall, A. G. F.

Wilder, D. R. See Berard, M. F.; Crick, R. F.; Held, P. C.; Wirkus, C. D.

Wiley, C. A. See Galli, G.

Wiley, R. C. See Goldstein, D.

Wiley, R. F. Apparatus for pressing articles of thermoplastic material, P (6) 212*f*.

Wilfinger, R. J. See Akmenkalns, J. G.

Wilhelm, G. Method of producing intermetallic superconducting compounds of niobium and gallium, P (5) 184*c*.

Wilhelm, H. A., and Bergman, R. M. Method of chlorinating metals with carbon tetrachloride and carbon dioxide, P (11) 382*c*.

Wilhelm, M. See Mueller, A.

Wilk, H. P. Synthesis of glass in the system P_2O_5-ZnO-UO_3, (4) 97*e*.

Wilke, H. Natural gas, (7) 261*e*.

Wilke, K. Th. See Schultze, D.

Wilke, W., and Fetzer, H. Manufacture of purified asbestos products, P (10) 342*g*.

Wilkes, J. G. Coatings on germanium bodies, P (7) 256*a*. Formation of coatings on germanium bodies, P (1) 18*e*.

Wilkes, J. G., and Rantell, A. Formation of coating on germanium bodies, P (8) 282*h*.

Wilkins, C. H. T., Hansen, J. P., and Moyer, R. E. Product research on anthophyllite from Tallapoosa County, Alabama, (4) 151*d*.

Wilkins, N. J. M. See Harrop, P. J.

Wilkinson, R. W. See Nelson, R. L.

Wilkinson, W. T. See Dinsdale, A.

Wilks, E. M. See Frank, F. C.

Wilks, R. S. Neutron-induced damage in BeO, Al_2O_3, and MgO, (8) 295*c*.

Wilks, R. S., Desport, J. A., and Bradley, R. Transmission electron microscopy of neutron-irradiated α-Al_2O_3 single crystals, (4) 162*f*.

Wilks, R. S., Desport, J. A., and Smith, J. A. G. Irradiation-induced macroscopic growth of α-Al_2O_3 single crystals, (4) 141*h*.

Will, G., and Eberspacher, O. Crystal structure of orthoferrites of rare earths (III) structure of thulium orthoferrite, (5) 193*j*.

Will, J. D., and Barnes, R. G. Activation energies for hydrogen diffusion in thorium hydrides, (4) 126*d*.

Willaime, C., and Authier, A. Topographic X-ray observations of dislocations in mica, (1) 39*g*.

Willardson, R. K. See Wagner, J. W.

Willcox, O. B. TiO_2 production by chromium removal from beneficiated titaniferous ore, P (5) 191*g*.

Willcox, O. B., Kolb, K. M., and Amin, R. B. Opacifying pigment glass composition, P (11) 372*c*.

Willemstein, A. See De Ruiter, J. W.

Willey, G. S. Fire resistant plaster product, P (10) 336*b*.

Willgallis, A. See Franke, W.; Heimann, R.

Williams, A. B. Casting high alumina shapes, (10) 340*g*.

Williams, A. J., Jr., and Gray, W. T. Electronic radiant energy pyrometers, P (4) 121*g*.

Williams, A. L. W. See Curran, D. R.

Williams, B. B. See Riley, J. E.

Williams, B. F. InGaAs-CsO, a low work function (less than 1.0 eV) photoemitter, (10) 344*g*.

Williams, B. F., and Simon, R. E. Electron emission from a "cold-cathode" GaAs *pn* junction, (9) 310*j*.

Williams, C. D. See Tipsword, R. F.; Whidden, C. J.

Williams, D. J. See Haddon, J. C.; Jones, D. W.; Mulcahy, M. F. R.; Nijjhar, R. S.

Williams, D. O. See Brivati, J. A.

Williams, D. W. Improved cold seal pressure vessels to operate to 1100°C at 3 kbars, (8) 285*d*.

Williams, E. F. See Hodgson, W. G.

Williams, E. F., Hodgson, W. G., and Brinen, J. S. Synthetic photochromic sodalite, (6) 238*h*.

Williams, E. G., Bergenback, R. E., Falla, W. S., and Udagawa, S. Origin of some Pennsylvanian underclays in western Pennsylvania, (6) 229*f*.

Williams, E. L., Jr., and Wilson, H. H. Mechanism of bonding in aqueous nickelous nitrate-magnesium oxide cements, (4) 92*a*.

Williams, E. R., Jr. See Birchler, R. O.

Williams, E. W. See Woolley, J. C.

Williams, F. V. Process for preparing crystalline boron arsenide, P (4) 116*b*. See Rossi, J. A.

Williams, H. D. See Gittins, A.

Williams, I. Developments in practical superconductivity—a short review, (2) 61*f*.

Williams, J. C. See Edelson, D.

Williams, J. E. See Tanton, G. A.

Williams, J. J., Jr. See Delaney, R. A.

Williams, J. L. See Bundy, A. J.

Williams, J. P. See Korda, E. J.; Ostertag, W.

Williams, L. S. See Bennett, C. E. G.; McKinnon, N. A.

Williams, M. Method of making superconducting magnets, P (6) 222*j*.

Williams, M. L. Fracture in viscoelastic media, B (1) 41*f*.

Williams, M. M. D. See Anderson, J. A.

Williams, M. W. See Arakawa, E. T.

Williams, N. R. Preparation of uranium monocarbide of controlled composition by carbothermic reduction of the oxides in vacuum, (4) 150*h*.

Williams, N. S. See Koester, C. J.; Siegmund, W. P.
Williams, P. M., and Yoffe, A. D. Scanning electron microscope studies of cathodoluminescence in ZnSe single crystals, (5) 199*e*.
Williams, R. J. P. See Joergensen, C. K.
Williams, R. H. See Thomas, R. T.
Williams, R. M. See Rodgers, J. T.
Williams, W. S. See Radosevich, L. G.
Williamson, K., Li, P., and Devlin, J. P. Vibrational spectra and structures of ionic liquids (II) the pure alkali metal nitrates, (5) 203*c*.
Williamson, R. B. Constitutional supersaturation in portland cement solidified by hydration, (7) 244*h*. Portland cement—pseudomorphs of original cement grains observed in hardened pastes, (8) 274*f*.
Williamson, W. O. See Faruqi, F. A.; Hutchison, C. R.
Williamson, W. R. See Houston, H. H.
Williford, J. F., Jr. HERF densifies ceramics, cermets, and composites, (4) 117*h*.
Willis, H. C. See Roessler, M. L.
Willis, J. B., and Dixon, M. Assessment and control of imperfections in crystals for laser devices, (9) 318*f*.
Willison, R. M. See Oliver, E. M.
Willmann, K. Plant for the simultaneous grinding of differently grindable materials, P (1) 24*b*.
Willock, C. B. Press for making blocks from loose fiber material, P (2) 68*c*.
Willshee, J. C., and White, J. Equilibrium relationships in the systems FeO-Fe_2O_3-Al_2O_3 and FeO-Fe_2O_3-Cr_2O_3 up to 1750°C in air, (4) 135*f*.
Wilma, D. D. See Slocombe, J. W.
Wilmot Engineering Co. Dryer, P (1) 20*d*.
Wilson, A. D. See Akmenkalns, I. G.
Wilson, A. L. See Morrison, I. R.; Webber, H. M.
Wilson, B. F. How to select and apply the right rust preventive, (5) 171*i*.
Wilson, B. S., Jr., and von Doenhoff, C. Process for producing silicon carbide articles employing pyromellitic dianhydride-limonene dioxide mixture, P (11) 375*b*.
Wilson, D. A. See Collins, J. H.
Wilson, H. C. Report on PEI Bulletin P-307, "Preparation of sheet steel for porcelain enameling," (1) 5*f*.
Wilson, H. H. Mullite formation from the sillimanite group minerals, (10) 341*g*. See Williams, E. L., Jr.
Wilson, H. L. See Gutierrez, W. A.
Wilson, H. S. Lightweight aggregates in Canada, (4) 101*i*.
Wilson, J. See Gottschalk, K.
Wilson, J. N. See Goosey, M. H.
Wilson, J. R. See Rowe, G. L.
Wilson, J. T. Techniques in modern brickmaking—American brick kilns, (10) 340*d*.
Wilson, M. Method and means for beneficiating ores, P (5) 191*c*.
Wilson, T. M. Spin-polarized energy-band structure of antiferromagnetic MnO, (9) 329*g*.
Wilson, W. D. Ultrasonic method for producing phase transitions in materials at high pressures, P (5) 186*f*.
Wilson, W. L. Process for preparing pigmentary titanium dioxide, P (6) 230*a*.
Wilson, W. L., Lott, H., Jr., and Dietz, A. Process for preparing pigmentary titanium dioxide, P (6) 230*b*.
Wilson, W. L., Strain, F., and Hoekje, H. H. Process for preparing pigmentary metal oxide, P (8) 288*e*.
Wilson, Lee, Engineering Co., Inc. Vitreous enameling steel and method of making same, P (2) 46*d*.
Wilwerger, F. Crystallization problems of drawn sheet glass, (8) 276*d*.
Wimber, R. T., and Stetson, A. R. Slurry coatings for tantalum-base alloys, (1) 5*g*.
Wimpfheimer, A., & Bro., Inc. Method of making improved glass fiber material and laminates thereof, P (9) 308*a*.
Win, S. See Fleet, B.
Windisch, S. See Rudy, E.
Windmann, H. Converting a container glass tank from oil to natural gas firing, (9) 305*f*.
Windmiller, L. R. See Ketterson, J. B.
Winefordner, J. D. See Smith, R.
Wingerson, R. C. Sputtering protection for tantalum cathodes in plasma devices, P (9) 314*d*.
Winings, R. H. Apparatus for polishing, P (7) 255*f*. Methods and apparatus for treating semiconductive materials with gases, P (5) 184*h*.
Winkler, G. Ferrimagnetic material for use at frequencies higher than 50 MHz having reduced loss factor and higher quality factor, P (11) 376*f*.
Winkler, H. See Geschke, D.
Winkler, R. A. See Larson, J. O.
Wins, M. J. Notes on the resistance to cold crushing of refractory materials, (6) 216*g*.
Winsett, D. L. Manufacture of coke and low CTE graphite from petroleum derived feed materials, P (11) 375*c*.
Winslow, N. M. Device for measurement of pore size and pore volume, P (7) 260*g*.
Winter, F. See Bacherescu, D.
Winter, G., and Reum, H. Mercury vapor tube with special discharge chamber means separating mercury electrodes, P (2) 53*e*.
Winter, W. E. See Garrison, L. H.
Winterbottom, W. L. Equilibrium shape of a small particle in contact with a foreign substrate, (1) 29*a*.
Winterhager, H., and Hanusch, K. Production of titanium nitride in a direct current plasma, (11) 373*d*.
Winterhalter, B. G. L. See Rep, R.
Winters, H. F. See Jones, R. E.
Winterton, R. H. S. See Tabor, D.
Wintruff, W. See Arija, S. M.
Wirick, M. P. Near ultraviolet optical constants of lanthanum fluoride, (1) 33*i*.
Wirkus, C. D. See Berard, M. F.
Wirkus, C. D., Berard, M. F., and Wilder, D. R. Oxygen diffusion in Gd_2O_3, (10) 358*g*.
Wirth, H., Helmberger, H., and Herrmann, H. Apparatus for manufacturing flawless stress-free boron rods, P (6) 217*g*.
Wirth, L. F., Jr., and Robertson, R. S. Polyphosphate glasses and water treatment uses thereof, P (6) 213*a*.
Wisconsin Alumni Research Foundation. Method and apparatus for treating particulate material in a fluidized bed, P (7) 259*b*.
Wise, W. N. See Colby, J. W.
Wishon, B. E. See Cobaugh, G. D.; Pavlica, S. R.
Wisman, E. C., and Kronlage, J. W. Apparatus and process for growing noncontaminated thermal oxide on silicon, P (8) 282*b*.
Wissmann, P. See Wedler, G.
Withers, G. L. See Cubicciotti, D.
Witkin, D. E., and Van Leemput, H. Effects of physical parameters pertaining to the isostatic pressing process, (4) 108*e*.
Witt, A. F. See Morizane, K.; Mroczkowski, R. S.; Singh, R.
Witt, A. F., and Gatos, H. C. Determination of microscopic rates of growth in single crystals, (4) 131*h*. Impurity distribution in single crystals (II) impurity striations in InSb as revealed by interference contrast microscopy, (1) 30*j*. Microscopic rates of growth in single crystals pulled from the melt: indium antimonide, (4) 144*a*.
Witt, F., Vook, R. W., and Luszcz, S. X-ray investigations on the structure of silver films evaporated on CaF and NaCl single-crystal substrates, (4) 164*e*.
Witte, H. O. Fluidized-bed combustion of graphite-based nuclear reactor fuels, (8) 278*j*.
Wittenbecher, R. Method and apparatus for making video tubes implosionproof, P (11) 371*d*.
Wittenwyler, C. V., and Magee, J. E. Process for sealing cement concrete surfaces, P (9) 304*d*.
Wittman, L. J. Production of decorated polytetrafluoroethylene coated glass cooking vessel, P (8) 278*b*.
Witzmann, H., Treichler, W., and Maihold, B. Zirconium pyrophosphate fluorescent material, (6) 240*a*.
Woelfel, E. See Panke, D.
Woellhaf, J. See Lehrer, E.
Woermann, E., Brezny, B., and Muan, A. Phase equilibria in the system MgO-iron oxide-TiO_2 in air, (10) 358*j*.
Woermann, E., Eysel, W., and Hahn, T. Chemical and structural studies of solid solutions of tricalcium silicate, (2) 43*j*.
Woessner, D. E., and Snowden, B. S., Jr. NMR doublet splitting in aqueous montmorillonite gels, (11) 386*i*.
Wohl, M. H. Designing for non-Newtonian fluids (V) dynamics of flow between parallel plates and in noncircular ducts, (1) 27*c*; (VI) isothermal turbulent flow in pipes; (VII) heat transfer in laminar flow; (VIII) heat transfer to non-Newtonian fluids; (IX) mixing of non-Newtonian fluids, (2) 69*d*.
Wohlleben, K. See Patzak, I.; Von Kahler, U.
Wold, A. See Kershaw, R.
Wolf, H. See Jost, K. H.
Wolf, W. F., and Kosiorek, R. Crystallizable enamels for glass-ceramics, P (6) 212*j*.
Wolfe, C. M. See Stillman, G. E.
Wolfe, W. C. Two fuel burner arrangement, P (4) 123*c*.
Wolff, E. A., Jr. See Cornelison, B.
Wolff, P. A. Tunable Raman laser, P (6) 224*b*.
Wollast, R., and Tazairt, A. Phase diagram of the MgO-V_2O_5 system, (9) 326*j*.
Wollenberg, T. S. Process for producing titanium dioxide pigments, P (4) 125*b*.
Wollenheit, L. Painting with glass — stained glass windows, (5) 170*a*.
Wolley, E. D. Process for diffusing gold into semiconductor material, P (7) 257*h*.
Wolski, W., Burewicz, A., and Skrzypczak, J. Heavy iron hydroxide, α-FeOOD, (6) 233*f*.
Woltersdorf, R. J. Colloidal silica-potassium silicate mixtures and method for preparing same, P (5) 190*g*.
Wones, D. R., and Gilbert, M. C. Fayalite-magnetite-quartz assemblage between 600° and 800°C, (10) 353*c*.
Wong, C., and Schuele, D. E. Pressure and temperature derivatives of the elastic constants of calcium fluoride and barium fluoride, (9) 328*e*.
Wong, J. Y., Berggren, M. J., and Schawlow, A. L. Far-infrared spectrum of Al_2O_3:V^{4+}, (8) 292*f*.
Wong, M. M. See Gomes, J. M.
Woo, T. C. Thermal stress problems in glass, (1) 9*f*.
Woock, H. J. Hard-facing matrix composition and method of preparing same, P (2) 58*g*.
Wood, A. F. B. Temperature compensating unit for piezoelectric crystals, P (4) 117*c*.
Wood, C. E. See Cole, W. C.
Wood, D. A. Method of separating frit-sealed glass bodies, P (4) 100*j*.
Wood, D. L. See Remeika, J. P.
Wood, D. L., Imbusch, G. F., Macfarlane, R. M., Kisliuk, P., and Larkin, D. M. Optical spectrum of Cr^{3+} ions in spinels, (6) 235*b*.
Wood, D. L., and Nassau, K. Characterization of beryl and emerald by visible and infrared absorption spectroscopy, (8) 289*e*. Infrared spectra of foreign molecules in beryl, (4) 140*h*.
Wood, G. C. See Harrop, P. J.
Wood, G. C., Ferguson, J. M., Vaszko, B., and Whittle, D. P. Substructures in oxide scales on nickel, cobalt, and nickel-cobalt alloys, (4) 157*h*.
Wood, J. D. See Walker, B. F.
Wood, J. D. C., and White, E. A. D. Growth of stoichiometric magnesium aluminate spinel crystals by flux evaporation, (10) 354*b*.
Wood, R. H. See D'Orazio, L. A.
Woodcock, R. F. See Snitzer, E.
Woodhouse, R. L. See Speros, D. M.
Woodruff, D. P. Morphology of the solid/liquid interface during melting, (4) 145*c*.
Woods, J. See Clark, L.
Woods, J. F. See Foster, L. M.
Woods, K. N., and Fine, M. E. Nucleation and growth of magnesioferrite in MgO containing 0.9% Fe^{3+}, (6) 235*j*.
Woods, W. W., Martin, D. L., and Marshall, J. K. Polarization pyrometer, P (11) 381*a*.
Woodward, D. See Bass, M.
Woolery, R. G., and Dresher, W. H. Reversible flocculation and redispersion of chrysotile asbestos, P (5) 191*d*.
Woolf, J. B. See Thorp, J. M.
Woolley, D. D. Ceramic-to-metal bonding method, P (2) 64*h*.
Woolley, J. C., and Berolo, O. Phase studies of the $Pb_{1-x}Sn_xSe$ alloys, (6) 236*d*.
Woolley, J. C., and Williams, E. W. Some cross-substitutional alloys of CdTe, (2) 83*f*.
Wooten, F. T., III. Temperature change measuring device, P (10) 348*b*.
Wootton-Davies, J. W. See Smith, H.
Worcester, L. E., and Webster, L. P. Process for manufacturing welding devices for semiconductors, P (11) 378*i*.
Worchel, G. S., and Reber, R. L. Multiemitter semiconductor device, P (11) 377*j*.
Work, L. T. See Snow, R. H.
Worlock, J. M. Thermal conductivity in sodium chloride crystals containing silver colloids, (1) 39*j*.
Worlton, T. G., Brugger, R. M., and Bennion, R. B. Pressure dependence of the Néel temperature of Cr_2O_3, (9) 328*d*.
Worner, H. K. Continuous production of alpha plaster, P (7) 245*c*.
Worobey, W. Thin film distributed RC network, P (8) 284*b*.
Woronoff, A. M. See Rudd, M. O.
Worrell, W. L., and Turkdogan, E. T. Iron-sulfur system (II) rate of reaction of hydrogen sulfide with ferrous sulfide, (4) 141*g*.
Wortman, J. J., and Stockard, R. R. Semiconductor *pn* junction stress and strain sensor, P (6) 223*i*.
Wosinski, J. F., Shay, G. C., and Edmister, W. H. Compressive creep characteristics of selected refractories, (6) 214*j*.
Woskow, M. Z., Colling, P. M., and Karkalits, O. C., Jr. Dehydrogenation process using cobalt or nickel ferrite, P (6) 229*f*.
Woulbroun, J. M., and Doyle, G. A. (editors). Second Symposium on Hybrid Microelectronics, Boston, October 1967, B (6) 242*f*.
Wratil, J. Nickel pretreatment of sheet steel, (10) 336*i*.
Wright, A. N., and Mathewson, W. F., Jr. Diamond and cubic boron nitride grains coated with photopolymerized material, P (2) 43*g*.
Wright, C. L. Composition resistor, P (4) 112*i*.
Wright, D. A. Electrical and optical properties of tin oxide crystals, (10) 352*g*.
Wright, G. B. See Mooradian, A.
Wright, G. F. Spark plug with an annular heat dam recess in the insulator nose, P (8) 280*e*.
Wright, H. C. Three region semiconductor having rectifying junctions of different compositions so that wavelength of emitted radiation depends on direction of current flow, P (2) 67*a*.
Wright, H. W., Jr. Research capabilities in the smaller company, (1) 40*f*.
Wright, L. W. See Thomas, P. M.
Wright, M. R. See Poplawsky, R. P.
Wright, T. L. X-ray and optical study of alkali feldspar (II) an X-ray method for determining the composition and structural state from measurement of 2θ values for three reflections, (6) 239*j*.
Wright, T. L., and Stewart, D. B. X-ray and optical study of alkali feldspar (I) determination of composition and structural state from refined unit-cell parameters and $2V$, (6) 239*g*.
Wright, W. L. See Pakulski, F. J.
Wrigley, C. Y. See Lindmayer, J.
Wrobel, E. J. See Honig, W. M.
Wu, J. C. C. Coated refractory for contacting molten glass and method of making, P (7) 252*g*.
Wu, S. Y., and Formigoni, N. P. Charge phe-

nomena in dc reactively sputtered SiO_2 films, (7) 254*f*.
Wuhrer, J. Production of hydraulic binders, P (5) 170*i*.
Wuhrer, J., and Wiensz, K. Manufacture of shaped refractories from dolomite, P (7) 252*b*.
Wulff, H. E. Traditional Crafts of Persia—Their Development, Technology, and Influence on Eastern and Western Civilizations, B (1) 42*e*.
Wulff, J. See Rauch, G. C.
Wurm, J. G., and Avogadro, A. Process for processing irradiated ceramic reactor fuels, P (1) 14*d*.
Wurtz, F. Vacuum metalizing a variety of products, (7) 259*c*.
Wyandotte Chemicals Corp. Abrasive cleaning compositions, P (11) 367*f*.
Wyatt, B. S. Effect of carbon on the δ-peritectoid reaction in uranium-silicon alloys, (8) 291*c*.
Wycisiak, J. Process for establishing low Zener breakdown voltages in semiconductor regulators, P (10) 345*f*.
Wyckoff, R. W. G. Crystal Structures (Vol. 4) Miscellaneous Inorganic Compounds, Silicates, and Basic Structural Information, B (7) 271*e*.
Wyllie, P. J. See Boettcher, A. L.; Koster van Groos, A. F.; Lambert, I. B.
Wyllie, P. J., and Boettcher, A. L. Liquidus phase relations in the system $CaO-CO_2-H_2O$ to 40 kbars pressure, (10) 356*j*.
Wymer, R. G. (coordinator). Proceedings of Second International Thorium Fuel Cycle Symposium, Gatlinburg, Tenn., May 1966, B (6) 242*a*.
Wymer, R. G., and Coobs, J. H. Preparation, coating, evaluation, and irradiation testing of sol-gel oxide microspheres, (4) 150*g*.
Wynblatt, P. Calculation of the vacancy migration energy in cubic crystals, (9) 318*a*.
Wynne, K. J. See George, J. W.
Wynne-Jones, L. See Lown, D. A.
Wythe, F. J. [Hydraulic] shears for molten glass feeders, P (7) 248*j*.

Xerox Corp. Solid state storage device, P (11) 379*a*.

Yaeoby, Y. See Arntz, F.
Yagi, K., and Onuma, K. Experimental study of the role of titanium in the alkaline basalts in the light of the system diopside-akermanite-nepheline-$CaTiAl_2O_6$, (10) 353*j*.
Yagi, Shoji. See Ono, Kazumasa.
Yagi, Takuo. See Miyatake, Kazumi.
Yaglov, V. N. Stimulated crystallization of some iron-containing glasses, (1) 9*d*.
Yagub'yan, E. S. See Mateiko, Z. A.
Yajima, J. See Touray, J. C.
Yajima, S. See Furuya, H.
Yakobson, K. K., and Nizheviasov, V. V. Influence of cement composition on shrinkage of high-strength concretes, (7) 244*i*.
Yakovlev, G. K. See Izergina, E. V.
Yakowitz, H. See Goldstein, J. I.
Yalouris, N. Unreported use for some Mycenaean glass paste beads, (4) 91*a*.
Yamada, Elzaburo. See Futaki, Hisao.
Yamada, Mamoru. See Minowa, Susumu.
Yamada, Nobuyoshi, and Iida, Shuichi. Details of the Richter-type magnetic relaxation in $Mn_xFe_{3-x}O_{4+\gamma}$, (2) 75*d*.
Yamada, Tamotsu. Retarders and accelerators for setting of calcium sulfate hemihydrate, (4) 92*e*.
Yamada, Tamotsu; Mizutani, Chihiro; and Nagai, Shoichiro. By-product gypsum from the phosphoric acid process (VII) dehydration and hydration in mineral acids, (4) 123*e*.
Yamada, Tamotsu; Sakimoto, Sadanori; and Nagai, Shoichiro. By-product gypsum from the phosphoric acid process (IX) statistical study of the crystal modifier in phosphate rocks, (4) 123*f*.
Yamada, Tomoaki. See Iwasaki, Hiroshi; Nii, Riro; Niizeki, Nobukazu.
Yamada, Tomoaki; Niizeki, Nobukazu; Iwasaki, Hiroshi; and Toyoda, Hiroo. Crystal growth of $LiNbO_3$, (1) 16*f*.
Yamada, Yahiko. See Takami, Katsumi.
Yamagishi, Haruo. Temperature dependence of surface potential of Si(III) surfaces with a silicon nitride layer, (1) 39*g*.
Yamaguchi, Goro. See Kubo, Yasushi; Yanagida, Hiroaki.
Yamaguchi, Goro, and Chiu, Wen-Chau. Delta and theta Al_2O_3 under hydrothermal conditions, (8) 290*j*. Hydration and crystallization of ρ-alumina and alumina gel in aqueous solutions of various basic reagents, (4) 138*j*.
Yamaguchi, Goro, and Suzuki, Kazutaka. Structures of alkali polyaluminates, (4) 156*e*.
Yamaguchi, Goro, and Tokuda, Toshio. Electron microscopic observation of two solid state reactions (MgO-FeO and $MgO-Al_2O_3$), (1) 28*h*.
Yamaguchi, Goro; Yanagida, Hiroaki; and Ono, Shuichiro. Formation conditions for tohdite $5Al_2O_3 \cdot H_2O$, (1) 30*b*.
Yamaguchi, Sadae. Ordered arrangement of oxygen in the interstitial solid solution of the zirconium-oxygen system, (2) 81*g*.
Yamaguchi, S., and Katsurai, T. Hydrothermal crystal growth of yttrium oxide and zinc sulfide, (9) 322*i*.
Yamaguchi, Shigeto, and Wada, Harue. Hydrothermal synthesis of ferrothiospinel, (10) 355*f*.
Yamaguchi, Tadashi. See Yoshida, Hideo.
Yamaguchi, Tadashi; Hanaoka, Masakazu; and Ishii, Toshio. Results obtained with fired basic bricks of Mg clinker with different magnesia contents used in open-hearth furnace roof, (2) 57*b*.
Yamaguchi, Takashi. Fundamental study on ferrite manufacturing process (V) relation between grain structure and magnetic properties of Mn-Zn ferrite, (4) 110*h*. Phase relations in the system Cu-Fe-O, (1) 34*i*.
Yamaguchi, Takashi, and Shiraishi, Takashi. Eutectoid decomposition of $CuFe_2O_4$-Fe_3O_4 spinel solid solution including $CuFe_2O_4$, (9) 321*a*.
Yamaguchi, Yasuo. See Takeda, Takayoshi.
Yamaji, N. See Ohtsuki, T.
Yamamoto, H., and Kennedy, G. C. Stability relations in the system $CaSO_4$-H_2O at high temperatures and pressures, (10) 360*i*.
Yamamoto, Hajime; Makishima, Shoji; and Shionoya, Shigeo. Vibronic structure in luminescence spectra of rare earth ions in $SrTiO_3$, $BaTiO_3$, and other perovskites, (2) 84*e*.
Yamamoto, Hiromi. See Ohba, Hiroshi.
Yamamoto, Hiroshi, and Ikeda, Koichi. Vitreous material for use in semiconductor devices, P (8) 284*a*.
Yamamoto, Hisao; Okada, Takuya; Watanabe, Hiroshi; and Fukase, Masahiro. Moessbauer effect study of spin relaxation in $CaFe_2O_4$, (2) 80*c*.
Yamamoto, Junnosuke, and Komatsu, Eiichi. Pelletizing the glass batch, (1) 8*b*.
Yamamoto, Keita. Method of making a woven fiber circuit element, P (9) 313*b*.
Yamamoto, Koichi. See Hashimoto, Tsunekazu.
Yamamoto, Naoichi. Shift of the spin flip temperature of α-Fe_2O_3 fine particles, (2) 82*j*.
Yamamoto, Noboru, and Niguchi, Noboru. Method for producing porcelain articles, P (11) 376*a*.
Yamamoto, Nobuyuki. See Miyauchi, Takeshi.
Yamamoto, Ryoichi. See Itoh, Kohji.
Yamamoto, Ryoichi; Inoue, Masashi; Itoh, Kohji; and Shitaya, Takao. Visible electroluminescence from *pn* junctions in $Cd_{1-x}Mg_xTe$, (9) 332*j*.
Yamamoto, Takaharu. See Suzuki, Hisashi.
Yamamoto, Tetsuo. See Noguchi, Tetsuo.
Yamasaki, Nakamichi. See Hirai, Toshio.
Yamashita, Akio. Semiconductor devices, P (7) 258*c*.
Yamashita, Akio, and Tanaka, Masaru. Negative resistance semiconductor device having an intrinsic region, P (11) 378*a*. Pressure-responsive semiconductor device, P (8) 283*i*. Semiconductor comprising plural deep-level-forming impurities, P (9) 313*h*.
Yamashita, Hajime. See Niwa, Shohei.
Yamashita, Katsuyuki. See Mizuno, Hideo.
Yamauchi, Fumie. See Akashi, Tsuneo.
Yamauchi, Hiroshi. See Watanabe, Hiroshi.
Yamauchi, Masakatu. See Sato, Atsushi.
Yamauchi, Michiaki. See Kobayashi, Kazuo.
Yamauchi, Shigeru, and Mukaibo, Takashi. Oxidation of graphite by carbon dioxide-carbon monoxide gas mixtures, (8) 295*h*.
Yamauchi, Shigeru; Mukaibo, Takashi; and Ikeda, Tadao. Effect of chlorine on the oxidation of graphite by carbon dioxide, (8) 291*e*.
Yamauchi, Shiro; Ozaki, Shunro; and Matsumoto, Hideo. Sintered materials of zirconia (I) grain growth and phase transition of ZrO_2, (4) 154*a*.
Yamazaki, S., Asaki, Z., and Kondo, Y. Thermal decomposition of pyrite in a fluidized bed, (4) 160*b*.
Yamazaki, Syunpei; Kato, Yogoro; and Taniguchi, Ichirou. Silicon nitride by using stain films on silicon, (8) 297*d*.
Yamazaki, Toshiji. See Hibino, Taizo.
Yanagawa, Takayuki. Avalanche transistor having reduced width in depletion region adjacent gate surface, P (8) 282*c*. See Kurosawa, Toshio.
Yanagi, Shigetoshi. Present condition of unshaped refractories in use at Chiba Iron Works of Kawasaki Steel Corporation and problems involved, (7) 251*d*.
Yanagida, Hiroaki. Thermal behavior of materials on the basis of crystal chemistry, (1) 39*j*. See Yamaguchi, Goro.
Yanagida, Hiroaki, and Kroeger, F. A. System Al-O, (1) 39*c*
Yanagida, Hiroaki, and Yamaguchi, Goro. Discussion on the phase diagram of the system Al_2O_3-H_2O considering the transformation mechanism of the polymorphs appearing in it, (1) 27*b*.
Yanagida, Hiroaki; Yamaguchi, Goro; and Kubota, Joe. Role of water vapor in formation of α-Al_2O_3 from transient alumina, (1) 36*g*.
Yanagida, Yoshiro. See Machiyama, Katsuhide.
Yanagihara, Takashi. See Miyatani, Shinya.
Yanase, Akira. See Hirota, Hozumi.
Yanase, Akira; Tawara, Yoshio; Iga, Atsushi; and Hirota, Hozumi. Ferromagnetic material, P (5) 183*a*.
Yang, G. C. See Chang, Tetse.
Yang, J. C. S. Slag cement compositions, P (9) 304*e*.
Yanir, E. See Mayer, I.
Yanovskii, V. K. Growing monocrystals of high-temperature oxides, (2) 62*d*. See Budnikov, P. P.
Yaremenko, Z. A. See Panasevich, V. M.
Yariv, A. See Van Atta, L. B.
Yarkho, G. A. See Belov, K. P.
Yaroker, Kh. G. See Botvinkin, O. K.
Yaroslı, P. Ya., Buslaev, F. P., and Sherstobytova, L. A. Investigation of fine structure of the faces of pyrite crystals by the electron microscope, (4) 141*d*.
Yasevich, A. I. New type of lightweight concrete with a lime-burned clay binder, (2) 44*h*. See Satalkin, A. V.
Yashiro, Takehisa. See Ono, Kazumasa.
Yasohama, Kazuhiko. See Saito, Yukinori.
Yastrebova, L. S., and Antonova, N. I. Study of the nature of the effect of two alkalis in silicate glasses, (2) 51*h*.
Yasuda, Eiichi. See Tagai, Hideo.
Yasufuku, Matami. Method of manufacture of superhigh-frequency transistor, P (11) 377*e*.
Yasui, Heiji. See Sugita, Tadaaki.
Yasukouchi, Ko. See Saito, Yukinori.
Yasunaga, Hitosi. Photo-Hall effect in strontium titanate, (2) 81*g*. Photomagnetoresistance of strontium titanate, (2) 81*h*.
Yasunaga, Hitosi, and Nakada, Ichiroh. Anomalous temperature dependence of photoconductivity in $SrTiO_3$, (2) 74*j*. Photoconduction of strontium titanate, (5) 198*j*.
Yasuoka, Hiroshi; Hirai, Akira; Shinjo, Teruya; Kiyama, Masao; Bando, Yoshichika; and Takada, Toshio. NMR determination of metal ion distribution in manganese ferrite prepared from aqueous solution, (5) 197*d*.
Yasutake, Yoshito, and Fujita, Yosisige. Process for preparing sodium metaphosphate, P (11) 382*h*.
Yates, B. See Bailey, A. C.
Yates, G. See Bramman, J. I.
Yates, G., and Bramman, J. I. Identification of an unknown constituent in the electron-probe microanalysis of inclusions in irradiated oxide fuels, (2) 69*j*.
Yates, P. C. Dense products of vanadium or zirconium nitride with iron, nickel, or cobalt, P (2) 58*b*. Metal bonded silicon nitride, P (2) 58*j*. Nitride-refractory metal compositions, P (2) 59*h*. Nitrides plus wear-resistant additives bonded with iron, cobalt, or nickel, P (2) 59*a*. Preparation of metal nitrides, P (9) 309*c*.
Yawata, Keisuke; Shiba, Hiroshi; and Anazawa, Shinzo. Sealed enclosure for electronic device, P (2) 66*j*.
Yawata Iron & Steel Co., Ltd. Stopper for ladle with air-cooled head, P (4) 108*a*.
Yenkley, R. L. See Bean, K. E.
Yeaple, F. D., Parisi, A. J., and Maddox, D. West Coast premiere — Product Engineering stars, (5) 170*b*.
Yee, Jick H. Calculations of two-photon conductivity in semiconductors, (11) 383*d*.
Yee, Tin B. Maximum temperature indicating ceramic film, P (4) 122*a*.
Yeh, H. J. C. See Huettner, D. J.
Yenawine, D. L., and Hirakis, E. C. Coating composition comprising aluminum and metal fluorides, P (4) 93*g*. Method of applying oxidation protective coatings to niobium, P (6) 208*c*.
Yeomans, L. S. See Ronceray, R. A. M.
Yerkess, J. See Grimes, N. W.
Yerouchalmi, D. Composite electrode for magnetohydrodynamic generator, P (6) 221*c*. Composite electrode for MHD conversion duct, P (6) 221*d*. See D'Albis, A.; Wang, R.
Yim, W. M., and Fitzke, E. V. Effects of growth rate on the thermoelectric properties of Bi_2Te_3-Sb_2Te_3-Sb_2Se_3 pseudoternary alloys, (5) 194*b*.
Yip, S. See Boutin, H.
Yissum Research Development Co. Means and method for the detection of uranium, P (1) 22*d*.
Yocom, P. N. Rare earth activated lanthanum and lutetium oxychalcogenide phosphors, P (4) 116*e*. See Larach, S.; White, J. G.
Yoffe, A. D. See Williams, P. M.
Yokoi, M. See Yoshida, K.
Yokom, J. C. See Piggott, M. R.
Yokomizo, Keiji; Sakamoto, Yoshimitsu; and Takano, Sumio. Results of service tests on various types of nozzle seating blocks for LD converter ladle, (11) 374*a*.
Yokota, Ryosuke. Eu^{3+} ion as electron trap in glass, (1) 7*c*. Nonclassical nucleation theory and phase separation by spinodal decomposition, (1) 33*e*.
Yokota, Ryosuke, and Imagawa, Hiroshi. Radiophotoluminescent centers in silver-activated phosphate glass, (1) 8*b*.
Yolken, H. T., and Kruger, J. Thermal regeneration of oxide covered iron [100] and [110] surfaces, (4) 160*i*.
Yonemochi, Osamu. See Noguchi, Tetsuo.
Yonemura, Michiko. See Kotera, Yoshihide.
Yoon, H. S. See Hoch, M.
York, C. M. See Skeen, C. H.
Yoshida, Hideo. Construction of roof of one-way top-fired soaking pit of recuperative type furnace with unshaped refractories, (5) 176*i*. Gunning repairs of walls and roofs of furnace and soaking pit, (2) 55*i*. Results of refractoriness-under-load test conducted on some magnesia clinker samples, (10) 342*e*. Results of service test on lime rotary kiln lined with castable and plastic refractories, (11) 373*i*. Use of castable refractories in lime-burning kiln at Mizushima Iron Works, (7) 252*a*.
Yoshida, Hideo, and Yamaguchi, Tadashi. Ten-

sile construction of heating furnace walls, (11) 381*i*.

Yoshida, K., Ishihara, T., and Yokoi, M. Solubility of aluminum in cryolite melts, (1) 37*h*.

Yoshida, Masayuki. See Watanabe, Yoshio.

Yoshida, Masayuki, and Saito, Ken. Dissociative diffusion of nickel in silicon and self-diffusion of silicon, (4) 131*j*.

Yoshimine, M. Computed ground state properties of BeO, MgO, CaO, and SrO in molecular orbital approximation, (8) 289*d*.

Yoshino, Hajime. See Nameishi, Naoyuki.

Yoshino, Katsumi; Iguchi, Shinichi; Kawabe, Kazuo; and Inuishi, Yoshio. *Q*-switching of ruby laser by pheophytin *a* and its derivatives, (2) 82*j*.

Yoshino, Kazumichi. See Hamano, Kenya.

Yoshio, Tetsuo. See Hirai, Taketsugu; Takahashi, Katsuaki.

Yoshioka, Satoshi, and Takayanagi, Shigetoshi. Deposition of silicon nitride films by the silane-hydrazine process, (4) 109*g*. Method for the deposition of silica films, P (8) 282*f*.

Yoshiwara, Hiromasa. Comparative service tests on roseki (pyrophyllite) brick and unfired silicon carbide brick in electric furnace ladle, (11) 372*g*.

Young, D. A. Process for the manufacture of metal-cation-deficient zeolites, P (11) 382*g*. See Jackson, B. J. H.

Young, H. When fingers think, (6) 206*e*.

Young, H. S. See Bither, T. A.; Larkins, T. H., Jr.

Young, J. C. BaO-Nb_2O_5-SiO_2 glass compositions for use in fiber optics, P (11) 371*a*.

Young, J. F. Influence of tricalcium aluminate on the hydration of calcium silicates, (4) 140*e*.

Young, J. P., Mamantov, G., and Whiting, F. L. Simultaneous voltammetric generation of U(III) and spectrophotometric observation of the U(III)-U(IV) system in molten lithium fluoride-beryllium fluoride-zirconium fluoride, (4) 154*j*.

Young, M. R., and Armstrong, J. A. Fluorescence microscopy with the quartz iodine lamp, (4) 119*h*.

Young, R. A. See Elliot, J. C.

Young, R. W. See Snitzer, E.

Young, R. W., Graf, R. E., and Robinson, C. C. Materials and structures for optical Faraday rotation devices, P (5) 175*h*.

Young, S. G. Electrical resistance furnaces, P (7) 261*h*.

Young, W. A. Specific heats, thermal diffusivities, and thermal conductivities of zirconium hydrides containing 4 at.% U, (10) 360*h*. See Moore, K. E.

Youngquist, D. Multiple capacitor and method of making the same, P (5) 184*a*.

Youngquist, Dave, & Co. Multiple capacitor and method of making the same, P (5) 184*a*.

Yount, J. G., Jr., and Powers, W. H. Simulated service tests of cement kiln brick, (8) 279*d*.

Yu, Hwa N. See Fang, F. F.

Yu, R. M. Structure of vacuum-deposited cadmium iodide films, (2) 83*i*.

Yuasa, M. See Tovoshima, Y.

Yuasa, Takaaki. See Tomita, Takanori.

Yuasa, Takaaki; Tomita, Takanori; and Tokonami, Masayasu. Silicon carbide 33T, (1) 36*c*.

Yucelen, Y. See Offner, M.

Yudin, N. A., and Fedorova, V. A. Staining glasses with rare earth elements, (6) 211*h*.

Yugo, Shigemi. See Tsuzuku, Takuro.

Yund, R. A. See Rutstein, M. S.

Yund, R. A., and Hall, H. T. Miscibility gap between FeS and $Fe_{1-x}S$, (2) 80*c*.

Yurasova, V. E. See Gladneva, L. I.

Yurchak, I. Ya., Entelis, F. S., and Sheinina, M. E. Mechanization and automatization in the porcelain-faience industry, (2) 60*g*.

Yushko, K. B. See Kormer, S. B.

Yvon, K., and Nowotny, H. Formation of carbohydrides of some transition metals, (1) 30*a*.

Zachos, T. H. Gaussian beams from GaAs junction lasers, (4) 137*c*.

Zadneprovskii, G. M. See Mill, B. V.

Zador, S. See Alcock, C. B.

Zadumin, V. I. Influence of heat treatment of glass during the precrystallization period on the nature of the crystallization, (2) 49*d*.

Zagar, L. Increased applicability of mercury porosimeter for testing ceramic materials and products, (7) 260*f*.

Zagar, L., and Arit, U. Dependence of specific surface of technical powdered glasses on chemical composition, (9) 305*g*.

Zahnfabrik Wienand Sohne & Co. G.m.b.H. Furnace for ceramic dental products, P (7) 261*i*.

Zaika, R. G., and Piven, A. I. Accelerating the milling of commercial alumina and the casting properties of alumina slip, (6) 224*f*.

Zaininger, K. H. See Revesz, A. G.; Wang, C. C.; Waxman, A.

Zaionts, R. M. See Mikadze, I. S.

Zaitsev, L. M., and Shubina, T. N. Aging of zirconium hydroxides, (5) 192*a*.

Zak, T. J. See Blum, R. T.

Zakharchenko, M. A. See Gontar, K. V.

Zakharchenko, M. A., Gladushchenko, V. A., and Aslanov, S. M. System Li,Ca,Ba‖Cl, (8) 299*d*.

Zakharov, B. M., and Trofimov, M. G. Erosion-resistant coatings made of tungsten carbide and tungsten cobalt carbide, B (5) 204*g*.

Zakharov, G. V. See Mazurov, D. J.

Zakharova, A. D. See Izergina, E. V.

Zalm, P. See van Stratum, A. J. A.

Zamecki, E. R. See Squire, C. F.

Zaminer, C. See Seiter, H.

Zanger, E. A., and Szasz, P. R. Semiconductor wafer pickup and bonding tool, P (11) 378*h*.

Zanio, K. R. Improved CdTe for gamma detection between −100° and +100°C, (10) 355*h*.

Zanoni, L. A. See Heilmeier, G. H.

Zanowick, R. L., Coker, J. E., and Morritz, F. L. Multilayer semiconductor heteroepitaxial structure, P (6) 222*j*.

Zapf, G. Process for the production of sintered articles, P (4) 107*c*.

Zapp, H. R. See Collins, J. H.

Zappia, A. T., and Bough, M. O., Jr. Hollow glassware forming machine, P (6) 212*h*.

Zarebski, J. See Kowalski, Z.

Zavazal, Z. See Bezouska, V.

Zavitsanos, P. D., and Sauer, W. E. Formation of crystalline films by laser evaporation, (5) 181*e*.

Zdanuk, E. J., and Krock, R. H. Method of producing tungsten powder bodies infiltrated with zirconium, P (9) 309*g*. Tungsten-indium powder bodies infiltrated with copper, P (5) 185*h*.

Zecchin, L. Case of the wrong word, (4) 90*d*. Maria Barovier and the "rosette," (4) 90*i*. Two pragmatic views on vasa diatreta (II), (4) 91*a*.

Zednicek, W. See Moertl, G.

Zeidler, W. Preparation of thin film sections, (8) 285*a*.

Zeidler, W., and Ramsden, A. R. Sectioning of friable deposits for microscopic examination, (10) 347*d*.

Zeigler, W. See Knausenberger, W. H.

Zeiringer, R. Piezoelectric pressure transducer, P (11) 378*e*. See List, H.

Zeiss, Carl. See Carl Zeiss-Stiftung.

Zeitsch, K. J. Refractory composites and method of making the same, P (2) 59*e*.

Zeldes, H. See Abraham, M. M.

Zelenka, J., Tichy, J., Chalupa, B., Michalec, R., and Petrzilka, V. Application of neutron diffraction to the determination of the quality of synthetic quartz crystals, (11) 379*i*.

Zelikman, A. N. See Kunev, D. K.

Zellers, J. T., Jr. Method of feeding glass batch material, P (7) 249*d*. Sheet glass manufacturer, P (4) 101*e*.

Zelwer, C. See de Rango, C.

Zemon, S., Zucker, J., Wasko, J. H., Conwell, E. M., and Ganguly, A. K. Parametric amplification of ultrasonic waves in CdS, (6) 235*e*.

Zen, E.-An. Stability relations in aluminum silicate polymorphs, (7) 269*h*.

Zenger, D. H. Determination of calcite and dolomite composition using the air comparison pycnometer, (1) 21*c*.

Zenith Radio Corp. Leadless inverted device forming process, P (11) 377*c*. Miniature ceramic microphone, P (7) 257*d*.

Zenker, K. Residence time of combustion gases in a glass tank, (9) 307*b*.

Zenker, R. O. See Miller, C. F.

Zenobi, G. V., and Szerdahelyi, D. Swiss prefab process used in 14 story building, (4) 102*a*.

Zental, P. Spectrochemical methods for geochemical purposes, (5) 188*f*.

Zentgraf, K. M. Determination of SO_2 in flue gas and desulfurization of flue gas by compounds of alkaline-earth metals, (7) 261*c*.

Zerbes, G. Ferrites with high temperature coefficient of initial permeability, (7) 254*h*.

Zerbst, M., Zschauer, K. H., and Touchy, W. Semiconductor device, particularly for response to variable pressure, P (4) 116*d*.

Zetterstrom, R. B. See Ellis, W. C.

Zettlemoyer, A. C. See Bassett, D. R.; Micale, F. J.

Zettlemoyer, A. C., Iyengar, R. D., and Scheidt, P. Heats of immersion and water sorption studies on bare and silica-coated rutile surfaces, (1) 30*d*.

Zhabotinskii, M. E., Rudnitskii, Yu. P., Tsapkin, V. V., Tsapkina, I. V., and Ellert, G. V. Influence of chemical bond on the luminescence of uranyl in glasses, (2) 49*a*.

Zharov, E. F. See Ved, E. I.

Zhdanov, G. S., and Vertsner, V. N. Determination of the temperature of specimens in the electron microscope, (2) 69*b*.

Zhitkevich, Z. V. See Pavlushkin, N. M.

Zhlinskas, R. P. See Meshkauskas, Yu. I.

Zhukov, O. A. See Abukov, A. A.

Zhukovskaya, E. G. See Bering, B. P.

Zhuravlev, G. I., and Avgustinik, A. I. Theory of the heat resistance of ceramic coatings, B (5) 204*e*.

Ziche, A. Apparatus for checking of impurities, P (11) 370*i*.

Zieber, F. L. See Compton, J. B.

Ziegenhain, W. C. See Acciarri, J. A.

Ziegler, D. L. See Acciarri, J. A.

Ziegler, H. W. See Schmeiser, K.

Zierfuss, H. Heat conductivity of some carbonate rocks and clayey sandstones, (7) 266*c*.

Ziering, L. K. Method for preparing reduced tungsten oxide, P (2) 74*e*.

Zilberman, E. K., and Morin, E. P. Lead-in for devices with a quartz bulb, P (9) 312*e*.

Zil'bershtein, Kh. L., Nenarokov, A. V., and Semov, M. P. Use of electrohydraulic crushing of pure materials for spectroscopic analysis, (2) 71*b*.

Zilokowski, J. See Deren, J.

Ziman, A. D. Adhesion number in tearing off of polydispersed particles, (7) 263*e*.

Zimina, T. N. See Safonov, V. V.

Zimmerman, K. G. See Hill, V. G.

Zinc, A. R., Jr. See Campbell, D. R.; Tomb, W. H.; Wessel, P. E.

Zinliker, W. M. See Kemp, J. C.

Zink, John, Co. Burner assembly producing radiant heat, P (4) 122*h*.

Zinkham, R. E. See Goodwin, R. J.

Zinko, H. See Wagner, J.

Zinn, R. E. Rotating [telescopic] sectioned furnace, P (7) 261*h*.

Zinser, E. J., and Page, J. A. Specific ion electrodes, (6) 227*c*.

Zirngibl, H., Gutsche, W., and Weidmann, W. Vapor phase process for the conversion of metal halides into their oxides, P (4) 126*b*.

Zisman, W. A. Surface chemistry of plastics reinforced by strong fibers, (10) 338*a*.

Zisner, T. See Tagai, Hideo.

Zitova-Nemcova, H. See Litomisky, J.

Zitter, R. N. Saturated optical absorption through band filling in semiconductors, (10) 360*c*.

Zivanovic, B. M. See Ristic, M. M.

Ziver, G. M. Cooking surfaces, P (2) 52*d*.

Zlatanovic, J. Two-component porcelain, (2) 60*h*.

Zlochevskaya, K. M. See Budnikov, P. P.

Zmbov, K. F., Hastie, J. W., and Margrave, J. L. Mass spectrometric studies at high temperatures (XXIV) thermodynamics of vaporization of SnF_2 and PbF_2 and the dissociation energies of SnF and PbF, (10) 356*j*.

Zmbov, K. F., and Margrave, J. L. Mass spectrometric studies at high temperatures (XI) sublimation pressure of NdF_3 and the stabilities of gaseous NdF_2 and NdF, (2) 80*i*; (XII) stabilities of dysprosium, holmium, and erbium subfluorides, (4) 143*d*; (XIII) stabilities of samarium, europium, and gadolinium mono- and difluorides, (5) 196*e*; (XIV) vapor pressure and dissociation energy of silver monofluoride, (6) 234*i*; (XV) sublimation pressures of chromium, manganese, and iron trifluorides and the heat of dissociation of $Fe_2F_6(g)$, (7) 267*a*; (XVI) sublimation pressures for TiF_3 and the stabilities of $TiF_2(g)$ and $TiF(g)$, (8) 294*f*; (XXII) stabilities of tantalum pentafluoride and tantalum oxytrifluoride, (9) 324*i*.

Zmli, V. I. See Nichiporenko, E. P.

Zocchi, M. See Marezio, M.

Zoellner, R. See Krause, E.

Zografou, C. Development of the structure of hard porcelain by the use of mineralizers, (11) 375*i*.

Zoldners, N. G. See Malhotra, V. M.

Zolotovitskaya, E. S. See Nesanelis, M. Z.

Zoltowski, P. Alumina layers prepared with a plasma gun (I) effect of preparation parameters on layer properties; (II) influence of heat treatment on properties of the layers, (9) 304*g*.

Zook, J. D. See Joseph, H. C.

Zook, J. D., and Casselman, T. N. Electro-optic effects in paraelectric perovskites, (2) 76*g*.

Zorin, Z. M., and Churaev, N. V. Observation in polarized light of steplike films of water on a quartz surface, (6) 235*a*.

Zorina, M. L., Milyukov, E. M., and Ushakov, D. F. Influence of the application process on the crystallization of a vitreous crystalline coating, (2) 45*h*.

Zrimsek, A. H., and Vingas, G. J. Waterless molding sand, P (6) 218*i*.

Zschauer, K. H. See Zerbst, M.

Zsolnay, L. M. Comparison of the American and European methods of manufacturing high voltage porcelain insulators, (1) 15*f*.

Zsutty, T. C. Beam shear strength prediction by analysis of existing data, (2) 68*j*.

Zubekhin, A. P. See Ponomarev, I. F.

Zubov, V. I. See Tul'chinskii, V. B.

Zuca, S. See Grjotheim, K.

Zucker, J. See Zemon, S.

Zuckerman, J. L. See Smith, D. L.

Zuegel, M. See Hoftmeister, W.

Zuleeg, R. Space-charge-limited current triode device, P (2) 66*h*.

Zuleeg, R., and Braunstein, M. Bistable two or three terminal double injection switching element, P (10) 344*c*.

Zumer, S. See Blinc, R.

Zunkel, A. D., and Larson, A. H. Slag-metal equilibria in the Pb-PbO-As_2O_3 system, (1) 37*a*.

Zupan, N. M. See Probst, R. O.

Zur Strassen, H. Process for the production of a low alkali content cement, P (9) 304*d*.

Zussman, J. (editor). Physical Methods in Determinative Mineralogy, B (6) 241*e*.

Zvanut, C. M. Method for making a coated silica fiber and product produced therefrom, P (6) 213*c*.

Zwicker, W. K. See Levitt, R. S.

Zysk, E. D., Osovitz, E. E., and Stephans, R. W. Noble metal thermocouple having base metal compensating leads, P (9) 315*j*.

Zyuzin, N. I. See Sobolev, N. V., Jr.

SUBJECT INDEX TO CERAMIC ABSTRACTS FOR 1969

The number in parentheses refers to the monthly issue of *Ceramic Abstracts;* the number following is the page number. The letter B or P preceding the reference number indicates an abstract of (B) a book, bulletin, or separate publication or (P) a patent. The italic letter following the page number indicates position on the page. For more complete indexing of papers published in the *Journal of The American Ceramic Society* and the *American Ceramic Society Bulletin,* see indexes to the *Journal* and the *Bulletin.*

Ablation, shield thickness, measuring, P (7) 261*a*.
Abrading apparatus. See *Grinding apparatus.*
Abrasion, resistance testing apparatus, P (2) 71*h*.
Abrasives. See also *Carbides; Diamonds; Grinding apparatus; Polishing apparatus; Silicon, carbide.*
alumina, grains, treating with iron nitrate and products made, P (5) 169*h*.
market study, (6) 205*f*.
-spinel composite material, P (7) 243*h*.
analysis, role in keeping blast cleaning variables under control, (5) 169*h*.
article, for use in tumbler-type grinders, P (10) 335*g*.
articles, porous, P (4) 90*a*.
barrel finishing media, P (6) 205*h*.
belts, P (6) 205*g*.
belts condition stainless, (5) 169*f*.
cleaning compositions, P (11) 367*f*.
cloth and product, coated, reducing friction on, P (4) 90*a*.
coated, adhesive for, (4) 89*f*.
cutting device, P (7) 243*h*.
cutting tools, contoured, P (7) 243*i*.
diamond tool, P (7) 243*i*.
disk, P (5) 169*f*.
disk, with glass fiber reinforcement, P (1) 1*j*.
engineering, at NCR, (8) 273*g*.
ferrous, used in hydraulic jet drilling, P (4) 89*i*.
for finishing ball tracks, (5) 169*g*.
fixed, for grinding glass, (11) 370*d*.
forming on resiliently yielding bases, process and product, P (1) 1*i*.
glass impact beads, market for, (7) 243*f*.
grains, diamond and cubic BN, coated with photopolymerized material, P (2) 43*g*.
granular materials, binary mixtures, packing density of, (1) 1*i*.
high quality, principles for production, (1) 1*f*.
honing state-of-art, adaptive control advances, (8) 273*f*.
industry, recent developments, (4) 89*f*.
and machines in bearing industry, (2) 43*f*.
metal sheet, P (1) 1*h*.
micro particle size distribution, practical determination by sedimentation, (10) 347*d*.
processes, expands investment casting operation, (5) 169*f*.
production improvements with Bakelite binders, (4) 89*f*.
shape in extruded grain, (11) 367*h*.
in sheet form, coated, P (1) 1*g*.
sheet material, flexible, butt joint for, P (1) 1*g*.
shot peening with glass best for thin materials, (7) 243*g*.
sintered α-Al_2O_3 and ZrO_2, product and process, P (10) 335*h*.
surface of revolution, accurately producing, P (7) 243*j*.
tool, P (5) 169*f*.
wheels. See *Grinding apparatus.*
Absorption, atomic, method for determination of Zn and Mg in glasses, (2) 48*e*.
bands, pressure shift, in $MgO:Fe^{2+}$ and the dynamic Jahn-Teller effect, (10) 359*a*.
CO_2 laser radiation, in semi-insulating GaAs, (9) 318*b*.
changes in Fe-doped CdTe under influence of high electric fields, (4) 111*f*.
coefficient of GaAs at microwave and millimeter wave frequencies, (1) 24*g*.
cross sections, for Al_2O_3, temperature dependence of, (1) 39*f*.
electric-field-induced infrared, in diamond, (2) 76*h*.
electro-, of CdS, (4) 134*g*.
in rutile, (2) 76*b*.
of ZnTe films, (10) 344*a*.
ESR, in evaporated BaO films, (8) 291*g*.
and emission phenomena in NaCl crystals with high concentration of copper, (6) 230*f*.
far-infrared, in ferrimagnetic spiral $MnCr_2O_4$, (2) 77*c*.
far-infrared, in fused quartz and soft glass, (9) 305*e*.
hydroxide, for gasometric determination of carbon in sediments, (1) 21*a*.
infrared, bands, of molten alkali-metal nitrates, (11) 385*h*.
Absorption, infrared *(continued)*
of calcite, pressure dependence, (10) 359*i*.
by hydrogen bonds in single crystal KH_2PO_4, KD_2PO_4, and KH_2AsO_4, (2) 79*b*.
intensity of ν_3 vibration of UO_2^{2+} ion in nitrate and thiocyanate media, (9) 323*j*.
multiphonon, in ZnO, (4) 145*e*.
light, of semiconductive phase in ZnO-In_2O_3 system, (10) 356*h*.
line (n = 1) of Cu_2O, (1) 24*g*.
line widths, R, R', and B, in ruby, (2) 82*i*.
"mirror" and fluorescence, in MgO, (1) 32*i*.
optical, in Cr-doped high resistivity GaAs in 0.6 to 1.5 eV range, (1) 33*g*.
γ-induced, in silicate glasses containing Ti, (6) 209*c*.
modulation, at intrinsic edge by acoustoelectric domains in n-GaAs, (1) 33*b*.
of neutral vacancy in diamond, (10) 357*j*.
of neutron-irradiated graphite, (2) 81*e*.
studies of color centers in heavily irradiated MgO, (8) 295*g*.
study, of Mo^{3+} in phosphate glass, (1) 7*b*.
of tetrahedral Fe^{2+} ($3d^6$) in cubic ZnS, CdTe, and $MgAl_2O_4$, (4) 147*h*.
in ZnO crystals, due to Co^{2+}, (2) 81*d*.
in oxygen-niobium system at very low pressure, (4) 126*e*.
phonon-assisted optical, in irradiated MgO, (2) 81*f*.
saturated optical, through band filling in semiconductors, (10) 360*e*.
spectra. See *Spectra.*
ultrasonic, in lanthanide sulfates, (8) 300*c*.
ultraviolet, of high purity soda-silica glass, effect of iron, (1) 6*b*.
Acids. See also specific types.
α-amino, sorption by copper montmorillonite, (7) 269*e*.
carbonic, in gas mixture, method and device for determining, P (1) 22*f*.
dodecamolybdosilicic, with organic bases, precipitation, (4) 120*e*.
EDTA, use in determination of Al_2O_3 in soda-lime-silica glasses, (7) 260*g*.
fatty, unsaturated, clay catalyst for polymerization of, P (4) 124*i*.
formic, mechanism of dehydration decomposition, over Al_2O_3 and SiO_2, absorption measurement during catalytic reaction, (8) 295*a*.
organic, effect on gypsum plaster setting: III, citrates, (2) 44*j*.
organic, sedimentation activity, in Al_2O_3 suspensions, (4) 140*j*.
orthotelluric, thermal decomposition, (5) 182*c*.
pentafluosilicic, (6) 235*f*.
silicic, and silicates, treating, P (5) 191*a*.
Acmite, high pressure stability, (9) 322*f*.
stability in presence of water, (9) 329*i*.
Acoustics. See also *Insulation, acoustical; Sound.*
acoustoelastic effect in vitreous silica, Pyrex, and T-40 glass, (11) 369*d*.
amplified flux, frequency shifts during growth in CdS, (8) 292*c*.
detection of minute particles suspended in gaseous atmosphere by, apparatus, P (6) 227*g*.
loss, low-temperature, in magnetite, electronic mechanism for, (1) 27*d*.
properties, of vitreous silica, factors influencing, (9) 305*d*.
Actinide, compounds, electrical and thermal properties, (10) 352*h*.
compounds, electrical and magnetic properties, (10) 360*d*.
halides, B (11) 389*e*.
higher sulfides, study, (1) 38*e*.
oxides, producing dense particles of, usable as fuels for nuclear reactors, P (1) 14*e*.
Activation, mechanical, of boehmite, gibbsite, and corundum, (4) 126*j*, 127*a*, *c*.
Additives, for lowering freezing temperature of cement mortars, selection by plastograms, (4) 92*b*.
in portland cement concrete, (5) 170*c*.
for production of spheroidal graphite cast iron consisting mostly of calcium-silicon, P (4) 93*i*.
retention in Y_2O_3, Gd_2O_3, La_2O_3, and α-Al_2O_3, (5) 199*e*.
soluble inorganic admixtures, effect on early hydration of portland cement, (2) 44*i*.
Adherence. See also *Enamels.*
evaluation of direct-on cover coat enamels, (1) 4*i*.
Adhesion, between basic refractories and portland cement clinker, (1) 12*d*.
enamel to metal, investigation of test for measurement, (1) 5*e*.
force, between spherical solid particles, effect of capillary liquid, (1) 27*e*.
number, in tearing off of polydispersed particles, (7) 263*e*.
strength of clay slurries to window glass, as function of slurry pH, (11) 370*d*.
testing of sheet ground-coat enamels, (1) 5*c*.
Adhesives, to adhere ceramic material to metal, P (8) 282*a*.
for coated abrasive, (4) 89*f*.
Adsorption, adsorbate, on surface coverage, dependence of heat capacity on BET theory assumptions, (1) 26*i*.
adsorbent charge, effect on competitive adsorption of divalent organic cations by layer-silicate minerals, (8) 290*j*.
adsorbents, carbon as, (7) 261*j*.
of alkylammonium cations by montmorillonite, (7) 263*f*.
on alumina, for lowering of surface energy, (1) 31*j*.
of benzene by heat-treated porous glass, (5) 173*c*.
of $Ca(OH)_2$ by montmorillonite and kaolinite, (1) 24*g*.
of calcium sulfonate on $CaCO_3$, crystal structure effects in, (1) 26*e*.
of CO_2 and water on MgO, infrared study, (8) 293*c*.
of clay mineral and colloidal hydrous Al_2O_3, electron microscopy investigation, (1) 33*e*.
-coagulation reactions of Zn(II) hydrolyzed species at ZnO-water interface, (1) 24*i*.
of colloid electrolyte micelles by inhomogeneous porous materials, (7) 263*h*.
of copper acetylacetonate on anatase and silica gel and of diphenylpicrylhydrasyl on silica gel, susceptibilities from 1°–4°K, (5) 200*h*.
effect on indentation deformation of nonmetallic solids, (4) 133*b*.
effect on strength of compacts of various oxides and salts, (2) 82*h*.
of ethanol and tertiary butanol on γ-Al_2O_3, (4) 126*f*.
gaseous, influence on metal-$BaTiO_3$ contact, (4) 140*a*.
of hydrocarbons on clay minerals—adsorption of benzene, (10) 349*h*.
krypton, low-temperature, for determination of specific surface area, (1) 27*f*.
of krypton and xenon by crystals of zeolite LiX and NaX, dependence on pressure and temperature, (4) 131*c*.
methanol vapor, on silica and soda-lime-silica glass, (6) 210*c*.
methylene blue, specific surface and dry strength by, (1) 15*d*.
in micropores: I, theoretical representations, (7) 263*h*.
model, for contact angle and spreading, (5) 191*i*.
of N_2 at −196°C on nonporous Al_2O_3, (10) 360*j*.
of orthophosphate on ternary borate glasses, radiochemical studies, (5) 173*j*.
oxygen, on impure ZnO, infrared study, (10) 355*g*.
in oxygen-niobium system at very low pressure, (4) 126*e*.
of ozone on silica gel, (1) 24*i*.
physical, on porous glass beads, (4) 96*h*.
polymer, effect on electrokinetic stability of dilute clay suspensions, (1) 28*b*.
at rutile-solution interface: I, thermodynamic and experimental study, (5) 191*i*.
solute, for determination of pore size distribution of powders, (6) 225*h*.
studies on hydrated and dehydrated silica, (5) 191*j*.
thermodynamics, of interaction of water and silica powders, (4) 126*g*.
of water, on NaCl, effect of prior exposure to HCl, CO_2, and water vapor, (4) 126*h*.
of water vapor, by inorganic oxides, (1) 24*j*.
Agglomerates, of light ash, installation and method for treatment at high temperature and cooling using fluidized layer, P (5) 186*a*.
microsphere glass, P (11) 371*j*.
moist, tensile strength, (7) 260*d*.
Agglomeration, adsorption-, reactions of Zn(II)

Agglomeration *(continued)*
hydrolyzed species at ZnO-water interface, (1) 24*i*.
of colloidal alumina dispersions by adsorbed surfactant ions, (1) 25*a*.
for determination of SiO_2, (for high-SiO_2, aluminosilicate, and aluminous materials), (10) 347*i*.
of MgO, high purity, (11) 372*h*.
method and apparatus, P (6) 225*e*.
of silica dispersions by iron(III), (1) 25*b*.
structure formation in aqueous suspensions of clay minerals, effect of duration of magnetic field action on, (4) 132*c*.
structures, mechanism of formation in aqueous dispersions of tremolite and hydromica under action of ultrasound, (7) 269*b*.
time, as function of electrolyte concentration —modified empirical relationship, (6) 239*b*.
of vitrifiable masses, and products, P (9) 308*b*.
Agglutination, element processes, phenomenology and geochemistry, (1) 34*j*.
Aggregates, bloated, color coating, P (8) 278*h*.
for building materials, especially road surfacing, P (6) 207*b*.
carbonized shaped cellulose crystallite, P (1) 14*i*.
compacted, for making structural elements, P (6) 214*f*.
Danish, for preparation of mortar bars, (4) 91*d*.
geometric characteristics, evaluation by particle index test, (5) 187*i*.
lightweight, in Canada, (4) 101*i*.
method and apparatus for production, P (2) 54*f*.
production at Freeport Brick, (4) 101*h*.
raw materials for, in Appalachian Region, Alabama, and Georgia, (8) 278*h*.
manufacture from siliceous materials, P (1) 11*g*.
of powdered materials, apparatus for forming, P (2) 67*f*.
reactions, in portland cement concrete, (6) 206*g*.
size, testing apparatus and process, P (7) 262*d*.
white, grained, with devitrifiable glassy material as component, P (6) 207*b*.
whitish granular, for building purposes from crystallizable vitreous material, P (11) 371*i*.
Aging, with ac, dc, and zero fields of complex high permittivity dielectric, (2) 61*c*.
characteristics of lime, (8) 287*a*.
effect on strength of E-glass fibers, (4) 95*c*.
of gypsum plaster, (11) 367*j*.
hydrothermal, of synthetic aluminosilicate gels, (7) 266*j*.
mechanism in polycrystalline $BaTiO_3$, (8) 294*i*.
in Nb(Cb)-Ti-O superconductors, (6) 230*f*.
oxidation vs. electrical, of sintered SiC heater elements, (2) 57*a*.
in tetragonal ferroelectric $BaTiO_3$, (6) 220*c*.
thermal, effect on physical properties of activated alumina, (1) 20*a*.
of Zr hydroxides, (5) 192*a*.
Air, compressed, drying, (2) 67*d*.
flow, determination, (1) 20*h*.
pollution, control in plant, (4) 117*j*.
and glass manufacturing, (10) 337*f*.
modern method of control, and evaluation of industrial hygiene in ceramic industry, (9) 333*e*.
Aircraft ceramics. See *Cermets; Spacecraft.*
Akermanite, stronium copper, distorted tetrahedra in, (6) 231*i*.
Albite, breakdown at depth in earth, investigations, (4) 141*b*.
synthesis at 250°–700°C, (9) 331*h*.
thermodynamics of disordering process in, (6) 239*h*.
Alcohol, gas phase autophobicity, adsorbed on alumina, (1) 30*f*.
Alite, crystallization, in portland cement clinkers, effect of additives, (1) 2*g*.
mixture, behavior during firing, influence of burning atmosphere, (4) 91*j*.
Alkaline earths. See also specific types.
aluminates, Eu(II) activated, fluorescence, (9) 321*f*.
aluminates, of type MAl_2O_4, activated by divalent Eu, fluorescent properties, (9) 321*g*.
compounds, desulfurization of flue gas by, (7) 261*c*.
dicarbides, vaporization, (5) 202*i*.
fluorides, H and F bands in, (10) 354*g*.
fluorides, hyperfine interactions of F centers in, (5) 195*i*.
hexaboride rods, zone melting, (8) 301*a*.
ions, differential kinetic analysis using stopped-flow spectrophotometry, (8) 284*j*.
metal sulfates and nitrates, effect on gas content of glass, (6) 208*h*.
oxides, chemisorption on: I, surface centers and fast irreversible oxygen adsorption on irradiated MgO, CaO, and SrO, (4) 128*d*; II, intrinsic bulk defects and adsorption of oxygen on MgO, CaO, and SrO, (8) 289*g*.
oxides, Faraday rotation studies of *F* centers in, (10) 353*b*.
stromtium phosphate compounds, Eu^{2+} activation in, (8) 292*d*.
systems. See *Systems.*
yttrate, luminescent materials [rare earth activated], P (9) 314*d*.
Alkalis. See also specific types.
chlorides, electrical conductivity, anion contributions to, (4) 126*e*.
effect in silicate glasses, (2) 51*h*.

Alkalis *(continued)*
effect on transition of γ-Fe_2O_3 into α-Fe_2O_3, (11) 384*c*.
fluoride mixtures, binary liquid, enthalpies of mixing in, (8) 292*b*.
halides. See *Halides, alkali.*
hydroxides, structure: III, microwave spectra of RbOH and RbOD, (10) 361*d*.
iodide crystals, paramagnetic resonance spectra of O^- trapped in, (8) 296*b*.
metal, aluminate tetrahydrate crystals, P (5) 191*f*.
borides, P (1) 24*d*.
carbonates, preparation from corresponding sulfates or sulfides, P (1) 24*c*.
fluorides, interaction with scandium fluoride, (7) 267*e*.
in glasses, electron-probe microanalysis, (11) 369*j*.
nitrates, pure, vibrational spectra and structures, (5) 203*c*.
phosphates, P (5) 191*a*.
salts, separation, P (4) 124*f*.
silicates, thermal decomposition, inhibiting, P (4) 124*c*.
sulfate, P (5) 191*b*.
thio- and seleno-compounds of transition metals: IV, of platinum, (5) 192*c*.
titanates, converting into their pure TiO_2 pseudomorphs, P (5) 191*e*.
nitrates, $LiNO_3$+$NaNO_3$+KNO_3, molten polarographic studies in: I, half-wave potential and diffusion coefficients, (8) 296*j*.
polyaluminates, structures, (4) 156*e*.
retention by calc-alkalic rhyolites during crystallization and hydration, (10) 359*h*.
system. See *Systems.*
Alloys, Al, dispersion strengthened, time and temperature dependence of hardness of, (9) 332*b*.
Al, binary, in contact with Be, B_4C, and graphite, wetting of, (6) 207*i*.
Al-Al_2O_3, blended and ball-milled, physical and mechanical properties, discussion, (1) 12*a*.
ductility, influence of microporosity, (9) 323*f*.
high temperature ductility, influence of grain size, (4) 140*b*.
SAP-type, oxide growth by hot stage transmission electron microscopy, (1) 34*e*.
Al_2O_3-chromia alloys, twist boundaries in, (4) 162*i*.
based on tungsten and niobium silicides, oxidation resistance, (6) 216*h*.
B-C-S, P (8) 279*j*.
binary, ternary, and quaternary of type AuCu and $AuCu_3$, order-disorder transformations for, (2) 81*f*.
BiSb, with small antimony content, electrical properties, (5) 181*a*.
Bi_2Te_3-Sb_2Te_3-Sb_2Se_3 pseudoternary, thermoelectric properties, effects of growth rate, (5) 194*b*.
for brazing silicon nitride material, P (6) 217*f*.
Cr-Re, ductile, high-temperature oxidation, (1) 30*f*.
Cu-Cu_2O eutectic, mechanical and electrical properties, (9) 324*j*.
Cu-Au, oxidation in CO_2 at 1000°C: I, linear kinetics, (4) 148*b*.
cross-substitutional, of CdTe, (2) 83*f*.
gold, for attaching lead to semiconductor body, P (6) 221*c*.
hard, titanium carbide, sintered, P (9) 309*e*.
for improving graphite properties, P (7) 252*b*.
Fe-Cr, binary, oxidation, (4) 148*c*.
carburization during oxidation in dry CO_2, (4) 127*f*.
oxidation kinetics, effect of oxide volatilization, (1) 28*b*.
Fe-Cr-Ni, liquid, nitrogen solubility in, (6) 235*h*.
Fe-Mn, internal oxidation, (4) 140*h*.
Fe-Ni-Cr, compatibility relationships with uranium carbides, (4) 129*f*.
$Pb_{1-x}Sn_xSe$, phase studies, (6) 236*d*.
magnet, directionally solidified permanent, with aligned ferromagnetic whiskers, P (6) 221*g*.
for metallizing ceramics, P (2) 64*c*.
nickel base, for engines, P (9) 304*h*.
Ni-20Cr-2ThO_2, creep and creep fracture, (1) 26*d*.
Ni-Co, substructures in oxide scales on, (4) 157*h*.
niobium, Fe_2 and SU_{16}, development and testing of protective coatings on, (4) 103*e*.
NbC-Fe, NbC-Ni, and NbC-Co, liquid-phase sintering of, carbide grain growth during, (10) 350*j*.
noble metal, adapted to receive porcelain cladding, artificial dental constructions, and preparation, P (4) 109*b*.
sintered, of Al with dispersed Al_2O_3, quenched-in resistivity in, (1) 17*j*.
sintered two-phase, crack formation in, (8) 289*g*.
superconductor quaternary, with high current capacities and high critical field values, P (4) 117*c*.
Ta-base, slurry coatings for, (1) 5*g*.
of W-LaB_6 system, preparation and physical properties, (7) 268*b*.
WC-10% (Ni-Fe), properties, (4) 151*j*.
WC-Co, fracture in, study by optical microscopy, (1) 32*e*.
WC-TaC-Co, abnormal structure of TaC phase in, (4) 102*i*.

Alloys *(continued)*
WC-TiC-10%Co, sintered, properties, effect of annealing, (4) 103*h*.
two-phase, in NbC-Co system, microstructural development during liquid-phase sintering of, (8) 295*d*.
U-C, high-temperature compressive creep and hot extrusion, (4) 138*d*.
U-Si, δ-peritectoid reaction, effect of carbon, (8) 291*c*.
Zr-2.7 wt% Nb, oxidation properties in temperature range 300°–500°C, (4) 148*h*.
Zr-O_2 single crystals, plastic deformation in range 77° to 950°K, (4) 149*j*.
Zr-O and Zr-Si, kinetics and evaporation mechanisms during electron beam melting of, (9) 309*e*.
ZrB_2-Mo, sintering characteristics, (2) 57*j*.
ZrC-graphite, arc-cast, elastic behavior, (11) 384*g*.
Alumina. See *Aluminum, oxide.*
Aluminates. See also *Alkaline earth.*
purification of solutions containing, P (10) 349*e*.
rare earth, (4) 152*d*.
reaction with tobermorite gel, (4) 152*i*.
solutions, decomposition, induction period during, (1) 30*j*.
solutions, decomposition rate, influence of radiations, (1) 31*a*.
Aluminosilicates, chemistry of radical ion formation on, (5) 192*h*.
crystalline, catalysts containing, methods of treating and using, P (6) 229*d*.
chemistry: IV, factors affecting formation of zeolites X and B, (5) 192*g*.
conversion of clays to, and catalysts from, P (6) 229*c*.
hydrocarbon separation process employing, P (11) 382*a*.
lithium-containing, P (4) 124*d*.
and oxygen, disproportionation of alkyl aromatics with, P (7) 262*g*.
crystallizing, P (5) 191*a*.
separating fluorine from, by pyrohydrolysis, simple apparatus for, (6) 227*a*.
zoisite, muscovite, anorthite, and orthoclase, heats of formation, critical evaluation, (4) 130*b*.
Aluminum, adherence of enamel to, (1) 5*b*.
-Al_2O_3-Sb junctions, tunneling characteristics, (8) 300*a*.
Al(I) fluoride (*g*) enthalpy of formation and entropy, (1) 29*g*.
AlCl(*g*), reaction with MgO(*c*) and heat of formation of $MgAl_2O_4$(*c*), (4) 152*d*.
$AlCl_3 \cdot 6H_2O$, pure crystals, recovery, and production of Al_2O_3 product from, P (2) 74*f*.
Al_2GeO_5, high pressure phase, (7) 266*d*.
$5Al_2O_3 \cdot H_2O$ (tohdite), formation conditions, (1) 30*b*.
Al$K\beta$ X-ray emission band among aluminum containing silicates and Al oxides, structural and chemical effects, (11) 387*g*.
Al_6SiO_5, polymorphs, transition metal content, (9) 332*c*.
Al_6SiO_5 polymorphs, coexistent, minor element content, (9) 324*h*.
$Al_2Si_2O_8$, mixed series (Ca, Sr), (10) 357*g*.
anodic oxidation, (10) 350*c*.
antimonide, high-temperature heat contents and heats of fusion, (10) 362*g*.
borates, rare-earth, nonstoichiometry in, (4) 146*h*.
borohydride, molecular structure, (8) 295*i*.
chloride, anhydrous, preparation, (10) 348*g*.
determination by fast neutron activation in thin films, (8) 280*h*.
electrolysis, reoxidation in, (1) 32*e*.
equilibrium with nitrogen in liquid 18% Cr-8% Ni stainless steel, (6) 232*c*.
-europium intermetallics, magnetic properties, (4) 110*f*.
fiber-reinforced, fatigue, (1) 4*b*.
films. See *Films.*
and fireclay, effect in molten steel on dissociation of Zr, (4) 103*i*.
fluoride, effect on formation of phases during calcination of Grossalmerode clay, (5) 199*b*.
pure basic, electrolytic preparation, (1) 23*f*.
vapor pressure, vapor dimerization, and heat of sublimation using entrainment method, (5) 202*i*.
hydride, thermodynamic properties, (4) 161*j*.
hydroxide, amorphous, influence on hydration of tricalcium aluminate, (9) 323*d*.
dehydration products, (4) 135*h*.
gelatinous and crystalline, calcination, surface chemistry of, (9) 330*f*.
influence on hydration of tricalcium silicate, (9) 323*a*.
thermal splitting of H_2 from, (6) 239*f*.
irradiated silica-fiber-reinforced, properties, (10) 341*i*.
micro and semimicro amounts, determination using fluoride activity electrode, (8) 284*i*.
nitride, analysis: I, determination of N and Al after decomposition under pressure with hydrochloric acid, (6) 225*f*.
nitride, sintered masses, P (7) 252*h*.
ores, treatment, for production of purified Al_2O_3, P (5) 191*b*.
oxalate, thermal decomposition, thermo-gravimetric and X-ray analysis study, (4) 160*j*.
oxide. See also *Boehmite; Corundum; Refractories.*
abrasive grains, treating with iron nitrate, and products made, P (5) 169*h*.

Aluminum, oxide *(continued)*
activated, physical properties, effect of thermal aging on, (1) 20*a*.
with additives, reactive hot-pressing, (8) 284*g*.
adsorption relations: III, adsorption of ethanol and tertiary butanol on γ-Al_2O_3, (4) 126*f*.
agglomerates, P (4) 124*f*.
a-, boundary surfaces: I, arrangement of adsorbed monocarboxylic molecules on, (2) 75*a*; II, sedimentation activity of organic acids in Al_2O_3 suspensions, (4) 140*j*.
a-, enthalpies, high-temperature adiabatic drop calorimeter for measurement between 330° and 1700°K, (5) 195*b*.
a-, formation from transient alumina, role of water vapor in, (1) 36*g*.
a-, high-resolution measurements of diffusion of inert gas in, (8) 293*c*.
a-, Mn-doped single crystals, formation from gas phase, (7) 265*j*.
a-, monohydrate, production, P (4) 125*j*.
a-, polycrystalline, VRH approximation and elastic moduli, (5) 203*d*.
a-, powder, high pressure densification, (11) 373*c*.
a-, retention of additives in, (5) 199*e*.
a-, single crystal, chemical polishing using silicon, (2) 75*c*.
a-, single crystals, irradiation-induced macroscopic growth, (4) 141*h*.
a-, single crystals, neutron-irradiated, transmission electron microscopy, (4) 162*f*.
a-, single crystal ribbons, growing, P (5) 186*d*.
a-, whiskers, growing, P (2) 59*c*.
a-, whiskers, room and elevated temperature strength and structural characteristics, (6) 216*c*.
a-, whiskers, X-ray microtopographs, (7) 270*f*.
a-, (0001) face, LEED studies, (7) 267*i*.
amorphous, P (2) 74*a*.
anhydrous, method and means for producing, P (2) 74*c*.
-based ceramics, reduction and nitridation reactions in, (1) 13*a*.
β-, in α-Al_2O_3 ceramics, formation and stability, (10) 354*d*.
β-, crystal structure, (6) 231*h*.
β-, and related phases, critical evaluation of literature data on: I, phase equilibria and characterization of, (9) 319*a*.
bodies, fabrication, uses, and properties, (2) 59*i*.
bodies, sealing to metals, P (1) 18*d*.
ceramics, densification, (4) 131*a*.
ceramics, pure, electrical properties, influence of thermal neutron radiation, (2) 63*a*.
ceramics, substrates and "snapstrates," (7) 255*c*.
ceramics, surface resistivity, factors affecting, (2) 62*b*.
cobalt in, determination of trace amounts by atomic-absorption spectroscopy, (6) 226*a*.
colloidal dispersions, aggregation by adsorbed surfactant ions, (1) 25*a*.
colloidal hydrous, mutual adsorption with clay minerals, electron microscopy investigation, (1) 33*e*.
commercial, accelerating milling of, and casting properties of Al_2O_3 slip, (6) 224*f*.
commercial ceramics, mechanical properties, (2) 56*c*.
commercial materials, at 9368 MHz, dielectric properties, (2) 62*g*.
content, available, in bauxite from "Onverdacht" Surinam, quantitative analysis, (6) 227*e*.
crystal, growth by flux-fusion method, (10) 346*f*.
crystals, impurity deposits on, (10) 355*i*.
crystals, morphology, (10) 357*b*.
crystals, preparation from vapor phase reaction by monitoring spectral scattering of light, P (9) 317*a*.
delta and theta, under hydrothermal conditions, (8) 290*j*.
densification by hot-pressing, (4) 131*b*.
density and lattice parameters, effect of low temperature neutron irradiation and 20°–400°C annealing on, (4) 133*a*.
dissolution in carbon-saturated liquid Fe, (10) 340*h*.
extraction by autoclave precipitation of basic sodium aluminum sulfate, (2) 72*i*.
extraction from bauxite, P (1) 23*h*; P (4) 124*i*.
films. See *Films*.
freezing, volume change, (4) 163*i*.
freezing point measurement with solar furnace, (7) 266*d*.
γ-, incorporation of heterogeneous ions into, (6) 233*g*.
γ-, and SiO_2-Al_2O_3, surface "acid" sites on, effect of fluoride, (8) 291*e*.
gas phase autophobicity of alcohols adsorbed on, (1) 30*f*.
glass bonded, P (10) 339*a*.
growth under neutron irradiation, (4) 137*e*.
heat of immersion into aqueous sodium dodecyl sulfonate solutions, (1) 30*c*.
high, ceramics, BaO glasses in, (10) 343*d*.
high, minerals, aqueous solubility studies, (8) 288*j*.
high, shapes, casting, (10) 340*g*.
high density, P (11) 382*a*.

Aluminum *(continued)*
high purity, producing from Al-bearing acidic sulfate solutions, P (7) 263*a*.
high purity refractories, compressive creep of, (8) 278*j*.
high surface area, and catalyst composite, P (4) 124*b*.
hot-pressed, dielectric properties, (1) 27*h*.
hot-pressing, production of complicated shapes by, (11) 379*h*.
hot-working: I, primary recrystallization and texture, (11) 385*f*.
hydrate, new, with structure of β-alumina, (2) 80*i*.
hydrate filter cake, viscosity reduction, P (2) 74*h*.
hydrate powders, reaction with NaOH, (4) 152*b*.
industry, review, (4) 123*d*.
kappa, P (8) 288*e*.
layers prepared with plasma gun: I, effect of preparation parameters on layer properties: II, influence of heat treatment on properties, (9) 304*g*.
liquid, (molten corundum and ruby), electrical conductivity, (4) 134*d*.
lowering surface energy by adsorption on, (1) 31*j*.
mechanism of decomposition of formic acid over, (5) 193*g*.
mechanism of dehydration decomposition of formic acid over, (8) 295*a*.
metal/, interfaces, strength, (9) 330*j*.
microwave dielectric constant, at 375 kbars, (9) 311*a*.
n-,·MO oxides, reduction, contribution to study of phases obtained during, (9) 318*h*.
neutron-induced damage in, (8) 295*c*.
outgassing in vacuum at 540° and 870°C, (6) 220*h*.
particles, caustic leach treatment to improve strength properties, P (11) 382*i*.
polycrystalline, changes induced in, by fast neutron irradiation, (4) 128*f*.
polycrystalline, istotropic elastic moduli, pressure and temperature dependences of, (7) 268*e*.
polycrystalline, transgranular and intergranular fracture in, (11) 388*c*.
porous polycrystalline, tensile creep, (2) 84*c*.
powder, ultrafine active, compaction, effect of gaseous adsorbates, (7) 253*g*.
pretreatment, dependence of rheological and technological properties of suspensions on, (4) 123*i*.
production, P (6) 229*a*.
production from dawsonite, P (11) 382*j*.
proton relaxation in liquids sorbed on, (5) 199*f*.
pure, sintering, microstructural changes during, (5) 177*g*.
radiation-induced molecule-ion in, theory of optical and magnetic properties, (10) 362*c*.
rate of dissolution in molten iron oxide, (4) 152*i*.
rate of surface hydration on, (4) 152*a*.
reaction with CaCl₂, (6) 237*a*.
recrystallized, corrosion by fluoride melts, (5) 176*i*.
relative energies of [$\bar{1}$100] tilt boundaries in, (1) 36*c*.
removal of fluorine from, by steam, P (8) 288*c*.
ρ-, and alumina gel, hydration and crystallization in aqueous solutions of various basic reagents, (4) 138*j*.
Rh-activated, fluorescence, (4) 110*g*.
separation of red mud from, P (8) 288*b*.
shock compression, material strength effect in, (6) 234*i*.
silico-, amorphous, structure and properties: II, Lewis and Bronsted acid sites, (1) 38*j*; III, hydrated and transition aluminas, (4) 156*a*.
·SiO_2 minerals, transformation behavior, (11) 388*e*.
-SiO_2-P_2O_5 alkaline compositions, hydrothermal crystallization, (1) 26*a*.
/SiO_2 reaction, effect of moisture, (9) 320*i*.
single crystal, defect diffusion in, (8) 290*i*.
single crystals, doped, influence of valence state of added impurity ions on observed color in, (9) 323*g*.
single crystal, neutron damage in, (1) 33*a*.
sintered, effect of fast neutron irradiation in, (4) 132*e*.
sintered, thermoluminescence, (10) 363*a*.
sintered bodies, modulus of rupture investigations, (2) 56*j*.
sintered materials, wear properties, (1) 13*e*.
in soda-lime-silica glasses, determination using EDTA, (7) 260*g*.
spectrophotometric determination, (4) 120*b*.
spheroidal, P (4) 124*i*.
-spinel composite material, P (7) 243*h*.
surface grain growth, effect of metal oxides, (1) 28*a*.
temperature dependence of Mie scattering and absorption cross sections for, (1) 39*f*.
thermal stability, (4) 163*f*.
thin sheets, without impurities as binder, (11) 374*c*.
-titanate ceramics, dielectric properties, (8) 281*b*.
treatment, P (1) 14*a*.
in vacuum ultraviolet, optical properties, (9) 326*e*.
:V^{4+}, far-infrared spectrum, (8) 292*f*.

Aluminum *(continued)*
very pure finely dispersed, preparation from triethylaluminum, (6) 236*j*.
wetting by molten Al and other metals, (10) 363*b*.
whiskers, tension testing, (5) 188*h*.
white fused, P (2) 74*b*.
-ZrO_2, phase equilibrium diagram, and examination of new phase of 99Al_2O_3-1ZrO_2 (ε-Al_2O_3), (2) 81*b*.
oxygen in, determination by means of 14 MeV neutrons with account of flux attenuation in sample, (6) 225*h*.
phosphate, as hardener for water glass cements, P (8) 274*b*.
phosphate, for retarding portland cement hardening, P (2) 45*f*.
phosphide, single crystals, vapor growth, (1) 40*a*.
synthesis and solution growth, (2) 83*e*.
vapor phase growth and properties, (10) 363*g*.
-porcelain enamel interface, observed by electron microscopy, (10) 336*e*.
silicate, compatibility relations, in systems MgO-Al_2O_3-SiO_2-H_2O and K_2O-MgO-Al_2O_3-SiO_2-H_2O at high pressure, (7) 264*h*.
hydrated, stability, (9) 329*j*.
polymorphs, stability relations, (7) 269*h*.
thermodynamic properties, (4) 161*j*.
triple point in kyanite-andalusite and andalusite-sillimanite equilibria, (7) 265*g*.
in silicate materials, determination, purification of commercial Alizarin Red S for, (4) 120*i*.
-Si long-range order in muscovite, (4) 142*i*.
sintered powders, extruded commercial materials, anisotrophy in mechanical properties of, (10) 349*j*.
solubility, in cryolite melts, (1) 37*h*.
solubility, in presence of hydroxide, fluoride, and sulfate, (9) 329*j*.
sputtering of oxide films in plasma anodization of, (4) 111*a*.
sulfate, thermal decomposition, thermodynamics, (4) 162*b*.
sulfates, synthetic crystalline basic, as compared with basaluminite, (9) 316*h*.
superpurity, in dry oxygen, kinetics and mechanism of oxidation: I, apparatus description and growth of "amorphous" oxide; II, growth of crystallites of γ-alumina, (1) 31*c*.
surfaces, ettringite formation on, (2) 44*b*.
systems. See *Systems*.
Alunite, natro-, in upper cretaceous sedimentary rocks, north central Texas, (6) 229*e*.
Americium, Am^{3+}, zero-field splittings, in cubic symmetry sites in CaF_2, (4) 164*c*.
Amines, aliphatic, reactions with montmorillonite, (9) 328*c*.
ethylamine, sorption on silica and silica xerogel, (1) 37*d*.
Ammonium, aluminosilicate, conversion to hydrogen aluminosilicate, P (4) 124*j*.
$NH_4Ag_4I_5$, relation of structure and ionic mobility in, (5) 199*b*.
copper(I) sulfite, crystal structure, (8) 290*b*.
dimethyldioctadecyl, derivatives of different clay minerals, gas-chromatographic investigations, (9) 321*j*.
fluoride, phase diagram to 20 kbars, (4) 148*j*.
metavanadate, thermal decomposition, (8) 300*d*.
molybdoselenite, and its iron salt, thermal decomposition, (4) 160*i*.
perchlorate, solid orthorhombic, thermal decomposition, effects of X- and γ-ray radiation: I, experimental and results; II, kinetics and discussion, (8) 291*a*.
phosphate, use in high concentration doping of silicon, P (4) 113*j*.
quaternary compounds, reaction with surface hydroxyl groups; and synthesis of, tested as possible promoters of filmwise condensation, in hydrophilation of glass surfaces, (9) 305*h*.
sulfate, producing from langbeinite, P (7) 263*b*.
vanadate, and NaF, effects on zircon formation, (5) 177*g*.
Amphiboles, coexisting, from blue schist facies metamorphic rocks, (7) 264*h*.
coexisting, chemical analyses, (1) 26*f*.
crystal chemistry, phase relations, and occurrence, B (1) 41*a*.
to pyroxene reaction, pseudo-polymorphic transition, (9) 328*h*.
metamorphic, stability, tremolite-ferroactinolite series, (4) 156*a*.
tremolite, aqueous dispersion, mechanism of formation of coagulation structures in, under action of ultrasound, (7) 267*b*.
Amplifier, integrated parametric, consisting of material with semiconductive and piezoelectric properties, P (4) 113*f*.
laser, construction, P (4) 99*j*.
semiconductor, using field-effect modulation of tunneling, P (11) 378*b*.
Analogs. See *Computers*.
Analysis. See also *Chromatography; Colorimetry; Electron diffraction; Microscopy; Particles; Photometry; Quality control; Screens and sieves; Spectrography; Spectrometry; Spectrophotometry; Spectroscopy; Testing; Thermal analysis; Thermodynamics; Thermogravimetry; Titration; X rays.*
acoustic wave, of operation of quartz-crystal film-thickness monitors, (7) 254*e*.

Analysis *(continued)*
activation, application to refractory materials, (5) 187*a*.
of arsenic, (2) 68*d*.
of silicon and arsenic, (2) 68*d*.
of trace contaminants in GaAs semiconductor materials, (5) 186*h*.
atomic absorption, for determination of Cu and Co in nickel ferrites, (6) 225*g*.
for Bingham plastic surface flow in canal viscosimeter, (1) 20*i*.
chemical, of fluorspar, (5) 186*j*.
of impurities of phosphogypsum, (4) 120*g*.
of trace coloring oxides in optical glasses, (8) 276*g*.
differential kinetic, of alkaline-earth ions using stopped-flow spectrophotometry, (8) 284*j*.
differential kinetic, of metallic elements, (8) 285*a*.
emission spectral, for iron determination in high purity quartz, (5) 187*a*.
fluorescence, of inorganic substances, (2) 69*f*.
of fresh concrete, apparatus for, P (4) 121*d*.
of Kablukov law, (8) 288*h*.
linked flux, of nucleation in condensed phases, (1) 31*h*.
luminescent, of inorganic substances, B (5) 203*j*.
magnon, of ferromagnetic resonance in planar ferrite, Zn_2Y, (8) 294*d*.
micro-, electron probe, of alkali metals in glasses, (11) 369*j*.
electron-probe, of inclusions in irradiated oxide fuels, identification of unknown constituent in, (2) 69*j*.
electron probe, of metal oxides, comparison of correction methods, (1) 21*h*.
quantitative electron-probe, of rock-forming minerals, (11) 380*f*.
of silicate rocks: V, spectrophotometric determination of Al_2O_3, (4) 120*b*.
microsample, internal reflection element for, P (4) 121*j*.
neutron activation, for determination of Cu and Bi in high purity Pb metal, (5) 187*e*.
determination of Dy in rock samples with Ge(Li) detector after chemical separation, (1) 21*i*.
fast, rapid and nondestructive, for elements, semiconductor detector for, (9) 315*j*.
at Illinois State Geological Survey, (9) 315*j*.
instrumental, for detection of trace impurities in stoichiometric spinel crystals, (7) 254*h*.
of medieval ceramics, (4) 120*f*.
nondestructive and destructive, of impurities of Si of semiconductor purity, (5) 187*e*.
for simultaneous determination of Ta and Hf in silicates, (1) 22*b*.
on-stream, X-ray fluorescence for, (4) 121*b*.
of particles, apparatus and method utilizing multiple apertures, P (8) 286*b*.
quantitative, of available Al_2O_3 content (by DTA) in bauxite from "Onverdacht" Suriname, (6) 227*e*.
in ceramic industry by X-ray fluorescence, (11) 380*e*.
by electron microprobe in oxide combinations, (9) 328*b*.
of gypsum by DTA, (4) 120*j*.
1,2-dimorpholinylethane as reagent in: VII, gravimetric determination of arsenic and silicon, (4) 120*b*.
spectral, of silicates, direct spectrochemical analyzer DSA 24 for, (10) 347*g*.
quantitative X-ray fluorescence, for geological samples using correction technique for matrix effects, (4) 121*a*.
quantitative X-ray phase, of mixtures of α-UO_3 with amorphous modification of UO_3 (4) 151*h*.
rational, of feldspars, clays, kaolins, and fine ceramic bodies, (4) 121*b*.
of silicates, (7) 259*h*.
spectral, of bentonites in solutions, (6) 227*c*.
spectral, of standard electrocorundum, (1) 22*d*.
spectroanalytical determination of chrome in rubies, (5) 188*f*.
spectrochemical, methods for geochemical purposes, (5) 188*f*.
spectrographic qualitative, of materials used in silicate industry, (8) 285*b*.
thermo-, for formation of zirconates of rare-earth elements, (1) 35*b*.
thermometric, of sintered nickel oxide, (2) 71*e*.

Analyzers. See also *Gases.*
direct spectrochemical, DSA 24, for quantitative spectral analysis of silicates, (10) 347*g*.
micro-, electron, in study of glass defects, (2) 48*f*.
ionic, wherein secondary ions are emitted from sample surface upon bombardment by neutral atoms, P (4) 121*j*.
TPD electron probe X-ray, (6) 227*e*.
X-ray, to study refractories, (7) 250*e*.

Anatase, stability in titania enamels, (7) 246*i*.

Andalusite, kyanite-, and -sillimanite equilibria, experimental determination—aluminum silicate triple point, (7) 265*g*.

Anelasticity, of glasses, network contribution to, (6) 210*a*.
of graphite, impurity-dope effects on, (8) 293*j*.

Anhydrite, finely divided soluble, transformation into orthorhombic anhydrite, (1) 39*i*.
in salt bearing formations of Moïzons in Ostolowaker, (4) 138*c*.

Anions. See *Ions.*

Anisotropy, of diffusion in rutile, (10) 349*j*.
exchange, in mixed phase of γ-Fe_2O_3 and α-Fe_2O_3, (9) 321*b*.
ferromagnetic, of Ni-on-SiO_2 particles, effects of hydrogen and oxygen chemisorption, (5) 194*c*.
hardness, of crystals, impression and scratching tests for, (2) 70*a*.
indentation microhardness, in minerals, effects of water desorption, (8) 285*a*.
induced, in $Mn_{1+\delta}Fe_{2-\delta}O_4$ single crystals at low temperatures, (2) 78*f*.
magnetic, of ferrous and ferric ions in ferrites with spinel structure, effect by hydrostatic pressure, (2) 76*b*.
magnetic, of NiO and MnO single crystals, (2) 70*f*.
magnetocrystalline effect, eliminating on spin resonance of ferrimagnetic materials, P (2) 65*i*.
in mechanical properties of extruded commercial S.A.P. materials, (10) 349*j*.
optical, of graphite, (4) 131*h*.
in single-crystal compounds: Vols. 1 and 2, B (7) 270*i*.
stress-induced magnetic, in natural single crystals of hematite, (2) 83*h*.
thermal expansion, of oxides and oxide solid solutions, (9) 332*c*.

Annealing, behavior, in vacuum-deposited films of silicon oxide, (8) 280*i*.
effect, on properties of sintered WC-TiC-10%Co alloys, (4) 103*h*.
ESR study, of radiation damage in graphite, (2) 74*i*.
of glass. See *Glass.*
influence on strength of corundum crystals, (2) 78*g*.
of irradiation-induced thermal conductivity changes in ThO_2-1.3 wt% UO_2, (6) 208*e*.
of oligoclase at high pressure, (10) 350*a*.
of phosphorus atoms, irradiated silicon-containing, (1) 25*g*.
of AgCl single crystals, slightly bent, (9) 318*c*.
of sulfide ores, single phase polycrystalline, (8) 288*i*.
thermal, effect on valence distribution of radiophosphorus in single crystal KCl, (9) 332*g*.
thermal, studies of irradiation defects in graphite and self-diffusion mechanism, (9) 331*c*.
20°–400°C, effect on density and lattice parameters of Al_2O_3 and MgO, (4) 133*a*.

Anodes. See also *Electrodes.*
anodization, selective masking of silicon wafer during, P (6) 223*b*.
anodization, plasma, of germanium, (9) 311*g*.
effect, repeatability in cryolite-alumina melts, (2) 82*c*.
graphite, in cryolite-alumina melts, chronopotentiometric measurements on, (6) 214*i*.

Anthophyllite, and talc deposits in Tallapoosa and Chambers counties, Alabama, (2) 73*h*.

Antiferromagnetism. See *Ferromagnetism.*

Antimony, Sb(III), solubility in chlorapatite, (10) 360*a*.
pentachloride, molecular adducts, thermodynamic properties and frequency shifts, (7) 270*b*.
systems. See *Systems.*
tritelluride, infrasensitive, vapor depositing, P (5) 185*i*.

Apatite, Al-rich, (8) 288*g*.
chlor-, single crystals, conversion into single crystal of hydroxyapatite, (4) 129*j*.
crystals, natural, fission tracks on (1010) cleavages of, (1) 29*g*.
flotation, P (2) 74*a*.
fluor-, formation, EPR study of chemistry of Mn^{2+} during, (4) 135*b*.
fluor-, new laser material, crystal growth, (4) 130*d*.
hydroxy-, preparation and solubility, (6) 236*e*.
hydroxy, single crystals, large, efforts to grow, (7) 268*g*.
hydroxyl-, synthetic, complexometric determination of Ca and P in, (6) 225*i*.
luminescent, stoichiometry, (4) 156*b*.
substitutions in: I, K-bearing, (8) 299*b*.
zeta potential, in aqueous solutions, and change during equilibration, (5) 203*e*.

Apophyllite, crystals, growth mechanism studied by surface microstructures, (6) 233*a*.
crystals, rotation of etch pits on basal cleavages of, (1) 36*i*.

Apparatus. See *Instruments; Machinery and equipment; Testing;* and specific types.

Aquasols. See *Colloids.*

Aragonite, -calcite transformation in aqueous solutions, temperature controls on, (11) 387*i*.
-calcite, and vaterite-, transformations, catalysis and inhibition in, (6) 230*g*.

Archeology, antique pottery, blood in ceramic body of, (6) 205*j*; (9) 303*f*.
bowl, with gold base discovered at Farrobo, Portugal, (4) 90*b*.
Egyptian glass articles of New Kingdom, (6) 205*a*.
glass, millefiori in classical antiquity, (4) 90*b*.
glass as model to reconstruct methods of working flint in stone age, (9) 305*h*.
Hellenistic glasses, Canosa group, in British Museum, (4) 90*c*.
potsherds from Tikal, in Peten, Guatemala, chemical and mineralogical examination, (9) 303*h*.

Archeology *(continued)*
thermal expansion measurement for determination of firing temperature of ancient ceramics, (10) 347*e*.

Argon, adsorption, use in determination of specific surface areas, (2) 71*j*.
content, of sputtered SiO_2 films, determination by X-ray fluorescence, (8) 280*i*.
ionically pumped, desorption from clean and metalized glass surfaces, (9) 305*i*.
sorption at 77.4°K on microporous glass, (4) 94*j*.

Armor, lightweight, with laminated base member resistant to delamination, P (8) 280*f*.
plate, curved, P (8) 280*c*.

Arsenic, activation analysis, (2) 68*d*.
amorphous, structure according to intensity curves, (10) 361*e*.
AsO_3^{2-} molecule-ion, ESR absorption spectrum, in γ-irradiated single-crystal calcite, (10) 353*a*.
determination by atomic absorption spectrometry with electrodeless discharge lamp as source of radiation, (10) 347*e*.
effect on composition of gas in seed during glass refining, (7) 247*d*.
pentafluoride, enthalpy of formation, (1) 29*i*.
and silicon, gravimetric determination, with 1,2-dimorpholinylethane as reagent in quantitative analysis, (4) 120*b*.
systems. See *Systems.*
trisulfide, hydrosol, stability in light of Derjaguin-Landau-Verwey-Overbeek theory, (4) 155*j*.

Arsenides, group IIIA, heat of formation, measured by DDC, (4) 151*f*.

Art and artware. See also *Archeology; Decoration; Design; Pottery; Tile.*
acquisitions, recent, (4) 90*f*.
Athenian vases, (6) 205*i*.
bent ware, (7) 244*a*.
building ceramics from Muehlendyck pottery center, (7) 244*b*.
candlesticks, tall, from short kiln, (7) 244*d*.
ceramic, in America, B (10) 364*h*.
ceramic antiquities, macrostructure, investigation by X rays, (6) 206*d*.
ceramic relief, based on modern architecture trends, (6) 205*j*.
ceramics and glass, in municipal museum of Landshut, Germany, (5) 169*j*.
Chinese porcelain, imported by Dutch East India Co., (11) 367*i*.
clay modeling from solid blocks, (10) 335*j*.
copper enameled wall panels, (6) 206*c*.
copper, shaping and texturing, (8) 278*j*; (10) 335*j*.
creative ceramics for beginner step by step, B (9) 333*i*.
decorative pottery development in India, (6) 206*b*.
in eastern Mediterranean, (5) 169*i*.
enameled garden lantern, (7) 244*a*.
enamels, scrolled, (8) 273*i*.
German ceramics, modern, development, (7) 244*f*; (11) 367*h*.
glass, ancient, weathering crusts, (8) 273*j*.
articles and book list, 1967, (4) 90*f*.
coach, (9) 303*f*.
colored silicate, alchemistical recipes from Persia, (9) 303*f*.
cups, shape, with low baluster type foot from 17th century, especially from Netherlands, (9) 303*g*.
cut, Achemenid bowl, from Nippur, (4) 91*a*.
filigree, identified with more descriptive word than "latticinio," (4) 90*d*.
gilt and enameled, from Cyprus, (4) 90*d*.
history, of "breathing spells" periods, (9) 303*g*.
and jewelry, museum in Jablonec, Czechoslovakia, (5) 169*j*.
masterpieces at British Museum, (5) 169*j*.
Mycenaean paste beads, unreported use, (4) 91*a*.
Roman bowl, from Krefeld-Gellep, (4) 90*g*.
Roman figure-cut vessel from Caerleon, (4) 90*f*.
Romer, studies on form, (4) 90*h*.
sculpture, (10) 335*i*.
stained windows, European, (5) 170*a*.
vessels, pseudo-ancient, from Italy, (4) 90*h*.
"Wolff," in English private collection, (4) 91*b*.
glass blowing, creative, B (10) 364*g*.
glazed clay cut-outs, (10) 335*i*.
Grecian vases, black- and red-figured, refiring for restoration, (5) 170*b*.
handling clay in large amounts, (10) 335*i*.
Hungarian faience wares, (11) 367*h*.
Italian centers: I, early periods, (1) 2*a*; II, beginnings and development of Italian majolica, (4) 90*e*.
majolica ware at low temperatures, (6) 206*e*.
mug from mold, (7) 244*c*.
off-center shapes, making on potter's wheel, (6) 206*f*.
in Persia, mosques in Isfahan, (5) 169*i*.
II, Teheran—formerly Rhages, (6) 205*f*.
traditional crafts, development, technology and influence on Eastern and Western civilizations, B (1) 42*e*.
porcelain figures—Victoria and Albert Museum, B (10) 365*j*.
porcelain reliefs, (7) 244*c*.
pottery, small, conversion to gas-fired kiln, (10) 335*i*.
Spanish, present day ceramics, (6) 206*a*.
stoneware, old Saxony, (1) 2*b*.

Art and artware *(continued)*
teaching techniques for children, (6) 206*e*.
Toby jugs, (7) 244*e*.
Turner factory, new discoveries, (4) 90*i*.
vasa diatreta, produced by lapidary methods, (4) 90*j*.
vase, square, throwing, (7) 244*e*.
wheel- and handmade pot, (7) 244*e*.
white porcelain masterpiece of unknown craftsman, (4) 90*j*.

Artists. Asshoff, Bruno and Ingeborg, (6) 205*j*.
Barovier, Maria, developer of glass millefiori canes, (4) 90*i*.
Batterham, Richard, prolific potter, (4) 90*e*.
Biemann, Dominik, glass engraver, (4) 90*g*.
Bontjes van Beek, Jan, (1) 2*b*.
Chasek, Denis, (7) 244*b*.
Conover, Claude, (8) 273*i*.
Derckum, Kurt, (1) 2*a*.
Geiger, Benno, (4) 90*f*.
Henze, Wolfgang, (7) 244*c*.
Heufelder, Walter A., (11) 367*h*.
Hohlt, Goerge, (11) 367*h*.
Hufnagel, Otto, (6) 205*j*.
Koppenhoefer, Ruth, (4) 90*e*.
Larson, Lisa, and Lindberg, Stig, Scandinavian creations, (5) 170*b*.
Loesche, Ernst, (6) 205*j*.
Lunghard, Rudolf, (1) 2*a*.
Mascarin, Mario, (6) 206*a*.
Parshall, Jane, (7) 244*b*.
Peace, David, engraved glasses, (4) 90*i*.
Pluquet-Ulrich, Elisabeth, (11) 367*h*.
Pozzi, Dr. Ambrogio, porcelains, (11) 367*i*.
Ravenscroft, George, "christalline" glass developer, (4) 90*h*.
Steigel, Henry William, B (1) 42*g*.
von Eichborn, Celine, (6) 205*j*.
Welch, Robin, sculpture and wall panels, (4) 90*d*.

Asbestos, anthophyllite, from Tallapoosa County, Alabama, product research on, (4) 151*d*.
aqueous suspensions, filtration properties, effect of polyacrylamide, (1) 23*e*.
-cement, products, impregnation with thermosetting formaldehyde resin, P (4) 92*i*.
chrysotile, colloidal suspensions: specific anion effects, (4) 128*i*; surface charge enhancement, (5) 193*a*.
reversible flocculation and redispersion, P (5) 191*d*.
whiskerlike fibers from, (4) 124*e*.
crude, separated from source rock, apparatus for dressing, P (6) 229*b*.
electric insulating bodies, P (11) 374*h*.
fibers, separation from foreign solids, P (5) 191*d*.
millboard conveyor rolls, for high temperature use, P (10) 342*a*.
from northwest Pakistan, mineralogy, (6) 229*d*.
opening up, with dimethylsulfoxide, P (4) 118*g*.
products, P (9) 317*e*.
purified products, P (10) 342*g*.
synthetic, from wastes of asbestos-concentration plants, (2) 73*b*.
yarn, P (10) 343*a*.

Ash, fly, carbon determination in, (2) 69*f*.
fly, as cement substitute, (1) 2*d*.
effect on steel reinforcement, (1) 2*h*.
process, at Mississauga plant, (7) 245*a*.
proportioning with cement for strength and economy in concrete production, (2) 45*d*.
specification for use as pozzolan, (1) 3*b*.
use in building industry, (2) 45*a*.
pulverized fuel, composition and pozzolanic properties, (2) 43*i*.
volcanic, Kansas, for cellular concrete, (2) 43*j*.
volcanic, Kansas, thermal expansion, (9) 317*b*.

Atmospheres, burning, influence on behavior of alite mixture during firing, (4) 91*j*.
effect on pores in firebrick, (11) 373*c*.
effect on refractory oxides properties, (1) 12*a*.
firing, effect on mullite formation from kaolinite-type minerals, (11) 384*f*.
furnace, influence on hot crushing strength of refractories, (6) 215*f*.
heating, effect on crystal growth of periclase, (7) 250*f*.
and minor constituents, effects on surface tension of glass melts, (4) 95*e*.
in preparing ferrites, controlling, P (4) 114*i*.
reducing, effect on combination of constituent oxides in portland cement burning, (4) 91*c*.

Atomic heat. *See Heat, capacity.*

Atomization, of solid samples, for atomic absorption spectroscopy, (2) 70*i*.

Atoms, atomic size, in NaCl-type uranium compounds, (1) 37*f*.
displaced by implanted ions or energetic recoil atoms, (10) 357*h*.
distribution, in Cu_3Zn_8, Cu_3Cd_8, and Cu_9Al_4, redetermination, (8) 297*h*.
interstitial, configuration, in irradiated graphite, (4) 129*c*.
tagged, to study movement of material and dust formation in rotary furnaces, (1) 3*f*.

Attapulgite, clay paper filler, and method of forming newsprint with, P (6) 229*b*.
product, and preparation, P (1) 23*g*.

Attrition. *See Crushing; Grinding.*

Augers. See *Extrusion.*

Autoclaves, hardened bodies, strength effect of slaked lime, siliceous materials, and blast-furnace slag mixtures, (4) 92*i*.

Balances (scales). See also *Weighing.*
centrifugal sedimentation, for measuring particle size of very fine powders, (4) 119*a*.
thermal, for measuring transport during vapor phase crystal growth, (5) 188*j*.

Ball mills. See *Mills.*

Barite. See *Barium, sulfate.*

Barium, aluminate, hydrated, structural change and mechanical strength at elevated temperature, (5) 170*h*.
BaClF and BaBrF, Raman spectra, (8) 297*c*.
$BaFPO_3$, NMR study, (10) 357*g*.
$BaMg(CO_3)_2$ norsethite, crystal structure, comparison with dolomite, $CaMg(CO_3)_2$, (6) 231*c*.
$BaNb_2O_6$, crystal growth and comparison with ANb_2O_6 and ATa_2O_6 phases [A=Ba, Sr, or Ca], (5) 192*d*.
$4BaO \cdot Nb_2O_5$, synthesis in solid phase, (10) 362*b*.
$Ba_2NaNb_5O_{15}$, continuous optical parametric oscillation in, (4) 129*h*.
continuous 0.532-μm solid-state source using, (4) 129*g*.
piezoelectric properties, (7) 255*i*.
$Ba_{4+x}Na_{2-2x}Nb_{10}O_{30}$, crystallographic data and thermal expansion coefficients, (11) 383*c*.
carbonate, metastable phase, (1) 33*b*.
preparation by carbonation of aqueous barium sulfide, P (5) 191*g*.
reaction with Cr_2O_3, (8) 297*d*.
reaction with iron(III) oxide in vacuo, (8) 297*e*.
reaction with titanium(IV) oxide (anatase), measurements at high temperatures, 6) 235*a*.
chloride, interaction with gallium chloride, (4) 140*e*.
-cobalt hexagonal ferrite, $BaCo_2Fe_{16}O_{27}$, X-ray and microstructural study of phase relations during formation of, (9) 333*a*.
diffusion, in MgO, (1) 27*j*.
feldspar. See *Feldspars.*
fluoride, crystals, F^- vacancy conductivity in, (5) 194*a*.
crystals, interstitial conduction in, (5) 195*g*.
elastic constants, pressure and temperature derivatives of, (9) 328*e*.
interaction with boric anhydride, (4) 140*b*.
(111) surface, variations in orientation of etch pits on, (8) 300*h*.
vapor pressure, evaporation coefficient, and heat of sublimation, (4) 163*f*.
-iron-oxygen compounds with varying oxygen content and iron valence, (2) 74*j*.
molybdate(IV), magnetic susceptibility, in range 2°–300°K, (11) 385*h*.
octaborate, Eu^{2+}-activated, fluorescence, (10) 353*f*.
oxide, evaporated films, ESR absorption in, (8) 291*g*.
interaction with oxides of rare-earth elements, (7) 267*d*.
$\cdot 6Fe_2O_3$ single crystal, ferromagnetic resonance in, (9) 321*d*.
X-irradiated polycrystalline, thermoluminescent study, (9) 332*a*.
sodium niobate, optical defects in, (8) 298*c*.
spectrophotometric determination, by means of dimethylsulfonazo-III and related compounds, (5) 188*g*.
strontium niobate, crystal structure, (5) 194*f*; (11) 385*a*.
sulfate, cleavage and etching, (1) 26*c*.
single crystals, growth by chemically reacted flux method, (7) 266*f*.
synthetic, single crystals, etching, (10) 353*i*.
systems. See *Systems.*
titanate. See also *Dielectrics.*
absolute reflective spectra, (1) 16*b*.
a-domain, growth, P (11) 376*i*.
body, P (6) 222*e*.
capacitors, controlled reduction and reoxidation, P (5) 182*a*.
ceramics, containing clay and dolomite, DTA, (4) 109*i*.
ceramics, for making integrated ultrasonic delay line, (4) 110*a*.
compositions containing Ce and Bi, P (8) 282*c*.
crystals, melt-grown, dielectric and optical properties, (10) 352*b*.
cubic and tetragonal phases, ESR of Eu^{2+} in, (2) 76*d*.
dense Gd-doped, determination of donor gradients within surface barriers formed on, (9) 310*g*.
dielectric properties, influence of microstructure, (10) 344*f*.
evidence from Raman scattering for overdamped optic mode in, (4) 135*j*.
ferroelectric, Moessbauer effect for ^{57}Fe in: vacancy-impurity associated state, (5) 197*g*.
ferroelectricity and antiferroelectricity in, (1) 16*h*.
fine-grained, internal field theory of high permittivity in, (2) 79*f*.
fine particles, dielectric properties and crystal structure, (4) 131*b*.
from glasses, (5) 172*f*.
irradiation influence on, (2) 60*f*.
La-doped, electrical resistivity, effect of oxide impurities, (2) 62*d*.
low-frequency transverse optic lattice vibration, temperature dependence of, (1) 39*e*.

Barium, titanate *(continued)*
metal-, contact, influence of gaseous adsorption on, (4) 140*a*.
microstructures, (2) 50*f*.
observation of ^{47}Ti and ^{49}Ti *hf* structure in *F*-center ESR line in, (1) 33*f*.
(100) free surface, lattice structure, (6) 234*j*.
orthorhombic and rhombohedral phases, ESR of Gd^{3+} in, (2) 76*d*.
phase transition in, pressure-squeezing effect on, (4) 150*j*.
polycrystalline, aging mechanism in, (8) 294*i*.
pure, high density sintering, (2) 67*h*.
reduced and reoxidized, phase composition, (4) 111*a*.
reduced, single crystal contacts to metal, electrical conduction of, (1) 16*b*.
reduction in nonisothermal hydrogen plasma, (7) 255*a*.
semiconducting, current-voltage characteristics, (2) 62*h*.
semiconducting, electrochemical oxidation, (6) 220*g*.
single crystals, butterfly twin, and $BaTiO_3$ used in, P (2) 66*h*.
single crystals, effective mass of 180° domain wall in, (1) 28*e*.
single crystals, reduced, electrical conduction in, (9) 320*i*.
single crystals, reduced, ESR of Mn^{2+} in, (1) 29*c*.
sintering, kinetics, (7) 255*d*.
soft optic modes in, (4) 155*d*.
surface layers, electron-mirror microscopy study, (4) 134*j*.
tetragonal, Debye-Waller factors, (8) 290*g*.
tetragonal, ferroelectric, aging in, (6) 220*e*.
tetragonal, X-ray studies of lattice vibration in, (5) 203*b*.
thermal conductivity, anomalous, near ferroelectric transition point, (2) 74*i*.
vibronic structure in luminescence spectra of rare earth ions in, (2) 84*e*.
tungstate, Bi-doped, phototropy, (4) 149*j*.
zirconium silicates, preparation and properties, (5) 199*a*.

Basalt, irradiated, diffusion of strontium in, (7) 265*c*.
Rovenskie, as raw materials for pressed stoneware ceramics, (6) 219*d*.

Base exchange. See *Ions.*

Batteries, fuel, with stabilized ZrO electrolyte, (6) 217*j*.
semiconductive electronegative element of, P (9) 313*d*.

Bauxite, deposits of India, (4) 164*i*.
domestic, high grade, revealed by General Refractories research project, (6) 215*b*.
extraction of alumina from, P (1) 23*h*.
impregnated sintered grains, and product, P (10) 335*g*.
from "Onverdacht" Surinam, quantitative analysis of available Al_2O_3 content (by DTA) in, (6) 227*e*.
and phases, behavior after mechanical activation: I, mechanical activation of boehmite; II, of gibbsite; III, of corundum, (4) 126*j*, 127*a,c*.

Bearings, ball tracks, finishing, complete abrasive process, (5) 169*g*.
device, for vertical shaft of crushing cone of gyratory crusher, P (4) 124*h*.
industry, abrasives and machines in, (2) 43*f*.
nonlubricated, with ceramic seals, P (2) 58*a*.
surface, manufacture on steel article including single sintered layer of bronze particles and layer of polytetrafluorethylene, P (4) 94*a*.

Belite, crystallization, in portland cement clinkers, effect of additives, (1) 2*g*.

Bending. See *Deformation.*

Beneficiation. See also *Classification; Classifiers; Crushing; Grinding; Filters; Flotation; Screens and sieves; Separation; Separators.*
of clay, by flotation of colored impurities, P (11) 382*c*.
of cryolite material, P (10) 349*a*.
of fluorspar ores, P (6) 229*c*.
of kaolinite clay from silica sand washings, (9) 316*f*.
of lead ore, low grade, (6) 228*j*.
of ores, method and means, P (5) 191*c*.
of raw materials by optical-electronic devices, (5) 189*i*.
of talc, P (4) 126*a*; P (11) 383*a*.

Bentonites, Indian, infrared spectra, (10) 355*g*.
isocapillary membranes, (6) 234*a*.
in solutions, spectral analysis, (6) 227*c*.
two Rajasthan, containing interstratified clay minerals, (10) 363*c*.

Benzene, adsorption on clay minerals, (10) 349*h*.
sorption and dielectric behavior on SiO_2 gel, (10) 361*f*.
ultraviolet light irradiated, adsorbed on SiO_2 gel and Al_2O_3, ESR study, (8) 291*i*.

Berkelium, separation from cerium, P (1) 24*a*.

Beryl, characterization by visible and infrared absorption spectroscopy, (8) 289*e*.
crystal chemical considerations in, (2) 73*b*.
infrared spectra of foreign molecules in, (4) 140*h*.
low-frequency vibrations of water molecules in, (6) 234*e*.
Sc analog of, synthesis, (8) 299*h*; errata (10) 362*c*.

Beryllates, fluoro-, comparative crystallochemical

Beryllates *(continued)*
systematics and morphotropic transformations of silicates and, (4) 129*c*.
Beryllia. See *Beryllium, oxide.*
Beryllium, aluminate (chrysoberyl), effect of irradiation on, (6) 232*e*.
$BeSiN_2$, preparation, properties, and crystal structure, (8) 299*b*.
chloride, interaction with gallium chloride, (4) 140*e*.
compounds, thermodynamics and physical properties, (1) 39*f*; IX, free energy of formation of beryllium hydroxide (*g*), (4) 161*h*; X, heats of formation and entropies of $BeCl_2(g)$ and $BeSiCl_4(g)$; XI, of beryllium (I) hydroxide(*g*), (5) 201*d*.
corrosion, retarded by chemical conversion coatings, (5) 171*c*.
fluoride, molten, viscosity and temperature dependence in, (1) 10*a*.
-LiF solutions, viscosity and density in, (10) 338*d*.
production, P (4) 125*e*.
structure and chemical properties in its glasses, (2) 51*d*.
fluorination, kinetics, (4) 142*d*.
in modern materials, B (4) 166*h*.
oxide, ceramics, field, problems and results, (4) 108*e*.
computed ground state properties in molecular orbital approximation (8) 289*d*.
containing up to 15% SiC and up to 2% MgO, properties, (4) 151*e*.
correlation between activation energies for steady-state creep and self-diffusion in, (8) 289*f*.
crystallite size determination, (8) 285*i*.
crystals, structure of paramagnetic lithium center in, (9) 330*c*.
crystals, X-ray diffraction contrast of inversion twin boundaries in, (10) 363*d*.
electrical transport processes in, (9) 321*e*.
escape of helium from, during irradiation, kinetics, (4) 142*b*.
growth under neutron irradiation, (4) 137*e*.
heat of fusion and high-temperature heat capacity, (1) 39*f*.
irradiated, diffusional release of tritium from, (4) 131*f*.
irradiated nonfissile, release of gas from, (1) 13*b*.
machined surfaces, recrystallization, (10) 342*a*.
modulus of rupture, effect of strain rate, environment, and surface condition, (4) 133*i*.
neutron-induced damage in, (8) 295*c*.
neutron irradiated at high temperatures, damage, (1) 33*i*.
outgassing in vacuum at 540° and 870°C, (6) 220*a*.
polycrystalline, elastic constants, as function of pressure and temperature, (7) 265*a*.
powders, production, P (6) 229*i*.
radiation-induced defects in, observation by means of long-wavelength neutron-scattering measurements, (4) 147*d*.
self-diffusion of oxygen in, by proton activation of oxygen-18, (10) 360*e*.
single crystals, hydrothermal growth, (4) 139*e*.
sintering, effect of water vapor, (5) 177*f*.
sintering: IV, mechanism, during hot-pressing, (11) 374*d*.
strength and Young's modulus, as function of density and grain size, (2) 81*c*.
systems. See *Systems.*
Binders, for abrasives. See *Abrasives.*
alumina, thin sheets without impurities, (11) 374*c*.
Bakelite, for improved production of abrasives, (4) 89*f*.
CO_2 cured silicate, use for preparation of sand cores, P (8) 280*a*.
carbonic, effect on properties of hydrothermally hardened silica-lime compositions in system CaO-SiO_2-H_2O-CO_2, (10) 372*j*.
hardening kinetics, determination, (2) 44*d*.
hydraulic, production, P (5) 170*i*.
organic, effect on granulation and forming of raw powders of ceramic dielectrics, (6) 220*f*.
plant for calcining, P (4) 107*j*.
retarders and accelerators, for setting calcium sulfate hemihydrate, (4) 92*e*.
for sheet glass, P (5) 174*j*.
three-component water-resisting, P (4) 92*j*.
Binding, chemical, and molecular charge distributions: III, isoelectronic series N_2, CO, BF, and C_2, BeO, LiF, (8) 295*i*.
properties, of phosphate systems, (7) 245*c*.
Biotite. See *Mica.*
Birefringence. See *Refraction.*
Bismuth, BiSb alloys, with small antimony content, electrical properties, (5) 181*a*.
$BiMnO_3$ and $BiCrO_3$, magnetic properties and crystal distortions, (8) 294*j*.
Bi_2O_3·$2MoO_3$, crystalline structure, new data, (4) 146*b*.
$3Bi_2O_3$·$17Nb_2O_5$, crystal structure, ideal, (8) 298*d*.
Bi_2Te_3, solidification, and its solid solutions with Bi_2Se_3 and Sb_2Te_3 under influence of ultrasonic agitation, (4) 155*e*.
chloride, fused, Raman spectra, (9) 328*b*.
chloride, interaction with indium chloride, (4) 140*d*.
determination by spectrophotometric reaction rate method using dimeric heteropolymolybdate, (8) 285*f*.
Bismuth *(continued)*
germanium oxide, optical activity and electro-optic effect in, (1) 33*g*.
photoactivity in, (4) 149*f*.
piezoelectric, $Bi_{12}GeO_{20}$, crystal structure, (4) 130*c*.
in high purity lead metal, determination by neutron activation, analysis, (5) 187*e*.
luminescent behavior, in rare-earth oxides, (4) 110*d*.
oxide, gaseous, absorption bands, rotational structure of, and spectrum, (1) 32*e*.
oxide, influence on sintering of SnO_2, (4) 154*g*.
systems. See *Systems.*
titanates and ferrites, (2) 62*e*.
trichloride and tribromide, properties, and fusibility in systems, (9) 329*b*.
trifluoride, thermodynamic properties, (10) 362*i*.
trihalides, phase diagrams at high pressure, (5) 198*g*.
in yttrium vanadate and yttrium europium vanadate phosphors, (4) 109*f*.
Black coring. See *Structural clay products.*
Blasting, wet abrasive, P (9) 314*h*.
Bleaching, of kaolin clays, potentiometric control, P (1) 24*b*.
Blending. See *Mixing.*
Blending apparatus. See *Mixers.*
Bodies, ceramic. See also *Dielectrics.*
dry, preparation with Mogensen sizer, (7) 258*j*.
of ferroelectric materials with perovskite structure, partially *p*-conducting and partially *n*-conducting, P (7) 255*i*.
formation, with negative coefficient of thermal expansion, (2) 60*c*.
forming with pressure shock wave, (5) 186*b*.
isostatic pressing, (11) 379*d*.
low-density, from clay and expanded volcanic ash from Kansas, (9) 316*f*.
mechanical properties during drying, (5) 179*i*.
model for connected porosity in, (2) 70*f*.
nomograms and graphical calculations for use in preparing, (5) 186*c*.
production, P (6) 220*b*.
from stoneware clays, yellow color of, (5) 180*a*.
strengthening, accelerated, (5) 176*f*.
thixotropic and sedimentation volumes, cause and influence, (11) 375*f*.
unfired, aqueous conductivity measurement, (1) 21*d*.
Boehmite, fibrillar synthetic, thermal decomposition, (7) 262*b*.
flow behavior during decomposition, (10) 353*d*.
mechanical activation, (4) 126*j*.
proton mobility in, dielectric and diffusion measurements, (8) 296*i*.
Bonding. See also *Seals and sealing.*
adhesively, metal plate to refractory brick, apparatus for, P (8) 279*i*.
ceramic-to-metal, P (2) 64*h*.
in $CsCuCl_3$, thermal and magnetic study, (10) 362*f*.
characteristics of glass surfaces, improving, P (4) 100*a*.
chemical, of semiconductor compounds, (4) 128*b*.
chemical, in silica and silicates, (4) 128*j*.
chips in substrate recess by epitaxial growth of bonding material, P (6) 223*g*.
composition, hard-facing matrix, P (2) 58*g*.
covalent, in diamond and silicon, X-ray studies, (5) 203*b*.
different materials by electromagnetic radiation, P (5) 183*a*.
epoxy, transducers to delay lines, P (2) 64*e*.
fusion, to nonmetals, P (4) 113*g*.
glass-to-metal, mechanisms in, (10) 336*f*.
gold-indium, for measurement of ultrasonic properties in solids at high temperatures, (7) 260*e*.
graphite with fused silver chloride, P (10) 342*b*.
leads to electrical components, P (7) 257*a*.
leads to quartz crystals, P (11) 376*g*.
material, apparatus for applying between implosion band and glass for cathode ray tubes, P (2) 52*i*.
mechanism, in aqueous $Ni(NO_3)_2$ MgO cements, (4) 92*a*.
metal-metal, in $La_4Re_6O_{19}$ and rutile-related dioxides, (6) 235*d*.
metal plate to refractory brick with chloroprene-phenolic adhesive, P (7) 252*d*.
metals, electrically conductive, to insulators, P (4) 112*d*.
metallic members with intermediate ceramic layer, P (1) 5*e*.
and metallizing, nonmetallic bodies, P (4) 114*e*.
of semiconductor parts, apparatus for effecting, P (9) 312*a*.
Si semiconductor devices, P (11) 377*g*.
structure and, B (6) 242*b*.
thermal, of semiconductor components to carriers, P (7) 256*j*.
thermoelectric elements to nonmagnetic refractory metal electrodes, P (9) 312*c*.
Bonds, adhesive, glass, for utrasonic devices, P (4) 98*h*.
chemical, in crystals and ferromagnetism, B (4) 166*h*.
effect on fine structure of X-ray emission spectra in microvolumes of Ti and Ti oxides, (4) 132*i*.
in IBr, ICl, and I_2Cl_6, studies by Moessbauer effect in ^{129}I, (4) 156*j*.
Bonds, chemical *(continued)*
influence on luminescence of uranyl in glasses, (2) 49*a*.
and relative intensities of Kα satellites, (4) 153*h*.
chemisorption, on semiconductor surfaces, (10) 357*e*.
Harghita kaolin, for abrasives, (4) 89*f*.
Si-O, of aryloxysilanes, investigation on basis of infrared spectra, (5) 195*h*.
strong metallic, forming to lead-containing glass, P (5) 175*d*.
vitreous, cylinder flow test for controlling, (4) 89*h*.
Bone, calcined, physical properties, effect of calcining conditions on, (6) 228*j*.
calcining and grinding, (10) 348*f*.
Borates, of dolomite structure, (1) 25*b*.
$MeMe'(BO_3)_2$, with dolomite structure, (7) 263*j*.
poly-, ions, cage structure for, (4) 127*g*.
rare earth, in systems Na_2O-B_2O_3-Ln_2O_3, (6) 236*i*.
Borax, decahydrate crystals, P (1) 24*b*.
dielectric behavior and proton conduction in, (4) 131*a*.
Boric acid, producing from alkali metal borates, P (10) 349*c*.
Boric oxide, anomaly in Nabal glasses, (11) 369*h*.
effect on magnesia properties, (6) 214*j*.
influence on vitrification on amorphous and crystalline forms of silica, (10) 337*h*.
production, P (4) 124*j*; P (9) 317*d*.
reduction, to boron monoxide, (1) 36*a*.
systems. See *Systems.*
viscosity, pressure dependence of, (1) 8*d*.
Borides, alkali metal, P (1) 24*d*.
with Cr_3C_2 structure, magnetic properties, (1) 17*g*.
compositions, densification, P (7) 252*i*.
di-, oxidation resistant metal composites, synthesis, (1) 13*h*.
of metals of groups II-VI, thermodynamics of reactions used for preparation, (1) 18*a*.
plasma-gun spraying of: II, properties of resulting products, (5) 177*j*.
plasma-sprayed, properties, (4) 93*f*.
spraying with plasma torch, (2) 58*a*.
ultrarefractory, mechanical properties, (1) 13*b*.
Boron, arsenide, crystalline, P (4) 116*b*.
arsenide-GaAs mixed crystals, preparation and properties, (1) 35*g*.
arsenides, preparation and properties, (1) 35*g*.
boric anhydride, interaction with fluorides of barium and lithium, (4) 140*b*.
and B_4C coatings, formation by vapor deposition, (1) 4*b*.
and BN, as coating for wire, P (9) 304*j*.
and BN, energy structure, investigation by ultralongwave X-ray spectroscopy, (4) 141*c*.
boroxol skeleton, vibrational assignment and valence force field, (1) 9*i*.
carbide, crystal whiskers, catalyst for growth, P (5) 178*d*.
powder plates, pressure sinter method of preparing, P (7) 252*i*.
producing, P (1) 14*j*.
reaction with oxygen, and effect of preirradiation in nuclear reactor, (5) 199*j*.
in clay minerals, geochemistry, (1) 30*h*.
containing coatings, codeposition, P (11) 368*c*.
coordination state, determination by electrode behavior of lithium borosilicate glasses, (2) 48*d*.
fluoride, heat of formation, (2) 55*i*.
halide-phosphorus halide complexes, thermochemistry, (4) 161*f*.
monofluoride molecules, magnetic properties, (2) 80*c*.
monohydride, molecules, magnetic properties, (2) 80*c*,
nitride, and BN composite, static oxidaton and compatibility to 2000°C, (8) 279*h*.
cubic, energy bands in, (4) 135*h*.
effect of ultrahigh pressure, (5) 177*d*.
fiber manufacture, P (6) 217*h*.
fibers embedded in resin matrix, for ablative antenna window compositions, P (5) 178*i*.
formation by reaction of boron trichloride with ammonia, and crystallization by heat treatment, (5) 177*i*.
heat of formation, (2) 55*i*.
hexagonal, irreversible transformation by shock compression, (2) 79*i*.
hexagonal, preparation, P (4) 107*a*.
nitrogen in, gasometric microdetermination, (6) 226*i*.
oxidizability at high temperatures, (2) 54*j*.
production, P (4) 107*d*; P (5) 179*d*.
oxide, crystalline, specific heat and heat of fusion, (4) 155*d*.
crystalline, structure, (6) 238*b*.
molecular structure, (5) 197*g*.
vapor pressure over range 1946°-2419°K, (4) 163*d*.
phosphide, analysis, decomposition of specimens in, (2) 69*c*.
photoluminescence and pair spectrum in, (2) 81*h*.
preparation, (6) 230*i*.
rods, flawless stress-free, apparatus for manufacturing, P (6) 217*g*.
surface, role as adsorption center for sorption of water by porous glass, (4) 97*e*.
systems. See *Systems.*
tetra-, silicide, coating with, P (10) 344*d*.
tetra-, silicide preparation, P (5) 179*f*.
tetragonal modification, formation, (8) 292*j*.
Brazing. See *Soldering.*

Brick. See also *Masonry; Refractories; Structural materials.*
ball mill lining, means for indicating wear, P (6) 225*b*.
burned building, small-scale manufacture, B (4) 168*g*.
calcium silicate, DTA and TGA, application in investigations, (9) 303*i*.
cubes, stabilizing, P (1) 11*h*.
decorative, P (1) 11*h*.
efflorescence, formation and prevention, (4) 101*j*.
efflorescent salts on, identification of by chromatographic separation, (9) 315*a*.
frost resistance. See *Frost resistance.*
full-size, moisture expansion, (6) 214*d*.
future, 1968, (9) 308*g*.
grooved construction and composite of, P (6) 214*d*.
hollow, thermal conductivity determined by electrical modeling, (2) 71*c*.
-making, clays for, B (1) 41*e*.
modern, techniques, quarrying and clay preparation, machinery, and American kilns, (10) 340*d*.
testing, and building, advances in, (2) 54*f*.
panels, prefab urethane bonded, marketed by Chattahoochee, (6) 213*j*.
produced in Denmark, (6) 214*a*.
Swiss prefab process used in, (4) 102*a*.
system of vertical casting of, (2) 54*g*.
protecting in rail shipments with air dunnage bags, (8) 278*e*.
raw materials, sensitivity during drying, and reduction of drying, (10) 340*e*.
sand-lime, resurgence, (8) 278*g*.
sand-molded colonial, popularity, (8) 278*h*.
thermal behavior, effect of raw materials, (8) 278*g*.
and tile, cutting method for manufacture, P (11) 372*g*.
veneer, experiences with shrink foil packaging of, (10) 340*e*.
wire-cut, with and without performations, for walls, performance: I, basis of experimentation; II, strength tests; III, tests of rain penetration; IV, photoelastic investigations of stress distribution in perforated sections, (6) 214*f*.
-work, movement, (10) 340*d*.

Brick industry. See also *Structural clay products industry.*
Acme Brick, automated for growth, (6) 213*j*.
American, B (5) 240*e*.
Belden, chooses flexibility over mass production, (4) 102*b*.
in Canada, (4) 102*e*.
Cherokee Brick and Tile, new approach to flexibility, (4) 102*b*.
costs analyzed, (6) 214*b*.
Denver, installs one-man grinding plant, (8) 278*f*.
dry-pressing in, (7) 249*j*.
Kerabedarf, brick from rubble, (6) 214*b*.
linking with building sites, (9) 308*g*.
Manor Brickcrafters, hand crafts by modern methods, (6) 214*c*.
Milliken, in Pennsylvania, gears for growth, (4) 101*j*.
mining methods compared, (7) 250*a*.
Nassau, modernizes soft mud operation, (4) 102*a*.
Ottumwa, automates with setting machine and tunnel kiln, (4) 102*c*.
packaging, heat shrink, cost, (7) 250*a*.
from siliceous materials, P (1) 11*g*.
in S. Carolina, built from scratch, (4) 102*b*.
in Switzerland, (4) 102*a*.
and tile, refractory construction materials in, (10) 340*e*.
and tile, total energy in, (1) 11*g*.

Brickmaking apparatus and equipment. See also *Dryers; Kilns; Materials handling; Presses.*
automated setting, (8) 284*c*.
for coating with fluid glaze, P (5) 176*f*.
concrete facing, with varied color and texture, P (5) 170*d*.
mottled, P (11) 372*f*.
perforated, P (4) 102*d*.
for stacking, P (2) 54*d*.

Brittle materials, ceramics, Griffith criterion and thermal shock resistance of single-phase vs multiphase, (7) 266*f*.
controlled separation using laser, (10) 343*j*.
crack growth and creep in, (11) 383*i*.
crystalline solids, thermal decomposition produced by fracture in, (9) 320*c*.
effective surface energy, (6) 232*h*.
internal strain energy and strength, (8) 293*f*.
porous ceramics, micromechanical thermal stresses and thermal stress resistance, (6) 235*e*.
solids, controlled fracture of, and interruption of electrical current, (5) 180*f*.
crack bifurcation in, (11) 383*h*.
with high densities of microcracks, analysis of strain at fracture of, (10) 349*h*.
structural ceramics and testing, B (11) 390*i*.
surface layer fracture, by giant laser pulses, (10) 361*i*.
tensile strength, Griffith flaws and effect of porosity, (10) 354*h*.
thermal stability, apparatus for programmed tests of, (2) 68*e*.

Brittleness, and impact resistance, (6) 230*i*.

Bromine, ^{79}Br, temperature dependence of nuclear quadrupole resonance frequency of, in $NaBrO_3$ and $KBrO_3$, (8) 299*j*.

Bromine *(continued)*
high-pressure form, crystallography, (11) 383*d*.
pentafluoride, fluorination of UO with, engineering-scale studies, (5) 177*h*.
vapor, exchange reaction with potassium bromide, (1) 29*c*.

Bronze, alkali rhenium, and WO_3-ReO_3 solid solution, preparation and properties, (4) 150*d*.
fluorine, of composition M_xFeF_3 (M = Na, Rb, Tl), (2) 77*e*.
hydrogen, tetragonal, H_xWO_3, X-ray and neutron diffraction study, (4) 164*e*.
indium tungsten, hexagonal, (11) 385*d*.
La and Y tungsten, (11) 385*c*.
molybdenum, electronic properties, (8) 298*b*.
potassium molybdenum, solid-state studies, (11) 387*e*.
potassium tungsten, hexagonal, Li solution in, (11) 387*e*.
sodium titanium, and related compounds, characteristics, (4) 155*g*.
sodium vanadium, single-crystal studies of electrical conductivity, Seebeck effect, and Hall voltage in, and crystal-field model of electron transport, (1) 17*e*.
tungsten, cubic, relations between lattice parameter and x value for, (11) 387*c*.
preparation from metal halides, (11) 376*d*.
reflectance spectra, (9) 328*i*.

Brucite, decomposition mechanism, (4) 143*h*.
fibrous, thermal insulation, P (6) 218*h*.

Bubbles, cavitation, destruction of glass by (9) 305*j*.
distribution in porcelain glazes, (7) 253*j*.
gas, formation and behavior in nonuniform temperature gradient, (8) 292*h*.
formation in glass melts, dependence on furnace atmosphere, (4) 95*h*.
nucleation, in reactor fuels, influence of irradiation in, (5) 195*j*.
in solids, (2) 77*a*.
krypton, migration in UO_2, (4) 144*f*.
of oxygen and sulfur dioxide, behavior in soda-lime glass, (4) 94*g*.

Building materials. See also *Aggregate, Brick; Enamels; Insulation, thermal; Structural clay products; Structural materials.*
and apparatus for testing, P (4) 119*a*.
block, interlocking, P (5) 176*g*.
casting and facing method and apparatus, P (5) 170*e*.
clay tile block, with passageways, P (4) 102*e*.
elasticity, static moduli, routine measurement with electromechanical transducer, (6) 227*g*.
large glass blocks, (6) 209*i*.
manufacture from siliceous materials, P (1) 11*g*.
panels, of expanded perlite, P (4) 102*g*.
roofing shingles, glass fiber reinforced asphalt, (2) 49*f*.
transport, shrink foils for, (10) 364*a*.
walls, thermal properties, (9) 308*g*.

Bulbs. See *Glass.*

Burners. See also *Flames.*
assembly, producing radiant heat, P (4) 122*h*.
atomizing jet, theoretical analysis of combustion process, (7) 261*f*.
for firing combustion chamber, P (4) 122*i*.
fluid fuel, P (5) 189*c*.
fuel, ignition and flame monitoring control apparatus for, P (2) 72*e*.
gas, P (2) 72*c*.
for atomic absorption spectroscopy, P (6) 227*h*.
for furnace walls, P (5) 189*g*.
radiant, P (7) 261*g*; P (8) 286*f*.
radiant spiral flame, P (5) 189*f*.
replaceable, mounting for, P (2) 72*e*.
with glass-ceramic heating plate, P (6) 212*h*.
industrial furnace, P (6) 228*g*.
for liquid fuel, P (8) 286*f*.
for low intensity radiant heater system, P (1) 23*b*.
natural gas, with added compressed air for heating glassmelting tanks, (9) 306*a*.
nozzle mixing gas, P (4) 123*b*.
plasma, P (11) 369*b*.
projecting into rotary kiln, P (10) 348*b*.
radiant, P (7) 261*g*.
spark ignited gas, P (7) 261*h*.
two fuel, arrangement, P (4) 123*c*.
tube assembly for heat-treating furnace, P (5) 189*g*.

Burning. See also *Calcination; Combustion; Firing; Lime.*

Burnishing. See *Polishing.*

Cadmium, in alkaline electrolytes, nature of anodic films on, (4) 145*f*.
Cd(II) fluoride, sublimation pressure, Knudsen and Langmuir measurements, (1) 31*g*.
CdF_2:Eu, EPR observation of Eu^{3+} to Eu^{2+} transformation in, (2) 77*a*.
$Cd_{1-x}Mg_xTe$, visible electroluminescence from *pn* junctions in, (9) 332*j*.
Cd_4SiS_6 and Cd_4SiSe_6, new ternary compounds, synthesis, photoconductive and fluorescent properties, (4) 109*i*.
$Cd_{1-x}Zn_xS$ single crystals, reflectivity spectra, (4) 153*g*.
fluoride:In and :Eu, optical and electrical properties, (10) 358*a*.
optical spectra of Yb in, (4) 147*e*.
single crystals, preparation and properties, (5) 199*a*.
germanate, high-pressure, garnet-like structures, (5) 194*b*.

Cadmium *(continued)*
hydroxide, adsorption by montmorillonite and kaolinite, (1) 24*g*.
iodide, crystals, of trigonal symmetry, 8-, 9-, and 12-sided growth spirals on, (7) 267*h*.
crystals, epitaxially grown, polytypic structures, (7) 267*h*.
films, vacuum-deposited, structure, (2) 83*i*.
with oxalate ions, complexes, polarographic study, (1) 34*h*.
oxide, single crystals, sublimation studies and preparation, (10) 361*d*.
selenide, control of photoconductive properties in, (4) 129*j*.
ESR of Fe^{3+} centers in, (1) 29*e*.
single crystals, growth by temperature gradient solution zoning in excess Se, (7) 266*f*.
single crystals, quantity of low-frequency current noise in, (5) 199*h*.
-(SeS) platelets, time behavior of exciton formation and laser emission in, (9) 311*f*.
sulfide, amorphous, P (6) 222*h*.
:Cu single crystals, effects of growth conditions on microstructures in, (2) 76*g*.
crystallographic polarity, determination by ion scattering, (7) 265*c*.
crystals, bulk, closed system vapor growth from elemental constituents, (4) 109*j*.
crystals, grown by different methods, nonstoichiometry, (10) 357*g*.
crystals, grown from vapor phase, dislocations and origin in, (4) 131*i*.
crystals, hexagonal, spontaneous polarization, (8) 292*c*.
crystals, hollow, Na-doped, (7) 268*d*.
crystals, sublinear photocurrents and surface recombination in, (2) 83*c*.
crystals, wurtzite-type, optically active lattice vibrations in, (4) 147*d*.
electroabsorption, (4) 134*g*.
electron-irradiated, anisotropic thermal conductivity, (7) 263*i*.
enhancement of Raman cross section in, due to resonant absorption, (2) 76*g*.
frequency shifts during growth of amplified acoustic flux in, (8) 292*c*.
growth from liquid Cd solution, (4) 137*d*.
high-conductivity *p*-type, (4) 138*i*.
interaction with telluric anhydride, (7) 267*f*.
laser-induced stimulated Brillouin scattering in, (9) 321*a*.
liquidus solubilities in metals solvent, (9) 324*f*.
parametric amplification of ultrasonic waves in, (6) 235*e*.
phosphorus-ion-implanted, (4) 149*e*.
recombination kinetics in, (9) 328*f*.
semiconductivity, as function of S-vapor pressure during heat treatment between 500° and 700°C, (10) 360*g*.
single crystal layers, epitaxial growth on ZnS platelets, (10) 353*c*.
single crystal, pure, photoconductivity near band edge, (8) 296*h*.
single crystals, of controlled composition, growth from vapor phase, (10) 354*h*.
single crystals, growth, (10) 354*j*.
trapping level disposition in, (5) 202*a*.
ZnS, and HgS, epitaxial growth on CdS and ZnS, (7) 265*e*.
systems. See *Systems.*
telluride, absorption spectra, effect of high electric field, (5) 193*h*.
cross-substitutional alloys, (2) 83*f*.
cubic, optical absorption of tetrahedral Fe^{2+} ($3d^6$) in, (4) 147*h*.
film growth, properties at substrate temperatures at which the coefficient of CdTe condensation $\alpha<1$, (5) 199*d*.
Fe-doped, absorption changes in, under influence of high electric fields, (4) 111*f*.
improved, for gamma detection between −100° and +100°C, (10) 355*h*.
influence of ionized impurity scattering on Gunn effect and impact ionization in, (1) 31*a*.
infrared absorption spectrum, (4) 140*g*.
n-, produced by ion implantation, type conversion and *pn* junctions in, (4) 163*a*.
superradiance in recombination radiation from, (1) 29*c*.

Calcia. See *Calcium, oxide.*

Calcination. See also *Firing.*
of cement. See *Cement, burning.*
of gelatinous and crystalline aluminum hydroxides, surface chemistry of, (9) 330*f*.
of Grossalmerode clay, effect of AlFs on formation of phases during, (5) 199*b*.
of limestone in fluidized bed, (4) 123*g*.
of Mg carbonate and magnesite containing ZnO, (4) 154*e*.
using pneumatic conveyor, (4) 92*b*.
temperature, effect on properties of MgO for use in Mg oxychloride cements, (8) 274*a*.

Calcining, of bone, (10) 348*f*.
conditions, effect on physical properties of calcined bone, (6) 228*j*.
conditions, effects on properties of MgO particles, (8) 291*i*.

Calcite, aragonite-, transformation, in aqueous solution, temperature controls on, (11) 387*i*.
-aragonite, transformation, catalysis and inhibition in, (6) 230*g*.
depolarization of Raman scattering in, (1) 27*b*.
and dolomite composition, determining with air comparison pycnometer, (1) 21*c*.

Calcite *(continued)*
in ground shale, separation by liquid-liquid particle transfer, (8) 287*g*.
infrared absorption, pressure dependence, (10) 359*i*.
single-crystal, ESR absorption spectrum of Y^{3+}-stabilized Co^{3-} molecule-ion in, (5) 194*d*.
γ-irradiated, ESR absorption spectrum of AsO_3^{2-} molecule-ion in, (10) 353*a*.
motional effects in ESR absorption spectrum of CO_3^- molecule-ions in, (2) 80*f*.
superhyperfine interaction due to ^{13}C in ESR absorption spectrum of Mn^{2+} in, (8) 299*c*.
zero point charge, (5) 203*d*.
Calcium, acid phosphate, anhydrous, decrystallization from dihydrate form, P (5) 191*d*.
α-, sulfate hemihydrate, production, P (4) 93*a*.
aluminates, of high-alumina cements, stability and stabilization possibility of hydration products from, (2) 45*a*.
aluminates, vitreous, stress induced defects in, (1) 38*a*.
aluminoferrites, stability and hydration activity, influence of reducing medium on, (1) 8*a*.
aluminum hydrates, lamellar, crystal structures, (4) 130*e*.
calcareous materials, radioisotope studies, (10) 354*b*.
$Ca_3Al_2(O_4D_4)_3$, garnetoid, neutron and X-ray diffraction study, (5) 197*b*.
$Ca_3(CrO_4,PO_4)Cl$, 80°K crystal spectrum, (8) 290*b*.
$CaFe_2O_4$, neutron diffraction study, (8) 295*j*.
$CaFe_2O_4$, spin relaxation in, Moessbauer effect study, (2) 80*c*.
$Ca_2Fe_2O_5$, magnetic structure, (2) 80*e*.
$CaNb_2O_6$, single crystals, preparation by chemical transport, (7) 268*e*.
CaP_4O_{11}, crystallographic data, (10) 351*f*.
Ca_2PO_4Cl, chlorospodiosite, ESR and optical spectroscopy of CrO_4^{3-} in, (4) 135*j*.
$\alpha CaSO_4{\cdot}^1/_2H_2O$ crystals, dissolution in water, (2) 83*b*; (7) 245*d*.
$CaTiSiO_5$, synthetic, and its germanium analog ($CaTiGeO_5$), (2) 83*h*.
$CaWO_4$:Yb^{3+}, optical absorption spectrum and optical Zeeman effect in, (4) 147*g*.
$Ca_5V_3O_4Cl$ and Ca_5AsO_4Cl, spodiosite, new analogs, (11) 386*i*.
carbide, in molten phase, formation by reaction of quicklime, (4) 123*h*.
reaction with Al_2O_3, (6) 237*a*.
reaction with SiO_2, (6) 237*b*.
reactivity of carbon in formation of, in molten phase, (9) 328*e*.
carbonate, P (8) 288*b*.
crystal, effects of initial reaction between milky lime and carbon dioxide gas on, (4) 91*c*.
crystallization modifications, (7) 264*i*.
estimation in limestone, dolomite, and other calcareous materials, (4) 119*f*.
and sulfate, forms in aerated portland cement, (4) 91*f*.
thermal decomposition, influence of dislocations, (4) 139*i*.
and ZrO_2 mixture, complex study of processes during heating of, (7) 264*a*.
chloride, effect on structure formation of lime-clay suspensions, (7) 253*f*.
chloride, interaction with gallium chloride, (4) 140*e*.
chlorophosphate crystal, pentavalent Mn-activated, for use in coherent light source, P (6) 221*b*.
chlorovanadates, blue luminescence in, (2) 75*a*.
determination by new metallochromic indicators of "calcon" type, (6) 235*g*.
determination by X-ray fluorescence analysis, (2) 68*f*.
dicalcium silicate, γ-, hydrothermal relations, (4) 139*j*.
reaction with sodium aluminate, (1) 3*a*.
solution kinetics in liquid phase of cement clinker, (8) 274*g*.
excess, uptake by calcium fluoride, diffusion processes during, (10) 352*j*.
ferrite, synthetic, mineralogical and metallurgical properties, (11) 374*j*.
ferrites, Moessbauer effect studies: I, temperatures above Néel point, (4) 145*d*.
fluor- and chlorapatite crystals, growth and crystallographic properties, (4) 137*g*.
fluoride, behavior of F^- interstitals during reduction of Dy^{3+} ions in, (4) 127*e*.
:Dy^{3+} crystals, generation of giant pulses in, using electrooptical shutter with $LiNbO_3$ crystal, (2) 77*b*.
elastic constants, pressure and temperature derivatives of, (9) 328*e*.
electron nuclear double resonance of *F* center in, (1) 28*i*.
irradiated, Y^{2+} as color center in, (11) 388*e*.
optical spectra of Pu in, (4) 147*c*.
plastic deformation, role of grain boundaries in, (2) 82*e*.
rare-earth-doped, photoreversible charge transfer in, (10) 358*g*.
single crystal, kinetics of hydrolysis from 1000° to 1120°C, (5) 196*e*.
zero-splittings of Am^{2+} and Cm^{3+} in cubic symmetry sites in, (4) 164*c*.
fluorophosphate, crystals, Czochralski growth, (9) 319*e*.
germanate, high-pressure, garnet-like structures, (5) 194*b*.

Calcium *(continued)*
hydrate pastes, flow properties, (11) 367*j*.
hydrosilicates, synthesis of wollastonite from, (11) 387*j*.
hydroxide, added to increase bending strength of humus-containing clays, (11) 382*e*.
and $Ca(OD)_2$ vibrational crystal structure, normal coordinate, analysis, and assignment, (4) 127*c*.
carbonatation, investigated by thermal and X-ray diffraction methods of analysis, (8) 289*b*.
compacts, length change characteristics on exposure to water vapor, (8) 286*j*.
effect on structural formation of clay suspensions, (7) 253*e*.
high purity, P (10) 349*b*.
reaction with allophane-kaolinite clay minerals, (8) 278*i*.
thermal dissociation at elevated pressures, (9) 332*b*.
in magnesite, determination by complexometric method employing coprecipitation of Ca and Sr sulfate, (6) 225*f*.
and Mg values, separation from Ca and Mg carbonates, P (4) 125*b*.
and Mn, double oxide, orthorhombic $CaMnsO_4$, structural study, (1) 38*d*.
metaborate, polycrystalline, ^{11}B NMR in, (2) 46*j*.
microdetermination in mixture, (9) 315*j*.
in minerals, photocolorimetric determination with aid of Arsenazo, (6) 226*j*.
molybdate, dielectric constants, (4) 131*a*.
molybdate, segregation coefficients of rare earth niobates in, (4) 154*c*.
nitride and cyanamide, formation and reactivity, (10) 353*i*.
nitride, vapor pressure and heats of sublimation, (8) 300*f*.
nitrite, as accelerator for portland cement, P (5) 170*j*.
orthophosphates, luminescence, activated by divalent Eu, (10) 356*c*.
orthosilicate and tricalcium silicate, high temperature studies to 1900°C, (7) 266*e*.
oxalate pyrolysis, kinetics, (4) 142*a*.
oxidation, reaction mechanisms, (4) 157*b*.
oxide. See also *Lime*.
Bi-doped and undoped, stress and Zeeman spectra in, (7) 269*a*.
color centers, Faraday rotation studies in, (8) 292*g*.
computed ground state properties in molecular orbital approximation, (8) 289*d*.
electric fusion crystallization, P (4) 106*d*.
electronic absorption spectrum of Ni^{2+} in, (8) 291*j*.
fabrication, characterization, and properties, (10) 350*j*.
irradiated, surface centers and fast irreversible oxygen adsorption on, (4) 128*d*.
kinetics of solution, in liquid phase of cement clinker, (7) 245*a*.
low-temperature thermal expansion, (10) 356*b*.
and MgO, high purity, recovery from magnesite and calcite ores, P (4) 125*h*.
in mineral standards, X-ray spectrometric determination by decomposition method, (6) 227*f*.
paramagnetic resonance of *N* center in, (11) 386*c*.
-SiO_2 ceramic materials, relatively high, P (11) 375*d*.
single crystal, grown in plasma furnace, properties, (1) 20*e*.
surface, paramagnetic defects associated with hydrogen adsorbed on, (5) 198*e*.
trace impurities in, (2) 69*d*.
transformation to CaS at 1400° to 1650°C, (4) 162*a*.
X-irradiated polycrystalline, thermoluminescent study, (9) 332*a*.
phosphate, amorphous, transformation to crystalline, influence of pyrophosphate on, (5) 195*b*.
phosphate, binary, surface tensions and molar volumes, (4) 158*g*.
polarographic determination, (9) 315*b*.
separation, quantitative, (1) 21*g*.
silicate, compositions, effect of cryolite, P (9) 304*b*.
hydrate, hydrothermal synthesis, influence of pore space, (11) 368*c*.
hydration, influence of tricalcium aluminate, (4) 140*e*.
in solution, reactions in liquid calcium fluoride, (4) 152*g*.
and surface layers in aqueous electrolyte solutions, (6) 230*j*.
in silicate minerals, colorimetric determination, (7) 259*j*.
silicofluoride, of tentative composition $(3CaO{\cdot}SiO_2)_2{\cdot}CaF_2$, (4) 127*h*.
in solutions of high sodium content, flame photometric determination, (7) 260*d*.
spurrite, formation in raw cement mixes, (11) 368*a*.
sulfate, role in manufacture of portland cement clinker, (6) 206*g*.
sulfate alpha-hemihydrate slurries, for casting in molds, preparation, P (6) 207*c*.
sulfate dihydrate, dehydration process, (5) 170*d*.
formed in media rich in phosphoric acid: I, precipitation; II, derived calcium sulfate hemihydrate, (9) 325*i*.

Calcium, sulfate *(continued)*
solubility in hydrochloric acid solutions, (9) 329*a*.
sulfate hemihydrates, formation, microscopic observation, (5) 170*g*.
heat of hydration measured by method of dissolution in HCl, (5) 170*c*.
preparation by autoclave process, (9) 304*c*.
reactivity, (2) 45*f*.
setting, retarders and accelerators for, (4) 92*c*.
sulfoaluminate hydrates, morphology, (11) 368*f*.
sulfonate, adsorption on $CaCO_3$, crystal structure effects in, (1) 26*c*.
in synthetic hydroxylapatite, complexometric determination, (6) 225*i*.
systems. See *Systems*.
tricalcium aluminate, hydration, influence of amorphous $Al(OH)_3$, (9) 323*d*.
influence on hydration of calcium silicates, (4) 140*e*.
isomorphic substitution phenomena in, (9) 304*c*.
tricalcium aluminate hexahydrate, dehyroxylation, (2) 44*c*.
tricalcium silicate, and β-dicalcium silicate, early hydration in neat portland cement pastes, (2) 44*c*.
chemical and structural studies of solid solutions, (2) 43*j*.
early hydration, solid reaction with induction and acceleration periods, (11) 384*c*.
effect of CrO on structural changes in, (6) 231*j*.
formation velocity, studies to stabilize and to increase, (8) 298*f*.
hydration, (8) 286*h*.
hydration, influence of $Al(OH)_3$ and lime, (9) 323*a*.
properties, effect of Mn, Fe, and F_2, (10) 336*a*.
solution kinetics in liquid phase of cement clinker, (8) 274*g*.
and tricalcium germanate, solid solutions between, (8) 297*g*.
tungstate, Bi-doped, phototropy, (4) 149*h*.
low-temperature thermal properties, (9) 324*g*.
and molybdate, lattice perturbations in, (2) 79*e*.
optical properties, influence of impurity defects, (4) 140*c*.
spin-resonance properties: I, vanadium in, (4) 155*i*.
Yb^{3+} spectrum in, by microwave-optical double resonance using polarized light, (5) 197*d*.
Calibration, of University of Southern California automatically recording settling tube, (11) 379*i*.
Calorimeter, differential scanning, with radiant heating and control, (9) 315*c*.
high-temperature adiabatic drop, for enthalpies of α-Al_2O_3, UC_2, and US between 330° and 1700°K, (5) 194*b*.
for measurement of thermal properties and dimensional changes, (9) 314*j*.
for measuring heat capacities at 1°–20°K and between 1.5° and 300°K for CaBr and CaI crystals, (4) 160*g*.
micro reaction, design and testing, (4) 119*i*.
quotient, principle and basic theory, (4) 120*g*.
Calorimetry, dynamic differential, quantitative application: II, heats of formation of group IIIA arsenides, (4) 151*f*.
fluorine bomb: XIII, enthalpy of formatior of AsF_5, (1) 29*i*.
halogen combustion, of refractory compounds—heats of formation of BN and BF_3, (2) 55*i*.
high-temperature solution, application to oxide systems, (5) 192*e*.
of molten Na_2MoO_4-MoO_3 mixtures at 970°K, (11) 383*e*.
Cameras. See *Photography*.
Capacitors, P (4) 115*c*; P (5) 182*g*.
$BaTiO_3$, controlled reduction and reoxidation of, and resulting capacitor, P (5) 182*a*.
$BaTiO_3$, donor-acceptor ion-modified, and process, P (5) 182*g*.
boron nitride film, P (4) 115*j*.
capacitance-adjusted ceramic, P (10) 344*c*.
capacitance and dissipation factor, apparatus and method for directly measuring, P (11) 376*g*.
ceramic, P (4) 112*f*.
ceramic, comprising semiconductive $BaTiO_3$ body and silver alloy electrodes containing minor amount of Cu, Ca, or Bi, P (4) 112*g*.
comprising ferroelectric ceramic with oxide silver electrodes and heterojunction barrier layer between electrodes and ceramic, P (4) 112*f*.
cylindrical ceramic, P (7) 257*j*.
dielectric compositions and capacitors made from, P (7) 255*h*.
foil solid Ta, powder on, P (11) 378*f*.
glass, P (11) 377*c*.
glass, life characteristics, (4) 96*a*.
hermetically sealed, P (11) 376*i*.
high temperature, construction, P (6) 223*g*.
junction, P (10) 345*d*.
Pb-Ti-O, amorphous, (8) 280*h*.
light responsive variable, P (5) 183*h*.
making with oxygen-pervasive and oxygen-impervious electrode, P (6) 222*f*.
making by vacuum depositing manganese oxide as electrolytic layer, P (6) 222*e*.

Capacitors *(continued)*
metal-insulator-semiconductor, radiation effects in, determined from conductance measurements, (1) 17*a*.
metal-oxide-semiconductor, using genetic semiconductor compound as dielectric, P (1) 18*a*.
MNS, memory behavior, (4) 144*f*.
for miniature electronic circuits, P (6) 220*i*.
moisture sensitive, P (10) 345*i*.
monolithic ceramic, platinum metal electrodes in fired multilayer construction, (7) 255*g*.
monolithic ceramic, treating, P (5) 184*f*.
multilayer ceramic, P (10) 345*g*.
multiple, P (5) 184*a*.
Nb_2O_5 thin film, growth and properties, (5) 181*f*.
pn junction, voltage-sensitive variable, with intermediate control zone, P (4) 117*e*.
solid electrolytic, with mixed dioxide semiconductor layer, P (11) 378*j*.
solid thin film, P (7) 256*g*.
stacked mica, with multiple value mica film, P (1) 19*b*.
thin film, P (11) 378*g*.
charting and removing defects in, P (2) 66*i*.
and method of adjusting capacitance, P (1) 19*g*.
thin film decoupling, incorporated in integrated circuit chip, P (11) 379*e*.
wire, powder on, P (5) 184*h*.
Carbides. See also specific types.
boro-, pyrolytic preparation, (8) 297*a*.
cemented, toughness testing, influence of sample preparation on Palmqvist's method for, (10) 347*h*.
composite, flame spray material, P (4) 93*j*.
compounds, formation by vapor deposition on graphite bodies, P (11) 374*i*.
couples, ceramics-cemented, friction and wear behavior, (5) 177*j*.
eta, of Mo-Fe, Mo-Co, and Mo-Ni, (10) 353*g*.
formation in CaO-SiO_2-Al_2O_3 system, thermodynamics, (4) 161*h*.
of group IVA and VA elements, anomalous superconducting properties, (10) 350*d*.
iron-manganese, tetragonal and hexagonal, (7) 270*f*.
metal, fibers, textiles, and shapes, production, P (1) 14*f*.
metal, finely divided crystalline, preparation, P (7) 253*b*.
metallic, P (1) 14*f*.
metallic, extruding, particularly uranium monocarbide, P (6) 217*g*.
mixed, production by auxiliary metal bath technique, (6) 236*a*.
molding and sintering methods, (2) 56*e*.
mono-, cubic refractory, cohesion in, (5) 192*j*.
sintered hard masses, disintegrating, P (7) 243*g*.
ternary, in system U-M-C, (10) 362*j*.
transition metal, interaction with liquid platinum, (5) 195*d*.
transition metal, low-temperature electrical properties, (8) 294*h*.
ultrarefractory, mechanical properties, (1) 13*b*.
ultrarefractory, mechanical properties at high temperature, (1) 12*b*.
Carbon. See also *Graphite*.
active, formation in twin-crucible studies of vanadium carbonitride solutions, (7) 265*j*.
as adsorbent and catalyst, (7) 261*j*.
allotropic form, observations, (1) 382*a*.
atoms, thermal vibration amplitudes, in graphite lattice parallel to *c* axis, (4) 161*c*.
batch, effect on strength of E-glass fibers, (11) 369*e*.
black-kaolin materials, sintered composite, electrical resistivity: IX, effects of firing time, firing atmosphere, and forming process on; X, effects of carbon materials on temperature dependence of resistivity; XI, resistivity-temperature dependence of compositions containing excess silica, (4) 134*g*; (5) 181*b*.
bodies, reinforced, P (11) 375*b*.
bodies, review, (11) 372*i*.
C_6H_6, CS_2, and CCl_4, high-pressure forms, crystallography, (11) 383*d*.
chemistry and physics: Vols. 1 and 2, B (5) 203*i*; Vol. 3, B (6) 240*g*.
composition, P (8) 279*j*.
continuous analysis, with flame ionization detector, P (4) 121*g*.
crystallographic axes, effect of high uniaxial pressure along, (9) 320*h*.
determination, in flue dust, fly ash, and cement clinker, (2) 69*f*.
diffusion, in single crystal graphite, (10) 352*d*.
in TaC, (8) 290*h*.
in UC, (10) 352*e*.
dioxide, gas, initial reaction with milky lime, effects on crystal of Ca-CO_3, (4) 91*f*.
liquid, inclusions, in quartz veins, (1) 38*f*.
and water, adsorption on MgO, infrared study, (8) 293*c*.
effect on δ-peritectoid reaction in U-Si alloys, (8) 291*c*.
effect on strength of thorium, (4) 132*h*.
evaporated, deposition, effect of substrate structure, (4) 110*c*.
fibers. See *Fibers*.
fibrous, products, decreasing metallic impurities of, P (4) 106*g*.
formation in $CaCO_3$-SiO_2 system at high pressures and temperatures, (4) 127*e*.
free, determination in TiC, ZrC, and HfC, (2) 69*h*.
Carbon *(continued)*
graphitization, effect of pressure: I, heat treatment of soft C under 1, 3, and 5 kbars, (4) 133*g*.
industrial, body, with oxidation inhibiting coating, P (11) 374*f*.
macroporous vitreous, P (8) 279*j*.
massive pyrolytic, deposition, P (1) 13*h*.
monoxide, atmosphere, behavior of refractory products in, (10) 340*f*.
equilibrium pressure above uranium oxycarbides in presence of UO_2, (1) 29*h*.
isotope exchange with TaC, (10) 350*b*.
photosensitized oxidation, on semiconductors supported by silver, (5) 181*a*.
organic, relations with grain size, clay content, and quartz, in Lake Erie and Lake Ontario sediments, (11) 382*f*.
and oxygen isotopic composition of marine carbonate sediments, factors affecting: III, Eniwetok Atoll, (6) 229*a*.
pyro-, production by reactions occurring on solar hot front, (5) 178*c*.
reactivity in formation of CaC_2 in molten phase, (9) 328*c*.
removal from mixtures of tungsten powder and thoria and insuring uniform dispersion of thoria, P (9) 317*g*.
in sediments, gasometric determination by hydroxide absorption, (1) 21*a*.
solubility in cobalt and nickel, (4) 155*f*.
solubility limit and diffusivity, in Mo, (1) 37*i*.
suboxide, solid, photoinduced reactions in, (4) 149*h*.
systems. See *Systems*.
tensile creep rate, stress dependent, (8) 298*a*.
tetrachloride, inhibiting effect on graphite oxidation, (9) 323*b*.
interaction with gallium chloride, (8) 293*c*.
vibrational relaxation in, (5) 203*b*.
Carbonaceous materials, behavior at very high pressures and high temperatures, (1) 25*a*.
body, angular, uniformly heating, P (2) 59*h*.
converting to diamond, P (10) 335*f*.
friction coefficient, stabilizing, and products thereof, P (5) 179*g*.
producing method, P (5) 179*c*.
solid, metal contaminant removal from, P (10) 342*h*.
Carbonates, alkali metal, preparation from corresponding sulfates or sulfides, P (1) 24*c*.
carbonatation of $Ca(OH)_2$ investigated by thermal and X-ray diffraction methods of analysis, (8) 289*b*.
facies and paleogeography of Blackjack Creek formation (Pennsylvanian), Missouri, (8) 286*h*.
lithified, from deep sea of equatorial Atlantic, (6) 229*c*.
minerals, simultaneous flotation with silica phosphates, P (6) 230*c*.
molten alkali, mixtures, tracer diffusion measurements in, (1) 39*h*.
of rare earths, P (1) 24*d*.
sediments, impure, froth flotation for, (1) 23*f*.
sediments, off west coast of Barbados, W. I., submarine cementation, (1) 23*i*.
Carburization, of Fe-Cr alloys during oxidation in dry CO_2, (4) 127*f*.
Castables, and moldables, (6) 224*g*.
Casting. See also *Molding; Molds; Refractories; Slip casting*.
apparatus, centrifugal, with smooth refractory nonhydrocarbon mold coating, P (7) 252*e*.
centrifugal method, P (10) 342*b*.
ceramic, techniques, P (6) 220*d*.
ceramic articles, automatic apparatus with continuously moving conveyors for, P (4) 109*b*.
ceramic articles, including separate closed loop conveyors for molds and cores, apparatus for, P (9) 309*j*.
ceramic fixture apparatus, with molds forming separate sections of fixture and means mating sections, P (9) 310*a*.
ceramic shapes, P (2) 61*a*.
continuous, refractories for, (1) 13*b*.
continuous, of steel, P (4) 93*j*.
cooling, with different thermophysical characteristics in mold and external insulation, calculation of temperature field, (2) 47*a*.
cylindrical grinding media, and mold for, P (1) 20*e*.
high Al_2O_3 shapes, (10) 340*g*.
methods, effect on magnesia brick properties, (11) 373*c*.
operation, investment, expanded by abrasive processes, (5) 169*f*.
of porcelain composition, effect of organic additions on rate and nature, (5) 179*j*.
precision investment, expendable pattern for, P (5) 178*g*.
process, practice, (6) 224*j*.
properties, of Al_2O_3 slip, (6) 224*f*.
slips. See *Slips*.
vertical, of brick panels, (2) 54*g*.
Cast Iron. See *Enameling metals; Iron*.
Catalysis, of graphitization of furfuryl alcohol coke by titanium and vanadium, (1) 11*j*.
Catalysts, alumina base, P (1) 24*c*.
Al_2O_3-Cr_2O_3, magnetic studies on, (6) 234*f*.
carbon as, (7) 261*j*.
clay, for polymerization of unsaturated fatty acids, P (4) 124*i*.
from clays converted to crystalline aluminosilicates, P (6) 229*c*.
cobalt molybdate, two stage heat treatment of, P (4) 126*a*.
$CuCr_2O_4$, magnetic studies, (6) 234*h*.
Catalysts *(continued)*
crystalline aluminosilicate-containing, treating and using, P (6) 229*d*.
crystalline zeolite composite, P (6) 230*b*.
gauze, ceramic support for, P (5) 178*g*.
for growth of B_4C crystal whiskers, P (5) 178*d*.
mixed oxide of Th and U monophased oxidation, P (11) 382*f*.
oxidation, P (6) 229*j*.
oxidatively regenerated molecular sieve, treatment, P (9) 317*g*.
oxide oxidation, mixed, with improved selectivity, production, P (1) 24*b*.
role in GeO_2 transformation, (6) 237*a*.
semiconducting, P (5) 183*a*.
support, silica-alumina, P (1) 24*f*.
supported, P (7) 263*a*.
Cathode-ray tubes. See *Tubes*.
Cathodes, electronic, with brushlike structure and relatively thick oxide emissive coating, P (4) 112*h*.
dispenser, made of tungsten powder with grain size <3 μm, P (11) 376*c*.
fast warmup, P (6) 221*j*.
heated, P (1) 18*g*.
high reactive, of rare-earth borides, holder for, P (11) 376*j*.
indirectly heated dispenser, for electric discharge tubes, P (10) 345*b*.
oxide, unified model, gives prominence to role of localized surface states on small crystals, (4) 111*h*.
processes, in molten nitrates and nitrites, (4) 127*g*.
secondary emission, or dynode, of porous matrix of W or Mo impregnated with secondary emission material, P (11) 378*b*.
structures, with metal-coated powders on base, P (2) 66*g*.
system, lanthanum, hexaboride, for electron beam generator, P (7) 256*g*.
Ta, in plasma devices, sputtering protection for, P (9) 314*d*.
temperature, electronic (initial current) measurement of, (6) 226*f*.
thermionic, P (6) 224*d*.
of thermionic valve, filament wire for use in, P (4) 113*d*.
thin-film cold, P (8) 284*a*.
tunnel, in matrix form with integral storage feature, P (8) 284*b*.
Cathodoluminescence. See *Luminescence*.
Cations. See *Ions, cations*.
Cells, $BaAl_2O_4$, precise determination, and certification of formation of iron-bearing solid solution, (1) 35*f*.
convection, constitutional supercooling in presence of, (4) 129*f*.
electroluminescent, comprising Zn-doped GaAs on one surface of SiN layer and spaced Cr-Au electrodes on other surface, P (5) 182*i*.
filamentary thermal, with ionically conductive glass coating, P (4) 94*a*.
fuel. See *Fuels, cells*.
galvanic, and gas equilibration techniques, (2) 69*f*.
high-temperature sample, for Kratky small-angle X-ray camera, (9) 315*g*.
Knudsen, thermochemistry of UOS; evaporation of US-UO_2 mixtures; on attainment of equilibrium in, (10) 362*i*.
liquid laser, P (9) 307*g*.
oxygen concentration, for measurement of oxygen pressure change in oxide powders, (1) 32*b*.
photo-, *pn*, epitaxially deposited on transparent substrate, P (7) 257*g*.
photoconductive, with high stability and dark resistance, P (8) 283*g*.
photoconductive thin film, responding to broad spectral range of light input, P (9) 313*b*.
photovoltaic, P (7) 257*g*.
CdS, attaching collector grid to, P (8) 283*j*.
heterojunction, with shorted substrate, P (10) 345*a*.
with integral protective covering, P (7) 257*b*.
panels, from nonuniform dendrites, P (4) 117*a*.
semiconductor, P (11) 377*d*.
silicon, making electrical contact on, and resultant product, P (6) 222*h*.
selenium memory, containing Ag up to 2 at.% adjacent rectifying contact, P (9) 313*h*.
solid-state electrochemical, based on ion conductive ceramics, (5) 188*e*.
thermo-, $(ZrO_2)_{0.85}(CaO)_{0.15}$ electrolyte, Seebeck coefficient of, (5) 199*f*.
unit-, parameters of synthetic diopside-hedenbergite solid solutions, (10) 363*d*.
X-ray spectrometer sample, with adjustable secondary X-radiation radiator and taut X-ray transparent window, P (2) 72*a*.
Celsian, polymorphism, (6) 238*d*.
Cement industry, automation in, (8) 274*g*.
material transport and homogenization in, (2) 44*f*.
in Philippines, suitable sites for, (1) 3*d*.
Cements. See also *Concrete; Mortars; Plasters; Pozzolans; Refractories*.
acid-resistant products, P (8) 304*f*.
Al_2O_3, high, (10) 336*d*.
long-time performance, (8) 274*b*.
physical properties, (11) 373*a*.
aluminous, early hydration, (11) 373*h*.
analysis, by atomic-absorption spectrophotometry, (7) 259*g*.

Cements *(continued)*
aqueous $Ni(NO_3)_2$ MgO, bonding mechanism in, (4) 92*a*.
asbestos-, products, impregnation with thermosetting formaldehyde resin, P (4) 92*i*.
ASTM standards, B (9) 333*h*.
bulk, method and apparatus for handling, P (6) 207*e*.
calcareous, strength development in, (4) 92*h*.
calcite, ferroan and nonferroan, in Pleistocene-Recent carbonates from New Hebrides, (11) 384*j*.
calcite, precipitational environment and correlation, deduced from artificial staining, (11) 380*e*.
carbonaceous, P (7) 252*d*.
cementation, submarine, of carbonate sediments off west coast of Barbados, W.I., (1) 23*i*.
cementitious articles, coating with hexavalent chromium-resinous dispersions, P (5) 170*f*.
chemistry, differential thermal analysis in, B (10) 364*b*.
clinker, carbon determination in, (2) 69*f*.
determination of free lime in, (2) 70*h*.
grate cooler control method and apparatus for, P (1) 3*g*.
grinding, gypsum waste products from boric acid production as additives in, (1) 2*f*.
hydration, effect of gypsum addition, (4) 91*i*.
liquid phase, solution kinetics of dicalcium and tricalcium silicate in, (8) 274*g*.
minerals, mixtures, and cements, hydration during initial periods, (1) 2*h*.
overgrinding, (11) 368*f*.
quality, petrographic control, (1) 3*f*.
X-ray diffraction analysis for determination of percentage of compounds in, P (6) 207*c*.
and clinkers, siliceous limestones, and raw mixes, analysis by atomic absorption spectrophotometry and hydrofluoric acid decomposition technique, (8) 284*i*.
cobalt determination in, (4) 91*e*.
compositions, P (4) 92*f*.
influence on shrinkage of high-strength concretes, (7) 244*i*.
lightweight high-strength, P (9) 304*c*.
concrete surfaces, sealing process for, P (9) 304*d*.
constitution, structural research into: II, isomorphic substitution phenomena in tricalcium aluminates, (9) 304*c*.
ferro-, boats, (7) 244*h*.
grinding efficiencies, increasing, P (5) 191*b*.
hardening, hydrothermal, materials for, (2) 44*f*.
high strength, production and properties, (2) 44*d*.
high temperature, P (6) 217*a*.
hydrated, carbonatation shrinkage, mechanism, (9) 303*j*.
hydration, rate equation, (11) 368*b*.
hydraulic, and aeroconcrete, use of Posidonia shales Lias Epsilon from Brunswick-Hondelage for manufacture of, (4) 92*d*.
hydraulic, curing method, P (6) 207*e*.
hydraulic mix, and additive, P (6) 207*d*.
hydraulic mix, containing saccharide polymers, P (6) 207*d*.
inorganic, hardening: II, effect of bivalent and trivalent ions on structure and strength of hardened Zn-phosphate cements, (7) 245*f*.
kilns. See *Kilns*.
low alkali content, production, P (9) 304*d*.
Mg oxychloride, effect of calcination temperature on properties of MgO for use in, (8) 274*a*.
Mg oxychloride, manufacture, catalytic action of NaCl on decomposition of dolomite for, (2) 43*i*.
making, P (8) 274*c*.
making, combined with waste treatment, method and means, P (8) 274*a*.
market, (7) 244*h*.
material, and phosphoric acid, production process, P (7) 245*f*.
mills. See *Mills*.
mixes, gap graded, design with poor grades of sand using rounded aggregates, (1) 2*f*.
mixing, kinks unsnarled by sonar system, (6) 206*j*.
mortars. See *Mortars*.
oil well, P (4) 93*a*.
paste, drying-rate curve and use in analyzing drying behavior, (1) 2*d*.
hardened, pore volume, influence on resistance of concrete exposed to seawater, (1) 3*a*.
portland, fiber reinforcement, (5) 170*g*.
steam-cured, sulfate-bearing phases in, (6) 206*j*.
phosphoanhydrite, strength, and phase transitions during firing of phosphogypsum, (8) 274*e*.
plugging, from ferromanganese slags, (1) 3*g*.
plugging, from phosphorous slag, (1) 3*h*.
portland, aerated, forms of $CaCO_3$ and $CaSO_4$ in, (4) 91*f*.
aromatic acetates as grinding aids in, P (5) 170*d*.
burning, effect of reducing atmospheres on combination of constituent oxides in, (4) 91*e*.
compositions, P (4) 93*c*.
constitutional supersaturation in, solidified by hydration, (7) 244*h*.
early stage of hydration of $3CaO \cdot Al_2O_3$ and

Cements, portland *(continued)*
$Na_2O \cdot 8CaO \cdot 3Al_2O_3$ as clinker minerals of, (4) 91*g*.
effect of chloride solutions on, (2) 44*g*.
hardening, accelerator for, P (5) 170*j*.
hardening kinetics, influence of inorganic salts and combinations on, (2) 44*e*.
hardening, retarded by $AlPO_4$, P (2) 45*f*.
hydrated compacts, properties, effect of organic surface agents, (1) 2*i*.
hydrating, reaction with ultramarine blue, (2) 45*e*.
hydration, effect of soluble inorganic admixtures on, (2) 44*i*.
kiln feed control, P (5) 170*f*.
and minerals, ground with grinding aids, P (8) 274*d*.
pseudomorphs of original cement grains observed in hardened pastes, (8) 274*f*.
rapidly hardening slag, hydration chemistry of, (1) 2*e*.
reinforced with glass fibers, (1) 7*e*.
slag, hardening during steaming, (1) 2*g*.
and sulfate-resisting, identification in hardened concrete samples, (6) 206*i*.
uncombined MgO in, quantitative determination by X-ray diffractometry, (9) 304*b*.
volume changes on heating, (6) 206*j*.
portland blast-furnace slag, laboratory studies, (1) 3*b*.
portland clinker, adhesion with basic refractories, (1) 12*d*.
alite and belite crystallization in, effect of additives, (1) 2*g*.
chemical and mineralogical processes in kiln, (6) 206*h*.
grinding, P (5) 170*h*.
manufacture, role of calcium sulfate in, (6) 206*g*.
white, influence of mineralizers on formation, (4) 92*a*.
preconditioning cohesive soils for stabilization with, (4) 92*c*.
production process, P (7) 245*e*.
proportioning with fly ash for strength and economy in concrete production, (2) 45*d*.
quality, relation to grinding temperature, (4) 92*d*.
raw materials. See *Materials, raw*.
raw mixes, spurrite formation in, (11) 368*a*.
reinforced hydraulic, and casts from, P (11) 368*f*.
-rock possibilities in Paleozoic rocks of eastern North Dakota, (9) 316*g*.
set retarding composition, P (6) 207*c*.
setting, ferrous sulfate as retarder, P (5) 170*e*.
silicate, subterranean consolidation, P (9) 304*f*.
sinter, fluxed, qualitative improvement, (10) 336*b*.
slag compositions, P (9) 304*e*.
slurry, hydraulic classification, improvement, (1) 2*j*.
solid solution, P (8) 274*f*.
sorel. See *Cement, magnesium oxychloride*.
special, forming process, P (7) 245*d*.
steam cured, P (9) 304*e*.
-sulfuric acid process at British Columbia, (7) 244*h*.
superwhite, P (5) 170*g*.
systems, P (9) 304*a*.
testing, RILEM-Cembureau method, (1) 2*e*.
testing, specification for standard sand for, (4) 92*h*.
water glass, hardener for, P (8) 274*b*.
white, P (9) 304*c*.
Centrifuges, modified, for heavy liquid separations, (1) 21*d*.
screen, wash, arrangement for, P (5) 191*g*.
Cermet. See *Cermets*.
Ceramic engineering. See *Engineering*.
Ceramic industry, clays for brickmaking and application in, B (1) 41*e*.
management through production at Stark, (4) 164*i*.
production operations and reference system for parts produced, (2) 85*b*.
short-cut formula may predict product's chance of success, (6) 240*d*.
Spanish, (6) 240*d*.
Ceramic materials. See also *Bodies, ceramic; Materials, raw;* and specific types.
binder and lubricant in, quantitative determination by TGA, (5) 187*j*.
deformation behavior, (6) 231*d*.
elasticity static moduli, routine measurement with electromechanical transducer, (6) 227*g*.
high temperature cross bending strength testing of, (6) 226*j*.
irradiation influence on, (2) 60*f*.
oxide-, sintering characteristics, based on MgO-Al_2O_3-spinel, (1) 36*e*.
problems of mechanics, (2) 85*c*.
for structural components, (1) 40*d*.
thermal behavior, on basis of crystal chemistry, (1) 39*j*.
toughness, measuring method, (6) 226*e*.
Ceramic-metal systems. See also *Enamels*.
aluminum-porcelain enamel interface as observed by electron microscopy, (10) 336*e*.
automating porcelain pretreatments, (7) 246*i*
bonds, forming, P (6) 208*d*.
cast iron bath tubs and stoves, enameling, (10) 336*h*.
in changing world, review, (1) 40*e*.
coated nickel base engine alloys, P (9) 304*h*.
coating heater coils, P (9) 304*h*.
coating metals with silicide layer and outer layer of Al silicate, P (8) 275*e*.

Ceramic-metal systems *(continued)*
combination drawing compounds and rust preventives, mill applied, (8) 275*a*.
electrocoating acid resistant porcelain panels, (7) 245*j*.
fixing backwave deposited metal onto beveling root, P (8) 275*f*.
high-temperature temporary protective ceramic coating compositions for metals, and resulting coated metal articles, P (11) 369*c*.
metal parts of artificial heart coated with enamel, (10) 336*e*.
metal surfaced with boron and coating of Si, SiC, or TiN, P (7) 246*f*.
patch kits, commercial, tests and evaluation, (7) 245*h*.
patching ceramic lined equipment, and patch for, P (4) 94*d*.
porcelain enameled parts from precoated coils, (5) 171*i*.
rust preventive for, selection and application, (5) 171*i*.
steel, thick plate, stress in enamels for, (10) 336*i*.
treatment systems, automatic control of, (1) 3*j*.
vacuum pack and vacuum slip-pack processes for coating refractory metals, (7) 246*a*.
vignetting or highlighting practices after application by electrostatic spray, (7) 246*c*.
welded joints between Al_2O_3 and metals, mechanical and thermal properties, (7) 246*b*.
Ceramics, articles, molded, P (7) 256*g*; drying on form, P (7) 259*c*.
in changing world, review, (1) 40*e*.
from liquids, (5) 189*j*.
medieval, neutron activation analysis, (4) 120*f*.
in modern world, B (2) 85*e*.
objects, new methods of forming, (2) 60*i*.
physical and chemical principles, B (10) 365*e*.
plasma sprayed, specialty of new plant, (2) 46*a*.
potential, (6) 240*e*.
products, apparatus for manufacture, P (10) 346*f*.
products, calcination, processes during: II, effect of small quantities of AlF_3 on formation of phases during calcination of Grossalmerode clay, (5) 199*b*.
science, Vol. 4, (10) 366*b*.
science, progress in, Vol. IV, B (7) 272*g*.
shapes, P (5) 180*c*.
shapes, casting, P (2) 61*a*.
special, Vol. 4, B (10) 366*g*.
toughness, and their work of fracture, (2) 85*b*.
used in medical world, (5) 190*f*.
Ceria. See *Cerium, oxide*.
Cerium, carbide molecules, mass-spectrometric evidence for, and predicted stability of diatomic carbides of electropositive transition metals, (11) 385*j*.
cerite, synthesis, (1) 39*a*.
Ce (III) fluoride, vapor pressure and heat of sublimation, (4) 163*f*.
CeO_2: Yb^{3+} and Er^{3+}, ESR of rare-earth ions in, (2) 76*f*.
oxide, magnetic susceptibility of Pr^{4+} in, (5) 196*d*.
platinum contamination and reduction, (1) 34*h*.
sintering, (1) 36*d*.
separation of berkelium from, P (1) 24*a*.
Cermets, alumina-silicon, reaction-formed, structure, (4) 156*c*.
of Al with TiC and Ti and Zr borides, P (11) 374*g*.
based on oxides and metals, review, (2) 55*a*.
bushings and rings, automatic press tool for calibrating, (2) 68*i*.
electrically conductive compositions, P (2) 58*c*.
high energy-rate forming for densifying, (4) 117*h*.
material, P (5) 178*d*.
for nuclear fuel, P (2) 59*f*.
packing material UMB-4S, stand tests, (6) 216*i*.
as protection against abrasive wear, (1) 1*g*.
resistance module, P (7) 256*a*.
resistors, composition and manufacture, P (4) 112*h*.
sintered-glass, mechanical properties, (1) 4*g*.
tape head, ceramic gapped, production, P (5) 185*c*.
WC-Co, X-ray stress analysis: I, procedures; II, temperature stresses, (7) 270*g*.
unstable combination U_3O_8-Al: I, technology; II, reaction behavior and properties, (6) 217*c*.
UO_2-metal, with oriented structure, preparation and thermal conductivity, (10) 341*h*.
UO_2-Mo, isothermal elastic modulus, (1) 12*j*.
UO_2-Mo and UO_2-W, fuel, preparation by metal vapor deposition in fluidized bed and hot-pressing, (1) 12*g*.
UO_2-niobium, high loaded, P (4) 107*b*; P (6) 217*a*.
UO_2-W, cosintering, phenomenological aspects, (5) 177*i*.
Cesium, in biotite, sanidine, and glass in Tuscany ignimbrites, Italy, (9) 329*d*.
borohydride, (7) 264*b*.
bromide and iodide, crystals, calorimeter for measuring heat capacities between 1.5° and 300°K of, (4) 160*g*.
$CsCuCl_3$, bonding in, thermal and magnetic study, (10) 362*f*.

Cesium *(continued)*
chloride, bromide, and iodide, lattice dynamics and specific-heat data, (5) 196*i*.
models, hard-sphere, slip in, (1) 37*c*.
and solid solutions, with RbCl, KCl, and CaBr, *Fm*3*m*-*Fm*3*m* transformations and Born-Mayer model, (4) 150*b*.
halides, energy of formation of Schottky defects in, (1) 29*f*.
iodide, ionic transport in, effects of alkaline earth impurities, (4) 133*c*.
layers, on refractory metals, field-electron-microscopy studies: work function change, (4) 136*g*.
nitrate, single crystals, EPR studies of VO^{2+} in, (8) 291*g*.
and nitrous oxide, recovery from fission product solutions containing NH_4NO_3, P (4) 125*g*.
superoxides, heats of formation and lattice energies, (1) 39*f*.
systems. See *Systems*.
Chalcogenides, alkaline earth, crystal properties, (4) 130*f*.
di-, transition metal, new, formed at high pressure, (4) 146*a*.
and oxides, structural investigation at normal and very high pressures, (9) 330*a*.
quaternary, with sphaleritic structure, (6) 236*g*.
quaternary, with spinel structure, (6) 236*g*.
systems, chemical composition and glass formation in, (4) 94*i*.
ternary: XVIII, of thallium with Ga and In, (6) 238*j*.
transition-metal, with layer structures with occupied trigonal-bipyramidal sites, band model for, (5) 192*f*.
transition-metal, phase transitions in, (4) 149*a*.
Chamotte. See *Refractories*.
Checker-brick. See *Refractories*.
Chelates, of rare compounds and promethium, separation by fractional sublimation, P (6) 240*b*.
Chemical analysis. See *Analysis*.
Chemical engineering. See *Engineering*.
Chemical properties, of aluminosilica gels, (1) 39*b*.
of Fe(III) oxide hydrate, (9) 318*b*.
Chemical reactions, dehydrogenation process using Co or Ni ferrite, P (6) 229*f*.
Chemisorption, on alkaline earth oxides: I, surface centers and fast irreversible oxygen adsorption on irradiated MgO, CaO, and SrO, (4) 128*d*; II, intrinsic bulk defects and adsorption of oxygen on MgO, CaO, and SrO, (8) 289*g*.
of hydrogen on nickel films, surface potential study, (9) 330*i*.
hydrogen and oxygen, effects on ferromagnetic anisotropy of Ni-on-SiO_2 particles, (5) 194*c*.
of methylene blue by kaolinite, (7) 253*d*.
of oxygen, on alkaline earth oxides, (1) 25*i*.
Chemistry. See also *Analysis; Electrochemistry; Geochemistry; Thermodynamics*.
of carbon, B (6) 240*g*.
of crystalline aluminosilicates: IV, factors affecting formation of zeolites X and B, (5) 192*g*.
high temperature, advances: Vol. I, B (4) 165*a*.
of minerals containing rarer elements from Far East district: LXI, yttrofluorite from Japan, (8) 289*f*.
of molten solutions: III, preparation of crystalline tungstates $M^{2+}WO_4$, (6) 231*a*.
oxide, of molten LiF-BeF_2 solutions, (11) 386*b*.
photo-, of $H_2B_2O_4$, (11) 385*j*.
physical, of transport processes, (10) 358*h*.
of radical ion formation on aluminosilicates, (5) 192*h*.
of silicates and oxides, collection of USSR papers, B (4) 168*h*.
of soil minerals, (1) 26*a*.
of soil minerals: IV, synthetic alkylammonium montmorillonites and hectorites, (4) 128*e*; V, low temperature hydrothermal transformations of kaolinite, (8) 289*i*.
solid state, principles, B (11) 390*f*.
study of silicates, (5) 192*d*.
surface, of calcination of gelatinous and crystalline aluminum hydroxides, (9) 330*f*.
infrared spectroscopy in, B (9) 334*i*.
of plastics reinforced by strong fibers, (10) 338*a*.
of solids, (6) 238*d*.
Chinaware. See *Art and artware; Dinnerware; Porcelain*.
Chlorides, of alkali metals and ammonia, compounds formed with tetrachlorides and oxychlorides of tetravalent Nb, properties, (7) 268*g*.
boratozirconium, P (5) 190*g*.
free energy of formation, (9) 321*i*.
ions, specific adsorption at mercury aqueous solution interface, (9) 329*d*.
solutions, effect on portland cement, (2) 44*g*.
Chlorination, of metals with CCl_4 and CO_2, P (11) 382*c*.
of rhodium and thermal transformations of trichloride, (8) 289*j*.
of titaniferous ores, P (4) 125*i*.
Chlorine, diffusion, into *p*-type PbTe at 700°C, (10) 352*g*.
effect on oxidation of graphite by CO_2, (8) 291*d*.
gas, exchange reaction with KCl crystal, (4) 136*a*.
Chlorine *(continued)*
inhibiting effect on graphite oxidation, (9) 323*b*.
oxysalts, thermal stability in solid state: I, kinetic study of disproportionation and explosion of chlorites; II, kinetic and derivatographic study of thermal decomposition of metal chlorates, (5) 201*j*.
systems. See *Systems*.
Chlorite, ortho-, structural decomposition, during acid dissolution, (1) 38*c*.
structures, synthesized, thermal analysis, (4) 160*h*.
Chloritoid, thermal stability, at high pressure and relatively high oxygen fugacity, (4) 161*b*.
Chromates, P (2) 74*c*.
Caromaticity. See *Color*.
Chromatographs, gas, for analysis of gaseous inclusions in glass, (5) 172*f*.
thin layer, of rare earths, (5) 188*a*.
Chromatography, gas, investigations on dimethyldioctadecyl ammonium derivatives of different clay minerals, (9) 321*j*.
separation of Na, K, Ca, and Mg ions applied to identification of soluble salts in clays and clay products and of efflorescent salts, (9) 315*a*.
separation of Sr from barites for mass spectrometric analysis, (9) 315*a*.
Chrome. See *Chromium; Refractories*.
Chrome-magnesite brick. See *Refractories*.
Chromia. See *Chromium, oxide*.
Chromite. See *Refractories*.
Chromium, boride-type phases, ternary, with Y, La, and rare earths, (11) 388*c*.
carbide, cemented, containing additions of phosphorus, P (8) 279*a*.
evaporation and thermodynamic properties, (1) 38*c*.
heats of formation, (5) 194*i*.
chromic oxide, antiferromagnetic, Davydov splitting of ^2E lines in, (4) 130*g*.
in elastomeric composition for use as rocket insulation, P (5) 178*f*.
Néel temperature, pressure dependence, (9) 328*d*.
reaction with barium carbonate, (8) 297*d*.
reaction with ZrO_2 in argon plasma, (6) 237*e*.
thermodynamic properties at high temperatures, (8) 300*h*.
vaporization, effect on sintering of MgO, (4) 132*a*.
Cr^{3+} ions, in MgO, acoustic paramagnetic resonance spectrum, (1) 24*h*.
Cr^{3+}, alignment in ruby, (1) 25*e*.
cathodoluminescence spectra and coordination in β-$LiAlSiO_4$, (10) 350*c*.
impurity ions, in ferroelectric $LiNbO_3$ and $LiTaO_3$ optical spectra, (11) 386*a*.
ion diffusion, in MgO, optical investigation, (4) 147*i*.
ions, in spinels, optical spectrum, (6) 235*b*.
optical reflectance spectra, in MgO solid solutions, (11) 370*b*.
paramagnetic resonance in $EuAlO_3$, (11) 386*b*.
CrB_4, crystal structure, (10) 351*i*.
CrO_4^{3-}, in chlorospodiosite, Ca_5PO_4Cl, ESR and optical spectroscopy, (4) 135*j*.
chromous oxide, effect on structural changes in tricalcium silicate, (6) 231*j*.
dioxide, ferromagnetic, P (5) 184*i*.
ferromagnetic, preparation by heating CrO_3 in presence of O_2 and Cr_2O_3, P (9) 317*b*.
and Ni, magnetic equation of state near Curie point, (4) 143*g*.
preparation and product, P (9) 317*c*.
sintered, electrical resistivity and electron-microscopic observation, (1) 28*d*.
MCr_3O_8, preparation, where M is alkali metal, from CrO_3, Cr_2O_3, and $M_2Cr_2O_7$, P (9) 317*c*.
oxidation kinetics, effect of oxide volatilization (1) 28*b*.
oxide, calcined gel, surface properties, (4) 158*d*.
effects in Na_2O-CaO-SiO_2 glass and on color and spectral transmission, (11) 369*j*.
glow phenomenon, (4) 137*j*.
high-purity, production by zone melting, (7) 262*a*.
particles, shape in $H_2+O_2+N_2$ premixed and diffusion flames, (6) 237*d*.
oxide/alumina, prepared with induction plasma torch, (9) 325*d*.
oxide/titania, prepared with induction plasma torch, (9) 325*f*.
phosphate, solid solubility in $AlPO_4$, (1) 37*e*.
-resinous dispersions, hexavalent, for coating cementitious articles, P (5) 170*f*.
-SiO thin layers, electrical parameters, stability, (9) 311*a*.
sites in simple glasses, effect of compression and compositional changes on the nature of, (2) 48*j*.
solubility in wustite at 1000°C: changes in oxygen activity and lattice parameter, (4) 128*g*.
systems. See *Systems*.
trichloride, enthalpy of formation, (4) 135*a*.
trifluoride, sublimation pressures, mass spectrometric studies at high temperatures, (7) 267*a*.
and V, in ZrO_2, crystal field studies, (4) 130*c*.
X-ray *K* emission spectra, in various Cr compounds, (10) 363*f*.
Chrysotile, modified colloidal, P (11) 382*f*.
Circuits, arrangement, for temperature measurement, P (1) 22*a*.
boards, printed, etching method of manufacturing, P (9) 312*h*.
complementary MOS transistor integrated, with inversion layer formed by ionic discharge bombardment, P (11) 376*j*.
component, semiconductor controlled switch, P (9) 313*i*.
components, peculiarities in diamond grinding of ceramics for, (4) 110*i*.
crystal-controlled, temperature compensation, P (10) 346*e*.
device, P (6) 223*j*.
devices, thin film, P (1) 19*c*.
electrical, P (11) 376*c*.
element, woven fiber, P (9) 313*b*.
ferroelectric control, P (10) 344*h*.
flip-chip integrated, forming, P (8) 282*i*.
insulation isolated semiconductor integrated, contacts for, P (7) 256*c*.
integrated, P (6) 222*c*; P (10) 345*g*; P (11) 377*a*.
containing multilayer Ta compounds, P (2) 65*e*.
electron beam techniques in, (10) 344*g*.
fabricating by controlled process, P (7) 257*b*.
isolated technique for obtaining, P (5) 185*e*.
isolation techniques for making: I, laminate substrates; II, dielectric refill techniques and decal air isolation, (8) 281*j*.
large scale, P (5) 183*g*.
monolithic, electrical isolation of circuit components of, P (2) 64*a*.
monolithic, with plurality of isolation zones, P (6) 222*j*.
monolithic bar, isolating individual devices in, P (8) 282*j*.
thin film, P (5) 184*f*.
using heavily doped surface region to prevent channels, P (10) 345*c*.
integrated complementary transistor, P (10) 345*c*.
integrated crystal, P (4) 113*f*.
integrated structure, including unipolar and bipolar transistor portions, P (2) 65*b*.
micro-, with complementary dielectrically isolated mesatype active elements, P (5) 184*h*.
devices, alignment on substrate, P (11) 377*g*.
monolithic semiconductor, with improved means for connecting points of common potential, P (5) 184*a*.
microelectronic, production of cooling module by cathodic sputtering for, P (7) 257*i*
microelectronics, connection arrangement for three-element component to, P (4) 112*b*.
monolithic ceramic electrical interconnecting structure, P (5) 184*j*.
printed, vibratory process for joining transistor chip to, P (2) 67*a*.
selective sputtering rate, forming process, P (7) 258*a*.
semiconductor integrated, P (4) 113*a*; P (5) 185*i*; P (7) 258*d*.
fabrication of structures for, P (5) 182*j*.
with improved isolation, P (11) 378*e*.
with improved isolation between active and passive elements, P (4) 116*e*.
Si controlled rectifier gating, with high frequency triggering voltage and photocells, P (11) 378*j*.
thermocouple reference junction compensating, P (11) 381*e*.
thick film, mounting semiconductor devices on, P (11) 377*f*.
thin film, with resistor-conductor pattern, P (5) 183*i*.
Circulators, ferrite junction, with biasing connector wire at ferrite center, P (10) 344*h*.
Classification. See also *Separation; Separators*.
of granular materials, P (8) 287*f*.
microplex pneumatic, for improving refractory clay quality, (10) 348*j*.
of pigmentary metal oxide, P (2) 74*b*.
pneumatically, pulverulent material, process and apparatus, P (8) 288*d*.
and rotary processing, method and apparatus, P (6) 229*h*.
substructure, of silicate glasses, (6) 211*d*.
Classifiers. See also *Beneficiation*.
air, and screening apparatus for finely divided materials, P (6) 225*d*.
air, vane control for, P (7) 263*d*.
and conveyor, P (7) 259*e*.
particle, P (7) 261*b*.
for particulate material, P (8) 284*d*.
Clays. See also *Fireclay; Kaolin*.
absorbent granules, from Kansas under clays, (9) 316*e*.
active, content, in molding sand compositions, determination by electrical conductivity test method, P (4) 121*f*.
beneficiating, by flotation of colored impurities, P (11) 382*c*.
bleaching earths, B (9) 333*i*.
for brickmaking and application in ceramic industry, B (1) 41*e*.
brightness, improving, P (7) 263*d*.
catalyst, for polymerization of unsaturated fatty acids, P (4) 124*i*.
ceramic, drying methods, (7) 258*i*.
of chain-like structure, mineralogical studies, (10) 357*g*.
and clay products, indentification of soluble salts in, by chromatographic separation, (9) 315*a*.

Clays *(continued)*
characteristics, related to dry strength, (5) 179*h*.
chemically treated, P (4) 124*i*.
china. See *Kaolin*.
concentrate, preparation from kaolin, (7) 262*i*.
content, relations with grain size, quartz, and organic carbon in Lake Erie and Lake Ontario sediments, (11) 382*f*.
conversion to crystalline aluminosilicates, and catalysts from, P (6) 229*c*.
deposits of Eocene Age in Jackson Purchase region, Kentucky, and adjacent parts in Tennessee, stratigraphic and mineralogic relations and ceramic properties, (9) 316*i*.
deposits, Westerwald, in Meisbach and Breitscheid, investigation, (1) 31*h*.
dispersion method, P (4) 124*h*.
drying, cyclic jet, with special consideration of Rotomixair system, (7) 258*h*.
electrical potential measurements in, (9) 321*d*.
expansive, identification from plasticity index and shrinkage index data, (4) 120*b*.
fractionated regularly interstratified X-ray data on, (8) 300*j*.
Grossalmerode, calcination, effect of AlF_3 on formation of phases during, (5) 199*b*.
heavy, specific surface, measuring methods and significance, (11) 380*i*.
humus-containing, bending strength, increasing by adding calcium hydroxide, (11) 382*e*.
Indian, chemical decolorization, (2) 73*a*.
Indian, investigations to find replacement for Rajmahal china clay, (4) 123*f*.
Israeli, DTA curves, (4) 132*d*.
Kansas, testing for nonceramic utilization, (2) 71*c*.
kaolin, bleaching, potentiometric control, P (1) 24*b*.
kaolin, chemically treated, P (8) 287*f*.
kaolinite, anisotropically consolidated, strength and deformation characteristics, (5) 190*a*.
kaolinite, beneficiation from silica sand washings, (9) 316*f*.
layer, in situ, measurements of volume change zone in, (5) 190*f*.
Lower Kittanning, semidry compaction, effects of varying water contents and pressures, (5) 176*g*.
macroporosity, importance of measuring during sintering of, (6) 233*f*.
materials, Illinois, new use in pesticide formulation, (9) 316*i*.
mineralogy, B (10) 364*i*.
minerals. See also specific types.
and adsorbed substances, infrared spectra, (7) 259*g*.
allophane-kaolinite, reaction with calcium hydroxide, (8) 278*i*.
aqueous solubility studies, (8) 288*j*.
aqueous suspensions, effect of duration of magnetic field action on formation of coagulation structures in, (4) 132*c*.
cation-substituted types, preparation, (7) 262*h*.
colloidal and surface properties, (4) 128*h*.
composition, complex study, (11) 379*j*.
dehydration processes, energy changes in, (7) 265*c*.
dehydration under N_2 reduced pressure by differential thermal analysis, (7) 264*j*.
development of electric potentials in, (10) 352*a*.
dimethyldioctadecyl ammonium derivatives, gas-chromatographic investigations, (9) 321*j*.
geochemistry of boron and gallium in, (1) 30*h*.
interstratified, electrochemical behavior, (11) 384*h*.
mutual adsorption with colloidal hydrous Al_2O_3, electron microscopy investigation, (1) 33*e*.
phosphate combination with and release from, through anion exchange treatment with ^{32}P, (4) 149*a*.
separation by continuous particle electrophoresis, (11) 380*g*.
standards, extracted from samples to be analyzed, use in quantitative X-ray diffraction analysis, (7) 260*a*.
studies of sediments and sedimentary rocks, quantification in, (8) 285*a*.
study by small-angle X-ray scattering, (8) 298*h*.
thermoluminescence, (4) 162*h*.
montmorillonite, interaction with anionic detergent, (4) 123*f*.
nonfissile Pleistocene, fabric, (10) 353*a*.
Norman, from Pays de Bray, (4) 123*h*.
operations, locations in Indiana, (4) 123*g*.
organic complexes, cation-dipole interactions in, (7) 264*c*.
organo-, sorption and intracrystalline porosity in, (1) 37*f*.
palygorskite, acidity nature, (5) 191*i*.
partially saturated, creep studies, (1) 23*j*.
particles, heat-treating, method and apparatus, P (7) 250*c*.
pellets, expanded, production using fluid bed process, (10) 348*h*.
porous, method and apparatus, P (2) 54*e*.
preparation plant, in fine-ceramics plant, (1) 15*e*.
powders, introducing into drilling muds in absence or presence of electrolyte coagulators, (7) 258*h*.
products, in changing world, review, (1) 40*e*.
pyroplastic properties, and role in formation of structure of ceramic materials, (11) 372*e*.
rational analysis, (4) 121*b*.
refractory, Anina, technological study, (4) 124*a*.
for chamotte quality improvement, (1) 13*f*.
improving quality by microplex pneumatic classification, (10) 348*j*.
machinery for mining in Westerwald, Germany, (10) 348*j*.
removing Ti mineral impurities from, P (9) 317*f*.
and sand, recovery from ore, P (5) 191*c*.
saturated, shear strength parameters for, (4) 153*d*.
sensitive, time-dependent consolidation, (8) 285*i*.
siliceous Kansas, thermal expansion, (4) 160*f*.
slurries, dried, strength of adhesion to window glass as function of slurry pH, (11) 370*d*.
soils, mechanical properties, effect of ion sheath, (5) 190*c*.
soluble salt content variations in, (5) 179*j*.
stress strain relations for, (1) 38*b*.
suspensions, aqueous, thermophysical properties, (6) 239*j*.
dilute, electrokinetic stability, effect of polymer adsorption, (1) 28*b*.
diluted, optical properties, (1) 13*i*.
forced-flow electrophoretic filtration, (1) 29*j*.
structural formation, effect of $Ca(OH)_2$, (7) 253*e*.
thixotropic and sedimentation volumes, cause and influence, (11) 385*f*.
swelling, deflocculation by nonionic and anionic detergents, (5) 189*i*.
system. See *Systems*.
treating, P (8) 288*b*.
treatment, P (7) 262*f*.
under-, Pennsylvania, in Illinois, petrography and application to mineral industries, (2) 73*i*.
under-, Pennsylvania, in Western Pennsylvania, origin, (6) 229*f*.
volumes, thixotropic and sedimentary, (4) 124*b*.
-water relations in stiff clays, (5) 192*i*.
-water system, dependence of plasticity on dispersed phase concentration, (7) 253*i*.
Cleaning, abrasive compositions, P (11) 367*f*.
composition, alkaline, effect on removal of drawing and stamping compounds from steel, (8) 274*j*.
compositions, and use, P (4) 164*j*.
degreasing technique "explodes" dirt, (5) 186*a*.
descaling, ferrous metal billets, method and apparatus, P (4) 94*c*.
electrodes in electrostatic dust separator, device for, P (6) 225*a*.
foundry cores, method and apparatus, P (10) 342*i*.
heat, effects on photoemission properties of GaAs surfaces, (10) 343*j*.
ultrasonic, (2) 67*d*; (4) 118*f*.
Cleavage, of barite, (1) 26*c*.
Clinker. See *Cement; Magnesite; Dolomite; Forsterite*.
Coagulation. See *Agglomeration*.
Coal. See *Fuels*.
Coatings. See also *Enamels; Glazes; Resins*.
alkali-metal silicate protective, P (4) 93*j*; P (10) 337*d*.
alkyd resin-aminoplast resin composition, for glass, P (5) 174*f*.
antireflection, and assembly with synthesized layer of index of refraction, P (6) 212*b*.
application. See *Electrostatic processes; Spraying*.
B and B_4C, formation by vapor deposition, (1) 4*b*.
boron containing, codeposition of, P (11) 369*c*.
ceramic, to analyze overall stress, (6) 225*h*.
ceramic, for ferrous metal, development and application methods, P (1) 5*e*.
ceramic-carbon material, with glass, and article, P (11) 377*g*.
chemical conversion, with enamels retard corrosion of Be, (5) 171*c*.
cladding-UO_2 gap under irradiation, (2) 54*h*.
cobalt oxide, formation on glass, physicochemical bases, (2) 50*a*.
composite infrared reflective, for heaters, P (8) 275*b*.
composition, of Al and metal fluorides, for niobium, P (4) 98*g*.
and application, P (7) 246*e*.
high temperature temporary protective ceramic for metals, and resulting coated metal articles, P (11) 369*c*.
low temperature cured ceramic, P (4) 114*a*.
containing graphite, for thermoelectric generator, P (1) 18*f*.
crystalline semiconductor, forming on alumina substrate, P (4) 114*e*.
by detonation gun process, (5) 171*c*.
electrically conductive solderable metallic, on nonmetallic bases, P (5) 182*h*.
electrically resistant, composition and process for producing on ferrous surfaces, P (5) 171*j*.
electro-, electrodeposition of organic coatings from aqueous media onto conductive substrates, (1) 4*h*.
electrostatic. See *Electrostatic processes*.
emissive, for refractory surfaces, P (2) 58*d*.
epitactic vapor, apparatus, P (11) 376*e*.
epitaxial semiconductor, as diffusion mask, P (2) 64*e*.
epitaxially, on substrate, apparatus for, P (11) 376*g*.
films. See *Films*.
fluid glaze, for brick, apparatus for applying, P (5) 176*f*.
on germanium bodies, P (1) 18*e*; P (7) 256*a*; P (8) 282*h*.
glass, articles, method and apparatus for repairing, P (7) 246*f*.
dual protective, and forming, P (5) 174*g*.
dual protective label accepting, and method, P (5) 174*j*.
for electrical devices, P (7) 248*b*.
with epoxy compositions, P (4) 100*h*.
forming on semiconductor, P (4) 114*f*.
ionically conductive, for filimentary thermal cell, P (4) 94*a*.
inorganic, P (11) 369*a*.
glass-ceramic, expand into commercial field, (2) 45*i*.
glass-ceramic, innovations, (1) 4*e*.
glass fibers, and fibers formed, P (11) 371*f*.
heater coils, P (9) 304*h*.
heat-resistant, P (10) 337*e*.
heat-resistant silicone resin, P (10) 337*e*.
hexavalent chromium-resinous dispersions, for cementitious articles, P (5) 170*f*.
high-temperature oxidation resistant, on refractory metal base article, P (6) 208*b*.
highly refractory anticorrosion, (2) 45*j*.
inorganic, engineering properties, (8) 274*j*.
low temperature temporary protective ceramic, compositions, for metals, and resulting articles, P (10) 337*a*.
metal boride, forming on wire, P (6) 208*a*.
metal oxide, on glass, study by infrared spectroscope, (1) 9*d*.
metal silicate, using electrostatic field, P (7) 256*i*.
metallic wire or strip with glass, P (9) 304*i*.
metalization, of selected regions of surfaces and products formed, P (4) 114*d*.
metalization, of Si semiconductor devices for making ohmic connections to, P (10) 345*e*.
metalizing, and bonding nonmetallic bodies, P (4) 114*e*.
ceramics, alloy for, P (2) 64*c*.
compositions containing critical proportions of metal (Pt-Au or Pd-Au) and specific high density frit, P (7) 256*j*.
compositions, noble metal, P (9) 313*j*.
of CuS with Al_2O_3, effect of kaolin addition, (2) 62*b*.
flame spray, P (11) 379*f*.
processes for electroceramics, (7) 255*f*.
vacuum, of glass, plastic, and metal, (7) 259*c*.
metals, with silicide layer and outer layer of Al silicate, P (8) 275*e*.
for nickel base engine alloys, P (9) 304*h*.
oxidation inhibiting, on industrial carbon body, P (11) 374*f*.
oxidation protective, application to niobium, P (6) 208*c*.
oxidation-resistant, forming on substrate, P (5) 172*b*.
oxidation-resistant, for refractory metal articles, P (8) 275*i*.
oxide, reliable, proper methods and materials, (6) 207*j*.
oxide, for semiconductor surfaces, P (11) 378*b*.
photoconductive, separated from reactive opaque pattern by transparent conductive layer, P (4) 115*e*.
plasma, characteristics, effect of fine grain, narrow band powders on, (1) 4*h*.
plating, electrolytic, of metal bump contacts to semiconductor devices on nonconductive substrates, P (2) 64*d*.
and polishing silicon planar surface, P (7) 257*a*.
vapor, apparatus, including rotatable substrate support, P (2) 67*a*.
protective, on F_{48} and SU_{18} niobium alloys, development and testing, (4) 103*e*.
for insulative surfaces, P (8) 275*a*.
for pickle tanks, (8) 275*d*.
pyrolytic, deposition, P (11) 379*e*.
refractory compositions, P (6) 218*c*.
refractory metal, P (4) 94*e*.
with metal modified oxides, P (4) 93*h*.
vacuum pack and vacuum slip-pack processes for, (7) 246*a*.
refractory ware with magnesia, P (9) 309*g*.
semiconductor, with mask and diffusing impurity in, P (9) 313*d*.
semiconductor, precipitated from gas phase, influencing surface profile of, P (4) 115*a*.
silica fiber, P (6) 213*c*.
silica, porous, to TiO_2 pigment, P (4) 125*f*.
silicide, for Ta-base alloys, (1) 5*g*.
silicide, Ti-modified, forming on NB-base substrates, and resulting articles, P (8) 275*f*.
of Si, SiC, or TiN, for metal surfaced with boron, P (7) 246*f*.
with SiC by immersion reaction, P (10) 342*c*.
SiN, on semiconductor, P (5) 185*j*.
solid particles with refractory metals, P (8) 279*b*.
for spacecraft, to control temperature and/or reflectivity, P (6) 208*b*.
spray, P (7) 246*h*.
spray, gas seals of gas turbines, P (7) 246*h*.
for steel, ferrous metal, and ferrous alloy substrates, P (4) 94*d*.

Coatings *(continued)*
sulfidation corrosion-resistant, containing rare-earth metal aluminides, P (9) 304*j*.
surfaces of light transparent materials associated with light sources, P (6) 212*i*.
surfaces of light transparent materials, such as cathode ray tubes, P (4) 98*j*.
temperature-stable protective, proceedings, 1966, B (5) 204*d*.
with tetraboron silicide, P (10) 344*d*.
thin films. See *Films, thin*.
thin uniform thickness stripe on substrate, apparatus for, P (11) 376*f*.
with Ti and related metals, and article produced, P (8) 280*f*.
TiC, on iron, chemical vapor deposition, (4) 93*c*.
TiO_2 pigment with hydrous metal oxides, P (4) 126*a*.
vanadium suboxide, P (10) 345*h*.
vapor, employing degassing of coating metal, P (2) 67*a*.
of glass containers, method and means, P (7) 249*h*.
high temperature, silicized carbon susceptor for, P (1) 19*e*.
vitreous crystalline, crystallization, influence of application process on, (2) 45*h*.
wire, with boron nitride and boron, P (9) 304*j*.
Cobalt, in Al_2O_3, determination of trace amounts by atomic-absorption spectroscopy, (6) 226*a*.
atomic fluorescence study on, (8) 284*j*.
chloride, interaction with indium chloride, (4) 140*d*.
Co^{2+}, light absorption, in 2,6-spinels, (7) 267*j*.
and Ni^{2+}, in MgO, near-infrared fluorescence and absorption spectra, (2) 80*h*.
octahedral-tetrahedral transitions, in sulfate-chloride glasses, (5) 173*h*.
in α-$Zn_3(VO_4)_2$, crystal field studies, (1) 26*d*.
Co(II), hydroxide, thermal decomposition, (1) 39*a*.
cobaltous oxide, single crystalline, electrical conductivity and thermogravimetric studies, (10) 352*f*.
determination, in cement, (4) 91*e*.
determination, direct fluorometric, (8) 284*j*.
effect in ground coat and direct-on white enamels, (10) 336*g*.
fluoride, piezomagnetism, from EPR pressure experiments, (4) 149*j*.
iodide, thermal transformations, (7) 270*h*.
ions, isothermal diffusion, in pure NaCl crystals and reconsiderations of Soret effect, (10) 356*e*.
molybdate catalysts, two stage heat treatment, P (4) 126*a*.
monoxide, scales, lattice deformation, effect of stoichiometry, (9) 320*b*.
and Ni-Co alloys, substructures in oxide scales on, (4) 157*h*.
in nickel ferrites, determination by atomic absorption analysis, (6) 225*g*.
or Ni ferrite, used in dehydrogenation process, P (6) 229*f*.
orthosilicate, synthesis and study of properties, (4) 158*e*.
oxalate, decomposition, effect of prior dehydration conditions upon, (1) 39*b*.
oxidation mechanism, between 750° and 1000°C using inert gold spheroidal markers, (10) 357*d*.
oxide, complex defects in, (11) 383*h*.
conductivity measurements on, in highly enriched oxygen atmospheres, (10) 351*c*.
effect of hydrostatic pressure on Néel temperature in, (1) 27*j*.
novel, and electrode with coating of, P (1) 18*h*.
O diffusion in, as measured by proton activation of ^{18}O, (8) 295*h*.
single crystals, transmission electron microscopy and etch pitting of, (4) 121*j*.
silicide, single crystals, growth and characterization, (9) 322*b*.
sulfide pyrite, single crystals, preparation by chlorine transport, (6) 236*c*.
systems. See *Systems*.
Coke. See also *Fuels*.
furfuryl alcohol, graphitization by titanium and vanadium, catalysis of, (1) 11*j*.
and low CTE graphite, manufacture from petroleum derived feed materials, P (11) 375*c*.
Coke ovens. See *Refractories*.
Colloids, aquasols, plutonia, P (11) 382*h*.
aquasols, uranium trioxide, process, P (10) 349*f*.
colloidal inclusions, trapping in growth of quartz crystals, (10) 363*b*.
electrolyte micelles, adsorption by inhomogeneous porous materials, (7) 263*h*.
gels, aged sesquioxide, phase changes in, and analogies with katamorphic process, (9) 326*h*.
alumina, hydrated and transition, structure and properties, (4) 156*a*.
alumina, hydration and crystallization in aqueous solutions of various basic reagents, (4) 138*j*.
aluminosilica, sorption properties, (1) 37*h*.
aluminosilica, synthesis and chemical properties, (1) 39*b*.
Al hydroxide, characterization by N_2 adsorption, (8) 289*d*.
Al hydroxide, structure, (2) 83*i*.
Colloids, gels *(continued)*
aqueous montmorillonite, NMR doublet splitting in, (11) 386*i*.
calcined chromium oxide, surface properties, (4) 158*d*.
gelling, delayed, of sodium silicate, and use for, P (7) 262*g*.
growth of crystals in by complex dilution method, factors influencing, (9) 329*a*.
for homogeneous glass preparation, (8) 276*a*.
inorganic, with predetermined pore structure, preparation, P (4) 125*i*.
nucleation and growth of crystals in, (4) 147*b*.
preparation of starting materials in MgO-SiO_2-Fe-O system, (10) 354*g*.
silica, adsorbed water, DTA at room temperature to -90°C, (4) 95*i*.
silica, interaction with iodine, nature of products from, (4) 145*j*.
silica, modification of porous structure on purification and associated change in dielectric behavior of adsorbed benzene, (4) 144*j*.
silica, pore sructure analysis, (1) 31*j*.
synthetic aluminosilicate, hydrothermal aging, (7) 266*j*.
thorium oxide, thermal treatment at low temperatures, (8) 287*c*.
tobermorite, reactions with aluminates, ferrites, and sulfates, (4) 152*i*.
sol-gel oxide microspheres, preparation, coating, evaluation, and irradiation testing, (4) 150*g*.
sol-gel processes, application to industrial oxides, (2) 54*i*.
sols, aluminum hydroxide-iron hydroxide, aluminum hydroxide-silicic acid, and iron hydroxide-silicic acid, mutual precipitation effects of, (6) 235*e*.
hydro-, of arsenic trisulfide, stability in light of Derjaguin-Landau-Verwey-Overbeek theory, (4) 155*j*.
silica, concentrated, P (11) 382*d*.
silica, containing large particle size SiO_2, P (7) 262*j*.
silica, continuous process for making, P (7) 262*g*.
silica, flocculating properties, effects of preparation conditions, (7) 262*c*.
silica, of minimum turbidity, preparation, P (7) 264*c*.
ThO_2-UO_2, P (2) 59*c*.
ZrO_2 and HfO_2, P (8) 288*c*.
solutions, of extremely finely divided oxides which are stable on storage, P (10) 349*b*.
Color. See also *Pigments; Stains*.
centers, in borate glass, (6) 208*h*.
in heavily irradiated MgO, optical absorption studies of, (8) 295*g*.
influence on plastic deformation of halide crystals, (2) 78*j*.
transient, in fused quartz, (9) 307*h*.
trigonal, in MgO, spin-orbit coupling and stress spectra of, (4) 155*h*.
Y^{3+}, in irradiated CaF_2, (11) 388*e*.
ceramic, and pottery decoration, B (10) 364*h*.
changes, in melts in glassmelting kilns, (8) 276*a*.
colorant, molten addition in glass furnace forehearth, P (8) 278*d*.
coloration origin in fluorites, (4) 147*g*.
of copper ruby glass, origin, (9) 306*a*.
decolorization, chemical, of Indian clays, (2) 73*a*.
determination, using color maps, P (2) 72*a*.
enamel, relation of particle size with firing temperature, (11) 368*h*.
inorganic vs organic, for glass decorting, (1) 7*c*.
of Italian enameled ceramic tiles, quantitative control of behavior, (9) 309*j*.
materials, ceramics, (10) 348*g*.
measurement. See *Colorimetry*.
porcelain, behavior in wash tests, (1) 15*b*.
resistance, to machine washing, (1) 15*g*.
and spectral transmission of Na_2O-CaO-SiO_2 glass, effects of Cu and Cr oxides on, (11) 369*j*.
transmitted, by dipole alignment in ferrite-type ceramic, (4) 111*e*.
Colorimetry, determination of Ca in silicate minerals, (7) 259*j*.
photo-, determination of calcium in minerals with aid of Arsenazo, (6) 226*j*.
Coloring materials. See *Decoration; Pigments; Stains*.
Columbium. See *Niobium*.
Combustion. See also *Burners; Firing; Flames; Furnaces; Heat; Kilns*.
fluidized-bed, of graphite-base nuclear reactor fuels, (8) 278*j*.
internal, cylinders and engines, combustion chamber design and material for, P (4) 93*i*.
process, in atomizing jet burner for superfine glass fiber manufacture, theoretical analysis, (7) 261*f*.
spontaneous, of coal, use of DTA in, (4) 122*f*.
Comminution. See *Crushing*.
Compaction. See also *Pressing*.
apparatus, for permanent magnet powders into pressings, P (4) 112*a*.
high density, of powders by Dynapak method, (4) 119*h*.
of magnetic powder, method and apparatus, P (1) 18*a*.
radiation, of vitreous silica, (9) 307*a*.
shredded carbonaceous fiber, P (2) 59*f*.
Compaction *(continued)*
of ultrafine active Al_2O_3 powder, effects of gaseous adsorbates, (7) 253*g*.
vibratory, for fabrication of ceramic nuclear fuel elements, P (4) 108*b*.
vibratory: III, rate of entry, (10) 346*h*.
Compacts, array, separating articles in, and composite assemblies formed, P (9) 313*f*.
$Ca(OH)_2$, length change characteristics on exposure to water vapor, (8) 286*j*.
glass powder, sintering, effect of water vapor, (4) 117*g*.
of MgO, ZnO, and NaCl, adsorption effect on strength of, (2) 82*h*.
Composites, Al_2O_3 whisker/Ni, electron microscope observations, (8) 279*f*.
article, high strength whisker, P (5) 178*i*.
assemblies, formed from separating articles initially in compact array, P (9) 313*f*.
BeO-SiC, thermal expansion, (7) 251*j*.
BN, and BN, static oxidation and compatibility to 2000°C, (8) 279*h*.
ceramic fiber reinforced metal, (1) 4*d*.
ceramic-plastic, for medical use, (1) 40*e*.
ceramic structural, P (11) 374*f*.
Cercom armor, (2) 59*j*.
crystalline zeolite catalyst, preparation, P (1) 24*a*; P (6) 230*b*.
engineering laminates, B (11) 388*f*.
fiber. See also *Glass, reinforced*.
-containing pyrolytic material, P (11) 374*i*.
-reinforced metal alloy, preparation by compaction in semimolten phase, P (7) 253*a*.
-reinforced, theoretical analysis of creep in, (11) 368*j*.
or whisker, oriented, P (6) 217*j*.
filament reinforced metal, for gas turbine blades, P (11) 374*i*.
glass-crystal, strength, (6) 211*i*.
glass, fiber-reinforced, dynamic moduli and damping ratios in, (2) 48*h*.
glass-filament-wound, nondestructive testing for void content, (10) 338*c*.
glass-filament-wound, quantitative measurement of void content in, and correlation of interlaminar shear strength with void content, (1) 8*a*.
glass filled polyphenylene oxide, fracture properties, (2) 49*g*.
glass-resin, microvoids in, (1) 7*j*.
glass-silicon, body, P (11) 371*h*.
heteroepitaxial structure, P (4) 112*i*.
high energy-rate forming for densifying, (4) 117*h*.
high surface area alumina and catalyst, P (4) 124*b*.
materials, B (4) 165*f*.
and articles produced by, P (11) 377*g*.
ceramic plastic, for radomes, P (7) 252*f*.
modern, B (7) 272*e*.
perfectly disordered, elastic moduli, (4) 133*j*.
self-lubricating fluoride-metal, P (4) 94*f*.
silicon, SiC whisker reinforced, P (11) 375*d*.
metal matrix, controlled solidification utilizing monovariant eutectic reactions, (7) 250*i*.
W-In powder bodies infiltrated with Cu, P (5) 185*h*.
workshop, proceedings, July 1967, B (4) 166*e*.
oxidation resistant metal diboride, synthesis, (1) 13*h*.
oxygen lance, refractory coated, P (6) 208*b*.
plasma-sprayed alumina-titania, (5) 171*i*.
powders, and apparatus for production, P (6) 208*a*.
production, to improve properties, (2) 60*i*.
properties, (2) 73*b*.
Radome structural, P (10) 340*a*.
refractory, P (2) 59*e*.
solid lubricant, P (5) 191*f*.
spinel ferrite epitaxial, P (5) 185*c*.
structural material incorporating metallic filaments in matrix, P (5) 178*e*.
structure, glass-resin, P (5) 174*j*.
thermal-shock-resistant, (8) 279*h*.
WC, wear resistant cobalt bonded, P (10) 343*c*.
Compressibility, modulus, correlation with density of cohesive materials, (5) 189*h*.
of sands and sandy gravels, (5) 189*j*.
Compression, effect on magnetic behavior of magnetite in thermal cycles across magnetocrystalline isotropic point, (7) 265*i*.
effect on phase transition in $BaTiO_3$, (4) 150*j*.
Computers, to calculate empirical formulas for desirable glass oxide content using linear programing, (2) 47*a*.
calculation applied to exchange equilibria between condensed and gas phases, (1) 26*i*.
high speed memory in, (4) 110*i*.
optical, comprising semiconductor *pn* junction components, P (6) 223*c*.
for powder diffraction identification system, (1) 21*a*.
in production control and sales forecasting for Wedgwood, (5) 179*i*.
techniques, for three-dimensional analysis in atomic-absorption flame photometry, (1) 21*a*.
Concentration, distribution, in binary powder mixtures of variable composition, calculation, (2) 67*d*.
Concentrators. See *Separators*.
Concretes. See also *Cement; Masonry; Mortars; Pozzolans*.
aero-, and hydraulic cement, use of Posidonia shales Lias Epsilon from Brunswick-Hondelage for manufacture of, (4) 92*d*.
air bubbles in, protected paste volume concept

Concretes *(continued)*
using new air-void measurement and distribution techniques, (5) 187*g*.
autoclave silicate, corrosion of reinforcement in, from lime-silica cement using hydrated lime, (2) 44*a*.
bars and cubes, change in strength as function of water content, (5) 192*i*.
cellular, of Kansas pozzolanic materials, (2) 43*j*.
or cement mortar, of improved strength, production, P (6) 207*a*.
chalk-aggregate, high strength, observations, (2) 44*j*.
compressive strength, relation with effective cement-water ratio calculated from hydration rate of cement, (7) 245*a*.
creep, at high temperatures, apparatus for measuring, (5) 170*d*.
creep under multiaxial compressive stress, measurement equipment, (1) 21*j*.
foamed, (7) 245*a*.
fresh, apparatus for analyzing, P (4) 121*d*.
gliezh-, structure, (8) 274*a*.
hardened samples, identification of ordinary portland cement and sulfate-resisting cement in, (6) 206*i*.
heat-resistant, properties of cordierite as filler for, (11) 368*a*.
high-strength, shrinkage, influence of cement composition on, (7) 244*i*.
keramsit porous, B (8) 302*g*.
lightweight, with lime-burned clay binder, (2) 44*h*.
and mortar, dimensionally stabilized, P (8) 274*b*.
physicochemical mechanics, scientific basis of vibration displacement of mixtures, (8) 274*e*.
porous silicate, production and uses, (2) 45*c*.
portland cement, admixtures in, (5) 170*c*.
fracture toughness, (10) 336*c*.
hydrogen evolution from ferrophosphorus aggregate in, (4) 91*h*.
reactions of aggregates in, (6) 206*g*.
prevention of alkali-aggregate reactions in, P (6) 207*d*.
production with fly ash and cement for strength and economy, (2) 45*d*.
quality control, and economics for paving projects, (4) 92*c*.
refractory, applications in France and England, (5) 176*h*.
refractory, erosion resistance, influence of particle size, (8) 279*b*.
resin, (4) 92*e*.
resistance, exposed to seawater, influence of hardened cement paste pore volume on, (1) 3*a*.
service behavior, for radiation shielding, (11) 368*d*.
silicate, research, B (4) 168*c*.
steam-curing, optimum period for, investigated by ultrasonic methods, (8) 274*d*.
strength, ring-tensile, comparison with compressive, flexural, and splitting-tensile strengths, (5) 187*b*.
stress distribution around holes in, (1) 3*c*.
tensile strength, effect of size and shape of test specimens on, (1) 21*g*.
tensile strength, splitting, effects of curing and drying environments on, (1) 2*j*.
in tension, microcracking and stress-strain curves for, (1) 3*f*.
unit weight, relation to heat flow factors, (1) 2*e*.

Condensers. See *Capacitors.*

Conductivity, electrical, and (or) **Conduction, electric,** ac, in amorphous films, (8) 280*e*.
of alkali chlorides, anion contributions to, (4) 126*e*.
of alkali-metal nitrates, fused activation volumes for, (8) 293*b*.
of Al_2O_3, liquid, (molten corundum and ruby), (4) 134*d*.
in $BaTiO_3$ reduced single crystals, (9) 320*i*.
of cobaltous oxide, single crystalline, (10) 352*f*.
for determination of active clay content in molding sand compositions, P (4) 121*f*.
and electrolysis of alkali ions in silica glass, (7) 247*g*.
elements, made from copper/vanadium oxide compositions, noble metal metalizing compositions containing vanadium oxide additives, P (7) 256*d*.
filamentary, in semiconducting glass diodes, (10) 337*g*.
of glass, effect of structural changes in transformation range on, (1) 6*c*.
in glasses containing transition metal oxides, evidence for small polaron as charge carrier, (2) 49*b*.
of glasses molten, and problems in electric glassmelting, (1) 6*g*.
of glasses, single-alkali, (2) 49*j*.
high frequency, of NiO, (2) 78*c*.
of rutile, (2) 78*e*.
of VO_2, (8) 292*j*.
in iron oxides at high temperatures, (8) 291*b*.
measurements on CoO and NiO in highly enriched oxygen atmospheres, (10) 351*c*.
mechanisms in oxides, B (7) 272*g*.
of metal-to-reduced $BaTiO_3$ single crystal contacts, (1) 16*b*.
metallic and superconductivity, in silver clathrate salts, (2) 80*b*.
method, for determining batch moisture content, (6) 226*d*.

Conductivity, electrical *(continued)*
mixed, in $Zr_{0.85}Ca_{0.15}O_{1.85}$ and $Th_{0.85}Y_{0.15}O_{1.925}$ solid electrolytes, (4) 144*i*.
of molten salts, (7) 262*f*; B (10) 365*f*.
in montmorillonites and silicas, (1) 39*e*.
of NiO at high temperature, (1) 28*j*.
noble metal composition, rendering nonwettable by solder, P (1) 18*d*.
in KCl-$MgCl_2$ system, (7) 265*b*.
of sapphire and ruby crystals, (10) 352*c*.
semi-, of CdS as function of S-vapor pressure during heat treatment between 500° and 700°C, (10) 360*g*.
semi-, properties of $LaCoO_3$, (10) 360*f*.
in semiconductors, (4) 109*f*.
of silica gel in presence of adsorbed water, (10) 352*e*.
in Si and Ge, amorphous, (8) 281*f*.
in silicon, self-compensation of, (7) 268*a*.
through SiC films, thin amorphous, (2) 62*g*.
in SiO vacuum-deposited films, (10) 343*h*.
of soda-lime-silica batches during latter stages of melting, (6) 209*f*.
space-charge-region surface, effect on change of resistance of thin germanium and silicon samples in high electric fields, (5) 180*f*.
specific, of molten lead bromide, (10) 360*h*.
of spinel LiV_2O_4, (4) 139*d*.
in sodium vanadium bronze, single-crystal studies, (1) 17*e*.
study, of Na^+ ion mobility in silicogermanate, aluminogermanate, and aluminosilicate melts, (2) 76*j*.
super-, in lanthanum sesquicarbide, (10) 357*i*.
properties, anomalous, of carbides and nitrides of group IVA and VA elements, (10) 350*d*.
properties of yttrium sesquicarbide, (10) 354*j*.
in pseudoferroelectrics, (2) 83*d*.
theory, through thin insulating films with large ionic space charge, (10) 362*b*.
of thin-film metal-dielectric systems, (9) 310*c*.
time-dependent, in rutile single crystals, (2) 84*a*.
of SnO_2, Zn-doped polycrystalline, effect of chemisorbed oxygen, (9) 320*g*.
through TiO_2 thin films with large ionic space charge, (10) 351*a*.
in ZnO crystals, due to Co^{2+}, (2) 81*d*.
of ZrO_2-CaO solid solutions at elevated temperatures, (6) 232*j*.
in ZrO_2-Y_2O_3-Ta_2O_5 system, (5) 195*g*.

Conductivity, electronic and(or) **ionic,** anionic, in refractory oxide solid solutions possessing fluorite, pyrochlore, and perovskite structures, (10) 349*h*.
in lithium fluoride, (8) 293*i*.
in magnesium orthosilicate, (4) 141*e*.
in NaCl pure and Mn-doped crystals, (8) 293*j*.

Conductivity, thermal. See also *Heat.*
of alkali halides, (4) 151*d*.
anisotropic, of electron-irradiated CdS, (7) 263*i*.
anomalous, of $BaTiO_3$ near ferroelectric transition point, (2) 74*i*.
of arsenic-sulfur binary glasses, (4) 97*e*.
of $BaTiO_3$-based solid solution and triglycine sulfate single crystals in phase transformation region, effect of constant electric field on, (4) 132*j*.
of carbonate rocks and clayey sandstones, (7) 266*c*.
of concrete, relation to unit weight, (1) 2*e*.
determination by hot-wire method, (4) 119*j*.
of ferroelecric crystals with hydrogen bonds, (8) 300*a*.
high temperature, of sintered UO_2, (2) 56*b*.
of hollow bricks determined by electrical modeling, (2) 71*c*.
low-temperature, of UN, (11) 385*e*.
of MgF_2 between 25° and 900°C, (6) 239*a*.
of MgO-$MgCr_2O_4$ and Al_2O_3-Cr_2O_3 solid solutions, temperature and concentration dependence of, (6) 238*h*.
measured by electron beam technique, (8) 285*b*.
measurements, furnace slag crust, (5) 189*a*.
in nonmetallic crystals, (2) 84*f*.
of nuclear fuel ceramics at high temperatures, (6) 217*b*.
through polyatomic gas mixtures, (7) 261*e*.
of pure fused quartz, precise determination, (9) 306*h*.
of refractories, rapid determination by hot-wire method, (11) 373*g*.
of refractory building materials under thermal and structural stress, determination, (4) 119*f*.
in NaCl crystals containing silver colloids, (1) 39*j*.
of sodium phosphates, vitreous, (4) 97*f*.
solid-phase, in glass fiber pad insulation, model for, (9) 306*h*.
study, of mixed oxides of U and Pu, (8) 300*c*.
of system UO_2-SiO_2 at 100°-800°C, (9) 331*e*.
of ThO_2-1.3wt% UO_2, changes induced by irradiation, annealing, (6) 208*e*.
of two-phase porous materials—dry soils, (9) 315*d*.
of UO_2, effect of porosity, (4) 133*e*.
at very high temperature gradients, comments, (8) 289*a*.
-metal cermets with oriented structure, (10) 341*h*.
of Zr hydrides containing 4 at.% U, (10) 360*h*.

Conductors, electrical. See also *Semiconductors.*
lead-in, for electrical devices, P (5) 175*d*.
photo-, P (5) 184*e*.

Conductors, electrical *(continued)*
photo-, device, with target including selenium blocking layer, P (2) 66*c*.
sheathed, with hermetic seal, P (9) 314*b*.

Conferences, on applications of X-ray analysis, proceedings of 15th, B (1) 40*h*.
Clay Plant Operators, engineered brick masonry, (4) 101*h*.
on Glass, Seventh International, July 1965 in Brussels, Vols. I and II of proceedings, B (4) 168*g*.
International Ceramic, in Madrid, highlights, (4) 108*c*.
International Clay, Jerusalem, Israel, June 1966, proceedings, B (4) 167*h*.
on material science: II, ceramic science and technology, (10) 353*d*.
on silicate industry, 1967, B (7) 272*h*.
third ceramic chemists', on silicate analysis, B (10) 366*j*.
on X-ray analysis, August 1967, B (9) 333*e*.

Congresses. See *Conferences.*

Contacts, aluminum-gold, to silicon and germanium, P (1) 17*h*.
electrical, providing by sputtering gold film on layer of sputtered Mo, P (7) 257*c*.
electrical, to semiconductor body, (2) 65*f*.
for insulation isolated semiconductor integrated circuitry, P (7) 256*c*.
low resistance, to diffused junction germanium transistor, P (2) 65*i*.
metal, on Si planar devices, masking for, (4) 111*h*.
metal-$BaTiO_{3-x}$, barrier height, (1) 25*j*.
metal-to-reduced $BaTiO_3$ single crystal, properties of barrier layers of, (2) 63*d*.
metal system of Al layer adjacent to semiconductor and layer of Au-Al intermetallics adjacent to conductive metal, P (7) 256*b*.
nonrectifying laminated ohmic, for semiconductors consisting of Cr and 80% Ni, P (7) 257*e*.
ohmic, consisting of bilayer of Au and Mo over alloyed region of Al-Si, P (7) 257*f*.
consisting of first level of Mo-Au and mixture of Au and V and second level of Mo-Au, P (6) 223*b*.
to semiconductor devices, P (4) 115*d*.
to substrate of insulating material with doped semiconductive oxide providing stepped energy gap, P (8) 283*g*.
p-, for compensated *p*-germanium crystal, P (11) 378*e*.
palladium ohmic, to silicon semiconductor, P (6) 223*c*.
semiconductor, P (8) 282*h*.
semiconductor, and interconnection structure, P (8) 283*b*.
structure, semiconductor device, P (4) 116*c*.

Containers. See *Glass.*

Controls. See also *Instrumentation; Temperature.*
antishock devices, for electrically heated glass panels, P (9) 307*j*.
automatic, of metal treatment systems, (1) 3*j*.
automatic system for combustion air flow in long ovens operating on wet process principle, (10) 336*a*.
furnace atmosphere, (2) 70*b*.
furnace heating, P (9) 316*d*.
grate cooler, method and apparatus, P (1) 3*g*.
for ore grinding mill, P (4) 125*d*.
technology, importance in highly mechanized porcelain plants, (10) 343*e*.
temperature, automatic, for laboratory furnaces, (2) 68*j*.
temperature, system, for glass manufacturing, P (4) 98*e*.

Conveyors. See also *Materials handling.*
for appliances, (7) 245*j*.
automates tile production, (2) 59*j*.
and classifier, P (7) 259*e*.
mechanism, P (7) 261*d*.
pneumatic, feeding, (8) 284*d*.
pneumatic, use in calcination, (4) 92*b*.
rolls, asbestos millboard, for high temperature use, P (10) 342*a*.

Cookeite, from Mulane pegmatite, Zambezia, Mozambique, (4) 130*a*.

Coolers, comprising sloping grate sections, P (4) 118*c*.

Cooling, device, liquid, for glass furnace electrode, P (1) 10*j*.
glass fibers, (4) 95*a*.
super-, constitutional, in presence of convection cells, (4) 129*f*.
TiO_2 with Mg surface, P (8) 287*i*.

Copper, acetylacetonate, susceptibilities, adsorbed on anatase and silica gel, and diphenylpicrylhydrazyl adsorbed on silica gel from 1°-4°K, (5) 200*h*.
in alkali metals and hydroxides, spectrophotometric determination with 4,4′-dihydroxy-2,2′-biquinoline, (8) 285*e*.
base friction material with dispersed spinels, P (6) 229*d*.
chloride, single crystals, growing with flux, (4) 144*h*.
-containing sulfides and selenides with spinel structure, magnetic and electrical properties, (4) 143*e*.
Cu(I) sulfide, anodic dissolution, and direct recovery of Cu and elemental sulfur from white metal, (4) 126*f*.
Cu(II) ion, spectrometric determination by N-8-quinolyl-*p*-toluenesulfonamide, (8) 285*e*.
Cu^{2+}, in KH_2PO_4, EPR, (2) 76*b*.

Copper, *(continued)*
- Cu-Cu_2O eutectic alloys, mechanical and electrical properties, (9) 324*j*.
- and Cu-Au alloys, oxidation in CO_2 at 1000°C: I, linear kinetics, (4) 148*b*.
- $CuFe_2O_3$ and $CuFe_2O_4$-Fe_3O_4 spinel solid solution, eutectoid decomposition, (9) 321*a*.
- $Cu_{1-\xi}Mg_{\xi}Fe_2O_4$, oxygen content and thermomagnetic properties in, (1) 34*e*.
- $CuO_{0.97}$, reduction in hydrogen, (1) 36*b*.
- $CuTl(PO_3)_3$ and $CuRb(PO_3)_3$, crystallographic data, (9) 331*f*.
- Cu_2Zn_3, Cu_2Cd_3, and Cu_2Al_3, redetermination of distribution of atoms in, (8) 297*h*.
- cupric molybdate, paramagnetic, crystal structure, (4) 130*e*.
- cupric molybdate, single crystal, growth and properties, (7) 266*h*.
- cupric oxide, dissociation, near-equilibrium kinetics, (4) 145*j*.
  - effects on formation of zircon, (8) 291*j*.
  - effects in Na_2O-CaO-SiO_2 glass and on color and on spectral transmission, (11) 369*j*.
  - free energy of formation, (4) 136*e*.
  - thermodynamic properties, by emf measurements, (10) 362*j*.
- cuprous chloride, single crystals, growth, for optical modulators, (5) 194*d*.
- cuprous oxide, absorption line (n = 1), (1) 24*g*.
  - crystal growth by hydrothermal technique, (9) 319*a*.
  - effect of silicon on, (9) 320*j*.
  - optical properties in ultraviolet, (4) 147*a*.
  - single crystals, growth in SiO_2 gel at near ambient temperatures, (10) 354*j*.
  - temperature dependence of nuclear quadrupole resonance in, (4) 159*b*.
- in high purity lead metal, determination by neutron activation analysis, (5) 187*e*.
- montmorillonite, sorption of α-amino acids by, (7) 269*e*.
- in nickel ferrites, determination by atomic absorption analysis, (6) 225*g*.
- (111) face, structural characteristics of Cu_2O film on, (8) 298*b*.
- rapid extraction and direct spectrophotometric determination, with thiothenoyltrifluoroacetone, (8) 285*b*.
- role in transformation of hexagonal ZnS, (4) 153*g*.
- sealing in silica body, P (8) 278*b*.
- selenide, marcasite-type superconductor, (9) 318*j*.
- in soda-boric oxide glasses, (6) 208*i*.
- sulfide, crystals, large, synthesis, (9) 331*i*.
- sulfide, metalizing with Al_2O_3, effect of kaolin, (2) 52*b*.

systems. See *Systems.*

thin films. See *Films, thin.*
- valence state, in cubic $CuMn_2O_4$ spinel, determination by X-ray absorption edge measurements, (9) 319*f*.
- /vanadium oxide compositions, noble metal metalizing compositions containing vanadium oxide additives, and electrical conductor elements made with, P (7) 256*d*.

Cordierite, coexisting with biotite and garnet, distribution of Mg and Fe in, (7) 265*g*.
- phase transformations in firing of spinel-mullite mixtures and charges of, (6) 238*f*.
- properties, as filler for heat-resistant concrete, (11) 368*a*.
- structure, electroceramics with, (2) 62*h*.

Cores, ceramic, P (5) 178*j*.
- ceramic, apparatus for helixing path in carbon film deposited on, P (2) 64*f*.
- ferrite, with different regions of varying permeability, P (4) 113*c*.
  - matrices, wiring, P (11) 377*j*.
  - processing, P (5) 184*b*.
- foundry, liquid mixes for, P (5) 178*i*.
- foundry, or molds, P (6) 218*c*.
- lithium ferrite magnetic, P (4) 115*d*.
- magnetic, high temperature, P (4) 113*a*.
- miniature magnetic, memory array, P (7) 257*f*.
- mold, method and apparatus for dusting, P (2) 60*j*.
- sand, P (6) 218*a*.
- sand, preparation using CO_2 cured silicate binders, P (8) 280*a*.
- sand foundry, polyurea bonded, P (10) 343*a*.
- welding, for tubes, P (4) 109*d*.

Corrosion, accelerated vertical, peculiarities, (9) 306*d*.
- of aluminosilicate refractories under service conditions, (7) 251*a*.
- of casting pit refractories by slag, (10) 340*j*.
- of ceramic decoration during machine washing, (1) 15*g*.
- of firebrick by brown coal ash, (5) 176*j*.
- effect of slag composition on dolomite clinker, (11) 372*i*.
- of enameled surfaces: I, enamels for sanitary ware, (10) 336*f*.
- of high-fired magnesite-chromite brick, fired dolomite brick, and fired magnesia brick by different basicity slags, (11) 372*h*.
- joint, and upward drilling in glass tanks, physical and chemical reactions leading to, (9) 306*e*.
- mechanism, in basic brick, (11) 372*i*.
- of metals, influence of electric charges, (7) 267*h*.
- of mullite refractory with 70-72% alumina by ash of fuel oil, (4) 103*b*.
- of optical glass polished surfaces by small droplet of etchant solution, (6) 208*j*.

Corrosion, *(continued)*
- on preirradiated Zircaloy-2 and Zr, (4) 148*i*.
- of recrystallized alumina by fluoride melts, (5) 176*i*.
- of refractories for glassmelting furnaces, P (1) 11*j*.
- of refractories by molten steel, (7) 251*i*.
- of refractory materials by glass melts, (9) 305*a*.
- of reinforcement in autoclave silicate concrete from lime-silica cement using hydrated lime, (2) 44*a*.
- resistance, of Cr_2O_3 containing high silica pyrophyllite brick for cupola, (7) 250*e*.
- resistant materials, high, to fluorine attack at cryogenic temperatures, and preparation, P (6) 217*d*.
- of steel in lightweight concrete specimens, (4) 91*d*.
- test, by crucible method, for cupola brick, (7) 251*h*.
  - by induction furnace method, for ladle brick, (7) 251*h*.
  - on refractories immersed in molten iron, (10) 342*d*.
- testing and service performance, B (10) 366*a*.
- of waste heat boilers attached to heavy-oil-fired regenerative glass tanks with operating pressures of 10 and 30 atm, (6) 211*h*.

Corundum. See also *Aluminum, oxide; Refractories.*
- (α-Al_2O_3), lattice sites, self-consistent ionic potentials, fields, and field gradients at, (9) 329*e*.
- α-, surfaces, chemical polishing, with V_2O_5, (4) 150*f*.
- ceramics for high-temperature furnaces with hydrogen atmosphere, (2) 54*h*.
- ceramics, microstructure and heat resistance, (10) 341*d*.
- crystals, grown by verneuil method, motion of dislocations in, (10) 357*d*.
  - oriented basal flakes, effect of etching on dislocations in, (1) 27*h*.
  - strength, influence of annealing, (2) 78*g*.
- electro-, standard, spectral analysis, (1) 22*d*.
- electrofused, impurities in, (11) 382*c*.
- heat content, from 0° to 2000°K, toward equation of, (7) 270*c*.
- Fe^{3+} in, Moessbauer hyperfine spectra of—magnetic- and crystal-field effects, (2) 80*e*.
- mechanical activation, (4) 127*c*.
- quartz-, stability, problem, (10) 359*c*.
- Raman effect, (4) 152*c*.
- sintering, effect of additions, (5) 177*c*.

Costs, standard, (6) 240*d*.

Cracks, bifurcation in brittle solids, (11) 383*h*.
- deep, in glass, generation, and reply, (8) 276*a*.
- formation, in sintered two-phase alloys, (8) 289*g*.
- front, interaction with cleavage steps on MgO fracture surfaces, (4) 140*j*.
- in glass, analysis, (4) 94*h*.
- growth, in brittle ceramics, (11) 383*i*.
- nucleation, from dislocation pileup, criterion for, (2) 75*g*.
- nucleation, and mechanical twinning in lithium niobate, (9) 324*b* .

Crazing. See *Glazes.*

Creep, in brittle ceramics, (11) 383*i*.
- of clays, partially saturated, (1) 23*j*.
- compressive, characteristics, of selected refractories, (6) 214*i*.
- compressive, of high purity Al_2O_3 refractories, (8) 278*j*.
- of concrete at high temperatures, apparatus for measuring, (5) 170*d*.
- of concrete under multiaxial compressive stress, measurement equipment, (1) 21*j*.
- and creep fracture, of Ni-20Cr-2ThO_2 alloy, (1) 26*d*.
- data, observations on interpretation, (1) 37*b*.
- during dehydroxylation of $Mn(OH)_2$, (10) 351*f*.
- in fiber-reinforced composites, theoretical analysis, (11) 368*j*.
- high-temperature, effect of liquid formation, (2) 55*e*.
- high-temperature, of magnesia, effect of minor additives, (11) 373*c*.
- high-temperature compressive, of U-C alloys, (4) 138*d*.
- of LiF, polycrystalline, (9) 319*a*.
- rate, effect on cavity growth mechanism, (1) 27*e*.
- in SiC, (4) 130*i*.
- of sintered oxide ceramics, (4) 163*i*.
- steady-state, in BeO, activation energies, correlation with self-diffusion, (8) 289*f*.
- tensile, of porous polycrystalline Al_2O_3, (2) 84*c*.
- tensile, rate, in carbons and graphites, stress dependence of, (8) 298*a*.
- of ThO_2 and ThO_2-CaO solid solutions, (2) 75*f*.
- time-dependent, with concurrent grain growth, correlation between models, (6) 231*g*.
- of ZrB_2 at high temperatures, (5) 176*j*.

Cristobalite. See also *Silicon, oxide.*
- α- and β-, for glass-ceramic articles, P (8) 277*e*.
- heat of fusion, (7) 267*g*.
- high, metastability in vitreous silica, (8) 295*b*.
- as separation phase in porcelain glazes containing spinel, (7) 253*h*.
- solution and diffusion of He and Ne in, (5) 200*a*.

Crocidolite, dehydroxylation, kinetics and mechanism, (4) 142*f*.
- thermal decomposition, (2) 84*f*.

Crucibles. See *Refractories.*

Crushing. See also *Crushing apparatus; Mills.*
- attrition scrubbing, of Cheyenne sandstone, (9) 316*e*.
- limestone, by electromagnetic-thermal means, requirements of apparatus for, (6) 224*g*.
- material, P (6) 229*g*.
- pelletizing, on flat surface using three-dimensional vibrations, (8) 284*f*.
- process, effect of water on crushed quantity and grain size of raw material during: I, in dry pan mill; II, in edge runner mill; III, by impeller breaker, (10) 341*d*.
- size reduction, literature review, (1) 20*b*.
- size reduction, review, (4) 118*c*.

Crushing apparatus. See also *Mills.*
- bearing support for, P (8) 287*e*.
- cone, with noneccentric drive, P (8) 287*g*.
- dynamical selector device for, P (5) 190*h*.
- gas-hydraulic system for, P (4) 124*a*.
- granulator, fine, P (7) 259*a*.
- gyratory, P (4) 124*b*; P (5) 190*j*.
  - bearing device for vertical shaft of crushing cone of, P (4) 124*h*.
  - bowl securing and bowl removing means, P (7) 262*d*.
  - capacitance measuring means for indicating clearance in, and means to compensate for stray capacitance, P (7) 262*e*.
  - clearance measuring means with resonant coupling circuits, P (7) 262*i*.
  - combined with attrition, P (10) 349*c*.
  - load control system, P (11) 382*b*.
- gyratory bowls, clamping and release means for, P (11) 382*i*.
- high speed, P (6) 229*g*.
- jaw, P (5) 190*j*.
- rock, lining ring assembly for, P (2) 74*b*.
- for rock material, utilizing complex sonic wave action, P (4) 124*h*.
- rotary, feeding aid, P (8) 288*d*.
- and sorting, solid particles, P (5) 190*d*.
- twin rotor high efficiency, P (4) 126*c*.
- for wet sizing finely divided solid materials, P (7) 259*b*.

Cryolite, effect on calcium silicate compositions, P (9) 304*b*.
- liquid, identification of complex ions in, (6) 233*d*.
- material, beneficiation, P (10) 349*a*.

Crystal chemistry, of amphiboles, B (1) 41*a*.
- of binary systems of donor and acceptor molecules, (7) 264*e*.
- inorganic, fundamentals, B (11) 388*g*.
- of manganese arsenates: III, crystal structure of eveite, $Mn_3(OH)(AsO_4)$, (10) 351*g*.
- of sodium scandium titanate, and its isomorphs, (11) 383*j*.
- thermal behavior of materials on basis of, (1) 39*j*.

Crystalline materials, bodies, preforming, P (11) 378*j*.
- ceramics, average grain size in, (10) 350*h*.
- elastic strain measurement in, by X-ray diffraction, (9) 315*e*.
- poly-, ceramics, fracture-exposed surfaces, characteristics, (1) 25*g*.
  - electronic, and inorganic single crystal, preparation, P (6) 222*d*.
  - media, third-order elastic constants, (2) 84*i*; and relationships to single crystal constants, (2) 84*j*.
  - oxide bodies, P (8) 274*e*.
  - oxidic ceramic, treating objects of, P (11) 377*h*.
  - thermal grooving, data evaluation, (8) 292*e*.
- rod, increasing cross section during crucible-free zone melting, method and apparatus, P (4) 114*g*.
- rods, crucible-free floating zone melting, apparatus for, P (10) 344*b*.

Crystallinity, percentage determination, of partly crystallized glass, (4) 120*d*.
- role in sintering of UO_2 powders, (2) 57*d*.
- of UO_2 powders, evaluation by streaming potential studies, (2) 55*h*.

Crystallization, of alite and belite in portland cement clinkers, effect of additives, (1) 2*g*.
- of ρ-alumina and alumina gel in aqueous solutions of various basic reagents, (4) 138*j*.
- of aluminosilicates, P (5) 191*a*.
- of boron nitride formed by reaction of boron trichloride with ammonia, by heat treatment, (5) 177*i*.
- centers, formation in light-sensitive glasses, (2) 51*b*.
- cycles, effect on formation of fine needle-shaped mullite, (6) 215*e*.
- electric fusion, of oxides of Mg, Zr, and Ca, P (4) 106*d*.
- electro-, processes, effect of diffusion through solution and along surface: I, potentiostatic case; II, Faradaic impedance; III, influence of finite rate of lattice formation, (4) 132*c*.
- in enamels, TiO_2-opacified: I, theory; II, comparison of theory with experiment, (4) 93*d*.
- of eucryptite, high-form, (6) 231*j*.
- of GaP from stoichiometric melt in Ga solution, (8) 290*f*.
- of glass, aluminosilicate, nucleation by spinodal decomposition into vitreous phases, (6) 210*i*.
  - Al_2O_3-SiO_2, (4) 96*d*.
  - in BaO-SiO_2 system, (2) 51*h*.
  - bulk, kinetics, (10) 338*a*.
  - change in structure and mechanical properties during, (2) 47*d*.

Crystallization, of glass *(continued)*
devitrification studies with X rays, (6) 208*g*.
drawn sheet, problems, (8) 276*d*.
initiating and controlling, P (8) 277*i*.
iron-containing, stimulated, (1) 9*d*.
kinetics, (4) 96*b*.
influence of heat treatment during precrystallization period, (2) 49*d*.
influence of trace impurities, (1) 7*a*.
lead-silicate, of $2PbO{\cdot}SiO_2$ composition, study by infrared spectroscopy, (7) 269*c*.
lithia-alumina-silica, study of initial stages by Moessbauer effect and X-ray phase analysis, (1) 9*a*.
of low network-former content, (8) 276*i*.
metastable liquidus and its effect, (6) 210*c*.
slag, fluorine-containing, (2) 47*h*.
sulfoselenide, oxygen-free, (7) 247*a*.
in system Li_2O–Al_2O_3–SiO_2, (8) 276*c*.
in system Li_2O–Al_2O_3–SiO_2 electron microscopy, (1) 6*i*.
in system Na_2O-CaO-MgO-Al_2O_3-SiO_2, effect of fluoride, (6) 209*c*.
in system Na_2O-MgO-CaO-Al_2O_3-SiO_2, (6) 211*f*.
X-ray diffraction method for quantitative determination, (6) 208*g*.
of glass powder with cordierite composition, (1) 36*h*.
of gold onto color-centered cleavage surface of rock salt, (6) 235*j*.
hydrothermal, of alkaline $Al_2O_3SiO_2$-P_2O_5 compositions, (1) 26*a*.
hydrothermal, of II-VI compounds, (8) 293*c*.
influence on properties of glasses in Fe_2O_3-BaO-B_2O_3 system, (10) 337*i*.
kaolinite, from H-exchanged zeolites, (6) 234*c*.
of lanthanum hexaboride, (9) 319*i*.
of $PbO{\cdot}2B_2O_3$ from supercooled melt, (8) 276*d*.
mixed, of UN with nitrides, (9) 324*i*.
modifications, of calcium carbonate, (7) 264*i*.
phases, initial, for glasses of system SiO_2-Al_2O_3-BaO-TiO_2 by optical anisotropy, (10) 337*j*.
phases, new single-, in Cu-Nb-S system, vapor growth, (9) 332*i*.
of phases and decomposition of melilite during cooling of molten blast-furnace slag, (6) 231*i*.
of KCl from aqueous solutions in presence of lead ions; I, calorimetric study, (7) 264*i*.
re-, of anhydrous calcium acid phosphate from dihydrate form, P (5) 191*d*.
hydrothermal, of porcelanite to quartz, (9) 322*j*.
of machined surfaces of BeO, (10) 342*a*.
of Ni-coated carbon fibers, (9) 328*g*.
and texture of Al_2O_3, (11) 385*f*.
review, (4) 164*i*.
of Ag and Au on doped NaCl substrates, (2) 62*j*.
in Sr-Zn glazes, (8) 280*b*.
temperature, of vitroceramics, decrease, (11) 369*d*.
of Ti, Zr, and Hf oxides and titanate and zirconate compounds under hydrothermal conditions, (8) 290*f*.
of tungsten disulfide, from molten slags, P (1) 13*h*.
by verneuil method, behavior of solid solutions of rare earth oxides in binary systems during, (9) 318*g*.
of vitreous crystalline coating, influence of application process, (2) 45*h*.

Crystallography, characteristics, of praseodymium hydrides, (2) 79*h*.
comparative crystallochemical systematics and morphotropic transformations of silicates and their analogs (germanates and fluoroberyllates), (4) 129*c*.
data, of $Ba_{4+x}Na_{2-2x}Nb_{10}O_{30}$, (11) 383*c*.
for CaP_4O_{11}, (10) 351*f*.
primary, (7) 268*f*.
of rare-earth iron borates, (11) 387*i*.
for tetrametaphosphates of type $M_2^{III}P_4O_{12}$, (2) 75*h*.
for two varieties of $ZnNH_4PO_4$, (2) 75*i*.
of high-pressure forms of C_6H_6, CS_2, Br_2, CCl_4, and KNO_3, (11) 383*d*.
history, (1) 40*d*.
optical, B (10) 365*b*.
polarity, of CdS, determination by ion scattering, (7) 265*c*.
polarity, of GaSb, (9) 321*f*.
properties, of alkali strontium-barium-lead niobate systems with tungsten bronze structure, (7) 254*e*.
of η phase in Mn-Ga system, (2) 79*h*.
X-ray, of cummingtonite-grunerite series, (4) 164*c*.
of rare-earth double oxides of type $LaTO_3$ where T = Ho, Y, Er, Tm, Yb, Lu, (6) 231*b*.
of rare-earth fluorides, complex, (9) 319*j*.
of series Mn_x $Fe_{1-x}HoO_3$, (10) 351*f*.
of Na_2FeF_5, (7) 264*j*.
structure of $LiCuVO_4$, (2) 75*i*.
X-ray, (4) 121*a*.

Crystals. See also specific kinds.
absorbing uniaxial, longitudinal and transverse optical constants determination, (4) 131*h*.
alkali halide, doped with hydroxyl ion, growth and characterization, (2) 78*d*.
NMR measurements of distortion effects around substitutional monovalent ions in, (8) 295*g*.
shell model for calculation of surface distortion in, (4) 126*i*.
spectroscopic constants for O_2^- ions in, (8) 298*c*.

Crystals, alkali halide *(continued)*
theory of thermal equilibrium charge on edge dislocations in, (4) 160*g*.
alkali iodide, paramagnetic resonance spectra of O^- trapped in, (8) 296*b*.
alkali metal aluminate tetrahydrate, P (5) 191*f*.
$AlCl_3{\cdot}6H_2O$, pure, recovery, and production of Al_2O_3 product from, P (2) 74*f*.
Al_2O_3, growth by flux-fusion method, (10) 346*f*.
impurity deposits on, (10) 355*i*.
morphology, (10) 357*b*.
preparation from vapor phase reaction by monitoring spectral scattering of light, P (9) 317*a*.
β-Al_2O_3, structure, (6) 231*h*.
ammonium copper(I) sulfite, structure, (8) 290*b*.
apatite, natural, fission tracks on $(10\bar{1}0)$ cleavages of, (1) 29*g*.
apophyllite, growth mechanism studied by surface microstructures, (6) 233*a*.
apophyllite, rotation of etch pits on basal cleavages of, (1) 36*i*.
artificial, of isomorphous series scheelite-powellite, production and study, (4) 151*e*.
axial, Gruneisen, functions for, (2) 77*j*.
BaF_2, F^-vacancy conductivity in, (5) 194*a*.
BaF_2, interstitial conduction in, (5) 195*g*.
$BaTiO_3$, fine particles, structure, (4) 131*b*.
$BaTiO_3$, melt-grown, dielectric and optical properties, (10) 352*b*.
BeO, X-ray diffraction contrast of inversion twin boundaries in, (10) 363*d*.
$BeSiN_2$, structure, (8) 299*b*.
bi-, MgO, transgranular fracture studies on, (5) 202*i*.
bi-, mathematical characterization, (1) 32*a*.
$3Bi_2O_3{\cdot}17Nb_2O_5$, ideal composition, structure, (8) 298*d*.
borax decahydrate, P (1) 24*b*.
BAs-GaAs, preparation and properties, (1) 35*g*.
CdI$_2$, polytypic, nucleation and epitaxial growth, (7) 267*h*.
CdI$_2$, of trigonal symmetry, 8-, 9-, and 12-sided growth spirals on, (7) 267*h*.
CdS, bulk, closed system, vapor growth from elemental constituents, (4) 109*j*.
grown by different methods, nonstoichiometry, (10) 357*g*.
grown from vapor phase, dislocations and origin in, (4) 131*i*.
hollow, Na-doped, (7) 268*d*.
sublinear photocurrents and surface recombination in, (2) 83*c*.
calcium chlorophosphate, pentavalent Mn-activated, for use in coherent light source, P (6) 221*b*.
calcium fluor- and chlorapatite, growth and crystallographic properties, (4) 137*g*.
CaF_2:Dy^{2+}, generation of giant pulses in, using electrooptical shutter with $LiNbO_3$ crystal, (2) 77*b*.
calcium fluorophosphate, Czochralski growth, (9) 319*c*.
$Ca(OH)_2$ and $Ca(OD)_2$ vibrational structure, normal coordinate, analysis, and assignment, (4) 127*c*.
of α-$CaSO_4{\cdot}\frac{1}{2}H_2O$, dissolution in water, (2) 83*b*.
of Ce(III) exchanged faujasite, structure, (4) 130*g*.
CrB_4, structure, (10) 351*i*.
clinochlore, new analyzing, for X-ray region 5–27 Å, (8) 284*j*.
common analyzing, angular positions of X-ray emission lines of elements for, (9) 318*b*.
of $CuMoO_4$, paramagnetic, structure, (4) 130*e*.
Cu_2O, growth by hydrothermal technique, (9) 319*a*.
CuS, large, synthesis, (9) 331*i*.
corundum, grown by verneuil method, motion of dislocations in, (10) 357*d*.
oriental basal flakes, effect of etching on dislocations in, (1) 27*h*.
strength, influence of annealing, (2) 78*g*.
or crystalline layer, growing by means of direct current arc discharge, P (8) 282*j*.
crystallite size determination of BeO, (8) 285*i*.
crystallites, of γ-alumina, growth, (1) 31*e*.
cubic, calculation of vacancy migration energy in, (9) 318*a*.
cubic, subjected to moderately high hydrostatic pressure, elastic constants, (9) 320*g*.
data on, $La_2GeC_{1.8}$, (9) 319*b*.
defect, detection by metrology method, P (1) 22*f*.
defect clusters in electron and neutron irradiated LiF, (8) 290*h*.
defect structure, high-temperature, of NiO, (8) 293*c*.
deformation, effect on lattice vibration of oxide spinels, (1) 27*f*.
diamond, filamentary, (7) 265*i*.
-like, theory of third-order elastic constants of, (4) 160*h*.
natural of cube form, structure studies, (1) 38*c*.
seed, growing diamond on, P (5) 186*e*.
synthetic, P (8) 273*g*.
diatomic, force constants and cohesive energies, (2) 77*g*.
dipolar coupling and molecular vibration in, (8) 290*i*.
dislocations. See *Dislocations*.
distortions, of $BiMnO_3$ and $BiCrO_3$, (8) 294*j*.

Crystals *(continued)*
electric field in: III, refractivity of α-quartz, (4) 134*a*.
ettringite, structure, (9) 319*e*.
europium sulfide, selenide, and telluride, high temperature vapor phase growth, (9) 322*h*.
faujasite, number of hydroxyl groups at exterior surfaces of, (2) 81*b*.
ferroelectric, with hydrogen bonds, thermal conductivity, (8) 300*a*.
KH_2PO_4-type, dynamic theory of phase transition in, (2) 75*j*.
tungsten bronze-type, structures: I, barium strontium niobate, (5) 194*f*; II, barium sodium niobate, (11) 385*a*.
field, of ruby and stressed MgO:Cr^{3+}, (10) 351*h*.
field parameters of Eu^{2+} in YPO_4, (9) 327*i*.
field studies, of Co^{2+} in α-$Zn_3(VO_4)_2$, (1) 26*d*.
of Ni^{2+} in α-$Zn_3(VO_4)_2$, (7) 264*e*.
on V and Cr in ZrO_2, (4) 130*c*.
fluoride, structures: I, WOF_4 (5) 194*i*; II, $MoOF_4$; $ReOF_4$, (8) 292*g*.
fluorides, growth, in lanthanide series, (7) 264*f*.
fluorite, with impurities of Sc, Y, and La, (10) 353*g*.
formation. See *Crystallization*.
fragile, machining, P (9) 314*h*.
$GdAlO_3$, growth, (7) 264*g*.
$GdFeO_3$ type, structure, (2) 75*h*.
GaAs, grown from silica boats, photoluminescence study of thermal conversion in, (7) 255*h*.
GaP, dendritic, with grown-in *pn* light emitting junctions, P (5) 185*c*.
grown from Ga solutions, vapor phase, and liquid phase epitaxial deposition, defect structure, (10) 351*g*.
grown by VLS mechanism with Ga as liquid-forming agent, morphology, (7) 267*e*.
large, solution grown, preparation and properties, (4) 111*d*.
Li-diffused Mn-doped, EPR detection of triple Li ion centers in, (10) 353*f*.
pulled by liquid encapsulation method, (5) 187*i*.
pulling by liquid encapsulation, (7) 255*a*.
GaS, cooled homogeneous, electroluminescence from, P (8) 282*f*.
garnet-like, structure, of high-pressure calcium germanate and cadmium germanate, (5) 194*b*.
gem-like, P (6) 224*c*.
p-germanium, compensated, *p*-contact for, P (11) 378*c*.
growing, flame fusion, employing vertically displaceable pedestal responsive to temperature, P (8) 282*h*.
growth: Vol. 6, parts A and B, B (9) 334*c*.
Czochralski, radial solute segregation in, (4) 151*i*.
Czochralski, temperature oscillations in, (4) 159*g*.
Czochralski, tri-arc furnace for, with cold crucible, (5) 188*b*.
effect of segregation of impurities in molten salts induced by cellular convection on, (7) 268*j*.
epitaxial, wherein distance between carrier and transfer material is adjusted to effect either material removal from carrier surface or deposition on, P (5) 185*b*.
in gel by complex dilution method, factors influencing, (9) 329*a*.
high-temperature solution (flux) and high-pressure solution (hydrothermal), (10) 355*b*.
horizontal, thermal convection in, (6) 239*a*.
hydrothermal, large noble metal can technique for, (5) 187*c*.
hydrothermal, of spinel LiV_2O_4, (4) 139*d*.
of laser material, fluorapatite, (4) 130*d*.
least square method to determine theoretical rate of, versus relative supersaturation curve from accurate data, (5) 196*a*.
of metastable quartz solid solutions in MgO-Al_2O_3-SiO_2 glasses, (7) 264*h*.
models, for slightly supersaturated solutions, analysis, (5) 192*d*.
from molten salts, surface microstructures, (4) 158*c*.
rate from solution, (7) 266*h*.
rates, determination with Peltier effect, (4) 126*i*.
in silica gel using cosolute, (9) 322*d*.
from solution, kinetics, (5) 196*e*.
from solution, at low supersaturations, error analysis of technique to determine rate of, (5) 194*e*.
from solution, rate, relation to relative supersaturation at low supersaturation, (6) 233*i*.
from solution, theoretical analysis of requirements for, (7) 270*g*.
of spinels in system MgO·Al_2O_3-Al_2O_3 by flame fusion, (9) 319*c*.
spiral, of monocrystalline layers of ferrites, (4) 155*j*.
and surface structures of crystal faces, mechanism, (1) 32*d*.
of ternary metal oxides by chemical transport, (10) 351*i*.
of transition metal niobates, (6) 239*c*.
from vapor, and apparatus, P (4) 112*c*.
vapor phase, thermal balance for measuring transport during, (5) 188*j*.
by various methods, inhomogeneities, optical investigations of, (10) 358*b*.

Crystals, growth *(continued)*
- at very high gas pressures, equipment for, (7) 254*h*.
- VLS, mechanism of branching and kinking during, (4) 143*h*.

habits of $Mg(OH)_2$, effect on MgO sintering, (1) 28*g*.
halide, plastic deformation, influence of color centers, (2) 78*j*.
hardness anisotropy, impression and scratching tests for, (2) 70*a*.
ice, growth from melt, preferred orientation in, (5) 198*g*.
inclusions, in glasses, (4) 95*c*.
of In_2O_3 and $In(OH)_3$, rhombohedral, structure, (4) 139*i*.
ionic, electric fields produced by charge density in, (4) 134*c*.
- electrostatic potentials and spatial derivatives about point defects in, (4) 135*c*.
- energy of formation of Schottky defects in, (1) 29*g*.
- migration of inert gases in, (9) 324*g*.
- theory of slow electrons in, quadratic approximation, (10) 356*b*.

$Fe(NH_4)_2{\cdot}6H_2O$ and $KAl(SO_4)_2{\cdot}12H_2O$ seed, isothermal dissolution and growth rates, effects of high magnetic fields, (4) 133*g*.
of lamellar calcium aluminum hydrates, structure, (4) 130*e*.
larger and more perfect needed, (7) 254*g*.
for laser devices, assessment and control of imperfections in, (9) 318*f*.
lattice, damage in MgO caused by electrical breakdown, (9) 324*f*.
- GaAs, temperature dependence of microwave dielectric constant of, (4) 159*b*.
- imperfections, testing in transparent materials, P (4) 100*a*.
- parameters, of Al_2O_3 and MgO, effect of low temperature neutron irradiation and 20°–400°C annealing on, (4) 133*a*.
- perturbations in $CaWO_4$ and $CaMoO_4$, (2) 79*e*.
- reciprocal spikes, in type Ia diamonds, (4) 153*e*.
- spacings, of periclase-chromite solid solutions, (4) 142*h*.
- spectrophotometric determination of coordination ratios in: III, Mg_3TeO_6 and Mg_2InSbO_6, (9) 329*f*.
- spinel, ferromagnetic exchange coupling in, (4) 136*d*.
- spinel, magnetization process in, (2) 80*g*.
- sub-, magnetic, of lanthanide ferrite garnets, reversal of, (2) 77*c*.
- theory of surface effects on thermal diffuse scattering of X rays or electrons from, (2) 84*e*.

lattice constant, of α-FeOOH prepared by different methods, (9) 324*d*.
- of cubic solid solutions ZrO_2-CaO and ZrO_2-Y_2O_3, (6) 234*f*.
- and space groups of tridymite at 20°C, (6) 234*j*.
- in systems $BaSO_4$-$SrSO_4$-$PbSO_4$, (10) 361*e*.

lattice defects, in ionic crystals, inert-gas diffusion as probe for, (8) 293*j*.
lattice defects, in quartz, X-ray moire topography, (9) 333*b*.
lattice deformation, of CoO scales, effect of stoichiometry, (9) 320*b*.
lattice dynamics, of CsCl, CsBr, and CsI, (5) 196*i*.
- of imperfect alkali halides, (6) 234*j*.
- of IBr, ICl, and I_2Cl_6, study by Moessbauer effect in ^{129}I, (4) 156*j*.
- of NaCl, X-ray study, (4) 164*b*.

lattice parameter, in Fe_3O_4, NiO, and Ni-Fe ferrite, influence of stoichiometry, (10) 344*g*.
- of lanthanide compounds, interrelations with melting point and heat of formation, (10) 355*i*.
- of solid solution of lithium oxide in nickel oxide, variations in, (9) 332*j*.
- of $Y_{0.25}TaO_3$, determination, (8) 290*e*.

lattice planes, small tilt angles in, determination by Berg-Barrett X-ray diffraction microscopy, (10) 359*d*.
lattice sites, of corundum (α-Al_2O_3), self-consistent ionic potentials, fields, and field gradients at, (9) 329*e*.
lattice structure of (100) free surface of $BaTiO_3$, (6) 234*j*.
layer-type, enhanced reactivity at dislocations in, (4) 135*j*.
lead halide, ESR and optical studies of low-temperature radiation effects in, (8) 291*i*.
$PbaMgNb_2O_6$, devices using, P (10) 344*f*.
of lithium aluminum hydride, structure, (4) 130*h*.
lithium metagallate, growth by Czochralski method, (6) 231*b*.
lithium metaniobate, growth from melt containing MgO, P (4) 113*i*.
$LiNbO_3$, EPR of lanthanide ions and Cr^{3+} in, (2) 76*c*.
- growth, (1) 16*f*; P (8) 282*i*.
- growth ridges, etched hillocks, and structure, (8) 292*e*.
- second harmonic generation in by picosecond pulses, (7) 268*j*.
- second-harmonic phase-matching temperature in, dependence on melt composition, (1) 26*j*.
- works to pack in 1000 holograms, (5) 181*g*.

Crystals *(continued)*
- lithium tantalate, oriented, and devices using, P (11) 378*b*.

$MgAl_2O_4$ spinel, stoichiometric, growth by flux evaporation, (10) 354*b*.
MgO, cube-oriented, deformation under pressure, (8) 290*i*.
- neutron-irradiated, zero-phonon lines and phonon coupling in, (2) 84*i*.
- origin of water-induced toughening in, (4) 148*a*.

Mg_2PtO_4 and Zn_2PtO_4, structure, (10) 362*a*.
Mg_2SiO_4, structure, high-pressure modifications, and crystallochemical and geophysical implications, (10) 354*h*.
magnetite, remanent and transitory effects of elastic deformation of, (4) 153*j*.
Mn ferrite, growth, (7) 254*g*.
MnO, hyperfine interaction in, (2) 78*e*.
MnO, total energy and 2*p* O^{2-} ion wave function, (5) 202*h*.
melt-growth process, wherein melt surface is covered with inert liquid, P (1) 18*d*.
metal and $BaTiO_3$, contacts, barrier height of, (1) 25*j*.
micro-, α-Fe_2O_3, Morin transition in, (4) 145*c*.
of mixed-alkali ferrite: $K_xNa_{1-x}Fe_7O_{11}$, ion mobility in, (10) 356*d*.
mixed $(Ca_xSr_{1-x})F_2$ and $(Sr_xBa_{1-x})F_2$, Raman scattering from, (2) 82*a*.
mixed, formation in system CaO-SrO, (2) 77*g*.
molecular, physical properties, B (6) 241*i*.
of MoO_3, structure, refinement, (4) 153*f*.
molybdenum oxide, growth and microstructure, (9) 322*g*.
mono-. See *Crystals, single*.
morphology and growth mechanisms of α-Fe_2O_3 whiskers on iron, (4) 130*e*.
multisublattice ionic, cation distributions in, and applications to solid solutions of ferrimagnetic garnets and spinels, (10) 350*c*.
neodymium monotellurooxide, structure, (11) 388*c*.
NiBr₂, surface-spike growth on, VLS mode of crystal growth, (4) 158*g*.
nickel ferrite, growth from barium borate by pulling method, (7) 254*j*.
$Ni(OH)_2$, magnetic heat capacity at low temperatures, particle size dependence of, (4) 148*f*.
nickel iron ferrite, grown using arc image furnace techniques, (4) 146*b*.
NiO, fluxed-melt growth, and electrical properties, (7) 254*i*.
- growth by solar furnace fusion, (7) 266*g*.
- lithiated, P (6) 221*j*.

Nb_2O_5, diffusional properties of oxygen in, (5) 193*e*.
NbO_6, preparation and dielectric properties, (10) 359*f*.
noncentrosymmetric, growth in polar direction, role of superficial polarization, (4) 138*a*.
nonmetallic, thermal conductivity, second sound, and phonon hydrodynamic phenomena in, (2) 84*f*.
of norsethite, $BaMg(CO_3)_2$, structure, comparison with dolomite, $CaMg(CO_3)_2$, (6) 221*e*.
nucleation and growth in gels, (4) 147*b*.
olivines, natural, structures, (8) 290*c*.
orthoferrites of rare earths, structure: III, of thulium orthoferrite, (5) 193*j*.
oxide, melt-grown, developments in, (7) 254*j*.
parawollastonite, structure, (6) 231*i*.
periclase, growth, effect of heating atmosphere, (7) 250*f*.
perovskite ferroelectric, introduction of oxygen vacancies in, P (5) 185*a*.
piezoelectric, growing, P (6) 225*c*.
- manufacturing apparatus, and X-ray diffraction method for location of atomic planes relative to crystal surface, P (9) 313*c*.
- temperature compensating unit for, P (4) 117*c*.

piezoelectric assemblies, P (4) 115*c*.
piezoelectric bismuth germanium oxide, $Bi_{12}GeO_{20}$, structure, (4) 130*c*.
Pt_2Ge_3, structure, (10) 351*j*.
Pt_2P_3, structure, (4) 130*d*.
plug, hydraulic permeability, variations in, (1) 40*b*.
poly-, overall strain, contribution of grain boundary sliding to, (1) 26*b*.
KBr, dislocation conduction and decoration in, (9) 320*e*.
KBr, NMR measurements of field gradients at Br nuclei surrounding substantial Cl ion in, (4) 146*f*.
KCl, exchange reaction with chlorine gas, (4) 136*a*.
KCl, melt grown, observation of dislocations in, by thermal etching, (10) 357*i*.
potassium manganate, structure, (4) 130*c*.
$KMnCl_3{\cdot}2H_2O$ and $K_2MnCl_4{\cdot}2H_2O$, structure, (8) 290*c*.
$KNbO_3$, ferroelectric, temperature dependence of absorption edge in, (1) 39*d*.
potassium permanganate, structure, (4) 130*c*.
potassium-strontium and potassium-lead niobates containing La, growth, (10) 351*h*.
$KTaO_3$-$KNbO_3$, mixed, hydrothermal growth, and material produced, P (7) 256*b*.
potassium tantalate niobate, growth from melt, P (6) 223*f*.
KTN, high resistivity, origin of lamellas in, (5) 198*a*.
production by vapor deposition, controlling feed of nuclei i.., P (4) 114*a*.

Crystals *(continued)*
- properties, of heavy metal halides and alkaline earth chalcogenides, (4) 130*f*.
- of proustite, and pyrargyrite, growth, optical quality, (9) 319*c*.
- and related compounds, Czochralski-grown, (9) 319*c*.
- smithite, and pyrargyrite, and system Ag_2S-As_2S_3, (2) 83*i*.

pulled, temperature distribution in, analysis, (7) 263*i*.
pulling, liquid encapsulation, at high pressures, (7) 255*d*.
pyrite, fine structure of faces, investigation by electron microscope, (4) 141*d*.
quartz, bonding leads to, P (11) 376*g*.
- grown in RbOH and other alkali hydroxides, hydrothermal synthesis, surface topography, and optical perfection, (7) 267*a*.
- growth, trapping colloidal inclusions in, (10) 363*b*.
- hydrothermal growth: III, effects of constraints, (4) 139*g*.
- internal structure and growth peculiarities, (4) 155*i*.
- synthetic, quality determination by neutron diffraction, (11) 379*i*.

rare-earth chlorides, anhydrous, structures, (9) 319*h*.
rare-earth compounds, growth, (8) 289*i*.
rare-earth sesquisulfides, monoclinic, preparation and structure, (11) 387*h*.
refractory, production by vapor transport reactions, (9) 328*f*.
Rh_2Si_3, structure, (10) 351*b*.
Rh_4Si_5, structure, and relation to other members of MnP structure family, (10) 351*c*.
ruby, electrical conductivity, (10) 352*c*.
rutile, flux-grown, dielectric measurements on, without contacting electrodes, (9) 310*g*.
rutile, TiO_{2-x}, nonstoichiometric, defect structure, (4) 156*g*.
sapphire, Czochralski, interface growth features, (7) 269*c*.
- electrical conductivity, (10) 352*c*.
- growth from melt, (7) 266*i*.
- high-strength, (2) 82*c*.
- sapphirine, structure, (9) 319*g*; (10) 351*d*.

semiconductor, of fibrous structure, P (8) 283*c*.
- habit and morphology, influence of solvent and impurities on, (8) 293*b*.
- potential distribution in, measurement with electron beam, (5) 187*c*.

shapes, with optically related surfaces, P (11) 377*c*.
shaping, by acid cutting, P (2) 68*b*.
SiAs, vapor grown, (4) 163*d*.
SiC, β-, solution growth, influence of carbon transport kinetics on, (4) 139*g*.
- β-, submicroscopic, with sheath of silica, for fibers, P (2) 58*f*.
- epitaxial growth by thermal reduction technique, (1) 29*h*.
- growth studies, (1) 30*j*.
- high-purity, preparation, trace impurities in, (2) 77*a*.
- polymorphism, (1) 35*a*.
- 33*T*, (1) 36*c*.

silver azide, growth and spectral characteristics, (5) 194*f*.
AgBr, epitaxial growth from melt and formation of oriented bubbles, (10) 353*c*.
AgI, structure, at 3 kbar, (4) 130*f*.
single, alkali halide, fluorometric microdetermination of thallium in: I, in sodium iodide, (6) 226*h*.
- alkali halide infrared spectra of borohydride ions in, (4) 140*g*.
- α-Al_2O_3, chemical polishing using silicon, (2) 75*c*.
- α-Al_2O_3, irradiation-induced macroscopic growth, (4) 141*h*.
- α-alumina, Mn-doped, formation from gas phase, (7) 265*j*.
- α-Al_2O_3, neutron-irradiated transmission electron microscopy, (4) 162*f*.
- α-alumina, ribbons, growing, P (5) 186*d*.
- Al_2O_3, defect diffusion in, (8) 290*i*.
- Al_2O_3, doped, influence of valence state of added impurity ions on observed color in, (9) 323*g*.
- Al_2O_3, neutron damage in, (1) 33*a*.
- AlP, vapor growth, (1) 40*a*.
- $BaO{\cdot}6Fe_2O_3$, ferromagnetic resonance in, (9) 321*d*.
- $BaSO_4$, growth by chemically reacted flux method, (7) 266*f*.
- $BaSO_4$, synthetic, etching of, (10) 353*i*.
- $BaTiO_3$, butterfly twin, and $BaTiO_3$ used in, P (2) 66*h*.
- $BaTiO_3$, effective mass of 180° domain wall in, (1) 28*e*.
- $BaTiO_3$, ESR of Mn^{2+} in, (1) 29*c*.
- $BaTiO_3$, reduced, electrical conduction in, (9) 320*i*.
- BeO, electrical transport processes in, (9) 321*c*.
- BeO, hydrothermal growth, (4) 139*e*.
- CdF_2, preparation and properties, (5) 199*a*.
- CdO, sublimation studies and preparation, (10) 361*d*.
- CdSe, growth by temperature gradient solution zoning in excess Se, (7) 266*f*.
- CdSe, quantity of low-frequency current noise in, (5) 199*h*.
- CdS, of controlled composition, growth from vapor phase, (10) 354*h*.
- CdS, growth, (10) 354*j*.

Crystals, single *(continued)*
- CdS layers, epitaxial growth on ZnS platelets, (10) 353*c*.
- CdS, pure, photoconductivity near band edge, (8) 296*h*.
- CdS:Cu, effects of growth conditions on microstructures in, (2) 76*g*.
- CdS:Cu and CdS:Au, annealed, direct observation of precipitate phenomena and dislocations in, (4) 131*i*.
- $Cd_{1-x}Zn_xS$, reflectivity spectra, (4) 153*g*.
- calcite, γ-irradiated, ESR absorption spectrum of AsO_2^{2-} molecule-ion in, (10) 353*a*.
- CaF_2, kinetics of hydrolysis from 1000° to 1120°C, (5) 196*e*.
- $CaNb_2O_6$, preparation by chemical transport, (7) 268*e*.
- of CaO, grown in plasma furnace, properties, (1) 20*e*.
- of chlorapatite, conversion into single crystals of hydroxyapatite, (4) 129*j*.
- CoO, electrical conductivity and thermogravimetric studies, (10) 352*f*.
- CoO, transmission electron microscopy and etch pitting of, (4) 121*j*.
- complex oxide, growth from fluoride melts, (8) 292*e*.
- compounds, anisotropy in: Vols. 1 and 2, B (7) 270*i*.
- constants, relationships of third order elastic constants of polycrystalline media to, (2) 84*j*.
- CuCl, growing with flux, (4) 144*h*.
- CuCl, growth, for optical modulators, (5) 194*d*.
- cupric molybdate, growth and properties, (7) 266*h*.
- Cu_2O, growth in SiO_2 gel at near ambient temperatures, (10) 354*j*.
- domain $LiNbO_3$, hydrothermal synthesis by transport reactions, (10) 355*g*.
- ferrite, P (4) 114*b*.
- ferroelectric polymorph, growth, system $PbNb_2O_6$ and its bearing on, (2) 83*j*.
- fracture-exposed surfaces, characteristics, (1) 25*g*.
- with Gd molybdate structure, P (7) 258*f*.
- GaSb, effects of back-melting on dislocation density in, (5) 194*a*.
- GaSb, growth by floating zone technique, (5) 181*f*.
- GaSb, prepared from nonstoichiometric melts, (1) 30*e*.
- GaP, growth from stoichiometric melt, (4) 137*i*.
- garnet, seeded growth from molten salts, (7) 259*b*.
- GeO_2, hexagonal, flux growth and characterization, (9) 321*h*.
- graphite, radiolytic oxidation, nature of active species, and *G* values, (9) 311*i*.
- growing, using differences in chemical potential, P (11) 378*h*.
- growth, microscopic rates determination, (4) 131*h*.
- growth, from nonstoichiometric melts, B (7) 272*h*.
- hematite, remanent magnetization, (1) 36*c*.
- high-melting points, growing, and apparatus for, P (4) 114*j*.
- of high-temperature oxides, growing, (2) 62*c*.
- of ice, γ-irradiated, ESR at 77°K—identification of hydroxyl radical and its trapping site, (5) 194*f*.
- ice, void formation during nonbasal glide in, under tension, (4) 163*f*.
- impurity distribution in: II, impurity striations in InSb as revealed by interference contrast microscopy, (1) 30*j*; III, impurity heterogeneities in single crystals rotated during pulling from melt, (4) 139*e*; IV, growth characteristics and impurity incorporation during facet growth, (10) 355*j*.
- indium antimonide, pulled from melt, microscopic rates of growth in, (4) 144*a*.
- inorganic, and polycrystalline electronic materials, preparation, P (6) 222*d*.
- inorganic, from reactions in fused salts, (8) 293*d*.
- Fe, oxidation at 350°C, (4) 148*c*.
- Fe-Ni oxide spinel, growth by arc image techniques, (6) 220*h*.
- α-Fe_2O_3, formation by hydrothermal treatment of α-FeOOH, (7) 266*b*.
- FeS_2, CoS_2, and NiS_2 pyrites, preparation by chlorine transport, (6) 236*e*.
- large of hydroxyapatite, efforts to grow, (7) 268*f*.
- PbO, electrical and optical properties, (1) 28*b*.
- PbO, tetragonal, hydrothermal growth and phase width, (8) 298*e*.
- lead sulfide, growth in silica gels at ambient temperatures, (7) 266*j*.
- $Pb_{1-x}Sn_xTe$, growth from nonstoichiometric melts, (9) 322*i*.
- of PbTe-SnTe, growth and characterization, (2) 77*d*.
- LiF, recovery of strain amplitude independent dislocation damping in, (1) 35*j*.
- Li metaniobate, stoichiometry, (9) 330*i*.
- $LiNbO_3$, optical phenomenon in, (2) 81*e*.
- $LiNbO_3$, piezoelectric and optical properties, (1) 34*d*.
- $MgAl_2O_4$ spinels, growth by traveling isotherm technique, (5) 188*d*.

Crystals, single *(continued)*
- $MgAl_2O_4$ spinel, large stoichiometric, growth and characterization, (10) 354*i*.
- MgO, heat treatment and deformation, (2) 78*a*.
- MgO, irradation damage and hardening in, after low neutron doses $<10^{18}nvt$ (>1MeV), (5) 196*a*.
- MgO, "mirror" absorption and fluorescence in, (1) 32*i*.
- Mn ferrite, ^{55}Mn NMR of Mn^{2+} ions located at B-sites in, (1) 32*j*.
- $Mn_{1+x}Fe_{2-x}O_4$, induced anistropy at low temperatures, (2) 78*f*.
- MnO, elastic moduli, (9) 320*h*.
- HgS and $Hg_3S_2Cl_2$, growth by vapor phase method, (5) 194*e*.
- mixed cation iron garnets, growth in ytterbium-gallium and yttrium-calcium silicate systems, (10) 354*i*.
- MoO_3, optical and photoelectric properties, (1) 34*b*.
- MO_2-$nM'O_2$ compounds (M = Si, Ge, Ti; M' = Zr, Hf, Ce, Th), comparison of structure, (9) 318*c*.
- natural, of hematite, stress-induced magnetic anisotropy in, (2) 83*h*.
- nickel manganite, growth, (6) 233*b*.
- NiO and MnO, magnetic anisotropy, (2) 79*f*.
- niobates, growth, for electrooptic and nonlinear applications, (6) 233*d*.
- Nb_2O_5, *B*-modification, ac polarization in, (10) 349*g*.
- nongarnet, growing garnet on, P (6) 221*d*.
- nonmetallics, method and apparatus for growing, P (8) 287*j*.
- of noselite [$Na_8SO_4Al_6Si_6O_{24}$], interpretation of superlattice, (9) 323*d*.
- oligoclase, annealing at high pressure, (10) 350*a*.
- KCl, valence distribution of radiophosphorus in: I, initial distribution; II, effect of thermal annealing, (9) 332*g*.
- KH_2PO_4, KD_2PO_4, and KH_2AsO_4, infrared absorption by hydrogen bonds in, (2) 79*b*.
- of KNb_3O_8, (4) 142*g*.
- KNO_3 and $CsNO_3$, EPR studies of VO^{2+} in, (8) 291*g*.
- $KTa_xNb_{1-x}O_3$, growth and electrical properties, (2) 77*g*.
- preparation for improved electron emission, P (6) 222*f*.
- rare-earth orthoferrites, Bi-substituted, preparation and magnetic properties, (10) 359*h*.
- rare-earth orthoferrites, flux-grown, lead substitution in, (8) 294*d*.
- rare-earth oxide, phase transition from monoclinic B- into hexagonal A-form in, (9) 323*f*.
- ruby, wear along plane close to basal plane, (6) 239*e*.
- ruby, wear along plane slightly inclined to basal plane, (4) 164*a*.
- rutile, reduction, (11) 387*b*.
- rutile, time-dependent electrical conduction in, (2) 84*a*.
- of semiconductors, homogeneous, synthesis and growth from solution, (7) 255*f*.
- Si, anodic passivation, (7) 263*j*.
- SiC, polytypism in, (4) 157*b*.
- Si rods, growth, P (9) 312*a*.
- SiP_2, orthorhombic, preparation, (10) 359*i*.
- silicon surfaces, chemically etched and thermally oxidized, surface areas and *c* values by krypton absorption, (1) 38*i*.
- AgCl, slightly bent, annealing, (9) 318*c*.
- of silver halides, growth in silica gels at near ambient temperatures, (7) 266*j*.
- silver iodide, growth in silica gel, (7) 266*a*.
- NaCl, cleavage surface covered by amorphous C layer, decoration by vacuum condensation of PbS, (6) 231*c*.
- NaCl, condensation coefficients of Au on, (4) 129*j*.
- NaCl, doped, precipitation hardening and dislocation locking in, (2) 81*j*.
- NaCl, latent hardening, work hardening, and plastic deformation, (2) 79*c*.
- NaCl, evaporation mechanism, (9) 330*e*.
- NaCl, manganese-doped, particle hardening in, (2) 81*j*.
- NaCl, vaporization rate, effect of dislocations, (2) 75*j*.
- spinel, defect structure and mechanical properties, (2) 75*j*.
- spinel, epitaxial growth of Ge on, (4) 135*c*.
- spinel, properties of epitaxial Si layers on, (5) 199*e*.
- $Sr_{1-x}Ba_xNb_2O_6$, tungsten bronze ferroelectric, growth and properties, (6) 233*c*.
- of SrCl2, ESR spectra of Er^{3+} and Yb^{3+} in, (6) 232*c*.
- of $SrTiO_3$, ESR of Fe^{3+} in, (1) 29*a*.
- $SrTiO_3$, growth from silica flux, (7) 266*b*.
- $SrTiO_3$, hydrogen and deuterium in, (9) 322*h*.
- of sulfides, selenides, and tellurides of metals of groups II and III of periodic system, growing, P (4) 115*h*.
- Tb and Ho ferrite garnets, magnetostriction at low temperatures, (2) 80*h*.
- SnO_2, weak-field magnetoresistance in, (10) 363*i*.
- TiO_2, growth by chemical transport with $TeCl_4$, (5) 194*e*.

Crystals, single *(continued)*
- TiN, oxidation kinetics by optical measurements, (11) 386*a*.
- transition metal oxides, growth by arc-transfer method, (4) 138*a*.
- transition metal silicide (CoSi) growth and characterization, (9) 322*b*.
- triglycine sulfate, thermal conductivity in phase transformation region, effect of constant electric field on, (4) 132*j*.
- WO_3 and MoO_3, vapor growth, (8) 300*e*.
- II-IV-V_2 semiconducting compounds, growth, (7) 255*a*.
- UO_2, relaxation processes in, (8) 297*j*.
- UO_2, yield and flow, (9) 333*a*.
- US, electron microscope studies: I, slip behavior; II, precipitation phenomena, (1) 28*f*.
- β-US_2, preparation and electrical resistance, (4) 150*j*.
- VO_2, epitaxial growth, and anisotropic properties in electrical resistivities, (10) 353*c*.
- VO_2, growth by isothermal flux-evaporation, (9) 329*f*.
- VO, epitaxial growth, and electrical properties, (2) 76*i*.
- V_2O_3, metallic, magnetic susceptibilities, (4) 143*i*.
- V_2O_3, optical properties, (5) 198*a*.
- vermiculite, proton magnetic resonance in, (6) 236*b*.
- YAG, optical quality, rare-earth activator ions in, (10) 355*a*.
- $Y_3Al_5O_{12}$, strain-free, growth, (7) 266*a*.
- yttrium-gadolinium-aluminum garnet, growth and laser characteristics, (9) 322*e*.
- YIG, growth, (7) 258*h*; (10) 354*j*.
- YIG, improvement in yield, (7) 255*b*.
- YIG, king size, growing, (2) 62*i*.
- ZnO, growth by vapor phase reaction method, (10) 354*c*.
- ZnO, Li-doped, electronic drift mobilities and space-charge-limited currents in, (9) 321*i*.
- ZnO, vapor phase growth, (6) 239*d*.
- ZnSe cathodoluminescence in scanning electron microscope studies, (5) 199*e*.
- ZnS, growth from melt at 1850°C under Ar pressure of 50 atm, (6) 233*c*.
- ZnTe, growth in Zn atmosphere, (7) 266*c*.
- of ZnTe and $ZnTe_{1-x}Se_x$, growth by temperature gradient solution zoning, (2) 77*h*.
- Zr-O_2 alloy, plastic deformation in range 77° to 950°K, (4) 149*i*.
- ZrB_2, growth and characterization, (9) 322*b*.
- small classical, entropy for, (8) 292*b*.
- small piezoelectric, resonating at low frequencies, method and apparatus, P (6) 222*b*.
- NaCl, containing cavities, work of fracture in, (2) 84*f*.
- containing silver colloids, thermal conductivity in, (1) 39*j*.
- dissolution kinetics at dislocation sites in, (6) 231*h*.
- with high concentration of copper, absorption and emission phenomena in, (6) 230*f*.
- movement of dislocations in, in electric field, (5) 197*h*.
- pure and Mn-doped, ionic conductivity in, (8) 293*j*.
- structure of cleavage surfaces around precipitates in, (1) 38*f*.
- structure, measure of ion overlap in, by strain polarizability constant, (6) 237*j*.
- structure, plastic behavior, (1) 34*g*.
- thermal diffusion of Sr ions in, (4) 160*e*.
- $NaH_3(SeO_3)_2$ and $NaD_3(SeO_3)_2$, ferroelectric, growth, (4) 137*i*.
- $NaIn(SiO_3)_2$, structure, (4) 130*h*.
- Na_2O·SiO_2·$6H_2O$ and isostructural Na_2O·GeO_2·$6H_2O$, structure, (7) 268*d*.
- $NaSi_2O_7$, structure, new type of silicate sheet, (4) 130*j*.
- sodium tin germanium oxide hydroxide, ordered structure, (4) 130*a*.
- spinel, β-Mn_3GeO_4, structure, (11) 386*e*.
- β-spodumene, structures, stereographic projection, (6) 237*j*.
- staurolite, structure, (9) 319*h*.
- stoichiometric spinel, detection of trace impurities in, by instrumental neutron activation analysis, (7) 254*h*.
- strontium copper akermanite, structure, distorted tetrahedra in, (6) 231*i*.
- structure, of adularia and refinement of structure of orthoclase, (5) 193*i*.
- alterations purposely produced, role in manufacture of ceramic products, (6) 220*j*.
- amarantite, (6) 231*g*.
- calculation of properties of vacancies and interstitials, B (9) 333*h*.
- of ceramic pigments, for classification, (2) 72*i*.
- effects, in adsorption of calcium sulfonate on $CaCO_3$, (1) 26*e*.
- of high-temperature phase PdS, (9) 319*f*.
- influence on luminescence, (8) 293*a*.
- in $(La,Gd)_2CoMnO_6$ system, (10) 356*g*.
- marcasite type, compounds with: I, compositions of binary pnictides; II, crystal structures of binary pnictides, (10) 350*g*.
- models of framework tetrahedra, inexpensive, (8) 285*e*.
- predetermined, P (10) 347*a*.
- refinements, of B 20 and monoclinic (CoGe-type) polymorphs of FeGe, (4) 130*d*.

Crystals, structure *(continued)*
sectorial, grown from melt, regularity in, (4) 153*h*.
of sheet silicates, (9) 317*h*.
in Ti-P system, (4) 156*g*.
of transition-metal molybdates and tungstates: IV paramagnetic $CuMoO_4$, (4) 130*e*; V, paramagnetic $Nd_2(MoO_4)_3$, (10) 351*e*.
Vol. 4, miscellaneous inorganic compounds, silicates, and basic structural information, B (7) 271*j*.
surface specific heat, at low temperatures, lattice-dynamical calculation, (2) 79*d*.
surfaces, structure, (1) 38*h*.
symmetry, of interface charge distribution in thermally oxidized silicon, (4) 158*i*.
synthetic spinel, study with scanning electron microscope, (8) 298*j*.
with SnI_4 structure, theoretical morphology, (7) 270*h*.
tin oxide, electrical and optical properties, (10) 362*g*.
Sn_4P_3, structure, (4) 130*d*.
twinning, mechanical, and crack nucleation in lithium niobate, (9) 324*b*.
UO_2, grown by solar furnace, (7) 270*e*.
vermiculite, hydrated, restricted anisotropic diffusion and anisotropic nuclear spin relaxation of protons in, (5) 199*c*.
verneuil, uncommon, growth and characteristics by light scattering, (9) 322*b*.
whiskers, B_4C, catalyst for growth, P (5) 178*d*.
whisker, grown from solder terminations in electrotransport process, (5) 203*g*.
X-ray diffraction in, apparatus and process for eliminating preferred orientation in, P (4) 121*d*.
yttrium aluminate, production, P (4) 125*a*.
yttrium aluminum oxide garnet, production, P (6) 222*g*.
of Y_2O_3 and ZnS, hydrothermal growth, (9) 322*i*.
zeolite, LiX and NaX, adsorption of krypton, and xenon by, dependence on pressure and temperature, (4) 131*c*.
ZnO_2 and BeO, structure of paramagnetic lithium center in, (9) 330*c*.
-Cu, photoconductive effect, (9) 327*e*.
Mn(II)-doped, paramagnetic resonance, (9) 326*a*.
maximum efficiency transverse wave, P (7) 258*e*.
morphology and polarity, (8) 295*j*.
photoconductivity decay in oxygen, (4) 149*f*.
semiconductor, magnetic susceptibility, (4) 143*j*.
ZnSe, growth and properties, by chemical transport, (9) 322*a*.
ZnS, CdS, and ZnO, hexagonal, spontaneous polarization, (8) 292*c*.
cubic, molten flux growth, (10) 357*a*.
dendritic growth, (6) 231*e*.
growth from vapor, distribution of stacking faults in, (11) 383*j*.
ZnSe, ZnTe, GaS, $GaSe_3$, and InS, synthesis and growth in Ga and In melts, (6) 238*g*.
ZnS_xSe_{1-x} mixed, optical phonons in, (4) 147*j*.
ZrB_2, structure and orientation of second phase in, (5) 200*i*.
Curing, continuously, resistor elements, P (11) 377*h*.
instant, of coating, (5) 189*d*.
of refractory ceramic, by addition of exothermic compound, (5) 190*b*.
steam-, of concrete, optimum period for, investigated by ultrasonic methods, (8) 274*d*.
Curium, Cm^{3+}, zero-field splittings, in cubic symmetry sites in CaF_2, (4) 164*c*.
trivalent, ground-state splitting, in $ZrSiO_4$, $HfSiO_4$, and $ThSiO_4$, determined by ESR, (11) 385*c*.
Currents, through AlN thin films, (9) 319*a*.
space-charge-limited, in Li-doped ZnO, (9) 321*i*.
thermally released, in glasses damaged by ultraviolet radiation, (4) 96*c*.
thermally stimulated, in rutile, (6) 239*g*.
Cutting, grinding, and polishing ornamental stone, P (9) 314*g*.
method, for brick and tile, P (11) 372*g*.
Cutting tools. See *Tools.*
Cyclones. See *Classifiers; Separators.*

Damping, ratios, in glass fiber-reinforced composites, (2) 48*h*.
strain amplitude independent dislocation, recovery in single crystal LiF, (1) 35*j*.
Data storage, devices, P (7) 256*c*.
electron beam charge device, P (11) 376*d*.
memories, cryoelectric, P (9) 312*d*.
memory, thin film nondestructive, P (9) 314*b*.
memory apparatus, P (11) 377*j*.
memory core, high speed, in computer, (4) 110*i*.
memory device, ceramic ferroelectric, P (11) 376*i*.
glassy bistable electrical switching and, P (7) 256*j*.
matrix-type permanent, P (11) 377*d*.
piezoelectric, P (9) 312*d*.
memory element, multiremanence ferroelectric ceramic, P (6) 222*j*.
with stacked magnetic layers, P (11) 377*e*.
with two orthogonally disposed magnetic films, P (11) 377*e*.
Data storage, memory element *(continued)*
variable threshold FET, charge storage model for, (9) 310*b*.
memory system, ferriresonant, P (11) 376*f*.
solid state device, P (11) 379*a*.
Dealkalization, of soda-lime-silica glasses, (1) 9*h*.
surface, effect on mechanical, chemical, and electrical properties of glass, (10) 337*h*.
Debye-Waller factor, of tetragonal $BaTiO_3$, (8) 290*g*.
Decals. See *Decoration.*
Decay, thermal, of *V'* center in MgO, (9) 331*g*.
Decomposition, alkaline, of ilmenites containing Cr, (7) 261*j*.
of aluminate solutions, induction period during, (1) 30*j*.
of brucite, mechanism, (4) 143*h*.
dehydration, mechanism, of formic acid over Al_2O_3 and SiO_2, adsorption measurements during catalytic reaction, (8) 295*a*.
of dolomite, for manufacture of Mg oxychloride, cement, catalytic action of NaCl on, (2) 43*i*.
electron or laser-beam, of inorganic metallic compounds for production of electrically conductive tracks: I, oxide systems, (8) 281*e*.
eutectoid, of $CuFe_2O_4$-Fe_3O_4 spinel solid solution including $CuFe_2O_4$, (9) 321*a*.
high-pressure, of titanate spinels, (4) 138*j*.
hydrofluoric acid, technique, for analysis of inorganic silicious materials: IV, of cements, clinkers, raw mixes, and siliceous limestones, (8) 284*i*.
of NiO, (4) 130*g*.
phase, diffusion stage, in solutions and glasses, (10) 362*a*.
phase, fluctuation stage, in solutions and glasses, (2) 52*a*.
products of modified ilmenite treated with sulfuric acid, water extraction of, (7) 262*c*.
rate, of aluminate solutions, influence of radiations, (1) 31*a*.
of sands and quartzites by formaldehyde-volatilization method, (5) 187*g*.
spinodal, (1) 37*h*.
for nonclassical nucleation theory and phase separation, (1) 33*e*.
in soda-silica glass, (8) 276*g*.
structural, of orthochlorite during acid dissolution, (1) 38*c*.
thermal, of alkali metal silicates, inhibiting, P (4) 124*c*.
of aluminum sulfate: Al-S-O system from 850° to 1050°K, thermodynamics of, (4) 162*c*.
of aluminum sulfate, thermodynamics of, (4) 162*b*.
of ammonium metavanadate, (8) 300*d*.
of ammonium molybdoselenite, (4) 160*i*.
of boehmite, fibrillar synthetic, (7) 262*b*.
of calcium carbonate, influence of dislocations, (4) 139*i*.
of crocidolite, (2) 84*f*; kinetics and mechanism, (4) 142*f*.
of fluorspar by water vapor, (6) 239*b*.
high-temperature, of apatitic phosphates, (6) 233*j*.
of α-FeOOH prepared by different methods, (9) 324*d*.
of iron(II), cobalt(II), and nickel(II) hydroxides, (1) 39*a*.
kinetics, of kaolinite, (6) 234*d*.
kinetics and mechanism: II, temperature and vapor pressure dependence of dehydroxylation of serpentine, (4) 142*g*.
of metal chlorates, kinetic and derivatographic study, (5) 201*j*.
of nickel malonate, (9) 331*i*.
of orthotelluric acid, (5) 182*c*.
of oxalates: V, nickel oxalate dihydrate; VI, and surface properties of ferric oxalate; VII, effect of prior dehydration conditions upon subsequent decomposition of cobalt oxalate, (1) 39*a*; VIII, of Al oxalate; IX, of oxalate complexes of iron, (4) 160*j*.
of potassium hexafluorotitanate, (8) 300*e*.
produced by fracture in brittle crystalline solids, (9) 320*c*.
of pyrite in fluidized bed, (4) 160*b*.
of solid orthohombic ammonium perchlorate, effects of X- and γ-ray radiation: I, experimental and results; II, kinetics and discussion, (8) 291*a*.
of TaO_2F, (4) 156*j*.
of tricalcium aluminate hexahydrate, (2) 44*c*.
two-stage, of solids: II, effects of inert materials, (5) 170*i*.
of uranium(IV) and uranyl(IV) formates, (5) 201*d*.
of β-UO_3·$2H_2O$ produced from γ-UO_3, (5) 194*j*.
of $UOCl_2$ dissolved in molten UCl_4, for preparation of crystalline UO_2, (10) 359*e*.
of uranyl(VI) oxalate, (5) 201*e*.
of yttrium hydroxide in nitrogen stream, (8) 296*e*.
of Zr compounds in presence of Al hydroxides, (6) 239*c*.
voltage, of Na_2O-SiO_2 system, measurements at elevated temperature by commutator technique, (1) 7*g*.
Decoration. See also *Art and artware; Color; Engobes; Glazes.*
brush and sgraffito, (7) 244*b*.
Decoration *(continued)*
ceramic, corrosion during machine washing, (1) 15*g*.
of ceramic artware, —glass, porcelain, and faience, precis of, B (8) 302*h*.
clay in-lay, by Parshall and Chasek, (7) 244*b*.
decalcomania, vitreous, applying, P (7) 249*e*; P (8) 277*h*.
glass, automating operation, (1) 5*i*.
electrical printing methods and apparatus for cylindrical articles, P (11) 371*f*.
inorganic vs organic colors for, (1) 7*c*.
organic, (2) 50*j*.
with organic coatings, (2) 50*f*.
of glass articles, stencil screen for, P (5) 176*b*.
of glass bottles, rotary screen decorating machine for, P (5) 176*a*.
of glass bottles, soft drink, (5) 172*i*.
of glass-ceramic substrates, P (4) 98*g*.
offset plate, and apparatus, P (2) 53*j*.
with plastic foam, (7) 244*d*.
of plates, with banding machines, possibilities and problems, (4) 108*i*.
of plates, possibilities and problems with edging machines, (7) 254*b*.
porcelain, change during maching washing, optical evaluation, (11) 375*f*.
porcelain, wear in industrial and domestic dish washers, (1) 15*h*.
pottery, ceramic colors and, B (10) 364*h*.
reverse motif, (6) 206*b*.
screen, with thick coating to define image, electrical printing apparatus, P (8) 277*h*.
screen printing, mechanical details, (7) 259*c*.
slip trailer, from moisture-proof paper, (10) 335*j*.
of ware at Metlox, (2) 60*i*.
wax resist and glaze, (7) 244*f*.
De-enameling. See *Enameling.*
Defects. See also *Crystals; Enameling; Enamels; Glass; Structure.*
in alkali halides, ultramicroscopic study, (8) 300*b*.
complex, in CoO, (11) 383*h*.
concentrations, across *p*-type oxide layer on metal, (2) 75*f*.
gas, in minerals, analysis, and method of progressive heating, (1) 25*g*.
irradiation, in graphite and self-diffusion mechanism, thermal annealing studies, (9) 331*c*.
optical, in barium sodium niobate, (8) 298*c*.
optical, regularity in bent glass plates, (5) 173*h*.
paraelectric, in alkali halides, symmetry, (2) 83*d*.
paramagnetic, associated with hydrogen adsorbed on surface of MgO and CaO, (5) 198*e*.
partially ordered, in hypostoichiometric metal oxide, statistical model, (10) 360*j*.
partially ordered, in UO_{2+x}, statistical model, (9) 330*f*.
point, in ceramics, (8) 296*i*.
in crystalline solids, (4) 150*c*.
in molybdenite surfaces, identification and properties, (5) 195*i*.
radiation-induced, in BeO, observation by long-wavelength neutron-scattering measurements, (4) 147*d*.
Schottky, energy of formation, in cesium halides, (1) 29*f*.
energy of formation in ionic crystals, (1) 29*g*.
formation and kinetics of dissolution of precipitates containing divalent cation impurities in alkali halides, (8) 297*c*.
and stains, effect on electrical properties of mica, (5) 190*d*.
stress induced, in vitreous calcium aluminates, (1) 38*a*.
symmetry properties, studied by uniaxial stress spectroscopy, (8) 299*f*.
texture, influence on properties of electrical ceramics, (1) 16*j*.
in thin film capacitors, techniques for charting and removing, P (2) 66*i*.
Deflocculation. See *Dispersion.*
Deformation, of anodic oxide films, (2) 75*c*.
in aqueous dispersions of montmorillonite, effect of Na humus on structure formation and mechanism of development of, (7) 262*d*.
behavior, of ceramic materials, (6) 231*d*.
in bend of periclase-silicate mixtures at high temperatures, effect of composition and microstructure, (6) 215*b*.
compensated tetragonal, in spinels $Cu_{0.5}Mn_xFe_{2.5-x}O_{4+\gamma}$, (7) 264*j*.
compressive, effect of plastic instability on, (6) 226*f*.
elastic, remanent and transitory effects, of magnetite crystals, (4) 153*j*.
indentation, of nonmetallic solids, effect of adsorption, (4) 133*b*.
low-temperature, of silica glass, (4) 96*b*.
of MgO single crystals, (2) 78*a*.
nonlinear Hertzian, and gage length, effect on measurement of elastic energy release rate, (5) 193*i*.
plastic, of CaF_2, role of grain boundaries in, (2) 82*e*.
of cube-oriented MgO crystals under pressure, (8) 290*i*.
of electrodeposited coating for preparing hermetic metal-ceramic joints, (2) 62*j*.
of glass with diamond indenters, (6) 211*a*.
of halide crystals, influence of color centers, (2) 78*j*.

Deformation, plastic *(continued)*
in magnesium aluminate spinel, (8) 296*h*.
of NaCl single crystals, (2) 79*c*.
of upper mantle silicate materials, B (6) 241*c*.
of Zr-O_2 alloy single crystals in range 77° to 950°K, (4) 149*i*.
in KCl, (8) 292*e*.
of refractories, (6) 214*i*.
and strength characteristics of anisotropically consolidated kaolinite clay, (5) 190*a*.
studies, of UN by electron microscopy, (1) 33*j*.
tetragonal, Jahn-Teller type, in spinels of $MgGa_{2-x}Mn_xO_4$ and $MgCr_{2-x}Mn_xO_4$, X-ray and neutron diffraction study, (10) 363*g*.
Degassing, outgassing, of Al_2O_3 and BeO in vacuum at 540° and 870°C, (6) 220*h*.
in oxygen-niobium system at very low pressure, (4) 126*e*.
Dehumidifiers. See *Dryers*.
Dehydration, of clay minerals, energy changes in, (7) 265*c*.
of clay minerals under N_2 reduced pressure by differential thermal analysis, (7) 264*j*.
of $Mg(OH)_2$, (1) 26*h*.
of porous glass, (4) 95*e*.
process, of calcium sulfate dihydrate, (5) 170*d*.
products, of aluminum hydroxides, (4) 130*h*.
Dehydroxylation. See *Decomposition, thermal*.
Delay line, integrated ultrasonic, made of $BaTiO_3$ ceramics, (4) 110*a*.
nondispersive electrically variable microwave acoustic, comprising ferrite Faraday rotator coupled to anisotropic piezoelectric crystal, P (6) 223*b*.
YIG, optical probing of magnetostatic modes in, (4) 147*j*.
Densification, of alumina ceramics, (4) 131*a*.
of alumina by hot-pressing, (4) 131*b*.
of boride compositions, P (7) 252*i*.
of ceramics, cermets, and composites, by high energy-rate forming, (4) 117*h*.
of ferric oxide and ferrites containing Bi_2O_3 additions, (10) 343*j*.
high-pressure, of α-Al_2O_3 and MgO powders, (11) 373*e*.
mechanisms, in high-pressure hot-pressing of HfB_2, (4) 131*b*.
of oxides, effect of impurities, (4) 132*i*.
in powder metallurgy, by isostatic hot-pressing, (4) 117*g*.
process, theoretical consideration, associated with sintering under applied pressure, (4) 160*c*.
role in deformation of glasses under point loading, comments and reply, (7) 247*a*.
of silica glass, effect of impurities, (7) 247*f*.
of TaN-ZrB_2, (8) 278*j*.
Density, of Al_2O_3 and MgO, effect of low temperature neutron irradiation and 20°-400°C annealing on, (4) 133*a*.
apparent, determination, of rough porous matter, (5) 187*d*.
of boronated graphite, (4) 143*c*.
bulk, of soda ash, increasing by adding Ca and Mg ions prior to precipitation, P (11) 382*b*.
of cohesive materials, correlation with modulus of compressibility, (5) 189*h*.
determinations, accuracy and application to sphalerite stoichiometry, (10) 347*c*.
of glasses, effects of water content on, (6) 209*i*.
as function of thermal history, (9) 305*f*.
measurement at high temperatures, (6) 210*a*.
in system Na_2O-MgO-SiO_2, dependence on composition, (2) 47*c*.
green, relations with shrinkage for ceramic mold design, (9) 314*f*.
of iron oxide melt in equilibrium with CO_2-CO gas mixture, (8) 290*j*.
measurements on UO_2 and UC samples irradiated at low temperatures, (8) 290*a*.
meter, vibrating spool fluid, (11) 381*d*.
in molten BeF_2-LiF solutions, (10) 338*d*.
of molten salts, (7) 262*f*; B (10) 365*f*.
of oxide refractory samples, mercury pycnometer for precise determination, (7) 260*h*.
packing, of binary mixtures of granular abrasive materials, (1) 1*i*.
and particle size, of fine powders, (4) 148*h*.
powder, measurement by hydrostatic weighing, (8) 285*i*.
relation with state of order in plagioclase from anorthosite rocks, (9) 328*i*.
soil, measurements, reliability of using nuclear methods for different soils, (5) 188*a*.
space charge, of ZnO electrophotographic layers, effect of electric field, (5) 180*i*.
vacancy, cation, in Mn-Zn ferrites, (1) 25*c*.
Dental ceramics, artificial constructions, noble metal alloy adapted to receive, P (4) 109*b*.
artificial tooth, P (8) 280*e*; P (9) 309*j*.
composite artificial tooth, P (5) 179*b*.
dentrifice compositions comprising zirconium silicate of particular particle size, P (10) 335*h*.
furnace for, P (7) 261*i*.
materials, wettability and adhesiveness, (6) 220*a*.
molds, or molding material, method and package for producing, P (2) 61*a*.
porcelain and resin tooth with silicon bonding agent, P (5) 179*d*.
prosthesis, cast porcelain, P (1) 15*j*.
tooth structure with means for chemically
Dental ceramics *(continued)*
bonding diverse materials together, P (5) 180*d*.
Deposition, of Al_2O_3 films obtained by pyrolytic decomposition of aluminum alkoxide, (4) 131*d*.
of carbon, massive pyrolytic, P (1) 13*h*.
chemical vapor, of oxide and glass films, apparatus for, (8) 280*j*.
chemical vapor, of TiC coatings on iron, (4) 93*c*.
co-, of boron containing coatings, P (11) 369*c*.
electro-, of magnetic thin films, P (2) 64*c*.
for porcelain enamels, (7) 246*h*.
for WC preparation, (8) 286*i*.
epitaxial, or diffusion processes employing SiC masking layer, P (9) 313*c*.
of GaAs in argon atmosphere, (4) 135*c*.
of GaAs from atmosphere of hydrogen and Ga_2H_6+$AsCl_3$+AsH_3 vapors, P (2) 64*d*.
of GaAs and $GaAs_{1-x}P_x$, multiwafer growth system for, (9) 311*b*.
of GaAs in holes, (2) 82*j*.
on one side of substrate with simultaneous vapor etching on opposite side, P (6) 223*h*.
wherein spent reaction gases are added to fresh reaction gas as viscosity-increasing component, P (8) 282*f*.
of evaporated carbon, effect of substrate structure, (4) 110*c*.
of kaolinite suspensions, (9) 329*a*.
metal boride-metal carbide-graphite, P (11) 377*f*.
modern evaporite, of coexisting brines, The Sabkha, Trucial Coast, Arabian Gulf, (8) 286*h*.
of $NbaSn$, P (5) 182*b*.
pyrolytic, of SiC, P (4) 107*e*.
pyrolytic, of SiO_2 films in evacuated system, (9) 322*a*.
of pyrolytic graphite, P (8) 279*e*.
of pyrolytic material, P (10) 344*f*; P (11) 379*e*.
sputter-, processes for forming Schottky-barrier diode, P (9) 313*f*.
selective, method and article for use in, P (2) 66*a*.
selective, of semiconductor materials, P (2) 66*b*.
of SiO_2 films by glow discharge technique, (2) 75*c*.
of silicon films on single-crystal spinel substrates, (4) 131*d*.
of SiN films by silane-hydrazine process, (4) 109*g*.
of silicon oxide, closed tube apparatus for, (1) 20*j*.
of thin film circuits, large area, bakeable vacuum evaporator for, (1) 20*i*.
of thin films, new binary oxide, by pyrolytic decomposition of trimethylsiloxy-aluminum-isopropoxide, (5) 190*a*.
vacuum, on negatively biased substrate, apparatus for, P (6) 220*h*.
vapor, apparatus, P (9) 314*d*.
apparatus including orbital substrate support, P (10) 346*c*.
controlling feed of nuclei in production of crystals by, P (4) 114*a*.
for formation of B and B_4C coatings, (1) 4*b*.
for formation of carbide compounds on graphite bodies, P (11) 374*i*.
of glass particles on entire exposed surface of object, P (7) 257*c*.
metal, in fluidized bed and hot-pressing for preparation of UO_2-Mo and UO_2-W cermets fuel, (1) 12*g*.
of superconducting metallic film, P (7) 257*d*.
vacuum, (4) 118*g*.
Design. See also *Art and artware; Decoration*.
ceramic-collar insulator, wins award, (9) 303*h*.
of glass ovenware, (4) 90*i*.
influence, in ceramic tile industry, (6) 206*d*.
practical and impractical, (7) 244*f*.
shapes, cut-out, for enameled wall pieces, (7) 244*e*.
show, west coast premiere, (5) 176*b*.
trademark seals on glass from 17th century A.D., (6) 206*e*.
Desorption, and exchange of octadecylamine and stearic acid on steel and glass, (1) 27*c*.
ion impact, of hydrogen from glass, (5) 173*a*.
thermal, of stearic acid monolayers from mica and silver, (1) 39*b*.
water, effects on indentation microhardness anisotropy in minerals, (8) 285*a*.
water, from rutile surface, kinetics, (1) 31*d*.
Detectors. See also *Tubes, electron*.
Be doped Ge photoconductive, P (10) 344*b*.
compact radiation, with superimposed filter, phosphor, glass, and photosensitive layers, P (5) 182*a*.
for filter cake buildup, P (6) 225*b*.
flame ionization, P (1) 22*b*; P (4) 121*g*.
Ge(Li), for neutron activation analysis of Dy in rock samples, determination after chemical separation, (1) 21*i*.
infrared, employing single crystal Te or Se, P (4) 113*d*.
infrared ray, using ferroelectric single crystal, P (10) 345*b*.
laser small-particle, P (2) 71*j*.
neutron, with radioactive vanadium emitter, P (1) 18*g*.
np- and *pn*-type semiconductor, with pulse
Detectors *(continued)*
shape discrimination, investigation of signal shape given by, (5) 195*g*.
photo-, P (10) 345*e*.
photo-, high gain Si, P (7) 256*a*.
pyroelectric radiation, providing compensation for environmental temperature changes, P (10) 345*h*.
radiation, with semiconductor body, P (10) 345*i*.
scintillation, using single crystal of GaAs, P (4) 116*j*.
semiconductor, with lithium compensated shelf region between opposite conductivity type regions, P (4) 116*b*.
semiconductor, for rapid and nondestructive fast-neutron activation analysis for elements, (9) 315*j*.
semiconductor nuclear particle, producing by diffusing, P (4) 115*h*.
semiconductor radiation, extended area, and novel readout arrangement, P (4) 113*a*.
semiconductor radiation, lithium drifted, P (4) 113*i*.
surface-barrier, effects of oxidation, (5) 180*g*.
temperature, P (4) 117*d*.
thin film atomic hydrogen, (2) 71*f*.
thin window drifted silicon charged particle, P (5) 185*g*.
ultrafast optical coincidence, P (8) 284*c*.
Deuterium, oxide vapor, laser emission from, (8) 295*d*.
permeation, diffusion, and solubility, in Pyrex glass, (6) 210*h*.
selective deuteration for study of hydroxyl groups in kaolin minerals, (7) 269*e*.
Diamonds, abraded surfaces, strains in, (1) 38*a*.
in abrasive wheels. See *Grinding apparatus*.
bits, P (10) 335*f*.
covalent bonding in, X-ray studies, (5) 203*b*.
crystals, P (7) 243*h*.
filamentary, (7) 265*i*.
natural, of cube form, structure studies, (1) 38*c*.
synthetic, P (8) 273*g*.
direct absorption edge, fine structure in, (2) 77*e*.
dodecahedral form, studies, (7) 269*c*.
electric-field-induced infrared absorption in, (2) 76*h*.
energy bands in, (4) 135*h*.
gold mine, study, (8) 287*b*.
growing on diamond seed crystal, P (5) 186*c*.
growth, nucleation in, (2) 77*c*.
lonsdaleite, hexagonal polymorph of, (4) 143*a*.
optical absorption of neutral vacancy in, (10) 357*j*.
origin, in drift of north Central United States, (4) 147*i*.
particles, sintering process, P (1) 1*j*.
preparation, high pressure reaction vessel for, P (2) 67*j*.
production by conversion of carbonaceous material, P (10) 335*f*.
reclamation, (11) 367*f*.
refractive index, variation with hydrostatic pressure to 7 kbars, (9) 332*i*.
semiconducting, thermoluminescence, (2) 84*i*.
structures and properties, (1) 23*d*.
synthesizing, P (1) 20*f*.
synthetic, preparation by using direct electric current for heating, P (7) 243*i*.
trigons on, (1) 40*c*.
type Ia, reciprocal lattice spikes in, (4) 153*e*.
Dicalcium silicate. See *Calcium*.
Dielectrics. See also *Ferrites; Ferroelectricity; Ferroelectric materials; Ferromagnetism; Ferromagnetic materials; Glass; Porcelain, electrical; Steatite; Titanates; Whiteware*.
behavior, of benzene on SiO_2 gel, (10) 360*f*.
in borax, (4) 131*a*.
of water adsorbed by partially dehydrated K Cr alum, (9) 319*i*.
ceramic, P (4) 112*g*; P (5) 182*j*; P (6) 220*j*; P (7) 255*j*.
high-quality, sintered in reducing atmosphere, (2) 62*g*.
raw powders, granulation and forming, (6) 220*f*.
for temperature compensating electric condensers, P (1) 17*j*.
complex high-permittivity, aging with ac, dc, and zero fields of, (2) 62*c*.
constant, control of temperature coefficient in glass-ceramic materials by doping, (1) 6*b*.
in fine-grained $BaTiO_3$, internal field theory of, (2) 79*f*.
of ionic solids, and change with hydrostatic pressure, (1) 27*h*.
of $PbMoO_4$ and $CaMoO_4$, (4) 131*a*.
measurement means and method using frequency sweep and fixed probe, P (1) 18*d*.
microwave, of Al_2O_3 at 375 kbars, (9) 311*a*.
microwave, of GaAs lattice, temperature dependence of, (4) 159*b*.
of silicate glasses, calculating temperature-frequency change of, (2) 50*d*.
ionic thermocurrents in, (2) 79*h*.
losses, control of by doping in glass-ceramic materials, (1) 6*b*.
method, use in study of chemical inhomogeneities in sodium borosilicate glasses, (10) 338*c*.
in system $PbaMgNb_2O_9$-$PbaNiNb_2O_9$, (5) 180*g*.
measurements, on flux-grown crystals of rutile without contacting electrodes, (9) 310*g*.

Dielectrics (continued)
measurements, of proton mobility in boehmite, (8) 296*j*.
metal-, systems, thin-film, conductivity, (9) 310*c*.
multilayer laser mirrors, effect of laser radiation on properties, (8) 281*c*.
polycrystalline ZnO, (4) 111*a*.
properties, of alumina, hot-pressed, (1) 27*h*.
of $BaTiO_3$ fine particles, (4) 131*b*.
of $BaTiO_3$, influence of microstructures, (10) 344*f*.
of $BaTiO_3$, melt-grown, (10) 352*b*.
of commercial alumina materials at 9368 MHz, (2) 62*g*.
of Nb_2O_5 crystals, (10) 359*f*.
of refractory low-loss ceramics, transient effects of nuclear radiation at microwave frequencies, (9) 311*h*.
of sample, nondestructive measurement by electron beam, P (9) 315*i*.
of Na-Li niobate solid solution ceramics with small Li concentrations, (1) 17*j*.
of thin films of Al_2O_3 and SiO_2, (8) 281*a*.
of titanate-Al_2O_3 ceramics, (8) 281*b*.
study, of $A_2Sn_2O_7$ stannates, (2) 82*f*.
thin film capacitor, selection, (8) 281*f*.
Dies. See also *Extrusion*.
fireable ceramic, tapered hollow dowels for, and method for use, P (10) 343*g*.
geometry, effects on extrusion of claylike material, (6) 224*i*.
improved, for making glass headers, (5) 172*i*.
liquid, for forming metals, P (4) 94*b*.
Differential thermal analysis. See *Thermal analysis*.
Diffraction. See also *Electron diffraction; Neutrons; X rays*.
multiple, effect on determination of electron density distributions, (11) 384*g*.
patterns, powder, for cubic materials, indexing, (11) 385*g*.
Diffractometers. See *electron diffraction; X rays*.
Diffractometry, powder, variance and other measures of line broadening in; II, particle size determination, (9) 315*f*.
Diffusion, anionic, of KBr, measurement by isotopic exchange, (8) 294*g*.
anistropy, in rutile, (10) 349*j*.
anomalies, in thin metallic films, (10) 343*h*.
anomalous, of Ni in single crystals of PbSe at 700°C, (4) 126*f*.
barium in MgO, (1) 27*j*.
C, in single-crystal graphite, (10) 352*d*.
in TaC, (8) 290*h*.
and U in UC, (10) 352*e*.
cation, in Mn-Zn ferrites, coefficients and vacancy densities, (1) 25*c*.
cation, in UO_{2+x} and ThO_2 using α-ray spectrometry, (8) 298*f*.
coefficient measurements, effects of short-circuiting paths on, (7) 265*a*.
coefficients, across *p*-type oxide layer on metal, (2) 75*f*.
grain-boundary, surface, and volume, obtained from sintering data, (9) 325*d*.
from light scattering in glass, (5) 172*i*.
decorated paths in quartz, (9) 319*d*.
diffusional interaction in ion-exchange membrane, (11) 383*g*.
diffusional release of tritium from irradiated beryllium oxide, (4) 131*f*.
dissociative, of Ni in Si and self-diffusion of Si, (4) 131*j*.
effects of ultrasonics, (4) 157*f*.
electron, in ferrites, direct check by microwave technique, (1) 16*h*.
of gases in transition region, effects of structures of porous solids, (4) 133*g*.
grain boundary, and dislocation in growth of α-Fe_2O_3 whiskers and twinned platelets peculiar to gaseous oxidation, (9) 320*f*.
hydrogen, P (4) 109*c*.
rate, in room-temperature irradiated quartz, (5) 199*i*.
in thorium hydrides, activation energies for, (4) 126*d*.
impurity-delayed, (1) 30*i*.
inert gas, in α-Al_2O_3, high-resolution measurements, (8) 293*c*.
inert-gas, as probe for lattice defects in ionic crystals, (8) 293*j*.
ion, into fused silica from molten salts, (5) 195*j*.
ionic, of single-alkali glasses, (2) 49*j*.
iron, in single-crystal NiO, (4) 131*d*.
iron oxide, into MgO single crystals in reducing atmosphere, (1) 27*j*.
isothermal, of Sr and Co ions in pure NaCl crystals and reconsiderations of Soret effect, (10) 356*c*.
lattice and grain-boundary, of protactinium in ThO_2 and in ThO_2-UO_2 solid solution, (5) 196*i*.
lattice and grain boundary, of U in ThO_2 and ThO_2-UO_2 solid solutions, (8) 294*c*.
lead ions, in purified NaCl crystals, (4) 131*e*.
in lithium borate glasses, NMR studies, (1) 8*a*.
measurements, of proton mobility in boehmite, (8) 296*i*.
Ni and Cl$_2$ into *p*-type PbTe at 700°C, (10) 352*g*.
in oxides, (1) 27*a*.
oxygen, in CoO as measured by proton activation of ^{18}O, (8) 295*h*.
in Gd_2O_3, (10) 358*g*.
in growing ZrO_2 films, (10) 352*g*.
Diffusion, oxygen *(continued)*
in hypostoichiometric Zr oxide in temperature range 875°-1050°C, (4) 148*j*.
in monoclinic ZrO_2, (5) 198*d*.
in monocrystalline rare earth oxides, (1) 27*b*.
in near-stoichiometric α-Nb_2O_5, (4) 131*e*.
in UO_2 at high temperatures, (10) 361*b*.
paths in quartz, (10) 352*h*.
paths, short-circuit, in NiO films, (1) 33*h*.
phenomena, in glass, study by X-ray fluorescence contact radiographic method, (2) 46*g*.
potential in silicate systems with unipolar conductivity, evaluation, (2) 48*j*.
processes during uptake of excess Ca by calcium fluoride, (10) 352*j*.
rare earths, into II-VI compounds, (11) 383*e*.
rare-gas, in neutron-irradiated K halides, (8) 297*d*.
reproducible, of Zn into GaAs, (2) 82*d*.
restricted anisotropic, of protons in hydrated vermiculite crystals, (5) 199*c*.
self-, in BeO, activation energies, correlation with steady-state creep, (8) 289*f*.
cation, in polycrystalline Y_2O_3 and Er_2O_3, (4) 128*d*.
coefficient of Ni atoms in nickel sulfide, (8) 290*e*.
mechanism, and thermal annealing studies of irradiation defects in graphite, (9) 331*c*.
of oxygen in BeO by proton activation of oxygen-18, (10) 360*e*.
of oxygen in ceramics, determination by nuclear activation, (6) 231*e*.
in KBr, entropies and enthalpies for, (4) 135*a*.
in simple oxides, (7) 268*b*.
in single crystals of molecular solids, mechanism, (8) 293*i*.
of Na in montmorillonite suspension at equilibrium, (4) 154*e*.
of sodium in sodium aluminosilicate glasses, (9) 307*c*.
of Na in sodium silicate liquids, (1) 36*j*.
of Na^+ and K^+ in their molten fluorides, (8) 297*d*.
surface, of UO_2, (4) 158*f*.
in UC, measurements, and application to related activated processes, (4) 143*e*.
SiO_2, in molten sodium silicate, electrochemical study, (4) 134*h*.
silver, in alkali-calcium-silica glasses, (1) 6*g*.
^{22}Na, in SiO_2 glass, effect of α, β-quartz transformation on, (6) 208*i*.
solid-state, reformulation of Fick's first law, for, (2) 82*a*.
stage of phase decomposition in solutions and glasses, (10) 362*a*.
strontium, in irradiated basalt, (7) 265*e*.
surface, for sintering of wires, (1) 39*h*.
surface, studies on UO_2 and MgO, (6) 238*f*.
thermal, of Sr ions in NaCl crystals, (4) 160*e*.
thermal, of Zr hydrides containing 4 at.% U, (10) 360*h*.
thermally activated, of electronic carriers in iron phosphate glasses, (5) 173*h*.
through solution and along surface, effect on electrocrystallization processes: I, potentiostatic case; II, Faradaic impedance; III, influence of finite rate of lattice formation, (4) 132*c*.
tracer, measurements in mixtures of molten alkali carbonates, (1) 39*h*.
^{233}U, in UO_2, (11) 383*f*.
water, into fused quartz lamps, calculation, (7) 246*j*.
water, in soda-lime glass within and near transformation range, (7) 247*b*.
Diffusivity, of C in Mo, (1) 37*i*.
in lithium fluoride, (8) 293*j*.
oxygen, in bcc iron stabilized by phosphorus, (2) 81*j*.
oxygen-ion, in hypostoichiometric ZrO_2, (8) 295*i*.
surface, of UO_2, tracer study, (7) 270*d*.
thermal, of cracked specimens, flash method for measuring, (9) 315*d*.
thermal, of UO_2-SiO_2 system with varying UO_2 concentrations at 100°-800°C, (10) 342*j*.
Dilatometers. See also *Expansion*.
frost, for specimens up to size of standard prisms, (7) 260*h*.
Dilatometry, of system Bi_2O_3-MoO_3, (8) 290*i*.
of tubular pyrolytic graphite, (1) 11*j*.
Dinnerware. See also *Art and artware; Pottery; Whiteware*.
abrading apparatus for finishing, P (1) 15*i*.
for Canadian hotel, from Syracuse, (2) 60*h*.
chinaware, P (1) 16*a*.
decorated, behavior in household dishwashers, (1) 15*a*.
plates, decoration with banding machines, possibilities and problems, (4) 108*i*.
porcelain decoration, behavior in domestic dishwashers, (1) 15*c*.
Diodes. See also *Tubes, electrons; Rectifiers*.
controlled breakdown voltage, P (4) 112*c*.
controllable tunnel, P (11) 376*b*.
device, irradiated temperature compensated Zener, P (1) 18*i*.
electroluminescent, effects of disturbance of transfer of electrons in, by electrode transparency, (8) 281*f*.
GaAs avalanche, high-power and high-efficiency, (10) 344*e*.
GaP, radiative efficiency in, dependence on heat treatment, (1) 26*j*.
Diodes *(continued)*
Ge silver bonded, breakdown characteristics and microwave oscillation, (4) 109*g*.
high voltage, for low pressure applications, P (2) 65*a*.
injection EL, P (4) 113*e*.
injection-luminescent GaAs, with graded *pn* junction, P (4) 113*c*.
negative resistance, P (2) 66*c*.
noise, with alloy Zener junction, P (10) 345*c*.
photo-, cryogenic avalanche, of InSb with negative resistance characteristic at potential greater than reverse breakdown, P (9) 312*e*.
photo-, low ohmic semiconductor tuned narrow bandpass barrier, P (9) 312*f*.
pin, with nonuniform intrinsic region width, P (11) 378*e*.
Schottky-barrier, formed by sputter-deposition processes, P (9) 313*f*.
semiconducting glass, filamentary conduction in, (10) 337*g*.
semiconductive field-controlled device, P (10) 346*a*.
semiconductor, P (6) 222*i*; P (6) 223*f*.
construction and mounting, P (11) 378*e*.
high-voltage, with ceramic envelope, P (4) 113*c*.
of junction type with heat sink at surface nearer to junction, P (10) 346*c*.
negative resistance, P (4) 115*a*.
negative resistance electroluminescent, P (7) 258*e*.
rectifier, for power current with particular doping, P (7) 258*e*.
reverse recovery transient, apparatus for automatically measuring, P (11) 376*f*.
silicon, variable capacitance, with hyper abrupt junction, P (4) 115*c*.
SiC, perform in searing heat, (5) 178*e*.
SiC *pn* jun electroluminescent, P (11) 378*i*.
structure, S) 185*j*.
Ta_2O_5 and troluminescence and photorespor 76*b*.
temperatu mpensated reference, forming, P (4) 114*h*.
thin Nb_2O_5, photoconductivity, electroluminescence, and hole injection in, (8) 281*d*.
tunable cr tal, P (9) 314*c*.
tunnel, P (11) 379*b*.
tunnel, wherein height of reduced cross section of mesa is minimized, P (2) 67*b*.
variable capacitance, P (7) 257*c*.
Disintegrators. See *Crushing apparatus*.
Dislocations, in CdS:Cu and CdS:Au single crystals, annealed, (4) 131*i*.
climb forces on, (10) 350*f*.
configurations, in deformed MgO, (2) 75*f*.
edge, in alkali halide crystals, theory of equilibrium charge on, (4) 160*g*.
effect on vaporization rate of NaCl single crystals, (2) 75*j*.
and grain boundary diffusion in growth of α-Fe_2O_3 whiskers and twinned platelets peculiar to gaseous oxidation, (9) 320*f*.
influence on thermal decomposition of calcium carbonate, (4) 139*i*.
in layer structures, enhanced reactivity at, (4) 135*j*.
locking, in doped NaCl, (2) 81*j*.
material, during glass scratching, (9) 306*d*.
in melt grown KCl crystals, observation by thermal etching, (10) 357*i*.
in mica, topographic X-ray observations, (1) 39*g*.
mobility, rate theory, (1) 35*i*.
motion, in corundum crystals grown by verneuil method, (10) 357*d*.
movement, in NaCl crystals in electric field, (5) 197*h*.
nonbasal, in molybdenite surfaces, identification and properties, (5) 195*i*.
and origin, in CdS crystals grown from vapor phase, (4) 131*i*.
in KCl, melt-grown, (7) 265*e*.
in $RbFeF_3$, (7) 265*e*.
screw, cluster of, in SiC, direct observation, (7) 265*d*.
piling up, against circular cylindrical rigid inclusion, (11) 386*g*.
process for growth of 2H-SiC whisker, (9) 308*i*.
stress field, precipitation hardening by diffusion in, (1) 35*e*.
and surface flaws on glass, (9) 305*a*.
Dispersion, aqueous, of montmorillonite, effect of Na humus, on structure formation and mechanism of development of deformations in, (7) 262*d*.
aqueous, of tremolite and hydromica, mechanism of formation of coagulation structures in, under action of ultrasound, (7) 267*b*.
chrysotile asbestos fiber, including monocarboxylic acid, P (2) 74*a*.
of clay, P (4) 124*h*.
clay-mineral, physicochemical mechanics, B (2) 85*h*.
colloidal alumina, aggregation by adsorbed surfactant ions, (1) 25*a*.
montmorillonite-kaolinite, structural-mechanical properties, controlling, (7) 262*a*.
re-, and reversible flocculation of chrysotile asbestos, P (5) 191*d*.
revised method, for low plagioclase, (6) 237*i*.
silica, aggregation by iron(III), (1) 25*b*.
of swelling clays by nonionic and anionic detergents, (5) 189*i*.
Y_2O_3-Zr, structure and properties, (10) 361*e*.

Dissolution. See *Solutions.*
Dolomite. See also *Refractories.*
and calcite composition, determination with air comparison pycnometer, (1) 21*c*.
$CaCO_3$ and $MgCO_3$ in, estimation, (4) 119*f*.
$CaMg(CO_3)_2$, crystal structure, comparison with norsethite, $BaMg(CO_3)_2$, (6) 231*e*.
decomposition, for manufacture of Mg oxychloride cement, catalytic action of NaCl on, (2) 43*i*.
dedolomitization, diagenetic, in Albian-Cenomanian Yagur dolomite on Mt. Carmel (Northern Israel), (8) 290*g*.
detrital, in Onondaga limestone (Middle Devonian) of New York, implications to dolomite question, (9) 319*h*.
dolomitization in carbonate platform system, Edwards formation, Texas, (7) 262*b*.
and limestone, selected, reactivity with SO_2, (1) 20*h*.
Mg in, rapid volumetric determination, (6) 227*f*.
physical and chemical properties, changes when fired at 1600°, 1800°, and 2000°C, (10) 340*h*.
plaster. See *Plaster.*
pre-Cambrian, Beck Spring, Kingston Range, California, petrology and depositional environments, (6) 229*h*.
selective flotation away from magnesite, P (4) 125*j*.
shaped refractories from, P (7) 252*b*.
structure, borates. $MeMe'(BO_3)_2$ with, (7) 263*j*.
synthesis, (4) 158*b*.
Domains. See *Ferroelectricity; Ferroelectric materials; Ferromagnetism; Ferromagnetic materials.*
Doping. See *Additives.*
Dosimeter, controlled defect [fused quarts] coloration, P (10) 344*e*.
material, thermoluminescent radiation, P (4) 117*e*.
Drilling, hydraulic jet, using ferrous abrasives, P (4) 89*i*.
Drills, bit, percussion, for shattering hard formations, P (2) 74*a*.
Dry pressing. See *Pressing.*
Dryers. See also *Drying.*
counterflow rotating drum, P (1) 20*d*.
fluidized, and separation, P (10) 348*c*.
German, for ceramic shapes, (7) 261*d*.
for hard-fired brick, (5) 188*j*.
industrial microwave, for drying by means of dielectric losses, (11) 381*g*.
for pottery ware, P (4) 123*c*.
rotary, for aggregate, P (2) 72*g*.
spray, preparation of ceramic molding powder in, (11) 375*h*.
tunnel zone controlled, P (10) 348*e*.
water models, flow studies on, (4) 119*g*.
Drying. See also *Dryers.*
blast furnace wall, (2) 58*d*.
bodies, P (8) 287*i*.
ceramic clays, new methods, (7) 258*i*.
ceramic products, P (10) 348*c*.
clays and ceramic bodies, investigation with bu relattograph, (10) 346*f*.
compressed air, (2) 67*d*.
cyclic jet, of clay, with special consideration of Rotomixair system, (7) 258*h*.
degree, influence on dry strength of porcelain bodies, (2) 60*e*.
direct, of vitrified clay pipes, (7) 249*j*.
of heavy clayware, B (8) 302*c*.
of hollow ceramic building units, (2) 54*d*.
molded ceramic article on form, P (7) 259*c*.
and palletizing, fully automatic, in structural clay industry, (7) 250*a*.
particulate material, P (2) 67*h*.
and preheating apparatus, for pulverulent material, particularly raw cement material, P (5) 170*c*.
problems, relating to laying of blast furnace bottom brick, (2) 55*d*.
raw brick materials, reduction, (10) 340*e*.
review, (4) 122*f*.
simultaneous moisture and heat transfer in porous systems with particular reference to, (6) 228*d*.
spray, in Kobanya Porcelain Works, (8) 280*c*.
techniques, review, (4) 122*f*.
wall and floor tiles, (1) 15*c*.
wet solid and semisolid materials, P (2) 68*c*.
Ductility, high-temperature, of Al-Al_2O_3 alloy, influence of grain size, (4) 140*b*.
Dusts. See also *Air, pollution; Particles; Powders.*
airborne, quartz in, in 0.5- to 2-μm size range, evaluation, (7) 260*b*.
collecting, (8) 274*i*.
collector, P (6) 225*a*.
control in ceramic industry, (6) 224*g*.
control, problem of works medicine relating to, (6) 224*j*.
electrostatic precipitation, apparatus for, P (8) 284*d*.
extraction, wet separators for, (4) 118*i*.
extractor, selection hints, (4) 117*i*.
extractor, "Tornado-Flow," operation and application, (4) 118*d*.
flue, carbon determination in, (2) 69*f*.
measurement in ceramic industry, problems, discussion, (6) 227*a*.
measurements in ceramic works, methods and results, (6) 226*d*.
in nature and technology, determination as impurities, and detection of F compounds in air, (6) 226*a*.
Dusts *(continued)*
removal, at quartz grinding works, (6) 224*h*.
Dysprosium, Dy^{3+} ions, reduction in CaF_2, behavior of F^- interstitials, (4) 127*e*.
oxide, activation of glasses in system Na_2O-B_2O_3 by, (2) 51*d*.
oxide, polycrystalline, elastic properties, room temperature measurements, (10) 352*a*.
in rock samples, determination by neutron activation analysis with Ge(Li) detector after chemical separation, (1) 21*i*.
subfluoride, stability at high temperatures, (4) 143*d*.

Earthenware, bodies, firing, (7) 253*h*.
bodies, pore size distribution in, (1) 15*b*.
stoneware, and porcelain, (6) 218*e*.
Eclogite, clinopyroxenes, from kimberlite pipes of Yakutia, (4) 132*f*.
differentiation, and possible causes, (5) 193*d*.
Ecuryptite, high-form, crystallization and polymorphism, (6) 231*j*.
Efflorescence, on bricks and brickwork, formation and prevention, (4) 101*j*.
Elasticity, and anelastic, behavior of V_2O_5-P_2O_5 glasses, (11) 369*f*.
behavior, of arc-cast ZrC-graphite alloys, (11) 384*g*.
constants, of alpha quartz, calculation from model, (4) 127*j*.
of CaF_2 and BaF_2, pressure and temperature derivatives of, (9) 328*e*.
of ceramics, measurement by resonant frequency methods, (6) 226*c*.
of chalcogenide glasses, (8) 276*f*.
of cubic crystal subjected to moderately high hydrostatic pressure, (9) 320*g*.
of polycrystalline BeO as function of pressure and temperature, (7) 265*a*.
third order, of GaAs, (4) 162*i*.
third-order, of polycrystalline media, (2) 84*i*; and relationships to single crystal constants, 84*j*.
third-order, theory, of diamond-like crystals, (4) 160*h*.
transformation, for anisotropic media by successive simple rotations, (8) 286*a*.
delayed, in inorganic glasses, (4) 95*g*.
micro-, behavior during scratching of glass and Plexiglas, (6) 210*e*.
modulus, of basic refractories, temperature dependence of, (2) 78*j*.
of chalcogenide infrared optical materials, (2) 48*e*.
of composite materials, perfectly disordered, (4) 133*j*.
in glass fiber-reinforced composites, (2) 48*h*.
isothermal, of UO_2 and UO_2-Mo cermets, (1) 12*j*.
of MnO, (9) 320*h*.
isotropic, of polycrystalline Al_2O_3, pressure and temperature dependences, (7) 268*e*.
of polycrystalline ZnO, TiO_2, and α-Al_2O_3, (5) 203*d*.
of refractories at high temperatures, (4) 103*a*.
shear, temperature-dependent, of UO_2, calculation, (4) 127*b*.
static, of ceramic and building material, routine measurement with electromechanical transducer, (6) 227*g*.
and yield curve, of polycrystalline graphite, effect of microporosity, (10) 341*b*.
photo-, study of dislocation pileup in colored LiF, (1) 34*j*.
properties, of isotropic graphite, (2) 76*g*.
of polycrystalline Y_2O_3, Dy_2O_3, Ho_2O_3, and Er_2O_3, room temperature measurements, (10) 352*a*.
of polycrystalline Y_2O_3, Ho_2O_3, and Er_2O_3, high-temperature measurements, (11) 384*h*.
Young's modulus, of artificial graphite, effect of porosity and crystalline orientation, comments, (4) 129*a*.
of BeO, as function of density and grain size, (2) 81*c*.
measurement simultaneous with thermal expansion, setting-temperature of vitreous enamel in form of thin layer, (10) 336*g*.
Electric resistors. See *Resistors, electrical.*
Electrical ceramics. See also *Electronics.*
with cordierite structure, (2) 62*h*.
dry-pressed, dimensional control, (10) 343*d*.
influence of texture defects on properties, (1) 16*j*.
metalizing processes for, (7) 255*f*.
preparation of powders for, (11) 379*f*.
progress, (1) 16*c*.
Electrical conductivity. See *Conductivity, electrical.*
Electrical properties, of actinide compounds, (10) 352*h*.
of alkali-free borate glasses, (11) 369*h*.
of Al_2O_3 ceramics, pure, influence of thermal neutron radiation, (2) 63*a*.
anodic passivation, of Si single crystals, (7) 263*j*.
anomalous, of solution grown, p-type GaP, (9) 318*d*.
of BiSb alloys with small antimony content, (5) 181*a*.
of CdF_2:In and CdF_2:Eu, (10) 358*a*.
of cermet films of Cr-SiO, (4) 110*e*.
of CeO$_2$ films, evaporated, (7) 254*f*.
of cermet films of CrSiO, (4) 110*e*.
charge flow in KCl, (8) 292*e*.
charge phenomena in dc reactively sputtered SiO_2 films, (7) 254*f*.
Electrical properties *(continued)*
of compounds of rare earths and actinides, (10) 360*d*.
of copper-containing sulfides and selenides with spinel structure, (4) 143*e*.
of Cu-Cu_2O eutectic alloys, (9) 324*j*.
dipole moment of cyclic $H_2B_2O_3$, (4) 144*f*.
double layers, in fused alkali metal nitrates, (9) 320*j*.
electrolytic conductance of melts in system LiBr-KBr, (9) 321*h*.
electrostatic potentials and spatial derivatives about point defects in ionic crystals, (4) 135*c*.
of glasses, (9) 307*e*.
effect of surface dealkalization, (10) 337*h*.
in system Na_2O-MgO-SiO_2, dependence on composition, (2) 47*h*.
of PbO single crystals, (1) 28*b*.
of lithium, sodium, and potassium silicate glasses, (10) 337*j*.
of $Li_xV_{2-x}O_3$, (10) 352*a*.
low-temperature, of transition metals and transition-metal carbides, (8) 294*h*.
of manganese ferrites, influence of Mn^{2+} ion clustering, (10) 355*c*.
membrane potentials of Pyrex glass electrodes, (5) 173*e*.
of mica, effect of stains and inclusions, (5) 190*d*.
of NiO, (8) 293*c*.
of NiO crystals, (7) 254*i*.
of niobium selenide and tungsten selenide, (11) 376*d*.
parameters, of thin layers of Cr-SiO, stability, (9) 311*a*.
of perovskite Sr_2(FeMo)O_6 and related compounds, (2) 79*j*.
of potassium-strontium and potassium-lead niobates, containing La, (10) 351*h*.
of $KTa_xNb_{1-x}O_3$ single crystals, (2) 77*g*.
potential, of clay, measurement, (9) 321*d*.
development in clay minerals and Al_2O_3-SiO_2 system, (10) 352*a*.
of glass electrodes in molten salts, (5) 172*j*.
of SiC films prepared in microwave discharge, (5) 181*j*.
of SiN films prepared by silane-ammonia reaction, (5) 180*j*.
thermo-, of systems SnTe-Bi_2Te_3 and PbTe-Sb_2Te_3, (4) 149*f*.
of thorium borides, (6) 232*b*.
of (Th,U)C solid solutions, (10) 341*e*.
of tin oxide crystals, (10) 352*g*.
of VO single crystals, (2) 76*i*.
of vitreous coatings, (7) 245*j*.
of Zn-Ni manganites, (9) 321*b*.
Electrical resistance. See *Resistance, electrical.*
Electricity, charges, influence on corrosion of metals, (7) 267*h*.
effect in ruby, (9) 320*h*.
field, applied, effect on EPR spectra of doped ferroelectric Rochelle salt, (4) 132*h*.
constant, effect on thermal conductivity of $BaTiO_3$-based solid solution and triglycine sulfate single crystals in phase transformation region, (4) 132*j*.
in crystals: III, refractivity of α-quartz, (4) 134*a*.
effect on space charge density of ZnO electrophotographic layers, (5) 180*i*.
high, change absorption in Fe-doped CdTe, (4) 111*f*.
high, effect on absorption spectra of CdTe, (5) 193*h*.
influence on mechanical properties of surface oxide layers, (2) 45*i*.
produced by charge density in ionic crystals, (4) 134*c*.
network, passive, P (1) 18*h*.
photo-, apparatus for refractive index determination by immersion method, (10) 347*c*.
properties, of MoO_3 single crystal and thin film, (1) 34*b*.
threshold, in MOS structure, effect of heating under bias, (2) 76*b*.
Electroceramics. See *Electrical ceramics.*
Electrochemistry. See also *Corrosion.*
behavior of interstratified clay minerals, (11) 384*h*.
properties, of clay minerals, (4) 128*h*.
properties, of zirconia-neodymium oxide system at high temperatures, (1) 28*d*.
studies, in molten Li_2CO_3-Na_2CO_3, (4) 134*g*.
study of diffusion of SiO_2 in molten sodium silicate, (4) 134*h*.
Electrodes. See also *Heating elements.*
arc temperature in, use of CN bands for determination, in presence of silicates containing higher amounts of Fe, (2) 71*e*.
arc welding, P (4) 93*c*.
arc welding, coated, P (9) 304*i*.
assembly, carbon furnace, P (6) 217*i*.
carbon, for electric arc stabilization in electric arc melting, P (11) 374*h*.
carbon or graphite, connecting pin and assembly, P (4) 106*e*.
cleaning, device in electrostatic dust separator for, P (6) 225*a*.
coated, and process for electric arc welding, P (5) 171*j*.
coating composition for, P (10) 337*d*.
with cobalt oxide coating, P (1) 18*h*.
composite, for magnetohydrodynamic generator, P (6) 221*c*.
composite, for MHD conversion duct, P (6) 221*d*.
composite structure, P (4) 106*c*.

Electrodes *(continued)*
conductive, for reducing electric field in region of junction of junction semiconductor device, P (4) 112*a*.
for electric arc welding, P (5) 172*a*.
fluoride activity, for determination of micro and semimicro amounts of Al, (8) 284*i*.
furnace, assembly, P (2) 72*h*.
glass, P (4) 99*a*.
composite, P (1) 10*a*.
composition, P (4) 98*j*; P (6) 212*b*.
electrical potentials in molten salts, (5) 172*j*.
fluoride-containing compositions, P (9) 307*d*.
for measuring pH with temperature compensating diode means, P (2) 71*i*.
for measuring K ion, (11) 381*f*.
glass furnace, liquid cooling device for, P (1) 10*j*.
glass pH, effects of light on, (7) 260*b*.
glassmelting, for glassmelting furnaces, P (4) 123*a*.
graphite, influence of chemical reactions in, on intensity of spectral lines, (2) 78*i*.
graphite, oxygen overvoltage on, in fused salts, (6) 216*i*.
for heating glass in furnace tank, P (4) 99*d*.
high temperature fluid coke, P (8) 279*c*.
holder, for glass furnaces, P (4) 98*c*.
joints, strengthened arc carbon, P (2) 59*g*.
laminated glass, diaphragm, P (11) 371*b*.
low pressure electric discharge lamp, P (9) 312*f*.
making by freezing wet powder and sintering, P (5) 183*h*.
for MHD converter, P (5) 182*h*.
platinum metal, in fired multilayer construction, (7) 255*g*.
Pyrex glass, membrane potentials, (5) 173*e*.
Na-responsive glass, for determination of Na in high purity water, (9) 315*c*.
specific ion, (6) 227*c*.
spherical metal, simple method of preparation, (10) 344*j*.
stationary platinum, for potential sweep voltammetry of Na_2O-SiO_2 glass melt, (1) 8*b*.
tube wire, P (2) 46*c*.
tubular welding, P (11) 369*c*.
Electrography, method for locating pinholes in thin SiO_2 films, (1) 21*h*.
Electroluminescence. See *Luminescence.*
Electroluminescent materials. See *Luminescent materials.*
Electrolysis, aluminum, metal reoxidation in, (1) 32*e*.
of refractory metallic oxide, (1) 23*h*.
of SiO_2 on silicon, (8) 291*d*.
in UO_2, (8) 291*c*.
Electrolytes, aluminum cell, liquidus curves, (1) 31*h*.
apparent molal volumes and expansibilities, in dilute aqueous solution, (8) 288*i*.
concentration, time of coagulation as function of—modified empirical relation, (6) 239*b*.
liquid, double layer relaxation in: I, theory of space charge polarization, (9) 320*g*.
spent, used for electrolytically descaling steel, process for reclaiming, P (2) 46*b*.
solid, $Zr_{0.85}Ca_{0.15}O_{1.85}$ and $Th_{0.85}Y_{0.15}O_{1.925}$, mixed conduction in, (4) 144*i*.
solid binary (ZrO_2) (CeO_2), physiochemical properties, (9) 327*e*.
Electrolytic, preparation, of pure basic aluminum fluorides, (1) 23*f*.
Electromagnets. See *Magnets.*
Electromechanical properties. See *Mechanical properties.*
Electron diffraction, low-energy, studies of (0001) face of α-Al_2O_3, (7) 267*i*.
measurements, filtered, from thick polycrystalline metal foils, (4) 136*h*.
patterns, of thin alloy films, interpretation, (4) 144*j*.
reflection scanning, from growing films, (4) 153*f*.
selected area, orientation determination by, (9) 314*i*.
small angle filtered, from growing films, (4) 121*h*.
studies, low-energy, of UO_2, (6) 234*e*.
study, selected area, of twinned α-Fe_2O_3 bladelike platelet growths on iron, (10) 361*d*.
Electron probes, microanalysis of metal oxides, comparison of correction methods, (1) 21*h*.
Electron tubes. See *Tubes.*
Electronic equipment, adaptors, heat-dissipating, for single-ended halogen quartz lamps to existing electrical lighting apparatus, P (1) 18*g*.
article, comprising stabilized zirconia and current collector embedded in, P (2) 64*f*.
attenuator, reciprocal ferrite, P (4) 116*f*.
attenuator, solid state microstripline, P (6) 224*b*.
bushing, cast electrical, P (6) 220*i*.
ceramic spacers, plurality, for separating planar grids, P (6) 223*f*.
component, P (10) 345*h*.
joining to substrate, P (6) 222*e*.
thin film, P (1) 18*f*.
connections for microminiature functional components, P (10) 344*e*.
connector, low resistivity semiconductor underpass, P (8) 282*c*.
connector, metal, attaching to semiconductor body, P (4) 115*h*.
cylinder with internal photosensitive coating and prism on outer surface for admitting light at angle to be totally internally reflected, P (8) 282*d*.
device, sealed enclosure for, P (2) 66*j*.
devices, thin film, plastic substrates for, (8) 281*d*.
discharge device, gas-filled, with grid with element particularly spaced from cathode, P (2) 64*i*.
discharge device, high pressure electric, containing mercury, halogen, scandium, and alkali metal, P (2) 65*a*.
with electric circuit elements, dividing into parts, P (4) 114*b*.
electrical device, comprising metal oxide-containing solid electrolyte and electrode, P (7) 256*e*.
enclosing, P (2) 65*j*.
epitaxial growth method of fabricating, P (11) 377*i*.
including stabilized zirconia solid electrolyte, P (2) 64*i*.
electrical temperature sensor device, P (2) 64*c*.
electrically conductive tool, P (6) 221*h*.
electrically conductive tracks, production by electron or laser-beam decomposition of inorganic metallic compounds: I, oxide systems, (8) 281*e*.
electron gun, with electrode cup in ceramic cavity, P (10) 344*g*.
envelope wall with two continuous ledges for positioning and supporting aperture mask, P (2) 64*d*.
field effect devices, integral grid and multichannel, P (2) 65*e*.
field effect device, variable threshold insulated gate, P (6) 224*c*.
with fused quartz-to-metal seals, (8) 280*h*.
high capacity epitaxial, and method, P (5) 182*d*.
image orthicon glass target with Al-Ta oxide coating, P (7) 256*b*.
incorporating SiN insulating films, P (4) 114*b*.
intensifier, electrooptic image, P (11) 376*e*.
image, comprising perforated glass substrate, and method of making, P (2) 65*b*.
photoconductive electrooptic image, using polarized light, P (9) 313*b*.
lead-in, for devices with quartz bulb, P (9) 312*e*.
magnetic recording member, wear resistant, P (11) 379*b*.
MHD conversion duct, composite electrode for, P (6) 221*d*.
microphone, miniature ceramic, P (7) 257*d*.
microwave power limiter comprising abutting semiconductor and ferrite elements, P (5) 184*i*.
monolithic silicon device containing dielectrically isolating film of SiC, P (1) 18*f*.
multistable device, operating on principle of stimulated emission of radiation, P (5) 184*b*.
optical-, for beneficiation of raw materials, (5) 189*i*.
overvoltage protective device and conductor support, combined, P (9) 312*d*.
phase shifter, ferrite, reciprocal microwave, P (6) 223*a*.
planar high voltage four layer structures, P (6) 223*e*.
refractory ceramic discharge device envelopes $[Al_2O_3]$, sealing means for, P (9) 313*g*.
scanistors, diffused-epitaxial, P (7) 256*e*.
scintillator, Na-activated CsI, P (8) 283*g*.
semiconductor-insulator-metal sandwich, metal-degenerate, exhibiting voltage controlled negative resistance characteristics, P (8) 282*d*.
sensing device, simplified piezoresistive force, P (4) 116*j*.
sensor, laser fluid flow, insensitive to rotation, P (9) 312*d*.
radiation, utilizing semiconductor body with photoelectromagnetic effect, P (2) 66*j*.
stress and strain, semiconductor *pn* junction, P (6) 223*i*.
shock wave devices, electrical, and control, P (6) 221*h*.
signal device, piezoelectric semiconductor [ZnO] acoustic wave, P (6) 223*e*.
solid-state components, contacting arrangement, P (10) 344*e*.
spark gaps, P (8) 283*i*.
storage device, light sensitive, including diode array, P (4) 113*h*.
structural element, with closely neighboring terminal contacts, P (4) 112*f*.
susceptor, for growing polycrystalline silicon on monocrystalline silicon wafers, P (1) 19*e*.
switching element, bistable two or three terminal double injection, P (10) 344*c*.
terminal, fluorine-resistant, P (4) 113*e*.
thermoelements, segmenting PbTe-Si Ge, P (10) 345*j*.
thin wafer-channel multiplier, P (11) 379*a*.
transistorized, for study of excited nuclear states by angular correlation methods, (1) 21*b*.
vacuum operated chip placement head, P (10) 346*c*.
valves, ceramics in, (2) 63*h*.
vapor device, P (5) 183*j*.
vibrator, ceramic piezoelectric, P (9) 313*d*.
X-ray converter, with terbium activated lanthanum compound phosphor, P (1) 19*h*.
Electronics. See also *Electrical ceramics; Electronic equipment.*
Electronics *(continued)*
aligning method and apparatus, P (11) 376*e*.
carriers, thermally activated diffusion, in iron phosphate glasses, (5) 173*h*.
ceramic materials, review, (1) 16*d*.
ceramics, from titanates, (2) 64*b*.
in changing world, review, (1) 40*e*.
donor gradients, determination within surface barriers formed on dense Gd-doped barium titanates, (9) 310*g*.
electrets, discussion of various materials, (5) 180*j*.
gap, glass-filled, forming, P (11) 377*a*.
glass applications in, (7) 247*j*.
glass in, (5) 172*f*; (10) 338*j*.
image translation system employing optical fibers, P (11) 376*j*.
(initial current) measurement of cathode temperature, (6) 226*f*.
leadless inverted device forming process, P (11) 377*c*.
mechanism, for low temperature acoustic loss in magnetite, (1) 27*d*.
micro-, hybrid, second symposium, 1967, B (6) 242*f*.
network, thin film distributed RC, P (8) 284*b*.
properties, of CdS films, chemically grown, (8) 281*g*.
of $Pb_{1-x}Sn_xTe$, $Pb_{1-x}Sn_xSe$, and other IV-VI alloys, (2) 80*c*.
of Mo bronzes, (8) 298*b*.
of neptunium monocarbide and mononitride, (10) 353*a*.
surface and bulk, of Li-doped NiO, (4) 111*c*.
tunneling characteristics, in Al-Al_2O_3-Sb junctions, (8) 200*a*.
structure, of graphite, optical study, (2) 81*f*.
thermionic-field resistance maxima in metal semiconductor (Schottky) barriers, (9) 311*e*.
tunneling, Fowler-Nordheim, into thermally grown SiO_2, (9) 310*f*.
Electrons, affinities, ionization potentials, and screening constants: VII, comparison with Hartree-Fock calculations, (9) 323*g*.
barriers, formation on phosphor particles, P (9) 312*j*.
beam, apparatus for evaporation of low temperature semiconductor material, and means for draining electric charge from, P (4) 112*b*.
E-S high-vacuum setup, (2) 62*a*.
for growing thin film semiconductors, P (4) 114*j*.
for measurement of potential distribution in semiconductor crystal, (5) 187*c*.
method of measuring diffusion voltage in semiconductors, (5) 187*g*.
for nondestructively measuring dielectric properties of sample, P (9) 315*i*.
scanning, anomalous transmission patterns, (8) 297*a*.
techniques in integrated circuits, P (10) 344*g*.
technique for measuring thermal conductivity, (8) 285*b*.
beam welders and lasers, characteristics and potentials, (11) 379*f*.
beam zone refiner, conversion to rf heating, (4) 119*i*.
density distributions, determination, effect of multiple diffraction, (11) 384*g*.
density distribution in TiC, X-ray study, (6) 240*b*.
emissions. See *Emissions.*
energization threshold, of phosphor particles, increasing, P (2) 65*c*.
energy distribution, tunneling through metal-insulator-metal sandwich structure, (8) 292*a*.
free, in ZnO, optical properties, (4) 147*b*.
hopping, in octahedral sites of Fe_3O_4, Moessbauer study, (9) 325*j*.
microprobe, to investigate enameling problems, (5) 171*g*.
microprobe, for quantitative analysis in oxide combinations, (9) 328*b*.
movement, in cathode sputtering, electrostatic control, P (4) 112*j*.
optical studies, of reaction processes between kaolinite and sodium carbonate, (8) 293*j*.
photoemission, from *n*-type degenerate Si in SiO_2, (4) 149*a*.
radioactive capture of positrons by, and use of Born approximation, (4) 111*e*.
slow, in ionic crystals, theory, quadratic approximation in, (10) 356*b*.
slow, use in transmission electron microscopy, (2) 71*d*.
transfer effects of disturbance by electrode transparency in electroluminescent diodes, (8) 281*f*.
transfer reactions, role of water in, (6) 237*a*.
transport, crystal-field model of, in sodium-vanadium bronze, (1) 17*e*.
trapped, spatial distribution, in γ-irradiated organic glasses, (8) 298*d*.
Electrooptic, coefficients, relation between linear and quadratic in $LiNbO_3$, $LiTaO_3$, and other oxygen-octahedra ferroelectrics based on direct measurement of spontaneous polarization, (2) 82*a*.
device with concentric arrangement of layers, P (8) 282*f*.
effect, in $Bi_{12}GeO_{20}$, (1) 33*g*.
effects, in paraelectric perovskites, (2) 76*g*.
logic device, four terminal, P (4) 113*f*.
Electrophoresis, continuous particle, for separation of clay minerals, (11) 380*g*.
deposition of enamel, (5) 171*e*; (9) 304*i*; (10) 337*a*.

Electrophoresis *(continued)*
electrophoretic mobility, of crystalline silica, effect of cationic polymers structure, (1) 28*d*.
forced-flow, for clay filtration, (1) 29*j*.
and industrial applications, (6) 220*g*.
Electrophotography. See *Photography*.
Electrostatic processes, coating apparatus, P (7) 246*f*.
coating, and surface preparation, (10) 337*b*.
for decorating glass and vitreous enamels for use in, P (7) 248*f*.
field, for metal silicate coating, P (7) 256*i*.
field effect, in epitaxial growth of gold particles evaporated onto NaCl, (6) 232*c*.
finishing, fundamentals, (7) 246*b*.
precipitation of dust, apparatus for, P (8) 284*d*.
separation of dry materials, P (11) 382*a*.
sorting, of granular materials, method and apparatus, P (1) 20*e*; P (2) 74*d*.
spray, at Philco-Ford, (7) 246*f*.
spray, vignetting or highlighting practices after application by, (7) 246*c*.
spray device, P (5) 186*f*.
spraying, (2) 67*a*.
of enamel, exhaust equipment developments for, (1) 4*a*.
of enamel on range ware, (1) 5*b*.
by hand gun, (1) 20*b*.
of vitreous enamels, (1) 4*i*.
Electrostriction, in perovskite-type, ferroelectric materials, calculation, (1) 16*b*.
Elements, ceramic, with honeycomb structure, apparatus for manufacturing, P (2) 67*g*.
TaC, for incandescent devices, P (7) 248*f*.
heating. See *Heating elements*.
Emeralds, characterization by visible and infrared absorption spectroscopy, (8) 289*e*.
Emission, and absorption phenomena in NaCl crystals with high concentration of copper, (6) 230*f*.
electron, from "cold-cathode" GaAs *pn* junction, (9) 310*j*.
electron tunnel, apparatus and methods, P (9) 312*f*.
from LiF during thermoluminescence, (8) 298*e*.
low-field microwave, from InSb, theoretical explanation, (9) 331*a*.
photo-, from Al-Al_2O_3 films in vacuum ultraviolet region, (11) 376*c*.
of electrons from *n*-type degenerate Si into SiO_2, (4) 149*h*.
of holes from Si into SiO_2, (4) 149*h*.
from InP-Cs-O, (1) 34*a*.
low work function (less than 1.0 eV), by InGaAs-CsO, (10) 344*g*.
properties of GaAs surfaces, effects of heat cleaning, (10) 343*j*.
spectral, in LiF, due to lattice vibrations, (8) 298*e*.
spectral, of transparent materials, radiation induced changes in, (4) 152*b*.
thermo-, of W alloyed with lanthanide oxides, (9) 332*j*.
X-ray. See *X rays*.
Emittance, high-temperature hemispherical, of uranium oxides at 0.65 and 0.70 μm, (6) 233*a*.
of opaque substance, effect of surface porosity, (6) 232*h*.
Emitters, field-enhanced thermionic, P (11) 376*f*.
photo-, negative-electron-affinity, low-work-function surfaces, (11) 385*e*.
preparation, for X-ray fluorescence analysis of powders, (6) 227*a*.
semiconductor light, and combination light emitter-photocell, P (11) 378*f*.
Emulsions, vitrifiable photosensitive, P (2) 61*a*.
Enameled ware, dishwasher, cost of enamel vs plastisol for coating, (1) 4*g*.
with patterned surface, P (10) 337*c*.
ovens, self-cleaning, (2) 45*h*.
pots and pans, origin to modern day, (5) 171*f*.
range, spraying electrostatically, (1) 5*b*.
utensils, evolution of sheet steel ware for, (6) 207*g*.
water solubility, (10) 337*c*.
Enameling, by coil coating, (7) 246*f*.
direct, research, (4) 93*h*; (6) 207*g*.
direct-white, improved steel for, (1) 4*d*.
dry process, foundry control improves, (2) 45*i*.
electrophoretic, technical problems, (5) 171*e*; (10) 337*a*.
equipment. See *Spraying*.
furnaces. See *Furnaces*.
inside of long tubes of small ID, physical conditions, (10) 336*j*.
multicolor, (6) 207*j*.
operations, water pollutants from, (5) 171*b*.
problems, use of electron microprobe to investigate, (5) 171*g*.
progress, (1) 4*a*.
single layer, direct-on, mechanism of adherence for, (10) 336*c*.
Enameling apparatus. See *Furnaces; Spraying*.
Enameling metals, aging of, (1) 3*j*.
aluminum, (11) 368*h*.
for architectural uses, (8) 275*b*.
cookware, streamlined at Mirro, (8) 275*b*.
in India, (2) 46*c*.
cast iron, effect of gases and development of gases during, (5) 171*g*.
cast iron bathtubs, partial mechanization suggestions, (5) 171*c*.
Enameling metals *(continued)*
cast iron bath tubes and stoves, (10) 336*h*.
coil steel stock, (8) 275*c*.
coiled steel, (5) 171*i*.
de-, chemical, of gray cast iron, (6) 207*f*.
direct-on, white, techniques, (5) 171*d*.
oven panels, self-cleaning, at Crown Stove, (11) 368*g*.
pickling. See *Pickling*.
preparation of sheet steel for, (1) 5*f*; (1) 5*d*.
pretreated steel sheets for, (7) 246*g*.
problems with heat-resistant steels, (10) 337*b*.
process using fluidized bed, P (2) 46*e*.
sheet, P (4) 94*b*.
sheet iron, process control in, (4) 93*e*.
sheet steel for single-coat method, P (4) 94*e*.
steel, P (7) 246*g*.
cost reduction through design of components using, (8) 274*i*.
low carbon, yield strength after firing, (8) 275*g*.
newly developed for appliances, (11) 368*i*.
stainless steel and Al surfaces for electrical insulation, P (9) 337*d*.
Enamels. See also *Coatings*.
acid and alkali resistant, for chemical industry apparatus, (5) 171*a*.
acid and alkali resistant, for chemical processing industry, improvement by use of oxides of transition elements, (10) 336*j*.
acid-resistant, electrocoating to steel, (7) 245*j*.
adherence to aluminum, (1) 5*b*.
adherence to steel, torsion test for determination, (2) 71*g*.
for aluminum, permanent color, (1) 5*a*.
aluminum-, interface, observed by electron microscopy, (10) 336*e*.
color, relation between particle size and firing temperature of, (11) 368*h*.
composite, P (8) 275*c*.
composition, for insulation of high-temperature magnet wire, P (8) 275*d*.
controlled deflection strainline test, (7) 245*i*.
cover-coat, solubility and aging behavior, (1) 4*e*.
crackle, application to copper, (6) 207*g*.
crystallizable, for glass-ceramics, P (6) 212*j*.
defects, direct-on cover coat, (7) 245*i*.
direct-on cover coat, adherence evaluation, (1) 4*i*.
dry process, apparatus for deposition on heated substrate, P (5) 171*i*.
dry process, nozzle applicator for, P (1) 5*f*.
electrical properties, (7) 245*j*.
electrodeposition for, (7) 246*h*.
electrophoretic deposition, (9) 304*i*.
frits. See *Frits*.
in form of thin layer, simultaneous measurement of thermal expansion, setting-temperature, and Young's modulus, (10) 336*g*.
on gas-fired heat exchanger, to beat corrosion, (1) 3*j*.
glass-crystalline, based on lithium metasilicate, (6) 207*i*.
ground coat and direct-on white, effect of cobalt and nickel in, (10) 336*g*.
for heat transfer surface, (1) 4*j*.
hot water tank, determining effective coverage, (7) 245*h*.
industry, cost accounting system, (1) 5*b*.
leaching, (1) 15*i*.
low temperature, combined with conversion coatings for retardation of corrosion of Be, (5) 171*c*.
low-temperature titania-opacified, (2) 46*a*.
manufacturing process, magnetic handling and purification equipment applied to, (1) 4*f*.
to metal, adhesion, investigation of test for measurement, (1) 5*e*.
one-coat, bubble structure and adherence, (5) 171*b*.
one-coat white, effect of water vapor in furnace atmosphere on, (8) 274*i*.
phosphorescent, (1) 4*i*.
powder, applicator for, P (6) 207*j*.
powders, surface modified electrostatic, and method, P (1) 5*f*.
properties, influence of iron oxides, (1) 7*j*.
satin finish vitrifiable, P (2) 54*a*.
semicrystallized ground coats, and enameled articles from, P (11) 369*c*.
sheet ground-coat, adhesion testing, (1) 5*c*.
sheet steel, composition, (1) 4*e*.
slips. See *Slips*.
technology, B (4) 168*i*.
TiO_2, stability of anatase in, (7) 246*i*.
one-coat, viscosity, (6) 207*h*.
-opacified, crystallization and phase transformation in: I, theory; II, comparison of theory with experiment, (4) 93*d*.
-opacified reflectance, (6) 207*f*.
-opacified, role of P_2O_5 in, (7) 246*h*.
toxic constitutents extracted from, according to proposed standard DIN 51166, (5) 171*a*.
use in chemical industry, (5) 171*h*.
for use in electrostatic method of decorating glass, P (7) 248*f*.
vitreous crystalline, influence of application process on crystallization of, (2) 45*h*.
white, effects of moist furnace atmosphere, (8) 274*j*.
Energy, activation, for hydrogen diffusion in thorium hydrides, (4) 126*d*.
Energy *(continued)*
activation, of silicate glasses, effect of melting aids, (2) 48*c*.
in sintering, (10) 349*h*.
for steady-state creep and self-diffusion in BeO, correlation between, (8) 289*f*.
bands, in BN, cubic, (4) 135*h*.
bands, in diamond, (4) 135*h*.
changes in dehydration processes of clay minerals, (7) 265*c*.
dissociation, of gaseous gallium monophosphide, (6) 231*h*.
of molecule BO, mass spectrometric determination, (9) 324*i*.
of AgF, (6) 234*i*.
of thallium monofluoride, (2) 76*i*.
of SnF and PbF, (10) 356*j*.
of $TiO(g)$, (11) 383*i*,*j*.
elastic, release rate, measurement, effect of nonlinear Hertzian deformations and gage length on, (5) 193*i*.
of formation, of Schottky defects in cesium halides, (1) 29*f*.
of formation, of Schottky defects in ionic crystals, (1) 29*g*.
fracture, of glass, (9) 305*f*.
fracture surface, of glass, (4) 95*i*.
fracture surface, measuring by double cantilever method, critical analysis and discussion, (2) 47*f*.
free, of adhesion and equilibrium of contact reactions at solid-fluid interfaces: I, perfect solid and fluid, (1) 30*d*.
free of formation, of beryllium hydroxide (g), (4) 161*h*.
of chlorides and fluorides, (9) 321*i*.
of cupric oxide, (4) 136*e*.
of fayalite, (4) 129*j*.
of groups II–IV semiconductors, (4) 161*c*.
of NbO and Ta_2O_5, (8) 292*b*.
of palladium oxide, (4) 136*f*.
of ReS_2, (4) 136*g*.
of sulfides of transition elements and zinc, (1) 37*j*.
of UC and UC_2, (4) 157*h*.
internal strain, and strength of brittle materials, (8) 293*f*.
lattice, of cubic oxides, (1) 31*h*.
lattice, and heats of formation, of superoxides of K, Rb, and Cs, (1) 39*f*.
microscopic free, and order parameters of antiferroelectrics, (4) 144*j*.
optical wave, second harmonic, generation of, P (2) 65*a*.
photon, of GaAs in lightly doped limit, (9) 324*d*.
point-defect formation, in alkaline-earth fluorides, Born-model calculation of, (8) 288*i*.
quaternary excess free, and ternary phase diagrams, predicting using binary data, (10) 359*d*.
radioactive, sources, P (10) 345*a*.
relative, of [$\bar{1}$100] tilt boundaries in Al_2O_3, (1) 36*c*.
structure, of B and BN, investigation by ultra-longwave X-ray spectroscopy, (4) 141*c*.
surface, effective, of brittle materials, (6) 232*h*.
of glasses below transformation temperature, (11) 370*e*.
lowering by adsorption on alumina, (1) 31*j*.
ratio of grain boundary to, for UC, (6) 236*j*.
thermal, consumption, of glass furnaces, (2) 52*c*.
total, in brick and tile industry, (1) 11*g*.
transfer, and fluorescence processes in Bi^{3+} and Eu^{3+} activated YVO_4, (4) 135*i*.
mechanisms involving trivalent Er and Tb or Tm in sodium rare-earth tungstates, (4) 144*a*.
mechanisms involving trivalent Tb and Nd in sodium rare-earth tungstates, (4) 144*a*.
between trivalent rare-earth ions in inorganic solids, (4) 135*h*.
vacancy migration, in cubic crystals, calculation, (9) 318*a*.
volume free, of nucleation of crystalline phase from multicomponent regular solution, calculation, (6) 230*f*.
Engineering, helps doctors cure bedridden hospital patients, (9) 333*c*.
opportunities in, B (6) 241*c*.
properties, of inorganic coatings, (8) 274*j*.
and science, creativity, (1) 40*f*.
Engineers, in building materials, graduate program for, (9) 333*d*.
Engobes, colored bodies, and glazes, review, (4) 108*d*.
Enthalpy. See *Heat, content*.
Entropy, of aluminium(I) flouride(g), (1) 29*g*.
of $BeCl_2(g)$, $BeCl_4(g)$, and beryllium(I) hydroxide(g), (5) 201*d*.
characteristic, of refractory Th compounds, (4) 128*i*.
configurational, of vitreous SiO_2 in random network theory, (4) 129*d*.
of GeO_2, tetragonal, (4) 135*b*.
high-temperature, of four crystalline sodium-calcium silicates, (5) 195*c*.
measurement techniques, and application to uranium compounds, (5) 200*j*.
for self-diffusion in KBr, (4) 135*a*.
for small classical crystals, (8) 292*b*.
-symmetry-volume relations, in polymorphs, (1) 39*a*.
Epitaxy. See *Crystallization*.

Electrodes *(continued)*
conductive, for reducing electric field in region of junction of junction semiconductor device, P (4) 112*a*.
for electric arc welding, P (5) 172*a*.
fluoride activity, for determination of micro and semimicro amounts of Al, (8) 284*i*.
furnace, assembly, P (2) 72*h*.
glass, P (4) 99*a*.
composite, P (1) 10*a*.
composition, P (4) 98*j*; P (6) 212*b*.
electrical potentials in molten salts, (5) 172*j*.
fluoride-containing compositions, P (9) 307*d*.
for measuring pH with temperature compensating diode means, P (2) 71*i*.
for measuring K ion, (11) 381*f*.
glass furnace, liquid cooling device for, P (1) 10*j*.
glass pH, effects of light on, (7) 260*b*.
glassmelting, for glassmelting furnaces, P (4) 123*a*.
graphite, influence of chemical reactions in, on intensity of spectral lines, (2) 78*i*.
graphite, oxygen overvoltage on, in fused salts, (6) 216*i*.
for heating glass in furnace tank, P (4) 99*d*.
high temperature fluid coke, P (8) 279*c*.
holder, for glass furnaces, P (4) 98*c*.
joints, strengthened arc carbon, P (2) 59*g*.
laminated glass, diaphragm, P (11) 371*b*.
low pressure electric discharge lamp, P (9) 312*f*.
making by freezing wet powder and sintering, P (5) 183*h*.
for MHD converter, P (5) 182*h*.
platinum metal, in fired multilayer construction, (7) 255*g*.
Pyrex glass, membrane potentials, (5) 173*e*.
Na-responsive glass, for determination of Na in high purity water, (9) 315*c*.
specific ion, (6) 227*c*.
spherical metal, simple method of preparation, (10) 344*j*.
stationary platinum, for potential sweep voltammetry of Na_2O-SiO_2 glass melt, (1) 8*b*.
tube wire, P (2) 46*c*.
tubular welding, P (11) 369*c*.
Electrography, method for locating pinholes in thin SiO_2 films, (1) 21*h*.
Electroluminescence. See *Luminescence.*
Electroluminescent materials. See *Luminescent materials.*
Electrolysis, aluminum, metal reoxidation in, (1) 32*e*.
of refractory metallic oxide, (1) 23*h*.
of SiO_2 on silicon, (8) 291*d*.
in UO_2, (8) 291*c*.
Electrolytes, aluminum cell, liquidus curves, (1) 31*h*.
apparent molal volumes and expansibilities, in dilute aqueous solution, (8) 288*i*.
concentration, time of coagulation as function of—modified empirical relation, (6) 239*b*.
liquid, double layer relaxation in: I, theory of space charge polarization, (9) 320*g*.
spent, used for electrolytically descaling steel, process for reclaiming, P (2) 46*b*.
solid, $Zr_{0.88}Ca_{0.12}O_{1.88}$ and $Th_{0.88}Y_{0.12}O_{1.88}$, mixed conduction in, (4) 144*i*.
solid binary (ZrO_2) (CeO_2), physiochemical properties, (9) 327*c*.
Electrolytic, preparation, of pure basic aluminum fluorides, (1) 23*f*.
Electromagnets. See *Magnets.*
Electromechanical properties. See *Mechanical properties.*
Electron diffraction, low-energy, studies of (0001) face of α-Al_2O_3, (7) 267*i*.
measurements, filtered, from thick polycrystalline metal foils, (4) 136*h*.
patterns, of thin alloy films, interpretation, (4) 144*j*.
reflection scanning, from growing films, (4) 153*f*.
selected area, orientation determination by, (9) 314*i*.
small angle filtered, from growing films, (4) 121*h*.
studies, low-energy, of UO_2, (6) 234*e*.
study, selected area, of twinned α-Fe_2O_3 blade-like platelet growths on iron, (10) 361*d*.
Electron probes, microanalysis of metal oxides, comparison of correction methods, (1) 21*h*.
Electron tubes. See *Tubes.*
Electronic equipment, adaptors, heat-dissipating, for single-ended halogen quartz lamps to existing electrical lighting apparatus, P (1) 18*g*.
article, comprising stabilized zirconia and current collector embedded in, P (2) 64*f*.
attenuator, reciprocal ferrite, P (4) 116*f*.
attenuator, solid state microstripline, P (6) 224*b*.
bushing, cast electrical, P (6) 220*i*.
ceramic spacers, plurality, for separating planar grids, P (6) 223*f*.
component, P (10) 345*h*.
joining to substrate, P (6) 222*c*.
thin film, P (1) 18*f*.
connections for microminiature functional components, P (10) 344*e*.
connector, low resistivity semiconductor underpass, P (8) 282*c*.
connector, metal, attaching to semiconductor body, P (4) 115*h*.
cylinder with internal photosensitive coating
Electronic equipment *(continued)*
and prism on outer surface for admitting light at angle to be totally internally reflected, P (8) 282*d*.
device, sealed enclosure for, P (2) 66*j*.
devices, thin film, plastic substrates for, (8) 281*d*.
discharge device, gas-filled, with grid with element particularly spaced from cathode, P (2) 64*i*.
discharge device, high pressure electric, containing mercury, halogen, scandium, and alkali metal, P (2) 65*a*.
with electric circuit elements, dividing into parts, P (4) 114*b*.
electrical device, comprising metal oxide-containing solid electrolyte and electrode, P (7) 256*e*.
enclosing, P (2) 65*j*.
epitaxial growth method of fabricating, P (11) 377*i*.
including stabilized zirconia solid electrolyte, P (2) 64*i*.
electrical temperature sensor device, P (2) 64*c*.
electrically conductive tool, P (6) 221*h*.
electrically conductive tracks, production by electron or laser-beam decomposition of inorganic metallic compounds: I, oxide systems, (8) 281*e*.
electron gun, with electrode cup in ceramic cavity, P (10) 344*g*.
envelope wall with two continuous ledges for positioning and supporting aperture mask, P (2) 64*d*.
field effect devices, integral grid and multichannel, P (2) 65*e*.
field effect device, variable threshold insulated gate, P (6) 224*c*.
with fused quartz-to-metal seals, (8) 280*h*.
high capacity epitaxial, and method, P (5) 182*d*.
image orthicon glass target with Al-Ta oxide coating, P (7) 256*b*.
incorporating SiN insulating films, P (4) 114*b*.
intensifier, electrooptic image, P (11) 376*e*.
image, comprising perforated glass substrate, and method of making, P (2) 65*b*.
photoconductive electrooptic image, using polarized light, P (9) 313*b*.
lead-in, for devices with quartz bulb, P (9) 312*e*.
magnetic recording member, wear resistant, P (11) 379*b*.
MHD conversion duct, composite electrode for, P (6) 221*d*.
microphone, miniature ceramic, P (7) 257*d*.
microwave power limiter comprising abutting semiconductor and ferrite elements, P (5) 184*i*.
monolithic silicon device containing dielectrically isolating film of SiC, P (1) 18*f*.
multistable device, operating on principle of stimulated emission of radiation, P (5) 184*b*.
optical-, for beneficiation of raw materials, (5) 189*i*.
overvoltage protective device and conductor support, combined, P (9) 312*d*.
phase shifter, ferrite, reciprocal microwave, P (6) 223*a*.
planar high voltage four layer structures, P (6) 223*e*.
refractory ceramic discharge device envelopes [Al_2O_3], sealing means for, P (9) 313*g*.
scanistors, diffused-epitaxial, P (7) 256*e*.
scintillator, Na-activated CsI, P (8) 283*g*.
semiconductor-insulator-metal sandwich, metal-degenerate, exhibiting voltage controlled negative resistance characteristics, P (8) 282*d*.
sensing device, simplified piezoresistive force, P (4) 116*j*.
sensor, laser fluid flow, insensitive to rotation, P (9) 312*d*.
radiation, utilizing semiconductor body with photoelectromagnetic effect, P (2) 66*j*.
stress and strain, semiconductor *pn* junction, P (6) 223*i*.
shock wave devices, electrical, and control, P (6) 221*h*.
signal device, piezoelectric semiconductor [ZnO] acoustic wave, P (6) 223*e*.
solid-state components, contacting arrangement, P (10) 344*c*.
spark gaps, P (8) 283*i*.
storage device, light sensitive, including diode array, P (4) 113*h*.
structural element, with closely neighboring terminal contacts, P (4) 112*f*.
susceptor, for growing polycrystalline silicon on monocrystalline silicon wafers, P (1) 19*e*.
switching element, bistable two or three terminal double injection, P (10) 344*c*.
terminal, fluorine-resistant, P (4) 113*e*.
thermoelements, segmenting PbTe-Si Ge, P (10) 345*j*.
thin wafer-channel multiplier, P (11) 379*a*.
transistorized, for study of excited nuclear states by angular correlation methods, (1) 21*b*.
vacuum operated chip placement head, P (10) 346*c*.
valves, ceramics in, (2) 63*h*.
vapor device, P (5) 183*j*.
vibrator, ceramic piezoelectric, P (9) 313*d*.
X-ray converter, with terbium activated lanthanum compound phosphor, P (1) 19*h*.
Electronics. See also *Electrical ceramics; Electronic equipment.*
Electronics *(continued)*
aligning method and apparatus, P (11) 376*e*.
carriers, thermally activated diffusion, in iron phosphate glasses, (5) 173*h*.
ceramic materials, review, (1) 16*d*.
ceramics, from titanates, (2) 64*b*.
in changing world, review, (1) 40*e*.
donor gradients, determination within surface barriers formed on dense Gd-doped barium titanates, (9) 310*g*.
electrets, discussion of various materials, (5) 180*j*.
gap, glass-filled, forming, P (11) 377*a*.
glass applications in, (7) 247*j*.
glass in, (5) 172*f*; (10) 338*j*.
image translation system employing optical fibers, P (11) 376*j*.
(initial current) measurement of cathode temperature, (6) 226*f*.
leadless inverted device forming process, P (11) 377*c*.
mechanism, for low temperature acoustic loss in magnetite, (1) 27*d*.
micro-, hybrid, second symposium, 1967, B (6) 242*f*.
network, thin film distributed RC, P (8) 284*b*.
properties, of CdS films, chemically grown, (8) 281*g*.
of $Pb_{1-x}Sn_xTe$, $Pb_{1-x}Sn_xSe$, and other IV-VI alloys, (2) 80*c*.
of Mo bronzes, (8) 298*b*.
of neptunium monocarbide and mononitride, (10) 353*a*.
surface and bulk, of Li-doped NiO, (4) 111*c*.
tunneling characteristics, in Al-Al_2O_3-Sb junctions, (8) 300*a*.
structure, of graphite, optical study, (2) 81*f*.
thermionic-field resistance maxima in metal semiconductor (Schottky) barriers, (9) 311*e*.
tunneling, Fowler-Nordheim, into thermally grown SiO_2, (9) 310*f*.
Electrons, affinities, ionization potentials, and screening constants: VII, comparison with Hartree-Fock calculations, (9) 323*g*.
barriers, formation on phosphor particles, P (9) 312*j*.
beam, apparatus for evaporation of low temperature semiconductor material, and means for draining electric charge from, P (4) 112*b*.
E-8 high-vacuum setup, (2) 62*a*.
for growing thin film semiconductors, P (4) 114*j*.
for measurement of potential distribution in semiconductor crystal, (5) 187*c*.
method of measuring diffusion voltage in semiconductors, (5) 187*g*.
for nondestructively measuring dielectric properties of sample, P (9) 315*i*.
scanning, anomalous transmission patterns, (8) 297*a*.
techniques in integrated circuits, P (10) 344*g*.
technique for measuring thermal conductivity, (8) 285*b*.
beam welders and lasers, characteristics and potentials, (11) 379*f*.
beam zone refiner, conversion to rf heating, (4) 119*i*.
density distributions, determination, effect of multiple diffraction, (11) 384*g*.
density distribution in TiC, X-ray study, (6) 240*b*.
emissions. See *Emissions.*
energization threshold, of phosphor particles, increasing, P (2) 65*c*.
energy distribution, tunneling through metal-insulator-metal sandwich structure, (8) 292*a*.
free, in ZnO, optical properties, (4) 147*b*.
hopping, in octahedral sites of Fe_3O_4, Moessbauer study, (9) 325*j*.
microprobe, to investigate enameling problems, (5) 171*g*.
microprobe, for quantitative analysis in oxide combinations, (9) 328*b*.
movement, in cathode sputtering, electrostatic control, P (4) 112*j*.
optical studies, of reaction processes between kaolinite and sodium carbonate, (8) 293*j*.
photoemission, from *n*-type degenerate Si in SiO_2, (4) 149*g*.
radioactive capture of positrons by, and use of Born approximation, (4) 111*e*.
slow, in ionic crystals, theory, quadratic approximation in, (10) 356*b*.
slow, use in transmission electron microscopy, (2) 71*d*.
transfer effects of disturbance by electrode transparency in electroluminescent diodes, (8) 281*f*.
transfer reactions, role of water in, (6) 237*a*.
transport, crystal-field model of, in sodium-vanadium bronze, (1) 17*e*.
trapped, spatial distribution, in γ-irradiated organic glasses, (8) 298*d*.
Electrooptic, coefficients, relation between linear and quadratic in $LiNbO_3$, $LiTaO_3$, and other oxygen-octahedra ferroelectrics based on direct measurement of spontaneous polarization, (2) 82*a*.
device with concentric arrangement of layers, P (8) 282*f*.
effect, in $Bi_{12}GeO_{20}$, (1) 33*g*.
effects, in paraelectric perovskites, (2) 76*g*.
logic device, four terminal, P (4) 113*f*.
Electrophoresis, continuous particle, for separation of clay minerals, (11) 380*g*.
deposition of enamel, (5) 171*e*; (9) 304*i*; (10) 337*a*.

Electrophoresis *(continued)*
electrophoretic mobility, of crystalline silica, effect of cationic polymers structure, (1) 28*d*.
forced-flow, for clay filtration, (1) 29*j*.
and industrial applications, (6) 220*g*.
Electrophotography. See *Photography*.
Electrostatic processes, coating apparatus, P (7) 246*f*.
coating, and surface preparation, (10) 337*b*.
for decorating glass and vitreous enamels for use in, P (7) 248*f*.
field, for metal silicate coating, P (7) 256*i*.
field effect, in epitaxial growth of gold particles evaporated onto NaCl, (6) 232*c*.
finishing, fundamentals, (7) 246*b*.
precipitation of dust, apparatus for, P (8) 284*d*.
separation of dry materials, P (11) 382*a*.
sorting, of granular materials, method and apparatus, P (1) 20*e*; P (2) 74*d*.
spray, at Philco-Ford, (7) 246*j*.
spray, vignetting or highlighting practices after application by, (7) 246*c*.
spray device, P (5) 186*f*.
spraying, (2) 67*a*.
of enamel, exhaust equipment developments for, (1) 4*a*.
of enamel on range ware, (1) 5*b*.
by hand gun, (1) 20*b*.
of vitreous enamels, (1) 4*i*.
Electrostriction, in perovskite-type, ferroelectric materials, calculation, (1) 16*b*.
Elements, ceramic, with honeycomb structure, apparatus for manufacturing, P (2) 67*g*.
TaC, for incandescent devices, P (7) 248*f*.
heating. See *Heating elements*.
Emeralds, characterization by visible and infrared absorption spectroscopy, (8) 289*c*.
Emission, and absorption phenomena in NaCl crystals with high concentration of copper, (6) 230*f*.
electron, from "cold-cathode" GaAs *pn* junction, (9) 310*j*.
electron tunnel, apparatus and methods, P (9) 312*f*.
from LiF during thermoluminescence, (8) 298*e*.
low-field microwave, from InSb, theoretical explanation, (9) 331*a*.
photo-, from Al-Al_2O_3 films in vacuum ultraviolet region, (11) 376*c*.
of electrons from *n*-type degenerate Si into SiO_2, (4) 149*h*.
of holes from Si into SiO_2, (4) 149*h*.
from InP-Cs-O, (1) 34*a*.
low work function (less than 1.0 eV), by InGaAs-CsO, (10) 344*g*.
properties of GaAs surfaces, effects of heat cleaning, (10) 343*j*.
spectral, in LiF, due to lattice vibrations, (8) 298*e*.
spectral, of transparent materials, radiation induced changes in, (4) 152*b*.
thermo-, of W alloyed with lanthanide oxides, (9) 332*j*.
X-ray. See *X rays*.
Emittance, high-temperature hemispherical, of uranium oxides at 0.65 and 0.70 μm, (6) 233*a*.
of opaque substance, effect of surface porosity, (6) 232*h*.
Emitters, field-enhanced thermionic, P (11) 376*f*.
photo-, negative-electron-affinity, low-work-function surfaces, (11) 385*e*.
preparation, for X-ray fluorescence analysis of powders, (6) 227*a*.
semiconductor light, and combination light emitter-photocell, P (11) 378*f*.
Emulsions, vitrifiable photosensitive, P (2) 61*a*.
Enameled ware, dishwasher, cost of enamel vs plastisol for coating, (1) 4*g*.
with patterned surface, P (10) 337*c*.
ovens, self-cleaning, (2) 45*h*.
pots and pans, origin to modern day, (5) 171*f*.
range, spraying electrostatically, (1) 5*b*.
utensils, evolution of sheet steel ware for, (6) 207*g*.
water solubility, (10) 337*c*.
Enameling, by coil coating, (7) 246*f*.
direct, research, (4) 93*h*; (6) 207*g*.
direct-white, improved steel for, (1) 4*d*.
dry process, foundry control improves, (2) 45*i*.
electrophoretic, technical problems, (5) 171*e*; (10) 337*a*.
equipment. See *Spraying*.
furnaces. See *Furnaces*.
inside of long tubes of small ID, physical conditions, (10) 336*j*.
multicolor, (6) 207*j*.
operations, water pollutants from, (5) 171*b*.
problems, use of electron microprobe to investigate, (5) 171*g*.
progress, (1) 4*a*.
single layer, direct-on, mechanism of adherence for, (10) 336*e*.
Enameling apparatus. See *Furnaces; Spraying*.
Enameling metals, aging of, (1) 3*j*.
aluminum, (11) 368*h*.
for architectural uses, (8) 275*b*.
cookware, streamlined at Mirro, (8) 275*b*.
in India, (2) 46*c*.
cast iron, effect of gases and development of gases during, (5) 171*g*.
cast iron bathtubs, partial mechanization suggestions, (5) 171*e*.
Enameling metals *(continued)*
cast iron bath tubes and stoves, (10) 336*h*.
coil steel stock, (8) 275*c*.
coiled steel, (5) 171*i*.
de-, chemical, of gray cast iron, (6) 207*f*.
direct-on, white, techniques, (5) 171*d*.
oven panels, self-cleaning, at Crown Stove, (11) 368*g*.
pickling. See *Pickling*.
preparation of sheet steel for, (1) 5*f*; (1) 5*d*.
pretreated steel sheets for, (7) 246*g*.
problems with heat-resistant steels, (10) 337*b*.
process using fluidized bed, P (2) 46*e*.
sheet, P (4) 94*b*.
sheet iron, process control in, (4) 93*c*.
sheet steel for single-coat method, P (4) 94*c*.
steel, P (7) 246*g*.
cost reduction through design of components using, (8) 274*i*.
low carbon, yield strength after firing, (8) 275*g*.
newly developed for appliances, (11) 368*i*.
stainless steel and Al surfaces for electrical insulation, P (9) 337*d*.
Enamels. See also *Coatings*.
acid and alkali resistant, for chemical industry apparatus, (5) 171*a*.
acid and alkali resistant, for chemical processing industry, improvement by use of oxides of transition elements, (10) 336*j*.
acid-resistant, electrocoating to steel, (7) 245*j*.
adherence to aluminum, (1) 5*b*.
adherence to steel, torsion test for determination, (2) 71*g*.
for aluminum, permanent color, (1) 5*a*.
aluminum-, interface, observed by electron microscopy, (10) 336*e*.
color, relation between particle size and firing temperature of, (11) 368*h*.
composite, P (8) 275*c*.
composition, for insulation of high-temperature magnet wire, P (8) 275*d*.
controlled deflection strainline test, (7) 245*i*.
cover-coat, solubility and aging behavior, (1) 4*e*.
crackle, application to copper, (6) 207*g*.
crystallizable, for glass-ceramics, P (6) 212*j*.
defects, direct-on cover coat, (7) 245*i*.
direct-on cover coat, adherence evaluation, (1) 4*i*.
dry process, apparatus for deposition on heated substrate, P (5) 171*i*.
dry process, nozzle applicator for, P (1) 5*f*.
electrical properties, (7) 245*j*.
electrodeposition for, (7) 246*h*.
electrophoretic deposition, (9) 304*i*.
frits. See *Frits*.
in form of thin layer, simultaneous measurement of thermal expansion, setting-temperature, and Young's modulus, (10) 336*g*.
on gas-fired heat exchanger, to beat corrosion, (1) 3*j*.
glass-crystalline, based on lithium metasilicate, (6) 207*i*.
ground coat and direct-on white, effect of cobalt and nickel in, (10) 336*g*.
for heat transfer surface, (1) 4*j*.
hot water tank, determining effective coverage, (7) 245*h*.
industry, cost accounting system, (1) 5*b*.
leaching, (1) 15*i*.
low temperature, combined with conversion coatings for retardation of corrosion of Be, (5) 171*c*.
low-temperature titania-opacified, (2) 46*a*.
manufacturing process, magnetic handling and purification equipment applied to, (1) 4*f*.
to metal, adhesion, investigation of test for measurement, (1) 5*e*.
one-coat, bubble structure and adherence, (5) 171*b*.
one-coat white, effect of water vapor in furnace atmosphere on, (8) 274*i*.
phosphorescent, (1) 4*i*.
powder, applicator for, P (6) 207*j*.
powders, surface modified electrostatic, and method, P (1) 5*f*.
properties, influence of iron oxides, (1) 7*j*.
satin finish vitrifiable, P (2) 54*a*.
semicrystallized ground coats, and enameled articles from, P (11) 369*c*.
sheet ground-coat, adhesion testing, (1) 5*e*.
sheet steel, composition, (1) 4*e*.
slips. See *Slips*.
technology, B (4) 168*i*.
TiO_2, stability of anatase in, (7) 246*i*.
one-coat, viscosity, (6) 207*h*.
-opacified, crystallization and phase transformation in: I, theory; II, comparison of theory with experiment, (4) 93*d*.
-opacified reflectance, (6) 207*f*.
-opacified, role of P_2O_5 in, (7) 246*h*.
toxic constitutents extracted from, according to proposed standard DIN 51166, (5) 171*a*.
use in chemical industry, (5) 171*h*.
for use in electrostatic method of decorating glass, P (7) 248*f*.
vitreous crystalline, influence of application process on crystallization of, (2) 45*h*.
white, effects of moist furnace atmosphere, (8) 274*j*.
Energy, activation, for hydrogen diffusion in thorium hydrides, (4) 126*d*.
Energy *(continued)*
activation, of silicate glasses, effect of melting aids, (2) 48*c*.
in sintering, (10) 349*h*.
for steady-state creep and self-diffusion in BeO, correlation between, (8) 289*f*.
bands, in BN, cubic, (4) 135*h*.
bands, in diamond, (4) 135*h*.
changes in dehydration processes of clay minerals, (7) 265*c*.
dissociation, of gaseous gallium monophosphide, (6) 231*h*.
of molecule BO_2, mass spectrometric determination, (9) 324*i*.
of AgF, (6) 234*i*.
of thallium monofluoride, (2) 76*i*.
of SnF and PbF, (10) 356*j*.
of TiO(*g*), (11) 383*i*,*j*.
elastic, release rate, measurement, effect of nonlinear Hertzian deformations and gage length on, (5) 193*i*.
of formation, of Schottky defects in cesium halides, (1) 29*f*.
of formation, of Schottky defects in ionic crystals, (1) 29*g*.
fracture, of glass, (9) 305*f*.
fracture surface, of glass, (4) 95*i*.
fracture surface, measuring by double cantilever method, critical analysis and discussion, (2) 47*f*.
free, of adhesion and equilibrium of contact reactions at solid-fluid interfaces: I, perfect solid and fluid, (1) 30*d*.
free of formation, of beryllium hydroxide (*g*), (4) 161*h*.
of chlorides and fluorides, (9) 321*i*.
of cupric oxide, (4) 136*e*.
of fayalite, (4) 129*j*.
of groups II–IV semiconductors, (4) 161*c*.
of NbO and Ta_2O_5, (8) 292*b*.
of palladium oxide, (4) 136*f*.
of ReS_2, (4) 136*g*.
of sulfides of transition elements and zinc, (1) 37*j*.
of UC and UC_2, (4) 157*h*.
internal strain, and strength of brittle materials, (8) 293*f*.
lattice, of cubic oxides, (1) 31*h*.
lattice, and heats of formation, of superoxides of K, Rb, and Cs, (1) 39*f*.
microscopic free, and order parameters of antiferroelectrics, (4) 144*j*.
optical wave, second harmonic, generation of, P (2) 65*a*.
photon, of GaAs in lightly doped limit, (9) 324*d*.
point-defect formation, in alkaline-earth fluorides, Born-model calculation of, (8) 288*i*.
quaternary excess free, and ternary phase diagrams, predicting using binary data, (10) 359*d*.
radioactive, sources, P (10) 345*a*.
relative, of [1100] tilt boundaries in Al_2O_3, (1) 36*c*.
structure, of B and BN, investigation by ultralongwave X-ray spectroscopy, (4) 141*c*.
surface, effective, of brittle materials, (6) 232*h*.
of glasses below transformation temperature, (11) 370*e*.
lowering by adsorption on alumina, (1) 31*j*.
ratio of grain boundary to, for UC, (6) 236*j*.
thermal, consumption, of glass furnaces, (2) 52*c*.
total, in brick and tile industry, (1) 11*g*.
transfer, and fluorescence processes in Bi^{3+} and Eu^{3+} activated YVO_4, (4) 135*i*.
mechanisms involving trivalent Er and Tb or Tm in sodium rare-earth tungstates, (4) 144*a*.
mechanisms involving trivalent Tb and Nd in sodium rare-earth tungstates, (4) 144*a*.
between trivalent rare-earth ions in inorganic solids, (4) 135*h*.
vacancy migration, in cubic crystals, calculation, (9) 318*a*.
volume free, of nucleation of crystalline phase from multicomponent regular solution, calculation, (6) 230*f*.
Engineering, helps doctors cure bedridden hospital patients, (9) 333*c*.
opportunities in, B (6) 241*c*.
properties, of inorganic coatings, (8) 274*j*.
and science, creativity, (1) 40*f*.
Engineers, in building materials, graduate program for, (9) 333*d*.
Engobes, colored bodies, and glazes, review, (4) 108*d*.
Enthalpy. See *Heat, content*.
Entropy, of aluminium(I) flouride(*g*), (1) 29*g*.
of $BeCl_2(g)$, $Be_2Cl_4(g)$, and beryllium(I) hydroxide(*g*), (5) 201*d*.
characteristic, of refractory Th compounds, (4) 128*f*.
configurational, of vitreous SiO_2 in random network theory, (4) 129*d*.
of GeO_2, tetragonal, (4) 135*b*.
high-temperature, of four crystalline sodium-calcium silicates, (5) 195*c*.
measurement techniques, and application to uranium compounds, (5) 200*j*.
for self-diffusion in KBr, (4) 135*a*.
for small classical crystals, (8) 292*b*.
-symmetry-volume relations, in polymorphs, (1) 39*a*.
Epitaxy. See *Crystallization*.

Equations, for concentration distribution in binary powder mixtures of variable compositions, (2) 67*d*.
empirical, in computing surface tension by sessile-drop method, verification, (1) 40*b*.
rate, of cement hydration, (11) 368*b*.
thermal diffusion flux, for zirconium hydride at high hydrogen contents, (2) 84*g*.
with two and three constants, for calculating viscosity-temperature data for silicate glass, (5) 172*h*.

Equilibrium studies. See also *Systems*.
equilibria, kyanite-andalusite and andalusite-sillimanite, experimental determination—aluminum silicate triple point, (7) 265*g*.
exchange, between condensed and gas phases, computer calculation applied to, (1) 26*i*.
ion-exchange, between glass and molten salts, (5) 172*j*.
oxidation-reduction, of dilute magnesiowustites, (5) 200*b*.
phase diagram, of Al_2O_3-ZrO_2, and examination of new phase of $9Al_2O_3$-$1ZrO_2$(ε-Al_2O_3), (2) 81*b*.
of bismuth trihalides at high pressure, (5) 198*g*.
for ceramists, 1969 supplement, B (11) 390*c*.
cupric oxide-molybdenum oxide, in air and in oxygen, (4) 130*f*.
of H_2O and D_2O at high pressures, (6) 235*g*.
Mn-O contribution to, at high temperature, (4) 129*i*.
of NH_4F, to 20 kbars, (4) 148*j*.
pseudobinary, of PuO_2 with Al_2O_3, BeO, and MgO, and pseudoternary PuO_2-ThO_2-BeO, (1) 35*d*.
relation to reaction kinetics and structure of glass melts, (9) 307*b*.
simple, locating field boundaries in, by means of discriminant functions, (8) 294*g*.
ternary, and quaternary excess free energy, predicting using binary data, (10) 359*d*.
U-UAs, (4) 163*b*.
phase equilibria, and characterization of β-alumina phases, (9) 319*a*.
of subsolidus phases bounded by $BaaMgSi_2O_8$, $Sr_3MgSi_2O_8$, and $Ca_3MgSi_2O_8$, (10) 353*g*.

Equipment. See *Machinery and equipment* and specific types.

Erbium, chloride, interaction with KCl in melts, (4) 140*e*.
Er^{3+}, ESR spectra, in $SrCl_2$ single crystals, (6) 232*c*.
Er^{3+} in II-VI compounds, EPR, host crystal effects on, (4) 138*i*.
ions, magnetically ordered, in $ErFeO_3$, relaxation phenomena in Moessbauer spectra, (2) 82*c*.
oxide, polycrystalline, cation self-diffusion in, (4) 128*d*.
polycrystalline, elastic properties, high-temperature measurements, (11) 384*h*.
polycrystalline, elastic properties, room temperature measurements, (10) 352*a*.
subfluoride, stability at high temperatures, (4) 143*d*.
systems. See *Systems*.

Erosion, of brick for cupola lining due to changes in atmosphere, (10) 342*g*.
of magnesite bricks, (4) 104*a*.
and mineralogical change of brick after service in cupola, (7) 251*d*.
resistance, of refractory concretes, influence of particle size, (8) 279*b*.
test, on ladle brick, observation by RI ^{45}Ca, (11) 373*d*.
test, on refractories immersed in molten iron, (10) 342*d*.
velocity, of steelmaking ladle brick, (7) 250*h*.

Etch, pits, orientation, variations in, on (111) surface of BaF_2, (8) 300*h*.
pits, rotation, on basal cleavages of apophyllite crystals, (1) 36*i*.
pitting, of CoO single crystals, (4) 121*j*.

Etching, of barite, (1) 26*c*.
effect on dislocations in oriented basal flakes of corundum crystals, (1) 27*h*.
electrolytically, semiconductor with single impurity gradient, P (4) 114*c*.
for forming leads on semiconductor devices, P (5) 183*c*.
gas, followed by gas plating, P (11) 376*g*.
gas phase, of sapphire with sulfur fluorides, (4) 137*c*.
gas phase, of sapphire: II, fluorinated hydrocarbons, (5) 194*c*.
of glass, and ion exchange, for increasing strength, (8) 276*a*.
glass-ceramics "Quasicerams," problem of inhibitors in, (4) 97*c*.
method, of manufacturing printed circuit boards, P (9) 312*h*.
rates, of dielectric films, measurement, (8) 281*i*.
refractory metal based materials uniformly along surface, P (4) 106*h*.
semiconductor material, P (5) 183*c*.
of Si through windows in SiO_2, (4) 137*h*.
SiC, P (5) 183*d*.
SiO, and etchant solutions for, P (6) 223*h*.
solution, method for machining fragile crystals, P (9) 314*h*.
structural, of chrome spinellids, (4) 156*f*.
of synthetic $BaSO_4$ single crystals, (10) 353*i*.

Etching *(continued)*
thermal, of ice, surface features observed during, (5) 200*g*.
vapor, simultaneous on one side of substrate with epitaxial deposition on opposite side, P (6) 223*h*.

Ethylamine. See *Amines*.

Ettringite, crystal structure, (9) 319*e*.
formation, on Al surfaces, (2) 44*b*.

Europium, -aluminum intermetallics, magnetic properties, (4) 110*f*.
divalent, luminescence in BaO-MgO-P_2O_5 system, (10) 356*d*.
Eu^{2+}-activated phosphors, efficient, new classes, (5) 200*c*.
activation in alkaline earth strontium phosphate compounds, (8) 292*d*.
in cubic and tetragonal phases of $BaTiO_3$, ESR, (2) 76*d*.
Eu^{3+}-activated phosphors, quantum efficiencies, measurement using excitation to selected Eu^{3+} levels, (5) 196*i*.
-activated sodium lanthanide titanates, fluorescence of, (5) 194*h*.
to Eu^{2+} transformation in CdF_2:Eu, EPR observation, (2) 77*a*.
fluorescence and cathodoluminescence, in alkali and alkaline earths with yttrates and gadolinates as hosts, (4) 136*a*.
ion as electron trap in glass, (1) 7*c*.
polarized spectra and crystal-field parameters, in YPO_4, (9) 327*i*.
relaxation processes, in Y_2O_3 and YVO_4 using pulsed cathode-ray excitation, (8) 297*i*.
Eu(III) and terbium chloride, interaction with Na and K chlorides, (7) 267*d*.
$EuAlO_3$, paramagnetic resonance of Cr^{3+} in, (11) 386*b*.
mono- and difluoride, stabilities, mass spectrometric studies at high temperatures, (5) 196*e*.
oxide, infrared transmission, magnetic birefringence, and Faraday rotation in, (10) 355*i*.
oxide, reflectivity and band structure, (11) 387*b*.
sulfide, selenide, and telluride, high temperature vapor phase growth, (9) 322*h*.
systems. See *Systems*.
trivalent, in YGaG, magnetic susceptibilities, (6) 234*h*.
valences in compounds, (10) 363*e*.

Eutectics, unidirectionally solidified NaF-NaCl, optical properties, (8) 276*f*.

Evaporation, of chromium carbides, (1) 38*c*.
coefficient, of BaF_2, (4) 163*f*.
coefficient, of praseodymium trifluoride, (10) 363*g*.
droplet, effects of electrostatic force, relative humidity, heating surface temperature, and size and shape on rate, (6) 224*f*.
evaporator, bakeable vacuum, for deposition of large area thin film circuits, (1) 20*i*.
flash, for formation of thick semi-insulating GaAs films, (5) 186*a*.
flash, of gold on NaCl and KCl substrates, unexpected effects of forced high nucleation densities by, (9) 311*i*.
mechanism, of NaCl single crystals, (9) 330*e*.
of PuO_2, hypostoichiometric, from 2070° to 2380°K, (1) 29*c*.
of semiconductor low-temperature material, by electron beam impingement on material, apparatus for, and means for draining electric discharge from materials, P (4) 112*b*.
of silicon oxide, nature of residual gases during, (2) 80*h*.
of UO_2 and UC, mass spectrometric study, (1) 32*j*.
of US-UO_2 mixtures; on attainment of equilibrium in Knudsen cells, (10) 362*i*.

Excitation, of polarons, (10) 353*j*.
of surface elastic waves by transient surface heating, (1) 29*d*.

Expansion. See also *Dilatometers*.
after-, of fireclay refractory, (4) 102*j*.
of clays, potential, (4) 120*b*.
of glass. See *Glass*.
ionization, of pile-exposed vitreous SiO_2, (11) 385*j*.
of MgO, radiation-induced, evidence for *F* center, (4) 152*b*.
measurement, at high temperature by X-ray diffraction, (11) 380*g*.
moisture, of full-size bricks, (6) 214*d*.
moisture: I, kinetics and mechanisms in literature, (9) 325*a*; II, dynamic measurement, (11) 380*i*.
thermal, anisotropy, of oxides and oxide solid solutions, (9) 332*c*.
of baddeleyite-corundum refractories, (6) 217*c*.
of BeO-SiC composites, (7) 251*j*.
coefficients of $Ba_{4+2x}Na_{2-2x}Nb_{10}O_{30}$, (11) 383*c*.
of high and low iron containing magnesite brick, (9) 309*c*.
high-temperature, of magnesite and chrome-magnesite bricks, (1) 12*e*.
of infrared-transmitting materials, (1) 39*c*.
of Kansas volcanic ash, (9) 317*b*.
of leucite group of minerals, (10) 362*d*.
low temperature, of alkali halides with CsCl structure, (2) 79*e*.
low temperature, of LiH, MgO, and CaO, (10) 356*b*.
measurement, for determination of firing

Expansion, thermal *(continued)*
temperature of ancient ceramics, (10) 347*e*.
measurement, simultaneous with setting-temperature and Young's modulus, of vitreous enamel in form of thin layer, (10) 336*g*.
of selenium and tellurium, comparison, (4) 129*e*.
of siliceous Kansas clays, (4) 160*f*.
of $AgNO_3$, X-ray determination, (4) 121*a*.
of sulfides of transition metals, (1) 39*d*.
of synthetic β-spodumene and β-spodumene–silica solid solutions, (1) 9*e*.
of two phase material, (4) 121*g*.
of VO_2 tetragonal phase, (2) 84*g*.
of ZrO_2, (8) 300*f*.
volume, coefficient, of glasses, measurement at high temperatures, (6) 210*a*.

Extraction, of alumina, by autoclave precipitation of basic sodium aluminum sulfate, (2) 72*i*.
of alumina from bauxite, P (1) 23*h*; P (4) 124*i*.
of berkelium values in tetravalent state using 2-thenoyltrifluoracetone, P (2) 67*i*.
continuous, of moisture from suspended matter, apparatus for, P (11) 379*d*.
of soluble metal complexes using amine solvents, P (2) 68*b*.

Extrusion. See also *Dies*.
clay, auger designs for, (4) 102*f*.
of claylike material, effects of die geometry, (6) 224*i*.
hot, of U-C alloys, (4) 138*d*.
of metallic carbides, particularly uranium monocarbide, P (6) 217*g*.

Faraday, effect, in ferrite garnets, effect of magnetic field, (2) 76*c*.
effect, of lanthanide ferrite garnets, (2) 77*c*.
rotation, in EuO, (10) 355*h*.
studies of *F* centers in alkaline earth oxides, (10) 353*b*.
studies in MgO and CaO color centers, (8) 292*g*.

Fatigue, behavior, high-strain, of nickel, effect of dispersed hard particles, (6) 232*b*.
dynamic, of soda-lime-silica glass, (9) 305*b*.
factors, occupational, affect quality and production control of firebrick, (4) 104*i*.
of fiber-reinforced aluminum, (1) 4*b*.
test, automatic temperature programer, P (2) 71*i*.
thermal, of solids in liquid metal, apparatus for measuring, (2) 68*e*.

Faujasite, Ca-exchanged, dehydrated, positions of cations and molecules, (2) 81*i*.
Ce(III) exchanged, crystal structure, (4) 130*g*.
crystals, number of hydroxyl groups at exterior surfaces of, (2) 81*b*.
dehydrated La-exchanged and hydrated Ca-exchanged, positions of cations and molecules in, (8) 296*a*.
high-silica, P (11) 382*e*.
reactions of phosphates with, (1) 26*a*.

Fayalite, composition, and standard free energy of formation, (4) 129*j*.
-magnetite-quartz assemblage between 600° and 800°C, (10) 353*c*.
paramagnetic, Moessbauer studies of Fe^{2+} in, (4) 145*g*.

Feeding apparatus, bulk solids, and pneumatic separator, P (7) 263*c*.
particulate materials, P (4) 118*a*.
slurry, P (11) 379*h*.

Feldspars, adularia and orthoclase, crystal structure, (5) 193*i*.
alkali, within Rader Creek pluton, Boulder batholith, Montana, zonal distribution of variations in structural state of, (4) 164*d*.
alkali, X-ray and optical study: I, determination of composition and structural state from refined unit-cell parameters and $2V$; II, X-ray method for determining composition and structural state from measurement of 2θ values for three reflections, (6) 239*g*.
analysis by atomic absorption spectrophotometry and hydrofluoric acid decomposition technique, (9) 314*j*.
barium, calculated powder patterns, (10) 350*h*.
commercial, behavior in ceramic casting slips, (6) 219*a*.
microcline, iron content of, (9) 325*h*.
natural alkali, nonequilibrium mixing in, (9) 325*g*.
oligoclase, annealing at high pressure, (10) 350*a*.
oxygen isotope and cation exchange chemistry, (4) 148*a*.
plagioclase, far infrared absorption spectra, (9) 321*c*.
rational analysis, (4) 121*b*.
sanidine crystalline solutions, mixing properties: III, calculations based on two-phase data, (11) 386*b*.
separation from granite, (8) 287*j*.
spinodal precipitation applied to exsolution in, (8) 298*h*.
study by high-temperature microscopy, (8) 298*i*.

Ferric, Ferrous, etc. See *Iron*.

Ferric oxide. See *Iron, oxide, ferric*.

Ferrites. See also specific types.
(2) 63*a*; P (6) 222*b*.
aluminum-containing, P (4) 115*j*.

Ferrites *(continued)*
barium-cobalt hexagonal, $BaCo_2Fe_{n}O_{3\pi}$, X-ray and microstructural study of phase relations during formation of, (9) 333*a*.
bodies, P (5) 183*d*.
bodies, joining by fusion bonding, P (4) 113*g*.
ceramic wafers, cut with coated tungsten wires, (4) 110*e*.
devices, dielectrically loaded parallel-plane microwave, P (5) 182*d*.
disorder in, (2) 61*i*.
export, from Canada, (6) 229*f*.
and ferric oxide, containing Bi_2O_3 additions, densification, (10) 343*j*.
with high temperature coefficient of initial permeability, (7) 254*h*.
hot-pressed fine-grained, high-frequency and microwave properties, (2) 62*e*.
with hysteresis loops of rectangular shape, method of improving switching coefficient, P (11) 377*b*.
magnets, P (4) 115*b*.
Mn, electron diffusion in, direct check by microwave technique, (1) 16*h*.
Mn-Zn, P (4) 114*b*.
cation diffusion coefficients and vacancy densities in, (1) 25*c*.
magnetic properties, effect of sintering conditions, (2) 62*f*.
with very high permabilities, (2) 63*g*.
$Mn_xZn_{1-x}Fe_2O_4$, X-ray and neutron diffraction studies on, (9) 333*b*.
manufacturing process: V, relation between grain structure and magnetic properties of Mn-Zn ferrite, (4) 110*h*.
materials, cadmium-substituted, P (7) 255*g*.
mixed-alkali: $K_xNa_{1-x}Fe_{11}O_{17}$, crystals, ion mobility in, (10) 356*d*.
monocalcium, Fe_2O_3·CaO, Moessbauer effect and neutron diffraction study, (1) 33*b*.
monocrystalline layers, spiral growth, (4) 155*j*.
Ni, containing cobalt, lead, and silicon, P (9) 313*h*.
and Cr-substituted nickel ferrite, Moessbauer study of ferromagnetic ordering in, (4) 145*h*.
internal fields, (4) 140*f*.
Ni-Fe, crystals grown by arc image furnace techniques, (4) 146*b*.
Ni-Fe, influence of stoichiometry on lattice parameter in, (10) 344*g*.
phase shifter, broadband reciprocal dual meander line, P (9) 312*c*.
phase shifter, reciprocal microwave, P (6) 223*a*.
powdered or sintered, P (2) 66*f*.
preparation, controlling atmosphere in, P (4) 114*i*.
reaction with tobermorite gel, (4) 152*i*.
rods, magnetized, dynamic mode surface waves on, (9) 310*i*.
single crystals, P (4) 114*b*.
with spinel structure, effect of hydrostatic pressure on magnetic anisotropy of ferrous and ferric ions in, (2) 76*b*.
spinel-type, in different compositions and in different states, X-ray spectroscopy, (4) 164*f*.
+2 valent metal yttrium and rare earth, preparation, P (7) 257*b*.
-type ceramic, can display color images, (4) 111*e*.
for use in pulse relay cores, production, P (5) 184*j*.
Zn, formation by hydrothermal method, (4) 136*c*.

Ferroelectric materials. See also *Barium, titanate; Ferroelectricity.*
ceramics, P (5) 183*j*; P (7) 256*h*.
with high permittivity, effect of high forming pressures on properties, (7) 254*j*.
lead zirconate titanate, internal friction in, (2) 63*c*.
crystallized glasses, properties, (2) 49*h*.
dynamic polarization, investigation, (2) 79*g*.
$LiNbO_3$, crystal growth, (1) 16*f*.
multidomain, stable remanence and memory, (5) 200*g*.
order-disorder type hydrogen-bonded, cluster approximations: I, small clusters; II, application to KH_2PO_4, (1) 26*d*.
with perovskite structure, partially *p*-conducting and partially *n*-conducting, ceramic bodies of, P (7) 255*i*.
perovskite-type, electrostriction and polarization in, calculation, (1) 16*b*.
powders, P (10) 345*j*.
Rochelle salt, doped, EPR spectra, effect of applied electric field on, (4) 132*h*.
$NaH_3(SeO_3)_2$ and $NaD_3(SeO_3)_2$ crystals, growth, (4) 137*i*.

Ferroelectricity. See also *Barium, titanate; Ferroelectric materials.*
and antiferroelectricity, in $BaTiO_3$, (1) 16*h*.
and antiferroelectric $Pb(Zr,Ti)O_3$ compounds, electrocaloric effects in, (1) 16*c*.
antiferroelectrics, microscopic free energy and order parameters, (4) 144*j*.
body, preparation by heating, and devices, P (9) 312*i*.
crystals, with hydrogen bonds, thermal conductivity of, (8) 300*a*.
crystals, KH_2PO_4-type, dynamic theory of phase transition in, (2) 75*j*.
domain structure of β-In_2S_3 "single crystals" due to ordering of In vacancies, (7) 265*g*.

Ferroelectricity *(continued)*
domain structure, of pigeonite and clinoenstatite, (11) 384*a*.
domain wall motion, in double Ni-Fe films, (4) 132*c*.
domains, Gunn, interaction with ^{71}Ga nuclei in GaAs, (11) 385*i*.
field effect device, bistable, P (5) 182*g*.
insulated-gate field-effect device, P (9) 312*i*.
nonlinearity, at ultrahigh frequencies, (2) 63*d*.
oxygen-octahedra, calculation of nonlinear optical tensor coefficients in, (4) 127*j*.
oxygen-octahedra, relation between linear and quadratic electrooptic coefficients based on direct measurement of spontaneous polarization, (2) 82*a*.
-polarization field effect, comment, (2) 75*d*.
properties, of $Pb(Sc_{1/2}Nb_{1/2})_{1-x}Ti_xO_3$ system, (1) 16*g*.
pseudo-, superconductivity in, (2) 83*d*.

Ferromagnetic materials. See also *Ferromagnetism.*
P (2) 64*f*; P (5) 182*a*; P (5) 185*d*.
CrO_2, P (5) 184*i*.
compounds, P (5) 183*a*.
element, for making fine line patterns, P (9) 313*a*.
eliminating magnetocrystalline anisotropy effect on spin resonance of, P (2) 65*i*.
ferrimagnetic, for use at frequencies higher than 50 MHz with reduced loss factor and higher quality factor, P (11) 376*f*.
ferrite, high permeability, P (5) 183*c*.
film, sharp thin, P (6) 223*j*.
and processes, P (10) 344*i*.
thin film, P (5) 185*d*.
thin films, magnetization ripple in, (2) 63*e*.

Ferromagnetism. See also *Ferromagnetic materials; Magnetic materials.*
anti-, local order, in single-crystal MnO above Néel temperature, (1) 31*i*.
anti-, in Ti_2O_3, (2) 74*j*.
couplers, employing transition from air dielectric wave guide to solid dielectric wave guide, P (4) 113*b*.
in crystals, and chemical bonds, B (4) 166*h*.
domain structure, of hematite, (1) 29*e*.
exchange coupling, in spinel lattice, (4) 136*d*.
in $LaNi_{1/2}Mn_{1/2}O_3$, (1) 29*g*.
ordering, in nickel ferrite and Cr-substituted nickel ferrite, Moessbauer study, (4) 145*h*.
weak, of $YCrO_3$, (4) 163*j*.

Fibers, asbestos, separation from foreign solids, P (5) 191*d*.
boron nitride, P (6) 217*h*.
carbon, high modulus, structure, (4) 156*g*.
high strength, high modulus, microstructure of, (4) 144*c*.
interstitial compounds with K, (9) 323*e*.
material, new, mechanical properties, (6) 216*c*.
Ni-coated, recrystallization, (9) 328*a*.
production and compositions containing, P (4) 107*e*.
structures, determination by ESR, (10) 351*j*.
ceramic and carrier, blending, P (4) 106*a*.
chrysotile asbestos, dispersion including monocarboxylic acid, (2) 74*a*.
glass. See also *Mineral wool.*
aminoalkyl silicone lubricant, P (11) 370*h*.
apparatus for producing, P (6) 212*g*.
bodies, including strands, P (8) 277*i*.
Canadian producer uses European techniques, (2) 49*e*.
chemical resistance, (2) 47*e*.
cloth, P (10) 339*d*.
coating, and fibers formed, P (11) 371*f*.
compositions, P (2) 52*h*.
with controlled torsional forces, P (6) 212*f*.
cooling, (4) 95*a*.
cord construction, P (8) 277*b*.
decorative product, P (11) 372*d*.
dulling with oxalic acid including pretreatment with calcium salts, P (2) 54*a*.
E-, strength, effect of batch carbon, (11) 369*e*.
E-, strength, effect of environment and temperature: II, heating and aging, (4) 95*c*.
elastomeric-, products and process and elements for use in, P (4) 98*c*.
flexibility, (2) 49*f*.
forming wtih combination resin coating, P (7) 248*g*.
forming tube for, P (9) 307*e*.
high strength, P (11) 371*a*.
impregnation method, P (6) 213*b*.
improved material and laminates of, P (9) 308*a*.
improving bonding characteristics, P (4) 100*a*.
magnesium aluminosilicate, for reinforcing plastics, P (1) 10*d*.
for manufacture of sheets or wicks, P (8) 277*f*.
materials, antistatic agents for, P (4) 98*c*.
method and apparatus for conveying and treating, P (8) 277*f*.
method and apparatus for producing, P (4) 99*h*.
nozzle with interior guide for producing, P (4) 100*d*.
opalescent, P (4) 100*e*.
optic device, sealing, P (8) 278*b*.
pad insulation, model for solid-phase heat conduction in, (9) 306*h*.
reinforced elastomers, P (5) 174*f*.
reinforced elastomers, and composition for

Fibers *(continued)*
sizing and impregnating such systems, (1) 10*e*.
reinforced resin impregnated mats, manufacture, P (2) 53*g*.
reinforced thermoplastic polyarylene polyether resin article, and process, P (6) 212*d*.
for reinforcement of cement products, (1) 7*e*.
for reinforcing asphalt roofing shingles, (2) 49*f*.
rodlike member, connecting to metallic terminal, P (11) 377*h*.
roving, spool, resin impregnating, P (9) 308*c*.
size, use of novel reaction product as, P (11) 372*b*.
sized with hydroformylated polymer and laminate from, P (5) 174*f*.
sized with polycarbonate, P (2) 52*i*.
sizing composition for, P (10) 340*a*.
sizing, with polybutadiene-dicarboxylic acid anhydride amino salt adducts, P (4) 101*b*.
staple, for manufacturing twisted fiber strands, method and apparatus, P (5) 175*b*.
strength, (2) 51*h*.
strength, statistical theory, (4) 97*g*.
systems, thermoelastic properties, theories predicting, (2) 47*g*.
tensile strength, relation with temperature of glass from which fiber is drawn and fiber diameter, (6) 209*f*.
treated bundles, and combination with elastomeric material, P (10) 340*a*.
and treatment for, P (8) 277*b*.
untwisted, for strongest laminates, (5) 174*a*.
vessel, with clevis joint, P (5) 176*d*.
graphite, direct production, P (9) 309*e*.
graphite-type, P (8) 279*j*.
high silica products, $NaCO_3$ treatment of, (10) 340*b*.
individual, separation from fibrous mass, means and method, P (5) 186*e*.
inorganic, (2) 79*d*.
inorganic, containing positively charged SiO_2 and fibrous potassium titanate, P (11) 375*a*.
metal, P (2) 59*d*.
metal or metalloid carbide, making by decomposing respective chloride in presence of carbon yarn, P (6) 217*i*.
Ni-coated carbon, recrystallization, (9) 328*g*.
-optic cable, comprising plurality of ribbons each with plurality of light conductive fibers, P (4) 98*e*.
-optic cable, comprising rows of interleaved light-conducting fibers, P (4) 98*f*.
optical, apparatus for coupling and amplifying between, P (2) 52*i*.
bundle coupling system, P (10) 339*g*.
for image translation system, P (11) 376*j*.
image-enhancing devices, systems, P (9) 307*d*.
system, image-transmitting, attachment for introducing light into, for illuminating object, P (9) 307*a*.
optics, BaO-Nb_2O_5-SiO_2 compositions for, P (11) 371*a*.
optics, fused quartz, for ultraviolet transmission, (5) 172*f*.
pyrolytic, method and appartus for manufacture, P (4) 106*e*.
refractory, P (4) 107*i*.
refractory, for service to 2700°F, P (9) 309*d*.
-reinforced materials, P (9) 309*c*.
reinforcement, of portland cement paste, mortar, and concrete, (5) 170*g*.
reinforcement, strengthening of ceramic parts, (1) 4*c*.
reorientation during mechanical working, (10) 342*b*.
silica, coated, method, and product produced, P (6) 213*c*.
reinforcement of aluminum, fatigue, (1) 4*b*.
weakening by heat treatment, (6) 211*j*.
SiC, P (9) 309*f*.
of β-SiC crystals, submicroscopic, with sheath of silica, P (2) 58*f*.
TiC and TiO_2, P (7) 252*f*.
whiskerlike, from chrysotile asbestos, (4) 124*e*.

Filaments. See also *Fibers, glass; Glass.*
alumina-coated, use in catalytic mufflers testing with single cylinder engine, (7) 260*e*.
boron, preparation in electrical discharge, P (7) 253*a*.
boron and tungsten, metal finishing, P (4) 118*h*.
carbon, high strength and high modulus, method and apparatus for manufacture, P (1) 14*g*.
coiled lamp, P (11) 371*c*.
current, in semi-insulating GaAs, (4) 147*c*.
filamentary materials, P (11) 375*a*.
filamentary metal structures, P (2) 65*f*.
of hexaboride of rare earth metal, for incandescent lamp, P (1) 18*i*.
high-modulus, high-strength, tension test method, (11) 381*a*.
lamp, assembling method, and support structure, P (2) 53*b*.
mono-, high-strength whisker-reinforced metallic, P (10) 342*e*.
pyrolytically coated, P (5) 179*d*.
refractory, apparatus for continuous formation, P (1) 13*f*.
refractory, high strength, P (8) 279*h*.
SiC, continuous vapor deposited, metallographic structure, (4) 110*g*.
support, single-ended electric incandescent lamp, P (1) 19*i*.

Filaments *(continued)*
TaC and Ta-alloy carbide, production, P (4) 107*b*.
wire, for use in cathode of thermionic valve, P (4) 113*d*.
Films, alkali halides, molten, periodic oscillations in, (9) 326*g*.
Al-Al_2O_3, photoemission from, in vacuum ultraviolet region, (11) 376*c*.
Al_2O_3, obtained by pyrolytic decomposition of aluminum alkoxide, deposition and properties, (4) 131*d*.
amorphous, ac conduction in, (8) 280*g*.
anodic, heat treatment on tantalum: V, thermal redistribution of incorporated phosphorus, (2) 78*a*.
anodic, nature, on cadmium in alkaline electrolytes, (4) 145*f*.
anodic oxide, deformation, (2) 75*c*.
heat-treatment on niobium, (2) 77*j*.
on Ti, Nb, and Ta, comparative studies, (8) 280*h*.
of antimony, epitaxial, production on disordered substrates, (5) 181*f*.
BaO, evaporated, ESR absorption, (8) 291*g*.
$BaTiO_3$, in rhombic phase, domain structure, (2) 61*j*.
black foam, adsorption of inorganic ions in, (9) 317*j*.
BN, for capacitors, P (4) 115*j*.
cadmium iodide, vacuum-deposited, structure, (2) 83*j*.
$Cd_xHg_{1-x}Te$, by cathodic sputtering, (4) 128*e*.
CdS, chemically grown, structure and electronic properties, (8) 281*g*.
CdS, electron bombarded, electron microscope study of transition from amorphous to crystalline condition of, (7) 265*b*.
CdTe, growth, properties at substrate temperatures at which the coefficient of CdTe condensation $\alpha<1$, (5) 199*d*.
(Cd,Zn)S photoconductive sintered layer, (4) 109*i*.
CaF_2, evaporated, dielectric relaxation and dc-temperature measurements in, (8) 281*b*.
carbon, deposited on ceramic core, apparatus for helixing path in, P (2) 64*f*.
carbon resistor, forming, P (4) 114*e*.
ceramic, for indicating maximum temperature, P (4) 122*a*.
CeO_2, evaporated, electrical properties, (7) 254*f*.
cermet, of Cr-SiO, electrical and structural properties, (4) 110*e*.
of compounds with at least two anions, forming by cathode sputtering, P (4) 114*f*.
condensation, on glass surfaces: I, investigation of possible promoters of filmwise condensation; II, reaction of quaternary ammonium compounds with surface hydroxyl groups; III, synthesis of novel quaternary ammonium compounds tested as possible promoters of filmwise condensation, (9) 305*h*.
conductive, closely spaced, P (11) 377*b*.
Cu_2O, on (111) face of copper, structural characteristics, (8) 298*b*.
crystalline, formation by laser evaporation, (5) 181*e*.
dielectric, etch rates, technique for measuring, (8) 281*i*.
electrical resistance, electroless formation, P (1) 18*e*.
EuO, doped with trivalent rare-earth oxide, magnetic and magnetooptic properties, (7) 255*d*.
fcc, bcc, and β-Ta, formation by evaporation, (8) 281*h*.
ferrimagnetic, making by cathodic sputtering, P (7) 257*e*.
ferromagnetic, sharp thin, P (6) 223*j*.
GaAs, epitaxial, effects of substrate misorientation in, (9) 320*d*.
epitaxial, propagation of growth striae in, (4) 151*e*.
thick semi-insulating, formation by flash evaporation, (5) 186*a*.
GaP, vacuum-deposited, polymorphism in, (1) 35*a*.
garnet, preparation by sputtering, (6) 220*j*.
germanium nitride, amorphous, preparation and properties, (9) 328*b*.
gold, chromium, and germanium alloy, for coating transparent articles, P (1) 11*e*.
growing, small angle filtered electron diffraction from, (4) 121*h*.
InAs, epitaxial, on InAs substrates, (4) 110*f*.
insulating, porosimeter for determining sizes of flaws in, in situ, (2) 70*e*.
interfacial amorphous, polarization structure, (6) 220*i*.
lead, growth on stainless steel, reflection scanning electron diffraction, (4) 153*f*.
PbSe, epitaxial, structure and growth, (8) 281*h*.
liquid, tension and contact angles between film and bulk liquid, (10) 362*i*.
luminescent, containing rare earth oxides, P (6) 221*j*.
magnetic ferrite, P (2) 65*e*.
metal, clean and oxidized, of Fe, Ni, and Pb, kinetics of interaction of sulfur dioxide with, (9) 324*b*.
discontinuous, use in determining rate of formation of very thin oxide films, (5) 188*e*.
-tungsten bronze, P (10) 337*a*.
metallic, deposited on polycrystalline garnets, bond strength of, (5) 180*f*.
Films *(continued)*
Ni, surface potential study of chemisorption of hydrogen on, (9) 330*i*.
Ni, vapor-deposited, on quartz glass, X-ray diffraction study of structure, (8) 281*j*.
Ni-Fe, double, domain wall motion in, (4) 132*c*.
nickel-iron-manganese ferromagnetic, sputter deposition, P (1) 19*a*.
nickel oxide, growth, role of structural defects in, (5) 181*j*.
NiO, nature of short-circuit diffusion paths in, (1) 33*h*.
niobium, high purity, formed by glow discharge cathode sputtering, P (6) 221*f*.
NbN, upper critical field H_{c2}, prepared by reactive sputtering, (11) 388*c*.
organic, detection on metal surfaces, (1) 4*f*.
oxide, and glass, chemical vapor deposition, apparatus for, (8) 280*j*.
on [100] and [110] iron surfaces, thermal regeneration, (4) 160*i*.
on Si substrates, X-ray dynamical diffraction effects of, (4) 111*i*.
sputtering, in plasma anodization of Al, (4) 111*a*.
phosphor, activation, P (11) 376*e*.
phosphosilica, on silicon substrates, nondestructive determination of phosphorus in, (4) 120*j*.
rare earth iron garnet, uniform, fabricating by sputtering, P (7) 257*c*.
resistor, appartus for making slab cuts in, P (4) 112*b*.
semiconductor, depositing, using thermal gradient, P (5) 182*b*.
semiconductor, thin deposited, modes of propagating light waves in, (10) 344*h*.
silica, dc reactively sputtered, charge phenomena in, (7) 254*f*.
deposition, P (8) 282*f*.
deposition by glow discharge technique, (2) 75*c*.
deposition by nitric oxide process, (4) 146*d*.
electron-gun-deposited, effects of heat treatment, (6) 220*f*.
nondestructive determination of thickness and perfection, (2) 81*b*.
P concentration profile and phase segregation in phosphosilicate glass on, (4) 149*d*.
phosphorus diffused in, measurement of distribution using ^{32}P as tracer, (8) 294*g*.
pyrolytic deposition in evacuated system, (9) 328*a*.
on silicon, cationic migration in, (4) 128*d*.
on silicon, characterization by electron microprobe and ellipsometry, (9) 311*f*.
sputtered, argon content determination by X-ray fluorescence, (8) 280*i*.
steam-grown, tracer evaluation of H_2 in, (4) 162*a*.
studies of Na in, by neutron activation and radiotracer techniques, (4) 157*b*.
thermal growth in water vapor-O_2-Ar mixtures, kinetics, (1) 31*f*.
thermally grown, fused glass penetration into, (1) 17*b*.
thermally grown, irradiation effect in, (9) 323*i*.
thickness measurements over small geometries, (9) 315*e*.
utilizing plasma, P (6) 224*a*.
silicon, deposition on single-crystal spinel substrates, (4) 131*e*.
and GaAs, chemically deposited epitaxial, growth and perfection, (7) 255*a*.
heteroepitaxy on stoichiometric spinel, (10) 354*e*.
stain, growth, effects of light and temperature, (9) 320*b*.
SiC, prepared in microwave discharge, optical and electrical properties, (5) 181*j*.
SiC, vapor deposited, properties, (4) 155*a*.
Si_3N_4, amorphous, preparation and properties, (4) 150*e*.
amorphous, properties, (1) 35*i*.
deposited by reactive sputtering, (4) 111*j*.
deposition by silane-hydrazine process, (4) 109*g*.
insulating, depositing, and electric devices incorporating, P (4) 114*b*.
prepared by silane-ammonia reaction, electrical characteristics, (5) 180*j*.
-SiO_2 mixtures, (4) 136*g*.
structure and Na migration in, (10) 361*g*.
thermally grown, properties, (1) 35*i*.
vapor deposited, properties, using SiH_4-NH_3-H_2 system, (4) 155*b*.
SiO, evaporated, properties, effects of ultraviolet irradiation, (6) 220*f*.
insulating, double, effects on electroluminescence of evaporated ZnS:Mn films, (4) 110*d*.
optical properties, effect of ultraviolet radiation, (1) 28*e*.
resistance-heated and electron-gun evaporated, physical properties, comparison, (1) 16*d*.
vacuum-deposited, annealing behavior in, (8) 280*i*.
vacuum-deposited, conduction processes in, (10) 343*h*.
$Si_xO_yN_z$, on Si, properties, (4) 151*j*.
silver, and Au, epitaxy on doped NaCl substrates, (2) 62*j*.
-Ge, vapor-quenched, structure, (9) 311*d*.
growth on KCl observed by LEED and Auger emission spectroscopy, (8) 281*i*.
halide, epitaxial, (8) 292*c*.
Films, silver *(continued)*
structure, evaporated on CaF and NaCl single-crystal substrates, X-ray investigations, (4) 164*e*.
steplike, of fater, on quartz surface, observation in polarized light, (6) 235*a*.
superconducting metallic, forming by vapor deposition, P (7) 257*d*.
surface oxide, mechanical properties, influence of electrical field on, (2) 45*i*.
surface oxide, mechanical properties, influence on oxidation mechanisms: I, vibrational technique to study nature and growth of thermally formed [Fe and Ni] oxide films on metals; II, mechanical properties and adhesion of surface oxide films on Fe and Ni measured during growth, (10) 355*a*.
thick, symposium proceedings, 1967, B (5) 204*d*.
thickness, acoustic wave analysis of operation of quartz-crystal monitors, (7) 254*e*.
apparatus for measuring and controlling, P (10) 346*f*.
determination of N_2 diffusion in ZrN, (5) 194*g*.
monitoring apparatus, P (1) 22*b*.
thin, alloy, interpretation of electron diffraction patterns, (4) 144*j*.
AlN, currents through, (9) 319*a*.
of Al_2O_3 and SiO_2, dielectric properties, (8) 281*a*.
analysis for Si, O, and Al by fast neutron activation, (8) 280*h*.
of barium lanthanum titanate, (2) 64*a*.
BN, preparation and properties, (5) 198*i*.
of CdS, oriented, from vapor phase reaction, (5) 181*a*.
cermet, preparation by electron bombardment evaporation, (5) 178*c*.
characterization by electron microprobe and ellipsometry—SiO_2 films on Si, (9) 311*f*.
Cr, Cr-SiO, and Cr-Si, phase composition, (9) 311*e*.
Cr-SiO, electrical parameters, stability, (9) 311*a*.
cobalt oxide, (5) 182*d*.
of controlled thickness, sputtering processes for depositing, P (1) 19*b*.
Cu oxides formed on, at elevated temperatures, electron microscopic observation, (8) 291*e*.
deposition on glass sheets at L-O-F plant, (10) 346*h*.
dielectric, prepared by cathodic sputtering of single-phase and multiphase materials, structure, (2) 63*g*.
evaporated dielectric, low frequency polarization effects in, (1) 17*e*.
ferrimagnetic garnet, growth, structure, and magnetic properties, (10) 344*b*.
ferromagnetic, P (5) 185*d*.
ferromagnetic, magnetization ripple in, (2) 63*e*.
grown on rough surfaces, measuring thickness and optical properties, (4) 120*g*.
InTe tetragonal, physical properties, characteristics, (5) 192*b*.
insulating, with large ionic space charge, theory of conduction through, (10) 362*b*.
lead, nucleation and growth on amorphous substrates, (2) 63*j*.
PbTe, crystalline structure, (8) 280*i*.
PbTe, vacuum-deposited, mobility studies, (8) 281*b*.
Mg, self-supported, heat oxidation, and structure, (8) 281*i*.
magnetic, electrodeposition, P (2) 64*e*.
magnetic, heat-treating in transverse magnetic field, P (2) 65*d*.
MnO, preparation and characterization, (4) 111*e*.
metallic, diffusion anomalies in, (10) 343*h*.
molybdenum, heteroepitaxial growth on insulating substrates, (1) 30*f*.
MoO_3, optical and photoelectric properties, (1) 34*b*.
of NpO_2, evaporated, cavities in, (8) 280*g*.
new binary oxide, deposition by pyrolytic decomposition of trimethylsiloxy-aluminum-isopropoxide, (5) 190*a*.
NbN and TaN deposited by reactive evaporation, (1) 17*g*.
noble metal, influence on Zr oxidation, (5) 195*c*.
oxide, mechanism of formation on Ni, (5) 196*j*.
oxide, preparation by pyrolysis method, (2) 63*c*.
of rare earth chalcogenides, vapor deposition method for producing, P (9) 313*e*.
Si, epitaxy on quartz, (9) 310*d*.
silicon-nitrogen compounds, produced by radio frequency glow discharge reaction, preparation and properties, (4) 150*g*.
SiC, amorphous, electrical conduction through, (2) 62*g*.
SiC, epitaxic growth, analysis by X-ray diffraction topography, (10) 349*j*.
SiO_2, electrograph method for locating pinholes in, (1) 21*h*.
SiO, evaporated, forming process in, (1) 30*c*.
silver, unexpected properties, (1) 15*d*.
standard, preparation by automatic stepping shutter system for electron microprobe analysis, (9) 314*i*.

Films, thin *(continued)*
thickness, measuring using interferometric-capacitance technique, P (5) 183*i*.
TiO_2, with large ionic space charge, conduction through, (10) 351*a*.
of type PbS_xSe_{1-x}, vacuum-deposited, (4) 163*c*.
vacuum deposition, possibilities of using in mirror making, (9) 306*g*.
vanadium (di-, sesqui-, and pent-) oxide, preparation, (5) 181*d*.
ZnS, transient phenomena in dc electroluminescence in, (8) 300*i*.
ZrO_2, (<2000 Å) thermally formed, transmission electron microscopy, (9) 332*d*.
tin oxide, study, (8) 280*h*.
titania, colored transparent durable, on glass, (5) 174*a*.
VO_2, preparation and properties, (5) 181*c*.
YIG, epitaxial on YAG, for generation of shear waves at microwave frequencies, (4) 111*i*.
YIG, narrow line width, epitaxial growth, (7) 254*g*.
Y_2O_3 and rare earth oxides on glass, preparation and properties, (8) 281*d*.
ZnO, stoichiometric, cathodic sputtering of, P (5) 182*i*.
ZnS, lead-containing, electroluminescence, (4) 134*i*.
ZnS:Mn, evaporated, electroluminescence, effects of double insulating layers, (4) 110*d*.
ZnTe, electroabsorption, (10) 344*a*.
ZrO_2, diffusion of oxygen in growing, (10) 352*g*.

Filters, aid products, perlite, P (7) 263*a*.
glass, optically neutral, calculation of transmittance, (6) 211*e*.
glass, method and apparatus, P (5) 174*d*.
radiation, P (4) 107*f*.
TE_{02} mode, for TE_{01} mode circular waveguide at millimeter wavelengths, (4) 111*c*.
utilizing glass balls for filtering fluids, P (4) 98*g*.

Filtration, basics, (10) 335*f*.
forced-flow electrophoretic, of clay suspensions, (1) 29*j*.
process, with scraping and blowback cake removal, P (2) 74*a*.
properties, of aqueous asbestos suspensions, effect of polyacrylamide, (1) 23*e*.

Fine ceramics. See *Whiteware.*

Firebrick. See *Refractories.*

Fireclay. See *Refractories.*

Firing. See also *Burners; Calcination; Combustion; Flames; Furnaces; Kilns; Sintering.*
of alumina in roller hearth kiln, (4) 105*h*.
brick, roofing tile, and stoneware, in reducing atmosphere, (4) 101*i*.
ceramic and refractory materials at various atmospheres at increased pressures, apparatus for, (2) 54*h*.
clay slate and clay, and kiln used, P (6) 228*g*.
earthenware bodies, (7) 253*h*.
enamel, survey of methods of testing strength of decarburized steel after, (1) 5*c*.
and furnace design fundamentals, and systems for heavy clayware, B (8) 302*c*.
high-temperature, effect on properties of magnesia brick, (11) 373*b*.
at high temperatures, problems, (10) 348*d*.
influence on strains in ceramic articles, (7) 253*i*.
jet, creates new tunnel kiln design, (4) 122*i*.
liquid-gas, conversion to, (6) 228*d*.
natural gas, in glass melting furnaces, B (11) 389*j*.
porcelain, role of gas medium in, (10) 343*d*.
pre-, of refractory materials, P (5) 179*a*.
rapid, of faceplates in roller kilns, (11) 372*e*.
rapid, requirements, possibilities, and limits, (11) 381*i*.
reactions in multiphase ceramics during, B (10) 366*d*.
temperature, of ancient ceramics, determination by measurement of thermal expansion, (10) 347*e*.
effect on photoluminescence in ZnSe(Cu,In), (1) 28*h*.
of enamel color, relation with particle size, (11) 368*h*.
uniformity, effect of tunnel kiln channel width on, (6) 228*h*.

Fission fragments, tracks in semiconducting layer structures, (4) 136*i*.

Fission products, effects of irradiation by, (2) 73*e*.
metallic, inclusions in irradiated oxide fuels, (5) 197*b*.
nongaseous, recoiled into graphite, escape behavior, (10) 341*f*.
segregation at surface of irradiated UO_2 particles, (6) 232*g*.
solid, variation, and gas swelling in U compounds with thermal neutron dose rate, (8) 300*g*.

Flame photometry. See *Photometry.*

Flames. See also *Burners; Firing.*
air-acetylene vs nitrous oxide-acetylene in atomic absorption spectrometry, Mg spinel interferences in, (8) 285*h*.
gas, characteristics, control of, P (2) 72*f*.
hydrogen/argon/entrained-air, interference effects in, (1) 21*c*.
$H_2+O_2+N_2$ premixed and diffusion, shape of Cr_2O_3 particles in, (6) 237*d*.
postaerated gas jets, P (7) 261*f*.

Flaws. See also *Defects.*
Griffith, and effect of porosity on tensile strength of brittle ceramics, (10) 354*h*.
in materials, ultrasonic pulse echo method and apparatus for detecting, P (10) 348*a*.

Flocculation, reversible, and redispersion of chrysotile asbestos, P (5) 191*d*.
of silica, crystalline, effect of cationic polymers structure, (1) 28*d*.

Flotation. See also *Beneficiation.*
of apatite, P (2) 74*a*.
beneficiation, of Cheyenne sandstone, (9) 316*c*.
froth, for impure carbonate sediments, (1) 23*f*.
kinetics, validity of equations for, (4) 163*c*.
of muscovite, from Alabama graphitic-mica schist, (10) 348*h*.
process, P (5) 190*i*.
simultaneous of silica phosphates and carbonate minerals, P (6) 230*c*.

Flow, capillary, technique, for measurement of surface tension of glasses, (6) 226*d*.
differentiation in xenolithic ultrabasic dikes of Cuillins and Strathaird Peninsula, Isle of Skye, Scotland, (4) 136*j*.
dynamics of non-Newtonian fluids between parallel plates and in noncircular ducts, (1) 27*c*.
effect on homogenization in glass in flat glass tanks, (6) 209*a*.
fluid, in system of parallel cylinders perpendicular to flow direction at small Reynolds numbers, (1) 29*i*.
hydromagnetic laminar, through conducting parallel porous walls, (1) 30*h*.
isothermal turbulent, of non-Newtonian fluids in pipes, (2) 69*d*.
liquid, equivalent value coefficients for, (1) 21*j*.
nonisothermal, of gases through packed beds, (4) 146*f*.
non-Newtonian, analog for, (4) 118*j*.
patterns, of gases in ceramic tunnel kilns by model techniques, (4) 122*f*.
properties, of calcium hydrate pastes, (11) 367*j*.
studies, on water models for kilns and dryers, (4) 119*g*.
surface, of adsorbed gases and vapors, (1) 38*i*.

Flue gases. See *Gases.*

Fluidization, progress review, (1) 20*g*.

Fluids. See also *Liquids.*
non-Newtonian, designing for: V, dynamics of flow between parallel plates and in noncircular ducts, (1) 27*c*; VI, isothermal turbulent flow in pipes; VII, heat transfer in laminar flow; VIII, heat transfer to; IX, mixing, (2) 69*d*.

Fluorapatite. See *Apatite,* fluor-.

Fluorescence, of Al-1-(2-pyridylazo)-2-napthol, quenching of for determination of Ni (II) and direct fluorometric determination of Co, (8) 284*j*.
of Al_2O_3, Rh-activated, (4) 110*g*.
analysis. See *Analysis.*
atomic, study on Fe, Co, and Ni, (8) 284*j*.
of barium octaborate, Eu^{2+}-activated, (10) 353*f*.
characteristic broad-band, concentration quenching, (10) 350*i*.
coherent, from ZnS excited by two-photon absorption, (2) 75*c*.
dye penetrant technique for displaying obscure structures in limestone, (1) 21*j*.
of Eu^{2+}-activated phases in binary alkaline earth orthosilicate systems, (10) 353*f*.
of Eu^{2+} in alkali and alkaline earths with yttrates and gadolinates as hosts, (4) 136*a*.
fluorometry for determination of Mg in presence of Ca, using 8-hydroxyquinoline-5-sulfonic acid, (5) 187*e*.
of garnets, Eu^{+3}-activated, containing pentavalent vanadium, (4) 136*b*.
glass standard for, P (4) 99*c*.
of Fe, Co, and Ni in reduced germanate glass, (5) 172*e*.
"mirror," and absorption, in MgO, (1) 32*i*.
near-infrared, of Co^{2+} and Ni^{2+} in MgO, (2) 80*h*.
processes, and energy transfer in Bi^{3+} and Eu^{3+} activated YVO_4, (4) 135*i*.
properties, of alkaline earth aluminates of type MAl_2O_4 activated by divalent Eu, (9) 321*g*.
properties, of Cd_4SiS_6 and Cd_4SiSe_6, (4) 109*i*.
quantitative X-ray, for analysis of geological samples using correction technique for matrix effects, (4) 121*a*.
of silicates and alkaline earth aluminates, Eu(II) activated, (9) 321*e*.
of sodium lanthanide titanates, Eu^{3+}-activated, (5) 194*h*.
U-activated materials, P (10) 346*b*.
of U-activated compounds with rock salt lattice, (10) 353*g*.
of zirconium pyrophosphate material, (6) 240*a*.

Fluorides. See also *Glass.*
alkaline-earth, Born-model calculation of point-defect formation energies in, (8) 288*i*.
with Ce(III)- or La(III)-alizarin fluorine blue in presence of dimethylsulfoxide, ultraviolet spectrophotometric determination, (1) 22*g*.
crystal structures: II, $MoOF_4$; III, $ReOF_4$, (8) 292*g*.
determination, rapid, in silicate rocks, (4) 121*b*.
effect as crystallization promoter in glasses

Fluorides *(continued)*
in system Na_2O-CaO-MgO-Al_2O_3-SiO_2, (6) 209*c*.
effect on surface "acid" sites on γ-Al_2O_3 and SiO_2-Al_2O_3, (8) 291*e*.
free energy of formation, (9) 321*i*.
in lanthanide series, crystal growth, (7) 264*f*.
melts, growth of complex oxide single crystals from, (8) 292*e*.
molten, solutions, infrared reflection spectra—hydrolysis of Ta(V) in potassium fluoride-lithium fluoride, (2) 79*c*.
reaction of kaolin with: III, hydrolysis of SiF_4 by kaolinite at elevated temperatures, (8) 287*a*.
salts of Li, Na, and K, solubility of Nb_2O_5 in melts of, (7) 269*b*.
systems. See *Systems.*
ternary, solid state study; synthesis, identification, relationships, and miscibility, (1) 37*g*.

Fluorination, of Be, kinetics, (4) 142*d*.
fluorinating agent, silicon tetrafluoride, (1) 36*d*.
of nuclear fuel with recovery of plutonium tetraflouride and uranium hexafluoride, P (6) 217*g*.
selective ClF, as method for processing nuclear fuel with separation of UF_6 and PuF_4, P (6) 218*c*.
of UO_2 pellets by F_2, kinetics, (5) 196*c*.
of UO, with bromine pentafluoride, engineering-scale studies, (5) 177*h*.

Fluorine, compounds, detection in air around smelting furnaces, (6) 226*g*.
compounds, with iron and monovalent cations, structural classification, and relation to magnetic properties, (6) 237*j*.
effect on properties of tricalcium silicate, (10) 359*a*.
removal from Al_2O_3 by steam, P (8) 288*c*.
separating from aluminosilicates by pyrohydrolysis, simple apparatus for, (6) 227*a*.
in silicate glasses, behavior, (2) 46*j*.
in silicate rocks and minerals, rapid determination, (8) 285*b*.
in silicates, determination, (4) 119*b*.
and silicon compounds, P (10) 349*b*.

Fluorite, coloration in, origin, (4) 147*g*.
crystals, with impurities of Sc, Y, and La, (10) 353*g*.
yttro-, from Japan, chemical studies, (8) 289*f*.

Fluorspar, analysis, (5) 186*j*.
ores, beneficiation, P (6) 229*c*.
thermal decomposition by water vapor, (6) 239*b*.

Fluxes, arc welding, P (4) 93*d*.
bonded welding, P (6) 207*b*.
welding, compositions, P (2) 46*d*.

Fly ash. See *Ash.*

Forming, process, in evaporated SiO thin films, (1) 30*c*.

Forsterite. See also *Refractories.*
ceramics, and their vacuum tightness, (6) 219*f*.
crystalline solutions, (7) 267*e*.
formation kinetics and mechanism, by solid state reaction of MgO and enstatite, (4) 142*j*.

Forums. See *Conferences.*

Fractionation. See *Separation.*

Fracture, analysis of strain at, in brittle solids with high densities of microcracks, (10) 349*h*.
behavior, of glass rods in oil jacket pressure tests with superimposed tensile stress, (9) 305*f*.
in brittle, crystalline solids, thermal decomposition produced by, (9) 320*c*.
controlled, of brittle solids and interruption of electrical current, (5) 180*f*.
delayed, of glazed porcelain, (2) 59*j*.
delayed, in SiC, (4) 130*i*.
of glass. See *Glass.*
mechanism, at high temperatures, conditions affecting, (2) 75*e*.
of metals, polymers, and glasses, B (1) 41*d*.
mode, of HfB_2 and ZrB_2, (4) 156*c*.
properties, of glass filled polyphenylene oxide composites, (2) 49*g*.
properties, Griffith criterion and thermal shock resistance of single-phase vs multiphase brittle ceramics, (7) 266*f*.
of refractories, (6) 214*i*.
of sapphire, (11) 385*b*.
strains, of technical refractories, (2) 55*g*.
studies, in glass-reinforced gypsum plaster using scanning electron microscope, (4) 91*g*.
surface layer, of brittle material by giant laser pulses, (10) 361*i*.
toughness, of electrical porcelain materials, (6) 219*i*.
toughness, of portland cement concretes, (10) 359*c*.
transgranular, studies on MgO bicrystals, (5) 202*i*.
transgranular and intergranular, in polycrystalline Al_2O_3, (11) 388*c*.
in WC-Co alloys, study by optical microscopy, (1) 32*e*.
work, of ceramics, important to toughness, (2) 85*b*.
work, in NaCl crystals containing cavities, (2) 84*f*.

Freezing, of Al_2O_3, volume change, (4) 163*i*.
point, measurement, of metal oxides with solar furnace, (7) 266*d*.
points, of lanthanide oxides measured with solar furnace, (4) 136*g*.

Freezing *(continued)*
pre-, cellular, and premelting phenomena in alkali halides, (7) 264*e*.
Freezing and thawing, tests. See *Frost resistance.*
Frequency, dependence, of ε and $tg\delta$ of sitalls containing compounds of Ce, Bi, and Pb, (2) 77*i*.
high, properties, of hot-pressed fine-grained ferrites, (2) 62*e*.
infrared absorption, of halides and oxides of heavier salts, (2) 79*a*.
resonant, methods for measurement of elastic constants of ceramics, (6) 226*b*.
Friction, constants for fused salts, (8) 292*c*.
internal, in alkali silicate glasses, influence of proton exchange, (6) 209*e*.
apparatus, improved, (9) 315*h*.
of basic refractories, temperature dependence of, (2) 78*j*.
of graphites, (4) 140*f*.
high-temperature, and transport mechanisms in sodium silicate glasses, (1) 7*g*.
in lead zirconate titanate ferroelectric ceramics, (2) 63*c*.
measurements in alkali silicate glass, electrical polarization during, (1) 6*i*.
of sheet glass under high stress, (8) 276*d*.
of sodium borosilicate glass, phase separated, at high temperatures, (4) 96*g*.
of sodium disilicate glass after ion exchange, (11) 370*f*.
studies of stabilization of sheet glass, (4) 96*h*.
in system $Pb_3MgNb_2O_9$-$Pb_3NiNb_2O_9$, (5) 180*g*.
reducing, on coated abrasive cloth and product, P (4) 90*a*.
and wear behavior of ceramics-cemented carbide couples, (5) 177*j*.
Frits, enamel, amperometric determination of Mo in, (2) 68*f*.
fusion flow test for calculating viscosity of, (6) 225*i*.
TiO_2 nucleated porcelain enamel, preparation, and white-enameled cast iron bodies prepared from, P (2) 46*a*.
zircon-containing glaze, high-temperature X-ray diffraction study, (10) 343*d*.
Frost resistance, of bricks and roofing tiles, influence of production methods on, (4) 101*h*.
of concrete, protected paste volume concept using new air-void measurement and distribution techniques, (5) 187*g*.
of glazed tiles, P (6) 220*c*.
of limestone in glaciogenic material in Lohja region, SW. Finland, (9) 325*i*.
Fuel cells, comprising metal oxide-containing solid electrolyte and electrode, P (4) 112*d*.
intermediate temperature, Zr phosphate membranes for, (4) 164*c*.
membranes, P (5) 179*b*.
past, present, future, (10) 344*d*.
Fuel elements, P (4) 106*g*; P (10) 342*d*.
ceramic, pore migration in, (8) 296*j*.
nuclear, P (2) 59*a*; P (10) 342*g*.
composite green structures for, P (7) 252*i*.
vibratory compaction method for fabrication, P (4) 108*b*.
for nuclear reactions, P (4) 106*g*.
nuclear reactor, P (2) 59*b*; P (5) 179*g*; P (6) 218*f*; P (7) 252*a*.
process, P (6) 218*j*.
Fuels. See also *Ash, fly; Combustion; Gases; Oil.*
BeO-dispersion, X-ray studies of radiation damage in, (4) 164*g*.
irradiated oxide, metallic fission product inclusions in, (5) 197*b*.
irradiated oxide, unknown constituent identification in electron-probe microanalysis of inclusions in, (2) 69*j*.
LP-gas, use, (2) 72*c*.
nuclear, Al_2O_3 and ZrO_2 coated particle, preparation, (5) 178*b*.
bodies, low permeability, P (2) 59*b*.
ceramics, thermal conductivity at high temperatures, (6) 217*b*.
cermet, preparation, P (2) 59*f*.
fluorinating, with recovery of plutonium tetrafluoride and uranium hexafluoride, P (6) 217*g*.
high temperature, B (7) 271*e*.
materials, P (8) 279*a*.
processing by selective ClF fluorination with separation of UF_6 and PuF_4, P (6) 218*c*.
sintered pellets, consisting of UO_2, P (2) 59*c*.
for nuclear reactors, P (4) 106*i*; P (6) 218*b*; P (11) 375*e*.
coated-particle, treating, P (2) 59*g*.
dense particles of oxides of actinides usable as, P (1) 14*e*.
graphite-base, fluidized-bed combustion of, (8) 278*j*.
particles, coated, for high-temperature reactors, (4) 103*j*.
particles, pyrocarbon- and silicon carbide-coated, mathematical model for calculating stresses in, (10) 341*a*.
pellets, irradiated UO_2, transmission electron microscopy, (8) 300*j*.
pellets, (U,Pu)C nuclear, synthesis and fabrication from U-Pu alloy, (10) 342*j*.
processing, in fluidized beds, (1) 20*b*.
reactor, influence of irradiation in nucleation of gas bubbles in, (5) 195*j*.
reactor, irradiated ceramic, processing, P (1) 14*d*.
Fuels *(continued)*
rods, cirene, facilities for in-pile tests of, (7) 260*d*.
savings, 40–80%, with recuperation, (8) 286*d*.
specification for plants, (9) 316*d*.
system, ternary, for power burst facility, irradiation testing (pulse conditions), (9) 308*i*.
thorium, cycle, proceedings of second international symposium, 1966, B (6) 242*a*.
UO_2, oxygen redistribution in, (8) 295*j*.
Furnaces. See also *Burners; Fuels; Glassmaking apparatus and equipment; Kilns; Ovens; Refractories.*
apparatus, with series of hearths, P (6) 228*f*.
atmospheres. See *Atmospheres.*
basic oxygen, refractory performance in, (4) 105*g*.
Bridgman type, hydraulic driving system for, (4) 120*b*.
carbon, electrode assembly, P (6) 217*i*.
carbon baking, P (9) 309*e*.
for ceramic dental products, P (7) 261*i*.
chemistry, P (2) 72*d*.
continuous, heat effect in, (5) 189*b*.
continuous heating, design and construction, (11) 381*g*.
conventional, adding preheat section to, (8) 275*f*.
design, and firing, of heavy clayware, B (8) 302*c*.
electric, with heating element of C or graphite for producing temperatures under high pressures, P (1) 23*a*.
with refractory brick of specific composition in critical wear areas, (1) 13*j*.
with replaceable liner tube sections, P (5) 189*a*.
electrical resistance, P (2) 72*g*; P (7) 261*h*.
enameling, box type, development and operation, (5) 171*c*.
enameling, U-type, development and operation, (5) 171*f*.
glass, construction, new trends in, (9) 306*b*.
electrical pot, with Kanthal-Super elements, (9) 305*c*.
electrode holder for, P (4) 98*c*.
forehearth, molten addition of colorant in, P (8) 278*d*.
gas fired frit melter, P (11) 371*g*.
heated by electricity, flow in, (8) 276*i*.
for heating electrically, P (7) 248*h*.
high pressure waste heat boilers, as energy supply for average sized container plant, (6) 209*h*.
joints, seal for, P (11) 372*b*.
large oil-fired container, temperature control of, (9) 307*g*.
melter, end-fired, temperature distribution in, (1) 9*e*.
process dynamics, following step change of batch component, (11) 370*c*.
suspended skimmer wall, P (1) 10*c*.
thermal energy consumption, (2) 52*c*
with two separate throat passages, P (5) 174*g*.
use of waste heat from, to generate electric power, (9) 316*d*.
wall arrangement, P (8) 277*c*.
glass bending, P (6) 212*b*.
glass bending, with partitions defining separate longitudinally disposed heating areas, P (10) 339*a*.
glass container, factors affecting stack emissions from, (10) 338*j*.
glassmelting, P (5) 174*i*.
electrical, patents on, (9) 306*d*.
for flat glass, P (1) 11*b*.
glassmelting electrodes for, P (4) 123*a*.
insulation, (9) 308*j*.
natural gas firing in, B (11) 389*j*.
with vacuum feed means, P (6) 212*e*.
glassmelting tanks, electric boosting, (2) 48*e*.
emptying and removing contents at end of campaign, (6) 209*g*.
natural gas burners with added compressed air for heating, (9) 306*a*.
wall construction for, P (7) 249*g*.
glass tank, arrangement and method, P (11) 371*g*.
automatic control problems, (5) 173*j*.
container, converting from oil to natural gas firing, (9) 305*f*.
continuously operating, waste heat boilers for, (6) 211*i*.
day, economics and application, (2) 48*j*.
discontinuous control of molten glass level in basin of, (2) 48*g*.
with greater transverse heat conduction, P (1) 10*g*.
heavy-oil-fired regenerative, with operating pressures of 10 and 30 atm, waste heat boilers attached to, (6) 211*h*.
joint corrosion and upward drilling in, physical and chemical reactions leading to, (9) 306*e*.
mathematical model, (4) 96*b*.
plate, heating with natural gas, (9) 306*h*.
refractories, advances, (1) 5*i*.
residence time of combustion gases in, (9) 307*b*.
response to variations in batch composition, (1) 8*f*.
on stream, world's largest in Calif., (2) 50*j*.
with graphite heating element assembly, P (1) 23*b*.
heat-treating, burner tube assembly for, P (5) 189*g*.
Furnaces *(continued)*
heat-treating, hearth for, P (5) 189*b*.
high pressure, P (5) 189*d*.
high temperature, P (4) 123*a*.
with hydrogen atmosphere, corundum ceramics for, (2) 54*h*.
multiple hearth, P (4) 123*b*.
for neutral or oxidizing atmosphere, (9) 316*c*.
for X-ray diffraction analysis of melts, (2) 69*i*.
induction, P (1) 14*c*.
with composite lining of refractory brick, P (1) 14*d*.
construction, P (6) 217*c*.
induction crucible, comprising rammed crucible, P (10) 348*d*.
industrial, optimum operating point, and determination as exemplified by enameling U-kiln, (11) 368*i*.
laboratory, automatic temperature control for, (2) 68*j*.
laboratory, temperature regulation to 800°C with accuracy of ±0.02°C, (1) 22*j*.
linings. See *Refractories.*
metallurgical, P (6) 217*e*.
mineral wool, P (4) 122*j*.
moisture control, use of neutrons for, (1) 3*e*.
muffle, conditioned atmosphere, P (4) 122*j*.
ovens, rotary clinker, automation; automatic control system for combustion air flow in long ovens operating on wet process principle, (10) 336*a*.
plasma, for single crystal growth of ultrarefractory materials, (1) 20*e*.
refractories for. See *Refractories.*
rocking electric tube, P (4) 123*b*.
roofs. See *Refractories.*
rotary, cooling and suction device of, with burner on one side and distributor of material on other, P (8) 286*f*.
rotary, tagged atoms to study movement of material and dust formation in, (1) 8*f*.
rotating telescopic sectioned, P (7) 261*h*.
shuttle hearth, P (1) 23*b*.
SiC, and plants, P (6) 218*f*.
solar, fusion, for growth of NiO single crystals, (7) 266*g*.
growth of UO_2 crystals by, (7) 270*e*.
measurement of freezing points of metal oxides with, (7) 266*d*.
for measuring heating curves and melting point, (5) 187*h*.
use for fundamental research in system ZrO_2-CaO, (5) 194*j*.
strip heating, preformed refractory block for, P (1) 14*c*.
tooling design for heavy loading, (8) 275*b*.
tri-arc, for Czochralski growth with cold crucible, (5) 188*b*.
tunnel, and ovens, method and device for improving temperature equalization of gases in, P (8) 286*f*.
Fuses, precision electric, P (1) 18*c*.
Fusion, effect on thermoelectric force of silver halides, (6) 232*d*.
in porcelain glazes, (6) 219*i*.
of $ZrTe_5O_8$, (1) 30*e*.

Gadolinium, Gd^{3+}, in orthorhombic and rhombohedral phases of $BaTiO_3$, ESR, (2) 76*d*.
Gd^{3+} in YVO_4 and YPO_4, determination of parameters for, from variable-frequency EPR, (8) 290*j*.
Gd^{3+} in YVO_4 and YPO_4, zero-field resonance, (8) 301*a*.
$GdAlO_3$, crystal growth, (7) 264*g*.
Gd:CaF_2, photochromic, photoconductivity of, (10) 358*f*.
$GdFeO_3$ type, crystal strurture, (2) 75*h*.
mono-, and difluoride, stabilities, mass spectrometric studies at high temperatures, (5) 196*e*.
oxide, as host material for solid state laser device, P (5) 185*b*.
oxygen diffusion in, (10) 358*g*.
retention of additives in, (5) 199*e*.
structural stabilization with WO_3, (8) 298*c*.
phosphate-vanadate, structure and luminescence, (4) 156*h*.
sesquisulfide and monosulfide, preparation and physical properties, (6) 236*h*.
trivalent, ground-state splitting, in $ZrSiO_4$, $HfSiO_4$, and $ThSiO_4$, determined by ESR, (11) 385*c*.
Gages, contact, for rapid and accurate three-dimensional grain size measurement of loose sand particles, (11) 380*a*.
gaging system, nuclear, for moisture content of irregular stream of bulk material, P (6) 228*b*.
length, and nonlinear Hertzian deformations, effect on measurement of elastic energy release rate, (5) 193*i*.
semiconductor strain, P (4) 116*h*.
shear strain responsive strain, elements, and circuits for using, P (10) 348*a*.
solder-bonded semiconductor strain, P (9) 314*c*.
Gallium, antimonide, and arsenide, high-temperature heat contents and heats of fusion, (10) 362*g*.
antimonide, electroluminescence and crystallographic polarity, (9) 321*f*.
single crystals, effects of back-melting on dislocation density in, (5) 194*a*.
single crystals, growth by floating zone technique, (5) 181*f*.

Gallium, antimonide *(continued)*
single crystals, prepared from nonstoichiometric melts, (1) 30*e*.
arsenide, absorption coefficient at microwave and millimeter wave frequencies, (1) 24*g*.
for bulk oscillators, (7) 254*j*.
chromium-doped high resistivity, optical absorption in 0.6 to 1.5 eV range, (1) 33*g*.
crystals, grown from silica boats, photoluminescence study of thermal conversion in, (7) 255*h*.
doped with Cr, obtained by epitaxy in liquid phase, (10) 354*g*.
epitaxial deposition in argon atmosphere, (4) 135*c*.
epitaxial deposition, from atmosphere of hydrogen and Ga_2H_6+$AsCl_3$+AsH_3 vapors, P (2) 64*e*.
epitaxial deposition in holes, (2) 82*j*.
epitaxy on vacuum-cleaved rock salt, (7) 265*e*.
field-ionized bulk, laser action in, (1) 31*g*.
and $GaAs_{1-x}P_x$, epitaxial deposition, multiwafer growth system for, (9) 311*b*.
high-purity epitaxial, far-infrared photoconductivity in, (8) 292*f*.
hole deposits, faceted, effects of vapor composition on growth rates, (10) 352*j*.
inhomogeneities in, study with scanning electron microscope, (7) 255*b*.
interaction of Gunn domains with ^{71}Ga nuclei in, (11) 385*i*.
laser transition and photon energy, in lightly doped limit, (9) 324*d*.
microwave dielectric constant of lattice, temperature dependence of, (4) 159*b*.
n-, modulation of optical absorption at intrinsic edge by acoustoelectric domains in, (1) 33*b*.
oxidation, (1) 34*a*.
phosphide, phosphorus-rich, nitrogen isoelectronic trap in, (9) 311*d*.
photoexcited, current oscillations in, (9) 310*f*.
photoexcited, current oscillations by two bulk negative-resistance effects in, (9) 310*e*.
polarization and intensity of Raman scattering from plasmons and phonons in, (4) 150*c*.
pressure sintering, (6) 236*j*.
semiconductor materials, activation analysis of trace contaminants in, (5) 186*h*.
semi-insulating, CO_2 laser radiation absorption in, (9) 318*b*.
semi-insulating, current filaments in, (4) 147*c*.
single-crystal, on insulating substrates, (1) 17*d*.
single-crystal, scintillation detector using, P (4) 116*j*.
substrates, semi-insulating, epitaxial InAs on, (2) 77*a*.
surfaces, photoemission properties, effects of heat cleaning, (10) 343*j*.
third order elastic constants, (4) 162*i*.
chloride, interactions with Be, Mg, Ca, and Ba chlorides, (4) 140*c*.
chloride, interaction with C, Si, Ge and Ti tetrachlorides, (8) 293*c*.
in clay minerals, geochemistry, (1) 30*h*.
films. See *Films*.
gallioisilicates, crystalline, P (6) 229*c*.
$GaAs_{1-x}P_x$, epitaxial growth on germanium substrates, (9) 310*b*.
large area epitaxial growth, for display applications, (9) 310*g*.
vapor-deposited epitaxial, preparation and properties using arsine and phosphine, (1) 35*h*.
$Ga_xIn_{1-x}As$, epitaxial, preparation, (4) 150*j*.
β-Ga_2O_3, Dy^{3+}-activated, luminescence, (4) 143*e*.
homogeneous distribution in single crystal YIG, effect of pressure, (11) 384*j*.
monophosphide, gaseous, dissociation energy, (6) 231*h*.
phosphide, crystallization, from stoichiometric melt in Ga solution, (8) 290*f*.
crystals, grown from Ga solutions, vapor phase and liquid phase epitaxial deposition, defect structure, (10) 351*g*.
crystals, grown by VLS mechanism with Ga as liquid-forming agent, morphology, (7) 267*e*.
crystals, Li-diffused Mn-doped, EPR detection of triple Li ion centers in, (10) 353*f*.
crystals, large, solution grown, preparation and properties, (4) 111*d*.
crystals, pulled by liquid encapsulation method, (5) 187*i*.
crystals, pulling by liquid encapsulation, (7) 255*a*.
dendritic crystals, with grown-in *pn* light emitting junctions, P (5) 185*c*.
epitaxial, preparation and properties, (4) 150*f*.
N_2-doped, solution growth, P (11) 379*b*.
oxidation, (1) 34*a*.
preparation in bulk ingot form, (4) 123*j*.
solution-grown, *p*-type, anomalous electrial properties, (9) 318*d*.
single crystals, large, growth from stoichiometric melt, (4) 137*i*.
synthesis and epitaxial growth, by fused salt electrolysis, (10) 362*a*.
Zn- and Cd-doped, epitaxial growth by $GaCl_2$ vapor transport, (10) 353*e*.

Gallium *(continued)*
sulfide, cooled homogeneous crystal, electroluminescence from, P (8) 282*f*.
sulfide and Ga_2Se_3, crystals, synthesis and growth in Ga and In melts, (6) 238*g*.
systems. See *Systems*.
Garnets, $[A^{2+}{}_3]$ $[Te_3]$ $(B^{2+}{}_2)$, preparation, (2) 82*b*.
almandine, stress effects around quartz inclusions in, and piezothermometry of coexisting aluminum silicates, (7) 269*j*.
cobalt ($Co_3Al_2Si_3O_{12}$), high pressure synthesis and stability field, (6) 233*h*.
coexisting with biotite and cordierite, distribution of Mg and Fe in, (7) 265*g*.
compositions, P (4) 113*h*; P (8) 282*i*.
Eu^{3+}-activated, containing pentavalent vanadium, fluorescence, (4) 136*b*.
$Eu_3Fe_{1.95}Ga_{3.05}O_{12}$, cation distribution in, (4) 127*i*.
ferrimagnetic light transmission, P (9) 312*h*.
ferrite, effect of magnetic field on Faraday effect in, (2) 76*c*.
fluorescent, compositions, and optical maser devices using, P (2) 64*g*.
gadolinium iron, chemical interaction with fused quartz, (4) 128*c*.
grossularite-spessartite series, synthesis, (8) 299*f*.
growing, on nongarnet single crystal, P (6) 221*d*.
hydro-, new synthetic, (4) 146*i*.
isomorphic impurity distribution in, as function of solubility of trivalent oxides in molten salts and of method of crystal growth, (10) 356*d*.
lanthanide ferrite, Faraday effect and reversal of magnetic sublattices, (2) 77*c*.
lanthanide ferrite, magnetic properties near Curie point, (2) 80*c*.
mixed cation iron, growth in ytterbium-gallium and yttrium-calcium silicate systems, (10) 354*i*.
polycrystalline, bond strength of metallic films deposited on, (5) 180*f*.
rare earth iron, magnetostriction constants, (1) 32*g*.
single crystals, seeded growth from molten salts, (7) 259*b*.
spinel-type, of different compositions and in different states, X-ray spectroscopy, (4) 164*f*.
Sr rare-earth hydro- and germanate, (7) 269*a*.
structure, new compounds with, (7) 267*f*.
Tb and Ho ferrite, single crystals, magnetostriction at low temperatures, (2) 80*h*.
yttria-alumina, spectroscopic determination of trace impurities in, (2) 70*j*.
yttrium alumina, crystals, production, P (6) 222*g*.
yttrium aluminum, single crystals, optical quality, rare-earth activator ions in, (10) 355*a*.
yttrium-gadolinium-aluminum, single crystals, growth and laser characteristics, (9) 322*e*.
yttrium gallium, magnetic susceptibilities of trivalent Eu in, (6) 234*h*.
yttrium iron, conditions of hydrothermal synthesis, (7) 264*b*.
delay lines, optical probing of magnetostatic modes in, (4) 147*j*.
dense ferrimagnetic perovskite allotropic form, possible existence, (1) 17*h*.
flux-grown, model for Fe^{2+}-Fe^{4+} equilibrium in, (9) 325*i*.
magnetized, dynamic mode surface waves on, (9) 310*i*.
magnetoelectric effect in, (9) 310*j*.
rods, longitudinal magnetoelastic waves in, (6) 232*e*.
single crystal king size, growing, (2) 62*i*.
single crystals, growth, (7) 258*h*; (10) 354*j*.
single crystals, improvement in yield, (7) 255*b*.
Tb-doped, spin-magnon relaxation in, (4) 155*g*.
zirconium and titanium, synthetic, (4) 158*g*.
Gases, access to porosity of graphite at high temperatures, (9) 317*j*.
adsorbates, effects on compaction of ultrafine active alumina powder, (7) 253*g*.
adsorbed, surface flow, (1) 38*i*.
cold, high-grade ionization in, (5) 189*c*.
combustion, residence time in glass tank, (9) 307*b*.
content of glass, effect of alkaline-earth metal sulfates and nitrates, (6) 208*h*.
diffusion, in transition region, effects of structures of porous solids, (4) 133*g*.
discharge, sintering in, (9) 329*g*.
effect on enameling of cast iron and development during enameling, (5) 171*g*.
effect on sheet steel surfaces, (10) 336*i*.
flue, desulfurization by limestone-dolomite processes, (1) 20*c*.
flue, SO_2 in, and desulfurization by compounds of alkaline-earth metals, (7) 261*c*.
inert, migration in ionic crystals, (9) 324*g*.
liquid, source, distribution, supplies, and prospects in Germany, (6) 228*e*.
mixtures, polyatomic, heat conduction through, (7) 261*c*.
molecular reorientation in, (9) 325*b*.
natural, (7) 261*c*.
oxidizing, preheating, reactant in TiO_2 pigment manufacture, P (9) 317*a*.
release, from irradiated nonfissile ceramics, (1) 13*b*.
residual, nature, during evaporation of silicon oxide, (2) 80*h*.

Gases *(continued)*
in seed, composition, effect of arsenic on, during refining of glass, (7) 247*d*.
-solid reactions, in industrial fluidized beds, (2) 67*h*.
temperature equalization, method and device for improving, in tunnel furnaces and ovens, P (8) 286*f*.
thermal evolution from minerals and rocks, measuring and sampling into gas chromatograph, apparatus for, (2) 68*g*.
Gels. See *Colloids; Silicon, dioxide; Tobermite*.
Gems. See also *Stones*.
-stones, synthetic, P (6) 224*c*.
Generators, electric flame, P (8) 286*d*.
electron beam, lanthanum hexaboride cathode system for, P (7) 256*g*.
glass furnace, refractories for, (4) 105*f*.
magnetohydrodynamic, composite electrode for, P (6) 221*c*.
microwave, P (10) 345*h*.
thermoelectric, graphite coating composition for, P (1) 18*f*.
Geochemistry, of boron and gallium in clay minerals, (1) 30*h*.
of coexisting brines, The Sabkha, Trucial Coast, Arabian Gulf, (8) 286*h*.
of differential leaching and element agglutination processes, (1) 34*j*.
of metamorphic marbles of French Massif Central, (1) 30*g*.
problems in evolution of ocean, (8) 292*d*.
of rocks, deep-seated, in Australian shield, (4) 137*d*.
Geology, Edwards formation (Lower Cretaceous), Texas—dolomitization in carbonate platform system, (7) 262*b*.
Eocene succession in Fawley Transmission Tunnel (Southampton Water, England), (4) 135*b*.
field methods for exploration and opening of raw materials deposits for clay, glass, and ceramic industries, (5) 190*c*.
of gypsum in southwestern Indiana, (4) 123*d*.
kaolin deposits at Lohrheim near Dietz an der Lahn, (7) 262*e*.
and mineral resources of Washington County, Indiana, (9) 316*j*.
Norra Karr alkaline body in southern Sweden, genesis, (4) 146*a*.
Geometry, of refractory metal dioxides, (4) 137*f*.
Germanates, comparative crystallochemical systematics and morphotropic transformation of silicates and, (4) 129*c*.
with garnet-type structure, hydrothermal synthesis, (7) 267*b*.
polygermanatosilicate melts, evidence of monomeric structures in, (7) 265*f*.
Germania. See *Germanium, dioxide*.
Germanides, of ceric group and yttrium rare earth metals, physical properties, (5) 198*c*.
Germanium, amorphous, electrical conduction in, (8) 281*f*.
bodies, coatings on, P (7) 256*a*.
bodies, formation of coatings on, P (1) 18*e*.
dioxide, amorphous, P (10) 349*b*.
hydrothermal investigation, (10) 355*e*.
influence on polymorphism of ZrO_2, (7) 267*b*.
single crystals, hexagonal, flux growth and characterization, (9) 321*h*.
tetragonal, entropy, (4) 135*b*.
thermal behavior, (1) 39*i*.
transformation, role of catalysts in, (6) 237*a*.
epitaxial growth, on single crystal spinel, (4) 135*c*.
Ge^{4+}, spinel phases containing, ligand field effect and structure, (10) 356*g*.
$GeFe_2O_4$, measurement of trigonal field splitting of Fe^{2+} in, by Moessbauer effect, (4) 143*e*.
oxide, kinetics of transformation, (4) 142*g*.
oxygen distribution coefficient in, (11) 383*j*.
plasma anodization, (9) 311*g*.
substrates, epitaxial growth of $GaAs_{1-x}P_x$ on, (9) 310*b*.
sulfide, quantitative precipitation, (6) 233*j*.
systems. See *Systems*.
tetrachloride, interaction with gallium chloride, (8) 293*c*.
tetrachloride, vibrational relaxation in, (5) 203*b*.
thin, and silicon samples, in high electric fields, effect of space-charge-region surface conductivity on change of resistance of, (5) 180*f*.
X-ray total reflection studies, by three-crystal spectrophotometer, (4) 121*c*.
Getters, quick flash high yield, with means to restrain warping and breaking of getter material, P (10) 345*i*.
Gibbsite, heated, low-angle X-ray diffraction maximum due to textural periodicity in, (8) 294*h*.
hydrargillite, P (4) 125*f*.
hydrargillite, water dispersible, P (4) 125*c*.
mechanical activation, (4) 127*a*.
Glass. See also *Art and artware; Furnaces; Glass industry; Glassmaking apparatus and equipment*.
with absorbent, cutting with laser beam, P (10) 339*d*.
acetate, formation, (6) 209*b*.
alkali, simple, heat of annealing in, (11) 370*f*.
alkali-borosilicate, ultrasonic studies—spectrum of relaxation times and fluctuation theory, (4) 97*e*.
alkali-calcium-silica, silver diffusion in, (1) 6*g*.

Glass *(continued)*
alkali-free borate, electrical properties, (11) 369*h*.
alkali halide-boron oxide, γ-irradiated paramagnetic resonance of room-temperature-stable *V*-type centers in, (6) 210*d*.
alkali metal nitrates, with group IIA and IIB metal nitrates and with $ZnCl_2$ and water, vibrational spectra, (5) 174*a*.
alkali metals in, electron-probe microanalysis, (11) 369*j*.
alkali silicate, binary, high temperature thermodynamic properties, measurement, (1) 7*d*.
binary and ternary, metastable liquid-liquid immiscibility in, (2) 51*e*.
electrical polarization during internal friction measurements in, (1) 6*g*.
influence of proton exchange on internal friction in, (6) 209*e*.
irradiated, nature of hole centers in, (8) 276*e*.
and melts, knowledge of structure from bonding of OH groups, (6) 209*h*.
mixed, mechanical relaxations in: I, results, (6) 210*b*.
alkaline earth phosphate, iron spectra in, (2) 51*e*.
Al_2O_3-SiO_2, immiscibility and crystallization in, (4) 96*d*.
aluminoborophosphate, absorption and fluorescence spectra of trivalent Mo in, (8) 275*i*.
aluminosilicate, physicochemical studies on, (4) 96*j*.
amorphous oxide, ionic transport in, (4) 96*j*.
ampoule, radiation sensitive, testing apparatus and method, P (4) 100*b*.
anelasticity, network contribution to, (6) 210*a*.
annealing, heat of, in simple alkali glasses, (11) 370*f*.
application in electronics, (10) 338*j*.
architectural, design, (2) 48*c*.
arsenic-sulfur binary, thermal conductivity, (4) 97*e*.
article, abrasion resistant, P (8) 277*d*.
arcuately shaped cellular, P (11) 370*j*.
with birefringence pattern, and production, P (5) 174*e*.
coated with gold, chromium, and germanium alloy film, P (1) 11*e*.
drawing, P (5) 175*c*.
hot casting under pressure, technological properties of slips for, (6) 211*e*.
sealed, of manufacture, P (4) 101*d*.
sintered, P (4) 101*a*.
surface treatment, P (6) 213*f*.
vacuum forming, with vented modules, P (10) 340*b*.
BaO in high alumina ceramics, (10) 343*d*.
BaO-Nb_2O_5-SiO_2 compositions for use in fiber optics, P (11) 371*a*.
BaO-SiO_2, development of two-phase structure in, (1) 6*f*.
$BaTiO_3$ from, (5) 172*f*.
batch, correction procedure, (4) 97*d*.
material, feeding method, P (7) 249*d*.
melting, submerged combustion principle, (5) 173*d*.
molten, use of TiO_2 granules in, P (6) 213*g*.
pelletizing, (1) 8*b*.
response of glass tank to variations in, (1) 8*f*.
baths, refining, P (8) 278*a*.
bead, abrasion resistant, with sharp softening range, and process, P (4) 98*b*.
high melting point, with sharp melting range, and process, P (6) 212*f*.
porous, physical adsorption on, (4) 96*h*.
reflective, Kansas raw materials for, (2) 50*b*.
bent, for lighting fixtures, design and decoration, (2) 46*i*.
beryllium fluoride, structure and chemical properties of BeF_2 in, (2) 51*d*.
bismuth, properties, in relation to structure, (7) 247*j*.
bisulfate, and melt, spectroscopic study of Mo^{5+} in, (6) 211*f*.
blocks, large, new building material, (6) 209*i*.
blowing, creative, B (10) 364*g*.
blowing, oral controlled pressure regulator for, P (6) 213*h*.
bodies, of devitrifiable glass, forming and devitrifying, P (11) 371*f*.
frit-sealed, separating, P (4) 100*j*.
magnetooptic, and electric circuit element in readout apparatus including, P (4) 99*a*.
borate, Cr-containing, absorption spectra, effect of pressure and compositional changes, (2) 48*j*.
color centers in, (6) 208*h*.
proton magnetic resonance in, (1) 8*a*.
ternary, radiochemical studies of adsorption of orthophosphate on, (5) 173*j*.
B_2O_3, structure, reference to vibrational assignment and valence force field of boroxol skeleton, (1) 9*i*.
B_2O_3, viscosity theories for, inadequacies, (4) 96*e*.
borosilicate, properties, (2) 50*d*.
bottler meets decorator, (5) 172*i*.
bottles. See also *Glass, containers.*
cristal, (10) 337*g*.
gaging, P (5) 174*a*.
one-way beer, practical experiences, (10) 338*g*.
breaks. See *Glass, fractures.*
brown, manufacture using Hungarian pyrolusite, (2) 50*c*.

Glass *(continued)*
brown, preparation with pyrites, (11) 370*b*.
bulb, electric, P (11) 371*g*.
bulb, light, with plurality of independently connected filaments for indicating graphic symbols, P (2) 65*h*.
calcium magnesium silicophosphate, fused, form of phosphate ion in, (4) 94*j*.
capsules, dimpled reed, method and apparatus, P (7) 249*b*.
"carbon-sulfur" amber, correction, (11) 369*i*.
cellular materials, P (7) 249*c*.
-ceramic, articles, α- and β-cristobalite, P (8) 277*e*.
articles, with internal cavity, forming, P (7) 249*e*.
articles, transparent, P (9) 308*d*.
conditioning forming rollers to form, P (9) 307*j*.
crystallizable enamels for, P (6) 212*j*.
greensheets, P (11) 371*b*.
$PbTiO_3$, (6) 209*j*.
Li_2O-Al_2O_3-SiO_2-TiO_2, secondary grain growth, (7) 248*c*.
material, for cooking surfaces, P (2) 52*d*.
materials, control of dielectric losses and temperature coefficient of permittivity by doping, (1) 6*b*.
materials, molten, improving roll forming properties, P (7) 249*e*.
materials, two-phase, strength, (4) 97*h*.
product, P (10) 339*a*.
"Quasicerams," etching, problem of inhibitors in, (4) 97*c*.
and silicates, data-book, B (4) 166*a*.
substrates, art of decorating, P (4) 98*g*.
transparent, Silital, (10) 338*b*.
underwater vehicle, structural evaluation, (1) 9*h*.
and ceramic systems, three-dimensional and stereo observations in, (4) 97*i*.
chalcogenide, elastic constants, softening temperature, and structure, (8) 276*f*.
in chalcogenide systems, chemical compositions and formation, (4) 94*i*.
in changing world, review, (1) 40*e*.
channels, method and apparatus for forming, P (5) 175*h*.
coated, P (11) 371*c*.
coaxing effect during dynamic fatigue of, (8) 276*c*.
cobalt oxide coating on, physicochemical bases of formation, (2) 50*a*.
with color zone with blurred boundary, P (10) 339*e*.
colored, effects of oxides of Cu and Cr in Na_2O-CaO-SiO_2 glass, and effect on color and spectral transmission, (11) 369*j*.
colored, Jablonec 1965, symposium, B (4) 165*b*.
coloring method, P (7) 249*c*.
commercial: I, mercurous nitrate solution for estimation of iron in glasses; II, dealkalization of soda-lime-silica glasses, (1) 9*h*.
commercial and experimental, pH equilibrium, and relation with chemical durability, (2) 51*a*.
composition, P (1) 10*d*; P (5) 176*c*; P (11) 371*h*.
amorphous, P (7) 248*h*.
control in plant, simplified low-temperature viscosity measurements for, (10) 338*a*.
with high index of refraction, P (4) 99*h*.
for laser applications, P (10) 339*b*.
method and articles, P (11) 371*h*.
for use as faceplate of image orthicon tube, P (4) 98*i*.
container, coated, P (4) 98*i*.
coated with lubricating film comprising carnauba wax and polyvinyl alcohol, P (8) 277*a*.
composite, assembling method, P (7) 249*c*.
one-way beverage, (10) 337*h*.
open mouth translucent, inspection for defects, P (2) 53*a*.
sealed, inspecting in closed cartons, P (9) 307*g*.
strengthening, P (9) 308*c*.
vapor coating, method and means, P (7) 249*h*.
containing radioactive tracer, bacterial attack on, (2) 46*i*.
containing transition metal oxides, evidence for small polaron as charge carrier in, (2) 49*b*.
cooking vessel, decorated polytetrafluoroethylene coated, P (8) 278*b*.
copper-red, color origin in: III, low temperature viscosity, (10) 338*d*.
copper ruby, origin of color in, (9) 306*a*.
Corning 7560, specific heat between 4.5° and 20°K, (1) 8*j*.
cracking, spontaneous, of hardened, (2) 51*g*.
cracks in, generation, and reply, (8) 276*a*.
cracks and fracture in, analysis, (4) 94*h*.
-crystal structures, lamellar, in system ZnO-B_2O_3, (7) 247*f*.
crystalline. See also *Glass-ceramics.*
crystalline article, strengthened, P (6) 213*f*.
crystalline inclusions in, (4) 95*c*.
crystallization. See also *Crystallization.*
change in structure and mechanical properties during, (2) 47*d*.
influence of trace impurities, (1) 7*a*.
crystallized, determination of percent of crystallinity, (4) 120*d*.
cullet, effect in melting soda-lime glasses, (1) 6*i*.
Czechoslovak technical, viscosity, (1) 9*j*.

Glass *(continued)*
damaged by ultraviolet radiation, thermally released current in, (4) 96*c*.
decoration. See *Decoration.*
deep sea submersible vehicles, (2) 47*j*.
defects, study by electron microanalyzer, (2) 48*f*.
deformation, under point loading, role of densification in, comments and reply, (7) 247*a*.
density, as function of thermal history, (9) 305*f*.
density and volume expansion coefficient, measurement at high temperatures, (6) 210*a*.
desorption and exchange of adsorbed octadecylamine and stearic acid on, (1) 27*c*.
destruction by cavitation, (9) 305*j*.
devitrified. See also *Glass-ceramics.*
devitrified, low melting point, and method, P (5) 175*f*.
dielectric loss in, measurement, (7) 247*h*.
diffusion coefficients from light scattering in, (5) 172*i*.
diffusion phenomena in, study by X-ray fluorescence contact radiographic method, (2) 46*g*.
discoloration, by vanadium in fuel oil, (4) 95*j*.
dislocations and surface flaws on, (9) 305*a*.
effect on strength of insulator porcelain, (2) 60*b*.
electrical conductivity, effect of structural changes in transformation range on, (1) 6*c*.
electrodes. See *Electrodes.*
electronically conducting, properties and possible applications in electronics, (7) 247*j*.
in electronics, (5) 172*f*.
elements, with different coefficients of expansion, sealing and resilient seal for, P (5) 175*g*.
empontilling, (1) 7*a*.
enameled, strength, (1) 9*e*.
encapsulation, for drawing microwires, (9) 306*h*.
engineering, in modern materials, B (4) 166*h*.
Eu^{3+} ion as electron trap in, (1) 7*c*.
fabric, treating, P (5) 176*e*.
fabric reinforced mica tape, P (6) 212*c*.
fabric structure, P (8) 277*a*.
ferroelectric crystallized, properties, (2) 49*h*.
fibers. See *Fibers, glass.*
filament, diameter, measurement by determination of mechanical resistance, (7) 247*g*.
filament, intermittently hollow, method and apparatus for producing, P (5) 175*b*.
filters. See *Filters.*
in fine granular form, manufacturing process, P (2) 54*c*.
fining, use of vacuum to intensify, (2) 50*c*.
fixed abrasive for grinding, (11) 370*d*.
flat. See also *Glass; plate, sheet, window.*
fine line defect determined, (1) 7*d*.
manufacture on molten metal bath, P (5) 175*g*.
float, and borosilicate, fracture energy, (9) 305*f*.
cutting, (5) 172*h*.
electrical viscosity control, method and apparatus, P (8) 277*g*.
first plant in Canada, (2) 47*c*.
with internal circulatory bath heat exchange, method and apparatus, P (7) 249*b*.
manufacture on bilevel support bath, method and apparatus, P (11) 371*c*.
method and apparatus for initially restricting divergent flow of, P (6) 213*a*.
with thickness greater than equilibrium thickness, manufacture, P (6) 212*i*.
using enclosed bath zones, P (11) 371*c*.
flow, in furnaces heated by electricity, (8) 278*i*.
flow control, of molten material in furnace, P (10) 338*i*.
fluoroberyllate, EPR of ions of iron transition group in, (8) 276*f*.
fluoroberyllate, melting, influence of gas atmosphere on light transmission in ultraviolet region of spectrum, (1) 7*h*.
foam, P (2) 54*b*; P (9) 307*a*.
mechanical properties, (2) 48*d*.
production from volcanic glasses, (1) 8*i*; with preliminary melting, 8*j*.
foamable granule product, preparation and molding, P (11) 371*f*.
foamed, with uniform cell size, P (8) 278*a*.
fracture, B (1) 41*d*.
analysis, (4) 94*h*.
energy, (9) 305*i*.
by impact, (1) 7*d*.
surface energy, (4) 95*i*.
surfaces, microstructure of mist zone on, (1) 7*i*.
fused, penetration into thermally grown SiO_2 films, (1) 17*b*.
fused quartz and soft, far infrared absorption in, (9) 305*e*.
γ-irradiated, containing lead, ESR studies, (4) 95*h*.
γ-irradiated organic, spatial distribution of trapped electrons in, (8) 298*d*.
gamma-ray-irradiated phosphate, and compounds, ESR spectra, (1) 7*a*.
gas content, effect of alkaline-earth metal sulfates and nitrates on, (6) 208*h*.
gaseous inclusion in, gas chromatographic analysis, (5) 172*f*.
germanate, reduced, fluorescence of Fe, Co, and Ni in, (5) 172*e*.
germania, silica, and radiation-damaged silica, neutron diffraction by, (7) 247*i*.

Glass *(continued)*
GeO_2, spectrum of relaxation times in, (1) 9*b*.
"glass" structure, (11) 370*c*.
glassy state, thermodynamics, (4) 97*h*.
grains, surface area estimations, used in durability testing, (7) 248*d*.
grinding. See *Grinding*.
hand-blown, sculptured, colored—philosophy and method, B (6) 241*b*.
handling operations, use of programmed robots in, (4) 98*b*.
hardened, spontaneous cracking, (2) 51*g*.
headers, improved die for making, (5) 172*i*.
headlights, nonglare sealed beam, P (6) 213*g*.
heat resistance, increasing by treatment in alkaline solutions, (6) 209*e*.
heat transfer member, P (4) 99*g*.
hemispheres, metal member for deep submergence spheres formed from, P (9) 307*h*.
high-lead, surface, chemical composition of phase reduced on, during heating in hydrogen, (8) 276*c*.
high-P, determination of P and Si in, by IR-spectroscopy method, (2) 69*i*.
high strength, P (6) 212*g*.
high silica content, P (11) 371*j*.
hollow particle, with metallic copper coating, P (5) 175*e*.
homogeneous, preparation, gel route to, (8) 276*a*.
homogenization, (2) 49*i*.
homogenization, in flat glass tanks, effect of flow on, (6) 209*a*.
homogenizing, by gas injection, P (4) 100*h*.
hot ribbons, in flat glass manufacture, thickness measurement, (9) 307*h*.
impact beads, market for, (7) 243*f*.
inclusions, analysis with X-ray microfluorescence, (5) 172*c*.
with increased breaking strength, oxidation method of producing, P (10) 339*h*.
infrared absorptive sealing, P (8) 277*c*.
infrared transmitting, melt-casting, P (9) 308*b*.
inorganic, delayed elasticity in, (4) 95*g*.
new, vitreous nature as shown by X-ray diffraction, (9) 307*i*.
and supercooled liquids, heat capacity, correction, (2) 49*i*.
investigations on, with electron microscope, (11) 370*b*.
ion-exchange equilibria with molten salts, (5) 172*j*.
ion exchange with molten salt, thermodynamic aspects, (5) 173*h*.
ion impact desorption of hydrogen from, (5) 173*a*.
iron-alkali-silicate, Moessbauer effect in, (9) 306*i*.
iron-containing, stimulated crystallization, (1) 9*d*.
iron phosphate, thermally activated diffusion of electronic carriers in, (5) 173*h*.
Kerr, optimum batch moisture and unique furnace feeding for, (7) 247*i*.
laboratory tubes, packaging method, P (10) 339*i*.
laminate, P (6) 212*d*.
improving strength characteristics, P (2) 53*d*.
and interlayer, P (7) 248*h*.
organophosphorus coupling agents for epoxy to, P (5) 176*b*.
-polyurethane-polyvinyl butyral-polyurethane-glass, P (11) 371*i*.
transparent safety, P (2) 54*b*.
laminated, assembly, bent, P (4) 98*i*.
assembly, with tapered inner layer, P (7) 248*j*.
panels, incorporating heating wires, P (7) 248*j*.
products, P (9) 308*b*.
safety, P (1) 10*j*.
laser, Nd and Yb doped borate, P (11) 372*b*.
material, hot-pressed polycrystalline, P (10) 339*g*.
with relatively low thermal expansion, P (10) 339*b*.
surface damage, mechanism for, (9) 306*e*.
laserable material, P (5) 174*h*.
lead, leaching by EDTA, kinetics, (8) 276*d*.
-containing, forming strong metallic bonds to, P (5) 175*d*.
shock-compressed, optical properties, (1) 7*a*.
structural compacting observed at different temperatures, (4) 97*b*.
$PbO \cdot 2B_2O_3$, crystallization from supercooled melt, (8) 276*d*.
$2PbO \cdot SiO_2$, study of crystallization by IR spectroscopy, (7) 269*c*.
lenses. See *Glass, optical*.
light control panel, P (7) 249*a*.
light projection device, and light source support means for, P (7) 249*a*.
light-sensitive, formation of crystallization centers in, (2) 51*b*.
lithia-alumina-silica, crystallization, study of initial stages by Moessbauer effect and X-ray phase analysis, (1) 9*a*.
lithia, water attack on, in relation to phase separation phenomena, (2) 52*f*.
lithium, sodium, and potassium silicate, electrical properties and structure, (10) 337*j*.
lithium borate, and compounds gamma-irradiated at 77°K, ESR studies, evidence for new interpretation of trapped-hole centers associated with boron, (2) 48*i*.
Glass *(continued)*
lithium borate, NMR studies of diffusion in, (1) 8*a*.
lithium borosilicate, electrode behavior, for determination of coordination state of boron, (2) 48*d*.
lithium silicate, binary, and melts, quartz formation and crystallization from, (9) 306*j*.
lithium silicate, strengthened by double ion exchange method, P (4) 98*b*.
$(Li_2O,MgO) \cdot Al_2O_3 \cdot nSiO_2$, thermally crystallized, high-quartz solid solution phases from, (1) 7*f*.
$Li_2O\text{-}SiO_2\text{-}P_2O_5$, phase separation in, direct observation, (9) 315*d*.
low melting, for use in semiconductor devices, P (8) 284*a*.
low melting oxide, P (3) 53*d*.
of low network-former content, structure and crystallization, (8) 276*i*.
low thermal expansion, P (2) 53*e*.
luminaire reflector, P (1) 11*a*.
luminescent, as material for lasers, (2) 50*b*.
machine-drawn plate, measuring and recording angle of deflection, deviation of refractive power and amount of striae of, (9) 306*g*.
$MgO\text{-}Al_2O_3\text{-}SiO_2$, crystal growth of metastable quartz solid solutions in, (7) 264*h*.
-making, automation and modern, (5) 172*e*.
for craftsman, flameworking, B (9) 333*j*.
method and chamber for, P (10) 339*j*.
open-air, under "concrete sun roof," (9) 306*c*.
photochromic, P (9) 308*a*.
use of platinum in, (4) 98*a*.
using gas pressure for glass sizing, P (6) 213*b*.
masses, agglomerating, and products, P (9) 308*b*.
materials, testing for lattice imperfections, P (4) 100*a*.
measuring diffusion coefficient of Ag^+ ions in, by ^{110}Ag radioisotope, (6) 210*c*.
mechanical, chemical, and electrical properties, effect of surface dealkalization, (10) 337*h*.
melting, P (8) 277*j*.
batch-free time versus crucible volume in, (10) 337*g*.
electric, (2) 48*f*.
electrical, in pot furnaces with Kanthal-Super elements, (9) 305*c*.
and fining, with sulfate, thermodynamic aspects, (1) 9*g*.
problems, and electrical conductivity of molten glasses, (1) 6*g*.
and supplying along feeder duct, P (1) 11*c*.
melting ingredients on molten metal bath, P (9) 308*b*.
melts, color change in glassmelting kilns, (8) 276*a*.
corrosion of refractory materials by, (9) 305*a*.
gas bubble formation in, dependence on furnace atmosphere, (4) 95*h*.
laboratory, improving homogeneity, (6) 211*d*.
nitrogen diffusion in, (9) 305*a*.
relation between phase diagrams, reaction kinetics and structure of, (9) 307*b*.
$Na_2O\text{-}SiO_2$, potential sweep voltammetry by stationary platinum electrodes, (1) 8*b*.
surface tension, effects of atmosphere and minor constituents, (4) 95*e*.
three-component silicate, refraction of oxygen ion in, (2) 50*g*.
membranes, sintered porous, ion-selective properties, (5) 173*b*.
-to-metal sealing. See *Seals and sealing*.
with metal oxide coatings, study by infrared spectroscope, (1) 9*d*.
metallic members for insertion into, P (4) 99*b*.
metaphosphate, I^- photosensitized reactions in, (5) 173*c*.
microhardness, (6) 210*g*.
microhardness, tests, (1) 8*g*.
microheterogeneous, origin of phase connectivity in, (4) 96*d*; correction, (8) 276*f*.
microporous, argon sorption at 77.4°K on, (4) 94*j*.
microscope cover, P (5) 176*a*.
mirrors. See *Mirrors*.
as model to reconstruct methods of working flint in stone age, (9) 305*h*.
in modern world, study of materials development, B (2) 85*e*.
molds. See *Molds*.
molten, electrical conductivity, and problems in electric glassmelting, (1) 6*g*.
hot-forming, laws of heat transmission during, (10) 338*b*.
and molten slag, wettability of refractories by, (5) 174*c*.
problem of boil in tank furnaces, (1) 8*f*.
as protective medium in heating blanks before deformation, (2) 50*f*.
SiO_2, dissolution in, (10) 338*g*.
treating with laser beam, P (4) 100*b*.
multiple glazed units, inspecting for dew point, P (4) 100*b*.
Nabal, boric oxide anomaly in, (11) 369*h*.
$Nb_2O_5\text{-}Na_2O\text{-}SiO_2$, ESR studies of radiation-induced niobium centers in, (2) 48*i*.
nodules, coated multicellular, making shaped article from, P (6) 213*d*.
nucleated. See *Glass-ceramics*.
opacifying pigment composition, P (11) 372*c*.
Glass *(continued)*
optical, chemical analysis of trace coloring oxides in, problem, (8) 276*g*.
chemical resistance, (2) 47*e*.
couplers, P (10) 339*b*.
crown, P (9) 308*e*.
crown, on phosphate base, P (10) 339*f*.
devices, coated, P (5) 174*a*.
element, ZnO infrared transmitting, forming, P (4) 99*i*.
elements, lanthanum fluoride infrared transmitting, P (7) 249*a*.
elements, ZnSe infrared transmitting, P (10) 339*b*.
Faraday rotation devices, materials and structures for, P (5) 175*h*.
fiber, image-conducting devices embodying varying controlled stray light absorbing means, P (7) 248*f*.
flint, P (8) 278*d*.
infrared transmitting element, P (6) 213*c*.
inspection devices, employing light-conducting fibers, P (10) 339*g*.
lens, apparatus for measuring optical characteristics of coatings on, P (8) 277*g*.
lens, apparatus for and methods of testing, P (7) 248*i*.
lens, generating, P (9) 307*j*.
lens, method for blocking and deblocking, P (2) 53*c*.
lens, multifocal, apparatus for grinding, P (5) 174*h*.
lens, multifocal, preformed blank for, P (2) 54*a*.
lens, ophthalmic, P (6) 213*e*.
polished surfaces, corrosion by small droplet of etchant solution, (6) 208*j*.
prism unit, P (9) 308*e*.
properties. See *Optical properties*.
quality glazing, methods of measuring, (6) 208*f*.
windows for lasers, P (5) 176*b*.
oxide content, determined by calculation of empirical formulas using linear programming, (2) 47*a*.
package, distinctiveness, (2) 48*h*.
panels, acoustical, P (9) 307*j*.
composite light transmitting and light reflecting, P (10) 338*i*.
crate for shipping, P (2) 52*e*.
electrically heated, antishock control devices for, P (9) 307*j*.
laminated transparent, with electrical heating wires, and production, P (2) 53*d*.
luminescent hardened, production, (1) 6*f*.
structural, P (7) 249*f*.
paramagnetic resonance of iron in, (10) 338*f*.
particles, vapor deposition on entire exposed surface of object, P (7) 257*c*.
peralkaline silicic, Sr and Mg contents of, and petrogenetic significance, (10) 348*i*.
phase separation in, nucleation of crystallization of aluminosilicate glasses by spinodal decomposition into vitreous phases, (6) 210*i*.
phosphate, absorption spectra of first row transition metal ions in, (4) 94*g*.
Cr-containing, absorption spectra, effect of pressure and compositional changes, (2) 48*j*.
ESR and optical absorption study of Mo^{3+} in, (1) 7*b*.
silver-activated, radiophotoluminescent centers in, (1) 8*b*.
for X-ray, gamma-ray, and thermal neutron dosimeters, P (9) 308*f*.
phosphosilicate, P concentration profile and phase segregation in, on SiO_2 films, (4) 149*d*.
photochromic, image display and storage system, P (6) 213*i*.
photochromic, production and article, P (4) 100*d*.
photoconducting oxide, two-liquid phase structure, (2) 52*d*.
photoconductive oxide, optimization of properties of, (6) 210*d*.
phototropic, with favorable kinetics of phototropic process, (4) 96*f*.
physical properties, B (6) 241*i*.
pipe. See *Pipe*.
plastic deformation, with diamond indenters, (6) 211*a*.
plate. See also *Glass: flat, sheet, window*.
plates, bent, regularity of optical defects in, (5) 173*h*.
and Plexiglas, microelastic behavior during scratching of, (6) 210*e*.
polished porous, ion-selective properties, (4) 96*j*.
polishing. See *Polishing*.
polishing agents, spent, rejuvenating by flocculation, P (7) 249*d*.
and polyesters, rendering adhesive to rubber, P (11) 372*a*.
polyphosphate, and water treatment uses of, P (6) 213*a*.
-porcelain bodies, structure and phase composition, (6) 211*j*.
porous, adsorbed water, DTA at room temperature to −90°C, (4) 95*i*
dehydration, (4) 95*e*.
as ionic membrane, (5) 173*i*.
reaction with HF, (6) 211*c*.
role of surface boron as adsorption center for sorption of water by, (4) 97*e*.
sintering,—benzene adsorption by heat-treated, (5) 173*c*.
pots. See *Glassmaking apparatus and equipment; Refractories*.

Glass *(continued)*
powder, with cordierite composition, sintering and crystallization processes, (1) 36*h*.
powdered, selectively removing, P (4) 115*i*.
powders, compaction and shaping, (1) 6*a*.
preserving jars, P (6) 212*f*.
properties, effect of disorder, (1) 6*a*.
effect of melting history, (7) 247*f*.
influence of iron oxides, (1) 7*j*.
physical and chemical, role of surface, (2) 50*j*.
Pyrex, exchange and diffusion of Ag^+ and Na^+ ions in, (2) 49*c*.
permeation, diffusion, and solubility of deuterium in, (6) 210*h*.
simple, inexpensive, to aluminous porcelain vacuum seal for use in thermal analysis, (6) 227*b*.
vitreous silica, and T-40, acoustoelastic effect in, (11) 369*d*.
quartz, microplasticity, effect of α-radiation, (2) 48*j*.
radiation induced crystallized, P (10) 339*c*.
refining, effect of arsenic on composition of gas in seed during, (7) 247*d*.
refining, influence of size of melt. (2) 49*f*.
refraction and densities, effects of water content on, (6) 209*i*.
research, review, (5) 172*g*; (7) 247*c*.
resistivity, effect of uniaxial stress on, (8) 276*f*.
retroreflective structure, P (5) 176*e*.
rods, fracture behavior in oil jacket pressure tests with superimposed tensile stress, (9) 305*f*.
ruthenium volatilization from, solubility dependence, (10) 338*h*.
safety. See also *Glass, laminated*. P (6) 213*d*.
scratching, material dislocation during, (9) 306*d*.
screen, glare reduced light ray, P (1) 10*c*.
sealing. See *Seals and sealing*.
segregation, in theoretical scheme for, fluctuation stage of phase decomposition, (2) 52*a*.
selective stressing and birefringent article, P (9) 308*c*.
semiconducting oxide, containing Na_2O, polarization effects in, (11) 370*b*.
semiconductive, "inverted" and iron aluminoborate, (2) 51*b*.
semicrystalline. See *Glass-ceramics*.
sheet. See also *Glass: flat, plate, window*.
bending with gas pressure cushions, P (10) 339*j*.
binders for, P (5) 174*j*.
container, P (9) 307*f*.
continuous, manufacture on molten metal bath, P (8) 277*e*.
drawing, detecting ribbon formation abnormalities in, P (4) 98*a*.
drawn, crystallization problems, (8) 276*d*.
forming on molten metal bath, P (5) 175*c*.
high-strength, influence of loading time on impact resistance of, (2) 49*e*.
internal friction under high stress, (8) 276*d*.
mold cover for bending, P (5) 176*b*.
mounting, P (11) 372*a*.
sizing and severing automatically, P (5) 174*i*.
stabilization, internal friction studies, (4) 96*h*.
strengthening by ion exchange, P (4) 101*b*.
thickness and taper, influence of change in height of molten glass, (2) 49*j*.
toughened enameled, (6) 211*b*.
transferring, P (4) 101*d*.
shot peening with, best for thin materials, (7) 243*f*.
silica, densification, effect of impurities, (7) 247*f*.
densified, energy spectrum, (7) 247*j*.
densified at very high pressures, anomalous changes in properties, (11) 369*c*.
effect of α, β-quartz transformation on diffusion of ^{22}Na in, (6) 208*i*.
electrical conductivity and electrolysis of alkali ions in, (7) 247*g*.
$\cdot GeO_2$, infrared spectra, (8) 276*c*.
hardness and low-temperature deformation, (4) 96*b*.
high content, porous, treating, P (11) 371*j*.
luminescent, modified with rare earth metal, P (11) 372*c*.
and soda-lime-silica, methanol vapor adsorption on, (6) 210*c*.
silica in, determination, (11) 380*b*.
silicate, activation energy, effect of melting aids, (2) 48*c*.
and chalcogenide, viscosity, new type of temperature function of, (2) 50*g*.
chemical durability, (1) 5*j*; (2) 47*e*.
chemical resistance, new methods of testing, (6) 210*c*.
Cr-containing, effect of pressure and compositional changes on absorption spectra of, (2) 48*j*.
containing Ti, gamma-induced absorption in, (6) 209*c*.
dielectric constant, calculating temperature-frequency change of, (2) 50*d*.
effect of two alkalis in, (2) 51*h*.
fluorine behavior in, (2) 46*j*.
irradiated, thermoluminescence, EPR, and electron absorption spectra, (8) 277*a*.
and phosphate, high-pressure Moessbauer studies of ^{57}Fe in, (5) 172*g*.

Glass, silicate *(continued)*
and phosphate, Fe^{3+} coordination in, (1) 6*d*.
and phosphate, Ru solubility in, (10) 338*i*.
physical properties and structure: I, additive relations in alkali binary glasses, (9) 306*f*.
strengthening by ion exchange, (4) 97*a*.
substructure classification, (6) 211*d*.
viscosity-temperature data, calculation with two and three constants equations, (5) 172*h*.
-silicon assemblies, P (2) 53*a*.
silvering reactions, kinetics, (9) 306*c*.
single-alkali, ionic diffusion and electrical conductivity, (2) 49*j*.
and sitall shapes, influence of diamond wheel characteristics on spherical grinding of, (2) 49*c*.
and sitall shapes, measurements of diamond grinding wheel wear in processing, (1) 7*f*.
sitalls, *s* and *tg*δ, containing compounds of Ce, Bi, and Pb, frequency and temperature dependence, (2) 77*i*.
formation in system $CaO–Al_2O_3–SiO_2$, (2) 51*j*.
microstructures, (2) 50*f*.
nontransparent, strengthening possibilities, (2) 50*b*.
properties, (2) 51*c*.
in system $Li_2O–Al_2O_3–SiO_2$, study by EPR, (7) 269*g*.
slab, ornamental, containing flat glass strips, P (5) 176*c*.
slag, fluorine-containing, crystallization, (2) 47*h*.
slagceram, nucleation and crystallization studies, (10) 338*c*.
soda-boric oxide, copper in, (6) 208*i*.
soda-lime, behavior of bubbles of oxygen and sulfur dioxide in, (4) 94*g*.
effect of cullet in melting, (1) 6*i*.
red stained, P (6) 213*c*.
"water" diffusion in, within and near transformation range, (7) 247*b*.
soda-lime-magnesia-silica, determination of K_2O in, comparison of flame photometric and gravimetric methods, (7) 259*i*.
soda-lime-silica, dealkalization, (1) 9*h*.
determination of Al_2O_3 in, by EDTA, (7) 260*g*.
dynamic fatigue, (9) 305*b*.
electrical conductivity during latter stages of melting, (6) 209*f*.
with high iron content, spectrophotometric studies, (1) 8*j*.
soda-potash crystal, solarization by sunshine, and stabilization, (8) 276*g*.
soda-silica, effect of water content on phase separation in, (11) 369*f*.
high purity, ultraviolet absorption, effect of iron, (1) 6*b*.
spinodal decomposition in, (8) 276*g*.
Tm-doped, Moessbauer effect determination of Tm^{3+} crystalline electric field parameters in, (6) 210*i*.
sodium aluminosilicate, sodium self-diffusion in, (9) 307*c*.
sodium borate, irradiated by ultraviolet light, ESR spectra, (1) 7*b*.
sodium borosilicate, phase separated, internal friction at high temperatures, (4) 96*g*.
phase-separated, viscosity and transformation temperature, (8) 277*b*.
use of dielectric loss method in study of chemical inhomogeneities in, (10) 338*c*.
sodium disilicate, internal friction after ion exchange, (11) 370*f*.
sodium silicate, high-temperature internal friction and transport mechanisms in, (1) 7*g*.
sodium silicate, sodium distribution in, studies by chemical difference method, (8) 276*j*.
sodium vapor-resistant at temperatures to 700°C, (7) 247*c*.
$NaF–B_2O_3$, properties and structure, (9) 306*i*.
$Na_2O–SiO_2$ melts, solution of fused quartz in, (9) 307*d*.
$Na_2O·2SiO_2$, containing NaCl and $NaSO_4$, Na^+ diffusion in, (9) 306*j*.
solder compositions, and sealing metal with, P (10) 340*b*.
staining, and compositions, P (5) 175*h*, *j*.
staining, with rare earth elements, (6) 211*h*.
stemware, with wide thin extremity portions, package for, P (10) 339*i*.
Stiegel, B (1) 42*g*.
strand, dispersal, method and means, P (4) 100*c*.
strength, apparatus for testing at various temperatures and in vacuo, (2) 46*f*.
increasing by etching and ion exchange, (8) 276*a*.
increasing by overglazing, P (6) 212*h*.
strengthening, P (11) 372*d*.
by ion exchange, (5) 173*d*.
by multiple alkali ion exchange, P (6) 213*f*.
by K nitrate-K borofluoride melt, P (8) 278*c*.
stress in, caused by ultraviolet radiation: VIII, kinetics, (6) 211*i*.
stretched laterally using gas inlets during float glass manufacturing, P (7) 249*d*.
struck, cause of dependence of light transmission of, on intensity of illumination, (9) 305*d*.
structure and electrical properties, (9) 307*e*.
sulfate-chloride, octahedral-tetrahedral transitions of Co^{2+} in, (5) 173*h*.
sulfoselenide, oxygen-free, crystallization, (7) 247*a*.

Glass *(continued)*
surface energy, below transformation temperature, (11) 370*e*.
surface tension, measurement by capillary flow technique, (6) 226*d*.
surfaces, abrasion resistant, P (7) 248*g*.
abrasion-resistant, method of rendering, and article produced, P (2) 53*h*; P (4) 100*g*,*h*; P (7) 249*i*.
abrasion and scratch resistant, method of rendering, P (7) 249*a*.
clean and metalized, desorption of ionically pumped argon from, (9) 305*i*.
coated with decorative organic coatings, P (7) 248*i*.
hydrophilation: I, investigation of possible promoters of filmwise condensation; II, reaction of quaternary ammonium compounds with surface hydroxyl groups; III, synthesis of novel quaternary ammonium compounds tested as possible promotors of filmwise condensation, (9) 305*h*.
imparting abrasion and scratch resistance to, and articles produced, P (4) 99*j*.
improving bonding characteristics, P (4) 100*a*.
and modern treatments, symposium, 1967, B (5) 204*h*.
porous layers at, (4) 97*b*.
role in physical and chemical properties, (2) 50*j*.
strengthened, treating to increase acid durability, P (9) 308*d*.
treatment, P (6) 213*e*; P (11) 372*c*.
treatment to make resistant to iridescence, staining, and scumming, P (4) 101*d*.
working, P (8) 278*c*.
syringe, P (4) 101*c*.
system, $BaO–SiO_2$, crystallization, (2) 51*h*.
$CaO–Al_2O_3–SiO_2$, sitall formation in, (2) 51*j*.
$Fe_2O_3–BaO–B_2O_3$, properties, influence of crystallization, (10) 337*i*.
$La_2O_3–B_2O_3–P_2O_5$, forming regions, (1) 9*i*.
$PbO–B_2O_3$, low melting, P (5) 175*e*.
$Li_2O–Al_2O_3–SiO_2$, crystallization, (8) 276*c*.
$Li_2O–Al_2O_3–SiO_2$, electron microscopy of crystallization, (1) 6*i*.
$Li_2O–Al_2O_3–SiO_2$, nucleation and crystallization behavior, (10) 338*d*.
$Li_2O–BaO–(Pr,Nd)_2O_3–SiO_2$, function of pH, (4) 95*i*.
$Li_2O·SiO_2–Li_2O·Al_2O_3·4SiO_2$, chemical stability, electron-microscope study, (2) 48*g*.
photoluminescent, P (7) 249*b*.
$P_2O_5–ZnO–UO_3$, synthesis, (4) 97*e*.
$RO–TiO_2$, Ti^{4+} coordination in, (4) 97*j*.
$SiO_2–Al_2O_3–BaO–TiO_2$, initial crystallization phases for, by optical anistropy, (10) 337*j*.
$SiO_2–Ga_2O_3–MgO$, region of formation, (2) 50*i*.
$Na_2O–B_2O_3$, activated by oxides of Sm, Tb, and Dy, (2) 51*d*.
$Na_2O–CaO–MgO–Al_2O_3–SiO_2$, effect of fluoride as crystallization promoter in, (6) 209*c*.
$Na_2O–MgO–CaO–Al_2O_3–SiO_2$, crystallization, (6) 211*f*.
$Na_2O–MgO–SiO_2$, properties, dependence on composition: I, glass formation; II, density and refractive index; III, refraction of oxygen ion; IV, electrical properties; V, microhardness, (2) 47*a*–48*a*.
$Na_2O–SiO_2$, decomposition voltage, measurements at elevated temperature by commutator technique, (1) 7*g*.
$SrO·SiO_2–CaO·SiO_2$: II, structure of strontium silicate glasses studied by infrared absorption spectra, (7) 247*d*.
technical powdered, specific surface, dependence on chemical composition, (9) 305*g*.
television tubes. See *Tubes*.
tempering, P (9) 308*c*.
and cooling, process and installation for, P (2) 54*b*.
differential chemical, method and article, P (8) 277*i*.
between roughened glass contacting surfaces, P (4) 101*c*.
utilizing organic polymer gaseous suspension, P (5) 175*j*.
thallium borate, NMR studies, (11) 370*i*.
thallium borate, NMR in: I, ^{203}Tl chemical shift, (5) 173*f*.
thallium silicate, cation distribution in, (8) 275*j*.
thermal stress problems in, (1) 9*f*.
thermoluminescence, (6) 208*e*.
Ti and ceramic mass from X-ray spectroscopic determination of valence of Ti and coordination number of Al, (2) 52*g*.
transition and polymer-melt viscosity—evaluation of Adam-Gibbs and free volume models, (4) 97*b*.
treating, P (5) 175*j*.
treatment with silsesquioxanes to improve durability of subsequent silicone treatments to washing, P (8) 278*c*.
two-phase, ion exchange with, (5) 173*a*.
tubes. See also *Tubes*.
tubing, cutting method, P (2) 53*c*.
tubing, sealing metallic wires into, (10) 337*g*.
tubular fibrous bodies, P (2) 53*h*.
under impact, behavior, (2) 46*f*.
uranium(IV), magnetic susceptibility, (4) 96*b*.
uranyl luminescence in, influence of chemical bond, (2) 49*a*.
vanadium-zinc borate solder, P (8) 278*c*.

Glass *(continued)*
V_2O_5-P_2O_5, elastic and anelastic behavior, (11) 369*f*.
viscosity change, forehearth addition process for, P (8) 277*j*.
viscosity, and electrical resistivity, simultaneous measurements at temperatures in melt- and working range, (5) 173*b*.
high, measurement by industrial viscosimeter, (5) 172*i*.
in range 10^4–$10^{2.5}$P, apparatus for measuring, (1) 8*i*.
-temperature curve, calculation, from fixed points, (4) 94*h*.
vitreous products, sintering in presence of vitreous phase, (6) 211*c*.
vitreous systems, effect of electromagnetic radiation on, (6) 208*j*.
vitroceramics, crystallization temperature, decrease, (11) 369*d*.
volcanic, for production of foam glass, (1) 8*i*; with preliminary melting, 8*j*.
wall, frustoconical lead-through elements in, sealing, P (4) 100*i*.
wall thickness, apparatus for determining, utilizing radiation absorption, P (5) 174*g*.
-ware, Czechoslovakia's expanding trade in, (7) 247*b*.
mounts for transportation and display, P (4) 100*d*.
treating, P (1) 11*b*.
window. See also *Glass: flat, sheet, plate.*
ridged dielectric, with Ti suboxide solely on ridges, P (7) 249*e*.
strength of adhesion of dried clay slurries to, as function of slurry pH, (11) 370*d*.
window panels, P (4) 100*e*.
window panels, laminated, P (4) 100*c*.
windshield, adhered, with concealed adherent, P (5) 174*e*.
bent laminated, P (10) 340*a*.
new construction, (5) 172*d*.
optical characteristics, (6) 210*d*.
tough, breaks into blunt shards, (5) 173*j*.
wool. See *Fibers, glass.*
X-ray analysis, (10) 338*c*.
X-ray total reflection studies, by three-crystal spectrophotometer, (4) 121*c*.
yarns. See *Fibers, glass.*
zinc-barium-silicate, used as standard for fluorescence, P (4) 99*c*.
Zn and Mg in, determination by atomic absorption method, (2) 48*c*
zinc tellurite, P (5) 176.
ZrO_2 soda-silica, durabilit , ffect of ZrO_2 substitution, (10) 337*i*.
Glass industry, air pollution in, (10) 337*f*.
container, energy supply, with emphasis on high pressure waste heat boilers, (6) 209*h*.
plant laboratory in, (10) 338*f*.
waste disposal becoming cost factor for, (9) 306*c*.
conversion to natural gas in, (9) 305*f*.
float, around world, (10) 337*h*.
float, Ford's plant, solid state drive system at, (10) 338*h*.
international brand names, problems in coining, (10) 363*j*.
Iran laboratory, (1) 5*j*.
L-O-F semicontinuous thermal evaporation, (10) 346*h*.
1968, (7) 247*b*.
perlites as raw materials for, (6) 210*g*.
raw materials and finished products in, supervision by X-ray fluorescence spectroscopy, (9) 307*g*.
refractories in, introduction; silica; high alumina; basic; zircon, chromium oxide, and mullite, (1) 8*c-e*.
sheet glass plant at Calif., has world's largest glass tanks on stream, (2) 50*j*.
shock absorbers in, (2) 51*b*.
Suriname, (1) 9*h*.
Glassmaking apparatus and equipment. See also *Burners.*
for armored sheet, P (11) 370*j*.
for article of vitreous material, P (4) 100*b*.
attachment for introducing light into image-transmitting fiber-optical system for illuminating object, P (9) 307*a*.
automatic control, for length of blanks blow-formed from molten thermoplastic materials, P (2) 52*b*.
banding, P (10) 338*h*.
for bedding, plates for grinding and polishing, P (4) 99*c*.
for bending, downward of sheets, P (2) 53*f*.
sheets, P (5) 174*f*; P (6) 212*b*.
sheets with aligning means, P (11) 370*h*.
and tempering sheets, P (2) 53*f*.
bottle gaging, P (2) 52*b*.
bottle-shaping, increasing wear resistance of components of, (2) 49*j*.
bottle sorting, P (2) 52*c*.
for bulking yarn, P (1) 10*c*.
for centrifugally casting articles, P (8) 277*e*.
for checking impurities, P (11) 370*i*.
color gun beading, P (6) 212*i*.
composite tweel, with internal suspension system, P (8) 277*h*.
container inspecting, light transparent, P (10) 339*h*.
container inspection, P (5) 174*b*.
for controlled heat softening of tubing, P (11) 370*i*.
for controlling tube and rod dimensions, P (1) 10*c*.

Glassmaking apparatus and equipment *(continued)*
for conveying, and curving sheet material on gas support bed, P (1) 11*d*.
and heat treating glass sheets over a gas support bed, P (1) 11*d*.
and treating fibers, P (8) 277*f*.
conveyor, and heat-treating process, P (10) 339*c*.
conveyor, pivotal attachment for moving sheets over hot gaseous support bed, P (1) 11*c*.
cutter [hand], P (11) 371*i*.
cutting head, P (1) 10*e*.
for cutting sheet automatically, P (7) 248*h*.
for detecting and recording locations of defects in sheet material in two dimensions, P (4) 98*c*.
drilling, for sheet, P (11) 371*c*.
for driving filamentary material collectors, P (1) 10*c*.
edge-grinding, for lenses, P (11) 371*c*.
edge grinding, for plate, P (9) 307*c*.
electrical printing, using screen with thick coating to define image, P (8) 277*h*.
for envelopes and float glass method, P (11) 371*f*.
feeder, pumping vane type, P (4) 100*j*.
feeders, molten, hydraulic shears for, P (7) 248*j*.
for feeding articles to endless or closed path conveyor, P (1) 10*f*.
fiber aligning, P (10) 338*i*.
for fibers, P (6) 212*g*.
for filament, intermittently hollow, P (5) 175*b*.
for filament-forming mineral materials, P (2) 53*j*.
filamentary material processing, creel adapter for, P (6) 212*j*.
for flat, P (2) 53*h*; P (4) 98*g*; P (6) 212*c*.
for flat on molten metal bath, P (2) 53*i*; P (4) 99*e*; P (5) 175*a*.
for flat sheet, P (4) 98*g*.
for flat wire, P (10) 338*g*.
flexible shaping [flange], P (9) 307*d*.
for float, with restricted lateral spread, P (6) 212*d*.
for fluorescent lamps, P (1) 10*h*.
for foamed silicate articles, P (6) 213*d*.
for footed stemware, P (10) 339*a*.
for forming, articles with air treating means, P (8) 277*f*.
with blowhead control, P (1) 10*h*.
bottles, P (1) 10*j*.
channels, P (5) 175*h*.
compound bend in sheet on gas support bed, P (2) 53*g*.
container neck ring, P (5) 174*g*.
cooling arrangement for, P (2) 52*e*.
fiber products, P (1) 10*f*.
helical grooves in thin wall glass tubing, P (1) 11*b*.
helically shaped tube, P (5) 174*g*.
hollow ware, P (6) 212*h*.
of hot glass, construction and operation, B (11) 389*a*.
mold closing boost mechanism for, P (11) 371*j*.
with molds with movable bottom sections, P (4) 99*a*.
precision tubing from molten glass supply, P (1) 10*g*.
rod and tube, with controlled dimensional uniformity, P (4) 99*b*.
sheet, with means to transform vertical flows into horizontal flow, P (6) 213*c*.
tube for fibers, P (10) 338*j*.
tubular fibrous insulating articles, P (8) 277*h*.
valve lever and latch mounting mechanisms for, P (11) 372*c*.
furnaces. See *Furnaces.*
gas support bed, for treating, P (10) 338*f*.
for glazing electronic housing members, P (7) 248*e*.
for grinding. See *Grinding apparatus.*
grinding fixture for television funnels, P (10) 339*g*.
for handling, bottles, P (5) 174*e*.
fibrous materials, and method, P (1) 11*c*.
sheet, P (4) 101*f*.
sheet materials, P (4) 98*b*.
strand, P (2) 53*h*.
ware for inspection, P (6) 212*c*.
heat exchange, for treating, P (10) 338*f*.
for heat-treating on fluid support, P (10) 338*f*.
for heating, P (5) 175*i*.
rollers, P (5) 175*j*.
and tempering glass sheets, P (1) 10*g*.
for hollow articles, by module immersion technique, P (10) 339*i*.
for hollow ware, P (5) 175*g*.
for indexing and rotating containers, P (11) 371*c*.
for inspecting, conveyor, P (4) 99*d*.
containers, P (4) 99*d*.
empty bottles, P (6) 212*a*.
empty bottle bottom and neck, using radiation sensitive means, P (4) 98*d*.
empty bottle, using both water soluble and oil soluble fluorescent dyes, P (4) 98*d*.
internal combustion burner nozzle construction, for attenuating glass to fibers, P (2) 53*c*.
internal ridging, P (2) 53*c*.
lamp bulb conveyor mechanism, P (1) 10*j*.
lapping, optical surfaces, P (11) 371*b*.
for laying down glass fiber blanket, P (8) 277*i*.
lehr, automatic temperature control in, (6) 208*g*.

Glassmaking apparatus and equipment *(continued)*
lens surfacing, for forming both surfaces of lens simultaneously, P (8) 277*e*.
lens trimming, P (10) 339*h*.
with liquid seal, P (4) 99*e*.
for manipulating bottles, P (10) 338*g*.
marble sorter, selectively rejectable of misshapen marbles and fragments of, P (4) 99*b*.
for mat of filaments, continuous production, P (8) 277*f*.
for measuring necks of bottles, P (7) 249*a*.
for melting and processing heat-softenable mineral materials, P (1) 10*h*.
for minimizing open bottom blisters on float, P (6) 212*e*.
molds. See *Molds, glass.*
mounts, for transportation and display, P (4) 100*d*.
for moving newly formed articles onto continuously moving conveyor, P (1) 10*i*.
for multiple sheet glazing units, P (7) 248*j*.
novel circulating system, (11) 370*a*.
operational mold safety cam bypass, P (4) 100*f*.
oscillatory spray tempering, P (10) 339*h*.
overflow wedge, constant force internal support for, P (7) 248*d*.
for packaging materials, P (1) 11*e*.
for packaging sheet material, P (4) 100*f*.
parison transfer and invert mechanism, P (8) 278*a*.
pipet plugger, P (11) 372*c*.
for polishing. See *Polishing apparatus.*
press, vertical index, for press forming articles, P (7) 249*g*.
for press bending sheets, P (4) 98*c*.
for press bending vertically suspended sheets, P (9) 307*i*.
for pressing articles, P (6) 212*f*.
pressure chuck, P (10) 339*i*.
for pressurized reed switches, P (5) 174*h*.
for processing heat-softened material, P (2) 53*a*.
for processing heat-softened mineral material, P (4) 99*f*.
for producing, fibers, P (4) 99*h*.
rod and tubing, P (4) 98*f*.
small holes, P (7) 248*j*.
radiation sensitive, for detecting dirt in bottles, P (4) 100*c*.
radiation senstive, for severing sheet along score mark, P (4) 101*c*.
for removing and transferring from molds, P (4) 98*h*.
for ribbed sheets, P (11) 370*j*.
roll bearing structures for, P (5) 176*a*.
rotating dead plate mechanism, P (9) 308*c*.
for scoring pipe, P (2) 52*g*.
for sealing off vessels, P (6) 212*h*.
for severing sheets, P (1) 10*j*; P (10) 339*i*.
for shaping, plastic sheets, P (11) 371*e*.
sheets, P (4) 99*h*.
and tempering sheets with means to support sheets there between, P (10) 338*g*.
for sheet, P (4) 101*e*.
for sheet, utilizing gas-permeable vertical dampers, P (8) 277*f*.
sheet edge control device, P (9) 308*c*.
sheet feeder, for cutting and processing machines, P (1) 10*f*.
sheet forming, with coated silica core roller and roller, P (2) 52*j*.
for sheet forming and annealing, support for, P (6) 212*i*.
sheet tempering, P (10) 339*f*.
sheet washing, P (9) 307*f*.
for stacking, horizontal, of sheets of rigid material, P (4) 98*d*.
for stretching molten sheet laterally, P (9) 307*a*.
for supporting, and conveying sheets on gas support bed, P (5) 174*h*.
and glazing articles, P (4) 98*f*.
sheet on gas and liquid support bed, P (7) 249*c*.
sheets on gaseous bed, P (9) 307*i*.
for suspending sheet, P (10) 338*h*.
takeout rolls, float glass, P (8) 277*j*.
tank coolers, P (11) 371*j*.
tongs, P (10) 340*a*.
for toughening sheets, P (6) 213*a*.
transporting rack, P (5) 175*a*.
for treating sheets, P (6) 213*g*.
tube, grinding, P (10) 339*f*.
tubular cutting tools, P (9) 308*d*.
vertical draw sheet, comblike catch pans for, P (7) 248*c*.
for vertical drawing, automation, (1) 5*i*.
vibratory bowl, P (6) 213*g*.
work holder, for aligning and sealing beaded wire element into glass tube, P (4) 101*e*.
Glazes. See also *Decoration.*
and body experiments, in Herend China Factory in 1840-42, (8) 273*i*.
calcium family, for cone 10, (6) 205*i*.
calculation, (1) 15*c*.
ceramic, optical properties: II, experiments with polarized light, (6) 219*j*.
ceramic, shade variations in, resulting from processing variables, (10) 343*c*.
colored bodies, and engobes, review, (4) 108*d*.
for cone 6, (7) 244*b*.
designing, with flow and crystal glazes, (7) 254*c*.
frits. See *Frits.*
fusion level, changing, (7) 244*d*.
leaching, (1) 15*i*.
leadless boron-free earthenware, (10) 343*f*.

Glazes *(continued)*
low-fire metallic, (10) 335*j*.
microstructure, (2) 50*f*.
of Ming dynasty, (10) 335*i*.
pinholes in, (6) 219*b*.
porcelain, containing spinel, cristobalite as separation phase in, (7) 253*h*.
distribution of bubbles in, (7) 253*j*.
studying fusion in, (6) 219*i*.
pottery, cracking in: II, cracking during decoration firing of dolomite earthenware glazes, (5) 179*j*.
for stoneware-type bodies, at cone 04-4 range, (6) 206*d*.
Sr-Zn, crystallization in, (8) 280*b*.
zinc silicate crystal, (7) 244*f*.
zircon, for structural ceramics, (11) 375*i*.
Glazing, ceramic bodies, crystalline glazed ceramic containing lead titanate crystals for, and method, P (2) 52*f*.
glass, electronic housing members, device for, P (7) 248*e*.
multiplane unit, P (11) 372*a*.
over-, for increasing strength of glass, P (6) 212*h*.
units, fusion sealed, laboratory testing, (1) 7*d*.
Glossaries. See *Nomenclature*.
Gold, alloy, for attaching lead to semiconductor body, P (6) 221*c*.
condensation coefficients, on NaCl single crystals, (4) 129*j*.
diffusing into semiconductor material, P (7) 257*h*.
doping, selective, for high resistivity regions in silicon, P (7) 257*j*.
effect on properties of Si-SiO_2 system, (4) 132*h*.
epitaxy, on doped NaCl substrates, (2) 62*j*.
flash-evaporated on NaCl and KCl substrates, unexpected effects of formed high nucleation densities by, (9) 311*i*.
AuCu and $AuCu_3$ type alloys, binary, ternary and quaternary, order-disorder transformations for, (2) 81*f*.
nucleation density and epitaxy of, deposited onto color-centered cleavage surface of rock salt, (6) 235*j*.
particles, epitaxial growth, onto NaCl, electrostatic field effect in, (6) 232*c*.
X-ray total reflection studies, by three-crystal spectrophotometer, (4) 121*c*.
Grain boundaries, cavitated growth, effect of creep rate, (1) 27*e*.
glide, mechanism, (1) 32*d*.
pore-, interactions, and grain growth, (4) 150*e*.
in KCl, melt-grown, (7) 265*e*.
ratio to surface energy for UC, (6) 236*j*.
role, in plastic deformation of CaF_2, (2) 82*e*.
sliding, contribution to overall strain of polycrystal, (1) 26*b*.
in NaCl, properties, influence of orientation, (1) 31*a*.
Grain growth, carbide, during liquid-phase sintering of alloys NbC-Fe, NbC-Ni, and NbC-Co, (10) 350*j*.
columnar, in UO_2, (4) 128*j*.
concurrent with time-dependent creep, correlation between models, (6) 231*g*.
exaggerated, occurrence in sintered bodies, (9) 316*c*.
and pore-grain boundary interactions, (4) 150*e*.
and pores, kinetics, (8) 296*a*.
secondary, of Li_2O-Al_2O_3-SiO_2-TiO_2 glass-ceramics, (7) 248*c*.
surface, of Al_2O_3, effect of metal oxides, (1) 28*a*.
in UO_2: III, factors influencing, (4) 137*b*.
of ZrO_2, (4) 154*a*.
Grains. See *Particles*.
Granite, leucogranites and rhyolites—trace element evidence for fractional crystallization and partial melting, (8) 294*e*.
melting, with excess water to 30 kbars pressure, (4) 144*b*.
origin, hydrothermal model, (4) 147*i*.
separation of feldspar, quartz, and mica from, (8) 287*j*.
Granular materials. See also *Powders*.
additives, premixing, method and apparatus, P (10) 346*i*.
air classifying and screening, methods and apparatus, P (6) 225*d*.
air permeability, (5) 189*h*.
apparatus for conditioning and dispensing, P (7) 259*d*.
classification, P (8) 287*f*.
classifying, pneumatically, process and apparatus, P (8) 288*d*.
crushed or powdered, conveying, P (7) 263*d*.
electrostatic sorting, method and apparatus, P (1) 20*e*; P (2) 74*d*.
gravity separation of, P (7) 262*h*.
high temperature treatment and cooling, utilizing fluidized layer, installation and method, P (5) 186*a*.
metering identical quantities of, method and apparatus, P (4) 118*f*.
mineral, artificially colored, P (5) 180*d*.
plasticity, theory, (5) 201*c*.
sampling, method and means, P (8) 286*a*.
solid, apparatus for treating, P (10) 346*j*.
tensile strength, (4) 159*h*; (10) 362*f*.
treating in fluidized bed, method and apparatus, P (7) 259*b*.
Granular materials *(continued)*
weighing, continuous, with weight regulation of flow, apparatus for, P (2) 67*e*.
wet, tensile strength, (7) 270*d*.
Granulation. See also *Crushing; Grinding*.
coalescence model for, (4) 117*f*.
Granulometry. See *Particle size*.
Graphite. See also *Carbon*.
anelasticity, impurity-dope effects on, (8) 293*j*.
artificial, Young's modulus, effect of porosity and crystalline orientation, comments, (4) 129*a*.
bodies, disintegrating, P (10) 343*a*.
extraction of materials embedded in, P (5) 178*j*.
reinforced, P (11) 375*b*.
bonding with fused silver chloride, P (10) 342*b*.
boronated, low-temperature specific heat and density of states, (4) 143*c*.
as ceramic material, (11) 382*c*.
-coated particles for nuclear reactors, method and apparatus, P (10) 342*j*.
coating composition, for thermoelectric generator, P (1) 18*f*.
compressed vermicular, preparation, P (9) 309*g*.
electronic structure, optical study, (2) 81*f*.
fibrous, P (10) 343*b*.
graphitization, of carbon, effect of pressure, (4) 133*g*.
graphitization, of furfuryl alcohol coke by titanium and vanadium, (1) 11*j*.
impregnation with refractory carbides, P (6) 217*b*.
internal friction, (4) 140*f*.
Ir-coated, P (8) 279*d*.
irradiated, configuration of interstitial atoms in, (4) 129*c*.
irradiation defects in, thermal annealing studies, and self-diffusion mechanism, (9) 331*c*.
isotropic, elastic properties, (2) 76*g*.
low CTE, and coke, manufacture from petroleum derived feed materials, P (11) 375*c*.
neutron-bombarded, partially annealed interstitial material in, (9) 326*c*.
neutron-irradiated, optical absorption, (2) 81*e*.
optical anisotropy of, (4) 131*h*.
oxidation, catalyzed by Pd, (9) 326*i*.
by CO_2, effect of chlorine, (8) 291*d*.
by CO_2-CO gas mixtures, (8) 295*h*.
effect of ultrahigh pressure, (8) 291*h*.
inhibiting effect of chlorine or carbon tetrachloride on, (9) 323*b*.
polycrystalline, elastic modulus and yield curve, effect of microporosity, (10) 341*b*.
porosity, access of gases to, at high temperatures, (9) 317*j*.
potassium, order-disorder transformation in, (9) 326*g*.
properties, alloys for improving, P (7) 252*b*.
purifying, P (4) 107*d*.
pyro-, low temperature, structure, (1) 38*i*.
pyrolytic, braze compositions for, (8) 279*c*.
depositing, P (8) 279*e*.
electron microscopy, (8) 291*f*.
radiation damage in, annealing study by ESR, (2) 74*i*.
reaction, with hydrogen, (4) 152*f*.
with hydrogen at 1900°–2400°K, mass-spectrometric investigation, (11) 386*a*.
with silica in vacuum, effect of physical parameters, (5) 193*i*.
reactivity to oxygen, effect of neutron bombardment on, (11) 384*h*.
silicon coated, P (6) 218*g*.
single crystal, diffusion of C in, (10) 352*d*.
single crystal, radiolytic oxidation, nature of active species, and *G* values, (9) 311*i*.
solubility in CaO-SiO_2-Al_2O_3 system, thermodynamics, (4) 161*h*.
spontaneously magnetized monoatomic iron layers in, (9) 329*h*.
structures, C-bonded, P (8) 279*h*.
changes on irradiation under restraint, (5) 192*a*.
hyperconductive, P (2) 58*g*.
resilient, P (5) 179*b*.
tensile creep rate, stress dependent, (8) 298*a*.
trigonal warping of bands and Hall effect in, (2) 84*d*.
tubular pyrolytic, dilatometry, (1) 11*j*.
-UO_2 reaction, from 1400° to 1756°C, kinetics, (7) 267*i*.
Gravity, gravimetry, rapid, determination of silica in carbonate rocks using gelatin, (5) 187*j*.
Grinding *(Comminution)*. See also *Crushing apparatus; Mills*.
aid, amide, P (11) 382*h*.
aromatic acetates, P (5) 170*d*.
mineral, P (8) 288*c*.
for minerals and portland cement, P (8) 274*d*.
vinyl acetate, P (8) 288*e*.
of bone, (10) 348*f*.
continuous wet, of solid materials in tube mills, P (7) 259*c*.
cylindrical, controlling residual stresses in, (4) 89*g*.
diamond, of ceramics for circuit components, peculiarities in, (4) 110*i*.
in drum mills, improving, (6) 224*h*.
effect on precipitated Mg hydroxide, (2) 73*c*.
efficiencies, of minerals and cements, increasing, P (5) 191*b*.
electrohydraulic, of pure materials for spectroscopic analysis, (2) 71*b*.
Grinding *(continued)*
fine, of SiO_2, processes occurring during, (4) 151*c*.
form, ceramic materials, (8) 284*d*.
glass, with diamond grinding surface and emulsifiable composition, P (10) 339*j*.
with diamond grinding surface and alkali metal soap emulsifiable composition, P (11) 372*a*.
by fixed abrasive, (11) 370*d*.
method and apparatus, P (5) 186*c*.
over-, of cement clinker, (11) 368*f*.
plant, for differently grindable materials, P (1) 24*b*.
portable, higher speed lowers cost, (2) 43*f*.
portland cement clinker, P (5) 170*h*.
quality and economy, improvement in, (5) 186*c*.
spherical, of glass and sitall shapes, influence of diamond wheel characteristics, (2) 49*c*.
temperature, relation to cement quality, (4) 92*d*.
wet, in ball mill, kinetics: I; II, effect of peripheral speed, (10) 346*g*.
Grinding *(Material removal)*. See also *Abrasives; Diamonds; Polishing*.
vibratory and barrel finishing, proper media and compounds for, (4) 89*g*.
Grinding apparatus. See also *Abrasives*.
abrading, for finishing plates, P (1) 15*i*.
abrasive device, for finishing paint brushes, P (4) 89*h*.
for accurate removal of thin layers from rock slabs, (11) 380*f*.
for changing eccentricity of grinding wheels, P (6) 205*f*.
coolants, cleaning, (10) 335*f*.
and cutting and polishing ornamental stone, P (9) 314*g*.
disk sanding, P (4) 89*h*.
electrically conductive, P (6) 221*h*.
for glass, and polishing, P (1) 10*i*.
member, P (4) 89*j*.
mill, autogeneous, P (2) 73*j*.
mill, ore, control for, P (4) 125*d*.
for multifocal lens, P (5) 174*h*.
sonic, for rock material to powder, P (6) 230*d*.
wheel, abrasive, comprising novolak resin and thermoplastic polyhydroxyether, P (2) 43*g*.
abrasive cutoff, P (4) 89*g*.
abrasive flap, P (2) 43*f*.
abrasive, structure, P (2) 43*g*.
diamond, characteristics, influence on spherical grinding of glass and sitall shapes, (2) 49*c*.
diamond, measurement of wear in processing glass and sitall shapes, (1) 7*f*.
diamond, metal-bonded, dressing, in grinding ceramics for circuit component, (4) 109*j*.
diamond, resin-bond, grinding conditions for, (4) 89*j*.
diamond, shapes and factors affecting performance, (5) 169*g*.
diamond abrasive, with metal coated graphite lubricant, P (1) 1*j*.
dressing method, P (5) 169*h*.
flexible abrasive, P (4) 89*i*.
graphite-bond, for precision grinding, P (10) 335*g*.
improved with diamond and cubic BN grains coated with photopolymerized materials, P (2) 43*g*.
increased speed "make" cylindrical abrasive machining, (11) 367*g*.
and machine, abrasive cutting system, (11) 367*f*.
prestressed, P (6) 205*g*.
reinforced, P (6) 205*g*.
selection, effect of grain sizes, (10) 335*f*.
testing, (7) 243*g*.
use but not abuse, (7) 243*g*.
Gunn, effect, in CdTe, influence of ionized impurity scattering, (1) 31*a*.
Gunning, castable refractories on inside walls of blast furnace, (11) 373*h*.
hot, applied to electric furnace using BRI gun, (10) 341*i*.
Gypsum. See also *Plaster*.
argillaceous, content of dihydrate in, and strength of hardened hemihydrate plaster, (7) 244*i*.
articles, resistant to water erosion, and production, P (4) 92*g*.
ASTM standards, B (9) 333*h*.
board, structure, for neutron shielding, P (10) 336*c*.
as by-product from phosphoric acid process: VII, dehydration and hydration in mineral acids; IX, statistical study of crystal modifier in phosphate rocks, (4) 123*c*.
calcined, P (4) 92*c*.
cast articles, apparatus for, P (11) 368*c*.
castings, formed, P (10) 336*c*.
dehydration mechanism, and rehydration of hemihydrate, (1) 3*d*.
dihydrate-hemihydrate transformation in, (9) 303*i*.
effect on hydration of cement clinker, (4) 91*i*.
geology and mining, in southwestern Indiana, (4) 123*d*.
minerals and plasters, analysis by thermogravimetry, (8) 284*h*.
phospho-, phase transitions during firing, and strength of phosphoanhydrite cement, (8) 274*e*.

Gypsum *(continued)*
plaster, aging, (11) 367*j*.
quantitative analysis by DTA, (4) 120*j*.
in salt bearing formations of Moizons in the Ostolowaker, (4) 138*c*.
synthetic, for plasterboard, P (8) 274*c*.
thermal decomposition, two-stage, effects of inert materials, (5) 170*i*.
waste products from boric acid production as additives in grinding of clinker, (1) 2*f*.

Hafnia. See *Hafnium, oxide.*
Hafnium, carbide, free carbon determination in, (2) 69*h*.
carbide, high-temperature oxidation, (4) 138*e*.
diboride, borothermic preparation, (5) 192*g*.
high-pressure hot-pressing, densification mechanisms in, (4) 131*b*.
high temperature oxidation, (2) 78*g*.
strength, fracture mode, and thermal stress resistance, (4) 156*c*.
dioxide, new modifications produced under high pressures, (4) 146*g*.
monoclinic oxides, and solid solutions, optical energy gaps in, (1) 33*h*.
nitride, finely divided nonpyrophoric, P (6) 218*a*.
oxide, allotropy under high pressure, (9) 318*a*.
crystallization under hydrothermal conditions, (8) 290*f*.
freezing point measurement with solar furnace, (7) 266*d*.
phosphides, new, (8) 295*d*.
silicate, ground-state splitting of trivalent Gd and Cm in, determined by ESR, (11) 385*c*.
in silicates, simultaneous determination with Ta by neutron activation analysis, (1) 22*b*.
spectrophotometric determination, as reduced molybdosulfatohafnic acid, (10) 347*h*.
surface, formation of positive and negative ions on, (8) 292*i*.
systems. See *Systems.*
tetrachloride, vapor pressure and heat of sublimation, (8) 300*f*.
Halides, alkali, cellular prefreezing and premelting phenomena in, (7) 264*c*.
alkali, with CsCl structure, low temperature thermal expansion and related thermodynamic properties, (2) 79*e*.
crystals, with CsCl-type structure, thermal properties: I, construction of calorimeter for temperature region 1°-20°K and heat capacities of CsBr and CsI between 1.5° and 300°K, (4) 160*g*.
crystals, doped with hydrodroxyl ion, growth and characterization, (2) 78*d*.
crystals, NMR measurements of distortion effects around substitutional monovalent ions in, (8) 295*g*.
crystals, shell model for calculation of surface distortion in, (4) 126*i*.
crystals, spectroscopic constants for O_2^- ions in, (8) 298*c*.
crystals, theory of thermal equilibrium charge on edge dislocations in, (4) 160*g*.
defects in, ultramicroscopic study, (8) 300*b*.
electronic structure and molecular properties: III, NaCl, (2) 84*e*.
imperfect, lattice dynamics, (6) 234*j*.
melting parameters, (4) 144*d*.
optical birefringence in, (4) 147*h*.
pseudolocalized vibrations of M^{2+}-vacancy complex and thermal conductivity of, (4) 151*d*.
Schottky defect formation and kinetics of dissolution of precipitates containing divalent cation impurities in, (8) 297*c*.
single crystals, fluorometric determination of thallium in, (6) 226*h*.
single crystals, infrared spectra of borohydride ions in, (4) 140*g*.
solid solutions, (5) 199*g*.
symmetry of paraelectric defects in, (2) 83*d*.
alkali-metal, aqueous solutions, X-ray diffraction studies, (4) 164*d*.
crystals, plastic deformation, influence of color centers, (2) 78*j*.
of heavier salts, infrared absorption frequency and characteristic Debye temperature of, (2) 79*a*.
ions, removal from crude lithium aluminate, P (9) 317*f*.
of lanthanides and actinides, B (11) 389*e*.
metal, heavy, crystal properties, (4) 130*f*.
metal, vapor phase process for conversion into oxides, P (4) 126*b*.
Hall effect, devices, MOS field-effect transistor, P (9) 313*g*.
in graphite, (2) 84*d*.
in MnO, Li-doped, (4) 138*c*.
photo-, in $SrTiO_3$, (2) 81*g*.
in semiconductive TiO_2, (8) 292*g*.
in semiconductors, (4) 109*f*.
Halogens, compounds, highly pure, of Ga and In, production, P (5) 184*c*.
halogenating, molten metals, P (1) 24*a*.
Hardening, of alkali silicates aqueous solutions, structural and mineral-phase conversions during, (2) 45*c*.
hydrothermal, of cements, materials for, (2) 44*f*.
of inorganic cements: II, effect of bivalent and trivalent ions on structure and strength of hardened zinc-phosphate cements, (7) 245*f*.
kinetics, of binders, determination, (2) 44*d*.
kinetics, of portland cement, influence of inorganic salts and combinations on, (2) 44*e*.
Hardening *(continued)*
latent and work, in NaCl, (2) 84*f*.
latent and work, of NaCl single crystals, (2) 79*c*.
of MgO by diffusion of iron, (4) 138*e*.
of $MgO–Al_2O_3–H_2O$, $MgO–SiO_2–H_2O$, and $Al_2O_3–SiO_2–H_2O$ systems under hydrothermal conditions, (2) 58*e*.
particle, in Mn-doped NaCl single crystals, (2) 81*j*.
of portland cement, retarded by $AlPO_4$, P (2) 45*f*.
precipitation, by diffusion in stress field of dislocation, (1) 35*c*.
precipitation, in doped NaCl, (2) 81*j*.
rapid solid solution, in bcc iron and LiF, (1) 35*h*.
of slag portland cement during steaming, (1) 2*g*.
surface, of AgCl, effect of aqueous environment, (1) 27*d*.
Hardness, Brinell impact tests, accuracy, (11) 379*i*.
of dispersion strengthened aluminum alloys, time and temperature dependence, (9) 332*b*.
indentations, in MnSe and MnSe-MnS solid solutions, (9) 329*i*.
micro-, of glass, (6) 210*g*.
of glass in system Na_2O-MgO-SiO_2, dependence on composition, (2) 48*a*.
of glass, tests, (1) 8*g*.
of oxides of elements, (7) 267*c*.
tests, comparison with different indenters, (4) 119*e*.
of TiO_2-Nb_2O_5 solid solutions, (11) 386*b*.
of silica glass, (4) 96*b*.
Health. See also *Air, pollution; Dusts; Safety; Silicosis.*
radiological, principles, B (6) 242*a*.
Heat. See also *Conductivity, thermal; Temperature.*
of annealing, in simple alkali glasses, (11) 370*f*.
capacity, of adsorbate on surface coverage, dependence on BET theory assumptions, (1) 26*i*.
changes, in transformations from high-surface-area amorphous ice to stable hexagonal ice, (2) 76*h*.
of inorganic glasses and supercooled liquids, correction, (2) 49*i*.
lattice, of groups II–IV semiconductors—Mg_2Si from 15°-300°K, (4) 161*c*.
magnetic, of $Ni(OH)_2$ crystals, at low temperatures, particle size dependence of, (4) 148*f*.
of $MnTiO_3$, from 30° to 300°K, (8) 292*i*.
of $MnUO_4$, $NiUO_4$, and $MgUO_4$, (5) 194*g*.
of PuO_2, (10) 354*e*.
of silver iodide: I, experiments on annealed samples; II, theory, (4) 138*g*.
of silver sulfide, (11) 385*c*.
of sodium aluminate solutions at 25°-90°, (1) 30*a*.
of uranium monosulfide from 1.5° to 350°K, (2) 84*d*.
of combustion of plutonium nitride, (4) 138*g*.
content, of α-Al_2O_3, UC_2, and US between 330° and 1700°K, high-temperature adiabatic drop calorimeter for measurement, (5) 195*b*.
changes, in transformations from high-surface-area amorphous ice to stable hexagonal ice, (2) 76*h*.
of corundum from 0° to 2000°K, toward equation of, (7) 270*c*.
high-temperature, of four crystalline sodium-calcium silicates, (5) 195*c*.
high temperature, and heats of fusion of InSb, GaSb, AlSb, InAs, and GaAs, (10) 362*g*.
of mixing, in binary liquid alkali flouride mixtures, (8) 292*b*.
of mixing, in ternary fused nitrates, (5) 194*e*.
for self-diffusion in KBr, (4) 135*a*.
of UO_2 from 1200°-3100°K, (5) 194*h*.
content of formation, of AsF_5, (1) 29*i*.
of chromium trichloride, (4) 135*a*.
and entropy of aluminum(I) fluoride(g), (1) 29*g*.
of gaseous tantalum oxide and dioxide, (2) 76*h*.
of rare-earth fluorides, (9) 319*e*.
of thallium monofluoride, (2) 76*i*.
conversion, in GaAs grown from silica boats, photoluminescence study, (7) 255*h*.
of dissociation, of $Fe_2F_6(g)$, mass spectrometric studies at high temperatures, (7) 267*a*.
effect in continuous furnaces, (5) 189*b*.
exchange, structure, for rotary kilns, P (6) 228*f*.
exchangers, gas-fired, application of porcelain enamel to beat corrosion, (1) 3*j*.
glassed, construction, P (5) 172*a*.
for powdered materials suspended in gases, P (8) 284*f*.
with sloping grate sections, P (4) 118*c*.
of formation, of anhydrous sodium borates, (1) 30*c*.
of aqueous orthophosphoric acid, (8) 298*h*.
of $BeCl_2(g)$, $Be_2C_4(g)$, and beryllium(I) hydroxide(g), (5) 201*d*.
of BN and BF_3, halogen combustion calorimetry, (2) 55*i*.
of chromium carbides, (5) 194*i*.
of fluoroborates of Li, Na, and K, (9) 322*d*.
Heat, of formation *(continued)*
of group IIIA arsenides, measured by DDC, (4) 151*f*.
of lanthanide compounds, interrelations with melting point and lattice parameters, (10) 355*i*.
of lanthanum oxide, (1) 30*b*.
and lattice energies of superoxides of K, Rb, Cs, (1) 39*f*.
of lithium hexafluoroaluminate, solid, (9) 322*e*.
of $MgAl_2O_4(c)$, in reaction of $AlCl(g)$ with $MgO(c)$, (4) 152*d*.
of point defects in transition metal oxides, calculation, (9) 318*j*.
of sodium triphosphates, sodium pyrophosphates, sodium trimetaphosphate, and sodium tetrametaphosphate, (9) 330*e*.
of NaH_2PO_4, Na_2HPO_4, and Na_3PO_4, (8) 298*i*.
of solid solutions in system (Na-Ag)Cl and (Na-Ag)Br, (1) 30*d*.
standard, of oxides and hexaborides of rare-earth elements, (7) 269*h*.
of UC, (4) 138*h*.
of zoisite, muscovite, anorthite, and orthoclase, (4) 130*b*.
of fusion, of cristobalite, (7) 267*g*.
of fusion, and high-temperature heat capacity, of BeO, (1) 39*f*.
grooves, of polycrystalline materials, data evaluation, (8) 292*e*.
of hydration, of calcium sulfate hemihydrates measured by method of dissolution in HCl, (5) 170*e*.
of immersion, of alumina into aqueous sodium dodecyl sulfonate solutions, (1) 30*b*.
of immersion, on rutile surfaces, bare and silica-coated, (1) 30*d*.
immersion, relations, for homogeneous surfaces, (1) 30*i*.
loss, from ladles holding molten steel, effect of slag thickness on, (1) 12*b*.
resistance, of corundum ceramics, (10) 341*d*.
resistance, of glass, increasing by treatment in alkaline solutions, (6) 209*e*.
source, radioisotopic, P (5) 179*e*.
specific, of Corning 7560 glass between 4.5° and 20°K, (1) 8*j*.
data of CsCl, CsBr, and CsI, (5) 196*i*.
and of fusion, of crystalline boron oxide, (4) 155*d*.
low-temperature, of boronated graphite, (4) 143*c*.
of magnetic salts at low temperatures, measurements, (2) 80*j*.
of MnS through Néel temperature, (2) 83*f*.
surface, of crystal at low temperatures, lattice-dynamical calculation, (2) 79*d*.
of Zr hydrides containing 4 at.% U, (10) 360*h*.
study, of bonding in $CsCuCl_3$, (10) 362*f*.
of sublimation, of AlF_3 using entrainment method, (5) 202*i*.
of BaF_2, (4) 163*f*.
of calcium nitride, (8) 300*e*.
of cerium(III) fluoride, (4) 163*f*.
of praseodymium trifluoride, (10) 363*g*.
of tetrachlorides of Zr and Hf, (8) 300*f*.
transfer, analysis of solidification of binary eutectic system, (4) 138*i*.
member of glass or glass-ceramic material, and manufacture, P (4) 99*g*.
to non-Newtonian fluids, (2) 69*e*.
radiant coefficient, nomograph for, (6) 228*d*.
simultaneous with moisture, in porous systems with particular reference to drying, (6) 228*d*.
surface, enamel for, (1) 4*j*.
thermographic measurement, (2) 63*j*.
of transition, of $PbZrO_3$, role of impurities in, (1) 36*g*.
transmission, laws, during hot-forming of molten glass, (10) 338*b*.
treating, refractory materials at high temperatures, method and means, P (9) 314*h*.
treating, thin magnetic films in transverse magnetic field, P (2) 65*d*.
treatment, of anodic oxide films on niobium, (2) 77*j*.
of anodic oxide films on Ta: V, thermal redistribution of incorporated phosphorus, (2) 78*a*.
of carbon under 1, 3, and 5 kbars, (4) 133*g*.
effects on electron-gun-deposited SiO_2 films, (6) 220*f*.
effect of mechanical forces during, B (10) 366*c*.
effect on tensile strength of sapphire, (2) 76*a*.
of glass, influence during precrystallization period on nature of crystallization, (2) 49*d*.
influence on polycrystalline structure of sintered TiO_2, (10) 355*f*.
influence on properties of Al_2O_3 layers prepared with plasma gun, (9) 304*h*.
of MgO single crystals, (2) 78*a*.
of minerals, apparatus for, P (4) 122*g*.
of thorium oxide gel at low temperatures, (8) 287*c*.
two stage, of cobalt molybdate catalysts, P (4) 126*a*.
weakening of silica fibers by, (6) 211*j*.
waste, from glass furnaces to generate electric power, (9) 316*d*.
Heat conductivity. See *Conductivity, thermal.*

Heaters. See also *Thermoelectricity.*
catalytic radiant, P (7) 261*g*.
coils, coating, P (9) 304*h*.
electric resistance, P (2) 58*b*; P (5) 183*e*.
fuel block, P (4) 102*f*.
granular solids, performance estimate, (4) 122*f*.
infrared lamp, equipped with composite coated heat reflectors, P (8) 275*b*.
infrared quartz, P (11) 377*a*.
low intensity radiant, and burner for, P (1) 23*b*.
semicatalytic infrared, P (2) 72*g*.
Heating. See also *Thermoelectricity.*
curves, measurements with solar furnace, (5) 187*h*.
effect on strength of E-glass fibers, (4) 95*c*.
formed products, method and apparatus, P (4) 123*a*.
material, by microwave device, P (8) 287*d*.
pre-, particulate feed material for rotary kiln, P (7) 261*e*.
processes, in rotary kiln, P (2) 67*i*.
progressive, in analysis of gas inclusions, in minerals, (1) 25*g*.
re-, influence on reactivity of lime, (6) 215*i*.
rods, SiC, electrical resistance, dependence on Al_2O_3 and Fe_2O_3 content of SiO_2 used, (4) 103*d*.
transient surface, for excitation of surface elastic waves, (1) 29*d*.
under bias, effect on photoelectric threshold in MOS structure, (2) 76*b*.
uniformly, annular carbonaceous body, P (2) 59*h*.
units, electric, P (7) 249*f*.
Heating elements. See also *Electrodes; Thermoelectricity.*
coil, electrical, high-temperature encapsulated, P (5) 172*c*.
electric, P (8) 282*e*.
electrical resistance, adhesion to metal frame coated with insulating, preferably ceramic, material, P (5) 183*j*.
graphite, and furnaces containing, P (1) 23*b*.
high-power, compositions, (2) 62*g*.
high temperature electrical, connector for, P (2) 72*e*.
incased graphite segmented, P (6) 221*g*.
resistance, and method of conditioning heating surface, P (2) 72*e*.
SiC, sintered, comparison between oxidation and electrical aging of, (2) 57*a*.
transfer, for rotary kilns, P (8) 286*e*.
Heavy clay industry. See *Structural clay products industry.*
Hectorite, alkylammonium, synthetic, chemistry, (4) 128*e*.
solutions, study of light scattered when subjected to electric fields, (5) 200*j*.
Helium, escape from BeO compacts during irradiation, kinetics, (4) 142*b*.
solution and diffusion in tridymite and cristobalite, (5) 200*a*.
Hematite. See also *Iron, oxide, ferric.*
determination of small amounts of divalent Fe in, (6) 225*i*.
ferromagnetic domain structure, (1) 29*e*.
hydrothermal preparation from amorphous iron(III) hydroxide, (8) 293*f*.
reduction kinetics, to magnetite in hydrogen-water vapor mixtures, (6) 237*f*.
rock structure, (6) 237*a*.
single crystals, natural, stress-induced magnetic anisotropy in, (2) 83*h*.
NMR of ^{57}Fe in, (4) 147*a*.
remanent magnetization, (1) 36*c*.
topochemical reduction, via intermediate oxides in isothermal countercurrent reactor, (2) 83*b*.
Holmium, chloride, interactions with KCl in melts, (4) 140*e*.
oxide, polycrystalline, elastic properties, high-temperature measurements, (11) 384*h*.
oxide, polycrystalline, elastic properties, room temperature measurements, (10) 352*a*.
subfluoride, stability at high temperatures, (4) 143*d*.
Holography, lithium niobate crystal works to pack in 1000 holograms, (5) 181*g*.
reconstruction of three-dimensional microscopic sample using, (4) 121*c*.
Homogeneity, of glass, (2) 49*i*.
in-, of crystals grown by various methods, optical investigation, (10) 358*b*.
in-, in sodium borosilicate glasses, use of dielectric loss method in study of, (10) 338*c*.
in glass in flat glass tanks, effect of flow, (6) 209*a*.
of laboratory melts, technique for improving, (6) 211*d*.
non-, optical, of quartz, nature of, (5) 197*j*.
non-, in semiconducting materials, determination by optical reflection method, (2) 61*e*.
Homogenization, in cement industry, (2) 44*f*.
Hot tops. See *Refractories.*
Humidity. See also *Moisture; Water.*
sensing element, cross-linked electrical resistance, P (11) 381*e*.
sensor, Al_2O_3, P (7) 260*f*.
Hydrates, hemi-, obtained from Kola phosphate rock, anomalous properties, (4) 126*h*.
Hydration, of ρ-alumina and alumina gel in aqueous solutions of various basic reagents, (4) 138*j*.
of aluminous cement, early, (11) 373*h*.
of $3CaO{\cdot}Al_2O_3$ and $Na_2O{\cdot}8CaO{\cdot}3Al_2O_3$ as
Hydration *(continued)*
clinker minerals of portland cement, early stage, (4) 91*g*.
of calcium silicates, influence of tricalcium aluminate, (4) 140*e*.
cement, rate equation, (11) 368*b*.
of cement clinker, effect of gypsum addition, (4) 91*i*.
chemistry, of rapidly hardening slag portland cement, (1) 2*e*.
of clinker minerals, mixtures, and cements during initial periods, (1) 2*h*.
heat of. *See Heat.*
of monatomic ions, continuous dielectric model for, (4) 129*f*.
of monatomic ions, discontinuous model for, (4) 131*i*.
of portland cement, effect of soluble inorganic admixtures on, (2) 44*i*.
products, formed from calcium aluminates of high-alumina cements, stability and stabilization possibility, (2) 45*a*.
states of expanded phlogopite in relation to interlayer cations, (7) 266*h*.
surface, rate, on alumina, (4) 152*a*.
of tricalcium aluminate, influence of amorphous $Al(OH)_3$, (9) 323*d*.
of tricalcium silicate, (8) 286*h*.
and β-dicalcium silicate in neat portland cement pastes, (2) 44*e*.
early, solid reaction with induction and acceleration periods, (11) 384*c*.
influence of $Al(OH)_3$ and lime, (9) 323*a*.
Hydrides, carbo-, of transition metals, formation, (1) 30*a*.
Hydrocarbons, adsorption on clay minerals—adsorption of benzene, (10) 349*h*.
benzene, adsorbed, change in dielectric behavior when porous structure of silica gel is modified on purification, (4) 144*j*.
hydrocracking, with catalyst composite comprising Ni and Sn, P (1) 23*i*.
separation process employing crystalline aluminosilicates, P (11) 382*a*.
Hydrocracking, of hydrocarbons, with catalyst composite comprising Ni and Sn, P (1) 23*i*.
Hydrocyclones. See *Separators.*
Hydrofluoric acid, aqueous, reaction with kaolin, (2) 73*f*.
decomposition technique, for analysis of ferrosilicon, feldspars, and ion ores and slags, (9) 314*i*.
recovery from waste fluosilicic acid, (5) 190*j*.
Hydrogen, adsorbed on surface of MgO and CaO, paramagnetic defects associated with, (5) 198*e*.
atomic, thin film detector for, (2) 71*f*.
chemisorption on nickel films, surface potential study, (9) 330*i*.
and deuterium, in $SrTiO_3$ single crystals, (9) 322*h*.
diffusion, P (4) 109*c*.
rate, in room-temperature irradiated quartz, (5) 199*i*.
in thorium hydrides, activation energies for, (4) 126*d*.
evolution, from ferrophosphorus aggregate in portland cement concrete, (4) 91*h*.
fluoride, reaction with porous glass, (6) 211*c*.
$H_3B_3O_3$, cyclic, microwave spectrum, molecular structure, and dipole moment of, (4) 144*f*.
$H_3B_3O_3$, photochemistry, (11) 385*j*.
$H_2B_4O_4(g)$ and $H_4B_6O_7(g)$, thermodynamic stabilities, (4) 161*j*.
ion impact desorption from glass, (5) 173*a*.
permeation in vitreous silica, proton transport during, (7) 248*b*.
reaction with graphite, (4) 152*f*.
reaction with graphite at 1900°–2400°K, mass-spectrometric investigation, (11) 386*a*.
sticking probabilities on Mo films and filaments, (9) 330*g*.
thermal splitting from $Mg(OH)_2$, $Al(OH)_3$, and kaolinite, (6) 239*f*.
tracer evaluation, in steam-grown SiO_2 films, (4) 162*a*.
Hydrogen ion concentration, equilibrium, of commercial and experimental glasses, and relation with chemical durability, (2) 51*a*.
function, of glasses in system Li_2O-BaO-(Pr, Nd)$_2O_3$-SiO_2, (4) 95*i*.
measurement with glass electrode with temperature compensating diode means, P (2) 71*i*.
scale, new standards, (6) 227*f*.
Hydrolysis, of metal ions: LIX, uranyl ion in $MgNO_3$ medium; LX, thorium(IV) ion in 3*M* (Na)Cl medium, (10) 361*i*.
pyro-, separation of fluorine from aluminosilicates by, simple apparatus for, (6) 227*a*.
of SiF_4 by kaolinite at elevated temperatures, (8) 287*a*.
of single crystal CaF_2 from 1000° to 1120°C, kinetics, (5) 196*e*.
of sodium silicate: ultracentrifugation in chloride solutions, (1) 30*h*.
of Ta(V) in potassium fluoride-lithium fluoride, (2) 79*c*.
of UN, (4) 139*a*.
Hydrometer, method, of particle size analysis, (1) 21*b*.
Hydrothermal process, investigation, of GeO_2, (10) 355*e*.
studies, of system NiO–H_2O, (2) 78*c*.
Hydroxides, flow behavior during decomposition, (10) 353*d*.
Hydroxyl, groups, in kaolin minerals, study
Hydroxyl *(continued)*
using selective deuteration and infrared spectroscopy, (7) 269*e*.
groups, number at exterior surfaces of faujasite crystals, (2) 81*b*.
groups, reaction on silica surface with water and alcohol molecules, (6) 237*d*.
ions, in alkali halide crystals—growth and characterization, (2) 78*d*.
radical, ESR studies of, in γ-irradiated ice, (5) 194*d*.
radical and trapping site in γ-irradiated single crystals of ice, identification by ESR at 77°K, (5) 194*f*.
surface, population in bone mineral, (4) 158*b*.

Ice, crystals, growth from melt, preferred orientation in, (5) 198*g*.
γ-irradiated, ESR studies of hydroxyl radical in, (5) 194*d*.
high-surface-area amorphous, enthalpy changes and heat-capacity changes in transformations to stable hexagonal ice, (2) 76*h*.
nucleation under pressure and in salt solution, (8) 293*h*.
polymorphs, neutron diffraction study: I, ice IX, (8) 295*c*.
powdered, sintering, (1) 36*i*.
and silicate surfaces, interface between, (1) 31*e*.
single crystals, γ-irradiated, ESR at 77°K—identification of hydroxyl radical and its trapping site, (5) 194*f*.
single crystals, void formation during nonbasal glide in, under tension, (4) 163*f*.
step growth, during freezing of pure water, (5) 200*h*.
thermal etching, surface features observed during, (5) 200*g*.
Ilmenite, containing Cr, alkaline decomposition, (7) 261*j*.
modified, treated with sulfuric acid, decomposition products, water extraction of, (7) 262*c*.
ores, massive, production of TiO_2 concentrate from, P (10) 349*d*.
Immiscibility, in Al_2O_3-SiO_2 glasses, (4) 96*d*.
liquid-liquid, in common aqueous salt solutions at low temperature, (10) 356*i*.
metastable liquid-liquid, in binary and ternary alkali silicate glasses, (2) 51*e*.
Impact, resistance, and brittleness, (6) 230*i*.
Impregnation, of asbestos-cement products with thermosetting formaldehyde resin, P (4) 92*i*.
of graphite with refractory carbides, P (6) 217*b*.
of magnesite bricks, (4) 104*a*.
Impurities, alkaline earth, effects on ionic transport in CsI, (4) 133*e*.
cation, additional, influence on localized vibration modes due to *U* centers in NaCl and KCl, (2) 78*g*.
cobalt, of magnetite, (1) 26*e*.
content, method of analyzing materials to determine, P (6) 227*j*.
defects, influence on optical properties of $CaWO_4$, (4) 140*c*.
deposits on Al_2O_3 crystals, (10) 355*i*.
distribution, isomorphic, in garnets as function of solubility of trivalent oxides in molten salts and of method of crystal growth, (10) 356*d*.
in single crystals, (4) 139*e*; (10) 355*j*.
in single crystals: II, impurity striations in InSb as revealed by interference contrast microscopy, (1) 30*j*.
in solids, investigation with β-active isotopes, (2) 70*c*.
effect, on densification of oxides, (4) 132*i*.
on densification of silica glass, (7) 247*f*.
on formation of mullite from kaolinite-type minerals, (11) 384*c*.
in ionization dilatation of vitreous silica, (9) 306*a*.
on solidification kinetics measured by thermal wave technique, (4) 132*j*.
in electrofused corundum, (11) 382*c*.
gaseous, in solid materials, apparatus for mass-spectrometric analysis by laser beam, (4) 118*j*.
hydroxyl, single-particle and equilibrium collective effects in KCl, (2) 82*d*.
low melting point, effects of formation of zircon, (9) 320*c*.
metallic, of fibrous carbon products, method of decreasing, P (4) 106*g*.
in molten salts, segregation induced by cellular convection, and effect on crystal growth, (7) 268*j*.
oxide, effect on electrical resistivity of La-doped $BaTiO_3$, (2) 63*d*.
of phosphogypsum, chemical analysis, (4) 120*g*.
polyvalent metal, removing from lithium aluminate, P (9) 317*e*.
rare earth, detection in ionic materials by X-ray-stimulated luminescence, (1) 21*b*.
role in heats of transition of $PbZrO_3$, (1) 36*g*.
of Si of semiconductor purity, nondestructive and destructive neutron activation analysis, (5) 187*e*.
Ti mineral, removing from clay, P (9) 317*f*.
trace, detection in stoichiometric spinel crystals by instrumental neutron activation analysis, (7) 254*h*.

Impurities, trace *(continued)*
evaluation, in preparation of high-purity SiC crystals, (2) 77*a*.
in high-purity CaO, (2) 69*d*.
influence on crystallization of glasses, (1) 7*a*.
in yttria-alumina garnets, spectroscopic determination, (2) 70*j*.
in $(U\text{-}Pu)O_2$, spectrographic analysis, (8) 285*e*.
Index of refraction. See *Refractive index.*
Indium, antimonate, P (9) 317*d*.
antimonide, and arsenide, high-temperature heat contents and heats of fusion, (10) 362*g*.
cryogenic avalanche photodiode, with negative resistance characteristic at potential greater than reverse breakdown, P (9) 312*e*.
quantum effects in electron cyclotron resonance in, (11) 386*j*.
single crystals, impurity striations in, revealed by interference contrast microscopy, (1) 30*j*.
single crystals, pulled from melt, microscopic rates of growth in, (4) 144*a*.
theoretical explanation of low-field microwave emission from, (9) 331*a*.
antimonide-oxide-metal structure, oscillatory tunnel conductance induced by longitudinal optic phonons in, (4) 148*a*.
arsenide, epitaxial, on semi-insulating GaAs substrates, (2) 77*a*.
arsenide substrates, epitaxial InAs on, (4) 110*f*.
borate, rare earth cathodoluminescence in, (4) 152*e*.
chloride, fused, Raman spectra, (9) 328*b*.
chloride, interaction with Fe, Co, and Bi chlorides, (4) 140*d*.
InGaAs-CsO, low work function (less than 1.0 eV) photoemitter, (10) 344*g*.
InP-Cas-O, photoemission from, (1) 34*a*.
β-In_2S_3 "single crystals," domain structure due to ordering of In vacancies, (7) 265*g*.
orthoborate, terbium activated, cathodoluminescence, (2) 75*b*.
oxide and hydroxide, rhombohedral, crystal structure, (4) 139*i*.
sesquioxide, degenerate, conduction-ESR in, (4) 129*b*.
silicate and hydrogarnet, synthetic, (10) 362*e*.
sulfide, crystals, synthesis and growth in Ga and In melts, (6) 238*g*.
systems. See *Systems.*
Infiltration, of metals. See *Impregnation.*
Infrared, beams, crystallochemical selection of materials for control of, (2) 62*i*.
materials, reflection and transmission: III, spectra from 2μ to 50μ; IV, bibliography, (1) 36*b*.
radiation. See *Radiation.*
study, of $As_2Sn_2O_7$ stannates, (2) 82*f*.
of oxygen adsorption on impure ZnO, (10) 355*g*.
of rare-earth sulfates (4000–80 cm^{-1}), (5) 195*d*.
of water adsorbed on silica, (1) 31*d*.
technique, for dynamic treatment of chemisorbed species, mechanism of decomposition of formic acid over alumina and silica, (5) 193*g*.
transmission, in EuO, (10) 355*h*.
-transmitting materials, thermal expansion and physical properties, (1) 39*c*.
up-conversion, in lithium niobate with large bandwidth and solid acceptance angle, (9) 323*i*.
Infrared absorption. See *Absorption.*
Infrared spectra. See *Spectra.*
Inorganic materials, siliceous, analysis by atomic absorption spectrophotometry and hydrofluoric acid decomposition technique: IV, cements, clinkers, raw mixes, and siliceous limestones, (8) 284*i*.
Inspection. See *Quality control.*
Instrumentation. See *Controls.*
Instruments. See also specific types.
Coulter Counter, comparison with electron microscopy in analysis of particle size distributions of "monodisperse" particles from 0.8 to 3.5 μm in diameter, (4) 119*c*.
for grain size determination, (11) 380*d*.
improving resolution in, by hydrodynamic focusing, (5) 187*a*.
densitometer, scanning, for thermal profile analysis, P (2) 72*a*.
fluorescence radiation, radiating at 280 nm wavelength, and making, P (5) 188*f*.
laboratory aerosol device, (5) 188*g*.
Langmuir trough, controlled atmosphere, with simultaneous automatic recording of ellipsometric, contact potential, and surface tension measurements, (5) 187*d*.
for measuring absolute reflectance and transmittance at cryogenic temperatures, P (1) 22*c*.
porosimeter, for determining sizes of flaws in zirconia or other insulating films in situ, (2) 70*e*.
porosimeter, mercury, increased applicability for testing ceramic materials and products, (7) 260*f*.
quartz crystal microbalance holder, for low-temperature use in vacuum, (1) 21*h*.
spindle stage with easily changed liquid and improved crystal holder, (8) 285*f*.
Instruments *(continued)*
for study of excited nuclear states by angular correlation methods: transistorized electronic equipment, (1) 21*b*.
universal motion device, for use in ultrahigh vacuum, (2) 71*j*.
Insulating material, BN, for transformer, P (6) 224*a*.
coated on metal frame, adhesion of band-shaped metal parts to, P (5) 183*j*.
slurries, with conducting liquid and insulating solid phase, electric resistivity, (2) 76*i*.
Insulation, electrical. See also *Dielectrics; Glass; Porcelain.*
of circuit components of monolithic integrated circuits, P (2) 64*a*.
layer, measuring thickness by variation of dielectric of condenser using contacting electrode, P (5) 183*i*.
Insulation, thermal. See also *Fibers, glass; Mineral wool; Refractories, insulating.*
of fibrous brucite, P (6) 218*h*.
hot-press system, P (11) 374*j*.
rock and slag wool materials for, specifications, (1) 13*f*.
Insulators, electrical, P (8) 280*c*.
anomalous X-ray emission from, (10) 350*e*.
bonding electrically conductive metals to, P (4) 112*d*.
boron carbonitride tube, for protection of metal thermocouples, (6) 215*g*.
ceramic, in cable connections, P (7) 255*j*.
ceramic, factors affecting electrical breakdown, (2) 60*c*.
porcelain for, P (6) 220*a*.
porcelain, high voltage, American and European methods of manufacturing, (1) 15*f*.
strength, effect of glaze on, (2) 60*b*.
strength increase, (2) 60*d*.
production, mechanized at Westinghouse, (6) 219*j*.
spinel, single crystal silicon on, P (4) 117*a*.
stabilizing resistivity, P (2) 64*j*.
surfaces, breakdown in vacuum under dc voltage, measurements, (2) 63*f*.
suspension, with cap with internal load transmitting surfaces, P (8) 280*e*.
thin film, evaluation, (2) 62*a*.
thin-film, refractive indices, (10) 359*h*.
20 kV open-air to withstand fog and salt, (7) 254*a*.
voltage graded, P (9) 310*a*.
Interferometry, measurement, of large indices of refraction, (1) 31*h*.
Intermetallic compounds, Eu-Al, magnetic characteristics, (4) 110*f*.
Iodides, process, transport mechanism of U in, (8) 300*a*.
Ag, K, and Rb, solid-state reactions between, kinetics, (4) 142*f*.
Iodine, bromide, chloride, and I_2Cl_6 crystal properties, studies by Moessbauer effect in ^{129}I: I, chemical bonds; II, lattice dynamics, (4) 156*j*.
interaction with silica gel, nature of products from, (4) 145*j*.
Ionization, dilatation, of vitreous silica, impurity effect in, (9) 306*a*.
equilibria, in water at 25°C, effect of pressure, (11) 384*a*.
expansion, of pressure-compacted vitreous silica, (9) 306*b*.
gas, role of peroxides in, (5) 189*e*.
high-grade, in cold gas, (5) 189*c*.
impact, in CdTe, influence of ionized impurity scattering, (1) 31*a*.
potentials, electron affinities, and screening constants: VII, comparison with Hartree-Fock calculations, (9) 323*g*.
Ions. See also specific kinds.
alkali, electrical conductivity and electrolysis in silica glass, (7) 247*g*.
anions, contributions to electrical conductivity of alkali chlorides, (4) 126*e*.
effects, on colloidal suspensions of chrysotile asbestos, (4) 128*i*.
exchangeable, effect on mullite formation from kaolinite-type minerals, (11) 384*e*.
inorganic, reduction, salt effects in, at dropping mercury electrode, (10) 360*a*.
silicate, of 14 A tobermorite of Crestmore, and dehydration products, structure of, (5) 192*d*.
bivalent and trivalent, effect on structure and strength of hardened Zn-phosphate cements, (7) 245*f*.
borohydride, infrared spectra, in alkali halide single crystals, (4) 140*g*.
cation-anion distances in chalcogenide spinels, (7) 264*b*.
cation-dipole interactions in clay organic complexes, (7) 264*c*.
cations, alkylammonium, adsorption by montmorillonite, (7) 263*f*.
coprecipitation with $CaCO_3$: IV, Sr^{2+} with aragonite between 16° and 96°C, (6) 231*f*.
distribution, determination in cummingtonite-grunerite series by Moessbauer spectra, (4) 131*e*.
distribution in ferrimagnetic spinels, temperature dependence, (11) 387*j*.
distribution in garnet $Eu_3Fe_{1.94}Ga_{3.06}O_{12}$, (4) 127*i*.
distribution in multisublattice ionic crystals and applications to solid solutions of ferrimagnetic garnets and spinels, (10) 350*c*.
Ions, cations *(continued)*
distribution in orthopyroxene series, determination by Moessbauer effect, (4) 119*a*.
divalent, dispersion in NaCl, (8) 298*h*.
divalent organic, competitive adsorption by layer-silicate minerals, effect of adsorbent charge, (8) 290*j*.
exchange, clay, effect on foundry sand characteristics, (10) 341*a*.
exchange, of kaolinite, (10) 360*a*.
-exchange capacity, of layer-lattice minerals: I, discrepancies between two methods of c.e.c. determinations on montmorillonite; II, two types of cation-exchange sites on montmorillonite and their determination, (4) 127*j*; 128*a*.
exchange chemistry, and oxygen isotope, of feldspars, (4) 148*a*.
exchange reactions, heterovalent, in montmorillonite clay, thermodynamics, (9) 332*e*.
exchangeable, effect on mullite formation from kaolinite-type minerals, (11) 384*c*.
exchangeable, effect on thermal reactions of kaolinite, (4) 136*a*.
migration in tetragonal spinels ($MgMn_2O_4$), (10) 350*e*.
partitioning between coexisting single and multisite phases with application to assemblages orthopyroxene-clinopyroxene and orthopyroxene-olivine, (6) 235*e*.
vacancies, of magnetite, (1) 26*e*.
vacancies, mobility, in solid solution KCl-RbCl, (9) 325*i*.
complex, in liquid cryolite, identification, (6) 233*d*.
exchange, of crystalline zeolites, P (1) 23*j*.
double, method for making glass article, P (4) 98*b*.
and etching, for increasing glass strength, (8) 276*a*.
between glass and molten salt, thermodynamic aspects, (5) 173*h*.
membrane, diffusional interaction in, (11) 383*g*.
method for preparing metal oxide microspheres, P (7) 262*i*.
of montmorillonite at high pressures, (10) 356*d*.
multiple alkali, for strengthening glass, P (6) 213*f*.
for separating yttrium from rare earths, P (10) 349*e*.
series of advances: Vol. 2, B (7) 271*a*.
for strengthening glass, (5) 173*d*.
for strengthening glass sheets, P (4) 101*b*.
for strengthening silicate glasses, (4) 97*a*.
with two-phase glass, (5) 173*a*.
exchangers, ammonium phosphomolybdate and others, use in determination of potassium and sodium, (7) 259*j*.
ferrous and ferric, in ferrites with spinel structure, effect of hydrostatic pressure on magnetic anisotropy of, (2) 76*b*.
heterogeneous, incorporation into γ-Al_2O_3, (6) 233*g*.
impurity, valence state, influence on observed color in doped Al_2O_3 single crystals, (9) 323*g*.
inorganic, adsorption in black foam films, (9) 317*j*.
ionic bombardment, for detection of structure of sintered materials of Me-MeO system, (7) 265*a*.
ionic materials, pressure sintering, comments, (1) 26*h*.
ionic materials, strength and deformation, B (6) 241*c*.
of iron transition group, EPR in fluoroberyllate glasses, (8) 276*f*.
metal, first row transition, absorption spectra, in phosphate glasses, (4) 94*g*.
mobility, in crystals of mixed-alkali ferrite: $K_xNa_{1-x}Fe_7O_{11}$, (10) 356*d*.
molecule-, radiation-induced, in Al_2O_3, optical and magnetic properties theory, (10) 362*c*.
monatomic, discontinuous model for hydration of, (4) 131*i*.
monatomic, hydration, continuous dielectric model for, (4) 129*f*.
motion in tetrafluoroborate salts: I, NH_4BF_4 and ND_4BF_4, (4) 141*c*.
negative, vacancies, in irradiated MgO, (9) 325*b*.
nitrate, ultraviolet spectrum, in molten mixtures of alkali metal nitrates, (5) 202*c*.
oxygen, refraction, in three-component silicate melts, (2) 50*g*.
pair concentrations, effect on photoluminescence in ZnSe(Cu,In), (1) 28*h*.
phosphate, form, in fused calcium magnesium silicophosphate glass, (4) 94*j*.
positive and negative, formation on Re, oxygenated W, Hf, La hexaboride, and thoriated W surfaces, (8) 292*i*.
potentials, fields, and field gradients at lattice sites of corundum, self-consistent, (9) 329*e*.
radical, formation on aluminosilicates, chemistry, (5) 192*h*.
-selective properties, of polished porous glass, (4) 96*j*.
-selective properties, of sintered porous glass membranes, (5) 173*b*.
selectivity of fused SiO_2 in molten salts, (5) 197*a*.
sheath, effect on mechanical properties of clay soils, (5) 190*c*.

Ions *(continued)*
Na, K, Ca, and Mg, chromatographic separation, applied to identification of soluble salts in clays and clay products and of efflorescent salts, (9) 315*a*.
thermionic-field resistance maxima in metal-semiconductor (Schottky) barriers, (9) 311*e*.
3*d* transition metal, in MgO·3.5Al_2O_3 spinel, optical spectra, (8) 295*g*.
Iridium, coating for graphite, P (8) 279*d*.
Iron. See also *Enameling metals; Steel.*
amarantite, crystal structure, (6) 231*g*.
atomic fluorescence study on, (8) 284*j*.
bcc rapid solid solution hardening in, (1) 35*h*.
bcc, stabilized by phosphorus, oxygen diffusivity in, (2) 81*j*.
borates, under hydrothermal conditions, (9) 330*e*.
boride-type phases, ternary, with Y, La, and rare earths, (11) 388*c*.
carbides, thermally induced phase transformations in, (4) 161*d*.
cast, effect of gases on enameling of, and determination of gases developed during enameling, (5) 171*g*.
gray, chemical de-enameling, (6) 207*f*.
spheroidal graphite, consisting mostly of calcium-silicon, additive for production, P (4) 93*i*.
today, (8) 275*g*.
chloride, interaction with indium chloride, (4) 140*d*.
content of microcline, (9) 325*h*.
determination in high purity quartz by emission spectral analysis, (5) 187*a*.
determination by X-ray fluorescence analysis, (2) 68*f*.
diffusion, in single-crystal NiO, (4) 131*d*.
divalent, small amounts in Ni ferrite and hematite, determination, (6) 225*i*.
effect, on properties of tricalcium silicate, (10) 336*a*.
on ultraviolet absorption of high purity soda-silica glass, (1) 6*b*.
on whiteness of kaolins from Lower Silesia, (9) 316*i*.
ferric fluoride, crystallographic phase transformation in, (9) 319*j*.
ferric oxide, additions, effect on MgO sintering, (1) 28*g*.
α-, fine particles, shift of spin flip temperature of, (2) 82*j*.
α-, $FeTiO_3$, and FeO, high pressure Moessbauer studies on, (4) 138*a*.
α-, microcrystals, Morin transition in, (4) 145*c*.
α-, piezomagnetism, from EPR pressure experiments, (4) 149*j*.
α-, single crystals, formation by hydrothermal treatment of α-FeOOH, (7) 266*b*.
α-, twinned, bladelike platelet growths on iron, selected area electron diffraction study, (10) 360*d*.
α-, whiskers, crystal morphology and growth mechanisms on iron, (4) 130*e*.
α-, whiskers and twinned platelets, growth, dislocation and grain boundary diffusion in, peculiar to gaseous oxidation, (9) 320*f*.
amorphous, P (4) 125*d*.
calcined, dissolution, (4) 132*b*.
colloidal hydrous, mineralogical constitution, (1) 32*f*.
and ferrites, containing Bi_2O_3 additions, densification, (10) 343*j*.
γ-, and α-Fe_2O_3 mixed phase, exchange anisotropy in, (9) 321*b*.
γ-, mechanism of transformation to α-Fe_2O_3, (6) 235*b*.
γ-, transition into α-Fe_2O_3, effect of alkali, especially K^+ additon, on, (11) 384*c*.
reaction with sodium metaphosphate, (8) 297*e*.
solid-state reaction with ZnO, (9) 311*j*.
ferric oxyhydroxides, proton transfer studies in: I, hydrogen exchange between α-FeOOH and water, (9) 328*h*.
ferrous, oxidation in vermiculite and biotite alters fixation and replaceability of K, (5) 198*c*.
ferrous-ferric electronic interaction as a source of pleochroism in polarized optical absorption spectra of tourmaline, cordierite, chloritoid and vivianite, (9) 327*g*.
ferrous oxide, effect of hydrostatic pressure on Néel temperature in, (1) 27*j*.
in refractory silicates, Groves' method for determining, (8) 285*c*.
stoichiometric compound, high-pressure synthesis, (4) 138*a*.
ferrous sulfate, as retarder in cement set, P (5) 170*c*.
ferrous surfaces, composition and process for producing electrically resistant coating on, P (5) 171*j*.
formation, metamorphosed, of Gagnon Region, Quebec, Canada, mineral compositions and equilibria, (7) 262*f*.
in glasses, estimation by use of mercurous nitrate solution, (1) 9*h*.
hydroxide, heavy, α-FeOOD, preparation, (6) 233*f*.
-iron interaction, in iron-containing ZnS, (1) 31*b*.
Fe^{2+}, ground state in Al_2O_3 and calculation of spin-lattice relaxation, (6) 232*j*.
-Fe^{4+} equilibrium in flux-grown YIG, model for, (9) 325*i*.
Iron, Fe^{2+} *(continued)*
Moessbauer studies, in paramagnetic fayalite (Fe_2SiO_4), (4) 145*g*.
trigonal field splitting, in $GeFe_2O_4$, measurement by Moessbauer effect, (4) 143*e*.
($3d^6$), tetrahedral, optical absorption, in cubic ZnS, CdTe, and $MgAl_2O_4$, (4) 147*h*.
Fe^{2+}, cathodoluminescence spectra and coordination in β-$LiAlSi_2O_6$, (10) 350*c*.
centers, photosensitive, ESR, in CdSe, (1) 29*e*.
coordination in glass, (1) 6*d*.
EPR spectrum, in synthetic brown quartz, (11) 384*j*.
ESR, in $SrTiO_3$, with reference to 110°K phase transition, (1) 29*a*.
ions, relaxation in MgO, (4) 153*i*.
in quartz, zero-field EPR, (11) 388*f*.
Fe(II) hydroxide, thermal decomposition, (1) 39*a*.
Fe(III) hydroxide, amorphous, hydrothermal preparation of hematite from, (8) 293*f*.
Fe(III) oxide, diffusion into MgO single crystals in reducing atmopshere, (1) 27*j*.
finely divided cubic, transformation to trigonal, (4) 162*b*.
hydrate, chemical and physical properties, (9) 318*b*.
reaction with $BaCO_3$ in vacuo, (8) 297*e*.
trigonal sintering at low temperatures, (4) 154*i*.
Fe(III) tellurate, magnetic susceptibility and Moessbauer studies, (9) 325*d*.
^{57}Fe, in ferroelectric $BaTiO_3$, Moessbauer effect for: vacancy-impurity associated state, (5) 197*g*.
and Mg-Fe order-disorder, hyperfine splitting in orthopryoxenes ($MgSiO_3$-$FeSiO_3$ solid solution), (4) 139*c*.
Moessbauer resonance in oxidic spinels containing Cu and Fe, (10) 357*h*.
NMR, in single-crystal hematite, (4) 147*a*.
in silicate and phosphate glasses, high-pressure Moessbauer studies, (5) 172*g*.
$FeSb_2O_4$, magnetic structure, (1) 32*f*.
$FeBO_3$, stability, infrared spectrum, and magnetic properties, (2) 83*g*.
Fe_3C particles coarsening in solid state, (9) 326*d*.
Fe-Cr binary alloys, oxidation, (4) 148*c*.
Fe-Cr_2O_3, thermodynamic properties at high temperatures, (8) 300*h*.
$FeCr_2S_4$, thermoelectric power, anomalous, near Curie temperature, (2) 74*i*.
FeGe, crystal structure refinements of B 20 and monoclinic (CoGe-type) polymorphs of, (4) 130*d*.
α-FeOOH, prepared by different methods, lattice constant and thermal decomposition, (9) 324*d*.
Fe-Ni oxide spinel single crystals, growth by arc image techniques, (6) 220*h*.
Fe_3O_4, influence of stoichiometry on lattice parameter in, (10) 344*g*.
Fe_3O_4, octahedral sites, Moessbauer study of electron hopping in, (9) 325*j*.
$FeSe_2$, neutron diffraction investigation, (9) 325*c*.
FeS and $Fe_{1-x}S$, miscibility gap between, (2) 80*c*.
FeS_2, smithite-rhombohedral, synthesis, (9) 331*i*.
Fe_3W, polycrystalline hexagonal, effect of varying ferrous contents, correction, (4) 150*c*.
in kaolins of Lower Silesia, (9) 326*d*.
layers, spontaneously magnetized monoatomic, in graphite, (9) 329*h*.
and Mg, distribution in coexisting biotite, garnet, and cordierite, (7) 265*g*.
and Mg, mixed hydroxides and oxides, surface area and pore structure, (1) 38*g*.
-manganese alloys, internal oxidation, (4) 140*h*.
molybdate, three modifications, magnetic, Moessbauer, and structural studies, (11) 385*h*.
ores and slags, analysis by atomic absorption spectrophotometry and hydrofluoric acid decomposition technique, (9) 314*j*.
oxalate, decomposition and surface properties, (1) 39*b*.
oxalate complexes, thermal decomposition, (4) 160*j*.
oxidation, effects of crystallographic orientation and oxygen pressure, (4) 133*e*.
oxide, interaction with zirconium oxide at high temperatures, (9) 323*c*.
melt, density, in equilibrium with CO_2-CO gas mixture, (8) 290*j*.
thermodynamic properties, by emf measurements, (10) 362*j*.
oxides, crystalline structure, relation with glass polishing efficiency, (5) 173*e*.
electrical conductivity and sintering at high temperatures, (8) 291*b*.
influence on properties of glasses and enamels, (1) 7*j*.
paramagnetic resonance, in glass, (10) 338*f*.
at parts-per-billion levels, determination by quenching of 2,2′2″-terpyridine luminescence, (8) 284*i*.
phosphate, solid solubility, in $AlPO_4$, (1) 37*e*.
powder, for forming sintered articles of improved strength, P (4) 106*c*.
rare-earth, borates, synthesis and crystallographic data, (11) 387*i*.
Iron *(continued)*
sheet, process control in application of enamel to, (4) 93*c*.
siderite, deposits, formation in system Mg^{2+}-Fe^{2+}-CO_3^{2-}-Cl^{2-}-H_2O, (10) 353*h*.
single crystals, oxidation at 350°C, (4) 148*c*.
spectra, in alkaline earth phosphate glasses, (2) 51*e*.
spectrophotometric determination in high purity Y_2O_3 with 1-(2-pyridylazo)-2-naphthol, (10) 347*g*.
spectrophotometric determination with 2-pyridyl-2′-hydroxymethane sulfonic acid, (10) 347*h*.
and steel industry in U.S., use of refractories in, (2) 57*h*.
and steelmaking, refractories for, problems from standpoint of iron industry, (5) 177*d*.
substitution in kaolinite, (4) 157*f*.
sulfide pyrite, single crystals, preparation by chlorine transport, (6) 236*e*.
surfaces, [100] and [110] oxide covered, thermal regeneration, (4) 160*i*.
systems. See *Systems.*
and titanium, simultaneous determination by polarographic methods, (5) 188*c*.
titrimetric determination, by tin(II) chloride-mercury(II) chloride-dichromate method, interference of V in, (9) 315*i*.
trifluoride, sublimation pressure, and heat of dissociation of $FeF_3(g)$, mass spectrometric studies at high temperatures, (7) 267*a*.
trivalent, germanates, (4) 137*g*.
Irradiation. See also *Radiation;* specific types.
damage and hardening, in single crystal MgO after low neutron doses $<10^{18}$ *nvt* (>1 MeV), (5) 196*a*.
effect, on chrysoberyl, (6) 232*e*.
by fission products, (2) 73*e*.
in thermally grown SiO_2, (9) 323*i*.
induction of macroscopic growth by, in α-Al_2O_3 single crystals, (4) 141*h*.
influence on ceramic materials, (2) 60*f*.
influence in nucleation of gas bubbles in reactor fuels, (5) 195*j*.
low temperature neutron, effect on density and lattice parameters of Al_2O_3 and MgO, (4) 133*a*.
neutron, of BeO at high temperatures, damage, (1) 33*i*.
fast, effect in sintered alumina and magnesia, (4) 132*e*.
fast, induces changes in polycrystalline Al_2O_3, (4) 128*f*.
pre-, effect on B_4C oxidation in nuclear reactor, (5) 199*j*.
target elements, aluminum-clad thoria, method of dissolving, P (2) 59*a*.
testing (pulse conditions) of ternary fuel system for power burst facility, (9) 308*i*.
ultraviolet, effects on properties of evaporated SiO films, (6) 220*f*.
under restraint, graphite structure changes on, (5) 192*a*.
Isotopes. See also *Radioactive tracers.*
β-active, for investigation of impurities distribution in solids, (2) 70*c*.
exchange, CO, with TaC, (10) 350*b*.
exchange, for measurement of anionic diffusion of KBr, (8) 294*g*.
fissionable, detection, identification, and analysis, P (10) 347*i*.
oxygen, and cation exchange chemistry of feldspars, (4) 148*a*.
effects in oxidation of water by transition metal ions, (9) 326*a*.
of minerals from carbonatites of Fen area, South Norway, (4) 148*c*.
radio-, ^{45}Ca, erosion tests on ladle brick by means of, (11) 373*d*.
heat source, P (5) 179*e*.
^{110}Ag, for measuring diffusion coefficient of Ag^+ ions in glass, (6) 210*c*.
for tagging foundry refractories, (2) 57*g*.
use to measure lining wear in steel furnaces continuously, (7) 250*h*.

Jadeite, thermodynamics, (9) 332*d*.
Jahn-Teller effect, in pressure shift of absorption bands in MgO:Fe^{2+}, (10) 359*a*.
Jewelry. See *Art and artware.*
Joints. See also *Seals and sealing.*
butt, for flexible abrasive sheet material, (1) 1*g*.
hermetic metal-ceramic, deformation-film method for preparing, (2) 62*j*.
pipe, P (6) 214*e*.
between refractory panels, method and material, P (6) 218*a*.
strengthened arc carbon electrode, P (2) 59*g*.
welded, between Al_2O_3 and metals, mechanical and thermal properties, (7) 246*b*.
Junctions, Al-Al_2O_3-Sb, tunneling characteristics, (8) 300*a*.
device, distributed barrier metal-semiconductor; multiplane, P (9) 312*e*.
electroluminescent, including Bi-doped group III(a)-V(a) composition, P (4) 112*g*.
light emitting, using silicon as dopant, P (5) 183*h*.
solid state, for ultraviolet detection, P (4) 117*b*.
diffused, avalanche breakdown in, (1) 16*b*.
fused, between Ge-Si semiconductor member and junction element, and production, P (7) 256*i*.

Junctions *(continued)*
GaAs *pn* ,"cold-cathode," electron emission from, (9) 310*j*.
hetero-, CdTe-InSb, formation, (8) 281*h*.
hetero-, devices, formation by epitaxial growth from solution, P (9) 312*j*.
pn, in $Cd_{1-x}Mg_xTe$, visible electroluminescence from, (9) 332*j*.
epitaxially producing in silicon, P (2) 65*a*.
formation in ion-implanted ZnTe, and type conversion, (9) 311*h*.
formation by thermal oxidation, P (4) 115*f*.
in *n*-CdTe produced by ion implanation, (4) 163*a*.
nitrogen-doped GaP, efficient green electroluminescence in, (9) 320*f*.
pn alloy, P (5) 183*g*.
semiconductor, device, P (11) 378*f*.
semiconductor, making by diffusion, P (8) 283*b*.
thin film rectifying, with graded CdSe-ZnSe film, P (4) 116*b*.

Kaolin, calcined, transformed into mixture of crystalline Na zeolite and amorphous aluminosilicate, P (9) 317*h*.
deposits, West German, geological and petrographic studies: I, sampling and investigational methods; II, at Lohrheim near Dietz an der Lahn, (7) 262*e*; III, Geisenheim/Rheingau; IV, granite kaolins in East Bavaria—Tirschenreuth, (11) 382*b*.
effect of metalizing CuS with Al_2O_3, (2) 62*b*.
Georgia, flow behavior during decomposition, (10) 353*d* .
Harghita, as ceramic bond for abrasives, (4) 89*f*.
from Lower Silesia, effect of iron content on whiteness, (9) 316*i*.
from Lower Silesia, occurrence of iron in, (9) 326*d*.
minerals, hydroxyl groups in, study using selective deuteration and infrared spectroscopy, (7) 269*e*.
preparation of clay concentrate from, (7) 262*i*.
rational analysis, (4) 121*b*.
raw, from Osmosa-Bogicany in West Bohemia, (6) 229*i*.
reaction with fluorides: I, effect of neutral and acid sodium fluoride solutions; II, effect of aqueous hydrofluoric acid, (2) 73*e*; III, hydrolysis of SiF_4 by kaolinite at elevated temperatures, (8) 287*a*.
reactions of phosphates with, (1) 26*a*.
suspensions, thixotropic and sedimentation volumes, cause and influence, (11) 375*f*.
systems. See *Systems*.
volumes, thixotropic and sedimentary, (4) 124*b*.
Kaolinite, cation exchange, (10) 360*a*.
chemisorption of methylene blue by, (7) 253*d*.
compacted, particle association in, (10) 358*g*.
crystallization, from H-exchanged zeolites, (6) 234*c*.
dehydroxylation kinetics, (6) 234*d*.
hot-pressing, reactive, (4) 153*a*.
intercalation mechanism, by alkali acetates, (4) 143*j*.
iron substitution in, (4) 157*f*.
layer structure, relaxation by dehydroxylation, (5) 196*b*.
low temperature hydrothermal transformations, (8) 289*i*.
minerals, high-temperature reactions, kinetics and mechanism of formation, (4) 142*e*.
reaction with sodium carbonate, kinetic and electron optical studies, (8) 293*j*.
suspensions, rheological characteristics and deposition, (9) 329*a*.
thermal reactions, high-temperature, effect of exchangeable cations, (4) 136*a*.
thermal splitting of H_2 from, (6) 239*f*.
Kilns. See also *Burners; Furnaces; Ovens*.
American brick, (10) 340*d*.
brick, brick chimney for, P (1) 23*a*.
brick firing, one-high, features production cycle of less than 24 h, (4) 122*j*.
Bull's trench, thermal efficiency, (10) 348*d*.
ceramic tunnel, studies on flow patterns of gases in, by model techniques, (4) 122*f*.
continuous pottery, with slidable stretchers, P (10) 348*d*.
design, construction, and operation, B (9) 334*g*.
design, unique, can save fuel costs, (8) 286*e*.
enameling U-, determination of optimum operating point of industrial furnace as exemplified by, (11) 368*i*.
enameling, U-type, review, (1) 4*c*.
for firing clay slate and clay, P (6) 228*g*.
gas chamber, with mobile hearth for firing technical ceramic bodies and articles, (6) 228*h*.
gas fired, continuous vertical, for heating formed products, P (4) 123*a*.
gas-fired, in small art pottery, (10) 335*i*.
glassmelting, color change of melts in, (8) 276*a*.
for hard-fired brick, (5) 188*j*.
Hover-, for faster firing, (4) 122*h*.
inclined, P (7) 261*c*.
linings. See *Refractories*.
recent developments, (7) 261*e*.
roller, rapid firing of face plates in, (11) 372*e*.
roller hearth, fires alumina, (4) 105*h*.
rotary, construction, P (5) 189*f*.
heat exchange structure for, P (6) 228*f*
Kilns, rotary *(continued)*
heat transfer elements for, P (8) 286*e*.
heating apparatus and process, P (5) 189*c*.
heating processes in, P (2) 67*i*.
multiple-support, pneumatic supporting device for, P (7) 261*f*.
and traveling grills, for thermal treatment of minerals, P (4) 122*g*.
rotary cement, sintering zone, wear of magnesia-chrome bricks in, (1) 18*d*.
top-fired, successful at Continental, (4) 122*e*.
tunnel, capacity and economic efficiency, for porcelain, (6) 228*d*.
channel width, effect on unformity of firing, (6) 228*h*.
continuous, having rotary roller sole for firing ceramic materials, P (10) 348*d*.
for continuously firing ceramic charge material, P (11) 381*j*.
for firing large diameter clay pipe in Germany, (6) 214*f*.
heat and energy balance, (10) 348*c*.
high temperature electric, for production of crystalline refractory and abrasive materials, P (6) 228*f*.
holds ±10°F throughout load, (8) 286*d*.
maintenance, P (10) 348*e*.
new design from jet firing, (4) 122*i*.
performance affected by channel width, (1) 22*j*.
research, (5) 188*j*.
unloader control and programing switch, P (7) 261*f*.
vertical, material distributing device in, P (4) 123*c*.
water models, flow studies on, (4) 119*g*.
Kinetics, of attack of high-temperature Mo and W by atomic oxygen, (4) 141*i*.
of Be fluorination, (4) 142*d*.
of bulk crystallization of glasses, (10) 338*a*.
of calcium oxalate pyrolysis, (4) 142*a*.
carbon transport, influence on solution growth of β-SiC crystals, (4) 139*g*.
of chemical reactions, sintering, and collective recrystallization of refractory oxides, role of surface phenomena in, (7) 268*h*.
of combination of O atoms with O molecules, (8) 294*b*.
of crocidolite, dehydroxylation, (4) 142*f*.
of crystal growth from solution, (5) 196*e*.
data, algorithm for evaluating, from nonisothermic thermogravimetric curve, (2) 68*e*.
of desorption of water from rutile surface, (1) 31*d*.
dissolution, at dislocation sites in NaCl crystals, (6) 231*h*.
dissolution, and Schottky defect formation, of precipitates containing divalent cation impurities in alkali halides, (8) 297*c*.
of effects of X- and γ-ray radiation on thermal decomposition of solid orthorhombic ammonium perchlorate, (8) 291*a*.
electro-, stability, of clay suspensions, effect of polymer adsorption, (1) 28*b*.
flotation, validity of equations for, (4) 163*c*.
of fluorination of UO_3 pellets by F_2, (5) 196*c*.
of formation, of forsterite by solid state reaction of MgO and enstatite, (4) 142*j*.
of $MnSO_4$ from MnO_2, Mn_2O_3, and Mn_3O_4 and decomposition to Mn_2O_3 or Mn_3O_4, (4) 142*e*.
of zinc ferrite, (4) 142*c*.
glass crystallization, (4) 96*b*.
of glass silvering reactions, (9) 306*c*.
grain growth, (8) 296*a*.
of graphite-UO_2 reaction from 1400° to 1756°C, (7) 267*i*.
growth, of grain-boundary precipitates, (1) 30*i*.
of helium escape from BeO compacts during irradiation, (4) 142*b*.
of heterogeneous reaction of silica with basic alkali-metal salt solutions in chloride melts, (9) 323*j*.
of hydrolysis of single crystal CaF_2 from 1000° to 1120°C, (5) 196*e*.
of interaction of sulfur dioxide with clean and oxidized metal films of Fe, Ni, and Pb, (9) 324*b*.
of isothermal sintering of low-fired MgO obtained from crystalline $MgCO_3$, (5) 196*f*.
of isothermal transformation, apparatus for investigation by X-ray method, (6) 225*g*.
of kaolinite minerals high-temperature reactions, (4) 142*e*.
of leaching of lead glass by EDTA, (8) 276*d*.
linear, of Cu and Cu-Ag alloys oxidation in CO_2 at 1000°C, (4) 148*b*.
of MnO reduction from basic slags by Si dissolved in liquid Fe, (2) 79*j*.
and mechanism of moisture expansion, (9) 325*a*.
of mullite formation in system Al-fluoride-SiO_2: II, mechanism of mullite formation with anhydrous AlF_3, (5) 196*h*.
near-equilibrium, of dissociation of cupric oxide, (4) 145*j*.
oxidation, of Cr and Fe-Cr alloys, effect of oxide volatilization, (1) 28*b*.
parabolic, of niobium, (2) 81*j*.
of Pt, with convective diffusion and surface reaction, (4) 150*a*.
of polydimensional SiO, (4) 148*e*.
of powdered silicon nitride, (6) 235*d*.
of single crystal TiN by optical measurements, (11) 386*a*.
of superpurity aluminum in dry oxygen, (1) 31*e*.
Kilns, oxidation *(continued)*
and vacancy generation, (9) 332*f*.
of Zr powder at high temperatures in O_2 and CO_2 atmospheres, (10) 358*f*.
of oxygen evolution at Pt anode in Li silicate melts, (7) 267*i*.
of phototropic process in glass, (4) 96*f*.
of precipitation in system $MgO-Al_2O_3-Cr_2O_3$, (6) 234*d*.
reaction, relation to phase diagrams and structure of glass melts, (9) 307*b*.
recombination, in CdS, (9) 328*f*.
reduction, of hematite to magnetite in hydrogen-water vapor mixtures, (6) 237*f*.
sintering, of $BaTiO_3$, (7) 255*d*.
sintering, based on geometric models, comments, (6) 231*e*.
of solid-state reactions between iodides of Ag, K, and Rb, (4) 142*f*.
of solid-state reaction between MgO and Fe_2O_3, (4) 142*e*.
solubility and dissolution, of precipitated amorphous SiO_2 in *M* $NaClO_4$ at 25°C, (8) 297*i*.
solubility of quartz, (9) 324*b*.
solution, of CaO in liquid phase of cement clinker, (7) 245*a*.
solution, of dicalcium and tricalcium silicate in liquid phase of cement clinker, (8) 274*h*.
steam oxidation, in UO_2 at high temperatures, (10) 361*b*.
of stress in glass caused by ultraviolet radiation, (6) 211*i*.
study, of disproportionation and explosion of chlorites and thermal decomposition of metal chlorates, (5) 201*j*.
in high-temperature processes accompanied by changes in weight, apparatus for, (2) 68*j*.
of reaction processes between kaolinite and sodium carbonate, (8) 293*j*.
of thermal growth of SiO_2 films in water vapor-O_2-Ar mixtures, (1) 31*f*.
transformation of GeO, (4) 142*g*.
of wet grinding in ball mill, (10) 346*g*.
Krypton, adsorption, low-temperature, for determination of specific surface area, (1) 27*f*.
bubbles, migration in UO_2, (4) 144*f*.
fission induced sorption, in UC, (9) 321*e*.
as probe of electrostatic fields in Y zeolites, (10) 348*g*.
Kyanites, -andalusite, and andalusite-sillimanite equilibria experimental determination—aluminium silicate triple point, (7) 265*g*.
concentrate, sintering in rotary-type furnaces, (10) 348*h*.
and sillimanite, heavily ground, high pressure hydrothermal measurements on, (7) 266*c*.
-sillimanite concentrate, Florida, refractory properties, (8) 279*c*.
-sillimanite equilibrium, thermochemistry, (7) 270*a*.
-sillimanite reaction, bivariant, experimental evidence, (7) 265*h*.
stability range, experimental determination, (6) 232*f*.
structure, comparison of two refinements, (1) 26*h*.

Ladles. See *Refractories*.
Laminates, composite engineering, B (11) 388*f*.
reinforced resin, evaluation, correlation and analysis of ultrasonic test results in, (11) 380*b*.
Lamps. See also *Glass; Glassmaking apparatus*.
Al_2O_3-ceramic sodium vapor, P (10) 344*a*.
bridge making method and apparatus, P (5) 175*c*.
bulb, baseless, making, P (2) 53*f*.
ceramic discharge, P (11) 376*i*.
colored, plural coated transparent, and forming, P (5) 176*c*.
compact source discharge, P (5) 174*b*.
composite article, with glass-ceramic lamp envelope, P (9) 307*b*.
discharge, with phosphor normally sensitive to lehring, P (6) 221*g*.
electric, P (1) 10*b*.
filament mount structure for, P (7) 248*g*.
and method of detecting leaks in, P (2) 52*h*.
removing alkali contamination from, P (5) 176*d*.
sealed-beam type, with noncircular lens component, P (4) 101*d*.
electric discharge, with arc tube mounting, P (2) 52*j*.
high-pressure, with magnetically actuable arc ignition and apparatus for starting, P (9) 312*b*.
with ionizable atmosphere, process for filling, P (5) 176*d*.
with starting resistor impedence twice that of lamp impedance, P (8) 282*e*.
electric heat, and electric devices, P (4) 112*d*.
electric incandescent, P (9) 307*c*.
filament support for, P (7) 248*g*.
with shock and vibration resistant filament support structure, P (7) 248*c*.
flash, containing combustible gas mixtures, method of heat-sealing, P (2) 53*d*.
fluorescent, P (11) 371*f*.
fluorescent, apertured, with lens along aperture, P (10) 344*a*.
fluorescent panel, with white emitting phosphor coated on envelope backplate and red emitting phosphor coated on envelope faceplate, P (2) 64*h*.

Lamps *(continued)*
fused projector, P (4) 113*g*.
gas filled, completed, method for gettering, and product, P (7) 249*e*.
glower, and process, P (6) 221*b*.
halogen regenerative cycle incandescent, P (10) 339*g*.
incandescent, P (4) 99*i*.
with addition of fluorine compounds to operating gas filling, P (4) 99*j*.
decorative, P (11) 371*e*.
direct filament enclosed, and contact means for, P (9) 307*b*.
fabrication and construction, P (4) 99*i*.
with filament of hexaboride of rare earth metal, P (1) 18*i*.
with filament surrounded by wire screen, P (10) 345*b*.
halogen-cycle, with planar filament, P (7) 248*i*.
with refractory metal carbide filament, P (2) 65*b*.
single-ended electric, filament support, P (1) 19*i*.
tubular halogen cycle, with inner cylinder for universal operation, P (6) 224*b*.
vacuum type electric, P (11) 371*i*.
infrared incandescent quartz, P (8) 282*j*.
lead wire terminal, P (5) 175*c*.
low pressure electric discharge, electrode for, P (9) 312*f*.
mercury, bismuth halide photochemical arc, light sources, P (9) 307*h*.
metal arc type, harness construction for, P (5) 182*c*.
metal vapor, with metal additive for improved color rendition and internal self-ballasting filament used to heat arc tube, P (8) 282*e*.
metal vapor discharge, P (9) 312*g*.
monogram and monogram ink, P (8) 277*d*.
panel, mechanically based rear loading, P (1) 11*b*
phosphor adherence, P (5) 183*g*.
photoflash, P (7) 249*b*.
projection, with wire screen for blackening prevention, P (11) 378*j*.
quartz, fused, calculation of water diffusion into, (7) 246*j*.
quartz iodine, for fluorescence microscopy, (4) 119*h*.
refractory oxide incandescent, P (9) 313*c*.
refractory oxide incandescent, with preheater, P (4) 116*g*.
regenerative cycle electric incandescent, P (4) 116*g*.
single-ended halogen quartz, heat-dissipating adaptors for, to existing electrical lighting apparatus, P (1) 18*g*.
sodium vapor discharge, with infrared reflecting coating, P (1) 19*j*.
tubular glass, surface, blackening and structural changes on, (9) 305*b*.
tungsten filament iodine cycle incandescent, with alkali metal getter, P (4) 117*b*.
twin filament, P (4) 101*e*.
vapor discharge, high-pressure metallic, including mercury and thallium iodide, (6) 221*f*.

Lanthanides, chelates, fluorescent, of dibenzylamine, P (5) 183*c*.
compounds, interrelations of melting point, heat of formation, and lattice parameters, (10) 355*i*.
halides, B (11) 389*e*.
higher sulfides of, study, (1) 38*e*.
ions, and Cr^{3+}, in $LiNbO_3$ crystals, EPR, (2) 76*c*.
$LnCrTeO_6$, new series of compounds based on $PbSb_2O_6$ structure, (10) 356*a*.
mixtures, containing cerium, fractionating, P (5) 191*f*.
oxides, freezing points of 15 measured with solar furnace, (7) 266*d*.
oxides, freezing points and melting behaviors measured with solar furnace, (4) 136*g*.
sulfates, ultrasonic absorption in, (8) 300*c*.

Lanthanons. See *Rare earths.*

Lanthanum, aluminate, preparation by joint precipitation, (5) 198*h*.
fluoride, near ultraviolet optical constants, (1) 33*i*.
hexaboride, crystallization, (9) 319*i*.
hexaboride, surface, formation of positive and negative ions on, (8) 292*i*.
hexaboride cathode system, for electron beam generator, P (7) 256*g*.
hydrides, magnetic properties and electronic structure, (4) 143*g*.
$LaCoO_3$, semiconducting properties, (10) 360*f*.
$La_5Fe_3C_{1.5}$, crystal data on, (9) 319*b*.
$LaNi_{1/2}Mn_{1/2}O_3$, ferromagnetism in, (1) 29*g*.
$La_3O_3{\cdot}5Nb_2O_5$, roentgenography, (8) 297*a*.
$La_4Re_6O_{19}$, characterization and structure, (11) 383*h*.
$La_4Re_6O_{19}$ and rutile-related dioxides, metal-metal bonding in, (6) 235*d*.
and neodymium oxides, reaction with oxides of elements of second group in periodic system, (8) 297*f*.
oxide, heat of formation, (1) 30*b*.
oxide, retention of additives in, (5) 199*c*.
phosphate-vanadate, structure and luminescence, (4) 156*h*.
sesquicarbide, superconductivity in, (10) 357*i*.
systems. See *Systems.*

Lapping, dual-wheel, kep to pump quality, (8) 273*f*.

Lapping *(continued)*
production, of lead zirconate-titanate ceramics, (1) 17*h*.

Lasers. See also *Masers.*
action, in field-ionized bulk GaAs, (1) 31*g*.
apparatus, utilizing luminescent material, P (9) 312*f*.
beam, for cutting glass with absorbent, P (10) 339*d*.
focusing by active CdS oscillator, (2) 77*f*.
for treating molten glass, P (4) 100*b*.
use in apparatus for mass spectrometric analysis of distribution of gaseous impurities in solid materials, (4) 118*j*.
characteristics, of single crystal yttrium-gadolinium-aluminum garnet, (9) 322*e*.
components, P (10) 339*b*.
construction, plural fiber optic, P (4) 100*g*.
for controlled separation of brittle materials, (10) 343*j*.
deflector, with nonuniform field applied to electrooptic crystal, P (11) 377*b*.
device, crystals for, assessment and control of imperfections in, (9) 318*f*.
device, solid state, using Gd_2O_3 as host material, P (5) 185*b*.
disk, with pumping means in direct optical combination with disk end faces, P (5) 174*b*, *c*.
and electron beam welders, characteristics and potentials, (11) 379*f*.
emission, from deuterium oxide vapor, (8) 295*d*.
emission, and time behavior of exciton formation in Cd(SeS) platelets, (9) 311*f*.
emission lines and materials, comments, (2) 75*d*.
evaporation, for formation of crystalline films, (5) 181*e*.
fluid flow sensor, insensitive to rotation, P (9) 312*d*.
GaAs junction, Gaussian beams from, (4) 137*c*.
glass compositions for, P (10) 339*b*.
glass material, P (5) 174*h*.
He-Ne, spatial coherence, experimental investigation, (5) 181*d*.
to induce diffusion, in making semiconductors, P (5) 183*h*.
-induced "blow-off" phenomena, (6) 234*e*.
ion, with metal tube shrink-fitted onto ceramic discharge tube, P (7) 256*f*.
$Pb_{1-x}Sn_xTe$ diode, long-wavelength infrared, (4) 142*j*.
liquid cell, P (9) 307*g*.
luminescent glasses as materials for, (2) 50*b*.
material, fluorapatite, crystal growth, (4) 130*d*.
hot-pressed polycrystalline, P (10) 339*g*.
inorganic, with ionic structure, (2) 63*b*.
Nd-glass, polarization of light emitted by, (8) 296*j*.
Nd:glass, use to produce second harmonic generation in $LiNbO_3$ crystals, (7) 268*j*.
Nd:YAG, picosecond pulses from, (4) 147*d*.
pulsed, passive mode locking, (10) 344*j*.
thermal effects and transverse mode control in, (1) 17*e*.
optical windows for, P (5) 176*b*.
pn junction injection, using refractive index gradient to confine laser beam, P (10) 345*f*.
pulses, giant, cause surface layer fracture of brittle materials, (10) 361*i*.
high power, shift of mercury line by, (11) 387*e*.
ps, self-focusing in gas breakdown produced by, (9) 311*h*.
radiation, effect on properties of dielectric multilayer laser mirrors, (8) 281*e*.
rods, dynamic optical path distortions in, (1) 27*c*.
ruby, giant pulsing, (4) 110*h*.
krypton-xenon flash tube for pumping, P (7) 256*g*.
output, effect of ultraviolet pumping, (1) 28*d*.
Q-switching by pheophytin *a* and its derivatives, (2) 82*j*.
self-Q-switching in, (4) 111*h*.
undamped regular spiking, in misaligned cavity, (4) 111*g*.
semiconductor junction, with electronically displaceable and deflectable beam, P (7) 258*d*.
semiconductor junction, frequency modulated, P (4) 113*f*.
semiconductor plasma, P (4) 116*g*.
shock wave optically pumped, P (9) 314*b*.
structure, fiber, P (10) 344*j*.
structure with laser element inserted concentrically within cylindrical light pump tube, P (9) 312*d*.
surface damage of glasses, mechanism for, (9) 306*c*.
systems, employing solid laser components and light-absorbing claddings, P (8) 282*a*.
systems, employing solid laser material, P (9) 312*d*.
tunable Raman, P (6) 224*b*.
twin semiconductor, P (6) 224*c*.

Lattice constants. See *Crystals.*

Lattice defects. See *Crystals.*

Lattice energy. See *Energy.*

Lattices. See *Crystals.*

Laws, Kablukov, analytical study, (8) 288*h*.

Leaching, differential, phenomenology and geochemistry, (1) 34*j*.
of glazes and enamels, (1) 15*i*.
of lead glass by EDTA, kinetics, (8) 276*d*.

Lead. See also *Glass; Glazes.*
bromide, molten, specific conductivity, (10) 360*h*.
diborate, $PbO{\cdot}B_2O_3$, modifications, (6) 234*b*.
ferrite, microstructure and magnetic properties, (8) 281*a*.
fluoride, vaporization thermodynamics, and PbF, dissociation energies, (10) 356*j*.
halide crystals, ESR and optical studies of low-temperature radiation effects in, (8) 291*i*.
header, braze grounded, P (7) 255*f*.
iodide, semiconducting, properties, (4) 151*i*.
ions, diffusion in purified NaCl crystals, (4) 131*e*.
$PbSb_2O_6$, structure, $LnCrTeO_6$, new series of compounds based on, (10) 356*a*.
$PbBaNb_2O_6$, crystals, devices using, P (10) 344*f*.
$Pb_xM_2O_{7-z}$ (M=Ru,Ir,Re), preparation and properties of oxygen deficient pyrochlores, (10) 358*h*.
$Pb_2(NiW)O_6$, synthesized under high pressures, phase transitions in, (2) 81*d*.
$PbSnO_3$, distorted perovskite, high-pressure synthesis, (7) 266*d*.
$Pb_{1-x}Sn_xTe$, single crystals, growth from nonstoichiometric melts, (9) 322*i*.
$Pb_{1-x}Sn_xTe$, $Pb_{1-x}Sn_xSe$, and other IV-VI alloys, metallurgical and electronic properties, (2) 80*c*.
PbTe-Sn-Te, single crystals, growth and characterization, (2) 77*d*.
$Pb_2Ti_2O_5F_2$, new pyrochlore, (4) 148*j*.
$Pb(Zn_{1/3}Nb_{2/3})O_3$, perovskite-type, high-pressure synthesis, (11) 385*f*.
$Pb(Zr,Ti)O_3$ ferroelectric and antiferroelectric compounds, electrocaloric effects in, (1) 16*c*.
molybdate, dielectric constants, (4) 131*a*.
molybdate, energy-level scheme for Np^{4+} in, (10) 353*b*.
monoxide, pure red, P (9) 317*g*.
monoxide, tetragonal, hydrothermal growth of single crystals and phase width, (8) 293*c*.
ore, low grade, beneficiation, (6) 228*j*.
oxides, equilibrium pressures of oxygen over, (1) 29*j*.
single crystals, electrical and optical properties, (1) 28*b*.
thermodynamic properties by emf measurements, (10) 362*j*.
selenide, single crystals, diffusion of Ni in at 700°C, (4) 126*f*.
silicates, syntheses, larsenite, barysilite, and related phases, (4) 158*j*.
substitution in flux-grown single crystal rare earth orthoferrites, (8) 294*d*.
sulfantimonides, from Madoc, Ontario: III, syntheses, paragenesis, origin, (1) 33*a*.
sulfide, single crystals, growth in silica gels at ambient temperatures, (7) 266*j*.
sulfide, sulfation, (1) 38*g*.
systems. See *Systems.*
telluride, epitaxial deposits, growth and morphology on rock salt, (9) 322*i*.
p-type, diffusion of Ni and Cl_2 into, at 700°C, (10) 352*g*.
preparation and examination by transmission electron microscopy, (4) 150*a*.
thermoelectric base composition, and devices using, P (11) 379*c*.
telluride-iron, pseudobinary section, constitution, (1) 26*a*.
titanate glass-ceramics, (6) 209*j*.
zirconate, heats of transition, role of impurities in, (1) 36*g*.
zirconate, pressure dependence of orthorhombic-cubic transformation in, (2) 82*e*.
zirconate-lead titanate piezoelectric ceramics, with iron oxide additions, (7) 255*c*.
zirconate-titanate, ceramics, production lapping, (1) 17*h*.
ferroelectric ceramics, internal friction in, (2) 63*c*.
piezoelectric ceramics, adulterated, high-field losses, (1) 17*d*.

Lehrs. See *Furnaces; Glassmaking apparatus and equipment.*

Lenses. See *Glass, optical.*

Lepidocrocite, -boehmite, solid solution formation of, and occurrence in soil, (7) 268*f*.

Leucite, minerals, thermal expansion, (10) 362*d*.

Ligands, field, of NiO, effect of interionic distance on, (4) 132*j*.

Light, arresters, gas-filled, for telecommunication installations, P (9) 307*e*.
effect on glass pH electrodes, (7) 260*b*.
effect on Si stain films growth, (9) 320*b*.
-emitting unit, self-luminous, P (2) 66*c*.
polarized, experiments in ceramic glazes, (6) 219*j*.
source, coherent, using pentavalent Mn-activated calcium chlorophosphate crystal, P (6) 221*b*.
transmission, of struck glass, cause of dependence on intensity of illumination, (9) 305*d*.

Lime. See also *Calcium, oxide; Glass.*
aging characteristics, (8) 287*a*.
ASTM standards, B (9) 333*h*.
carbonatation shrinkage, mechanism, (9) 303*j*.
effect on quantity of water-soluble V_2O_5 in melts of CaO-V_2O_5-Na_2O system, (8) 291*g*.
fines, briqueted, P (4) 92*i*.
free, determination in cement clinker, (2) 70*h*.
influence on hydration of tricalcium silicate, (9) 323*a*.

Lime *(continued)*
milky, initial reaction with carbon dioxide gas, effects on crystal of $CaCO_3$, (4) 91*c*.
products, new, for quicker slag formation in oxygen-blowing steel processes, (6) 216*e*.
quick-, reactivity, for formation of CaC_2 in molten phase, (4) 123*h*.
reactivity, influence of reheating, (6) 215*i*.
reactivity, and related oxides: XVI, sintering; XVII, sulfating with Mg and Al sulfates; XVIII, production of plasters, (8) 287*b*.
-silica porous body, hard-porosity, P (2) 59*g*.
uncombined, rapid routine determination by automatic absorptimetric method, (11) 380*g*.
Limestone, calcination, in fluidized bed, (4) 123*g*.
$CaCO_3$ and $MgCO_3$ in, estimation, (4) 119*f*.
coral, from Tokunoshima and Okierabushima, (4) 123*h*.
disintegrating, by electromagnetic-thermal means, requirements of apparatus for, (6) 224*g*.
and dolomite, minor constituents of, determination by quantitative emission spectroscopy using high-frequency plasma jet, (9) 315*b*.
and dolomites, selected, reactivity with SO_2, (1) 20*h*.
dolomitic, determination by DTA, (1) 22*c*.
fluorescent dye penetrant technique for displaying obscure structures in, (1) 21*j*.
high calcium, deposit in Rattler Gulch area, Granite County, Montana, (2) 73*e*.
Mg in, rapid volumetric determination, (6) 227*f*.
Ordovician Lexington, in central Kentucky, interrelation of mineralogy and texture within, (1) 23*g*.
siliceous, analysis by atomic absorption spectrophotometry and hydrofluoric acid decomposition technique, (8) 284*i*.
sulfur oxide capacity, (10) 336*b*.
weathering, in glaciogenic material in Lohja region, SW. Finland, (9) 325*i*.
Linings. See *Refractories.*
Liquids. See also *Fluids.*
capillary, effect on adhesion force between spherical solid particles, (1) 27*e*.
-gas equipment in porcelain factory, (6) 219*h*.
ionic, vibrational spectra and structures: II, pure alkali metal nitrates, (5) 203*c*.
molecular reorientation in, (9) 325*b*.
physical properties, B (6) 241*i*.
Liquidus, metastable, and effect on crystallization of glass, (6) 210*b*.
Lithia. See *Lithium, oxide.*
Lithium, aluminate, crude, removal of halide ions from, P (9) 317*f*.
aluminate, removing polyvalent metal impurities from, P (9) 317*e*.
aluminum hydride, crystal structure, (4) 130*h*.
borohydride, P (11) 382*d*.
borohydride, nuclear magnetic relaxation studies of internal rotations and phase transitions in, (11) 386*j*.
bromide, iodide, and fluoride, films, vacuum-deposited, dielectric, low frequency polarization effects in, (1) 17*e*.
ferrite, for magnetic cores, P (4) 115*d*.
ferrite, solid state reactions in, (6) 220*f*.
fluoride, -BeF_2 solutions, molten, oxide chemistry and thermodynamics, (11) 386*b*.
-BeF_2-ZrF_4, molten, simultaneous voltammetric generation of U(III) and spectrophotometric observation of U(III)-U(IV) system in, (4) 154*j*.
colored, photoelastic study of dislocation pileup in, (1) 34*j*.
crystalline, doped, thermoluminescent radiation dosimetric material, P (4) 117*c*.
Debye-Scherrer powder photographs of, using ^{57}Fe K X-rays, (5) 193*a*.
early fading of thermoluminescence induced by radiation in, (4) 132*c*.
electron and neutron irradiated, defect clusters in, (8) 290*h*.
-Fe_2O_3, preparation attempts, (8) 288*g*.
interaction with boric anhydride, (4) 140*b*.
ionic conductivity and diffusivity in, (8) 293*j*.
polycrystalline, creep, (9) 319*a*.
rapid solid solution hardening in, (1) 35*h*.
single crystal, recovery of strain amplitude independent dislocation damping in, (1) 35*j*.
spectral emission from, during thermoluminescence, (8) 298*e*.
spectral emission due to lattice vibrations in, (8) 298*e*.
fluoroborate, heats of formation, (9) 322*d*.
gallium oxide, optical properties, (1) 37*d*.
hexafluoroaluminate, solid, heat of formation and transition temperatures, (9) 322*c*.
hydride, low-temperature thermal expansion, (10) 356*b*.
iodate, large nonlinear optical coefficient and phase matched second harmonic generation in, (9) 310*i*.
ion centers, triple, EPR detection of, in Li-diffused Mn-doped GaP single crystals, (10) 353*f*.
Li_3Sb powder, NMR study, (6) 235*j*.
Li_2CO_3-Na_2CO_3, electrochemical studies in, (4) 134*g*.
$LiCuVO_4$, crystallographic structure, (2) 75*i*.
LiF-BeF_2 solutions, molten, oxide chemistry and thermodynamics, (11) 386*b*.
LiF-BeF_2-ZrF_4, molten, simultaneous voltammetric generation of U(III) and spectrophotometric observation of U(III)-U(IV) system in, (4) 154*j*.

Lithium *(continued)*
Li_2O-SiO_2 mixtures, thermodynamics of reactions in, (4) 161*j*.
Li_2TiO_3, structure, refinement, (10) 359*g*.
LiV_2O_4 spinel, hydrothermal crystal growth and electrical conductivity, (4) 139*d*.
$Li_xV_{2-x}O_3$, electric and magnetic properties, (10) 352*a*.
metagallate, Czochralski growth, (6) 231*b*.
metagallate, hydrothermal solubility in NaOH solutions, (4) 139*b*.
metaniobate, crystal growth from melt containing MgO, P (4) 113*i*.
metaniobate, single crystals, stoichiometry, (9) 330*i*.
niobate, crystals, EPR of lanthanide ions and Cr^{3+} in, (2) 76*c*.
crystals, growth, (1) 16*f*; P (8) 282*i*.
crystals, growth ridges, etched hillocks, and structure, (8) 292*e*.
crystals, second-harmonic phasematching temperature in, dependence on melt composition, (1) 26*j*.
crystals, single domain, hydrothermal synthesis by transport reactions, (10) 355*g*.
crystal, works to pack in 1000 holograms, (5) 181*g*.
Curie temperature, birefringence, and phasematching temperature variations in, as function of melt stoichiometry, (1) 26*e*.
ferroelectric, Curie point determination, (2) 62*d*.
high-efficiency optical parametric oscillation and power limiting in, (8) 292*i*.
with large bandwidth and solid acceptance angle, infrared up-conversion in, (9) 323*i*.
mechanical twinning and crack nucleation in, (9) 324*b*.
microwave frequency acoustic surface wave propagation losses in, (9) 311*a*.
piezo- and thermooptic behavior, (1) 34*f*.
relative signs of optical nonlinear coefficients d_{31} and d_{33} in, (8) 297*h*.
second harmonic generation in, by picosecond pulses, (7) 268*j*.
single crystals, optical phenomenon in, (2) 81*e*.
single crystals, piezoelectric and optical properties, (1) 34*d*.
and tantalate, ferroelectric, NMR study, (5) 197*f*.
and tantalate, ferroelectric, optical spectra of Cr^{3+} impurity ions in, (11) 386*a*.
and tantalate, relation between linear and quadratic electrooptic coefficients in, based on direct measurement of spontaneous polarization, (2) 82*a*.
paramagnetic center, structure, in ZnO and BeO crystals, (9) 330*c*.
peroxide, P (8) 288*b*.
phosphate, binary, surface tensions and molar volumes, (4) 158*g*.
plumbates(IV) and stannates(IV), (10) 356*j*.
silicate, novel compositions, P (11) 382*g*.
silicate melts, kinetics of oxygen evolution at Pt anode in, (7) 267*i*.
and Na M_A centers in, (4) 155*d*.
solution, in hexagonal potassium tungsten bronze, (11) 387*c*.
systems. See *Systems.*
tantalate, crystal, oriented, and devices using, P (11) 378*b*.
tantalate, light extinction in light modulation, (8) 294*f*.
trihydrogen selenite, proton magnetic resonance study, (4) 151*d*.
Lubricants, silicone, for glass molding machine molds, (6) 211*c*.
Lubrication, of refractory solids, at high temperature, (1) 32*b*.
Luminescence, analysis, of inorganic substances, B (5) 203*j*.
behavior, of Bi in rare-earth oxides, (4) 110*d*.
blue, in calcium chlorovanadates, (2) 75*a*.
of calcium orthophosphates activated by divalent Eu, (10) 356*c*.
cathodo-, of Eu^{3+} in alkali and alkaline earths with yttrates and gadolinates as hosts, (4) 136*a*.
rare earth, in $InBO_3$ and related orthoborates, (4) 152*e*.
of terbium activated indium orthoborate, (2) 75*b*.
in ZnSe single crystals, scanning electron microscope studies, (5) 199*e*.
crystal structure influence on, (8) 293*a*.
efficiency, of SiC doped with B and N, (4) 110*d*.
electro-, cell matrix material of improved stability, P (7) 256*f*.
from cooled homogeneous GaS crystal, P (8) 282*f*.
dc, in thin films of ZnS, transient phenomena in, (8) 300*i*.
device, P (4) 116*a*.
device, solid state, P (8) 283*g*.
display devices, P (11) 377*e*.
efficient green, in N-doped GaP *pn* junctions, (9) 320*f*.
of GaSb, (9) 321*f*.
of lead-containing ZnS films, (4) 134*i*.
light sources, P (11) 377*f*.
material and device, P (11) 376*d*.
properties, of ZnSe-type phosphors, (5) 194*c*.
of rare-earth and transition metal molecules in II-VI compounds via impact excitation, (9) 321*g*.

Luminescence, electro- *(continued)*
of Ta_2O_5 and TiO_2 diodes, (2) 76*b*.
in thin Nb_2O_5 diodes, (8) 281*c*.
visible, from *pn* junctions in $Cd_{1-x}Mg_xTe$, (9) 332*j*.
of ZnS:Mn evaporated films, effects of double insulating layers, (4) 110*d*.
ZnTe:O device, P (4) 117*d*.
of Eu, divalent, in BaO-MgO-P_2O_5 system, (10) 356*d*.
Eu^{2+}, of subsolidus phases bounded by $BaMgSi_2O_6$, $SrMgSi_2O_6$, and $Ca_3MgSi_2O_8$, (10) 353*g*.
of Eu^{3+} activated thorium, alkali metal vanadates, (10) 356*d*.
of β-Ga_2O_3, Dy^{3+}-activated, (4) 143*c*.
galvano-, of tin, (8) 281*h*.
of hardened glass panels, (1) 6*f*.
image device, and combinations of with optical filters, P (10) 345*d*.
of inorganic nitrite salts, (5) 196*b*.
in MgO, (6) 234*c*.
Mn-activated, in MgO-Al_2O_3-Ga_2O_3 system, (4) 143*c*.
in natural zircon, origin, (4) 147*j*.
of Nd^{3+} in $CaWO_4$, shape and internal structure of band, (4) 154*g*.
of phosphate-vanadates of Y, Gd, Lu, and La, (4) 156*h*.
of phosphors based on host lattices ABO_4 (A = Se, In; B = P, V, Nb), (11) 385*g*.
photo-, in BP, (2) 81*h*.
photo-, in ZnSe(Cu,In), effects of ion pair concentration and firing temperature, (1) 28*h*.
polychromatic devices, P (11) 378*c*.
properties, of $CaMoO_4$/$LnVO_4$ systems, (1) 32*c*.
radiophoto-, centers, in silver-activated phosphate glass, (1) 5*b*.
of rare earth-oxygen-sulfur compounds, selected Eu^{2+}-activated, (10) 359*g*.
substance, Tb or Tb and Gd activated mixed alkaline earth alkali metal borate, P (5) 185*f*.
and thermally stimulated currents in rutile, (6) 239*g*.
thermo-, application in glass study, (6) 208*e*.
of clay minerals, (4) 162*h*.
early fading induced by radiation in LiF, (4) 132*e*.
of irradiated silicate glasses, (8) 277*a*.
of semiconducting diamonds, (2) 84*i*.
of sintered alumina, (10) 363*a*.
spectral emission from LiF during, (8) 298*e*.
study of X-irradiated polycrystalline CaO, SrO, and BaO, (9) 332*a*.
of ZrO_2, (11) 388*e*.
2,2′2″-terpyridine, quenching of, for determination of Fe at parts-per-billion levels, (8) 284*i*.
of uranyl in glasses, influence of chemical bond, (2) 49*a*.
X-ray-stimulated, for detection of rare earth impurities in ionic materials, (1) 21*b*.
Luminescent materials, and apparatus for generating coherent radiation, P (8) 282*c*.
crystalline, ceramic, P (11) 371*d*.
and laser apparatus using, P (9) 312*g*.
preparing, P (7) 257*a*.
strontium yttrate, and alkaline earth yttrate, rare earth activated, P (9) 314*d*.
of zinc magnesium germanate activated with Mn, P (11) 377*c*.
Luminophors. See *Phosphors.*
Lutetium, oxychalcogenide phosphors, rare earth activated, P (4) 116*c*.
phosphate-vanadate, structure and luminescence, (4) 156*h*.

Machinery and equipment. See also *Materials handling* and specific types.
for brickmaking, (10) 340*d*.
for conditioning and dispensing particulated material, P (7) 259*d*.
for detecting filter cake buildup, P (6) 225*b*.
hopper, with vibratory means for uniform rate of material delivery, P (7) 259*a*.
installations, and methods for reduction of emissions from commercial installations and for determination of their effectiveness, (10) 363*j*.
magnetic handling and purification, applied to enamel manufacturing process, (1) 4*f*.
for mining refractory clay in Westerwald, Germany, (10) 348*j*.
for setting structural clay products, (6) 214*d*.
sorting apparatus for spherical bodies, P (7) 253*a*.
Magnesia. See *Magnesium, oxide.*
Magnesiowustite, dilute, oxidation-reduction equilibria, study, (5) 200*b*.
Magnesite. See also *Refractories.*
Ca and Mg in, determination by complexometric method employing coprecipitation of Ca and Sr sulfate, (6) 225*f*.
containing ZnO, calcination, (4) 154*c*.
deposits, formation in system Mg^{2+}-Fe^{3+}-CO_3^{2-}-Cl^--H_2O, (10) 353*h*.
Indian, calcined up to 2000°, petrography and microstructure, (2) 73*h*.
distribution and characteristics, (2) 55*b*.
petrography and X-ray analysis, (2) 73*j*.
preparation and properties of magnesite and chrome-magnesite bricks from, (5) 190*g*.
sintered, X-ray analysis, (2) 73*i*.
Mg in, rapid volumetric determination, (6) 227*f*.

Magnesite *(continued)*
talc, suitability for insulating firebrick and other brick, (1) 13*g*.
Magnesium, aluminate, cubic, optical absorption of tetrahedral $Fe^{2+}(3d^6)$ in, (4) 147*h*.
aluminate, multiple slip processes in, at high temperature, (2) 80*g*.
order-disorder in, (10) 358*e*.
sintering kinetics, (10) 355*h*.
spinel crystals, stoichiometric, growth by flux evaporation, (10) 354*b*.
spinel powders, coprecipitates yielding, (10) 340*j*.
spinel single crystals, large stoichiometric, growth and characterization, (10) 354*i*.
-aluminum hydroxides, mixed: I, preparation and characterization of compounds formed in dialyzed systems; II, structure and structural chemistry of synthetic hydroxy-carbonates and related minerals and compounds, (9) 324*j*, 325*b*.
and calcium values, separating from Ca and Mg carbonates, P (4) 125*b*.
carbonates, estimation in limestones, dolomite, and other calcareous materials, (4) 119*f*.
chloride, dehydration roasting and solvent, P (1) 23*h*.
chloride, interaction with gallium chloride, (4) 140*e*.
chlorides and sulfates, formation and reactivity, (10) 353*j*.
compounds, recovery from $MgCO_3$ and $CaCO_3$ bearing materials, P (1) 24*c*.
content of natural peralkaline silicic glasses and petrogenetic significance, (10) 348*i*.
determination, in presence of Ca by fluorometry, using 8-hydroxyquinoline-5-sulfonic acid, (5) 187*e*.
ferrite, nucleation and growth in MgO containing 0.9% Fe^{3+}, (6) 235*j*.
fluoride, hot-pressed, improving visible and infrared transmission of, P (2) 53*e*.
fluoride, thermal conductivity between 25° and 900°C, (6) 239*a*.
in glasses, determination by atomic absorption, (2) 48*e*.
hydroxide, P (9) 317*e*.
dehydration, and sintering behavior of compressed body, (1) 26*h*.
and oxide, highly dispersed fine-pore structures, effect of $MgSO_4$ on strength of, (6) 232*f*.
precipitated, effect of grinding on, (2) 73*c*.
production from aqueous solutions containing Mg and B values, P (5) 191*e*.
thermal splitting of H_2 from, (6) 239*f*.
and iron, distribution in coexisting biotite, garnet, and cordierite, (7) 265*g*.
and iron, mixed hydroxides and oxides, surface area and pore structure, (1) 38*g*.
in limestone, dolomite, and magnesite, rapid volumetric determination, (6) 227*f*.
in magnesite, determination by complexometric method employing coprecipitation of Ca and Sr sulfate, (6) 225*f*.
$MgAl_2O_4$:Cr, visible and ultraviolet emission and absorption spectra, (5) 208*e*.
$MgFe_2O_4$, formation by solid-state reaction of MgO and Fe_2O_3, kinetics, (4) 142*e*.
$MgFe_2O_4$ and $Mg(Cr,Al)O_4$, X-ray diffraction study of disorder in, (5) 203*h*.
$Mg_{3-3x/2}Mn_xAs_2$ phase, magnetochemical studies, (5) 181*g*.
Mg_2PtO_4, synthesis and crystal structure, (10) 362*a*.
Mg_2SiO_4 crystal structure, high-pressure modifications, and crystallochemical and geophysical implications, (10) 354*h*.
$MgSiP_2$, new member of II.IV.V_2 family of semiconducting compounds, (10) 357*f*.
microdetermination in mixture, (9) 315*j*.
nitride, formation and reactivity, (10) 353*i*.
nitride, rate of sublimation from effusion cells and from free surfaces in vacuo and in argon and nitrogen gases, (5) 199*i*.
orthosilicate, ionic and electronic conductivity in, (4) 141*e*.
oxide. See also *Refractories*.
adsorbed nitro-compounds and electron donor properties, (5) 191*j*.
adsorbed water on, proton magnetic resonance studies, (1) 35*a*.
adsorption of CO_2 and water on, infrared study, (8) 293*c*.
barium diffusion in, (1) 27*j*.
bicrystals, transgranular fracture studies, (5) 202*i*.
(*c*), reaction with AlCl(*g*), and heat of formation of $MgAl_2O_4$(*c*), (4) 152*d*.
caustic calcined, P (6) 230*a*.
Cr^{3+}, stressed crystal field, (10) 351*h*.
for coating refractory ware, P (9) 309*g*.
compatibility with TiO, (8) 289*a*.
color centers, Faraday rotation studies in, (8) 292*g*.
computed ground state properties in molecular orbital approximation, (8) 289*d*.
crystals, cube-oriented, deformation under pressure, (8) 290*i*.
crystals, neutron-irradiated, zero-phonon lines and phonon coupling in, (2) 84*i*.
crystals, origin of water-induced toughening in, (4) 148*a*.
dead-burned, from Ontario magnesite concentrate, (8) 278*j*.
deformed, dislocation configurations in, (2) 75*f*.
Magnesium, oxide *(continued)*
density and lattice parameters, effect of low temperature neutron irradiation and 20°–400°C annealing on, (4) 133*a*.
electric fusion crystallization, P (4) 106*d*.
electro-, with improved electric insulating power, P (9) 317*f*.
EPR spectra of radicals formed when NO_2 is adsorbed on, (5) 194*e*.
fracture surfaces, interaction between crack front and cleavage steps on, (4) 140*j*.
hardening by diffusion of iron, (4) 138*e*.
heavily irradiated, optical absorption studies of color centers in, (8) 295*g*.
high purity, agglomeration and sintering, (11) 372*h*.
high purity, and CaO, recovery from magnesite and calcite ores, P (4) 125*h*.
high-temperature creep, effect of minor additives, (11) 373*e*.
highly pure, sintering with additives, (8) 297*d*.
:Fe^{2+}, pressure shift of absorption bands in, and dynamic Jahn-Teller effect, (10) 359*a*.
:Fe^{2+}, temperature dependence of ultrasonic paramagnetic resonance in, (4) 159*d*.
irradiated, negative ion vacancies in, (9) 325*b*.
irradiated nonfissile, release of gas from, (1) 13*b*.
irradiated, phonon-assisted optical absorption in, (2) 81*f*.
irradiated, surface centers and fast irreversible oxygen adsorption on, (4) 128*d*.
low fired, obtained from crystalline $MgCO_3$, kinetics of isothermal sintering of, (5) 196*f*.
low-temperature thermal expansion, (10) 356*b*.
luminescence in, (6) 234*e*.
in Mg oxychloride cements, effect of calcination temperature on properties of, (8) 274*a*.
Mn^{2+} hyperfine coupling in, covalency and temperature dependence of, (2) 75*e*.
microscopic effects of electric breakdown in, (9) 324*f*.
near-infrared fluorescence and absorption spectra of Co^{2+} and Ni^{2+} in, (2) 80*h*.
neutron-induced damage in, (8) 295*c*.
optical investigation of Cr^{3+} ion diffusion in, (4) 147*i*.
particles, properties, effects of calcining conditions, (8) 291*i*.
polycrystalline, fine structure, behavior during sintering, (7) 263*f*.
powder, high-pressure densification, (11) 373*e*.
primary step growth in, observation by direct transmission electron microscopy, (1) 33*f*.
properties, effect of boric oxide, (6) 214*j*.
radiation-induced expansion and increase in refractive index, evidence for *F* center, (4) 152*b*.
reaction with SiO_2, atomic absorption spectroscopy to study kinetics of, (2) 71*a*.
Rebinder effects in, (4) 136*j*.
relaxation of Mn^{2+} and Fe^{2+} ions in, (4) 153*i*.
single crystals, heat treatment and deformation, (2) 78*a*.
single crystals, iron oxide diffusion into, (1) 27*j*.
single crystal, irradiation damage and hardening in, after low neutron doses $<10^{18}$ *nvt* (>1 MeV), (5) 196*a*.
single crystals, "mirror" absorption and fluorescence in, (1) 32*i*.
sintered, effect of fast neutron irradiation in, (4) 132*e*.
sintering: I, calcination of Mg carbonate and magnesite containing ZnO, (4) 154*c*.
sintering, effect of Cr_2O_3 vaporization, (4) 132*a*.
sintering, effects of crystal habits of $Mg(OH)_2$ and additions of Fe_2O_3 and SiO_2, (1) 28*g*.
slip casting with ethanol, (4) 105*i*.
solid solutions, optical reflectance spectra of Cr^{3+} in, (11) 370*b*.
spin Hamiltonian of $^{51}V^{2+}$ in, as derived from electron nuclear double resonance, (9) 329*g*.
spin-orbit coupling and stress spectra of trigonal color centers in, (4) 155*h*.
spin-orbit splitting of γ-excitation in, (2) 83*g*.
surface, paramagnetic defects associated with hydrogen adsorbed on, (5) 198*e*.
surface-diffusion studies, (6) 238*f*.
temperature dependence of *F* band in, (1) 39*d*.
thermal decay of *V'* center in, (9) 331*g*.
uncombined, in portland cement, quantitative determination by X-ray diffractometry, (9) 304*b*.
:V^{2+}, vibronic transitions in, (1) 40*c*.
polarographic determination, (9) 315*b*.
pyroxenes at high temperatures, inversion in clinoenstatite, (10) 356*e*.
reaction with N_2 in temperature range 400°–650°, (1) 33*d*.
silicate, polymorphism, (1) 34*i*.
in silicate and carbonate rocks, determination by Titan Yellow spectrophotometric method, (1) 21*c*.
stannide, far-infrared reflectivity, temperature dependence of, (2) 84*b*.
Magnesium *(continued)*
studies, of RuO_2 and its hydrate, (5) 196*c*.
sulfate, effect on strength of highly dispersed fine-pore structures of $Mg(OH)_2$ and MgO, (6) 232*f*.
sulfate, formation in basic linings of copper smelting furnaces, (10) 341*j*.
systems. See *Systems*.
tellurate, and indium antimonate, crystal lattices, spectrophotometric determination of coordination ratios in, (9) 329*f*.
uranate, heat capacity, (5) 194*g*.
values, recovery from dolomite, P (2) 74*d*.
Magnetic materials. See also *Ferrites; Ferromagnetic materials; Ferromagnetism*.
P (1) 18*j*; 24*a*.
compounds, properties in connection with crystal chemistry, B (7) 272*g*.
cores, high temperature, P (4) 113*a*.
cores, lithium ferrite, P (4) 115*d*.
forming or molding, apparatus and process, P (9) 312*a*.
powder, method and apparatus for compacting, P (1) 18*a*.
with rectangular hysteresis loops, P (7) 256*h*.
Magnetic properties. See also *Anisotropy; Resonance*.
anisotropy and magnetostriction of $Y_3Mn_{0.1}Fe_{4.9}O_{12}$ at 300°K, (10) 356*f*.
behavior of $FeSiO_3$-$MgSiO_3$ orthopyroxene system from NGR in ^{57}Fe, (9) 324*h*.
behavior, of magnetite in thermal cycles across magnetocrystalline, isotropic point, effect of compression on, (7) 265*i*.
birefringence, in EuO, (10) 355*h*.
of $BiMnO_3$ and $BiCrO_3$, (8) 294*j*.
of borides with Cr_3C_2 structure, (1) 17*g*.
of BF and BH molecules, (2) 80*c*.
circular dichroism in ruby, (8) 294*j*.
of compounds, of fluorine with Fe and monovalent cations, relation to structural classification, (6) 237*j*.
of formula, $MFeF_3$ (M=Na,K,Rb,Cs,NH_4,Tl), (10) 361*i*.
of rare earths and actinides, (10) 360*d*.
of copper-containing sulfides and selenides with spinel structure, (4) 143*e*.
domains, in Mn ferrite, X-ray observation, (2) 84*h*.
domains, in RbFeF$_3$, (7) 267*j*.
of η phase in Mn–Ga system, (2) 79*h*.
of Eu-Al intermetallics, (4) 110*f*.
of ferrimagnetic garnet thin films, (10) 344*b*.
field action, duration, effect on formation of coagulation structures in aqueous suspensions of clay minerals, (4) 132*c*.
field, effect on density distribution of injected plasma in semiconductor rods, (5) 180*f*.
effect on Faraday effect in ferrite garnets, (2) 76*c*.
high, effects on isothermal dissolution and growth rates of $Fe(NH_4)_2{\cdot}6H_2O$ and $KAl(SO_4)_2{\cdot}12H_2O$ seed crystals, (4) 133*g*.
interactions, in olivine structure, (5) 196*b*.
interactions, in system $(La,Gd)_2CoMnO_6$, (2) 80*b*; (10) 356*g*.
of $FeBO_3$, (2) 83*g*.
of lanthanide ferrite garnets near Curie point, (2) 80*c*.
of lanthanum hydrides, (4) 143*g*.
of lead ferrite, (8) 281*a*.
of $Li_xV_{2-x}O_2$, (10) 352*a*.
of magnetite, (4) 143*h*.
of magnetite crystals, remanent and transitory effects of elastic deformation on, (4) 153*j*.
magnetoabsorption, in single-crystal semiconducting ferromagnetic spinels, (2) 80*h*.
magnetochemical studies of phase $Mg_{3-3x/2}Mn_xAs_2$, (5) 181*g*.
magnetochemical studies of phases of ternary lithium-manganese-arsenic system, (5) 181*h*.
and magneto-optic, of EuO films doped with trivalent rare-earth oxide, (7) 255*d*.
magneto-optical, of transparent RbFeF$_3$, (4) 143*c*.
magnostatic modes, in canted antiferromagnetic $MnCO_3$, (1) 32*f*.
magnetostriction of single crystals of Tb and Ho ferrite garnets at low temperatures, (2) 80*h*.
magnostriction constants, of rare earth ion garnets, (1) 32*g*.
of Mn-Zn ferrite, effect of sintering conditions, (2) 62*f*.
effect of synthesis parameters on, (6) 220*e*.
relation with grain structure, (4) 110*h*.
of perovskite $Sr_3(FeMo)O_9$ and related compounds, (2) 79*j*.
of praseodymium hydrides, (2) 79*h*.
of radiation-induced molecule-ion in Al_2O_3, (10) 362*c*.
of rare-earth orthoferrites, Bi-substituted single crystal, (10) 359*h*.
of RbNiF$_3$, effect of pressure, (7) 265*j*.
susceptibility, of $BaMoO_4$(IV) and $SrMoO_4$(IV) in range 2°-300°K, (11) 385*h*.
calculations, dimensional analysis, (10) 343*i*.
of metallic V_2O_3 single crystals, (4) 143*i*.
and Moessbauer studies on iron(III) tellurate, (9) 325*d*.
of Pr^{4+} in CeO_2, (5) 196*d*.
of rare-earth compounds, (8) 289*i*.
of semiconductor ZnO, (4) 143*j*.
of SrTiO$_3$, insulating and semiconducting, (1) 32*f*.
of thorium carbides, nitrides, and carbonitrides, (4) 143*a*.

Magnetic properties, susceptibility *(continued)*
of trivalent Eu in YGaG, (6) 234*h*.
of uranium(IV) glasses, (4) 96*b*.
of uranium trifluoride in range 2°–300°K, (4) 143*b*.
thermo-, in $Cu_{1-x}Mg_xFe_2O_4$, (1) 34*e*.
thermo-, of Mn-bearing sintered wustite, (4) 145*g*.
of uranium oxide fluorides, and structural relation to U oxides, (10) 356*i*.
of Zn-Ni manganites, (9) 321*b*.
Magnetic resistance, in semiconductors, (4) 109*f*.
Magnetism, equation of state for CrO_2 and Ni near their Curie point, (4) 143*g*.
magnetic arrangements, ordered, (4) 147*e*.
magnetic head, with substantially bubble-free gap, P (10) 345*i*.
magnetic recording heads, P (4) 115*g*.
piezo-, of CoF_2 and α-Fe_2O_3 from EPR pressure experiments, (4) 149*j*.
in structural determination of inorganic compounds, (1) 22*h*.
structure, of $Ca_2Fe_2O_5$, (2) 80*e*.
structure, of $FeSb_2O_4$, (1) 32*f*.
studies, on Al_2O_3-Cr_2O_3 catalysts, (6) 234*f*.
of bonding in $CsCuCl_3$, (10) 362*f*.
on $CuCr_2O_4$ catalysts, (6) 234*h*.
of isomorphous series $Na(Sc,Fe)TiO_4$, (11) 385*g*.
of rare-earth double oxides of type $LaTO_3$ where T = Ho, Y, Er, Tm, Yb, Lu, (6) 231*b*.
of series $Mn_xFe_{1-x}HoO_3$, (10) 351*f*.
on three modifications of $FeMoO_4$, (11) 385*h*.
of Ti-O system, (8) 294*a*.
Magnetite, acoustic loss, low-temperature in, electronic mechanism for, (1) 27*d*.
cobalt impurity, cation vacancies, and magnetic relaxation of, (1) 26*e*.
crystals, remanent and transitory effects of elastic deformation of, (4) 153*j*.
magnetic behavior in thermal cycles across magnetocrystalline isotropic point, effect of compression on, (7) 265*i*.
magnetic properties, (4) 143*h*.
multidomain, stable remanence and memory, (5) 200*g*.
oxidation, to γ-Fe_2O_3, mechanism, (8) 295*a*.
oxidation, low-temperature, mechanism, (9) 324*d*.
reduction, factors which influence rate minimum phenomenon during, (4) 157*h*.
Magnetization, and critical fields of superconducting $SrTiO_3$, (2) 80*g*.
process in spinel lattice, (2) 80*g*.
remanent, of hematite single crystals, (1) 36*c*.
ripple in thin ferroelectric films, (2) 63*e*.
Magnetoelectric, effect in YIG, (9) 310*j*.
Magnetoresistance. See *Resistivity, electrical.*
Magnets, alloys, directionally solidified permanent, with aligned ferromagnetic whiskers, P (6) 221*g*.
ferrite, P (4) 115*b*.
permanent, P (9) 313*a*.
permanent, of rare earth metals containing Co or mixtures of Co, Fe, and Mn, production, P (5) 184*d*.
powders, permanent, apparatus for compacting into pressings, P (4) 112*a*.
superconducting, P (6) 222*j*.
Majolica. See *Art and artware.*
Management, technical information, how to use, B (2) 85*f*.
Manganese, aluminum, Mn_2NiC, and MnZns, neutron diffraction studies, (1) 12*f*.
arsenates, crystal chemistry: III, crystal structure of eveite, $Mn_5(OH)(AsO_4)_3$, (10) 351*g*.
μ-atomic Lyman and Balmer series in, (4) 145*e*.
and calicum, double oxide, orthorhombic $CaMn_2O_4$ structural study, (1) 38*d*.
carbonate, canted antiferromagnetic, magnetostatic modes in, (1) 32*f*.
dioxide, P (7) 263*a*; P (9) 317*e*.
preparation by electrolytic method, P (7) 262*h*.
ramsdellite, P (5) 191*g*.
effect on properties of tricalcium silicate, (10) 336*a*.
ferrite, crystal growth, (7) 254*g*.
electrical properties, influence of Mn^{3+} ion clustering, (10) 355*c*.
prepared from aqueous solution, neutron diffraction of, (2) 80*h*.
prepared from aqueous solution, NMR determination of metal ion distribution in, (5) 197*d*.
single crystals, ^{55}Mn NMR of Mn^{3+} ions located at B-sites in, (1) 32*i*.
spin echo spectra, at liquid helium temperature, (8) 298*e*.
X-ray observation of magnetic domains in, (2) 84*h*.
fluoride, Co-doped, magnon sidebands and local order in, (1) 32*i*.
fluoride, Er-doped, resonant impurity mode and Moessbauer effect for, (4) 153*c*.
hydroxide, dehydroxylation, creep during, (10) 351*f*.
inserting into semiconductors serving to produce electronic semiconductor structural components, P (9) 312*i*.
Mn(II) carbonate thermolysis, thermogravimetric analysis and simultaneous infrared absorption spectroscopy, (5) 202*f*.
Mn(II) ions, for observation of selective exchange of cation sites in zeolites, (9) 329*d*.

Manganese *(continued)*
Mn^{2+}, cathodoluminescence spectra and coordination in β-$LiAlSiO_4$, (10) 350*c*.
chemistry during formation of fluorapatite, EPR study, (4) 135*b*.
EPR in tremolite, apophyllite, and scheelite, (1) 28*i*.
ESR absorption spectrum, in single-crystal calcite, superhyperfine interaction due to ^{13}C in, (8) 299*c*.
ESR in reduced $BaTiO_3$ single crystals, (1) 29*c*.
ESR in α-$Sr_3P_2O_7$, (9) 321*i*.
hyperfine coupling in MgO, covalence and temperature dependence, (2) 75*e*.
ions, relaxation in MgO, (4) 153*i*.
$MnCr_2O_4$, ferrimagnetic spiral, far-infrared absorption in, (2) 77*c*.
$MnCr_2O_4$, magnetic resonance, frequency of, (2) 77*i*.
$Mn_xFe_{1-x}HoO_3$, crystallographic and magnetic study, (10) 351*f*.
$Mn_xFe_{3-x}O_{4+\gamma}$, Richter-type magnetic relaxations in, (2) 75*d*.
$Mn_{1+x}Fe_{2-x}O_4$ single crystals, induced anisotropy at low temperatures, (2) 78*f*.
Mn_4Si_7 thermoelectric element, process and product, P (2) 66*h*.
nodules, thorium, radium, and potassium in, (4) 124*d*.
oxide, antiferromagnetic, spin-polarized energy-band structure of, (9) 329*g*.
crystal, hyperfine interaction in, (2) 78*e*.
crystal, total energy and 2*p* O^{2-} ion wave function, (5) 202*h*.
Li-doped, Hall effect in, (4) 138*c*.
α-MnS, and α-MnSe, paramagnetic states, NMR in, (4) 147*a*.
α-MnS, and NiO, covalency parameters in, (4) 130*a*.
optical absorption spectra of crystal-field transitions in, (11) 386*a*.
Philippine, studies, (1) 23*d*.
producing from langbeinite, P (7) 263*b*.
reduction from basic slags by Si dissolved in liquid Fe, kinetics, (2) 79*j*.
single-crystal, elastic moduli of, (9) 320*h*.
single-crystal, local antiferromagnetic order in, above Néel temperature, (1) 31*i*.
single crystals, magnetic anisotropy, (2) 79*f*.
and sulfide, total intensities of crystal field transitions in, related to antiferromagnetism, (9) 332*b*.
thermodynamic properties by emf measurements, (10) 362*j*.
vacuum-deposited, as electrolytic layer of capacitor, P (6) 222*e*.
in various valence states, Mn$K\beta_5$ spectra and MnK absorption edges, (9) 325*h*.
selenide, and MnSe-MnS solid solutions, slip behavior and hardness indentations in, (9) 329*i*.
sulfate, formation from MnO_2, Mn_2O_3, and Mn_3O_4 and decomposition to Mn_2O_3 or Mn_3O_4, kinetics, (4) 142*e*.
sulfide, specific heat, through Néel temperature, (2) 83*f*.
systems. See *Systems.*
titanate, heat capacity from 30° to 300°K, (8) 292*i*.
trifluoride, sublimation pressure, mass spectrometric studies at high temperatures, (7) 267*a*.
tungstate, magnetic structure at 4.2°K, (4) 143*h*.
uranate, heat capacity, (5) 194*g*.
zinc ferrites, magnetic properties, effect of synthesis parameters on, (6) 220*e*.
Marble, metamorphic, of French Massif Central, geochemical study, (1) 30*g*.
synthetic, P (4) 109*a*.
Marketing, annual sales forecast, (6) 240*c*.
cement, (7) 244*h*.
exports, (4) 164*i*.
for profit, (6) 240*d*.
short-cut formula may predict product's chance of success, (6) 240*d*.
Masers. See also *Lasers.*
devices, utilizing fluorescent garnet compositions, P (2) 64*g*.
nontranslating variable output coupler for, P (9) 313*j*.
optical materials, Eu doped Y_2O_3, P (10) 344*g*.
ruby, laser-pumped, operation at 77°K, (5) 181*j*.
wide bandwidth millimeter, P (7) 258*d*.
Masonry, articles, water repellent, P (10) 336*d*.
brick, engineered, (4) 101*h*.
refractory, protection, method and device, P (8) 279*f*.
Materials. See also *Ceramic materials.*
construction, for breweries, (2) 45*h*.
dry, electrostatic separation, P (11) 382*a*.
high-temperature, and technology, B (1) 41*h*.
of high vacuum technology: Vol. 2, silicates, Vol. 3, auxiliary materials, B (2) 85*f*.
industrial, dangerous properties, B (4) 166*j*.
for medical use, (1) 40*e*.
modern, advances in development and applications: Vol. 6, B (4) 166*h*.
new, survey, (4) 164*j*.
porous. See *Porous materials.*
raw, beneficiation by optical-electronic devices, (5) 189*i*.
cement, apparatus for drying and preheating, P (5) 170*c*.

Materials, raw *(continued)*
ceramic, and green and fired bodies, phase composition, quantitative determination, (8) 280*c*.
ceramic—minerals and occurrence, B (8) 302*c*.
ceramic, preparation by strong-field magnetic and electrostatic separators, (7) 262*h*.
deposits, for clay, glass, and ceramic industries, geological field methods for exploration and opening of, (5) 190*c*.
effect on thermal behavior of brick and ceramic products, (8) 278*g*.
Kansas, for manufacture of reflective glass beads, (2) 50*b*.
for lightweight aggregate, in Appalachian Region, Alabama, and Georgia, (8) 278*h*.
preparation for technical ceramics, (5) 190*i*.
structure and influence of organic matter on use of, in area of mineralogy and metallurgy, B (11) 389*b*.
from Tokaj-Hegyalja, for pottery bodies, (2) 60*c*.
sciences, fundamental phenomena: Vol. 4, fracture of metals, polymers, and glasses, B (1) 41*d*.
transparent, spectral emission, radiation induced changes in, (4) 152*b*.
used in silicate industry, spectrographic qualitative analysis, (8) 285*b*.
Materials handling. See also *Conveyors; Feeding apparatus; Machinery and equipment.*
air conveyor and unloader for granular materials and unloading process for, P (10) 346*j*.
apparatus for delivering molten materials, P (5) 189*f*.
apparatus for filling valve bags with pulverous material, P (8) 284*e*.
automated, at Logan Clay improves customer service, (4) 123*e*.
bulk, outlet structure for unloading either by gravity or pneumatically, P (2) 74*h*.
conveying, of granular, crushed, or powdered materials, P (7) 263*d*.
conveyor, methods at Spode, (5) 179*i*.
palletizing, and drying, fully automatic, in structural clay industry, (7) 250*a*.
pallets, shrunk film packing for, (4) 118*b*.
preheated, device for periodic delivery, P (7) 261*h*.
preheating particulate feed material for rotary kiln, P (7) 261*e*.
tile setter loading device, P (4) 109*c*.
transport, in cement industry, (2) 44*f*.
wrapping and palletizing of cylindrical products, P (7) 250*b*.
Measurement, capacitative, of moisture, (7) 259*j*.
cinematic, of firing shrinkage, (5) 187*b*.
electronic (initial current), of cathode temperature, (6) 226*f*.
equipment, for creep of concrete under multiaxial compressive stress, (1) 21*j*.
of four-pole parameters of transistors, (4) 110*f*.
of industrial water usage, methods and installation, (10) 363*j*.
Knudsen and Langmuir, of sublimation pressure of cadmium(II) fluoride, (1) 31*g*.
of moisture content of ceramic pastes, (2) 70*d*.
of movement in masses of rock, P (4) 124*e*.
nondestructive, of material strength, P (1) 22*g*.
of pore-size distribution in refractories, comparison of methods, (2) 69*a*.
soil density, reliability of using nuclear methods for different soils, (5) 188*a*.
surface area, of variable length sample of finely divided solids, P (4) 122*b*.
of volume resistivity of insulating ceramics at high temperature, problems, (2) 70*f*.
Measurement devices, bolometer, immersed, P (5) 175*f*.
for creep of concrete at high temperatures, (5) 170*d*.
for load of controlled stroke press, (6) 225*b*.
for melting point of silicates in inert atmospheres, (2) 68*j*.
for particle length, P (7) 261*a*.
for pore size and pore volume, P (7) 260*g*.
volumetric unit, for powdered materials, P (1) 20*g*.
Mechanical properties, of alumina ceramics, commercial, (2) 56*c*.
of Al-Al_2O_3 alloys, blended and ball-milled, discussion, (1) 12*a*.
of basic refractories, significance at elevated temperatures, (6) 216*e*.
of carbon fiber material, (6) 216*c*.
of ceramic bodies drying, (5) 179*i*.
of ceramics, B (11) 389*h*.
of clay soils, effect of ion sheath, (5) 190*c*.
of Cu-Cu_2O eutectic alloys, (9) 324*j*.
of extruded commercial S.A.P. materials, anisotropy in, (10) 349*j*.
of glass, effect of surface dealkalization, (10) 337*h*.
of glass foam, (2) 48*d*.
of inorganic polymers, (4) 131*h*.
of refractories at working temperatures, (5) 178*f*.
of Roman pozzolanas, (5) 170*f*.
of silicon nitride, reaction-sintered, (2) 56*b*.
of sintered-glass cermets, (1) 4*g*.
of NaCl, polycrystalline, (2) 80*j*.
of spinel single crystals, (2) 75*j*.
of surface oxide films, influence on oxidation mechanisms, (10) 355*a*.

Mechanical properties *(continued)*
of surface oxide layers, influence of electrical field on, (2) 45*i*.
of ultra-refractory carbides, at high temperatures, (1) 12*b*.
vibration displacement of concrete mixtures, scientific basis, (8) 274*e*.
Meetings. See *Conferences*.
Melilite, crystallization of phases and decomposition, during cooling of molten blast-furnace slag, (6) 231*i*.
Melting, aids, effect on activation energy of silicate glasses, (2) 48*c*.
back-, effect on dislocation density in GaSb single crystals, (5) 194*a*.
behaviors, of lanthanide oxides measured with solar furnace, (4) 136*g*.
electric arc, electric arc stabilization using carbon electrodes in, P (11) 374*h*.
electron beam, of Zr-O and Zr-Si alloys, kinetics and evaporation mechanism during, (9) 309*c*.
glass batch, submerged combustion principle, (5) 173*d*.
granite with excess water to 30 kbars pressure, (4) 144*b*.
at high pressure, (4) 144*c*.
history, effect on glass properties, (7) 247*f*.
material which melts with difficulty, gas discharge method and arrangements, P (7) 261*e*.
metals, by resistance heating, apparatus for, P (7) 252*d*.
morphology of solid/liquid interface during, (4) 145*c*.
parameters, of alkali halides, (4) 144*d*.
point, of lanthanide compounds, interrelations with heat of formation, and lattice parameters, (10) 355*i*.
measurements with solar furnace, (5) 187*h*.
of neptunium mononitride, (4) 144*d*.
of oxides of rare-earth elements, (8) 290*c*.
of silicates in inert atmospheres, apparatus for measuring, (2) 68*j*.
studies of system UP-US, (8) 295*b*.
of UO_2, determination, (1) 27*e*.
pre-, and cellular prefreezing phenomena in alkali halides, (7) 264*e*.
of refractory metallic oxide, (1) 20*h*.
zone, crucible-free, of semiconductor materials, particularly Si, (10) 345*f*.
crucible-free floating, of crystalline rods, apparatus for, P (10) 344*b*.
increasing cross section of crystalline rod during, P (4) 114*g*.
liquid encapsulation refining, (LEZOR), (4) 110*c*.
for preparation of high purity metals, materials, and organic compounds, (4) 118*i*.
for production of high-purity chromium oxide, (7) 262*a*.
Melts, cryolite-alumina, chronopotentiometric measurements on graphite anodes in, (6) 214*i*.
cryolite-alumina, repeatability of anode effect in, (2) 82*c*.
glass, influence of size on refining, (2) 49*f*.
ionic, properties and applications, (1) 31*a*.
nonstoichiometric, for preparation of GaSb single crystals, (1) 30*e*.
polygermanatosilicate, evidence of monomeric structures in, (7) 265*f*.
silica, surface, (1) 38*j*.
spinellite, viscosity, up to 2500°, (8) 290*f*.
Membranes, ionic, porous glass as, (5) 173*i*.
isocapillary, of bentonite, (6) 234*a*.
phenomena: III, electric resistance; IV, potential and permeability; V, bulk flow through, (8) 298*e*.
potentials of fused SiO_2 in molten salts, (5) 197*a*.
Pyrex, potential, in nitrate binary melts, (5) 199*g*.
Memory, behavior, of MNS capacitor, (4) 144*f*.
ceramic, with piezoelectric drive member, P (1) 18*a*.
element, magnetic, comprising Ni-Fe and Zr and composition comprising Ni-Fe-Zr, P (5) 183*h*.
ground-state spin, in $\bar{E}(^2E)$ level of ruby in optical pumping via bands, (2) 77*c*.
indium sheet film, process control, P (1) 19*c*.
laminated ferrite, P (1) 18*b*.
laminated-ferrite, MOS field-effect transistor drivers for, (8) 281*b*.
Memory cores. See *Data storage*.
Memory devices. See *Data storage*.
Mercury, aqueous solution interface, specific adsorption of chloride ions at, (9) 329*d*.
mercuric sulfide and HgS_2Cl_2 single crystals, growth by vapor phase method, (5) 194*e*.
sulfide, CdS, and ZnS, epitaxial growth on CdS and ZnS, (7) 265*e*.
sulfide, interaction with telluric anhydride, (7) 267*f*.
Metalizing. See *Coatings*.
Metalloceramic compositions. See *Cermets*.
Metallurgy, powder, hot-pressing, isostatic, as densification method in, (4) 117*g*.
properties, of $Pb_{1-x}Sn_xTe$, $Pb_{1-x}Sn_xSe$, and other IV-VI alloys, (2) 80*c*.
Metals. See also *Enameling metals; Rare earths.*
-ceramics. See *Cermets*.
/Al_2O_3 interfaces, strength, (9) 330*j*.
backwave deposited, fixing onto beveling root, P (8) 275*f*.
chlorinating with CCl_4 and CO_2, P (11) 382*c*.
Metals *(continued)*
determination at micromolar level, piezoelectric transducer for, (8) 285*i*.
electrically conductive, bonding to insulators, P (4) 112*d*.
ferrous, billets, method and apparatus for descaling, P (4) 94*c*.
fibers, textiles, and shapes, P (2) 59*d*.
fluorophosphate, P (1) 24*d*.
foils, thick polycrystalline, filtered electron diffraction measurements from, (4) 136*h*.
forming, using liquid dies, P (4) 94*b*.
fracture, B (1) 41*d*.
hard, pressing, (11) 379*d*.
high-melting-point, electron optics method and apparatus for investigating high-temperature metallographic phenomena of, (6) 227*j*.
interface reactions with ceramics: IV, wetting of sapphire by liquid copper-oxygen alloys, (1) 31*g*.
melting by resistance heating, apparatus for, P (7) 252*d*.
metallic articles, low melting, reinforced with modified chrysotile, P (6) 217*c*.
metallic elements, differential kinetic analysis, (8) 295*a*.
molten, halogenating, P (1) 24*a*.
nucleation, amorphous, in, (4) 126*d*.
oxides. See *Oxides*.
oxidizing, oxygen gradients in: IV, kinetics of hafnium oxidation at high temperatures, (1) 38*b*.
physics, modern problems: Vol. II, chemical bonds in crystals and ferromagnetism, B (4) 166*h*.
pickling, process, P (8) 275*h*.
Pt-group, microgram amounts, in iron and stony meteorites, determination, (1) 21*d*.
prefinished, T-bend test for, (2) 71*b*.
rare-earth, silicides, (6) 216*a*.
refractory. See *Refractories*.
reoxidation, in aluminum electrolysis, (1) 32*e*.
semi-, and semiconductors, powdered, propagation and dimensional resonances of helicon-like waves in, (11) 386*h*.
sheet, enameling and forming, P (4) 94*b*.
strip, flexible, method of applying with good adhesion to metal frame coated with insulating, preferably ceramic, material, P (5) 183*j*.
substances, containing impurities, apparatus for producing striationless bodies of, P (4) 112*c*.
surfaces, organic film detection on, (1) 4*f*.
surfaces, treating, P (5) 172*a*.
system. See *Systems*.
transition, alkali metal oxofluorometallates, (10) 349*h*.
alkali metal thio- and seleno-compounds of: IV, of platinum, (5) 192*c*.
borides and carbides, wetting phenomena, interpretation by electron theory, (7) 267*h*.
carbohydrides formation, (1) 30*a*.
content of Al_2SiO_5 polymorphs, (9) 332*c*.
electropositive, mass-spectrometric evidence for molecules UC and CeC and predicted stability of diatomic carbides of, (11) 385*j*.
formation of metalloid-stabilized Zr-rich phases, (4) 141*f*.
high melting point intercalation compounds, structure and properties, (11) 374*h*.
molecules, in II-VI compounds, electroluminescence via impact excitation, (9) 321*g*.
molybdates and tungstates, crystal structure: IV, paramagnetic $CuMoO_4$, (4) 130*c*; V, paramagnetic alpha Nd_2 $(MoO_4)_3$, (10) 351*e*.
oxides, calculation of heats of formation of point defects in, (9) 318*j*.
oxides of, use for improvement of acid and alkali resistant enamels for chemical processing industry, (10) 336*j*.
sulfides, thermal expansion, (1) 39*d*.
and transition-metal carbides, low-temperature electrical properties, (8) 294*h*.
-tritides-yttrium tritide, stability, (4) 156*a*.
Metaphosphates. See *Phosphates*.
Mica. See also *Refractories; Vermiculite.*
A and B layers, and crystal structure of sheet silicates, (9) 317*h*.
coexisting with garnet and cordierite, distribution of Mg and Fe in, (7) 265*g*.
dislocations in, topographic X-ray observations, (1) 39*g*.
electrical properties, effect of stains and inclusions, (5) 190*d*.
fluorine, (10) 348*h*.
from granitic rocks of central Sierra Nevada batholith, California, (11) 383*c*.
hydro-, aqueous dispersion, mechanism of formation of coagulation structures in, under action of ultrasound, (7) 267*b*.
of metamorphic skarns in Western Moravia, (9) 316*g*.
phlogopite, hydration states in relation to interlayer cations, (7) 266*h*.
preheated, interstratification structure formed from, by acid treatments, (8) 293*h*.
separation from granite, (8) 287*j*.
sheets, normal and retarded van der Waals surface forces between, direct measurement, (4) 157*j*.
synthetic, with substitutions of NH_4 for K, Ga for Al, and Ge for Si, (1) 26*a*.
trioctahedral brittle, (4) 162*h*.
sinnwaldite, Moessbauer absorption in, (9) 325*j*.
Micrographs, scanning electron, of structural ceramic materials, (6) 227*i*.
Microhardness. See *Hardness*.
Microporosity. See *Porosity*.
Microradiography. See *Radiography*.
Microscopes, cover glass, and method, P (5) 176*a*.
electron, high magnification calibration, new technique, (9) 315*a*.
for investigation of fine structure of faces of pyrite crystals, (4) 141*d*.
investigations on glass with, (11) 370*b*.
observations of Al_2O_3 whiskers/Ni composites, (8) 279*f*.
photographs, of rough ceramic surfaces, replication procedures for, (4) 121*d*.
radiation source for reducing specimen contamination in, P (4) 122*d*.
high temperature, for investigation of system MgO-CaO-Cr_2O_3-SiO_2, (4) 141*j*.
lunar and planetary petrographic, (8) 285*f*.
polarizing, large rotating stage for, (1) 21*d*.
preparation of slide for viewing, P (9) 315*i*.
sample, three-dimensional, reconstruction using holographic techniques, (4) 121*c*.
scanning electron, for fracture studies in glass-reinforced gypsum plaster, (4) 91*g*.
operation and use, (1) 22*a*.
for studies of refractories textures, (4) 105*b*.
for study of fabric of fine-grained sediments, (8) 285*g*.
for study of synthetic spinel crystals, (8) 298*j*.
for three-dimensional and stereo observations in glass and ceramic systems, (4) 97*i*.
wide field lens for viewing rock textures, (9) 315*g*.
Microscopy, automated quantitative, niche for, (1) 21*f*.
Berg-Barrett X-ray diffraction, for quantitative investigation of domain structures; I, determination of small tilt angles in various lattice planes of crystals, (10) 359*d*.
electron, of crystallization of glasses in system Li_2O–Al_2O_3–SiO_2, (1) 6*i*.
comparison with Coulter Counter for analysis of particle size distributions of "monodisperse" particles from 0.8 to 3.5 μm in diameter, (4) 119*c*.
determination of temperature of specimens in, (2) 69*b*.
direct transmission, for observation of primary step growth in MgO, (1) 33*f*.
hot stage transmission, for oxide growth in Al-Al_2O_3 SAP-type alloy, (1) 34*e*.
in situ, anomalous sintering behavior revealed by, (1) 25*h*.
of montmorillonite dispersed at various pH, (11) 384*i*.
of mutual adsorption of clay minerals and colloidal hydrous Al_2O_3, (1) 33*e*.
observation of CrO_2, sintered, (1) 28*d*.
observation of oxides formed on thin film of copper at elevated temperatures, (8) 291*e*.
observation of solid state reactions MgO-FeO and MgO-Al_2O_3, (1) 28*h*.
for oxidation and deformation studies of UN, (1) 33*j*.
of pyrolytic graphite, (8) 291*f*.
replicas for study of porcelain structure, (10) 347*f*.
of sodium montmorillonite, (10) 352*j*.
stroboscopic, (2) 71*a*.
study of chemical stability of glasses in system Li_2O·SiO_2-Li_2O·Al_2O_3·$4SiO_2$, (2) 48*g*.
study of transition from amorphous to crystalline condition of electron bombarded CdS films, (7) 265*b*.
study of US single crystals: I, slip behavior; II, precipitation phenomena, (1) 28*f*.
transmission, of CoO single crystals, (4) 121*j*.
electron mirror, for inspecting semiconductor devices, P (2) 65*e*.
electron-mirror, study of $BaTiO_3$ surface layers, (4) 134*j*.
examination, sectioning of friable deposits for, (10) 347*e*.
field-electron, studies of Ce layers on refractory metals: work function change, (4) 136*g*.
field ion, study of formation of oxide particles on tungsten, (10) 353*c*.
fluorescence, with quartz iodine lamp, (4) 119*h*.
high-temperature, for study of feldspars, (8) 298*i*.
optical, study of fracture in WC-Co alloys, (1) 32*e*.
quantitative transmission, of ceramics, thickness error in, (8) 277*b*.
rotating plagioscopic method in, (2) 70*i*.
scanning electron, comments on interpretation of Kikuchi-like reflection patterns, (2) 75*d*.
scanning electron, studies of cathodoluminescence in ZnSe single crystals, (5) 199*e*.
simplified by new developments, (1) 21*f*.
slides of fine-grained unconsolidated sediments and ooze, method for making, (6) 226*d*.
technique for mounting, sectioning, and polishing particles smaller than 30 μm in diameter, (8) 285*h*.
thin film sections, (8) 285*a*.
thin sections, polished (8) 285*j*.
transmission electron, examination of PbTe, (4) 150*a*.
of irradiated UO_2 fuel pellets, (8) 300*j*.

Microscopy, transmission electron *(continued)*
of neutron-irradiated α-Al_2O_3 single crystals, (4) 162*f*.
of thin (<2000 Å) thermally formed ZrO_2 films, (9) 332*d*.
use of slow electrons in, (2) 71*d*.
ultra-, of defects in alkali halides, (8) 300*b*.
ultra thin-section, improves studies, (5) 188*b*.
Microstructure. See *Structure*.
Microwaves, device, negative resistance, P (5) 184*b*.
moisture measurement, (5) 187*d*.
phonon attenuation, in $MgAl_2O_4$, (4) 144*d*.
properties, of hot-pressed fine-grained ferrites, (2) 62*e*.
second harmonic and sum and difference frequency generation in semiconductors at low temperatures, (5) 181*e*.
Migration, cationic, in SiO_2 films on silicon, (4) 128*d*.
of inert gases in ionic crystals, (9) 324*g*.
Na, in SiN films, (10) 361*g*.
Milling. See also *Crushing; Grinding*.
ball, industry, procedures, (8) 275*b*.
of commercial Al_2O_3, accelerating, and casting properties of Al_2O_3 slip, (6) 224*f*.
dry, of quartz, changes as result of, (5) 192*j*.
dry, wear of porcelain balls during, (10) 346*i*.
dry ball-, for manufacturing ceramics, P (8) 284*f*.
fluid energy, P (11) 379*f*.
process and apparatus, P (4) 125*h*.
Mills. See also *Crushing apparatus; Grinding apparatus*.
ball, P (10) 346*g*.
drum, P (10) 346*h*.
electromagnetic, P (1) 20*d*.
lining bricks, means for indicating wear, P (6) 225*b*.
or rod, infeed and sealing means for, P (1) 23*j*.
cylindrical, for grinding cement, P (7) 245*d*.
drum, improving grinding process in, (6) 224*h*.
fluid energy, P (5) 186*f*.
for foundry sand, P (5) 178*a*.
grind to micron size without moving parts, (4) 117*h*.
grinding, liner for, P (11) 375*j*.
pug, apparatus, P (9) 314*h*.
pug, use of closed circuit TV in, (4) 117*f*.
sand, and process, P (10) 347*b*.
self-discharging finishing, P (5) 186*f*.
vibratory, and operation, P (6) 225*e*.
washing and grinding, P (11) 382*h*.
Mineral fibers. See *Mineral wool*.
Mineral wool. See also *Fibers, glass*.
furnaces, (4) 122*j*.
production, method and apparatus, P (7) 252*c*.
rock and slag, for thermal insulation, specifications, (1) 13*f*.
Mineralizers. See also *Fluxes*.
influence on formation of white portland cement clinker, (4) 92*a*.
for solid-state reactions, selection, (4) 154*c*.
Mineralogy, applied, for engineers, technologists, and students, B (8) 301*c*.
of asbestos from northwest Pakistan, (6) 229*d*.
association proceedings in India in 1964, B (4) 167*g*.
clay, B (10) 364*i*.
clay, of pluvial lake sediments, southern high plains, Texas, (1) 23*c*.
of clays of chain-like structure, (10) 357*g*.
constitution, of colloidal "hydrous ferric oxides," (1) 32*f*.
determinative, physical methods in, B (6) 241*e*.
elements of, B (1) 41*a*.
interrelation with texture within Ordovician Lexington limestone section in Central Kentucky, (1) 23*g*.
of metamorphosed iron formation of Gagnon Region, Quebec, Canada, (7) 262*f*.
petrogenesis in Caledonian basic igneous province of NE. Scotland, strontium isotope studies, (7) 262*b*.
quantitative, of sedimentary rocks, comparison of two methods, (1) 20*j*.
of sand size carbonate fraction of marine terrigenous and carbonate sediments, (1) 32*h*.
in Wettersteinkalk, Northern Limestone Alps, Bavaria and Tyrol, (1) 27*g*.
xenolithic ultrabasic dikes, of Cuillins and Strathaird Peninsula, Isle of Skye, Scotland, flow differentiation in, (4) 136*j*.
Minerals. See also *Raw materials; Rocks;* and specific types.
American Upper Ordovician standard: XI, multivariate classification of typical Cincinnatian calcarenites, (11) 383*b*.
analysis of gas inclusions in, progressive heating method, (1) 25*g*.
bone, surface hydroxyl population in, (4) 158*b*.
calcium in, photocolorimetric determination with aid of Arsenazo, (6) 226*j*.
chevkinite and perrierite, study, (4) 157*d*.
clay. See *Clays*.
common, infrared spectral reflectance, (1) 31*c*.
containing rarer elements from Far East district: LXI, yttrofluorite from Japan, (8) 289*f*.
cummingtonite-grunerite series, X-ray crystallographic properties, (4) 164*c*.
elements, common, field tests for, (2) 69*f*.
eutectic, penetration in chrome magnesite and magnesite refractories, (4) 104*i*.
Minerals *(continued)*
Gannett group of western Wyoming and southeastern Idaho, (11) 385*b*.
gmelinite, structure, (7) 269*b*.
grinding efficiencies, increasing, P (5) 191*b*.
indentation microhardness anisotropy in, effects of water desorption on, (8) 285*a*.
industrial, role in economic development of Rajasthan, (4) 123*j*.
kilchoanite, compacted synthetic, properties, (2) 73*c*.
langisite, and rare minerals cobalt pentlandite, siegenite, parkerite, and bravoite from Langis Mine, Cobalt-Gowganda area, Ontario, (9) 316*e*.
layer-lattice, cation-exchange capacity: I, discrepancies between two methods of c.e.c. determination on montmorillonite; II, two types of cation-exchange sites on montmorillonite and their determination, (4) 127*j*; 128*a*.
natural, Moessbauer spectra, (4) 145*e*.
niobian wolframite, from Nauparra pegmatite, Zambezia, Mozambique, (8) 295*e*.
from Norra Karr, Addendum, (8) 295*g*.
and occurrence—ceramic raw materials, B (8) 302*c*.
preparation, in Roumania, research, (4) 123*i*.
proustite and pyrargyrite, optical quality, synthesis, (8) 299*g*.
resources and geology of Washington County, Indiana, (9) 316*j*.
resources, of Saurashtra and Gujarat, chemicals from, (4) 123*g*.
rock-forming, quantitative electron-probe microanalysis, (11) 380*f*.
saline, nitrate determination in, (4) 119*c*.
soil, chemistry, (1) 26*a*.
soil, chemistry: IV, synthetic alkylammonium montmorillonites and hectorites, (4) 128*e*.
spinellite, viscosity of melts up to 2500°, (8) 290*f*.
storehouse in ocean, (9) 317*a*.
sulfosalts, studies: XII, nuffieldite, new species, (1) 38*a*.
thermodynamic properties at 298.15°K (25.0°) and 1 atm (1.013 bars) pressure and at higher temperatures, B (8) 302*h*.
tombarthite, new from Hoegetveit, Evje, South Norway, (8) 300*i*.
yttrialite, synthesis and study, (10) 362*c*.
Mines and mining, of Bavarian clay, quartz, kaolin, feldspar, and pegmatite sand, economic problems, (7) 262*a*.
Mirrors, Belgian industry, (9) 305*b*.
dielectric multilayer laser, properties, effect of laser radiation, (8) 281*e*.
lightweight optical, for astronomical equipment, P (10) 339*h*.
making, possibilities of using vacuum deposition of thin films in, (9) 306*g*.
telescope, of skeleton construction, lightweight and rigid, (7) 248*e*.
tinted, P (10) 340*c*.
Miscibility. See also *Solubility*.
gap, between FeS and $Fe_{1-x}S$, (2) 80*c*.
in molten salt systems, atlas, B (8) 301*j*.
in Th-ThC system from high-temperature X-ray data, (4) 144*h*.
of ternary fluorides, (1) 37*g*.
Missiles. See *Spacecraft*.
Mixers, conical, P (5) 186*e*.
continuous, P (6) 225*a*.
continuous operation gravity fed, and method for accurately proportioning foundry sand ingredients, P (6) 217*i*.
-grinder for foundry sands, P (10) 347*a*.
for premixing granular material additives, P (10) 346*i*.
for pulverulent materials, P (2) 68*b*.
for solids, P (4) 118*b*.
Mixing, bulk solids, and apparatus, P (11) 379*f*.
ceramic and carrier fibers, P (4) 106*g*.
dry material, in cement plant, digital control, (4) 91*g*.
of non-Newtonian fluids, (2) 69*f*.
properties, of sanidine crystalline solutions: III, calculations based on two-phase data, (11) 386*b*.
review, (1) 20*e*; (4) 117*i*.
solids-, techniques, (4) 118*c*.
with vibrations, (5) 186*c*.
Mobility, electron drift, in Li-doped ZnO, (9) 321*i*.
ionic, relation with structure in solid $MAgI_3$ [M = K, Rb, NH_4], (5) 199*b*.
studies, on vacuum-deposited PbTe thin films, (8) 281*b*.
Models, Adam-Gibbs and free-volume, evaluation—polymer-melt viscosity and glass transition, (4) 97*b*.
adsorption, for contact angle and spreading, (5) 191*i*.
band, for transition-metal chalcogenides with layer structures with occupied trigonal-bipyramidal sites, (5) 192*f*.
Born, calculation of point-defect formation energies in alkaline-earth fluorides, (8) 288*i*.
coalescence, for granulation, (4) 117*f*.
for connected porosity in ceramic bodies, (2) 70*f*.
continuous dielectric, for hydration of monatomic ions, (4) 129*f*.
continuum, for fiber-reinforced plastic materials, (1) 26*b*.
crystal growth, for slightly supersaturated solutions, analysis, (5) 192*d*.
Models *(continued)*
crystal structure, of framework tetrahedra, inexpensive, (8) 285*c*.
defect structure, for wustite, (4) 130*h*.
discontinuous, for hydration of monatomic ions, (4) 131*i*.
mathematical, of glass processing tanks, (4) 96*b*.
petrogenetic, for evolution of anorthosite kindred, (8) 296*b*.
rotational isomeric state, of sulfur and selenium chains: III, large rings in liquid sulfur and nature of S_π, (9) 329*b*.
shell, for calculation of surface distortion in alkali halide crystals, (4) 126*i*.
theoretical, of floc structure, (1) 39*h*.
Modulators, cubic crystal light, P (10) 344*c*.
electrooptic light, (1) 29*e*.
infrared, employing single crystal Te or Se, P (4) 113*d*.
optical, P (11) 378*b*.
optical $LiNbO_3$, P (8) 283*g*.
radiation, P (4) 101*a*.
reverse biased semiconductor laser light, made from same material as lase.· light source, P (11) 378*a*.
second harmonic semiconductor, for coherent radiation, P (10) 345*j*.
solid-state crystal optical, P (7) 258*a*.
Modulus of elasticity. See *Elasticity*.
Modulus of rupture. See *Rupture*.
Moessbauer, absorption, in zinnwaldite mica, (9) 325*j*.
effect, for determination of cation distribution in orthopyroxene series, (4) 119*a*.
determination of Tm^{3+} crystalline electric field parameters in Tm-doped soda-silica glasses, (6) 210*i*.
in ^{129}I, for studies of IBr, ICl, and I_2Cl_6 crystal properties, (4) 156*j*.
for ^{57}Fe in ferroelectric $BaTiO_3$:vacancy-impurity associated state, (5) 197*g*.
in iron-alkali-silicate glasses, (9) 306*i*.
for MnF_2, Er-doped, (4) 153*c*.
measurement of trigonal field splitting of Fe^{2+} in $GeFe_2O_4$ by, (4) 143*e*.
of monocalcium ferrite, Fe_2O_3·CaO, (1) 33*b*.
studies on calcium ferrites: I, temperatures above Néel point, (4) 145*d*.
for study of perovskites $Pb(Nb, Fe)_{1/2}O_3$ and $Sr(TaFe)_{1/2}O_3$, (10) 361*b*.
study of spin relaxation in $CaFe_2O_4$, (2) 80*c*.
for study of initial stages of lithia-alumina-silica glasses crystallization, (1) 9*a*.
in system $Co_{1-x}Fe_xS_2$, (11) 386*f*.
hyperfine spectra, of Fe^{2+} in corundum—magnetic- and crystal-field effects, (2) 80*e*.
and magnetic susceptibility studies on iron-, (III) tellurate, (9) 325*d*.
spectra, for determination of cation distribution in cummingtonite-grunerite series, (4) 131*e*.
of magnetically ordered erbium ions in $ErFeO_3$, relaxation phenomena, (2) 82*c*.
of natural minerals, (4) 145*e*.
study, of electron hopping in octahedral sites of Fe_3O_4, (9) 325*j*.
of ferrimagnetic ordering in nickel ferrite and Cr-substituted nickel ferrite, (4) 145*h*.
high-pressure, of ^{57}Fe in silicate and phosphate glasses, (5) 172*g*.
high-pressure, on α-Fe_2O_3, $FeTiO_3$, and FeO, (4) 138*a*.
of Fe^{2+} in paramagnetic fayalite (Fe_2SiO_4), (4) 145*g*.
of NiO bulk materials and ultrafine particles, (10) 357*i*.
on three modifications of $FeMoO_4$, (11) 385*h*.
of ulvospinel, $TiFe_2O_4$, (2) 80*e*.
Moisture. See also *Humidity; Steam; Water*.
content, batch, determination by electrical conductivity method, (6) 226*d*.
of ceramic pastes, measurement, (2) 70*d*.
of irregular stream of bulk material, nuclear gaging system for, P (6) 228*b*.
continuous extraction from suspended matter, apparatus for, P (11) 379*d*.
effect on Al/SiO_2 reaction, (9) 320*i*.
expansion: I, kinetics and mechanisms in literature, (9) 325*a*.
in furnace atmosphere, effects on white porcelain enamel, (8) 274*j*.
and heat transfer in porous systems with particular reference to drying, (6) 228*d*.
measurement, capacitative, (7) 259*j*.
measurement, microwave, (5) 187*d*.
Molding, carbides, (2) 56*c*.
composition, asbestos-phosphoric acid, P (1) 13*g*.
composition, and ceramics, high temperature phosphorus containing, P (9) 309*f*.
foamable granule product, P (11) 371*f*.
glass and ceramic materials, P (5) 175*f*.
injection, as shaping method in ceramics, review, (6) 224*i*.
magnetic substances, apparatus and process, P (9) 312*a*.
moldables and castables, (8) 224*g*.
objects from ceramic raw material, method and arrangement, P (10) 346*j*.
powder, ceramic, preparation in spray dryers, (11) 375*h*.
refractory bodies, shaped, with attached spacer of nonmetallic sheet material, P (2) 59*d*.
sand, P (8) 279*i*.
Molds. See also *Slip casting; Slips*.
casting, P (11) 375*c*.

Molds, casting *(continued)*
anisotropic continuous, P (7) 252*c*.
for cylindrical grinding media, P (1) 20*e*.
graphite continuous, P (11) 374*j*.
centrifugal, coating composition, P (9) 309*a*.
centrifugal forming, P (11) 371*b*.
for clay pipe and fittings, P (10) 340*e*.
colloidal silica compositions containing set indicator for, P (7) 252*h*.
cores for. See *Cores*.
cover, for bending glass sheets, P (5) 176*b*.
dental, or molding material, method and package for producing, P (2) 61*a*.
design, relations between shrinkage and green density for, (9) 314*f*.
foundry, or cores, P (6) 218*c*.
foundry, liquid mixes for, and manufacture, P (5) 178*i*.
glass, P (4) 98*e*.
molding machine, silicone lubricants for, (6) 211*c*.
sectional mounts, P (1) 11*d*.
glass fiber, for industrialized building, (1) 7*e*.
with high temperature strength and corrosion resistance against molten metals, P (1) 14*h*.
improving grain structures and soundness of castings, method and apparatus, P (7) 252*c*.
investment shell, for high integrity precision casting of reactive and refractory metals, P (5) 179*a*.
lens, P (11) 371*h*.
members, with network of passages, P (4) 109*b*.
poroplast as material for, (4) 108*h*.
precision casting, P (1) 14*b*.
precision casting, highly refractory electrofused materials for, (6) 215*d*.
precision metal casting, comprising Al_2O_3 coated SiO_2 and refractory, P (8) 279*i*.
refractory, composition and method, P (6) 218*c*.
refractory, preparation, P (6) 218*g*.
refractory shell, P (6) 217*j*.
sand, P (6) 218*h*.
shell, P (4) 106*b*.
endothermic material for making, P (10) 342*h*.
permanently backed, P (8) 279*j*.
permeable, P (10) 342*j*.
slurry pouring means and, P (1) 375*d*.
vibratory, P (11) 375*d*.

Molecules, adsorbed monocarboxylic, arrangement on α-Al_2O_3 surfaces, (2) 75*a*.
BO, dissociation energy, mass spectrometric determination, (9) 324*i*.
charge distributions and chemical binding: III, isoelectronic series N_2, CO, BF, and C_2, BeO, LiF, (8) 295*i*.
containing carbonyl group, thermodynamic properties and frequency shifts, (7) 270*b*.
donor and acceptor, binary systems, crystal chemistry, (7) 264*c*.
foreign, infrared spectra, in beryl, (4) 140*h*.
inorganic, molecular orbital method for, application to transition metal oxides, (4) 145*i*.
molecular properties, of alkali halides: III, NaCl, (2) 84*e*.
reactive organic, on silica surfaces, (4) 153*d*.
water, adsorbed, thermodynamic properties, (1) 39*e*.
and alcohol, reaction with hydroxyl groups on silica surface, (6) 237*d*.
low-frequency vibrations, in beryl, (6) 234*e*.

Molybdenite, surfaces, identification and properties of point defects and nonbasal dislocations in, (5) 195*i*.

Molybdenum, and alloys, silicidation, influence of allotropy, (9) 304*j*.
bronzes, electronic properties, (8) 298*b*.
dioxide, crystal structure refinement, (4) 153*f*.
dioxide, reaction with liquid sodium, (1) 35*i*.
disilicide, disintegration by oxidation at intermediate temperatures, influence of stress, (1) 31*b*.
disilicide, slip casting, (2) 57*h*.
in enamel frits, amperometric determination, (2) 68*f*.
films and filaments, sticking probabilities of hydrogen on, (9) 330*g*.
high-temperature, kinetics of attack by atomic oxygen, (4) 141*i*.
-iron, -cobalt, and -nickel, eta carbides, (10) 353*g*.
Mo^{5+}, paramagnetic relaxation in TiO_2, temperature dependence of, (4) 159*c*.
Mo^{5+}, in phosphate glass, ESR and optical absorption study, (1) 7*b*.
Mo^{5+}, in bisulfate melt and glass, spectroscopic study, (6) 211*f*.
oxide, crystals, growth and microstructure, (9) 322*g*.
oxide tetrafluoride, crystal structure, (8) 292*g*.
powder, for use in spray coating, P (2) 46*e*.
systems. See *Systems*.
ternary peritectics with tungsten and UC, (4) 159*i*.
trioxide, P (2) 74*b*.
single crystal and thin film, optical and and photoelectric properties, (1) 34*b*.
single crystals, vapor growth, (8) 300*e*.
trivalent, absorption and fluorescence spectra in aluminoborophosphate glasses, (8) 275*i*.

Monazite, opening up methods, (2) 73*g*.

Monticellite, crystalline solutions, (7) 267*e*.

Montmorillonite, adsorption of alkylammonium cations by, (7) 268*f*.
alkylammonium, synthetic, chemistry, (4) 128*e*.

Montmorillonite *(continued)*
aqueous dispersions, effect of Na humus on structure formation and mechanism of development of deformations in, (7) 262*d*.
cation-exchange capacity on, discrepancies between two methods of determinations, and two types of cation-exchange sites on, and their determination, (4) 127*j*, 128*a*.
clay, thermodynamics of heterovalent cation exchange reactions in, (9) 332*e*.
clays, physicochemical interpretation of shearing process in, (5) 198*e*.
copper, sorption of α-amino acids by, (7) 269*e*.
electrical conduction in, (1) 39*e*.
electron microscopy, dispersed at various pH, (11) 384*i*.
ion exchange at high pressures, (10) 356*d*.
-kaolinite dispersions, structural-mechanical properties, controlling, (7) 262*a*.
modified, containing exchangeable ammonium cations, and preparation, P (2) 74*h*.
organo-, hydrophilic-hydrophobic character, (5) 195*h*.
particle size, with various adsorbed cations, optical study, (9) 326*f*.
reactions with aliphatic amines, (9) 328*c*.
surface, interaction with water: III, applicability of BET equation on sorption isotherm of water vapor by montmorillonite, (7) 267*e*.
suspension, self-diffusion of Na in, at equilibrium, (4) 154*e*.
suspensions, tactoid rearrangement and optical density, during Na-Ca exchange reaction, (5) 200*j*.

Mordenite, crystalline, P (7) 263*b*.
hydrogen form, formation and properties: I, preparation of synthetic, dealuminizing process, and ion-exchange properties of zeolite, (7) 266*a*.
shaped bodies, P (8) 288*a*.

Morphology, of alumina crystals, (10) 375*b*.
of calcium sulfoaluminate hydrates, (11) 368*f*.
of GaP crystals grown by VLS mechanism with Ga as liquid-forming agent, (7) 267*e*.
of solubility of quartz, (9) 324*b*.
stability, (10) 357*b*.
of vermiculite clay particles as affected by genesis, (11) 386*f*.
of ZnS: I, influence of precipitating conditions, (4) 148*f*.

Mortars, aluminosilica refractory, tests, (4) 105*f*.
bars, prepared with sample of Danish aggregates, (4) 91*d*.
for building purposes, design and use, (2) 44*b*.
cement, or concrete, of improved strength, production, P (6) 207*a*.
freezing temperature, use of plastograms to select additives for lowering, (4) 92*b*.
hardening, electrical method for measuring strain by molded polyester resin strain gage, (1) 3*c*.
and concrete, dimensionally stabilized, P (8) 274*b*.
graphite bearing high MgO, P (8) 279*b*.

Mosaics, applying to curvate surfaces, means and method, P (4) 109*e*.

Mullite. See also *Refractories*.
bricks, high temperature properties, (4) 104*g*.
fine needle-shaped, formation, effect of crystallization cycles, (6) 215*e*.
formation, from kaolinite-type minerals, effects of impurities: I, effect of exchangeable cations; II, effect of exchangeable anions; III, effect of firing atmosphere, (11) 384*c*.
from sillimanite group minerals, (10) 341*g*.
in system Al-fluoride-SiO_2, kinetics: II, mechanism of formation with anhydrous AlF_3, (5) 196*h*.
spinel-, mixtures, firing, phase transformations in, and charges of cordierite and sapphirine, (6) 238*f*.
synthesis, by sintering process, (2) 58*f*.
volume changes on solidification, (7) 270*f*.

Muscovite. See also *Mica*.
flotation, from Alabama graphitic-mica schist ore, (10) 348*g*.
long-range order of Al-Si in, (4) 142*i*.

Neodymium, chloride, multiphoton process in, observation and saturation of, (2) 81*c*.
chloride and bromide, optical absorption spectra of coupled Nd^{3+} ions in, (4) 147*g*.
germanates, influence on polymorphism of ZrO_2, (7) 267*b*.
and lanthanum oxides, reaction with oxides of elements of second group in periodic system, (8) 297*f*.
monotellurooxide, crystal structure, (11) 383*c*.
Nd^{3+}, luminescence band in $CaWO_4$, shape and internal structure of, (4) 154*g*.
NdF_3, sublimation pressure, and stabilities of gaseous NdF_3 and NdF, (2) 80*i*.
$Nd_2(MoO_4)_3$, paramagnetic alpha-, crystal structure, (10) 351*c*.
systems. See *Systems*.

Neon, solution and diffusion, in tridymite and cristobalite, (5) 200*a*.

Neptunium, monocarbide and mononitride, electronic properties, (10) 353*a*.
mononitride, melting point and decomposition pressure, (4) 144*d*.
Np^{4+}, absorption spectrum, in single-crystal thorium oxide, (11) 383*b*.
Np^{4+}, energy-level scheme for, in $PbMoO_4$, (10) 353*b*.
Np(V) and (VI) oxyfluorides, (5) 197*a*.

Neutrons, activation, fast, for analysis of thin films for Si, O, and Al, (8) 280*k*.
bombardment, effect on reactivity of graphite to oxygen, (11) 384*h*.
damage, in Al_2O_3, single crystal, (1) 33*a*.
damage, in irradiated BeO at high temperatures, (1) 33*i*.
diffraction, application to determination of quality of synthetic quartz crystals, (11) 379*i*.
by GeO_2, SiO_2, and radiation-damaged SiO_2 glasses, (7) 247*i*.
intensities calculated for random network of vitreous silica, (4) 126*d*.
investigation of Fe_3Se_4, (9) 325*c*.
of manganese ferrite prepared from aqueous solution, (2) 80*h*.
on piezoelectric resonators, (9) 325*d*.
diffraction study, of $Ca_3Al_2(O_4D_4)_3$, garnetoid, (5) 197*b*.
of $CaFe_2O_4$, (8) 295*j*.
on ferrite $Mn_xZn_{1-x}Fe_2O_4$, (9) 333*b*.
of ice polymorphs: I, ice IX, (8) 295*c*.
of Jahn-Teller type of tetragonal deformation in spinels $MgGa_{2-x}Mn_xO_4$ and $MgCr_{2-x}Mn_xO_4$, (10) 363*g*.
of magnetic structure of terbium chromite, (10) 357*f*.
on MnAl, Mn_3Ni_2C, and MnZn, (1) 12*f*.
of monocalcium ferrite, $Fe_2O_3{\cdot}CaO$, (1) 33*b*.
of $Sr_2(FeMo)O_6$, (2) 80*i*.
of tetragonal hydrogen bronze H_xWO_3, (4) 164*e*.
of UC_2 at 300°–5°K, (4) 146*a*.
-induced damage in BeO, Al_2O_3, and MgO, (8) 295*c*.
irradiation, growth of ceramic oxides under, (4) 137*e*.
for moisture control in furnace, (1) 3*e*.
molecular spectroscopy with, B (10) 364*j*.
studies, of $Ag_2Sn_2O_7$ stannates, (2) 82*f*.
thermal, dose rate, effect on variation of solid fission product and gas swelling in uranium compounds, (8) 300*g*.

Nickel, arsenide structure, and vanadium chalcogenides, (9) 332*h*.
atomic fluorescence study on, (8) 284*j*.
atoms, self-diffusion coefficient in NiS, (8) 290*e*.
bromide crystals, surface-spike growth on, VLS mode of crystal growth, (4) 157*g*.
chloride, molten mixtures with alkali halides, thermodynamic properties, (10) 362*j*.
and CrO_2 magnetic equation of state near Curie point, (4) 143*g*.
or cobalt ferrite, used in dehydrogenation process, P (6) 229*f*.
diffusion into *p*-type PbTe at 700°C, (10) 352*g*.
diffusion, in single crystals of PbSe at 700°C, (4) 126*f*.
dissociative diffusion in Si, and self-diffusion of Si, (4) 131*j*.
effect in ground coat and direct-on white enamels, (10) 336*g*.
effects on structure of sintered uranium carbide, (4) 133*h*.
ferrite, and Cr-substituted, Moessbauer study of ferrimagnetic ordering in, (4) 145*h*.
Cu and Co in, determination by atomic absorption analysis, (6) 225*g*.
crystals, growth from barium borate by pulling method, (7) 254*j*.
determination of small amounts of divalent Fe in, (6) 225*i*.
effect of tetrahedral site Ni^{2+} ions in, (2) 76*f*.
ferrous microstructure control in, (5) 181*j*.
internal fields in, (4) 140*f*.
high-strain fatigue behavior at room temperature, effect of dispersed hard particles on, (6) 232*b*.
hydroxide, crystals, magnetic heat capacity at low temperatures, particle size dependence of, (4) 148*f*.
iodide, thermal transformations, (7) 270*h*.
-iron double films, domain wall motion in, (4) 132*c*.
iron ferrite crystals, grown using arc image furnace techniques, (4) 146*b*.
malonate, thermal decomposition, (9) 331*i*.
manganite, single crystals, growth, (6) 233*b*.
mechanism of formation of thin oxide layers on, (5) 196*j*.
metallic, in catalysts and ceramic materials, determination by differential thermal analysis, (8) 284*i*.
Ni(II), coordination states, in molten $ZnCl_2$–KCl mixtures, (4) 154*i*.
determination by quenching of fluorescence of Al-1-(2-pyridylazo)-2-naphthol and direct fluorometric determination of Co, (8) 284*j*.
hydroxide, thermal decomposition, (1) 39*a*.
Ni^{2+}, in CaO, electronic absorption spectrum, (8) 291*j*.
ions in spinel, absorption spectrum, (11) 383*b*.
ions, tetrahedral site, effect in nickel ferrite, (2) 76*f*.
light absorption in 2,6-spinels, (7) 267*j*.
in potassium magnesium fluoride, acoustic paramagnetic resonance, (1) 24*h*.
in α-$Zn_3(VO_4)_2$, crystal field studies, (7) 264*e*.
and Ni-Co alloys, substructures in oxide scales on, (4) 157*h*.

Nickel *(continued)*
- $Ni_{1/4}Fe_{2/4}$ oxyhydroxides, reactive hot-pressing, (4) 153*c*.
- orthosilicate, synthesis and study of properties, (4) 158*e*.
- oxalate dihydrate, thermal decomposition, (1) 39*c*.
- oxidation, by CO_2, (4) 148*g*.
- oxide, absorption spectrum, fine structures in, (1) 29*g*.
  - bulk material and ultrafine particles, Moessbauer studies, (10) 357*i*.
  - conductivity measurements on, in highly enriched oxygen atmospheres, (10) 351*c*.
  - covalency parameters in, (4) 130*a*.
  - crystals, fluxed-melt growth, and electrical properties, (7) 254*i*.
  - crystals, growth by solar furnace fusion, (7) 266*g*.
  - crystals, lithiated, P (6) 221*j*.
  - decomposition, (4) 130*g*.
  - effect of interionic distance on ligand field in, (4) 132*j*.
  - electrical conduction at high temperature, (1) 28*j*.
  - high frequency conductivity, (2) 78*e*.
  - high-temperature defect structure and electrical properties, (8) 293*c*.
  - influence of stoichiometry on lattice parameter in, (10) 344*g*.
  - Li-doped, surface and bulk electronic properties, (4) 111*c*.
  - single-crystal, iron diffusion in, (4) 131*d*.
  - single crystals, magnetic anisotropy, (2) 79*f*.
  - sintered, thermometric analysis: I, determination of Fe content; II, determination of Ni and Co content, (2) 71*c*.
  - stoichiometric and nonstoichiometric, thermodynamic and transport properties, (4) 161*f*.
  - thermodynamic properties, by emf measurements, (10) 362*j*.
- pretreatment of sheet steel, (10) 336*i*.
- sulfide pyrite, single crystals, preparation by chlorine transport, (6) 236*e*.
- systems. See *Systems*.
- uranate, heat capacity, (5) 194*g*.
- -Zn ferrite, relation between magnetic properties and powder characteristics in, (5) 181*g*.

Niobates, alkali-rare earth, with tungsten bronze-type structure, (8) 288*f*.
- Ba,Sr,Na, characteristics, (10) 360*c*.
- lead-barium, P (5) 183*j*.
- rare earth, segregation coefficients, in $CaMoO_4$, (4) 154*c*.
- rare earth, segregation coefficients, in $SrMoO_4$, (1) 36*j*.
- single crystal, growth, for electrooptic and nonlinear applications, (6) 233*d*.
- Na-Li, solid solution ceramics with small Li concentrations, properties, (1) 17*j*.
- sodium-potassium, isostatically hot-pressed, transducer material for ultrasonic devices, (1) 17*d*.
- transition metal, transport reactions and crystal growth, (6) 239*c*.

Niobium, and alloys, coating composition of Al and metal fluordies for, P (4) 93*g*.
- carbide, orthorhombic β' phases, (9) 326*h*.
- diboride, borothermic preparation, (8) 288*j*.
- NbC-Fe, NbC-Ni, and NbC-Co alloys, liquid phase sintering, carbide grain growth during, (10) 350*j*.
- Nb_6Cl_{18} cluster, electronic structure, (4) 136*d*.
- NbO_2F, thermal decomposition, vapor pressure studies, (4) 163*i*.
- $NbTe_4$, high-pressure induced transformations in, (10) 354*h*.
- Nb_3Sn, doped with ZrO_2 particles, diffusion-processed, superconducting performance of, (4) 157*h*.
- Nb_3Sn, solid bodies containing, manufacture, P (5) 184*a*.
- NbZn—μ-phase, (6) 235*f*.
- nitride, finely divided nonpyrophoric, preparation, P (6) 218*a*.
- oxidation protective coatings applied to, P (6) 208*c*.
- oxide, free energy of formation, (8) 292*b*.
  - high purity, P (2) 74*d*.
  - structural stabilization with WO_3, (8) 298*c*.
- parabolic oxidation kinetics, (2) 81*j*.
- pentoxide, α-, defect structure, (5) 193*b*.
  - α-, near-stoichiometric, oxygen diffusion in, (4) 131*e*.
  - crystals, preparation and dielectric properties, (10) 359*f*.
  - crystals and scales formed on Nb, diffusional properties of oxygen in, (5) 193*c*.
  - purification, P (7) 263*c*.
  - single crystals, *B*-modification, ac polarization in, (10) 349*g*.
  - solubility in melts of fluoride salts of Li, Na, and K, (7) 269*b*.
- selenide, preparation and electrical properties, (11) 376*d*.
- stannide, deposition, P (5) 182*b*.
- systems. See *Systems*.
- tetravalent, tetrachlorides and oxychlorides, compounds formed with chlorides af alkali metals and ammonia, properties, (7) 268*g*.
- -Ti binary alloys, silicided, oxidation behavior, (7) 246*d*.
- wire niobium stannide coated, P (2) 65*h*.

Nitrates, alkali-metal, fused, electrical conductance, activation volumes for, (8) 293*b*.

Nitrates *(continued)*
- alkali metal, fused, electrical double layers in, (9) 320*j*.
  - molten, infrared absorption band forms, (11) 385*h*.
  - molten mixtures, ultraviolet spectrum of nitrate ion in, (5) 202*c*.
- binary melts, Pyrex membrane potential in, (5) 199*g*.
- determination in saline minerals, (4) 119*b*.
- melts, glass-forming, transport in, under pressure, (10) 338*c*.
- melts, supercooled, relaxation processes in, (4) 153*j*.
- mercurous, solution, for estimation of iron in glasses, (1) 9*h*.
- molten, cathode processes in, (4) 127*g*.
- monazite rare-earth, optimization of solvent extraction plant to process, (8) 286*i*.
- ternary fused, enthalpies of mixing in, (5) 194*c*.

Nitrides, formation and reactivities: I, review and introduction; II, Ca and Mg nitrides and $CaCN_2$, (10) 353*i*.
- of group IVA and VA elements, anomalous superconducting properties, (10) 350*d*.
- metal, P (9) 309*c*.
- metal, fibers, textiles, and shapes, production, P (1) 14*g*.
- mono-, cubic refractory, cohesion in, (5) 192*j*.
- nitridation, direct, of silicon substrates, (5) 177*b*.
- nitridation, reactions in alumina-based ceramics, (1) 13*a*.
- nitriding reaction in system silicon-silica, (4) 146*d*.
- and oxynitrides, transition metal, solid solutions and preparation, P (4) 107*j*.
- plasma-gun sprayed: II, properties of resulting products, (5) 177*j*.
- plasma-sprayed, properties, (4) 93*f*.
- plasma torch, sprayed, (2) 58*a*.
- plus wear-resistant additives bonded with Fe, Co, or Ni, P (2) 59*a*.
- ultrarefractory, mechanical properties, (1) 13*b*.

Nitrites, molten, cathode processes in, (4) 127*g*.
- salts, inorganic, luminescence, (5) 196*b*.

Nitrogen, adsorption, for characterization of Al hydroxide gels, (8) 289*d*.
- adsorption, at −196°C on nonporous Al_2O_3, (10) 361*j*.
- in boron nitride, gasometric microdetermination, (6) 226*i*.
- determination in AlN after decomposition under pressure with hydrochloric acid, (6) 225*f*.
- determination in ceramic U compounds, (4) 120*h*.
- diffusion in glass melts, (9) 305*a*.
- diffusion in ZrN, film-thickness determination, (5) 194*g*.
- equilibrium with Al in liquid 18% Cr-8% Ni stainless steel, (6) 232*c*.
- isoelectronic trap in phosphorus-rich $GaAs_xP_{1-x}$, (9) 311*d*.
- NO_2, EPR spectra of radicals formed when adsorbed on MgO, (5) 194*e*.
- nitrous oxide and cesium, recovery from fission product solutions containing NH_4NO_3, (4) 125*g*.
- reaction with Mg in temperature range 400°–650°, (1) 33*d*.
- solubility, in liquid Fe-Cr-Ni alloys, (6) 235*h*.
- solubility, in Ta, (8) 298*a*.
- systems. See *Systems*.
- in UN, determination, (6) 226*i*.

Nomenclature, thesaurus of engineering and scientific terms, B (2) 86*a*.

Nomographs, nomograms, and graphical calculations for use in preparing ceramic bodies, (5) 186*c*.
- for radiant coefficient of heat transfer, (6) 228*d*.

Nose cones. See *Spacecraft*.

Nozzles. See *Refractories; Spacecraft*.

Nuclear power. See *Energy*.

Nucleation, amorphous, in metals, (4) 126*d*.
- and coarsening in binary condensed phases, (5) 197*i*.
- in condensed phases, linked flux analysis, (1) 31*h*.
- density, of gold deposited onto color-centered cleavage surface of rock salt, (6) 235*j*.
- in diamond growth, (2) 77*c*.
- and growth of magnesioferrite in MgO containing 0.9% Fe^{2+}, (6) 235*j*.
- ice, under pressure and in salt solution, (8) 293*h*.
- nonclassical theory, and phase separation by spinodal decomposition, (1) 33*c*.
- of thin lead films on amorphous substrates, (2) 63*j*.
- volume free energy, of crystalline phase from multicomponent regular solution, calculation, (6) 230*f*.

Oils, crude, process and catalyst for reducing pour point, P (1) 24*f*.

Olivine, Mg-Fe, synthetic, cell dimensions and X-ray determinative curve for, (11) 383*f*.
- natural, crystal structures, (8) 290*c*.
- oxidation, (9) 326*j*.
- solid solution series, X-ray diffraction study, (10) 363*e*.

Olivine *(continued)*
- -spinel stability relation, structural basis, (10) 361*b*.
- stability in Ni-Mg-Si-O system, (7) 269*f*.
- structure, magnetic interactions in, (5) 196*b*.
- in system MgO-"FeO"-SiO_2, equilibrium phase compositions and thermodynamic properties, (4) 135*d*.

Opacification. See *Enamels; Glass; Glazes*.

Optical devices, electron, method and apparatus for investigating high-temperature metallographic phenomena of high-melting-point metals, (6) 227*j*.
- utilizing substantially tetragonal ferroelectric tungsten-bronzes, P (5) 184*d*.

Optical materials, chalcogenide infrared, elastic moduli, (2) 48*e*.
- elements, MgO infrared transmitting, hot-pressing, P (1) 11*c*.
- glass for glazing, measurement of characteristics, (6) 208*f*.
- ultraviolet transmittance between 1050 and 3000 A, effects of simulated high-energy space environment, (1) 28*i*.

Optical properties, activity, in $Bi_{12}GeO_{20}$, (1) 33*g*.
- of Al_2O_3 in vacuum ultraviolet, (9) 326*a*.
- $BaTiO_3$, melt-grown, (10) 352*b*.
- CdF_2:In and CdF_2:Eu, (10) 358*a*.
- $CaWO_4$, influence of impurity defects, (4) 140*c*.
- ceramic glazes: II, experiments with polarized light, (6) 219*j*.
- clay suspensions, diluted, (1) 33*i*.
- constants, longitudinal and transverse, of absorbing uniaxial crystals, determination—optical anisotropy of graphite, (4) 131*h*.
- constants, near ultraviolet, of LaF_3, (1) 33*i*.
- of cuprous oxide in ultraviolet, (4) 147*a*.
- of free electrons in ZnO, (4) 147*b*.
- infrared, of VO_2 above and below transition temperature, (2) 79*b*.
- lead glass, shock-compressed, (1) 7*a*.
- PbO single crystals, (1) 28*b*.
- lithium gallium oxide, (1) 37*d*.
- $LiNbO_3$ single crystals, (1) 34*d*.
- MoO_3, single crystal and thin film, (1) 34*b*.
- nonlinear coefficients d_{31} and d_{33} in $LiNbO_3$, relative signs of, (8) 297*h*.
- nonlinear tensor coefficients in oxygen-octahedra ferroelectrics, calculation, (4) 127*j*.
- perfection, of quartz grown in RbOH and other alkali hydroxides, (7) 267*a*.
- phenomena, associated with Brazil-twin boundaries in quartz, (10) 358*c*.
- phenomenon, in $LiNbO_3$ single crystals, (2) 81*e*.
- of radiation-induced molecule-ion in Al_2O_3, (10) 362*c*.
- of SiC films prepared in microwave discharge, (5) 181*j*.
- silicon oxide films, effect of ultraviolet radiation, (1) 28*c*.
- study, of electronic structure of graphite, (2) 81*f*.
  - of isomorphous series $Na(Sc,Fe)TiO_4$, (11) 385*g*.
  - of low-temperature radiation effects in lead halide crystals, (8) 291*i*.
  - of particle size of montmorillonite with various adsorbed cations, (9) 326*f*.
- of thin films grown on rough surfaces, measuring technique, (4) 120*g*.
- tin oxide crystals, (10) 352*g*.
- TiC, (1) 33*i*.
- turbidity, basic instrumentation, (5) 187*a*.
- of unidirectionally solidified NaF-NaCl eutectic, (8) 276*f*.
- V_2O_5 single crystals, (5) 198*a*.

Ores, beneficiating, method and means, P (5) 191*c*.

Organic compounds, matter, structure and influence on use of raw materials in area of mineralogy and metallurgy, B (11) 389*b*.

Orientation, crystalline, effect on Young's modulus of artificial graphite, comments, (4) 129*a*.
- crystallographic, effect on dissolution of UO_2 in nitric acid, (5) 193*g*.
- crystallographic, effects on iron, oxidation, (4) 133*c*.
- dependence, of Rutherford scattering of protons from quartz, (4) 147*f*.
- determination, by selected area electron diffraction, (9) 314*i*.
- influence on properties of grain boundaries in NaCl, (1) 31*a*.
- mis-, substrate, effects in epitaxial GaAs, (9) 320*d*.
- preferred, in metals, determination, P (7) 261*a*.
- preferred, in X-ray diffraction in crystals, apparatus and process for eliminating, P (4) 121*d*.
- re-, of fibers during mechanical working, (10) 342*b*.
- re-, molecular, in liquids and gases, (9) 325*b*.

Orthochlorite. See *Chlorite, ortho-*.

Orthopyroxenes. See *Pyroxenes, ortho-*.

Orthosilicates. See *Silicates, ortho-*.

Oscillations, continuous optical parametric, in $Ba_2NaNb_5O_{15}$, (4) 129*h*.
- current, in photoexcited GaAs, (9) 310*f*.
- current, by two bulk negative-resistance effects in photoexcited GaAs, (9) 310*e*.
- high-efficiency optical parametric, in $LiNbO_3$, (8) 292*i*.
- microwave, of Ge silver bonded diode, (4) 109*g*.

Oscillations *(continued)*
temperature, in Czochralski crystal growth, (4) 159*g*.
Oscillators, CdS, active, for focusing of laser beam, (2) 77*f*.
CdS ultrasonic, active, (4) 126*d*.
crystal, temperature compensation, P (10) 346*e*.
GaAs bulk, (7) 254*j*.
grooved bulk semiconductor, P (10) 345*a*.
InAs Gunn, P (2) 65*d*.
microwave, structure and fabrication, P (6) 224*b*.
semiconductor, bulk negative conductivity, P (11) 376*h*.
semiconductor bulk, P (5) 185*g*.
semiconductor bulk effect microwave, P (6) 223*e*.
thin film piezoelectric, P (5) 185*f*.
Osmium, oxide pentafluoride, orthorhombic phase, structure, (5) 200*j*.
oxide pentafluoride, preparation and physical properties, (5) 195*j*.
tetroxide, ionization and dissociation, (2) 79*i*.
Ovens. See *Furnaces; Kilns.*
Oxalates, thermal decomposition, (1) 39*a*; (4) 150*j*.
Oxidation, anodic, of Al, (10) 350*c*.
anodic, of Ta, (10) 357*b*.
behavior of silicided Nb-Ti binary alloys, (7) 246*d*.
of calicum, reaction mechanisms, (4) 157*b*.
carbon and sulfur, in clays, relation of thermal behavior of pyrite to, (9) 308*g*.
catalyzed, of ZnS under acid pressure leaching conditions, (4) 127*g*.
of cobalt between 750° and 1000°C using inert gold spheroidal markers, mechanism, (10) 357*d*.
controlled, of silane, (8) 289*e*.
of Cu and Cu-Ag alloys in CO_2 at 1000°C: I, linear kinetics, (4) 148*b*.
effects on surface-barrier detectors, (5) 180*g*.
electrochemical, of semiconducting ceramic $BaTiO_3$, (6) 220*g*.
of ferrous iron in vermiculite and biotite alters fixation and replaceability of K, (5) 198*c*.
of GaP and GaAs, (1) 34*a*.
of graphite, by CO_2-CO gas mixtures, (8) 295*h*.
catalyzed by Pd, (9) 326*i*.
by CO_2, effect of chlorine, (8) 291*d*.
effect of ultrahigh pressure, (8) 291*h*.
inhibiting effect of chlorine or carbon tetrachloride, (9) 323*b*.
of hafnium, at high temperatures, kinetics, (1) 38*b*.
heat, of Mg thin films, self-supported, (8) 281*i*.
high-temperature, of ductile Cr-Re alloys, (1) 30*f*.
of Ta, rate-controlling processes in, (4) 152*g*.
III, ZrB_2 and HFB_2, (2) 78*g*; IV, ZrC and HfC, (4) 138*e*.
internal, of Fe-Mn alloys, (4) 140*h*.
of iron, effects of crystallographic orientation and oxygen pressure, (4) 133*e*.
of Fe single crystals at 350°C, (4) 148*c*.
of Fe-Cr binary alloys, (4) 148*c*.
kinetics. See *Kinetics.*
low-pressure, of Zr, (4) 143*b*.
of magnetite to γ-Fe_2O_3, mechanism, (8) 295*a*.
of magnetites, low-temperature, mechanism, (9) 324*d*.
mechanism, of superpurity aluminum in dry oxygen, (1) 31*e*.
of metals, oxygen gradients in: V, oxygen-saturated Zr, (2) 83*j*.
of Ni by CO_2, (4) 148*g*.
of olivines, (9) 326*j*.
oxidizability, of BN at high temperatures, (2) 54*j*.
photosensitized, of CO on semiconductors supported by silver, (5) 181*a*.
properties, of Zr-2.7 wt% Nb alloy in temperature range 300°–500°C, (4) 148*h*.
of pyrite, (4) 148*i*.
radiolytic, of single crystal graphite, nature of active species, and *G* values, (9) 311*i*.
re-, metal, in aluminum electrolysis, (1) 32*e*.
resistance, of alloys based on tungsten and niobium silicides, (6) 216*h*.
resistant, refractory compounds, P (4) 107*i*.
of silicon at high temperatures and low pressure under flow conditions, (1) 34*d*.
of SiC at 1150° to 1400°C and at 9×10^{-2} to 5×10^{-1} torr oxygen pressure, (2) 81*i*.
of SiC, temperature and oxygen pressure dependence of, (4) 159*h*.
steam, kinetics, in UO_2 at high temperatures, (10) 361*b*.
studies, of UN by electron microscopy, (1) 33*j*.
thermal, of silicon, transport processes in, (1) 40*a*; (4) 129*c*.
thermal, of silicon using wet oxygen, (1) 17*f*.
vacancy generation and kinetics, (9) 332*f*.
of water, by transition metal ions, oxygen isotope effects, (9) 326*a*.
Zr, in dry oxygen, (4) 136*i*.
Zr, influence of thin noble metal films on, (5) 195*c*.
ZrO_2, oxygen deficient, and relation to oxidation of Zr, (1) 34*b*.
Oxides. See also *Rare earths* and specific types.
and basic salts, formation and reactivity: I, basic Mg chlorides and sulfates; II, radioisotope studies of calcareous materials, (10) 353*j*.
bodies, polycrystalline, P (8) 274*e*.
ceramic, behavior toward SF_6 at high temperatures, (1) 11*i*.
ceramics, sintered, vaporization and creep, (4) 163*i*.
-ceramic materials, sintering characteristics, based on MgO-Al_2O_3-spinel, (1) 36*e*.
and chalcogenides, structural investigation at normal and very high pressures, (9) 330*a*.
combinations, quantitative analysis by electron microprobe in, (9) 328*b*.
complex, single crystals, growth from fluoride melts, (8) 292*e*.
compounds, stabilities, and activity/composition relations in oxide solid solutions, (5) 200*e*.
crystals, melt-grown, developments in, (7) 254*j*.
cubic, lattice energy, (1) 31*h*.
densification, effect of impurities, (4) 132*i*.
of different valence, influence on properties of ceramics in system ZnO–TiO_2, (2) 62*i*.
diffusion in, (1) 27*a*.
divided, extremely finely, P (2) 74*f*.
electrical conduction mechanisms in, B (7) 272*g*.
of elements, microhardness, (7) 267*e*.
of elements of second group in periodic system, reaction with oxides of lanthanum and neodymium, (8) 297*f*.
extremely finely divided, colloidal solutions of, which are stable on storage, P (10) 349*b*.
formed on thin film of Cu at elevated temperature, electron microscopic observation, (8) 291*e*.
of Gd, Y, or La, fluoro-substituted Eu-activated, for phosphor, P (4) 113*e*.
growth, in Al-Al_2O_3 SAP-type alloy by hot stage transmission electron microscopy, (1) 34*e*.
of heavier salts, infrared absorption frequency and characteristic Debye temperature of, (2) 79*a*.
high-pressure phase transformation, coordination and volume changes accompanying, (10) 351*e*.
high-temperature, monocrystals, growing, (2) 62*c*.
hot-pressing, cyclic high-pressure, P (2) 58*a*.
industrial, application of sol-gel processes to, (2) 54*i*.
infrared absorption spectra, (4) 140*e*.
inorganic, adsorption of water vapor by, (1) 24*j*.
layer, *p*-type, on metal, diffusion coefficients, oxygen activities, and defect concentrations across, (2) 75*f*.
MO_2-$nM'O_2$ compounds (M = Si, Ge, Ti; M' = Zr, Hf, Ce, Th), comparison of structure, (9) 318*c*.
mass transport in, B (5) 204*a*.
metal, deposit, scraped removal by ceramic edge, P (5) 191*c*.
effect on Al_2O_3 surface grain growth, (1) 28*a*.
electron probe microanalysis, comparison of correction methods, (1) 21*h*.
freezing point measurement, with solar furnace, (7) 266*d*.
and metalloids, P (4) 125*j*; P (7) 263*b*.
partially ordered defects in, statistical model, (10) 360*j*.
particles, of reduced size, production, P (6) 230*d*.
pigmentary, preparation, P (8) 288*e*.
pigmentary, process for classifying, P (2) 74*b*.
process and apparatus, P (1) 24*e*.
ternary, crystal growth by chemical transport, (10) 351*i*.
transition, single crystals, growth by arc-transfer method, (4) 138*a*.
mixed, P (4) 94*c*.
mono-, cubic refractory, cohesion in, (5) 192*j*.
of MOS structure, built-in voltage and charge distributions in, (8) 289*a*.
noncontaminated thermal, growing on Si, apparatus and process, P (8) 282*b*.
and oxide solid solutions, thermal expansion anisotropy, (9) 332*c*.
oxidizer, solid, for conversion of nitric acid to nitrogen dioxide, (2) 72*b*.
particles, formation on tungsten, field ion microscopy study, (10) 353*c*.
permeability, to gases, research at Leeds University, (1) 13*d*.
per-, role in gas ionization, (5) 189*e*.
powders, finely divided, synthesis, P (9) 317*a*.
properties, changes in during sintering, (4) 160*f*.
pure, compact shapes, production by hot-pressing, and properties, (2) 67*j*.
refractory metallic, melting and electrolysis, (1) 23*h*.
refractory samples, specific gravity, precise determination by mercury pycnometer, (7) 260*h*.
resilience, preparation of products, (9) 328*j*.
and silicates, chemistry, collection of USSR papers, B (4) 168*h*.
simple, self-diffusion in, (7) 268*b*.
sprayed with oxyacetylene torch, sintering, (2) 57*g*.
sub-, volatile, (4) 163*f*.
systems. See *Systems.*
Oxides *(continued)*
ternary, with fluorite structure, nonstoichiometry in, (5) 197*g*.
trace coloring, in optical glasses, problem of chemical analysis of, (8) 276*g*.
transition-metal, application of molecular orbital method for inorganic molecules to, (4) 145*i*.
transition-metal, reactions with liquid sodium: I, dioxides of Mo, W, and U, (1) 35*i*.
Oxygen, activities, across *p*-type oxide layer on metal, (2) 75*f*.
adsorption on impure ZnO, infrared study, (10) 355*g*.
in Al, determination by means of 14 MeV neutrons with account of flux attenuation in sample, (6) 225*h*.
atomic, kinetics of attack of high-temperature Mo and W by, (4) 141*i*.
atoms, kinetics of combination with O molecules, (8) 294*b*.
bubbles, behavior in soda-lime glass, (4) 94*g*.
and carbon isotopic composition of marine carbonate sediments, factors affecting: III, Eniwetok Atoll, (6) 229*a*.
chemisorbed, effect on electrical conductivity of Zn-doped polycrystalline SnO_2, (9) 320*g*.
chemisorption, on alkaline earth oxides, (1) 25*i*.
determination by fast neutron activation in thin films, (8) 280*h*.
diffusion, in CoO as measured by proton activation of ^{18}O, (8) 295*h*.
in $GdSO_3$, (10) 358*g*.
in growing ZrO_2 films, (10) 352*g*.
in hypostoichiometric Zr-oxide in temperature range 875°–1050°C, (4) 148*j*.
in monoclinic ZrO_2, (5) 198*d*.
in monocrystalline rare earth oxides, (1) 27*b*.
in near-stoichiometric α-Nb_2O_5, (4) 131*e*.
diffusional properties, in niobium pentoxide crystals and scales formed on Nb, (5) 193*e*.
distribution coefficient, in germanium, (11) 384*j*.
effect on rf-sputtering rate of SiO_2, (4) 133*c*.
equilibrium pressures, over oxides of lead at various temperatures, (1) 29*j*.
evolution, at Pt anode in Li silicate melts, kinetics, (7) 267*i*.
free-, content, of gas or dust mixture, process for determination, P (4) 122*c*.
in gas mixture, method and device for determining, P (1) 22*f*.
gradients, in oxidizing metals: IV, kinetics of hafnium oxidation at high temperatures, (1) 38*b*.
influence on existence domains of $\overline{U}$ $\overline{C}$ phases, (10) 355*e*.
influence on growth of 2H-SiC whiskers, (4) 140*d*.
intrinsic bulk defects and adsorption on MgO, CaO, and SrO, (8) 289*g*.
ion, refraction in glass in system Na_2O-MgO-SiO_2, dependence on composition, (2) 47*e*.
isotope and cation exchange chemistry of feldspars, (4) 148*a*.
isotopes, of minerals from carbonatites of Fen area, South Norway, (4) 148*c*.
ordered arrangement, in interstitial solid solution of Zr-O system, (2) 81*g*.
overvoltage, on graphite electrodes in fused salts, (6) 216*i*.
O^-, trapped in alkali iodide crystals, paramagnetic resonance spectra of, (8) 296*b*.
O_3^- ions, in alkali halide crystals, spectroscopic constants for, (8) 298*c*.
ozone, adsorption on silica gel, (1) 24*i*.
pressure, effect on iron oxidation, (4) 133*e*.
redistribution in UO_2 fuels, (8) 295*j*.
self-diffusion, in BeO by proton activation of oxygen-18, (10) 360*e*.
self-diffusion in ceramics, determination by nuclear activation, (6) 231*e*.
in silicates, (11) 385*a*.
systems. See *Systems.*
in UN, determination, (6) 226*i*.
and water vapor, reaction on UN, UC, and $(UPu)C_{1-x}O_x$, (1) 12*i*.

Packaging. See also *Shipping.*
of glass panels and like frangible materials, crate for, P (2) 52*e*.
for glass stemware, P (10) 339*i*.
heat shrink, in brick industry, (7) 250*a*.
for laboratory tubes, P (10) 339*i*.
protective, key to lower costs, (6) 225*a*.
shrink foil, of brick veneer, experiences with, (10) 340*c*.
for building materials transport, (10) 364*a*.
of palletized goods (drain tile), (10) 340*d*.
in whiteware industry, (10) 343*f*.
Palladium, catalyst for graphite oxidation, (9) 326*i*.
contact, ohmic, to Si semiconductor, P (6) 223*c*.
dichloride, whiskers, preparation and properties, (4) 148*d*.
oxide, free energy of formation, (4) 136*f*.
Pd_4S, high-temperature phase, crystal structure, (9) 319*f*.
tetravalent, new ternary oxides of, with pyrochlore structure, (2) 80*j*.
Pallets. See *Materials handling.*
Panels. See *Building materials; Glass.*
Paper, filler, attapulgite clay, and method of forming newsprint with, P (6) 229*b*.
vermiculite, P (6) 218*g*.
Paramagnetic materials. See *Magnetic materials.*

Particles. See also *Colloids.*
analyzing apparatus and method utilizing multiple apertures, P (8) 286*b*.
bauxite, impregnated, sintered, and product, P (10) 335*g*.
classifier for, P (7) 261*b*.
colloidal, multilayers, (1) 33*d*.
diamond and cubic BN, coated with photopolymerized material, P (2) 43*g*.
of different size, mechanism of mutual flocculation, (7) 253*j*.
of different sizes, method and apparatus for separating, P (11) 381*f*.
dispersed hard, effect on high-strain behavior of nickel at room temperature, (6) 232*b*.
distribution, according to volume, (5) 190*c*.
distributions, -diameter, determination in silica and gold suspensions, (5) 193*b*.
fine, α-Fe_2O_3, shift of spin flip temperature of, (2) 82*j*.
fine, surface area determination, rapid method, (6) 227*e*.
index test, for evaluation of geometric characteristics of aggregates, (5) 187*i*.
length, measuring apparatus, P (7) 261*a*.
in liquids, apparatus and method for removing concentration of, P (10) 349*a*.
metal oxide, of reduced size, P (6) 230*d*.
minute, suspended in gaseous atmosphere, apparatus for acoustically detecting, P (6) 227*g*.
Ni-on-SiO_2, ferromagnetic anisotropy, effects of hydrogen and oxygen chemisorption, (5) 194*c*.
particulate material, drying, P (2) 67*h*.
polydispersed, adhesion number in tearing off of, (7) 263*e*.
sand, contact gage for rapid and accurate three-dimensional grain size measurement of, (11) 380*a*.
shape, coefficients expressing influence in computation of specific surface, (1) 26*f*.
shape, indication by measuring capillary rise, (6) 226*a*.
SiC, graded by size and shape at Electro, (4) 104*h*.
size, average in crystalline ceramics, (10) 350*h*.
below 1 μm, possibilities of determining, (11) 380*d*.
between 10^4 and 10^8 Å, X-ray determination, (2) 71*e*.
characteristics, effect on DTA of powdered materials, (1) 21*f*.
classification, method and apparatus, P (4) 125*e*.
dependence of magnetic heat capacity of $Ni(OH)_2$ crystals at low temperatures, (4) 148*f*.
determination with Coulter Counter, (11) 380*d*.
determination by turbidity and refractive index increment, (4) 119*c*.
determination, variance and other measures of line broadening in powder diffractometry, (9) 315*f*.
determination by X-ray absorption, (2) 69*i*.
determination by X-ray absorption analysis, apparatus and process, P (9) 315*h*.
effect on reaction rate constants in formation of zinc aluminate spinel, (4) 133*d*.
effect on selection of grinding wheels, (10) 335*f*.
effect on strength of Ti diboride and Zr diboride, (2) 55*f*.
of enamel color, relation with firing temperature, (11) 368*h*.
influence on erosion resistance of refractory concretes, (8) 279*b*.
influence on high-temperature ductility of Al-Al_2O_3 alloy, (4) 140*b*.
limitation, modifications to Zener formula for, (8) 295*g*.
of montmorillonite with various adsorbed cations, optical study, (9) 326*f*.
and packing property of fine powders, (4) 149*h*.
relations with clay content, quartz, and organic carbon in Lake Erie and Lake Ontario sediments, (11) 382*f*.
scale, (11) 380*b*.
variation of surface characteristics of quart powder with, (4) 163*a*.
of very fine powders, centrifugal sedimentation balance for measuring, (4) 119*a*.
of ZnS: I, influence of precipitating conditions, (4) 148*f*.
size analysis, and distribution, using spatial filtering techniques, P (9) 315*j*.
effect of settling convection, (1) 22*a*.
hydrometer method, (1) 21*b*.
new method, (5) 187*d*.
size distribution, apparatus for recording, (1) 21*e*.
micro, of abrasives, practical determination by sedimentation, (10) 347*d*.
of "monodisperse" particles from 0.8 to 3.5 μm in diameter using Coulter Counter and electron microscopy, (4) 119*c*.
process and apparatus for determination, P (6) 228*b*.
sizing, fine, of mineral resources of Saurashtra and Gujarat, new process and apparatus, (4) 123*g*.
small, equilibrium shape in contact with foreign substrate, (1) 29*a*.
smaller than 30 μm in diameter, technique for mounting, sectioning, and polishing, (8) 285*h*.

Particles *(continued)*
solid, spherical, effect of capillary liquid on adhesion force between, (1) 27*e*.
spheroidal, SiO_2-Al_2O_3, P (7) 262*j*.
suspended, degree of dispersion, ultrasonic measurement, (2) 71*h*.
TiO_2, P (2) 74*g*.
UN, spherical, with porous interior, preparation, P (4) 106*j*.
vapor coated, apparatus for producing, P (6) 217*h*.
wet solid and semisolid, drying or treating, P (2) 68*c*.
Pelletization, of glass batch, (1) 8*b*.
Pellets, spherical, apparatus for forming, P (6) 225*e*.
Peltier effect, for determination of crystal growth rates, (4) 126*i*.
Periclase, crystal growth, effect of heating atmosphere, (7) 250*f*.
solid solutions, containing Li^+ and R^{3+} ions, (9) 326*d*.
Perlite, composition, porous low density perlite structure, P (8) 278*i*.
expanded, for panels, P (4) 102*g*.
expanded, separating with minimum particle breakage, P (9) 308*g*.
filter aid products, P (7) 263*a*.
as raw materials for glass industry, (6) 210*g*.
Permeability. See also *Porosity.*
air, of granular materials, (5) 189*h*.
coefficient, of cohesive soils, determination, (5) 190*a*.
hydraulic, of crystal plug, variations in, (1) 40*b*.
of oxides to gases, research at Leeds University, (1) 13*d*.
of sulfur in alpha iron, (4) 155*f*.
Permittivity. See *Dielectrics, constant.*
Perovskites, conditions for existence of, (4) 129*a*.
containing In and Tl, synthesis, (11) 387*i*.
ferroelectric crystals, introduction of oxygen vacancies in, P (5) 185*a*.
fluorides, infrared transmission spectra and lattice vibration analysis, (4) 140*j*.
$Pb(NbFe)_{1/2}O_3$ and $Sr(TaFe)_{1/2}O_3$, study with Moessbauer effect, (10) 361*b*.
$PbSnO_3$, new, high-pressure synthesis, (7) 266*d*.
paraelectric, electrooptic effects in, (2) 76*g*.
$Sr_2(FeMo)O_6$ and related compounds, magnetic and electrical properties, (2) 79*j*.
vibronic structure in luminescence spectra of rare earth ions in, (2) 84*e*.
Petrography, control of clinker quality, (1) 3*f*.
of Indian magnesites, (2) 73*j*.
of Indian magnesites calcined up to 2000°, (2) 73*h*.
of Pennsylvania underclays in Illinois, (2) 73*i*.
-porosity relations in carbonate-quartz system, Gatesburg formation (late Cambrian), Pennsylvania, (9) 326*g*.
and stratigraphic analysis, of Upper Jurassic-Lower Cretaceous Morrison and Kootenai formations, southwest Montana, (11) 387*f*.
Petrology, of dolomite (pre-Cambrian), Beck Spring, Kingston Range, California, (6) 229*h*.
of Grimsby sandstone (Lower Silurian) of Ontario and New York, (11) 386*d*.
of grospydite xenoliths from Zagadochnaya Kimberlite pipe in Yakutia, (1) 34*f*.
of Mt. Misery Volcano, St. Kitts, West Indies, (8) 296*d*.
sandstone, evidence from luminescence petrography, (1) 36*i*.
pH. See *Hydrogen ion concentration.*
Phase, ANb_2O_6 and ATa_2O_6, [A = Ba, Sr, or Ca], (5) 192*d*.
binary condensed, nucleation and coarsening in, (5) 197*i*.
boundaries, chemical processes in, (6) 231*d*.
boundaries, in thallium-lead system, calculation from activity data, (1) 25*c*.
composition, of ceramic raw materials and green and fired bodies, quantitative determination, (8) 280*c*.
compositions, of thin layers in system Cr-SiO, (9) 311*e*.
condensed and gas, computer calculation applied to exchange equilibria between, (1) 26*i*.
connectivity, in microheterogeneous glasses, origin, (4) 96*d*.
correlation, in systems formed by oxides of rare earths and chromium, (1) 34*g*.
crystalline, quantitative determination with X rays, (6) 226*e*.
crystalline, volume free energy of nucleation, from multicomponent regular solution, calculation, (6) 230*f*.
formation and structural behavior in sand-lime brick hardened with water vapor, (11) 373*i*.
high pressure, of Al_2GeO_5, (7) 266*d*.
high pressure, with corundum structure, (4) 146*f*.
orthorhombic β', of niobium and vanadium carbides, (9) 326*h*.
relations, of amphiboles, B (1) 41*a*.
between two varieties of uranium sesquinitride, (10) 358*b*.
during formation of barium-cobalt hexagonal ferrite $BaCo_2Fe_{16}O_{27}$, X-ray and microstructural study, (9) 333*a*.

Phase *(continued)*
separation, in glasses, direct observation, (9) 315*d*.
and nonclassical nucleation theory by spinodal decomposition, (1) 33*e*.
in soda-silica glasses, effect of water content, (11) 369*f*.
sillenite, problem, (8) 296*f*.
solid, reactions of titanates of bivalent metals, (7) 268*h*.
solid, solubility, at high pressure and stability of silica modifications, (1) 37*a*.
study, contribution obtained during reduction of n-Al_2O_3·MO oxides, (9) 318*h*.
surface, stability and transitions, (9) 330*b*.
TaC, abnormal structure, in WC-TaC-Co alloys, (4) 102*i*.
ternary FeB- and CrB-type with Y, La, and rare earths, (11) 388*c*.
transformations. See *Transformations, phase.*
transition metal, metalloid-stabilized Zr-rich, formation, (4) 141*f*.
transition, α-β, in quartz, Raman scattering study, (4) 152*c*.
in $BaTiO_3$, pressure-squeezing effect on, (4) 150*j*.
during firing of phosphogypsum and strength of phosphoanhydrite cement, (8) 274*c*.
high-temperature, in KH_2PO_4, (10) 355*b*.
in $Pb_3(NiW)O_9$ synthesized under high pressures, (2) 81*d*.
from monoclinic B- into hexagonal A-form in rare-earth oxide single crystals, (9) 323*f*.
in KH_2PO_4-type ferroelectric crystals, dynamic theory, (2) 75*j*.
in KNO_3 at low temperatures, (9) 327*a*.
and thermodynamics in monolayers, (1) 39*f*.
in transition-metal chalcogenides, (4) 149*a*.
ultrasonic method for producing in materials at high pressures, P (5) 186*f*.
in VO_2, (8) 296*f*.
of ZrO_2, (4) 154*a*.
vapor. See *Vapor, phase.*
Phase diagrams. See *Equilibrium studies.*
Phase rule. See *Equilibrium studies.*
Phlogopite. See *Mica.*
Phonons, hydrodynamic phenomena, in nonmetallic crystals, (2) 84*f*.
longitudinal optic, induce oscillatory tunnel conductance in InSb-oxide-metal structure, (4) 148*a*.
optical, in ZnS_xSe_{1-x} mixed crystals, (4) 147*j*.
zero-, lines and coupling, in neutron-irradiated MgO crystals, (2) 84*i*.
Phosphates. See also *Glass* and specific types.
alkaline earth, intermediate phases in basic solution precipitation of, (5) 195*g*.
apatitic, high temperature dehydroxylation, (6) 233*j*.
combination with and release from clay minerals through anion exchange treatment with ^{32}P, (4) 149*a*.
fluoro-, metal, P (1) 24*d*.
monocalcium, pure, P (1) 24*d*.
poly-, molten mixtures, surface tensions, (9) 330*j*.
pyro-, alkaline earth metal, production, P (2) 74*e*.
influence on transformation of amorphous to crystalline calcium phosphate, (5) 195*b*.
multivalent metal, P (1) 24*c*.
rare earth, spectral properties, (10) 358*f*.
reactions with kaolin and faujasite, (1) 26*a*.
rocks, crystal modifier in, (4) 123*f*.
separation, quantitative, (1) 21*g*.
systems. See *Systems.*
tetrameta-, of type $M_2^{II}P_4O_{12}$, crystallographic data for, (2) 75*h*.
Phosphorescence, in enamels, (1) 4*i*.
Phosphoric acid, and cement material, production process, P (7) 245*f*.
ortho-, aqueous, standard heat of formation, (8) 298*h*.
process, gypsum as by-product from: VII, dehydration and hydration in mineral acids; IX, statistical study of crystal modifier in phosphate rocks, (4) 123*e*.
pyro-, crystalline, P (10) 349*f*.
Phosphors, P (10) 345*h*; P (11) 378*c*, *d*.
activation, method, P (6) 222*a*.
alkaline earth halophosphate, activated by divalent Eu, (10) 349*j*.
Sb-activated halophosphate, with rare earth additive, P (6) 220*g*.
based on Ln_2SO_6, (10) 358*e*.
based on rare earth phosphates fast decay phosphors, (5) 198*j*.
based on rare earth phosphates: I, spectral properties of rare earth phosphates, (10) 358*f*.
Bi^{3+}-activated, investigations, (2) 79*h*.
calcium halophosphate, P (6) 220*h*.
Ca and Mg germanate, Tb-activated, P (9) 314*a*.
for cathode ray tubes, consisting of fluoro-substituted Eu-activated oxide of Gd, Y, or La, P (4) 113*c*.
for discharge lamp, normally sensitive to lehring, and method, P (6) 221*g*.
electroluminescent, P (4) 115*g*.
daylight and pink light emitting, preparation, P (1) 19*e*.
Zn-Cd sulfide-oxide, P (11) 377*g*.
Eu, mixed valence, (5) 197*d*.
Eu-activated, barium and strontium haloaluminate, P (9) 312*g*.

Phosphors, Eu-activated *(continued)*
containing LiF, P (11) 378*g*.
rare earth, borax-fluxed, P (11) 378*f*.
strontium fluoroborate, P (6) 221*i*.
yttrium and gadolinium vanadate-phosphate and vanadate-arsenate, P (4) 112*j*.
Y_2O_3 and Gd_2O_3, P (9) 313*c*.
Eu^{2+}-activated, efficient, new classes, (5) 200*c*.
Eu^{2+}-activated, quantum efficiencies, measurement using excitation to selected Eu^{2+} levels, (5) 196*i*.
fluorescent manganese activated magnesium digallate, P (2) 64*h*.
luminescence, based on host lattices ABO_4 (A = Sc, In; B = P, V, Nb), (11) 385*g*.
luminophors, thoria/europium fluoride, P (2) 66*j*.
luminophors, thoria/terbium fluoride, P (2) 66*j*.
orthovanadate, with zircon structure, (1) 33*i*.
particles, formation of electron barriers on, P (9) 312*j*.
particles, increasing electron energization threshold of, P (2) 65*c*.
and phosphor raw-mix materials, P (9) 313*a*.
rare earth activated, lanthanum and lutetium oxychalcogenide, P (4) 116*e*.
strontium lithium germanate, P (5) 185*f*.
yttrium and gadolinium oxychalcogenide, P (4) 116*e*.
rare earth silicate, composition, P (1) 19*g*.
red electroluminescent (Zn,Cd) (S, Se)-type, (5) 199*a*.
scandium-containing alkaline earth phosphate, with good temperature-dependence characteristics, P (4) 116*i*.
separating, P (9) 313*e*.
slurry coating composition, P (2) 65*j*.
strontium and barium substituted lanthanum phosphate, P (5) 185*c*.
strontium haloborate, P (6) 221*j*.
$Sr_3(PO_4)_2$-Tb, bluish-white emitting cathode-ray with long decay time, (5) 200*e*.
vanadate, P (5) 184*a*.
yttrium vanadate and yttrium europium vanadate, bismuth in, (4) 109*f*.
yttrium vanadate, europium, preparation by precipitation using ammonium carbonate, P (7) 258*e*.
(Zn,Cd) (S,Se,Te), impurity activated, emission spectra: II, silver activated, (1) 29*f*; III, self-activated, (4) 135*g*.
ZnO and Zn-CdO, (5) 203*g*.
ZnSe-type, electroluminescent properties, (5) 194*c*.
Zn silicate, of improved maintenance, P (4) 117*c*.
ZnS, P (7) 258*e*.

Phosphorus, atoms, irradiated silicon-containing, annealing, (1) 25*g*.
concentration profile and phase segregation in phosphosilicate glass on SiO_2 films, (4) 149*d*.
diffused in SiO_2 film, measurement of distribution using ^{32}P as tracer, (8) 294*g*.
halide-boron halide complexes, thermochemistry, (4) 161*f*.
oxide, and silicon oxide, to mask against diffusion of In or Ga into germanium semiconductor device, P (2) 67*c*.
pentoxide, role in TiO_2-opacified porcelain enamels, (7) 246*h*.
phosphogypsum, impurities, chemical analysis, (4) 120*g*.
in phosphosilica films on silicon substrates, nondestructive determination, (4) 120*j*.
P_4O_{10} and P_4O_6, molecular structures, (4) 145*a*.
radio-, valence distribution, in KCl single crystals: I, initial distribution; II, effect of thermal annealing, (9) 332*g*.
and Si determination in high-P glasses by IR-spectroscopy method, (2) 69*i*.
in synthetic hydroxylapatite complexometric determination, (6) 225*i*.
systems. See *Systems*.

Photoconductive effect, and (or) **Photoconductivity,** of CdS single crystal, pure, near band edge, (8) 296*h*.
decay of ZnO crystals in oxygen, (4) 149*f*.
far-infrared, in high-purity epitaxial GaAs, (8) 292*f*.
in oxide glasses, (6) 210*d*.
of photochromic Gd:CaF_2, (10) 358*f*.
properties, of Cd_4SiS_6 and Cd_4SiSe_6, (4) 109*i*.
properties, control in CdSe, (4) 129*j*.
of SiC, *n*-type, (9) 327*d*.
sintered layer, (Cd,Zn)S, (4) 109*i*.
in $SrTiO_3$, (5) 198*j*.
in $SrTiO_3$, anomalous temperature dependence of, (2) 74*j*.
in thin Nb_2O_5 diodes, (8) 281*c*.
two-photon, in semiconductors, calculations, (11) 383*d*.
of ZnO, effect of water vapor, (9) 320*b*.
of ZnO-Cu crystals, (9) 327*e*.

Photoconductors. See *Conductors, electrical, photo-*.

Photoelectric effect, in silver halides, (2) 81*g*.

Photography, camera, diffraction, and X-ray diffraction apparatus, (2) 70*i*.
camera, Kratky small-angle X-ray, high-temperature sample cell for, (9) 315*g*.
camera tube target, including *n*-type semiconductor having higher concentration of deep donors than shallow donors, P (1) 17*i*.
recording of high-speed processes, B (4) 167*f*.

Photometry, atomic-absorption flame, computer techniques for three-dimensional analysis in, (1) 21*a*.
flame, compared with gravimetry for determination of K_2O in soda-lime-magnesia-silica glasses, (7) 259*i*.
flame, determination of Ca in solutions of high Na content, (7) 260*d*.

Phyllites, pyrometamorphism, by dolerite plug, (8) 297*b*.

Physical chemistry. See *Chemistry*.

Physical properties, of activated alumina, effect of thermal aging, (1) 20*a*.
of Al-Al_2O_3 alloys, blended and ball-milled, discussion, (1) 12*a*.
of basic refractories, changes due to repeated heating and cooling, (11) 372*j*.
of beryllium compounds, (1) 39*f*; (4) 161*h*; (5) 201*d*.
of germanides of ceric group and yttrium rare earth metals, (5) 198*c*.
of glass-pot material, factors influencing, (2) 55*i*.
of infrared-transmitting materials, (1) 39*c*.
of Fe(III) oxide hydrate, (9) 318*b*.
of molecular crystals, liquids, and glasses, B (6) 241*i*.
of SiO films, resistance-heated and electron-gun evaporated, comparison, (1) 16*d*.
thermo-, of aqueous clay suspensions, (6) 239*j*.
of thin tetragonal InTe films, characteristics, (5) 192*b*.

Physicochemical properties, of aluminosilicate glasses, (4) 96*j*.
mechanics of dispersed structures, B (9) 334*j*.

Pickling, automatic analysis and control, (8) 274*h*.
equipment, planning, factors, (1) 4*b*.
ferric sulfate, for direct-on, cost controls, (1) 4*f*.
Frigidaire geared for direct-on, (10) 336*j*.
liquor, waste, (8) 275*g*.
metal, process, P (8) 275*h*.
procedures for sheet steel, (1) 5*d*.
steel strip, and regeneration of contact acid, P (8) 275*h*.
tanks, protective linings for, (8) 275*d*.

Piezobirefringence. See *Refraction, birefringence*.

Piezoelectricity, ceramic compositions, P (1) 18*i*; P (5) 184*f*; P (11) 378*d*.
ceramic materials, P (5) 184*g*.
ceramics, lead zirconate-lead titanate with iron oxide additions, (7) 255*d*.
ceramics, production and properties, (7) 255*j*.
composition, P (9) 313*b*.
constant, of quartz, temperature variation, (11) 388*b*.
crystal assemblies, P (4) 115*e*.
crystals, growing, P (6) 225*c*.
manufacturing apparatus, and X-ray diffraction method for location of atomic planes relative to crystal surface, P (9) 313*c*.
small, resonating at low frequencies, method and apparatus, P (6) 222*b*.
temperature compensating unit for, P (4) 117*c*.
device, P (11) 377*e*.
device, with encapsulating *pn* junction, P (8) 283*i*.
elements, joining by fluid amalgam, P (9) 312*h*.
lead zirconate-titanate ceramics, adulterated, high-field losses, (1) 17*d*.
material, polarizing, P (6) 222*c*.
materials, P (2) 66*c*.
piezo-optic behavior, nonlinear, of sphalerite (α-ZnS), (4) 146*g*.
properties, of $BaSrNaNb_5O_{15}$, (7) 255*i*.
of $LiNbO_3$ single crystals, (1) 34*d*.
of Na-Li niobate solid solution ceramics with small Li concentrations, (1) 17*j*.
sensing element, slotted, compensating means for, P (1) 18*c*.

Pigments. See also *Color; Stains*.
aluminosilicate, P (1) 23*f*.
base, zircon as, (5) 180*b*.
$CaHPO_4 \cdot 2H_2O$ and $CaSO_4 \cdot 2H_2O$, coprecipitated, P (8) 287*h*.
ceramic, classification by crystal structure, (2) 72*i*.
ceramic, in $R_2^{2+}R_2^{3+}(PO_4)_4$ system, synthesizing, (6) 219*g*.
chromium garnet-type, synthesis, (6) 219*f*.
composite colloidal particles, formation, and suspensions of, P (10) 349*c*.
dispersing in liquid media, P (11) 379*g*.
filter press cakes, or dispersion dyes, apparatus for mechanically after-dehumidifying and further treating, P (11) 379*d*.
inorganic blue to green, P (9) 317*d*.
inorganic thermal control, P (6) 208*b*.
purification, P (8) 288*c*.
sodium aluminum silicate, P (5) 191*a*.
Ti, P (11) 383*a*.
Ti, colored materials, with spinel structure, and preparation, P (5) 190*h*.
TiO_2, P (4) 125*b*.
acid-reacting ceramic grade, P (11) 382*g*.
-anhydrite composite, rutile, P (10) 349*e*.
apparatus for making, P (5) 190*e*.
coated with SiO_2 and Al_2O_3, P (7) 263*d*.
coating with hydrous metal oxides, P (4) 126*a*.
improved compositions, P (9) 317*c*.
manufacture, preheating oxidizing gas reactant in, P (9) 317*a*.

Pigments, TiO_2 *(continued)*
manufacture by reacting $TiCl_4$ with oxygen or gases containing oxygen, P (10) 349*f*.
porous silica coated, P (4) 125*f*.
stabilized, P (4) 125*a*.

Pipe. See also *Tile*.
clay, extruded horizontally by Dickey, (6) 214*a*.
polyester seals for, (4) 102*e*.
vitrified, direct drying, (7) 249*j*.
coupling, P (4) 93*b*.
glass, coupling, P (4) 99*b*.
glass, transparent reinforced, P (10) 339*a*.
plain-end, dominates Canadian production, (4) 102*d*.
plastic, nonporous asbestos-reinforced, P (11) 375*d*.
sewer, strength, increased by fine grinding, (8) 278*g*.

Plagioclase, from anorthosite rocks, relation between specific gravity and state of order in, (9) 328*i*.
low, revised dispersion method for, (6) 237*i*.

Plasma, "blow-off," at solid surfaces, laser-induced, (6) 234*e*.
burner, P (11) 369*b*.
direct current, production of TiN in, (11) 373*d*.
gun, Al_2O_3 layers prepared with, (9) 304*g*.
injected in semiconductor rods, effect of magnetic field on density distribution of, (5) 180*f*.
jet, for use in determination of minor constituents in limestone and dolomite by quantitative emission spectroscopy, (9) 315*b*.
torch, for preparing chromia/alumina and chromia/titania, (9) 325*d*.

Plaster of Paris. See *Gypsum; Plasters*.

Plasters, (8) 287*e*.
alpha, continuous production, P (7) 245*c*.
-board, from synthetic gypsum, P (8) 274*c*.
compositions, (10) 336*a*.
fire resistant product, P (10) 336*b*.
glass-reinforced gypsum, fracture studies using scanning electron microscope, (4) 91*g*.
gypsum, analysis by thermogravimetry, (8) 284*h*.
retarded compositions, P (9) 304*d*.
setting, effects of organic acids and salts on: III, citrates, (2) 44*j*.
hardened hemihydrate, strength, and content of dihydrate in argillaceous gypsum, (7) 244*i*.
model, large size, for making dies, shrinkage, (4) 92*g*.
molds. See *Molds*.
of Paris, P (5) 170*j*.
poroplast, material for molds, (4) 108*h*.
or sealing body, P (6) 207*c*.

Plasticity, dependence, of clay-water system on dispersed phase concentration, (7) 253*i*.
of granular substances, theory, (5) 201*c*.
index, reliability of determination, (5) 187*j*.
micro-, of quartz glass, effect of α-radiation, (2) 48*j*.
plastic limit, of soil, rapid technique for determination, (8) 285*c*.
pyro-, properties of clay, and role in formation of structure of ceramic materials, (11) 372*e*.

Plastics. See also *Resins*.
articles, hollow, P (2) 53*g*.
fiber-reinforced, elastic stiffness and economics, (1) 6*f*.
fiber-reinforced, radiant energy reflective and translucent structures of, P (4) 101*a*.
instability, effect on compressive deformation, (6) 226*f*.
materials, fiber-reinforced, continuum model for, (1) 26*b*.
reinforced by strong fibers, surface chemistry, (10) 338*a*.
surface flow, Bingham, analysis in canal viscosimeter, (1) 20*i*.
system, ceramic filled, P (11) 369*b*.
thermo-, polyarylene polyether resin article, glass fiber reinforced, P (6) 212*d*.

Plating. See *Coatings*.

Platinum, cobalt oxide, electrically conductive, low pressure synthesis, from platinum halide and oxide containing cobalt, P (4) 113*j*.
contamination and reduction of ceria, (1) 34*h*.
for high temperature crucibles used in processing radioactive wastes, (5) 178*a*.
liquid, interaction with transition metal carbides, (5) 195*d*.
oxidation kinetics with convective diffusion and surface reaction, (4) 150*a*.
Pt_2Ge_3, crystal structure, (10) 351*j*.
Pt_2P_3, crystal structure, (4) 130*d*.
stable and transient complexes, pulse radiolysis studies, (9) 328*a*.
tetravalent, new ternary oxides of, with pyrochlore structure, (2) 80*j*.
thio- and seleno- compounds of, (5) 192*c*.
use in glass industry, (4) 98*a*.

Plutonium, dicarbide, high temperature structure, (9) 322*g*.
dioxide, heat capacity and thermodynamic properties, (10) 354*e*.
hypostoichiometric, evaporation from 2070° to 2380°K, (1) 29*c*.
substoichiometric phase, thermodynamic study of vaporization behavior of, (4) 161*e*.
mononitride, consistent thermodynamic values for, (1) 26*i*.
nitride, heat of combustion, (4) 138*g*.
optical spectra, in CaF_2, (4) 147*c*.

Plutonium *(continued)*
recovery from refractory siliceous materials, P (4) 125*f*.
separation by LiF sorption technique, P (11) 383*a*.
systems. See *Systems*.
and uranium, mixed oxides, thermal conductivity study, (8) 300*c*.
Polarization, ac, in B-modification Nb_2O_5 single crystals, (10) 349*g*.
dynamic, of ferroelectric materials, investigation, (2) 79*g*.
effects, in semiconducting oxide glasses containing Na_2O, (11) 370*b*.
electrical, during internal friction measurements in alkali silicate glass, (1) 6*i*.
of light emitted by neodymium-glass laser, (8) 296*j*.
low frequency effects, in thin evaporated dielectric films, (1) 17*e*.
in perovskite-type ferroelectric materials, calculation, (1) 16*b*.
of piezoelectric material, P (6) 222*c*.
space charge, in liquid electrolytes, (9) 320*g*.
spontaneous, direct measurement, for relation between linear and quadratic electrooptic coefficients in $LiNbO_3$, $LiTaO_3$, and other oxygen-octahedra ferroelectrics, (2) 82*a*.
spontaneous, of hexagonal ZnS, CdS, and ZnO crystals, (8) 292*c*.
structure, of interfacial amorphous films, (6) 220*i*.
superficial, role in growth of noncentrosymmetric crystals in polar direction, (4) 138*a*.
Polarography, of complexes formed by cadmium with oxalate ions, (1) 34*h*.
determination of Ca and Mg, (9) 315*b*.
for determination simultaneously of Fe and Ti, (5) 188*c*.
in molten $LiNO_3$+$NaNO_3$+KNO_3: I, half-wave potential and diffusion coefficients, (8) 296*j*.
in molten salts, (4) 150*d*.
Polarons, excitations, (10) 353*j*.
Polishing. See also *Abrasives; Diamonds; Lapping*.
chemical, of α-corundum surfaces with V_2O_5, (4) 150*f*.
chemical, of single crystal α-alumina using silicon, (2) 75*c*.
glass: I, relation between polishing efficiency and crystalline structure of iron oxides; II, role of mechanical processes during, (5) 173*e*; III, action of material displacement on leveling of relief layer during polishing with free and bonded grains, (6) 211*b*; IV, surface defects during polishing with bonded grains, (9) 307*f*.
with bonded polishing agent: I, leveling of surface relief, (10) 338*f*.
mechanical, by PVC polishers, (10) 338*b*.
mechanism, (4) 117*j*.
method, for removal of material from monocrystalline semiconductor bodies, P (7) 257*h*.
and plating silicon planar surface, P (7) 257*a*.
Polishing apparatus. See also *Abrasives; Diamonds*.
and cutting and grinding ornamental stone, P (9) 314*g*.
for glass, and grinding, P (1) 10*i*.
and rounding, for crystalline carbon bodies, P (7) 243*j*.
for semiconductor slice, P (7) 255*f*.
for specimens, P (7) 260*h*.
Polyacrylamide, effect on filtration properties of aqueous asbestos suspensions, (1) 23*c*.
Polymerization, methacrylate and acrylate ester, ceramic packing material for prevention of, P (2) 67*g*.
Polymers, article, composite spheroidal phosphorescent organic, P (11) 376*j*.
cationic, structure, effect on flocculation and electrophoretic mobility of crystalline silica, (1) 28*d*.
fracture, B (1) 41*d*.
inorganic, dimensionality and mechanical properties, (4) 131*h*.
layer thickness, adsorbed on TiO_2, viscometric technique for determining, (5) 188*c*.
saccharide, in hydraulic cement mix, P (6) 207*d*.
Polymorphism, behavior, of TiO_2 under dynamic loading, (10) 358*h*.
of eucryptite, high-form, (6) 231*j*.
of HfO_2 under high pressure, (9) 318*a*.
of $MgSiO_3$, (1) 34*i*.
in rare earth sesquioxides at high temperature, (1) 34*i*.
of SiC crystals, (1) 35*a*.
of Ti_3O_5, (10) 358*j*.
in vacuum-deposited GaP films, (1) 35*a*.
of ZrO_2, (1) 35*b*.
of ZrO_2 influence of additions of GeO_2 and Y and Nd germanates, (7) 267*b*.
Polymorphs, aluminum silicate, stability relations in, (7) 269*h*.
Al_2SiO_5, coexistent, minor element content, (9) 324*h*.
stability, (1) 37*j*.
transition metal content of, (9) 332*c*.
high pressure, with corundum structure, (4) 146*f*.
ice, neutron diffraction study, (8) 295*c*.
symmetry-entropy-volume relations in, (1) 39*a*.
Polyphosphates. See *Phosphates*.
Porcelain, art. See *Art and artware*.
articles, P (11) 376*a*.
Porcelain *(continued)*
bodies, containing clays, feldspar, and quartz, isostatic pressing, (4) 108*g*.
dry strength, influence of drying degree, (2) 60*c*.
with higher Al_2O_3 content, thixotropy control, (10) 343*f*.
cladding, noble metal alloy adapted to receive, P (4) 109*b*.
colors, behavior in wash tests, (1) 15*b*.
composition, casting, effect of organic additions on rate and nature, (5) 179*j*.
dental. See *Dental ceramics*.
dielectric strength, effect of active admixtures, (7) 253*f*.
earthenware, and stoneware, (6) 219*e*.
electrical. See *Insulators, electrical*.
electrical materials, toughness parameter, (6) 219*i*.
-faience industry, mechanization and automatization in, (2) 60*g*.
firing, role of gas medium in, (10) 343*d*.
glass-, bodies, structure and phase composition, (6) 211*j*.
glazed, delayed fracture, (2) 59*j*.
greenware, water resistance, water absorption, and strength, relation with heating temperature, (6) 219*d*.
hard, structure, development by use of mineralizers, (11) 375*h*.
high strength, (7) 253*h*.
hollow products, formed by pressure shock-wave caused by electric discharge, (2) 67*f*.
industry, West Germany, central laboratory, (10) 343*g*.
for insulator, P (6) 220*a*.
irradiation influence on, (2) 60*f*.
liquid-gas equipment in factory, (6) 219*h*.
manufacture, technical faults in, and their elimination, B (1) 42*j*.
plants, highly mechanized, control technology in, (10) 343*e*.
pretreatments, automating, (7) 246*i*.
structure, study, electron microscopy replicas for, (10) 347*f*.
thermal shock resistance, (6) 219*h*.
two-component, (2) 60*h*.
Pores, distribution, in solids from sorption isotherms of nitrogen at −195.8°C, (2) 70*d*; (4) 120*d*.
in firebrick: III, effect of various atmospheres, (11) 373*c*; IV, influence of vacuum, during heating, (2) 56*i*.
formation and evolution, with different sintering temperatures, (6) 237*f*.
and grain growth kinetics, (8) 296*a*.
micro-, adsorption in: I, theoretical representations, (7) 263*h*.
micro-, analysis, (1) 31*i*.
migration in ceramic fuel elements, (8) 296*j*.
size, determination with mercury porosimeter, (7) 259*h*.
size distribution, analysis of experimental data in determining texture of microporous materials and apparatus for determination of sorption isotherms and curves of, (1) 25*e, f*.
in earthenware bodies, (1) 15*b*.
of powders, determination from solute adsorption, (6) 225*h*.
in refractories, measurement methods compared, (2) 69*a*.
size and volume, device for measuring, P (7) 260*g*.
space, influence on hydrothermal synthesis of calcium silicate hydrate, (11) 368*c*.
structure, analysis without pore shape model, (1) 35*c*.
complete analysis: I, micropores; II, four silica gels, (1) 31*i*.
of mixed hydroxides and oxides of Mg and Fe, (1) 38*g*.
systems, changes associated with sintering, (1) 25*e*.
texture, of pouring pit refractories, (11) 373*b*.
volume uncertainties for microporous solids, (4) 150*e*.
Porosity. See also *Permeability; Pores*.
of coated articles, testing, P (11) 381*a*.
connected, in ceramic bodies, model for, (2) 70*f*.
effect, on strength of Ti diboride and Zr diboride, (2) 55*f*.
on thermal conductivity of UO_2, (4) 133*e*.
on Young's modulus of artificial graphite, comments, (4) 129*a*.
Griffith flaws and effect of, on tensile strength of brittle ceramics, (10) 354*h*.
intracrystalline, in organo-clays, (1) 37*f*.
macro-, importance of measuring during sintering of clays, (6) 233*f*.
micro-, assessment, (2) 68*g*.
effect on elastic modulus and yield curve of polycrystalline graphite, (10) 341*b*.
influence on ductility of Al/Al_2O_3 alloys, (9) 323*f*.
petrography-, relations in carbonate-quartz system, Gatesburg formation (late Cambrian), Pennsylvania, (9) 326*g*.
in soda-lime-silica glass, (4) 97*b*.
surface, effect on emittance of opaque substance, (6) 232*h*.
Porous materials. See also *Cements; Concretes; Insulation, thermal*.
containing components of various hardness, thin sections preparation from, (2) 70*e*.
Porous materials *(continued)*
dusty-gas theory for thermal transpiration through, (11) 384*j*.
micro-, texture, analysis of experimental data in determining, size distribution of pores and apparatus for automatic determination of sorption isotherms and pore size distribution curves, (1) 25*e, f*.
structures, P (7) 252*f*.
two-phase, thermal conductivity, (9) 315*d*.
Portland cement. See *Cement, portland*.
Positrons, radioactive capture by electrons, and use of Born approximation, (4) 111*e*.
Potassium. See also *Alkalis*.
borohydride, nuclear magnetic relaxation studies of internal rotations and phase transitions in, (11) 386*j*.
bromide, anionic diffusion in, measurement by isotopic exchange, (8) 294*g*.
crystals, dislocation conduction and decoration in, (9) 320*e*.
crystal, NMR measurements of field gradients at Br nuclei surrounding substantial Cl ion in, (4) 146*f*.
entropies and enthalpies for self-diffusion in, (4) 135*a*.
exchange reactions with bromine vapor, (1) 29*c*.
partial thermodynamic functions in bromide-chloride mixtures, (8) 290*c*.
temperature dependence of *F*-center absorption in, (9) 331*j*.
chloride, with color centers, Schottky and Frankel disorder in, (2) 82*g*.
crystal, exchange reaction with chlorine gas, (4) 136*a*.
crystals, melt grown, observation of dislocations in, by thermal etching, (10) 357*i*.
crystallization, from aqueous solutions in presence of lead ions: I, calorimetric study, (7) 264*i*.
deformation and charge flow in, (8) 292*e*.
growth of Ag on, observed by LEED and Auger emission spectroscopy, (8) 281*i*.
interaction with chloride of Eu(III) and Tb, (7) 267*d*.
interaction with holmium chloride and erbium chloride in melts, (4) 140*e*.
melt-grown, dislocations and grain boundaries in, (7) 265*e*.
single-particle and equilibrium collective effects of hydroxyl impurities in, (2) 32*d*.
single crystal, valence distribution of radiophosphorus in: I, initial distribution; II, effect of thermal annealing, (9) 332*g*.
Na and Li M_A centers in, (4) 155*d*.
substrates, unexpected effects of forced high nucleation densities by flash evaporation of gold on, (9) 311*i*.
temperature dependence of *F*-center production in, (4) 159*a*.
zone purification, (4) 164*e*.
difluorophosphate, synthesis and properties, (8) 299*i*.
feldspars, calculated powder patterns, (10) 350*h*.
fixation and replaceability, altered by oxidation of ferrous iron in vermiculite and biotite, (5) 198*c*.
flame test, improving, (8) 285*e*.
fluoroborate, heats of formation, (9) 322*d*.
graphite, order-disorder transformation in, (9) 326*g*.
halides, neutron-irradiated, rare-gas diffusion in, (8) 297*d*.
hexafluorotitanate, thermal decomposition, (8) 300*e*.
interstitial compounds, with C fibers, (9) 323*e*.
iodide, thermal motion of holes in, (4) 160*g*.
ion, measuring, and glass electrode for, P (11) 381*f*.
manganate, crystal structure, (4) 130*c*.
in Mn nodules, (4) 124*d*.
niobate, crystals, ferroelectric, temperature dependence of absorption edge in, (1) 39*d*.
nitrate, high-pressure form, crystallography, (11) 383*d*.
phase transition in, at low temperatures, (9) 327*a*.
single crystals, EPR studies of VO^{2+} in, (8) 291*g*.
oxalate monohydrate, crystals, deuteron and proton magnetic resonance study, (8) 290*f*.
oxide, determination in soda-lime-magnesia-silica glasses, comparison of flame photometric and gravimetric methods, (7) 259*i*.
oxide, in mineral standards, X-ray spectrometric determination by decomposition method, (6) 227*f*.
permanganate, crystal structure, (4) 130*c*.
K^+, addition, effect on transition of γ-Fe_2O_3 into α-Fe_2O_3, (11) 384*c*.
K^+, self-diffusion in its molten fluoride, (8) 297*d*.
^{39}K in KH_2PO_4 in ferroelectric phase, NMR of, (2) 81*b*.
^{39}K, in KH_2PO_4, NMR by double resonance method, (8) 295*f*.
KD_2PO_4, photon-photon scattering in, (10) 351*i*.
KH_2PO_4, EPR of Cu^{2+} in, (2) 76*b*.
high-temperature phase transition in, (10) 355*b*.
KD_2PO_4 and KH_2AsO_4, single crystal, infrared absorption by hydrogen bonds in, (2) 79*b*.

Potassium *(continued)*
$KMnCl_3 \cdot 2H_2O$, and $K_2MnCl_4 \cdot 2H_2O$, crystal structure, (8) 290*c*.
$KMnF_3$, absorption spectra, fine structure in, (4) 136*h*.
KNb_3O_8, micalike crystal, (4) 142*g*.
KAg_4I_5, relation of structure and ionic mobility in, (5) 199*b*.
$KTa_xNb_{1-x}O_3$ single crystals, growth and electrical properties, (2) 77*g*.
KTN, crystals, high resistivity, origin of lamellas in, (5) 198*a*.
and sodium, determination after separation from each other and from other ions by ammonium phosphomolybdate and other ion exchangers, (7) 259*j*.
-sodium ratios in aqueous solutions and coexisting silicate melts, (5) 198*f*.
-strontium and potassium-lead niobates containing La, crystal growth and electrical properties, (10) 351*h*.
sulfate, producing from langeinite, P (7) 263*b*.
superoxides, heats of formation and lattice energies, (1) 39*f*.
.systems. See *Systems*.
tantalate niobate crystal growth from melt, P (6) 223*f*.
tantalate-$KNbO_3$ mixed crystals, hydrothermal growth, and material produced, P (7) 256*b*.
tantalate, Raman spectrum, temperature dependence of, (4) 159*c*.
vanadate, V quadrupole coupling tensor in, (4) 163*d*.
Potters. See *Artists*.
Pottery. See also *Archeology; Art and artware; Bodies, ceramic; Design; Dinnerware; Earthenware; Stoneware; Whiteware.*
American studio, B (2) 85*d*.
bodies, raw batches from ready-mixed Tokaj-Hegyalja materials, (2) 60*c*.
construction, from cardboard cartons and tubing, (10) 335*i*.
continuous forming machine, automatic preforming device for, P (5) 180*c*.
crockery, semifinished, equipment for varnishing, P (5) 179*b*.
decoration. See *Decoration*.
Greek, in Bronze Age, B (11) 389*b*.
Jomon, B (7) 271*e*.
manufacture, P (7) 254*b*.
Rookwood, (6) 206*c*.
Rookwood, Book of, B (7) 271*c*.
stoneware-type bodies and glazes at cone 04-4 range, (6) 206*d*.
from Tikal, in Peten, Guatemala, chemical and mineralogical examination, (9) 303*h*.
treating clay surfaces, (8) 273*i*.
Pottery industry, Zanesville, in color, B (4) 168*j*.
Potterymaking apparatus and equipment. See also *Dryers; Kiln furniture; Kilns; Materials handling; Molds.*
potter's wheel projects, B (2) 85*g*.
wheel, throwing tips, (8) 273*j*.
Powders. See also *Granular materials.*
alumina, submicron size, die-pressing problems, (4) 118*a*.
apparatus for filling valve bags with, P (8) 284*e*.
atomized, in isotatic pressing, (4) 108*c*.
BeO, P (6) 229*i*.
blending, method and apparatus, P (2) 68*b*.
ceramic, preparation, new methods, (11) 379*f*.
cohesiveness, (8) 284*h*.
drying and preheating apparatus, P (5) 170*c*.
electrostatic characteristics, (4) 117*h*.
fine, particle size and packing property, (4) 148*h*.
fine grain, narrow band, effect on plasma coating characteristics, (1) 4*h*.
on foil solid Ta capacitor, P (11) 378*f*.
glass, sintering during constant rates of heating, (4) 118*c*.
high density compacting by Dynapak method, (4) 119*h*.
infrared spectra, by means of internal reflection spectroscopy, P (6) 227*h*.
metal, with inert solid surface films, hot-pressing by adding activator elements, P (2) 68*b*.
metal-coated, preparation, and cathode structures, P (2) 66*g*.
mixtures, binary, of variable composition, calculation of concentration distribution in, (2) 67*d*.
pair-, NMR spectra of, least-squares analysis, (8) 294*d*.
particles, use in electrical printing process using an opposing field, P (5) 186*e*.
patterns, calculated: II, six K feldspars and Ba feldspar, (10) 350*h*.
properties, changes in during pressing of hard materials, (6) 230*i*.
sample material, radiometric analysis, (8) 286*b*.
samples, preparation for spark source mass spectrometric analysis, (10) 347*g*.
silica, interaction with water, adsorption thermodynamics of, (4) 126*g*.
specific surface, determination from ratio of flow rates measured under different conditions of gas flow in porous medium, (2) 69*a*.
specimens, grading in respect to dispersion and compactness by diffracted intensity, (9) 315*f*.
suspended in gases, heat exchanger for, P (8) 284*f*.
Powders *(continued)*
tantalum nitride, and preparation, P (5) 179*f*.
WO_3, CuO, or Fe_2O_3, oxygen pressure change in, measurement by oxygen concentration cells, (1) 32*b*.
white quartz, P (7) 263*a*.
X-ray fluorescence analysis of, preparation of emitters for, (6) 227*a*.
Power. See also *Energy.*
limiting, in $LiNbO_3$, (8) 292*i*.
thermoelectric, of system "FeO," "FeO"-SiO_2, and "FeO"-CaO, (4) 162*c*.
Pozzolans. See also *Cements; Mortars.*
fly ash specification for use as, (1) 3*b*.
pozzolanic materials, Kansas, for cellular concrete, (2) 43*j*.
pozzolanic properties, of pulverized fuel ashes, P (2) 43*i*.
Roman, mechanical properties, (5) 170*f*.
Praseodymium, hydrides, magnetic and crystallographic characteristics, (2) 79*h*.
phosphide, growth, transport reaction for, (9) 332*d*.
Pr^{4+}, magnetic susceptibility in CeO_2, (5) 196*d*.
trifluoride, vapor pressure, heat of sublimation, and evaporation coefficient, (10) 363*g*.
Precipitates, in arc-melted thoria, (1) 35*d*.
co-, yielding $MgAl_2O_4$ spinel powders, (10) 340*j*.
grain-boundary, growth kinetics, (1) 30*i*.
nature, in boron-doped TiC, (1) 33*g*.
phenomena, in CdS:Cu and CdS:Au single crystals, annealed, (4) 131*i*.
in US single crystals, electron microscope studies, (1) 28*f*.
Precipitation, autoclave, of basic sodium aluminum sulfate, for alumina extraction, (2) 72*i*.
of calcium sulfate dihydrate, (9) 325*i*.
co-, of cations with $CaCO_3$: IV, of Sr^{2+} with aragonite between 16° and 96°C, (6) 231*f*.
co-, in system GeS_2-In_2S_3, (7) 264*d*.
of dodecamolybdosilicic acid with organic bases, (4) 120*e*.
hydrothermal, of UO_3 from uranyl nitrate solution, (2) 73*f*.
mutual effects of aluminum hydroxide-iron hydroxide, aluminum hydroxide-silicic acid, and iron hydroxide-silicic acid sols on, (6) 235*e*.
quantitative, of GeS_2, (6) 233*j*.
for separation of traces of elements: IV, separation through carbonates, use in determining trace contaminants in U compounds, (10) 347*e*.
of AgCl from homogeneous solution: I, particle size and shape characteristics, (9) 327*j*.
spinodal, in silicates: I, introductory application to exsolution in feldspar, (8) 298*h*.
Prehnite, space group, (1) 37*h*.
Presses, automatic tool, for calibrating cermet bushings and rings, (2) 68*i*.
controlled stroke, simple aparatus for measuring load of, (6) 225*b*.
filter, device for separating plates and frames of, P (8) 284*e*.
press friction, forming capacity, (10) 341*i*.
isostatic molding, automatically operating air vent for, P (9) 314*h*.
for making blocks from loose fiber material, P (2) 68*c*.
rotary table, at Danish soft mud plant, (8) 278*f*.
Pressing, die-, submicron size alumina powder, problems, (4) 118*a*.
dry-, in brick industry, (7) 249*j*.
dry-, of urania pycnometer, (1) 12*a*.
hard metals, (11) 379*d*.
hot-, of Al_2O_3, production of complicated shapes by, (11) 379*h*.
of ceramic objects, to improve properties, (2) 60*i*.
changes in properties of powders of hard materials during, (6) 230*i*.
cyclic high-pressure, of oxides, P (2) 58*a*.
for densification of alumina, (4) 131*b*.
high-pressure, of HfB_2, densification mechanisms in, (4) 131*b*.
high pressure, refractory materials, (6) 215*c*.
isostatic-, apparatus, P (5) 186*g*.
isostatic, new densification method in powder metallurgy, (4) 117*g*.
isostatic, of refractory bodies, P (10) 342*f*.
for joining refractory metal compounds, (6) 215*j*.
liquid-phase-extrusion, (5) 177*e*.
MgO infrared transmitting optical elements, P (1) 11*c*.
of metal powders with inert solid surface films by adding activator elements, P (2) 68*b*.
and metal vapor deposition in fluidized bed for preparation of UO_2-Mo and UO_2-W cermets fuel, (1) 12*g*.
process, P (4) 118*e*.
of pure oxides for compact shapes, and properties, (2) 67*j*.
reactive, of Al_2O_3 with additives, (8) 284*g*.
reactive, of kaolinites, (4) 153*a*.
reactive, of $Ni_{1/3}Fe_{2/3}$ oxyhydroxides, (4) 153*c*.
of Ti and Zr diborides, (2) 56*c*.
TiO_2, P (11) 371*a*.
of ZrC-Ni mixture, (2) 56*e*; (6) 215*e*.
zirconia method, P (1) 14*c*.
hydrostatic, of sanitary ware, (11) 375*f*.
Pressing *(continued)*
isostatic, atomized powders in, (4) 108*c*.
automation, (4) 108*c*.
of ceramic bodies, (11) 379*d*.
of clay-containing bodies, (4) 108*g*.
effects of physical parameters pertaining to, (4) 108*e*.
effect of pump capacity on output, (4) 108*e*.
equipment and use, (4) 108*f*.
in industry, (4) 108*i*.
in insulator production, laboratory investigations, (4) 108*j*.
for making uniform crucibles, (6) 215*f*.
as production process, (4) 108*h*.
of refractories at Corhart, (6) 214*j*.
scientific and technical problems, (4) 108*f*.
of special shapes of high surface quality in single operation, (4) 108*i*.
particulate material, P (9) 314*f*.
semidry, of Lower Kittanning clay, effects of varying water contents and pressures, (5) 176*g*.
Pressure, decomposition, of neptunium mononitride, (4) 144*d*.
dependence, of adsorption of krypton and xenon by crystals of zeolite LiX and NaX, (4) 131*c*.
of B_2O_3 viscosity, (1) 8*d*.
of infrared absorption of calcite, (10) 359*i*.
of Néel temperature of Cr_2O_3, (9) 328*d*.
of nuclear quadrupole frequency of ^{23}Na in $NaBrO_3$, (10) 359*a*.
of orthorhombic-cubic transformation in lead zirconate, (2) 82*e*.
effect, on graphitization of carbon: I, heat treatment of soft carbon under 1, 3, and 5 kbars, (4) 133*g*.
on homogeneous distribution of Ga in single crystal YIG, (11) 384*j*.
on ionization equilibria in water at 25°C, (11) 384*a*.
on structure and magnetic properties of $RbNiF_3$, (7) 265*j*.
equilibrium, of CO above uranium oxycarbides in presence of UO_2, (1) 29*h*.
equilibrium, of oxygen over oxides of lead at various temperatures, (1) 29*j*.
high, hydrothermal measurements on heavily ground kyanite and sillimanite, (7) 266*c*.
quenchable effects on cubic monoxide of Ti, (2) 82*h*.
reaction vessel, for diamond preparation, P (2) 67*j*.
high forming, effect on properties of ceramics with high permittivity, (7) 254*j*.
high uniaxial, effect along main crystalloaxes of Si and C, (9) 320*h*.
hydrostatic, effect on magnetic anisotropy of ferrous and ferric ions in ferrites with spinel structure, (2) 76*b*.
hydrostatic, effect on Néel temperature in FeO and CoO, (1) 27*j*.
oxygen, change in oxide powders, measurement by oxygen concentration cells, (1) 32*b*.
oxygen, dependence of SiC oxidation, (4) 159*h*.
sublimation, of cadmium(II) fluoride, Knudsen and Langmuir measurements, (1) 31*g*.
sublimation, of NdF_3 and stabilities of gaseous NdF_3 and NdF_2, (2) 80*i*.
and temperature dependences of isotropic elastic moduli of polycrystalline Al_2O_3, (7) 268*e*.
-temperature studies, of anatase, brookite, rutile, and TiO_2-II, (10) 359*b*.
-temperature studies of sulfospinels, (1) 35*i*.
ultrahigh, effect on boron nitride, (5) 177*d*.
ultrahigh, effect on oxidation of graphite, (8) 291*h*.
vapor. See *Vapor pressure.*
very high, apparatus for producing, P (11) 379*e*.
very high, behavior of carbonaceous materials at, (1) 25*a*.
vessels, cold seal, to operate to 1100°C at 3 kbars, (8) 285*d*.
Proactinium, diffusion, lattice and grain-boundary, in ThO_2 and ThO_2-UO_2 solid solution, (5) 196*i*.
Probes, thermal, P (6) 228*a*.
Protons, conduction, in borax, (4) 131*a*.
mobility in solids: II, dielectric and diffusion measurements in boehmite, (8) 296*i*.
transfer studies in ferric oxyhydroxides: I, hydrogen exchange between *a*-FeOOH and water, (9) 328*h*.
transport, during H_2 permeation in vitreous silica, (7) 248*b*.
trapping, in TiO_2 and simple oxides, (4) 149*h*.
Proustite, optical quality, crystal growth, (9) 319*c*.
photomultiplier detection of 10.6 μm radiation using optical up-conversion in, (2) 81*h*.
and related compounds, Czochralski-grown, (9) 319*c*.
Pug mills. See *Mills*.
Pulpstones. See *Abrasives*.
Pulverizers. See *Crushing and grinding apparatus.*
Pulverizing. See *Crushing and grinding.*
Pulverulent materials. See *Powders.*
Pumps, capacity, effect on output of isostatic presses, (4) 108*e*.
diaphragm-piston, for spray-drying plants, (7) 258*i*.
Purification, of commercial Alizarin Red S for determination of Al in silicate materials, (4) 120*i*.
continuous countercurrent washing system by thickener method, P (8) 287*g*.

Purification *(continued)*
of enclosed inert atmosphere, apparatus for, P (1) 20*c*.
of graphite, P (4) 107*d*.
of Nb and Ta pentoxides, P (7) 263*c*.
of pigments, P (8) 288*c*.
of solutions containing aluminates, P (10) 349*e*.
Pycnometer, air comparison, for determination of calcite and dolomite composition, (1) 21*c*.
for determination of apparent density of rough porous matter, (5) 187*d*.
mercury, for precise determination of apparent specific gravity of oxide refractory samples, (7) 260*h*.
urania, dry-pressing, (1) 12*a*.
Pyrargyrite, optical quality, crystal growth, (9) 319*c*.
Pyristor. See *Temperature, measurement.*
Pyrite, crystals, fine structure of faces, investigation by electron microscope, (4) 141*d*.
oxidation, (4) 148*i*.
for preparation of brown glasses, (11) 370*b*.
solid solutions, of type $Fe_xCo_{1-x}S_2$, $Co_xNi_{1-x}S_2$, and $Cu_xNi_{1-x}S_2$, preparation, (7) 268*d*.
thermal behavior, and relation to carbon and sulfur oxidation in clays, (9) 308*g*.
thermal decomposition in fluidized bed, (4) 160*b*.
Pyrochlore, $A_2Sn_2O_7$ stannates; X-ray, neutron, infrared, and dielectric studies, (2) 82*f*.
new, $Pb_2TiSO_5F_2$, (4) 148*j*.
oxygen deficient, preparation and properties, (10) 358*h*.
Pyrolusite, Hungarian, used in brown glass manufacture, (2) 50*c*.
Pyrometers; Pyrometry. See *Temperature measuring instruments.*
Pyroxenes, of Bushveld intrusion, South Africa, (11) 386*j*.
clino-, eclogite, from kimberlite pipes of Yakutia, (4) 132*f*.
metamorphic, paragenetic types and compositions, (4) 148*d*.
in meteorites, (4) 151*e*.
ortho-, ($MgSiO_3$-$FeSiO_3$ solid solution), hyperfine splitting of ^{57}Fe and Mg-Fe order-disorder in, (4) 139*c*.
pigeonite and clinoenstatite, domain structure, (11) 384*a*.
stability in Ni-Mg-Si-O system, (7) 269*f*.
synthesized, and properties, (4) 124*a*.
in system MgO-"FeO"-SiO_2, equilibrium phase compositions and thermodynamic properties, (4) 135*d*.

Quality control, of concrete, and economics for paving projects, (4) 92*c*.
at General Shale, (8) 284*f*.
optical inspection system, (7) 259*d*.
Quartz. See also *Glass; Refractories; Silicon, dioxide.*
in airborne dust in 0.5- to 2-μm size range, evaluation, (7) 260*b*.
α-, elastic constants, calculation from model, (4) 127*j*.
Raman spectrum, at high pressures, (10) 359*g*.
refractivity, (4) 134*a*.
α-β phase transition in, Raman scattering study, (4) 152*c*.
chemical interaction with GdIG, (4) 128*c*.
-corundum stability, problem, (10) 359*c*.
crystals, bonding leads to, P (11) 376*g*.
grown in RbOH and other alkali hydroxides, hydrothermal synthesis, optical perfection, and surface topography, (7) 267*a*.
growth, trapping colloidal inclusions in, (10) 363*b*.
hydrothermal growth: III, effects of constraints, (4) 139*g*.
internal structure and growth peculiarities, (4) 155*i*.
synthetic, quality determination by neutron diffraction, (11) 379*i*.
decorated diffusion paths in, (9) 319*d*.
diffusion paths in, (10) 352*h*.
dry milling, changes in, (5) 192*j*.
elastic surface waves in, attenuation at frequencies of 316 MHz and 1047 MHz, (7) 263*e*.
fabric studies in rocks of Sonapet Valley, Singhbhum District, Bihar State, (4) 123*h*.
formation and crystallization from binary lithium silicate melts and glasses, (9) 306*j*.
formation from dilute solutions at low temperature, (6) 232*h*.
fused, pure, thermal conductivity, precise determination, (9) 306*h*.
solution in Na_2O-SiO_2 melts, (9) 307*d*.
transient color centers in, (9) 307*h*.
fused ceramics, slip casting features, (6) 216*g*.
heat-treated, light scattering, in relation to hydrogen-containing defects, (11) 385*c*.
hydrothermal recrystallization of porcelanite to, (9) 322*j*.
inclusions, in almandine, stress effects around, and piezothermometry of coexisting aluminum silicates, (7) 269*j*.
irradiated, room-temperature, rate of hydrogen diffusion in, (5) 199*i*.
lattice defects in, X-ray moire topography, (9) 333*b*.
maxima, measurements on X-ray rotating table, (6) 226*d*.
natural, birefringence, (1) 25*a*.

Quartz *(continued)*
"natural" intragranular flow experimentally induced in, (6) 232*f*.
optical nonhomogeneity, nature of, (5) 197*j*.
optical phenomena associated with Brazil-twin boundaries in, (10) 358*c*.
orientation dependence of Rutherford scattering of protons from, (4) 147*f*.
piezoelectric constant, temperature variation, (11) 388*b*.
powder, surface characteristics, variation with particle size, (4) 163*a*.
relations with grain size, clay content, and organic carbon in Lake Erie and Lake Ontario sediments, (11) 382*f*.
from Ries Crater, Germany, shock induced planar deformation structures in, (9) 329*e*.
sands, behavior in mixture with lime under hydrothermal conditions, (1) 2*c*.
separation from granite, (8) 287*j*.
and other silicates, hydrolytic weakening, B (6) 241*c*.
Si thin films on, epitaxy, (9) 310*d*.
solubility, in aqueous solutions of hydrogen fluoride and ammonium hydrogen fluoride and in solutions with organic liquid mixtures, kinetics and morphology, (9) 324*b*.
surface and bond-forming properties, and application in mineral processing techniques, (6) 238*j*.
surface, observation in polarized light of step-like films of water on, (6) 235*a*.
synthetic, additives to: II, effects on growth of synthetic colored quartz, (9) 317*h*.
first-order prism faces, hillocks on, (8) 293*d*.
first-order prism faces, microtopographical studies, (9) 324*f*.
synthetic brown, EPR spectrum of Fe^{3+} in, (11) 384*j*.
systems. See *Systems.*
trapped electron dating in, ESR studies, (10) 363*a*.
variation of Compton scattering with changes in structure of, (4) 163*j*.
white, powder, P (7) 263*a*.
zero-field EPR of Fe^{3+} in, (11) 388*f*.
Quartzite, in California, (2) 73*e*.
decomposition, by formaldehyde-volatilization method, (5) 187*g*.
"natural" intragranular flow experimentally induced in, (6) 232*f*.
Quenching, concentration, of characteristic broadband fluorescence, (10) 350*i*.
Quicklime. See *Lime.*

Radiation, α-, effect on microplasticity of quartz glass, (2) 48*j*.
blackbody, resultant from infrared irradiation, coating thickness determination by means of measuring, P (4) 121*e*.
CO_2 laser, absorption in semi-insulating GaAs, (9) 318*b*.
coherent, luminescent materials and apparatus for generating, P (8) 282*c*.
damage, in BeO dispersion fuels, X-ray studies, (4) 164*g*.
in graphite, annealing study, by ESR, (2) 74*i*.
in ZrO_2, (8) 297*b*.
device, fluorescence, radiating at 280 nm wavelength, and making, P (5) 188*f*.
effects, in metal-insulator-semiconductor capacitors, determined from conductance measurements, (1) 17*a*.
of metal-nitride-oxide-silicon structures, (6) 236*h*.
in quartz, silica, and glasses, B (7) 272*g*.
electromagnetic, for bonding two different materials, P (5) 183*a*.
electromagnetic, effect on vitreous systems, (6) 208*j*.
electron beam, for instant curing of coating, (5) 189*d*.
electronic, ionic, or shortwave electromagnetic, for reducing specimen contamination in electron microscopes, P (4) 122*d*.
influence on decomposition rate of aluminate solutions, (1) 31*a*.
low-temperature, effects in lead halide crystals, ESR and optical studies, (8) 291*i*.
10.6 μm, photomultiplier detection using optical up-conversion in proustite, (2) 81*h*.
nuclear, transient effects on dielectric properties of refractory low-loss ceramics at microwave frequencies, (9) 311*h*.
optical, semiconductor junction device for generating, P (2) 66*f*.
radiative efficiency, in GaP diodes, dependence on heat treatment, (1) 26*j*.
recombination, from CdTe, superradiance in, (1) 29*c*.
shielding, service behavior of concrete for, (11) 368*d*.
source, scanned line, using reverse biased pn junction adjacent Gunn diode, P (8) 283*a*.
thermal, for transient heating or cooling of spheres at bounding surface, (2) 84*b*.
thermal neutron, influence on electrical properties of pure Al_2O_3 ceramics, (2) 63*a*.
transfer, across spherical pore in linear temperature gradient, (10) 359*f*.
ultraviolet, cause of stress in glass, (6) 211*i*.
detection method, P (8) 286*c*.
effect on optical properties of silicon oxide films, (1) 28*e*.
X- and γ-ray, effects on thermal decomposition of solid orthorhombic ammonium perchlorate; I, experimental and results; II, kinetics and discussion, (8) 291*a*.

Radiation *(continued)*
Radioactive materials. See *Isotopes; Wastes.*
Radioactive tracers. See also *Isotopes.*
application in use of refractories, (2) 54*i*.
in glass, bacterial attack on, (2) 46*i*.
Radioactivity. See also *Isotopes.*
capture of positrons by electrons, and use of Born approximation, (4) 111*e*.
Radiochemistry, studies, of adsorption of orthophosphate on ternary borate glasses, (5) 173*j*.
Radiography, auto-, alpha, of $(U,Pu)O_2$ microspheres, (10) 347*b*.
micro-, contact, with filtered X-ray spectra, (5) 187*c*.
of rock types, exposure charts for, (2) 69*e*.
Radioisotopes. See *Isotopes.*
Radiometer, radiometric analysis of powdered sample material, P (8) 286*b*.
Radium, in Mn nodules, (4) 124*d*.
Radomes, ceramic plastic composite material for, P (7) 252*f*.
Raman effect, of corundum, (4) 152*c*.
cross section, enhancement in CdS due to resonant absorption, (2) 76*g*.
first order, in III-V compounds, (4) 136*i*.
Rare earths (lanthanons). See also specific types.
activator ions, in optical quality single crystals of YAG, (10) 355*a*.
aluminates, (4) 152*d*.
carbonates, P (1) 24*d*.
chlorides, anhydrous crystal structures, (9) 319*h*.
chromotography, thin layer, (5) 188*a*.
compounds, crystal growth and magnetic susceptibility, (8) 289*i*.
compounds, electrical and magnetic properties, (10) 360*d*.
disilicides, dimorphism, (4) 131*h*.
diffusion into II-VI compounds, (11) 383*e*.
double oxides, of type $LaTO_3$ where T = Ho, Y, Er, Tm, Yb, Lu, crystallographic and magnetic study, (6) 231*b*.
elements, separation, P (10) 349*e*.
elements, for staining glasses, (6) 211*h*.
fluorides, complex, crystallographic studies, (9) 319*j*.
fluorides, enthalpies of formation, (9) 319*e*.
ions, in CeO_2:Yb^{3+} and Er^{3+}, ESR, (2) 76*f*.
in $SrTiO_3$, $BaTiO_3$, and other perovskites, vibronic structure in luminescence spectra of, (2) 84*e*.
trivalent, energy transfer between, in inorganic solids, (4) 135*h*.
metal, recovery from orthovanadate compound, P (5) 191*d*.
metal compounds, P (1) 19*f*.
metal dicarbides, vaporization, (5) 202*i*.
metal hexaboride rods, zone melting, (8) 301*a*.
metal oxalate, efficient preparation, P (5) 190*i*.
molecules, in II-VI compounds, electroluminescence via impact excitation, (9) 321*g*.
orthoferrites, Bi-substituted single crystal, preparation and magnetic properties, (10) 359*h*.
crystal structure: III, of thulium orthoferrite, (5) 193*j*.
single crystal, flux-grown, lead substitution in, (8) 294*d*.
oxide single crystals, phase transition from monoclinic B- into hexagonal A-form in, (9) 323*f*.
oxides, and hexaborides, standard heats of formation, (7) 269*h*.
interaction with BaO, (7) 267*d*.
in luminescent films, P (6) 221*j*.
melting points, determination, (8) 290*c*.
monocrystalline, oxygen diffusion in, (1) 27*b*.
solid solutions of, behavior in binary systems during crystallization by verneuil method, (9) 318*g*.
-oxygen-sulfur compounds, selected Eu^{2+}-activated, preparation and luminescence, (10) 359*g*.
sesquioxides, polymorphism in, at high temperature, (1) 34*i*.
sesquisulfides, monoclinic, structure determination and crystal preparation, (11) 387*h*.
silicate phosphor composition, P (1) 19*g*.
sulfates (4000–80 cm^{-1}), infrared studies, (5) 195*d*.
systems. See *Systems.*
trivalent rare-earth, in inorganic solids, energy transfer between, (4) 135*h*.
vanadates, spectra, (10) 360*i*.
in Y_2O_3, determination on basis of luminescence spectra of crystalline phosphors, (2) 75*e*.
Raw materials. See *Materials; Sands; Rocks.*
Reactivity, of calcium sulfate hemihydrate, (2) 45*f*.
enhanced, at dislocations in layer structures, (4) 135*j*.
Reactors, atomic, UO_2 as fuel for, (2) 58*h*.
high-temperature, coated fuel particles for, P (4) 103*j*.
isothermal countercurrent, topochemical reduction of hematite via intermediate oxides in, (2) 83*b*.
large volume semiconductor coating, P (11) 377*b*.
nuclear, effect of preirradiation on B_4C oxidation in, (5) 199*j*.

Reactors, nuclear *(continued)*
fast, cooled by supercritical steam, P (2) 58*e*.
fuel or fertile element for, P (4) 106*g*.
fuel material for use in, P (6) 218*b*.
fuel materials for, P (4) 106*i*.
power burst facility, irradiation testing (pulse conditions), (9) 308*i*.
treatment of graphite-coated particles for, method and apparatus, P (10) 342*j*.
Rebinder effects, in MgO, (4) 136*j*.
Recrystallization. See *Crystallization.*
Rectifiers, controlled, pinch-off shunt for, P (10) 345*e*.
device, semiconductor controlled, P (6) 223*f*.
four-zone semiconductor, with spaced regions in one outer zone, P (2) 64*i*.
high speed controlled, with deep level dopants, P (8) 282*j*.
Se, P (7) 258*a*.
thin-film, comprising layer of CeF_3 between metal and CdS layer, P (7) 258*c*.
unit, controllable semiconductor, P (6) 221*g*.
Recuperators. See *Furnaces; Kilns; Refractories.*
Reduction, of boric oxide, to boron monoxide, (1) 36*a*.
of $CuO_{0.97}$ in hydrogen, (1) 36*b*.
of magnetite, factors which influence rate minimum phenomenon during, (4) 157*h*.
reactions in alumina-based ceramics, (1) 13*a*.
Reflectance. See *Reflection.*
Reflection, and band structure of EuO, (11) 387*b*.
element, internal, for microsample analysis, P (4) 121*j*.
far-infrared, of magnesium stannide, temperature dependence of, (2) 84*b*.
of infrared materials: III, spectra from 2μ to 50μ; IV, bibliography, (1) 36*b*.
infrared spectral, of common minerals, (1) 31*c*.
patterns, Kikuchi-like, observed by scanning electron microscopy, comments on interpretation of, (2) 75*d*.
surface, apparatus for inspecting, with projector of pattern of lines having different thickness, P (7) 260*g*.
of titania opacified porcelain enamels, (6) 207*f*.
X-ray total, studies, of Ge, Au, and glass by three-crystal spectrophotometer, (4) 121*c*.
Reflectivity. See *Reflection.*
Reflectors, heat, composite coated, and infrared lamp heater equipped with, P (8) 275*b*.
markers, and reflective elements for, P (4) 101*c*.
Refraction, birefringence, in $LiNbO_3$, as function of melt stoichiometry, (1) 26*e*.
birefringence, of natural quartz, (1) 25*a*.
optical, in alkali halides, (4) 147*h*.
optical phenomena, quantum field theory of: I, linear and nonlinear optical rotation, (1) 35*f*.
of oxygen ion in glass in system Na_2O-MgO-SiO_2, dependence on composition, (2) 47*e*.
of oxygen ion in three-component silicate melts, (2) 50*g*.
of α-quartz, (4) 134*a*.
Refractive index, determination by immersion method, photoelectric apparatus for, (10) 347*c*.
of diamond, variation with hydrostatic pressure to 7 kbars, (9) 332*i*.
of glasses, effects of water content on, (6) 209*i*.
of glasses in system Na_2O-MgO-SiO_2, dependence on composition, (2) 47*c*.
high, glass compositions with, P (4) 99*h*.
large, interferometric measurement, (1) 31*h*.
of MgO, radiation-induced increase in, evidence for *F* center, (4) 152*b*.
of ZnO, ZnS, and thin-film insulators, (10) 359*h*.
Refractivity. See *Refraction.*
Refractories. See also *Aircraft ceramics; Insulation, thermal; Kiln furniture; Silicon, carbide.*
ablative antenna window compositions, P (5) 178*i*.
ablative product, P (4) 105*j*.
alkaline mixtures, containing formaldehyde-furylethylenealdehyde resins and gunning with, P (2) 58*j*.
alumina, with AlN coating, manufacture, P (5) 179*c*.
high, in glass industry, (1) 8*d*.
high, improvements in manufacture, P (4) 106*a*.
high, modulus of rupture at elevated temperatures, and performance in arc-furnace roofs, (6) 216*d*.
high purity, compressive creep, (8) 278*j*.
aluminosilica, clays for, (1) 13*f*.
microstructure and corrosion under service conditions, (7) 251*a*.
thermal-shock resistance, in relation to strength, thermal expansion, and modulus of elasticity, (2) 58*c*.
anchors, elements for support of, P (4) 106*f*.
application of radioactive tracers in use of, (2) 54*i*.
armor plate, lightweight protective, P (7) 252*a*.
articles, TiN, ultrapure, P (9) 309*d*.
baddeleyite-corundum, thermal expansion and volume stability, (6) 217*c*.
basic. See also *Refractories, chrome-magnesite;* specific kinds.
Refractories, basic *(continued)*
adhesion with portland cement clinker, (1) 12*d*.
coke bonded, tar impregnated, P (7) 252*h*.
direct-bonded, high-temperature creep, effect of liquid formation, (2) 55*e*.
in glass tank regenerators, evaluation, (8) 279*b*.
high-temperature properties, equipment for determining, (6) 215*i*.
mechanical properties, significance at elevated temperatures, (6) 216*e*.
for oxygen converters, P (8) 279*i*.
physical properties, changes due to repeated heating and cooling, (11) 372*j*.
slip casting, P (9) 309*a*.
basic brick, corrosion mechanism in, (11) 372*i*.
direct-bonded, changes in properties in electric furnace walls having different SiO_2 contents, (7) 250*g*.
direct-bonded, service tests in open hearth roof, (7) 251*b*.
direct-bonded, used in walls of electric furnace, chemical and physical changes, (10) 340*i*.
high-fired, used in open-hearth furnace, properties, (11) 373*f*.
high-fired, used in open-hearth furnace roof, (2) 56*a*.
high-fired, fired, and unfired, slag corrosion resistance, (11) 374*f*.
high-fired, use in roof of open-hearth furnace, (11) 374*b*.
hot bending strength, (4) 104*b*.
internal friction and modulus of elasticity, temperature dependence, (2) 78*j*.
lining, and process, P (5) 178*a*.
spacer for, in metallurgical vessels, P (9) 309*e*.
structure, effect of temperature cycling in oxidizing and reducing atmospheres, (6) 215*f*.
torsional strength, (4) 105*g*.
used in ladle lining, test results, (11) 374*c*.
in basic oxygen furnaces, (4) 105*g*.
blast furnace, slagging action of alkali on, (11) 374*f*.
blast furnace linings. See *Refractories, linings.*
block, preformed, for strip heating furnaces, P (1) 14*c*.
bodies, electrically and thermally conducting, of sintered SiC, protectively treating, P (4) 107*c*.
formed with multiplicity of closely spaced long and narrow passages through, P (7) 252*g*.
isostatic hot-pressing, P (10) 342*f*.
shaped, with attached spacer of nonmetallic sheet material, molding, P (2) 59*d*.
BOF, at Basic, Inc., (4) 103*h*.
boshes, aluminosilicate blast furnace, failure mechanisms in, (7) 250*j*.
brick. See also *acid, basic* and specific types under *Refractories.*
aluminosilicate, P (5) 178*j*.
blast furnace bottom, drying problems relating to laying of, (2) 55*d*.
cased, service test, and improved masonry in front wall of open-hearth furnace, (11) 373*i*.
cement kiln, service tests, (8) 279*d*.
for composite lining of induction furnace, P (1) 14*d*.
composite nozzle, application to LD converter taphole, (7) 250*d*.
composition, effect on rate of wear of magnesite rotary furnace linings, (2) 55*a*.
containing grog from shale, spalling, (9) 309*b*.
for cupola, corrosion test by crucible method, (7) 251*h*.
erosion and mineralogical change after service in cupola, (7) 251*d*.
for floor construction, P (6) 218*d*.
furnace roof hangers for, P (1) 14*b*.
improvement of quality for steel ladles, (1) 12*g*.
for LD converter, (10) 340*f*.
lightweight, and aggregate, P (7) 252*b*.
life, used in dust collecting hole in roof of electric furnace, (10) 341*j*.
new, problems, (4) 104*h*.
pouring sleeve, for LD converter, (11) 373*c*.
roseki, $CrSO_3$-containing, for cupola, corrosion resistance, (7) 250*e*.
roseki (pyrophyllite) and unfired SiC, service tests in electric furnace ladle, (11) 372*g*.
service tests in cupola lining, (7) 251*g*.
special, (4) 105*j*.
suspension arrangement, P (2) 59*e*.
tar-dipped, for cupola lining, erosion due to changes in atmosphere, (10) 342*g*.
tar-soaked, used in cupola lining, service test, (11) 373*j*.
unburned, service tests in water-cooled cupola, (7) 251*d*.
unfired, comparison test with direct bonded magnesite-chromite brick in open-hearth furnace roof, (11) 372*h*.
unfired, used in cupola lining, service test, (11) 374*a*.
building materials, under thermal and structural stress, thermal conductivity determination, (4) 119*f*.
burner throat, P (10) 342*b*.
carbide-graphite compositions, solid solution, making, P (4) 106*j*.
Refractories *(continued)*
carbon bricks, resistance to attack of pig iron melts, (4) 105*c*.
castable, gunning, on inside walls of blast furnace, (11) 373*h*.
physical properties, effect of casting methods, (11) 373*c*.
setting time, variation with curing temperature, (11) 374*e*.
use in lime-burning kiln at Mizushima Iron Works, (7) 252*a*.
use in roof of electric lead smelting furnace, (11) 374*b*.
workability, and problems in method of measuring consistency, and importance of standardizing working conditions, (5) 178*h*.
castable and plastic, lining for lime rotary kiln, service test, (11) 373*i*.
castable and plastic, use in continuous slab heating furnace, (7) 251*j*.
casting cores, free-flowing hardening mixture, plant for conditioning, P (9) 309*b*.
casting pit, corrosion by slag: II, observations on slagging action during crucible test; III, corrosion of acid refractory minerals by slag, (10) 340*j*.
casting pit, spalling test, (2) 57*j*.
cement kiln, interaction with clinker, P (10) 366*d*.
ceramic, aids in own curing process, (5) 190*b*.
in changing world, review, (1) 40*e*.
checkerbrick and checkerwork construction for regenerators, P (7) 252*f*.
chrome castable, physical properties, (11) 373*b*.
chrome concentration, in rubies, spectroanalytical determination, (5) 188*f*.
chrome-magnesia brick, formation of direct bond in, and changes in properties after high temperature firing, (11) 373*e*.
chrome-magnesite. See also *Refractories, magnesite-chromite.*
chrome magnesite and magnesite, eutectic minerals penetration in, (4) 104*i*.
chrome-magnesite brick, high-temperature thermal expansion, (1) 12*e*.
chrome ore, basic brick, high duty Simultansinter, (4) 104*d*.
plastic, composition, P (2) 59*c*.
vaporization at high temperatures, (7) 252*a*.
chrome spinellids, structural etching, (4) 156*f*.
chromium oxide-sintered high alumina brick, in roof of electric furnace, deterioration, (10) 340*f*.
clays. See *Clays.*
coated, for contacting molten glass, and method, P (7) 252*g*.
coatings. See *Coatings.*
composition, P (5) 179*e*; P (7) 253*b*; P (8) 280*b*.
containing nitrides and wear-resistant additives bonded with Fe, Co, or Ni, P (2) 59*a*.
dense, of VN or ZrN bonded with Fe, Ni, or Co, P (2) 58*b*.
heat-initiated phosphate-bonded, P (5) 178*h*.
and making refractory shapes, P (4) 107*h*.
compounds, fundamentals, B (4) 166*a*.
halogen combustion calorimetry, heats of formation of BN and BF_3, (2) 55*i*.
oxidation resistant, P (4) 107*i*.
vaporization, mass spectrometric studies, (5) 196*f*.
compressive creep characteristics of, (6) 214*i*.
concrete. See *Concrete.*
construction materials, in brick and tile industry, (10) 340*e*.
for construction and repair work, testing, (6) 217*b*.
for continuous casting, (1) 13*b*.
cores, blowing, method and apparatus using microwave energy, P (6) 217*f*.
corrosion by molten steel, (7) 251*i*.
crucibles, P (7) 253*c*.
high temperature, for processing radioactive wastes, platinum for, (5) 178*a*.
metal vaporization, with upstanding walls for confining and condensing vapor, P (4) 106*e*.
nonporous sintered, for combustion analyzer, P (2) 58*i*.
uniform, made by isostatic pressing, (6) 215*f*.
crystals, production by vapor transport reactions, (9) 328*f*.
cupola, (2) 54*j*.
improving operation, P (4) 106*i*.
repair using gunning material, (7) 251*f*.
deformation and fracture, (6) 214*i*.
dense bodies, production from carbides, borides, nitrides, silicides, oxides, and cermets by pressure sintering, (11) 373*c*.
Detrick construction, (5) 177*a*.
dolomite, metallurgical, quality improved by sintering with mill scale, (1) 12*h*.
dolomite, tar-bonded, and behavior in oxygen converters, (4) 105*d*.
dolomite brick, corrosion-resisting tar-bonded, service test, (7) 251*a*.
fired, corrosion by different basicity slags, (11) 372*h*.
tar-bonded, service test in electric furnace, (10) 342*f*.
dolomite clinker, corrosive effect of slag composition on, (11) 372*i*.
elastic modulus, at high temperatures, (4) 103*a*.
electrocast. See *Refractories, fused cast.*
electrofused materials, for precision casting molds, (6) 215*d*.

Refractories *(continued)*
European, for insulation of glassmelting furnaces, (9) 308*j*.
fiber-reinforced, P (9) 309*c*.
filaments, high strength, P (8) 279*h*.
firebox, prefabricated masonry, P (11) 375*a*.
firebrick, and brick, suitability of talc magnesite for insulating, (1) 13*g*.
corrosion by brown coal ash, (5) 176*j*.
contribution of TiO_2 to manufacture, (10) 340*i*.
firing temperature, variation with Fe_2O_3 content of mullite, B (10) 366*d*.
insulating, for construction of furnace sidewalls, and proper layout of metal fittings based on mechanics, (5) 176*i*.
insulating, larger units at Johns-Manville, (5) 177*d*.
pore texture: IV, influence of vacuum, during heating, (2) 56*i*.
pores in: III, effect of atmospheres, (11) 373*c*.
quality and production control, affected by occupational fatigue factors, (4) 104*i*.
semistabilized, for LD converter, service test, and ways and means for quality improvement, (7) 251*j*.
fireclay, after-expansion, (4) 102*j*.
and Al, effect in molten steel on dissociation of Zr, (4) 103*i*.
materials, technical development in: III, mechanism of synthesis of mullite in system kaolinite-aluminum fluoride, (4) 105*d*.
standards, (1) 13*f*.
firing and bloating in various atmospheres at increased pressures, apparatus for, (2) 54*h*.
foamed, P (1) 13*j*.
forehearth addition process for viscosity change, P (8) 277*j*.
foundry, radioisotopes for tagging, (2) 57*g*.
foundry cores, cleaning method and apparatus, P (10) 342*i*.
and molding sand composition, P (1) 14*a*.
and molds, liquid mixes for, and manufacture of, P (5) 178*i*.
furnace hole closures, molten material, P (1) 14*b*.
fused cast, for glass factory, (1) 12*d*.
fusion cast, impurities and gases in, (9) 308*i*.
glass-asbestos water-laid sheet, forming, P (7) 252*f*.
glass contact (zircon), P (7) 252*j*.
for glass furnace generators, (4) 105*f*.
in glass industry, introduction, (1) 8*c*.
for glassmelting furnaces, corrosion of, (1) 11*j*.
glass-pot material, physical properties, factors influencing, (2) 55*i*.
glass tank, advances, (1) 5*i*.
granular specialty mixes, by automat, (4) 105*a*.
graphite bodies, molded, and process, P (7) 252*i*.
graphite forms, grain-oriented pyrolytic, and vapor deposition method of making, P (4) 106*i*.
graphite matrix, extruded, containing coated particles, P (4) 106*f*.
graphite structures, compressed vermicular, preparation, P (7) 252*h*.
graphite structures, low density, production, P (4) 107*a*.
greenlite, new, by new process, (8) 279*a*.
gunning, hot, in open-hearth furnace, result and future problems, (2) 57*b*.
gunning repairs of walls and roofs of furnace and soaking pit, (2) 55*i*.
hearth, P (10) 342*d*.
hearth, electric furnace, ramming, (11) 373*g*.
hearth plate, diffusion furnace, P (2) 72*f*.
hot crushing strength, influence of furnace atmosphere, (6) 215*f*.
hot top, apparatus for lining, P (6) 217*f*.
for big-end-up ingot molds, P (11) 374*j*.
liners, apparatus for forming, P (7) 252*d*.
structure, P (4) 106*j*.
immersed in molten iron, corrosion and erosion test: II, deterioration in sample bricks; III, comparison of tested sample bricks with pig iron and bricks dropped together into cupola, (10) 342*d*.
installation and use, (1) 12*i*.
insulating. See also *Refractories, firebrick*. P (4) 106*b*.
manufacture, (1) 12*j*.
insulating bodies, elastic, of inorganic fiber material, P (11) 374*h*.
insulating brick, coated, for furnace construction, P (1) 14*b*.
and insulating composition, and elements for lining of metal casting molds incorporating, P (2) 58*h*.
insulating structural sheets, P (7) 252*j*.
insulation, high temperature furnace, installing method, P (6) 217*h*.
in iron and steel industry, changes in usage, (4) 103*i*.
in iron and steel industry of U.S., (2) 57*h*.
for iron and steelmaking, problems, (5) 177*d*.
Japanese, and foreign countries, used for iron- and steel-making, (11) 373*h*.
ladle, with bottom of graphite-containing fireclay brick, service test, (11) 374*c*.
and cover, P (1) 14*d*.
holding molten steel, effect of slag thickness on heat loss from, (1) 12*b*.
LD converter, changes in lining, and improvement on intermediate repair method, (7) 250*e*.

Refractories, ladle *(continued)*
85-ton, at Nadahama LD converter plant of Kobe Steel Works, Ltd., service tests, (7) 251*e*.
185-ton, at LD converter plant of Sakai Iron Works, operating condition, (7) 251*c*.
rammed vs bricked, (7) 250*h*.
roseki (pyrophyllite), trial use, (11) 374*d*.
for use in treatment of molten metal, P (4) 106*c*.
ladle brick, bloating, (9) 308*h*.
containing CrO, service tests, (11) 374*c*.
corundum-containing high SiO_2 and high Al_2O_3, service tests, (7) 251*b*.
erosion tests, observation by RI ^{45}Ca, (11) 373*d*.
high silica, corrosion test by induction furnace method, (7) 251*h*.
quality and shape, study at Muroran LD converter steel plant to improve, (11) 374*i*.
pore texture, change due to reheating, (11) 373*b*.
service tests in lining of electric furnace ladle, (7) 251*f*.
special roseki, service tests, (7) 251*c*.
steelmaking, erosion velocity, (7) 250*h*.
teeming, possibilities of improving quality, (10) 342*i*.
ladle construction, bottom pour, P (5) 178*b*.
ladle spout bricks, service tests, (7) 251*c*.
ladle stopper head assembly, P (11) 375*b*.
ladle stopper rods, composite sleeve for, P (10) 342*c*.
for LD converter, (7) 251*e*.
lime, properties, (8) 279*h*.
liner, anisotropic mold, for continuous casting of metals, P (5) 178*j*.
for crucibles, P (1) 14*e*.
graphite, for smoking pipe, P (5) 178*g*.
kiln, block supporting structure, P (4) 106*c*.
lining, for arc furnaces adapted to facilitate dismembering on completion of campaign, P (11) 375*b*.
basic, of copper smelting furnaces, $MgSO_4$ formation in, (10) 341*j*.
for blast furnaces, (1) 17*b*.
BOF, development at NKK Tsurumi plant, (4) 103*g*.
composite, for basic oxygen furnace, P (4) 106*b*.
cracking under influence of stresses and thermal shock, (4) 103*c*.
in induction furnace, P (1) 14*c*.
LD converter at Muroran Works of Fuji Iron and Steel Co., Ltd., advancement in, (7) 250*d*.
magnesite rotary, rate of wear, factors influencing: I, slag and brick compositions; II, laboratory study of used bricks; III, research methods of metallurgical operation and progress in refractories, (2) 55*a-f*.
for oxygen blowing basic steel making vessels, P (4) 106*d*.
rotary kiln, P (8) 286*f*.
of soaking pit furnace by prefabrication method, (7) 251*f*.
sulfite cellulose digesting vessels, acid-resistant plates for, (11) 372*g*.
for vessels for vacuum melting of steel, testing and suitability, (4) 105*d*.
wear, continuous measurement in steel furnaces with radioisotopes, (7) 250*h*.
low-loss ceramics, dielectric properties, transient effects of nuclear radiation at microwave frequencies, (9) 311*h*.
made by liquid-phase-extrusion hot-pressing, (5) 177*e*.
magnesia, fused and dead-burned, comparison, (4) 103*j*.
and fused zircon, granular electrically insulating material, P (10) 342*e*.
magnesia-chrome, and chrome-magnesia, in glass industry, (1) 8*e*.
and production, P (2) 58*i*.
-ZrO_2, fused cast, P (4) 107*h*.
magnesia brick, changes in microstructure and composition during firing and cooling, (7) 250*f*.
fired, corrosion by different basicity slags, (11) 372*h*.
fused-cast, used in walls of electric furnace, mechanism of wear in, (10) 341*c*.
high-fired, used in walls of electric furnace, (2) 56*b*.
high purity, properties after service in mixer lining, (2) 57*e*.
properties, effect of high-temperature firing, (11) 373*b*.
used in converter outlet, deterioriation, (10) 340*g*.
magnesia-chrome, and chrome-magnesia products, process, P (6) 218*i*.
magnesia-chrome, unfired and high-fired, results in open-hearth furnace roof, (2) 57*c*.
magnesia-chrome brick, direct-bonded, properties after service in open-hearth furnace roof and mechanism of wear, (2) 57*c*.
of Mg clinker, results with different MgO contents used in open-hearth furnace roof, (2) 57*b*.
wear in sintering zone of rotary cement kilns, (1) 13*d*.
magnesia clinker, electric furnace hearth rammed with, service test, (11) 373*i*.
magnesia clinker, purity, effect on durability of basic brick for open-hearth furnace roof, (11) 373*d*.

Refractories *(continued)*
magnesia-dolomite clinker, sintering properties, (7) 251*g*.
magnesite. See also *Refractories, chrome-magnesite*.
and chrome-magnesite, (4) 104*h*.
and chrome-magnesite bricks, from Indian magnesites, preparation and properties, (5) 190*g*.
and magnesite-chromite brick, hot modulus of rupture at high temperatures, (4) 104*c*.
magnesite brick, behavior at high temperatures, (4) 103*d*.
erosion and impregnation, (4) 104*a*.
high and low iron containing, technological investigations, thermal expansion, and life tests, (9) 309*c*.
high-temperature thermal expansion, (1) 12*e*.
phosphate-impregnated, P (9) 309*b*.
magnesite-chrome and chrome-magnesite bricks, Indian, distribution and characteristics, (2) 55*b*.
magnesite-chrome, fine-grained, (6) 215*b*.
magnesite-chromite brick, direct bonded, comparison test with unfired brick in open-hearth furnace roof, (11) 372*h*.
magnesite-chromite brick, high-fired, corrosion by different basicity slags, (11) 372*h*.
magnesium-chromium brick, unfired, of high-purity MgO clinker, use in furnace roof, (11) 374*c*.
masonries, protection, method and device, P (8) 279*f*.
materials, activation analysis applied to, (5) 187*a*.
basic, slip casting, P (4) 107*f*.
corrosion by glass melts, (9) 305*a*.
heat-treating at high temperatures, method and means, P (9) 314*h*.
high pressure hot-pressing, (6) 215*c*.
metal based, etching uniformly along surface, P (4) 106*h*.
periclase-lime-chrome, (4) 105*a*.
plant for calcining, P (4) 107*j*.
prefiring, P (5) 179*a*.
resistance to cold crushing, (6) 216*g*.
for severe conditions, electrofused, (4) 104*a*.
silicon nitride as, (7) 251*g*.
stress/strain behavior at high temperatures, (10) 342*g*.
suitability determined by high temperature cross bending and compressive strengths, (4) 104*b*.
mechanical properties, at working temperatures, (5) 178*f*.
metal compositions, nitride, P (2) 59*h*.
metal compounds, joined by hot-pressing, (6) 215*j*.
metal dioxides, geometry, (4) 137*f*.
metallic (boride) compositions, P (10) 342*i*.
metallurgical degasser vessels, P (6) 217*e*.
metals, and alloys, treating, working, and bonding, P (4) 107*g*.
articles, P (8) 275*g*.
articles, with oxidation-resistant coating, P (8) 275*i*.
Ce layers on, field-electron-microscopy studies; work function change, (4) 136*g*.
coated, (1) 4*d*.
coating, P (4) 94*e*.
coating with metal modified oxides, P (4) 93*h*.
coating solid particles with, P (8) 279*b*.
coating by vacuum pack and vacuum slip-pack process, (7) 246*a*.
vapor pressures at high temperatures, determination by shock-tube method, (5) 188*c*.
mineral powder, nonabsorbent hydrophobic, P (7) 252*j*.
molds. See *Molds*.
for molten-iron-tapping branch spout of blast furnace, service test, (7) 251*i*.
monocarbides, mononitrides, and monoxides, cubic, cohesion in, (5) 192*j*.
monolithic, P (6) 218*e*.
mortar, graphite bearing high MgO, P (8) 279*b*.
joints, factors affecting slag penetration of, (1) 12*d*.
property changes caused by molten iron and effects of atmosphere, (11) 373*g*.
mullite, formation from sillimanite group minerals, (10) 341*g*.
in glass industry, (1) 8*e*.
mechanism of synthesis, in system kaolinite-aluminum fluoride, (4) 105*d*.
with 70–72% alumina, corrosion by ash of fuel oil, (4) 103*b*.
nozzles, fuel, for high temperature furnace, and method of operating, P (11) 381*i*.
high-silica, performance, effect of tar saturation, (2) 55*h*.
Indian and foreign, for pouring steel, laboratory study, (11) 373*g*.
with interior guide, P (4) 100*d*.
nuclear rocket engine, thermocouple cements for, (10) 342*a*.
seating blocks, containing $SiZr_4$ and C-SiC-clay, service test, (11) 373*j*.
seating blocks for LD converter ladle, service tests, (11) 374*a*.
service tests, (11) 372*g*.
spalling test, (2) 57*j*.
and stopper assemblies for teeming liquid metal, P (4) 107*i*.
tundish, construction, P (9) 309*f*.

Refractories, nozzles *(continued)*
zircon-containing, installed on 50-ton ladle, service tests, (11) 374*d*.
oxides, chemical reactions, sintering, and collective recrystallization, role of surface phenomena in kinetics of, (7) 268*h*.
in industry, (2) 56*f*.
material, for closing tube, P (6) 221*a*.
properties, effect of atmosphere, (1) 12*a*.
panels, method and material for making joints between, P (6) 218*a*.
periclase-silicate mixtures, deformation in bend at high temperatures, effect of composition and microstructure, (6) 215*b*.
plastic chrome, characteristics, relations with conditions for use, (5) 178*e*.
polycrystalline transparent, properties and application, (2) 56*h*.
potential performance in service, modulus of rupture as index of, (10) 341*e*.
pouring, slurry, means, and mold, P (11) 375*d*.
pouring pit, pore texture: I, change in pore texture of ladle brick due to reheating, (11) 373*b*.
pouring spout, for molten metal, P (11) 374*e*, 375*d*.
products, behavior in CO atmosphere, (10) 340*f*.
products, high quality acid resistant, (1) 12*d*.
properties, of Florida kyanite-sillimanite concentrate, (8) 279*c*.
protecting and insulating covering for furnace support members, P (9) 309*d*.
pump, controllable flow, for molten metal, P (11) 374*g*.
ramming composition, P (4) 107*i*.
ramming material for electric furnace cover, service test, (7) 251*i*.
raw materials, See *Raw materials*.
reaction with SF_6 at high temperatures, (1) 11*i*.
refractoriness under load, of MgO clinker, testing method, (11) 374*c*.
test conducted on magnesia clinker samples, (10) 342*c*; cooperative studies among areas of Chuugoku, Shikoku, and Tokai, Japan, (10) 342*d*.
test, problems, (10) 342*g*.
relaxation behavior, at high temperature, (4) 104*i*.
roof, construction, P (10) 342*d*.
dome-shaped electric furnace, construction, P (9) 309*c*.
of one-way top-fired soaking pit of recuperative type furnace, construction with unshaped refractories, (5) 176*i*.
open-hearth furnace, high-fired basic brick used in, (2) 56*a*.
steelmaking arc furnace, constructed of unshaped, refractories, performance and construction, (7) 251*c*.
runner brick, placed in radial mold gutters, service test, (11) 373*j*.
runner brick: V, protection from spalling and erosion, (2) 57*e*.
sand-lime brick, hardened with water vapor, phase formation and structural behavior, (11) 373*i*.
shaped, from dolomite, P (7) 252*b*.
shapes, P (1) 14*g*.
shapes, coated with organic material, P (10) 343*b*.
silica, expanded insulation material, P (4) 106*f*.
in glass industry, (1) 8*d*.
high, intermediate furnace barrier, P (4) 106*b*.
silica brick, for coking plants, (10) 341*a*.
impregnated with Cr_2O_3 used in electric furnace cover, (7) 251*f*.
unfired and fired, development of strength with temperature, (5) 177*a*.
silica insulating, (1) 12*a*.
siliceous and silicoalumina, structural changes in metallurgy, (2) 58*b*.
SiC, (1) 13*c*.
SiC tubes in fuel fired furnaces, (7) 251*d*.
sintered friction material, P (7) 253*c*.
sintering, in presence of vitreous phase, (6) 211*e*.
slag. See *Slags*.
sleeves, high-silica, having low refractoriness, use test on, (2) 58*i*.
inorganic fiber riser, P (10) 342*f*.
spalling, prevention by raising temperature gradually, (2) 57*b*.
spalling resistance, (2) 57*i*.
spalling test, (2) 57*j*; 58*a*.
spalling, of basic, (2) 58*g*.
spalling test for casting pit refractories, (2) 57*j*.
standardization problems, (1) 12*i*.
standardization and testing, (1) 13*j*.
stopper, for ladle with air-cooled head, P (4) 108*a*.
stopper brick screw parts, stress analysis by photoelasticity, (7) 251*h*.
stopper head, for large capacity open-hearth furnace, improvement of teeming practice by changing shape of, (2) 56*i*.
spalling test, (2) 57*j*; 58*a*.
tar impregnated fused silica, P (6) 218*g*.
top part, causes of breakdowns in, used at high temperature for long periods, (2) 56*i*.
for use at high temperature for long periods, (11) 372*h*.
structural, unusual ablative material, P (9) 309*f*.

Refractories *(continued)*
structures, containing shaped voids, P (6) 218*b*.
structures, high temperature resistant, P (6) 218*d*.
study by X-ray microanalyzer, (7) 250*e*.
substrate, for producing radiation filters, P (4) 107*f*.
suction box cover, P (7) 253*b*.
surfaces, emissive coating for, P (2) 58*d*.
tamping materials, properties, testing, (11) 381*b*.
tapping spout, electric furnace, constructed by ramming, test results, (7) 251*j*.
technical, fracture strains, (2) 55*g*.
textures, studies by scanning electron microscope, (4) 105*b*.
thermal conductivity, rapid determination by hot-wire method, (11) 373*g*.
thermochemical resistance, to slag effect, (10) 340*g*.
tile assembly for radiant gas burners, P (7) 253*b*.
transport processes in, spalling of basic, (2) 58*g*.
ultra-, carbides, nitrides, and borides, (1) 13*b*.
used in vacuum degassing process for steel, (7) 252*a*.
unshaped, in use at Chiba Iron Works of Kawasaki Steel Corp., present condition and problems, (7) 251*d*.
wall, blast furnace, drying study, (2) 58*d*.
blast furnace stock line, and construction, P (4) 106*a*.
electric furnace, high-fired magnesia brick used in, (2) 56*b*.
heat-resistant, P (10) 342*e*.
heating furnace, tensile construction, (11) 381*i*.
repairing, P (4) 107*c*.
ware, coating with magnesia, P (9) 309*g*.
zircon, in tuyere of ladle, mechanism of wear, (11) 373*h*.
zircon and zircon-chromium oxide, in glass industry, (1) 8*e*.
$ZrSiO_2$-Al_2O_3-SiO_2 brick, used for 80-ton open-hearth furnace ladle, (11) 374*b*.

Refractories industry, in America, survey and analysis, (5) 178*d*.
Canadian, specialties, (4) 105*j*.
Corhart, isostatic forming of refractories, (6) 214*j*.
Globe, automated brick plant, (4) 104*c*.
Kaiser, growth strategy, (6) 216*b*.
Kinader (European), automates brick plant, (4) 104*g*.
test methods and specifications, (6) 216*j*.

Refrigeration, cryogenic, for crystal X-ray diffraction studies, P (4) 121*f*.

Relaxation, anisotropic nuclear spin, of protons in hydrated vermiculite crystals, (5) 199*c*.
behavior, of refractories, (4) 104*i*.
dielectric, in evaporated CaF_2 films, (8) 281*b*.
dielectric, in $SrTiO_3$ solid solutions containing La_2O_3, (9) 320*a*.
double layer, in liquid electrolytes: I, theory of space charge polarization, (9) 320*g*.
of kaolinite layer structure by dehydroxylation, (5) 196*b*.
magnetic, of magnetite, (1) 26*c*.
magnetic, Richter-type, in $Mn_xFe_{3-x}O_{4+y}$, (2) 75*d*.
of Mn^{2+} and Fe^{2+} ions in MgO, (4) 153*i*.
mechanical, in mixed-alkali silicate glasses: I, results, (6) 210*b*.
nuclear magnetic, studies in internal rotations and phase transitions in borohydrides of Li, Na, and K, (11) 386*j*.
paramagnetic, of Mo^{5+} in TiO_2, temperature dependence of, (4) 159*c*.
phenomena in Moessbauer spectra of magnetically ordered erbium ions in $ErFeO_3$, (2) 82*c*.
phonon-induced, in ruby, (2) 82*j*.
processes, of Eu^{2+} in Y_2O_3 and YVO_4 using pulsed cathode-ray excitation, (8) 297*i*.
in single-crystal UO_2, (8) 297*j*.
in supercooled nitrate melts, (4) 153*j*.
proton, in liquids sorbed on Al_2O_3, (5) 199*f*.
spin, in $CaFe_2O_4$, Moessbauer effect study, (2) 80*c*.
spin-lattice, of ground state of Fe^{2+} in Al_2O_3, (6) 232*j*.
spin-magnon, in Tb-doped YIG, (4) 155*g*.
times spectrum, in GeO_2 glass, (1) 9*b*.
vibrational, in tetrachlorides of C, Si, Ge, Sn, and Ti, (5) 203*b*.

Research, and development, in industries, money continues pouring into, (9) 333*d*.
in smaller company, (1) 40*f*.
on special ceramics: Vol. 4, B (10) 366*g*.

Resins, furan, industrial applications, (5) 176*g*.
silicone, simplify fused silica processing, (2) 57*f*.

Resistance, electrical. See also *Conductivity, electrical; Electrical properties*.
controllable, P (4) 112*c*.
high pressure, of TiO_2, (5) 194*j*.
magneto-, weak-field, in SnO_2 single crystals, (10) 363*i*.
potential and permeability of membranes, (8) 298*e*.
stabilizing in semiconductor manufacture, P (8) 283*e*.
of thin germanium and silicon sample in high electric fields, effect of space-charge-region

Resistance *(continued)*
surface conductivity on change of, (5) 180*f*.
of β-US_2, single crystals, (4) 150*j*.

Resistivity, electric, of slurries with conducting liquid and insulating solid phase, (2) 76*i*.
electrical, anisotropic, of single VO_2 crystals, (10) 353*c*.
of CrO_3, sintered, (1) 28*d*.
of glass, simultaneous measurements with electrical viscosity at temperatures in melting and working range, (5) 173*b*.
of La-doped $BaTiO_3$, effect of oxide impurities, (2) 62*d*.
of SiC heating rods, dependence on Al_2O_3 and Fe_2O_3 content of SiO_2 used, (4) 103*d*.
of sintered composite carbon black kaolin materials: IX, effects of firing time, firing atmosphere, and forming process on; X, effects of carbon materials on temperature dependence of; XI, resistivity-temperature dependence of compositions containing excess silica, (4) 134*g*.
for Th-C system, (4) 134*e*.
high, group III-V compounds and alloys doped with iron from iron-arsenide source, P (5) 183*f*.
photomagnetoresistance, of $SrTiO_3$, (2) 81*h*.
quenched-in, in SAP, (1) 17*j*.
regions, high, in silicon, selective gold doping for, P (7) 257*j*.
of AgO, (5) 180*j*.
of sintered composite carbon black-kaolin materials: IX, effects of firing time, firing atmosphere, and forming processes on resistivity; X, effects of carbon materials on temperature dependence of resistivity; XI, resistivity-temperature dependence of compositions containing excess silica, (5) 181*b*.
surface, of Al_2O_3 ceramics, factors affecting, (2) 62*b*.
volume, of insulating ceramics, measurement at high temperature, problems, (2) 70*f*.

Resistors, electrical, P (2) 64*b*.
carbon composition, P (4) 112*i*.
cermet, composition and manufacture, P (4) 112*h*.
continuously evaporated, structure, (8) 281*g*.
trimming, P (11) 377*i*.
composition for fired-on electrically conductive contacts to, P (4) 112*j*.
elements, curing continuously, P (11) 377*h*.
film, P (2) 65*g*; P (7) 256*e*.
filmed, apparatus for helixing and sorting, P (8) 282*b*.
galvanomagnetic, with semiconductor top layer, P (4) 113*h*.
high strength, P (7) 256*a*.
high voltage low temperature, P (4) 113*b*.
indium oxide composition, method, and article, P (4) 113*c*.
isolated, for integrated circuit, P (6) 221*h*.
making by recrystallization, P (8) 283*a*.
printed circuit, fabrication technique, P (5) 185*d*.
pyrolytic graphite, P (4) 116*d*.
stabilized metal film, P (10) 345*g*.
tailoring machine, P (5) 185*f*.
thermistor, P (4) 117*d*; P (6) 222*a*; P (8) 283*j*.
composition, containing vanadium dioxide, P (1) 19*e*.
compositions, and thermistors made from, P (2) 66*i*.
device, P (6) 224*e*.
low noise assembly, and method, P (9) 312*e*.
theory and special applications, (2) 63*i*.
thin-film, P (11) 379*a*.
adjusting, P (6) 222*b*.
adjustment, P (11) 379*a*.
electric field tailoring, P (4) 112*c*.
unit, P (7) 257*i*.
utilizing group III or VB metal, P (4) 116*h*.
vitreous enamel composition, P (7) 246*i*.

Resonance, acoustic paramagnetic, of Ni^{2+} in potassium magnesium fluoride, (1) 24*h*.
acoustic paramagnetic, spectrum of Cr^{2+} in MgO, (1) 24*h*.
deuteron and proton magnetic, study of partly deuterated crystals: I, potassium oxalate monohydrate, (8) 290*f*.
electron cyclotron, in InSb, quantum effects in, (11) 386*j*.
electron nuclear double, of *F* center in CaF_2, (1) 28*i*.
electron nuclear double, spin Hamiltonian of $^{51}V^{2+}$ in MgO as derived from, (9) 329*g*.
electron paramagnetic, of Cu^{2+} in KH_2PO_4, (2) 76*c*.
detection of triple Li ion centers in Li-diffused Mn-doped GaP crystals, (10) 353*f*.
for determination of parameters for Gd^{3+} in YVO_4 and YPO_4, (8) 290*j*.
of Er^{3+} and Yb^{3+} in II-VI compounds, host crystal effects on, (4) 138*i*.
of ions of iron transition group in fluoroberyllate glasses, (8) 276*f*.
of irradiated silicate glasses, (8) 277*a*.
of lanthanide ions and Cr^{3+} in $LiNbO_3$ crystals, (2) 76*c*.
observation of Eu^{3+} to Eu^{2+} transformation in CdF$_2$:Eu, (2) 77*a*.
study of chemistry of Mn^{2+} during formation of fluorapatite, (4) 135*b*.
for study of sitalls in system Li_2O-Al_2O_3-SiO_2, (7) 269*g*.
studies of VO^{2+} in KNO_3 and $CsNO_3$ single crystals, (8) 291*g*.

Resonance, electron paramagnetic *(continued)*
of VO^{3+} in sphene and apophyllite and Mn^{3+} in tremolite, apophyllite, and scheelite, (1) 28*i*.
zero-field, of Fe^{3+} in quartz, (11) 388*f*.
electron spin, of α-chromia-alumina solid solutions, (8) 291*h*.
of CrO_4^{3-} in chlorospodiosite, Ca_5PO_4Cl, (4) 135*j*.
conduction-, in degenerate indium sesquioxide, (4) 129*b*.
for determination of carbon fiber structures, (10) 351*j*.
for determination of ground-state splitting of trivalent Gd and Cm in $ZrSiO_4$, $HfSiO_4$, and $ThSiO_4$, (11) 385*c*.
of Eu^{2+} in cubic and tetragonal phases of $BaTiO_3$, (2) 76*d*.
of Gd^{3+} in orthorhombic and rhombohedral of phases of $BaTiO_3$, (2) 76*d*.
investigation of photochromic sodalites, (4) 135*a*.
of Fe^{3+} in $SrTiO_3$ with reference to 110°K phase transition, (1) 29*a*.
of Mn^{3+} in reduced $BaTiO_3$ single crystals, (1) 29*c*.
of Mn^{3+} in α-$Sr_2P_2O_7$, (9) 321*i*.
of Mn(II) ions, for observing selective exchange of cation sites in zeolites, (9) 329*d*.
observation of ^{47}Ti and ^{49}Ti *hf* structure in *F*-center line in $BaTiO_3$, (1) 33*f*.
of photosensitive Fe^{2+} centers in CdSe, (1) 29*e*.
of rare-earth ions in CeO_2:Yb^{3+} and Er^{3+}, (2) 76*g*.
at 77°K, of γ-irradiated single crystals of ice —identification of hydroxyl radical and its trapping site, (5) 194*f*.
of sodium hexafluoroantimonate, X-ray irradiated polycrystalline and single-crystal, (4) 135*b*.
studies of gamma-irradiated glasses containing lead, (4) 95*h*.
studies of hydroxyl radical in γ-irradiated ice, (5) 194*d*.
studies of isomorphous series Na(Sc,Fe)-TiO_4, (11) 385*g*.
studies of lithium borate glasses and compounds gamma-irradiated at 77°K, evidence for new interpretation of trapped-hole centers associated with boron, (2) 48*i*.
studies, of low-temperature radiation effects in lead halide crystals, (8) 291*i*.
studies of radiation-induced niobium centers in Nb_2O_5-Na_2O-SiO_2 glasses, (2) 48*i*.
studies, of trapped electron dating, (10) 363*a*.
study, of Mo^{3+} in phosphate glass, (1) 7*b*.
study on ultraviolet light irradiated benzene adsorbed on SiO_2 gel and Al_2O_3, (8) 291*i*.
of thortveitite, (4) 135*b*.
of VOF_5^{3-} ion, (10) 353*g*.
ferromagnetic, in planar ferrite, Zn_2Y, magnon analysis, (8) 294*d*.
ferromagnetic, in single-crystal $BaO{\cdot}6Fe_2O_3$, (9) 321*d*.
impurity mode, for Er-doped MnF_2, (4) 153*c*.
line width, two-magnon ferrimagnetic, of hexagonal ferrite Zn_2Y, (2) 84*d*.
magnetic, of $MnCr_2O_4$, frequency, (2) 77*i*.
microwave-optical double, using circularly polarized light—spectrum of Yb^{3+} in $CaWO_4$, (5) 197*d*.
nuclear, for measuring thermal stress, apparatus and method, P (1) 22*i*.
nuclear magnetic, ^{11}B, in polycrystalline Ca metaborate, (2) 46*j*.
determination of metal ion distribution in manganese ferrite prepared from aqueous solution, (5) 197*d*.
doublet splitting, in aqueous montmorillonite gels, (11) 386*i*.
of ^{57}Fe in single-crystal hematite, (4) 147*a*.
^{55}Mn, of Mn^{2+} ions located at B-sites in Mn ferrite single crystals, (1) 32*j*.
in MnO, α-MnS, and α-MnSe paramagnetic states, (4) 147*a*.
measurements of distortion effects around substitutional monovalent ions in alkali halide crystals (8) 295*g*.
measurements of field gradient at Br nuclei surrounding substantial Cl ion in KBr crystal, (4) 146*f*.
of ^{39}K in KH_2PO_4 by double resonance method, (8) 295*f*.
of ^{39}K in KH_2PO_4 in ferroelectric phase, (2) 81*b*.
study of $BaFPO_3$, (10) 357*g*.
study of diffusion in lithium borate glasses, (1) 8*a*.
study of ferroelectric $LiNbO_3$ and $LiTaO_3$, (5) 197*f*.
study of Li_3Sb, Na_3Sb, and Na_3As powders, (6) 235*j*.
study of thallium borate glasses, (11) 370*i*.
in thallium borate glasses: I, ^{205}Tl chemical shift, (5) 173*f*.
nuclear quadrupole, in cuprous oxide, temperature dependence of, (4) 159*b*.
nuclear quadrupole, frequency of ^{79}Br in $NaBrO_3$ and $KBrO_3$, (8) 299*j*.
paramagnetic, of Cr^{3+} in $EuAlO_3$, (11) 386*b*.
of iron in glass, (10) 338*f*.
of Mn(II)-doped ZnO single crystals, (9) 325*a*.

Resonance, paramagnetic *(continued)*
of *N* center in CaO, (11) 386*c*.
of room-temperature-stable *V*-type centers in γ-irradiated alkali halide-boron oxide glasses, (6) 210*d*.
propagation and dimensional, of helicon-like waves in powdered semiconductors and semimetals, (11) 386*h*.
proton magnetic, in borate glasses, (1) 8*a*.
studies of adsorbed water on MgO, (1) 35*a*.
study of lithium trihydrogen selenite, (4) 151*d*.
in vermiculite single crystal, (6) 236*b*.
spin-, properties of scheelites: I, vanadium in $CaWO_4$, (4) 155*i*.
ultrasonic paramagnetic, in MgO:Fe^{2+}, temperature dependence of, (4) 159*d*.
zero-field, of Gd^{3+} in YVO_4 and YPO_4, (8) 301*a*.
Resonators, piezoelectric, P (1) 18*j*; P (5) 184*h*.
piezoelectric, neutron diffraction on, (9) 325*d*.
piezoelectric ceramic, P (6) 223*d*.
quartz, second overtone DT-cut, P (2) 66*a*.
Rhenium, oxide tetrafluoride, crystal structure, (8) 292*h*.
ReS_2, free energy of formation, (4) 136*g*.
surface, formation of positive and negative ions on, (8) 292*i*.
Rheology, behavior of sand vibrating in rotary viscometer, (5) 188*b*.
examination of ceramic casting slips, (8) 280*c*.
high temperature, of ceramic materials: I, drawing of flow curves; II, temperature dependence of internal friction and of modulus of elasticity of basic refractories, (2) 78*i*; III, relaxation behavior of refractories, (4) 104*i*.
of kaolinite suspensions, (9) 329*a*.
review, (4) 118*b*.
Rhodium, chlorination, and thermal transformations of trichloride, (8) 289*j*.
Rh_2Si_4, crystal structure, (10) 351*b*.
Rh_4Si_5, crystal structure, and relation to other members of MnP structure family, (10) 351*c*.
Robots, (7) 259*a*.
programmed, use in glass handling operations, (4) 98*b*.
Rock wool. See *Mineral wool.*
Rockets. See *Spacecraft.*
Rocks. See also *Phosphates; Silicates.*
analysis, using multichannel emission spectrometer, (1) 20*i*.
anorthosite kindred, petrogenetic model for evolution of, (8) 296*b*.
blue schist facies metamorphic, coexisting amphiboles from, (7) 264*h*.
breaking method and apparatus, P (11) 382*j*.
carbonate, codification, associated with low temperature hydrothermal ore deposits, (1) 23*j*.
carbonate, heat conductivity, (7) 266*c*.
common, exposure charts for radiography of, (2) 69*e*.
deep-seated, in Australian shield, geochemical investigations, (4) 137*d*.
essential characteristics, and requirements of apparatus for disintegrating limestone by electromagnetic-thermal means, (6) 224*g*.
evaporites, selected bibliography, (9) 316*j*.
fragments, experimental study, (6) 228*j*.
granitic, of central Sierra Nevada batholith, California, hornblendes from, (4) 138*h*.
masses, measurement of movement in, P (4) 124*e*.
nepheline syenite, plant and operation, in Canada, (5) 190*f*.
Paleozoic, of eastern North Dakota, cement-rock possibilities in, (9) 316*g*.
rhyolites, calc-alkalic, retention of alkalis during crystallization and hydration, (10) 359*h*.
sedimentary, quantitative mineralogical analysis of, comparison of two methods, (1) 20*j*.
sedimentary, and sediments, quantification in clay mineral studies of, (8) 285*a*.
silicate, microanalysis: V, spectrophotometric determination of Al_2O_3, (4) 120*b*.
silicate, rapid determination of fluoride in, (4) 121*b*.
source of tektites, (5) 198*b*.
strength determination, (4) 123*j*.
textures, wide field technique for viewing, (9) 315*g*.
topaz-sillimanite and kyanite bearing, from Tanzania, (1) 23*e*.
volcanic series, chemical variation within and between, (1) 25*h*.
Roughness. See *Surface.*
Rubidium, in biotite, sanidine, and glass in Tuscany ignimbrites, Italy, (9) 329*d*.
borates, of varying composition, infrared spectra, (4) 140*h*.
borohydride, (7) 264*b*.
hydroxide and RbOD, microwave spectra, (10) 361*d*.
$RbFeF_3$, dislocations in, (7) 265*e*.
magnetic and structural transformations in, (4) 143*h*.
phase transformations and magnetic domains in, (7) 267*j*.
transparent, magneto-optical properties, (4) 143*c*.
$RbMnF_3$, absorption spectra, fine structure in, (4) 136*h*.
$RbNiF_3$, structure and magnetic properties, effect of pressure, (7) 265*j*.

Rubidium *(continued)*
$RbAg_4I_5$, relation of structure and ionic mobility in, (5) 199*b*.
superoxides, heats of formation and lattice energies, (1) 39*f*.
systems. See *Systems.*
trizirconate and trihafnate, polymorphic modifications, properties, (4) 151*g*.
Ruby. See also *Lasers; Masers.*
alignment of Cr^{3+} in, (1) 25*e*.
crystal field, (10) 351*h*.
crystals, electrical conductivity, (10) 352*c*.
$\bar{E}(^2E)$ level, ground-state spin memory in, in optical pumping via bands, (2) 77*c*.
electric effect in, (9) 320*h*.
energy transport mechanisms in, (11) 386*a*.
epitaxially coating, with doped Al_2O_3, P (9) 312*g*.
magnetic circular dichroism in, (8) 294*j*.
R, *R'* and *B* absorption line widths and phonon-induced relaxation in, (2) 82*j*.
single crystals, wear along plane close to basal plane, (6) 239*c*.
single crystals, wear along plane slightly inclined to basal plane, (4) 164*a*.
vibronic transitions in, (1) 40*c*.
Rupture, modulus, of BeO effect of strain rate, environment, and surface condition, (4) 133*i*.
modulus, of BeO, as function of density and grain size, (2) 81*c*.
of high-alumina refractories at elevated temperatures, (6) 216*d*.
hot, at high temperatures of magnesite and magnesite-chromite brick, (4) 104*c*.
as index of potential refractory performance in service, (10) 341*c*.
of sintered Al_2O_3 bodies, (2) 56*j*.
Rust, preventives, combination drawing compounds and, mill applied, (8) 275*a*.
Ruthenium, dioxide, and its hydrate, magnetic and other studies, (5) 196*c*.
separation by LiF sorption technique, P (11) 383*a*.
solubility, in silicate and phosphate glasses, (10) 338*i*.
tetroxide, ionization and dissociation, (2) 79*i*.
volatilization from glass, solubility dependence, (10) 338*h*.
Rutile. See also *Titanium, dioxide.*
anisotropy of diffusion in, (10) 349*j*.
defect structure, (4) 146*i*.
electroabsorption in, (2) 76*b*.
flux-grown crystals, dielectric measurements on without contacting electrodes, (9) 310*g*.
mineral, Zr in, determination with Alizarin Red S, (6) 226*c*.
reduced, high frequency conductivity, (2) 78*c*.
-related dioxides, and $La_4Re_6O_{19}$, metal-metal bonding in, (6) 235*d*.
single crystals, time-dependent electrical conduction in, (2) 84*a*.
-solution interface, adsorption at: I, thermodynamic and experimental study, (5) 191*f*.
structure TiO_{2-x}, NbO_{2-x}, and $Ti_{0.5}Nb_{0.5}O_{2\pm x}$, thermodynamic study of dilute solutions of defects in, (5) 201*g*.
surface, kinetics of desorption of water from, (1) 31*d*.
surfaces, bare and silica-coated, heats of immersion and water sorption studies on, (1) 30*d*.
thermally stimulated currents and luminescence in, (6) 239*g*.
TiO_{2-x}, nonstoichiometric, defect structure, (4) 156*g*.

Safety. See also *Health.*
labor activities, in fine ceramics industry, aspects, (4) 164*h*.
Salts, alkali metal, separation, P (4) 124*f*.
basic, and oxides, formation and reactivity: I, basic Mg chlorides and sulfates; II, radioisotope studies of calcareous materials, (10) 353*j*.
effects in reduction of inorganic anions at dropping mercury electrode, (10) 360*a*.
fused, friction constants for, (8) 292*c*.
inorganic single crystals from reactions in, (8) 293*d*.
review, (1) 31*a*.
short-range order in: I, coordination states of Ni(II) in molten $ZnCl_2$-KCl mixtures, (4) 154*i*.
viscosity, effect of internal coulomb field on, (11) 384*f*.
heavier, oxides and halides, infrared absorption frequency and characteristic Debye temperature of, (2) 79*a*.
inorganic, and combinations, influence on hardening kinetics of portland cement, (2) 44*e*.
inorganic nitrite, luminescence, (5) 196*b*.
magnetic, specific heats at low temperatures, measurements, (2) 80*j*.
molten, binary mixtures, nonideality and association in, (9) 325*h*.
complex formation in—association constants of Ag chlorocomplexes in KNO_3 + $Ba(NO_3)_2$ and comparison with quasi-lattice theory, (9) 318*d*.
conformal solution theory, (4) 129*e*.
ion-exchange equilibria with glass, (5) 172*j*.
ion exchange with glass, thermodynamic aspects, (5) 173*h*.
polarography in, (4) 150*d*.
segregation of impurities in, induced by

Salts, molten *(continued)*
cellular convection, and effect on crystal growth, (7) 268*j*.
significant-structure theory applied to, (6) 237*e*.
transport in, under pressure: I, glass-forming nitrate melts, (10) 338*c*.
vibrational spectra: V, infrared and Raman spectra of molten sulfates, (10) 363*i*.
Vol. I, electrical conductance, density, and viscosity data, (7) 262*f*; B (10) 366*f*.
organic, effect on gypsum plaster setting: III, citrates, (2) 44*j*.
silver clathrate, metallic conductivity and superconductivity in, (2) 80*b*.
NaCl. See *Sodium, chloride.*
solutions, common aqueous, liquid-liquid immiscibility in, at low temperatures, (10) 356*i*.
sulfo-, mineral, studies: XII, nuffieldite, new species, (1) 38*a*.
systems, fused, high pressure studies on, activation volumes for electrical conductance of fused alkali-metal nitrates, (8) 293*b*.
systems, molten, atlas of miscibility gaps in, B (8) 301*j*.
tetrafluoroborate, ion motion in: I, NH_4BF_4 and ND_4BF_4, (4) 141*c*.
Samarium, borides, tetraboride-hexaboride conversion, (2) 82*g*.
dicarbide, vaporization, Knudsen cell studies of, (6) 234*e*.
mono- and difluorides, stabilities, mass spectrometric studies at high temperatures, (5) 196*e*.
oxide, activation of glasses in system Na_2O-B_2O_3 by, (2) 51*d*.
oxide, structural stabilization with WO_3, (8) 298*c*.
Sm^{2+}, fluorescence spectra and lifetimes, in host lattices, thermal dependence, (4) 160*d*.
Sampling, device, metal, P (10) 342*i*.
pulverulent material, method and means, P (8) 286*a*.
Sands, analysis, with inexpensive recording settling tube, (11) 380*f*.
black concentrates, (1) 23*c*.
and clay, recovery from ore, P (5) 191*c*.
decomposition, by formaldehyde-volatilization method, (5) 187*g*.
foundry, apparatus for milling, P (5) 178*a*.
characteristics, effect of clay cation exchange, (10) 341*a*.
testing, P (11) 381*c*.
molding, P (8) 279*i*.
molding compositions, electrical conductivity test method for determining active clay content in, P (4) 121*f*.
molding-coring, fluidization mechanism, (10) 341*i*.
molding-coring, for mechanical engineering applications, (10) 341*g*.
quartz, behavior in mixture with lime under hydrothermal conditions, (1) 2*c*.
and sandy gravels, compressibility, (5) 189*j*.
shape factor, determination, (5) 190*b*.
standard, for testing of cement, specification for, (4) 92*h*.
strength criterion for, (5) 190*a*.
vibrating, in rotary viscometer, rheological behavior, (5) 188*b*.
waterless molding, P (6) 218*i*.
Sandstones, aragonite-cemented, from Outer Continental Shelf off Delaware Bay, (8) 286*g*.
Cheyenne, attrition scrubbing and flotation beneficiation, (9) 316*e*.
clayey, heat conductivity, (7) 266*c*.
fracture mechanism in, experimental study, B (6) 241*c*.
Grimsby (Lower Silurian), of Ontario and New York, petrology, (11) 386*d*.
petrology, evidence from luminescence petrography, (1) 36*i*.
and siltstones, ultrasonic disaggregations, (8) 286*b*.
Upper Jurassic-Lower Cretaceous Morrison and Kootenai Formations, southwest Montana, stratigraphic and petrographic analysis, (11) 387*f*.
Sanidine. See *Feldspar.*
Sanitary ware, bathtubs, cast iron, enameling, suggestions for partial mechanization, (5) 171*c*.
bathtubs, dry process enameling of, (2) 45*i*.
enamels for, corrosion, (10) 336*f*.
European, marketing problems, (4) 108*j*.
hydrostatic pressing, (11) 375*f*.
industry, Crane production, (2) 59*j*.
with low porosity, (11) 375*i*.
production, speeded by smooth flow pattern at American Standard, (2) 60*e*.
toilet bowl construction, P (4) 109*c*.
toilet bowls, syphon-jet type, casting, P (11) 376*a*.
vitreous china, (4) 109*a*.
Sapphire, crystals, Czochralski, interface growth features, (7) 269*c*.
crystals, electrical conductivity, (10) 352*c*.
growth from melt, (7) 266*i*.
high-strength, (2) 82*c*.
fracture, (11) 385*b*.
gas phase etching with sulfur fluorides, (4) 137*c*.
gas phase etching: II, fluorinated hydrocarbons, (5) 194*c*.
heat-pulse propagation in, temperature dependence of, (2) 84*c*.
rods and boules, residual strain in, (2) 82*d*.
tensile strength, effect of heat treatment, (2) 76*a*.
Sapphire *(continued)*
wetting, by liquid Cu-O alloys, (1) 31*g*.
whiskers, tensile strength at elevated temperatures, (10) 362*g*.
Sapphirine, crystal structure, (9) 319*g*; (10) 351*d*.
phase transformations in firing of spinel-mullite mixtures and charges of, (6) 238*f*.
Scandium, analog of beryl, synthesis, (8) 299*h*; errata, (10) 362*c*.
antimonate, P (9) 317*d*.
fluoride, interaction with fluorides of alkali metals, (7) 267*e*.
titanite and vanadite, (4) 153*j*.
Scattering, atomic, of TiC components, X-rays to study, (1) 40*c*.
beta-ray, for testing coating thickness, (8) 284*j*.
ion, for determination of crystallographic polarity of CdS, (7) 265*c*.
ionized impurity, influence on Gunn effect and impact ionization in CdTe, (1) 31*a*.
laser-induced stimulated Brillouin, in CdS, (9) 321*a*.
light, characteristics of uncommon verneuil crystals by, (9) 322*b*.
of heat-treated quartz in relation to hydrogen, containing defects, (11) 385*c*.
by hectorite solutions when subjected to electric fields, (5) 200*j*.
Mie, for Al_2O_3, temperature dependence of, (1) 39*f*.
photon-photon, detection in KD_2PO_4, (10) 351*i*.
Raman, depolarization in calcite, (1) 27*b*.
evidence from, for overdamped soft optic mode in $BaTiO_3$, (4) 135*j*.
from mixed crystals $(Ca_xSr_{1-x})F_2$ and $(Sr_xBa_{1-x})F_2$, (2) 82*a*.
from plasmons and phonons in GaAs polarization and intensity of, (4) 150*c*.
study of $\alpha-\beta$ phase transition in quartz, (4) 152*c*.
Rutherford, of protons from quartz, orientation dependence of, (4) 147*f*.
small-angle X-ray, for study of clay minerals, (8) 298*h*.
thermal diffuse, of X rays or electrons from crystal lattices, theory of surface effects on, (2) 84*e*.
Scheelite, -powellite isomorphous series, artificial crystals of, production and study, (4) 151*e*.
Schiff's bases, compounds of, with U(IV), Zr(IV), and Th(IV), (4) 129*j*.
Schist, from granitic rocks of central Sierra Nevada batholith, California, (4) 138*h*.
Science, creative process, (1) 40*g*.
and engineering, creativity, (1) 40*f*.
Screen process printing. See *Decoration.*
Screening, and air classifying, of finely divided material, methods and apparatus, P (6) 225*d*.
color cathode-ray tube, P (6) 223*j*.
constants, ionization potentials, and electron affinities: VII, comparison with Hartree-Fock calculations, (9) 323*g*.
machines for wet and dry screening, (7) 259*b*.
Screens and sieves, cathode ray tube, structure, P (2) 64*g*.
cathode ray tube color, P (7) 255*i*; P (7) 257*a*; P (9) 312*j*.
drum, P (11) 382*j*.
electroluminescent, composition, P (9) 312*f*.
high efficiency achieved through probability sizing, (8) 284*e*.
image display, P (7) 257*d*.
molecular, P (1) 24*b*.
multicolor luminescent, P (6) 222*a*.
phosphor, treatment, in cathode ray tube, P (2) 67*b*.
polychrome striped, for color television receiver comprising filaments of homogeneous glass, P (1) 18*j*.
pulsatory, P (4) 118*i*.
separator, improving performance, P (5) 186*b*.
silk, stencil decorating apparatus for bottles, P (5) 176*a*.
stencil, for decorating molded glass articles, P (5) 176*b*.
vibratory mounting for, P (8) 288*e*.
Sculpture. See *Art and artware.*
Seals and sealing See also *Bonding; Soldering.*
aluminum oxide bodies to metals, P (1) 18*d*.
aluminous porcelain vacuum, Pyrex to, for use in thermal analysis, (6) 227*b*.
cement concrete surfaces, P (9) 304*d*.
ceramic, and bearing members, P (2) 58*a*.
of ceramic material, P (8) 282*c*.
ceramic-metal, P (1) 18*b*; P (6) 220*j*.
ceramic-to-metal, P (4) 94*e*; P (7) 257*d*.
ceramic-to-metal, high vacuum-tight, (7) 255*a*.
compact ampoule, P (7) 248*d*.
composition, CaO-MgO-Al_2O_3, (7) 255*g*.
connectors, in planar structure, P (8) 278*b*.
copper in silica body, P (8) 278*b*.
electric, in space age, (7) 247*g*.
for enclosures subjected to high pressures and temperatures, P (11) 379*g*.
fiber optic devices, P (8) 278*b*.
frustoconical lead-through elements, P (4) 100*i*.
gas, of gas turbines, spray coating of, P (7) 246*h*.
glass, containing lead titanate crystals, and method, P (2) 52*f*.
electrically conductive hermetic, for spark plug, P (2) 66*h*.
Seals and sealing, glass *(continued)*
high expansion, and composite article, P (9) 307*f*.
Kovar, P (5) 175*b*.
to other materials by solderable metal layer, (1) 17*b*.
for turbine, P (1) 10*f*.
glass coated connection, P (7) 246*e*.
glass compositions, method, and article, P (5) 176*a*.
glass-ceramic, stressed hermetic, P (7) 249*f*.
for glass furnace joints, P (11) 372*b*.
glass-to-metal, P (2) 52*i*.
annealing, (1) 5*i*.
radiant energy means, back reflector for, P (11) 371*a*.
and seal produced, P (2) 66*b*.
vacuum-tight aluminate, use of active soldering for making, (4) 97*j*.
heat, flash lamps containing combustible gas mixtures, P (2) 53*d*.
metal-to-glass, high temperature-pressure, constructions, P (6) 212*g*.
metal with solder glass compositions, P (10) 340*b*.
metallic wires into glass tubing, (10) 337*g*.
for microhematocrit tube, P (4) 100*d*.
Mo-W thimble, P (6) 222*i*.
multiple surface glass, for high voltage discharge device, P (10) 345*c*.
Nb end, for Al_2O_3 ceramic lamp, P (9) 313*i*.
polyester, for clay pipe, (4) 102*e*.
process for producing, P (4) 100*i*.
quartz-to-metal, fused, for advanced components, (8) 280*h*.
for refractory ceramic discharge device envelopes [Al_2O_3], P (9) 313*g*.
and resilient seal, for elements with different coefficients of expansion, P (5) 175*g*.
spacing members in double or multiple glass pane assembly to margins of glass panes, P (1) 11*a*.
vacuum, for thin Be X-ray window, P (4) 122*c*.
Sedimentation, sedimentary consolidation, (4) 154*c*.
settling convection, effect on grain-size analysis, (1) 22*a*.
tube, automatic recording, University of Southern California, calibration, (11) 379*i*.
tube, inexpensive recording, for sand analysis, (11) 380*f*.
Sediments, fine-grained, consolidation data, (1) 26*g*.
fabric, study with scanning electron microscope, (8) 285*g*.
unconsolidated, and ooze, method for making slides of, (6) 226*d*.
Lake Erie and Lake Ontario, relations of grain size, clay content, quartz, and organic carbon in, (11) 382*f*.
marine carbonate, factors affecting carbon and oxygen isotopic composition of: III, Eniwetok Atoll, (6) 229*a*.
marine terrigenous and carbonate, mineralogy of sand size carbonate fraction of, (1) 32*h*.
and sedimentary rocks, quantification in clay mineral studies of, (8) 285*a*.
tertiary argillaceous, initial porosity, relation with paleosalinity in Rheintalgraben (SW. Germany), (8) 287*h*.
tidal marsh, shear strength, (8) 285*d*.
Seebeck, coefficient of $(ZrO_2)_{0.85}(CaO)_{0.15}$ electrolyte thermocell, (5) 199*f*.
Selenide, metal, of groups II and III, growing single crystals of, P (4) 115*h*.
Selenium, amorphous, structure according to intensity curves, (10) 361*e*.
dioxide, infrared spectrum and structure, (2) 79*c*.
glass transition temperature and isothermal volume change, (4) 137*h*.
hexafluoride, vibrational analysis, (4) 163*f*.
oxide, sublimation, thermodynamic study, (9) 332*i*.
and sulfur chains, rotational isomeric state models of: III, large rings in liquid sulfur and nature of S_π, (9) 329*b*.
tetrachloride and tetrabromide, infrared spectra, (11) 385*h*.
thermal expansion, comparison with Te, (4) 129*e*.
vaporization, laser-induced, mass spectrometric studies, (5) 196*f*.
Semiconductors, P (5) 185*h*; P (6) 223*d*; P (11) 378*g*.
arrangement with capacitative shielding means between conductive strips and semiconductor body, P (2) 66*d*.
arrangements, manufacture using masking step, P (8) 282*d*.
assembly, with semiconductor element in area contact under pressure with conductive terminal elements, P (6) 223*d*.
attachment of leads to, P (1) 17*i*.
automatic classifying device, P (9) 312*b*.
bidirectional component, P (7) 258*b*.
of blende type, anomalous diffusion of X rays in, (9) 318*d*.
body, attaching electric connections to, P (4) 115*h*.
making electrical contact to, P (2) 65*f*.
monocrystalline, polishing method for removal of material from, P (7) 257*h*.
with photoelectromagnetic effect, for use in radiation sensor, P (2) 66*j*.
of silicon and germanium, aluminum-gold contact to, P (1) 17*h*.

Semiconductors *(continued)*
camera tube targets, P (1) 18*c*.
circuit device, doped integrated, P (8) 283*d*.
coating with mask, and diffusing impurity in, P (9) 313*d*.
composition, Gd or Sm doped silicon, P (2) 64*j*.
compositions, novel quaternary, P (5) 184*c*.
compound, P (11) 378*j*.
chemical bonding and structure, (4) 128*b*.
electrolytic preparation, P (4) 112*g*.
epitaxially growing layers of, P (11) 377*i*.
comprising plural deep-level-forming impurities, P (9) 313*h*.
conductivity, Hall effect, and magnetic resistance in, (4) 109*f*.
conductor, solid ionic, P (8) 283*c*.
crystals, of fibrous structure, P (8) 283*c*.
habit and morphology, influence of solvent and impurities on, (8) 293*b*.
potential distribution in, measurement with electron beam, (5) 187*c*.
degenerate, α-Ag_2Se as, (1) 25*a*.
devices, P (2) 65*g*; 66*d*; 66*e*; P (4) 116*c*; 116*e*; P (5) 184*d*, *e*; P (6) 223*h*; P (7) 257*b*, *h*, *j*, 258*c*; P (8) 283*b*, *d*; P (9) 312*h*; P (10) 345*g*; P (11) 378*g*.
adapted for pressure mounting, P (10) 346*c*.
apparatus to sever gold wire bonded to, P (9) 312*b*.
attachment of leads to, P (4) 112*d*.
or components, treating, P (6) 222*i*.
compression assembled, using spherical force transmitting member, P (1) 18*c*.
compression bonded, P (4) 112*a*.
comprising III-V epitaxial deposit on substitutional III-V substrate, P (7) 258*b*.
comprising two parallel-connected semiconductor systems in pressure contact, P (8) 283*e*.
with connecting leads attached to, production, P (5) 184*e*.
constant current, P (6) 221*e*.
contact structure, P (4) 116*c*.
with controllable noise characteristics, P (1) 19*h*.
with cup-shaped regions, P (11) 378*e*.
with dielectric and metal protectors, P (7) 258*b*.
diffused, P (6) 222*g*.
diffusion type, with plural protective coatings, P (5) 182*d*.
doped with gold just to point of no excess, P (8) 283*e*.
double-diffused, P (8) 282*g*.
with emitter, base, and collector region, P (11) 378*d*.
employing punchthrough, P (11) 378*c*.
encapsulated, including ceramic substrate, P (7) 256*g*.
etching for forming leads on, P (5) 183*e*.
five-layer light-actuated, with bevelled sides, P (5) 182*c*.
germanium, use of silicon oxide and phosphorous oxide to mask against diffusion of In or Ga into, P (2) 67*c*.
[Ge, Si] using AuAl layer as diffusion barrier that prevents "purple plague," P (1) 19*h*.
glass-sealed, P (8) 283*c*.
heat conductive mounting base for, P (6) 221*e*.
heterojunction, employing carrier multiplication in high gap ratio emitter-base heterojunction, P (4) 113*i*.
for high frequency and high power use, P (8) 283*f*.
high-voltage, with electrical gradient-reducing groove, P (4) 113*b*.
high-voltage planar, P (11) 376*i*.
implanting buried layers in, P (11) 378*i*.
implanting grids in, P (6) 223*i*.
with improved resistance to radiation damage, P (11) 378*c*.
including beam leads, P (5) 185*h*.
with increased resistance to second breakdown, P (9) 313*i*.
with increased reverse and forward blocking voltages, P (2) 66*e*.
inspecting with electron mirror microscopy, P (2) 65*e*.
with integral electrodes, constituting unitary vitreous structure, P (10) 346*b*.
integrated, P (4) 113*f*.
with interelectrode capacitance compensation, P (1) 19*i*.
with inversion layer, underneath oxide coating, compensated by gold dopant, P (9) 313*j*.
isolation, P (2) 65*g*.
junction, conductive electrode for reducing electric field in region of junction of, P (4) 112*a*.
with lateral retrograded *pn* junction, P (6) 223*g*.
letter symbols for, (1) 17*e*.
light emitting, of improved transmission characteristics, P (8) 282*b*.
making and testing, P (11) 378*i*.
metalized, with fired-on glaze, P (11) 377*f*.
[MOS] with region having portions of differing depth and concentration, P (9) 314*a*.
mounting on thick film circuits, P (11) 377*f*.
multiemitter, P (11) 377*j*.
multilayer epitaxial, P (10) 345*b*.
multilevel terminal metallurgy for, P (11) 377*j*.

Semiconductors *(continued)*
multiple, P (10) 345*c*.
negative resistance, P (11) 378*a*.
negative resistance, with intrinsic region, P (11) 378*a*.
ohmic contact to, P (4) 115*d*.
oxygenated SiN, and silane method for making, P (5) 184*e*.
particularly for response to variable pressure, P (4) 116*d*.
passivation, P (10) 345*e*.
phosphorus-protected, P (7) 257*g*.
photosensitive, P (1) 19*c*.
pressure assembled, using massive flexibly mounted terminals, P (9) 313*c*.
pressure-responsive, P (5) 184*j*.
printed circuits, P (8) 283*e*.
and process for embedding in plastic, P (7) 258*c*.
for producing and amplifying electrical signals of very high frequencies, P (11) 378*d*.
production by use of ion beam implantation, P (8) 283*j*.
for reducing distortion in electron optics, P (9) 313*h*.
with regions with preselected different minority carrier lifetimes, P (5) 185*g*.
with Schottky barrier formed on (100) plane of GaAs, P (10) 346*b*.
Si, bonding, P (11) 377*g*.
simplified stacked, P (9) 314*b*.
stable, P (5) 183*i*.
[structure], P (9) 313*j*.
surface-protected, P (7) 258*a*.
surface treatment for, P (9) 314*e*.
surface treatment of, P (8) 283*j*.
thyristor, *pnpn*, P (8) 283*b*.
thyristor, with positively bevelled junctions, P (7) 258*c*.
thyristors, with electrically interchangeable anodes and cathodes, P (7) 257*i*.
tunneling, exhibiting storage characteristics, P (4) 117*b*.
vitreous material for use in, P (8) 284*a*.
dice, thin, P (8) 283*a*.
diffusion voltage in, electron beam method of measuring, (5) 187*g*.
disk, individual wafers, separation, P (11) 378*h*.
element, controllable, P (6) 221*f*; P (7) 256*c*.
diffusion process for making, P (9) 313*d*.
with disturbed crystalline surface structure in junction area, P (8) 283*f*.
mosaic, interconnected in XY matrix, P (9) 313*g*.
producing array, P (10) 345*j*.
switchable, method and article for making, P (6) 222*c*.
extremely anisotropic, interband optical transitions in: I, bound and unbound exciton absorption; II, coexistence of exciton and Landau levels, (5) 195*e*.
field-effect devices, of junction type, P (9) 312*j*.
forming glass coating on, P (4) 114*f*.
forming by masking and diffusing, P (4) 114*g*.
fundamental principles, (10) 344*d*.
generation of microwave second harmonic and sum and difference frequency in, at low temperatures, (5) 181*e*.
groups II–IV, thermal study, lattice heat capacities and free energies of formation, (4) 160*c*.
inserting manganese into, serving to produce electronic semiconductor structural components, P (9) 312*i*.
integrated circuit device, P (9) 314*a*.
isolated cathode array, P (9) 312*c*.
isolating individual devices in integrated circuit monolithic bar, P (8) 282*j*.
joining to base, P (6) 222*c*.
junction device, for generating optical radiation, P (2) 66*f*.
layer, crystalline, forming on alumina substrate, P (4) 114*e*.
precipitated from gas phase, influencing surface profile of, P (4) 115*a*.
thin, double-stream interaction in, (4) 132*d*.
layer structures, fission fragment tracks in, (4) 136*i*.
lead iodide, properties, (4) 151*i*.
light-emitting, with relatively heavy outer layers for heat-sinking, P (6) 221*i*.
magnetic, $Ag_xCd_{1-x}CrSe_2$, helicon-spin wave interaction in, (1) 30*f*.
making by diffusion, P (7) 257*c*.
making by laser induced diffusion, P (5) 183*h*.
manufacture, role of purposely produced alterations of crystal structure in, (6) 220*j*.
manufacture, stabilizing resistance in, P (8) 283*e*.
materials, apparatus for horizontal zone refining of, P (1) 17*i*.
device for inductively heating, P (7) 256*d*.
diffusing gold into, P (7) 257*h*.
doped, growing from source which includes unstable isotope which decays to dopant element, P (9) 312*i*.
epitaxial precipitation on spinel-type lattice substrate, P (5) 183*b*.
etching, P (5) 183*c*.
graded composition mixed compound, P (7) 257*f*.
growth of shaped epitaxial deposits on substrate, P (5) 183*h*.
low temperature, apparatus for evaporation

Semiconductors, materials *(continued)*
by electron beam impingement on, and means for draining electric charge from, P (4) 112*b*.
methods and apparatus for treating with gases, P (5) 184*h*.
nonhomogeneities in, determination by optical reflection method, (2) 62*e*.
novel ternary, P (10) 345*d*.
novel Zn manganese arsenide, P (5) 184*c*.
selective deposition of, P (2) 66*b*.
silicon, crucible-free zone melting, P (10) 345*f*.
structure and method for preventing spurious growths during epitaxial deposition of, P (5) 185*c*.
members, precipitation method of producing, P (9) 313*c*.
metal-oxide-, tetrode, P (5) 184*a*.
microcontact Schottky barrier device, P (9) 313*g*.
multilayer, heteroepitaxial structure, P (6) 222*j*.
narrow doped region devices, structure and production, P (10) 346*d*.
new, $MgSiP_2$, (10) 357*f*.
niobate tantalate compositions, P (4) 116*a*.
n-type, included on camera tube target, having higher concentration of deep donors than shallow donors, P (1) 17*i*.
optical device, P (10) 345*d*.
optical radiation device, P (10) 346*d*.
opto-*pn* junction, with greater recombination in *p*-type region, P (4) 115*d*.
packages, O-bend lead for, P (9) 313*a*.
photosensitive, with large area light absorbing junctions, P (4) 115*c*.
photosensitive, with two radiation sources for producing two transition steps, P (4) 115*f*.
photosensitive device, for obtaining light source position data, P (8) 283*h*.
pinch effect in, theory, (5) 201*c*.
planar, Si, masking for metal contacts on, (4) 111*h*.
pn junction, with polycrystalline layer on one region, P (8) 283*i*.
pressure-responsive device, P (8) 283*i*.
process, including reduction of substrate thickness, P (6) 223*j*.
properties of $AgInSe_{34}$, (4) 149*b*.
of Mn-bearing sintered wustite, (4) 145*g*.
of thallium selenide, (1) 17*c*.
with protective glass coating, P (4) 115*c*.
rectifier structure with semiconductor element assembly screwed into place on support base, P (10) 346*d*.
regulators, establishing low Zener breakdown voltages in, P (10) 345*f*.
with reinforced lead structure, P (9) 314*a*.
resistance, P (10) 346*a*.
ribbon, crystalline, method and apparatus, P (10) 346*i*.
rods, effect of magnetic field on density distribution of injected plasma in, (5) 180*f*.
saturated optical absorption through band filling in, (10) 360*c*.
SCR with emitter electrode space from semiconductor edge equal to 10 times base thickness, P (9) 313*g*.
and semimetals, powdered, propagation and dimensional resonances of helicon-like waves in, (11) 386*h*.
Si, with metal-silicide heterojunction, P (11) 378*j*.
Si, palladium ohmic contact to, P (6) 223*c*.
Si devices, metalization, for making ohmic connections to, P (10) 345*e*.
SiN coating on, P (5) 185*j*.
single crystals, homogeneous, synthesis and growth from solution, (7) 255*f*.
with single impurity gradient, electrolytically etching, P (4) 114*c*.
slice, apparatus for polishing, P (7) 255*f*.
sputtering, low power density, on, P (6) 221*j*.
structural component, P (11) 378*g*.
structure, with electrically isolated region of semiconductor material, P (11) 377*j*.
with glass insulated islands, P (10) 345*a*.
including opposite conductivity segments, making, P (1) 18*e*.
for integrated circuitry, P (7) 258*f*.
with layers of preselected resistivity and conductivity type, P (7) 257*i*.
for performing unipolar transistor functions in integrated circuits, P (4) 116*i*.
substances, containing impurities, apparatus for producing striationless bodies of, P (4) 112*c*.
surfaces, chemisorption bond on, (10) 357*e*.
controlling electrical characteristics, and product produced, P (1) 18*b*.
oxide coating for, P (11) 378*b*.
surface devices, with thin oxide films in, protection means for, P (11) 378*a*.
switching devices, with tunnel junction diode in series with gate electrode, P (6) 223*j*.
thin film, growing with an electron beam, P (4) 114*j*.
three region, with rectifying junctions, P (2) 67*a*.
III-V compound, survey of radiative and nonradiative recombination mechanisms in, (2) 83*d*.
with trilayered metal contact, P (2) 66*f*.
tunneling, device applications, (1) 16*h*.
tunneling device, metal-insulator-metal, with

Semiconductors *(continued)*
exponential I-V characteristic only in negative resistance range, P (8) 282*e*.
tunneling phenomena in solids, B (11) 390*d*.
two-photon conductivity in, calculations, (11) 383*d*.
type II, containing magnetic particles, P (9) 314*d*.
wafers, apparatus for dicing, P (5) 182*f*.
electrically insulating-heat conductive mass for, P (11) 376*e*.
forming aligned oxide patterns on opposite surfaces of, P (2) 65*c*.
forming plurality of rectifiers, P (11) 378*h*.
with low field junction surface, P (7) 258*f*.
pickup and bonding tool, P (11) 378*h*.
probe assembly for testing, including wafer vibrator for effecting good test connections, P (10) 345*f*.
welding devices for, P (11) 378*i*.
ZnO, field dependence of ultrasonic attenuation in, (4) 136*f*.
Separation. See also *Beneficiation; Classification; Flotation.*
alkali metal salt, P (4) 124*f*.
of berkelium from cerium, P (1) 24*a*.
dry, of mixtures of solid materials, P (8) 287*i*.
electrostatic. See *Electrostatic processes.*
gravity, of particulate material, P (7) 262*h*.
heavy liquid, modified centrifuge apparatus for, (1) 21*d*.
quantitative, of calcium, strontium, and phosphate, (1) 21*g*.
of red mud from dissolved Al_2O_3, P (8) 288*b*.
sizing, of discrete particles in fluid medium, method and apparatus, P (10) 346*j*.
of traces of elements by precipitation: IV, through carbonates, use in determining trace contaminants in U compounds, (10) 347*e*.
vapor, of silicate melts at high temperatures and atmospheric pressures, (5) 202*f*.
Separators, gravity, stone and heavy grain discharge outlet for, P (2) 74*g*.
hydrocyclones, for vortical separation of solids, P (4) 124*f*.
particle classification device and method, P (7) 259*e*.
pneumatic, and bulk solids feeder, P (7) 263*c*.
and classifier apparatus, and method, P (5) 191*e*.
inertial type, P (2) 68*b*.
with rotating members, for powder into fine and coarse particles, P (10) 346*i*.
slow magnetic drum ore, control device, P (6) 230*d*.
strong-field magnetic and electrostatic, for preparation of ceramic raw materials, (7) 262*h*.
vibratory, P (5) 186*g*.
wet, for dust extraction, (4) 118*h*.
Serpentine, of Bay of Audierne, (2) 73*h*.
dehydroxylation, temperature and vapor pressure dependence, (4) 142*g*.
Setting. See *Binders.*
Settling. See *Sedimentation.*
Sewer pipes. See *Pipe.*
Shales, of Decorah formation, southeastern Minnesota, clay mineralogy, fabric, and industrial uses, (9) 316*g*.
Graneros (Upper Cretaceous), central Kansas, vivianite in, (9) 317*b*.
ground, separation from calcite by liquid-liquid particle transfer, (8) 287*g*.
Kansas, testing for nonceramic utilization, (2) 71*c*.
operations, locations in Indiana, (4) 123*g*.
Posidonia, Lias Epsilon from Brunswick-Hondelage, use in manufacture of hydraulic cement and aeroconcrete, (4) 92*d*.
Shock, compression, of Al_2O_3, material strength effect in, (6) 234*i*.
compression, for irreversible transformation of hexagonal BN, (2) 79*i*.
-induced preferred disorder in solids, (10) 360*g*.
wave, pressure, for forming ceramic bodies, (5) 186*b*.
Shock resistance, thermal, of aluminosilicate refractories, in relation to strength, thermal expansion, and modulus of elasticity, (2) 58*c*.
and Griffith criterion, of single-phase vs multiphase brittle ceramics, (7) 266*e*.
of hollow tiles, measurement and calculation, (1) 15*j*.
of porcelain, (6) 219*h*.
Shrinkage, carbonatation, of lime and hydrated cement, mechanism, (9) 303*j*.
firing, cinematic measurement, (5) 187*b*.
of plaster model used for making dies, (4) 92*g*.
relations with green density for ceramic mold design, (9) 314*f*.
of two phase material, (4) 121*g*.
Sieves. See *Screens and sieves.*
Silex. See *Quartz.*
Silica. See *Silicon, dioxide.*
Silicates, alkali, aqueous solutions, structural and mineral-phase conversions during hardening of, (2) 45*c*.
analysis, (7) 259*h*.
analysis, third ceramic chemists' conference on, B (10) 366*j*.
ceramics, glass, data-book for, B (4) 166*a*.
chemical studies: XXXIV, structure of silicate anions of 14 Å tobermorite of Crestmore and dehydration products, (5) 192*d*.
comparative crystallochemical systematics and morphotropic transformations of, and their analogs (germanates and fluoroberyllates), (4) 129*c*.
crystalline, infrared spectroscopy, (11) 380*g*.
densities, in CaO-MgO-SiO_2 system, (10) 351*h*.
dicalcium. See *Calcium, dicalcium silicate.*
Eu(II) activated, fluorescence, (9) 321*c*.
ferromagnesian, tourmaline, cordierite, chloritoid, and vivianite—ferrous-ferric electronic interaction as a source of pleochroism in polarized optical absorption spectra, (9) 327*g*.
fluo-, P (11) 382*i*.
fluorine determination in, (4) 119*b*.
foamed, slags and glass, (4) 104*c*.
with garnet-type structure, hydrothermal synthesis, (7) 267*b*.
hydrate of Zr and Na, lemoynite, new, from St. Hilarie, Quebec, (9) 324*e*.
and ice surfaces, interface between, (1) 31*c*.
industry, proceedings of 1967 conference, B (7) 272*h*.
in materials of high vacuum technology, B (2) 85*f*.
materials, industry, in U.S., economic tendencies, (2) 85*a*.
specific surface, measurement, (10) 347*h*.
synthesis for filtration and aeration, (11) 374*b*.
melting point, in inert atmospheres, apparatus for measuring, (2) 68*j*.
melts, with Al_2O_3, TiO_2, and FeO, solubility of water in, at 1550°C, (11) 374*g*.
aqueous solutions and coexisting, K-Na ratios in, (5) 198*f*.
vapor fractionation at high temperatures and atmospheric pressures, (5) 202*f*.
mica-type layer, swelling, estimation of layer charge in, (4) 154*i*.
minerals, layer-, effect of adsorbent charge on competitive adsorption of divalent organic cations by, (8) 290*j*.
surface area, by BET method using adsorption of xenon at −78°, (5) 200*e*.
surface and bond-forming properties, and application in mineral processing techniques, (6) 238*j*.
mixtures, colloidal silica-potassium, and preparation, P (5) 190*g*.
molten, viscosities, viscometer for measuring, (2) 70*a*.
and oxides, chemistry, collection of USSR papers, B (4) 168*h*.
oxygen in, (11) 385*a*.
packing material, for prevention of methacrylate and acrylate ester polymerization, P (2) 67*g*.
particles, expanded, P (9) 317*d*.
quantitative spectral analysis of, direct spectrochemical analyzer DSA 24 for, (10) 347*g*.
refractory, Groves' method for determining ferrous oxide in, (8) 285*c*.
resilience, preparation of products, (9) 328*j*.
rocks, analysis by atomic absorption spectrophotometry and hydrofluoric acid decomposition technique, (5) 186*j*.
and minerals, rapid determination of F in, (8) 285*b*.
rapid determination of fluoride in, (4) 121*b*.
X-ray fluorescence analysis, calibration of intensity data for, (8) 289*a*.
science: Vol. I, silicate structures; Vol. II, glasses, enamels, slags; Vol. III, dry silicate systems; Vol. IV, hydrothermal silicate systems; Vol. V, ceramics and hydraulic binders, B (2) 85*h*.
sheet, crystal structure, (9) 317*h*.
and silica, chemical bonding in, (4) 128*j*.
and silicic acids, treating, P (5) 191*a*.
Si$K\beta$ X-ray line for, structural and chemical effects on, (4) 156*d*.
spinodal precipitation in: I, introductory application to exsolution in feldspar, (8) 298*h*.
stability, high temperature and pressure aqueous solubility data bearing on, (4) 138*g*.
staurolite, crystal structure, (9) 319*h*.
study, application of atomic absorption spectrophotometry to, (5) 186*i*.
systems. See *Systems.*
thermodynamic properties, determination from locations of conjugation lines in ternary systems, (4) 131*i*.
upper mantle materials, plastic deformation, B (6) 241*c*.
Silicides, of rare-earth metals, (6) 216*a*.
silicidation, of Mo and its alloys, influence of allotropy, (9) 304*j*.
transition metal, uranium-, of UM_2Si_2 composition, (5) 202*e*.
Silicon, activation analysis, (2) 68*d*.
Al-, long-range order in muscovite, (4) 142*i*.
amorphous, electrical conduction in, (8) 281*f*.
and arsenic, gravimetric determination, with 1,2-dimorpholinylethane as reagent in quantitative analysis, (4) 120*b*.
arsenide, crystals, vapor-grown, (4) 163*d*.
carbide. See also *Refractories.*
articles, employing pyromellitic dianhydride-limonene dioxide mixture, P (11) 375*b*.
β-, crystals, solution growth, influence of carbon transport kinetics on, (4) 139*g*.
β-, with sheath of silica, for fibers, P (2) 58*f*.
β-, whiskers, growing, P (2) 59*e*.
β-, whiskers, structure, comments, (4) 129*c*.
bodies, carbon-bonded, P (8) 279*g*.
cluster of screw dislocations in, direct observation, (7) 265*d*.
coating with, by immersion reaction, P (10) 342*c*.
continuous vapor deposited filaments, metallographic structure, (4) 110*g*.
crystal, 33*T*, (1) 36*c*.
crystals, epitaxial growth by thermal reduction technique, (1) 29*h*.
crystals, growth studies (1) 30*j*.
crystals, high-purity, trace impurities in preparation of, (2) 77*a*.
crystals, polymorphism, (1) 35*a*.
cubic, stabilization, P (2) 59*g*.
delayed fracture and creep in, (4) 130*i*.
deposited on Si substrate to form suction box cover, P (7) 253*b*.
device, P (2) 66*g*.
diodes, perform in searing heat, (5) 178*e*.
doped with B and N, luminescence efficiency, (4) 110*d*.
epitaxial growth, P (11) 378*h*.
epitaxic growth layers, X-ray diffraction topography for analysis of, (10) 349*j*.
etching, P (5) 183*d*.
furnaces and plants, P (6) 218*f*.
grain, graded by size and shape at Electro, (4) 104*h*.
heating elements, sintered, comparison between oxidation and electrical aging of, (2) 57*a*.
masking layer, processes of epitaxial deposition or diffusion employing, P (9) 313*e*.
n-type, photoconduction, (9) 327*d*.
oxidation at 1150° to 1400°C and at 9×10^{-3} to 5×10^{-1} torr oxygen pressure, (2) 81*i*.
oxidation, temperature and oxygen pressure dependence of, (4) 159*h*.
polytypes, revised X-ray diffraction line intensities for, (10) 347*d*.
polytypism in, (10) 359*c*.
porous cubic, radiation-induced changes in, (4) 151*i*.
pyrolytic, structure and properties, (10) 342*i*.
pyrolytic, texture, (4) 160*a*.
pyrolytic deposition, P (4) 107*e*.
ribbons, P (8) 279*e*.
single crystals, polytypism in, (4) 157*b*.
surfaces, wetting, (5) 203*e*.
2H-, whisker, growth by screw dislocation process, (9) 308*i*.
2H-, whiskers, influence of oxygen on growth, (4) 140*d*.
vapor-liquid-solid and melt growth, (5) 202*g*.
composite material, SiC whisker reinforced, P (11) 375*d*.
content, total, of water, determination, (6) 225*j*.
covalent bonding in, X-ray studies, (5) 203*b*.
crystallographic axes, effect of high unaxial pressure along, (9) 320*h*.
determination, in cast iron, steels, slags, and ferrosilicon, (1) 21*h*.
by fast neutron activation in thin films, (8) 280*h*.
by precipitation of dodecamolybdosilicic acid with organic bases, (4) 120*c*.
dioxide. See also *Coesite; Cristobalite; Glass; Quartz; Quartzite; Refractories; Sands.*
additions, effect on MgO sintering, (1) 28*g*.
-Al_2O_3 particles, spheroidal, P (7) 262*j*.
amorphous, finely divided, apparatus for producing, P (5) 189*f*.
amorphous and crystalline forms, vitrification, influence of boric oxide, (10) 337*h*.
-based materials, X-ray fluorescence analysis, comparison with spectrography and chemistry results, (5) 188*d*.
body, sealing copper in, P (8) 278*b*.
in carbonate rocks, rapid gravimetric determination using gelatin, (5) 187*j*.
chemically vapor-plated, environmental effects on, (1) 16*d*.
coesite and stishovite, high-pressure modifications of, (9) 316*h*.
colloidal compositions, containing set indicator, P (7) 252*h*.
crystalline, electrophoretic mobility and flocculation, effect of cationic polymers structure, (1) 28*d*.
determination by coagulation (for high-SiO_2, aluminosilicate, and aluminous materials), (10) 347*i*.
determination in glasses, (11) 380*b*.
diffusion in molten sodium silicate, electrochemical study, (4) 124*h*.
dispersion, aggregation by iron(III), (1) 25*b*.
dissolution in molten glass, (10) 338*g*.
electrical conduction in, (1) 39*e*.
electrolysis on silicon, (8) 291*d*.
extremely finely divided inorganic mixtures containing, P (6) 230*b*.
fine grinding, processes occurring during, (4) 151*c*.
finely divided precipitated, production, P (6) 230*c*.
flocculated slurry, continuous thickening, (2) 67*e*.
fused, ion diffusion into from molten salts, (5) 195*j*.
fused, membrane potentials and ion selectivity, in molten salts, (5) 197*a*.
fused, vibrational spectra, interpretation, (4) 140*i*.

Silicon, dioxide *(continued)*
gel, crystal growth in using cosolute, (9) 322*d*.
gel, electrical conductivity in presence of adsorbed water, (10) 352*e*.
gel, surface structure, (8) 299*d*.
gels, adsorption of ozone on, (1) 24*i*.
gels, pretreated, surface area studies in, (10) 361*h*.
gels. See also *Colloids*.
hydrated and dehydrated, adsorption studies, (5) 191*j*.
in India, (4) 123*j*.
infrared study of water adsorbed on, (1) 31*d*.
kinetics of heterogeneous reaction with basic alkali-metal salt solutions in chloride melts, (9) 323*j*.
layers, doped, deposited from premixed hydrides, diffusion characteristics, (8) 281*d*.
layers, doped, deposited from SiH_4, diffusion characteristics and applications, (8) 281*c*.
-lime compositions, hydrothermally hardened, in system CaO-SiO_2-H_2O-CO_2, effect of carbonic binder on properties, (11) 372*j*.
lime-, porous body, hard-porosity, production, P (2) 59*g*.
materials, P (6) 229*h*.
materials, highly porous and reactive, production, P (7) 263*b*.
mechanism of decomposition of formic acid over, (5) 193*g*.
mechanism of dehydration decomposition of formic acid over, (8) 295*a*.
melts, surface, (1) 38*j*.
microspheroidal, P (10) 349*c*.
monodisperse spheres, controlled growth in micron size range, (1) 26*c*.
and other oxides, apparatus and method for producing, P (5) 190*f*.
packing material, for prevention of methacrylate and acrylate ester polymerization, P (2) 67*g*.
phosphates, simultaneous flotation with carbonate minerals, P (6) 230*c*.
pile-exposed vitreous, ionization expansion, (11) 385*j*.
-potassium silicate, colloidal mixtures, and preparation, P (5) 190*g*.
powders, interaction with water, adsorption thermodynamics of, (4) 126*g*.
precipitated amorphous, in 1*M* $NaClO_4$ at 25°C, solubility and dissolution kinetics, (8) 297*i*.
processing, simplified with silicone resins, (2) 57*f*.
reaction with CaC_2, (6) 237*b*.
reaction with graphite in vacuum, effect of physical parameters, (5) 193*i*.
reaction with MgO, atomic absorption spectroscopy to study kinetics of, (2) 71*a*.
reduction, rate and mechanism, (9) 309*a*.
rf-sputtering rate, effect of oxygen, (4) 133*c*.
and silicates, chemical bonding in, (4) 128*j*.
and SiO_2 xerogel, sorption of ethylamine on, (1) 37*d*.
slurries, aged, providing low viscosities for, P (1) 24*e*.
sols, concentrated, P (11) 382*d*.
spherical particles, dissolution in molten sodium disilicate, (8) 276*d*.
surface, reaction of hydroxyl groups with water and alcohol molecules on, (6) 237*d*.
surfaces, reactive organic molecules on, (4) 153*d*.
surface topography and interface structure, investigation, (7) 255*c*.
thermal properties at low temperatures, (4) 160*i*.
thermally grown, Fowler-Nordheim tunneling into, (9) 310*f*.
thermally grown, irradiation effect in, (9) 323*i*.
transformations in system PbO-SiO_2, (1) 36*b*; comments and discussion, (8) 289*j*.
vitreous, acoustic properties, factors influencing, (9) 305*d*.
vitreous, acoustoelastic effect in, (11) 369*d*.
vitreous, configurational entropy, in random network theory, (4) 129*d*.
vitreous, ionization dilatation, impurity effect in, (9) 306*a*.
vitreous, metastability of high cristobalite in, (8) 295*b*.
vitreous, pressure-compacted, ionization expansion, (9) 306*b*.
vitreous, proton transport during H_2 permeation in, (7) 248*b*.
vitreous, radiation compaction, (9) 307*a*.
vitreous, random network, X-ray and neutron diffracted intensities calculated for, (4) 126*d*.
vitreous, viscosity in transformation range, (8) 300*h*.
-water interface, (1) 36*b*.
-X, thermal behavior and relation to natural silica minerals, correction, (9) 331*e*.
doping, high concentration, using ammonium phosphate, P (4) 113*j*.
effect on Cu_2O, (9) 320*j*.
epitaxial, (111) and (100), growth, geometrical stability of shallow surface depressions during, (9) 322*a*.
epitaxial layers, properties on spinel single crystals, (5) 199*e*.
epitaxially producing *pn* junctions in, P (2) 65*a*.

Silicon *(continued)*
ferro-, analysis by atomic absorption spectrophotometry and hydrofluoric acid decomposition technique, (9) 314*j*.
films. See *Films*.
and fluorine compounds, P (10) 349*b*.
Gd or Sm doped, for semiconductor composition, P (2) 64*j*.
growth and etching through windows in SiO_2, (4) 137*h*.
heteroepitaxy on stoichiometric spinel, (10) 354*e*.
hydride (silane), controlled oxidation, (8) 289*e*.
monoxide, etching, and etchant solutions for, P (6) 223*h*.
polydimensional, oxidation kinetics, (4) 148*e*.
properties, (6) 237*i*; (9) 329*b*.
monoselenide, (7) 255*b*.
n-type degenerate, photoemission of electrons from, into SiO_2, (4) 149*g*.
nitride, P (10) 343*b*.
coating on semiconductor, P (5) 185*j*.
deposited on GaAs, infrared spectra, (4) 110*j*.
material, alloys for brazing, P (6) 217*f*.
metal bonded, P (2) 58*j*.
powdered, oxidation kinetics, (6) 235*d*.
pyrolytic, preparation and properties, (2) 82*d*.
pyrolytic, property changes in, with reactant composition changes, (4) 151*c*.
reaction-sintered, mechanical properties, (2) 56*b*.
as refractory materials, (7) 251*g*.
-SiO_2 mixtures, films, (4) 136*g*.
by using stain films on silicon, (8) 297*d*.
wetting, P (1) 18*e*.
whiskers, vapor deposition preparation, P (4) 107*b*.
-nitrogen, thin film compounds, produced by radio frequency glow discharge reaction, preparation and properties, (4) 150*g*.
oxidation, at high temperatures and low pressure under flow conditions, and vapor pressure of, (1) 34*d*.
oxide, evaporation, nature of residual gases during, (2) 80*h*.
oxide, and phosphorus oxide, to mask against diffusion of In or Ga into germanium semiconductor device, P (2) 67*c*.
phosphates, studies, (6) 238*c*.
phosphide, single crystal orthorhombic, preparation, (10) 359*i*.
phosphide, synthesis of pyrite-type modification of, (4) 158*e*.
and P determination in high-P glasses by IR-spectroscopy method, (2) 69*i*.
photoemission of holes from, into SiO_2, (4) 149*h*.
planar surface, plating and polishing, P (7) 257*a*.
radiation resistant semiconductor grade, containing metal oxide, P (8) 283*j*.
rods, single crystal, growth, P (9) 312*a*.
self-compensation of conductivity in, (7) 269*a*.
self-diffusion, and dissociative diffusion of Ni in Si, (4) 131*j*.
of semiconductor purity, impurities of, nondestructive and destructive neutron activation analysis of, (5) 187*e*.
silanes, aryloxy-, Si—O bond of, investigation on basis of infrared spectra, (5) 195*h*.
siliceous materials, inorganic, analysis by atomic absorption spectrophotometry and hydrofluoric acid decomposition technique, (8) 284*i*.
Si(III) surfaces with silicon nitride layer, temperature dependence of surface potential of, (1) 39*g*.
-SiO_2 solid-solid interface system, (4) 155*a*.
single crystals, anodic passivation, (7) 263*j*.
on spinel insulators, P (4) 117*a*.
surfaces, chemically etched and thermally oxidized, surface areas and *c* values by krypton absorption, (1) 38*i*.
site transfer, in GaAs, (1) 37*a*.
slices, apparatus for holding, P (10) 344*b*.
solid state epitaxial growth by migration from silicon-aluminum alloy deposit, P (4) 117*b*.
substrates, direct nitridation, (5) 177*b*.
surfaces, defect structure after thermal oxidation, (2) 75*b*.
systems. See *Systems*.
tetrachloride, interaction with gallium chloride, (8) 293*e*.
tetrachloride, vibrational relaxation in, (5) 203*b*.
tetrafluoride, as fluorinating agent: II, (1) 36*d*.
tetrafluoride, hydrolysis by kaolinite at elevated temperatures, (8) 287*a*.
thermal oxidation, transport processes in, (1) 40*a*; (4) 129*c*.
thermal oxidation using wet oxygen, (1) 17*f*.
thermally oxidized, symmetry of interface charge distribution in, (4) 158*i*.
and thin germanium samples, in high electric fields, effect of space-charge-region surface conductivity on change of resistance of, (5) 180*f*.
vitreous, random network model, ring configurations in, (4) 153*g*.
wafer, selective masking during anodization, P (6) 223*b*.
in water, absorptiometric determination: VI, of polymeric silicic acid; VII, improved method for determining total Si content of high-purity water, (7) 259*g*.

Silicosis, fight against, relating to combating of dust, (6) 224*j*.

Sillimanite. See also *Refractories*.
group minerals, mullite formation from, (10) 341*g*.
and kyanite, heavily ground, high pressure hydrothermal measurements on, (7) 266*c*.
-kyanite reaction, bivariant, experimental evidence, (7) 265*h*.
ore deposit in Argentina, and properties of ore, (7) 262*a*.
ore, impurities, from Union of South Africa, (11) 373*g*.
phase, problem, (8) 296*f*.

Silver, axide, crystals, growth and spectral characteristics, (5) 194*f*.
bromide, crystals, epitaxial growth from melt and formation of oriented bubbles, (10) 353*c*.
chloride, precipitation, from homogeneous solution: I, particle size and shape characteristics, (9) 327*j*.
single crystals, slightly bent, annealing, (9) 318*c*.
surface hardening, effect of aqueous environment, (1) 27*d*.
chlorocomplexes, association constants, in molten KNO_3+$Ba(NO_3)_2$ and comparison with quasi-lattice theory, (9) 318*d*.
diffusion, in alkali-calcium-silica glasses, (1) 6*g*.
epitaxy, on doped NaCl substrates, (2) 62*j*.
films. See *Films*.
halides, photoelectric effects in, (2) 81*g*.
single crystals, growth in silica gels at near ambient temperatures, (7) 266*j*.
thermoelectric force, effect of fusion, (6) 232*d*.
iodide, crystal structure at 3 kbar, (4) 130*f*.
heat capacity: I, experiments on annealed samples; II, theory, (4) 138*g*.
single crystals, growth in silica gel, (7) 266*a*.
monofluoride, vapor pressure and dissociation energy, (6) 234*i*.
nitrate, thermal expansion, X-ray determination, (4) 121*a*.
peroxide, electric resistivity, (5) 180*j*.
selenide, α-, as degenerate semiconductor, (1) 25*a*.
Ag^+ ions, diffusion coefficient in glass, measuring with ^{110}Ag radioisotope, (6) 210*c*.
Ag_3AsS_3 and Ag_3SbS_3, optical quality, synthesis, (8) 299*g*.
$Ag_xCd_{1-x}Cr_2Se_4$, magnetic semiconductor, helicon-spin wave interaction in, (1) 30*f*.
$AgIn_5Te_{11}$, semiconducting properties, (4) 149*b*.
sulfide, heat capacity, (11) 385*c*.
systems. See *Systems*.

Silvering. See *Glass*.

Single crystals. See *Crystals*.

Sintering, activation energy in, (10) 349*h*.
of alloys NbC-Fe, NbC-Ni, and NbC-Co, liquid-phase, carbide grain growth during, (10) 350*j*.
of Al_2O_3, pure, microstructural changes during, (5) 177*g*.
behavior, anomalous, revealed by in situ electron microscopy, (1) 25*h*.
of compressed body from dehydration of $Mg(OH)_2$, (1) 26*h*.
of fine structure of polycrystalline MgO during, (7) 263*f*.
$BaTiO_3$, kinetics, (7) 255*d*.
of BeO, effect of water vapor, (5) 177*f*.
of BeO: IV, mechanism during hot-pressing, (11) 374*d*.
carbides, (2) 56*e*.
of cerium oxide, (1) 36*d*.
of clays, importance of measuring macroporosity during, (6) 233*f*.
changes in pore systems associated with, (1) 25*e*.
characteristics, of oxide-ceramic materials based on MgO-Al_2O_3-spinel, (1) 36*e*.
co-, of UO_2-W cermets, phenomenological aspects, (5) 177*i*.
conditions, effect on magnetic properties of Mn-Zn ferrite, (2) 62*f*.
of corundum, effect of additions, (5) 177*c*.
control method and apparatus, in conveyor type sintering machines, P (1) 23*b*.
data, new method of obtaining volume, grain-boundary, and surface diffusion coefficients from, (9) 325*d*.
diamond particles, P (1) 1*j*.
diffusion-controlled, initial stages, time and length corrections in analysis of, (6) 239*b*.
filter technology, theoretical bases, (1) 39*g*.
in gas discharges, (9) 329*g*.
of glass powder compacts, effect of water vapor, (4) 117*g*.
of glass powder with cordierite composition, (1) 36*h*.
of glass powders, during constant rates of heating, (4) 118*c*.
high density, of pure $BaTiO_3$, (2) 67*h*.
of high-quality ceramic dielectrics in reducing atmosphere, (2) 62*g*.
high temperature treatment and cooling apparatus for granular or divided solid products utilizing fluidized layer, P (5) 186*a*.
in iron oxides at high temperatures, (8) 291*b*.
isothermal, of low-fired MgO obtained from crystalline $MgCO_3$, kinetics, (5) 196*f*.

Sintering *(continued)*
kinetics, of $MgAl_2O_4$, (10) 355*h*.
kyanite concentrate in rotary-type furnaces, (10) 348*h*.
of lime, (8) 287*b*.
liquid-phase, of two-phase alloys in NbC-Co system, microstructural development during, (8) 295*d*.
of low alkaline charges, (7) 268*c*.
from macroscopic aspect, (6) 237*f*.
of MgO: I, calcination of Mg carbonate and magnesite containing ZnO, (4) 154*c*.
effect of Cr_2O_3, (4) 132*a*.
effects of crystal habits of $Mg(OH)_2$ and additions of Fe_2O_3 and SiO_2, (1) 28*g*.
high purity, (11) 372*h*.
highly pure, with additives, (8) 297*d*.
of metallurgical dolomite with mill scale to improve quality, (1) 12*h*.
of mixtures in systems ZrO_2-$MoSi_2$ and ZrO_2-SiC, and properties, (1) 36*h*,
of oxides sprayed with oxyacetylene torch, (2) 57*g*.
parameters, identification and measurement, (6) 233*c*.
plasma, P (6) 225*d*.
of porous glass, benzene adsorption by heat-treated porous glasses, (5) 173*c*.
of powdered ice, (1) 36*i*.
pressure, of ceramics, B (7) 272*g*.
of $CuCr_2Se_{4-x}Br_x$ spinels, (1) 17*h*.
of GaAs, (6) 236*j*.
for production of dense bodies from carbides, borides, nitrides, silicides, oxides, and cermets, (11) 373*c*.
of NaCl and ionic materials, comments, (1) 26*h*.
process, examination with reference to changes in properties of oxides during, (4) 160*f*.
processes, addition agents for, P (4) 112*a*.
properties of magnesia-dolomite clinker, (7) 251*g*.
reactions during, B (10) 366*d*.
sintered articles, P (4) 107*c*.
of improved strength, iron powder for forming, P (4) 106*c*.
with refractory backing layer, P (8) 280*a*.
sintered bodies, exaggerated grain growth in, (9) 326*c*.
sintered parts, high porosity, P (10) 347*a*.
of SnO_2: I, influence of addition of bismuth oxide, (4) 154*g*.
of trigonal iron(III) oxide at low temperatures, (4) 154*i*.
under applied pressure, densification process associated with, theoretical consideration, (4) 160*c*.
under ultrahigh pressure, (4) 154*j*.
of UO_2, development of high density and controlled microstructure in sintered UO_2 pellets, (11) 374*e*.
of UO_2, initial phase, Dorn method in study of, comment and reply, (1) 26*g*.
of UO_2 powders, role of crystallinity, (2) 57*d*.
of vitreous products and refractories in presence of vitreous phase, (6) 211*c*.
of wires by surface diffusion, (1) 39*h*.
of ZrB_2-Mo alloys, (2) 57*j*.
of ZrO_2, problems, (4) 105*f*.
Size reduction. See *Crushing; Grinding.*
Slags, basic, containing CaF_2, sulfide capacities, (7) 245*b*.
basicity, conductometric determination, (2) 54*j*.
blast-furnace, molten, crystallization of phases and decomposition of melilite during cooling of, (6) 231*i*.
standardization, (4) 91*c*.
viscosity properties, (5) 178*f*.
composition, effect on rate of wear of magnesite rotary furnace linings, (2) 55*a*.
converter, rich in Mn, temperature and melting range, (1) 13*j*.
corrosion of casting pit refractories by, (10) 340*j*.
corrosion resistance, of high-fired, fired, and unfired basic brick, (11) 374*f*.
crust, furnace, heat conductivity measurements, (5) 189*a*.
effect, thermochemical resistance of refractories to, (10) 340*g*.
ferromanganese, for making plugging cement, (1) 3*g*.
formation, quicker, in oxygen-blowing steel processes with new lime products, (6) 216*e*.
molten, and molten glass, wettability of refractories by, (5) 174*c*.
penetration, of refractory mortar joints, factors affecting, (1) 12*d*.
phosphorus, for making plugging cement, (1) 3*h*.
red mud, phase transformation in complex processing of, (6) 216*j*.
slagging action of alkali on blast furnace refractories, (11) 374*f*.
thickness, effect on heat loss from ladles holding molten steel, (1) 12*b*.
Slip casting, basic refractory materials, P (4) 107*f*; P (9) 309*a*.
of ceramic objects, to improve properties, (2) 60*i*.
fused quartz ceramics, features, (6) 216*g*.
of MgO with ethanol, (4) 105*i*.
of $MoSi_2$, (2) 57*h*.
Slips. See also *Suspensions.*
apparatus and method for making, P (11) 382*h*.
behavior and hardness indentations in MnSe and MnSe-MnS solid solutions, (9) 329*i*.

Slips *(continued)*
behavior, in US single crystals, electron microscope studies, (1) 28*f*.
casting, ceramic, rheological examination, (8) 280*c*.
ceramic casting, behavior of commercial feldspars in, (6) 219*a*.
in hard-sphere CsCl models, (1) 37*c*.
for hot casting glass articles under pressure, technological properties, (6) 211*e*.
processes, multiple, in $MgAl_2O_4$ at high temperature, (2) 80*g*.
Smelting. See *Metallurgy.*
Soapstone. See *Talc.*
Soda or Soda ash. See *Sodium, carbonate.*
Sodalites, noselite [$Na_8SO_4Al_6Si_6O_{24}$], single crystals, interpretation of superlattice, (9) 323*d*.
photochromic, ESR investigation, (4) 135*a*.
synthetic photochromic, (6) 238*h*.
Sodium. See also *Alkalis.*
aluminate, reaction with dicalcium silicate, (1) 3*a*.
aluminate, solutions, heat capacity at 25°–90°, (1) 30*a*.
aluminosilicates, hydrated, by hydrothermal metamorphosis of nepheline-carnegieite minerals, (6) 233*a*.
aluminosilicates, hydrated, relating to nepheline-carnegieite minerals, relations among crystal lattices and thermal transformations, (6) 233*c*.
borates, anhydrous, heat of formation, (1) 30*c*.
borohydride, nuclear magnetic relaxation studies of internal rotations and phase transitions in, (11) 386*j*.
bromide, partial thermodynamic functions in bromide-chloride mixtures, (8) 290*c*.
bromide, temperature dependence of *F*-center absorption in, (9) 331*j*.
-calcium hydroaluminosilicate, conditions of formation and physicochemical properties, (8) 289*d*.
-calcium silicates, crystalline, high-temperature heat contents and entropies, (5) 195*c*.
carbonate, bulk density, increasing by adding Ca and Mg ions prior to precipitation, P (11) 382*b*.
hydrates, disorder in, thermodynamic investigation, (9) 332*h*.
preparation from Wyoming trona, and product, P (5) 191*c*.
reaction with kaolinite, kinetic and electron optical studies, (8) 293*j*.
for treatment of high silica fiber products, (10) 340*b*.
chloride, adsorption of water on, effect of prior exposure to HCl, CO_2, and water vapor, (4) 126*h*.
catalytic action, on decomposition of dolomite for manufacture of Mg oxychloride cement, (2) 43*i*.
crystals, containing cavities, work of fracture in, (2) 84*f*.
crystals, containing Ag colloids, thermal conductivity in, (1) 39*j*.
crystals, dissolution kinetics at dislocation sites in, (6) 231*h*.
crystals, with high concentration of copper, absorption and emission phenomena in, (6) 230*f*.
crystals, movement of dislocations in, in electric field, (5) 197*h*.
crystals, pure and Mn-doped, ionic conductivity in, (8) 293*j*.
crystals, structure of cleavage surfaces around precipitates in, (1) 38*f*.
crystals, thermal diffusion of Sr ions in, (4) 160*e*.
dispersion of divalent cations in, (8) 298*h*.
doped substrates, epitaxy of Ag and Au on, (2) 62*j*.
effect on structure formation of lime-clay suspensions, (7) 253*f*.
electronic structure and molecular properties, (2) 84*e*.
influence of orientation on properties of grain boundaries in, (1) 31*a*.
interaction with chloride of Eu(III) and Tb, (7) 267*d*.
lattice dynamics, X-ray study, (4) 164*b*.
polycrystalline, mechanical properties, (2) 80*j*.
pressure sintering, comments, (1) 26*h*.
purified crystals, lead ions diffusion in, (4) 131*e*.
single crystal cleavage surface covered by amorphous C layer, decoration by vacuum condensation of PbS, (6) 231*c*.
single crystals, condensation coefficients of Au on, (4) 129*j*.
single crystals, doped, precipitation hardening and dislocation locking in, (2) 81*j*.
single crystals, evaporation mechanism, (9) 330*e*.
single crystals, latent hardening, work hardening, and plastic deformation, (2) 79*c*.
single crystals, Mn-doped particle hardening in, (2) 81*j*.
single crystals, vaporization rate, effect of dislocations, (2) 75*j*.
substrates, unexpected effects of forced high nucleation densities by flash evaporation of gold on, (9) 311*i*.
work hardening and latent hardening in, (2) 84*f*.
determination in high purity water with sodium-responsive glass electrodes, (9) 315*c*.

Sodium *(continued)*
disodium hydrogen phosphate, hydrates, thermodynamic investigation of disorder in, (5) 201*c*.
distribution, in Na silicate glasses, studies by chemical difference method, (8) 276*j*.
fluoride, Co^{2+}-doped, absorption spectrum, (6) 230*f*.
F-aggregate centers in, (4) 136*d*.
neutral and acid solutions, reaction with kaolin, (2) 73*c*.
and NH_4VO_3, effects on zircon formation, (5) 177*g*.
fluoroborate, heats of formation, (9) 322*d*.
halides, thermal reactions, (5) 201*i*.
hexafluoroantimonate, X-ray irradiated polycrystalline and single-crystal, ESR, (4) 135*b*.
humus, effect on structure formation and mechanism of development of deformations in aqueous dispersions of montmorillonite, (7) 262*d*.
hydroaluminosilicate, of sodalite type, crystallizing at 280°C in system Na_2O-Al_2O_3-SiO_2-H_2O, properties, (8) 296*h*.
hydroxide, reaction with alumina hydrate powders, (4) 152*b*.
indium silicate, crystal structure, (4) 130*h*.
iodide, single crystals, fluorometric determination of thallium in, (6) 226*h*.
ions, exchange and diffusion in Pyrex glass, (2) 49*c*.
-kaolin and NaCl in kaolin suspensions, apparent and partial molal volumes, (8) 288*j*.
lanthanide titanates, Eu^{3+}-activated fluorescence, (5) 194*h*.
liquid, reactions with transition-metal oxides: I, dioxides of Mo, W, and U, (1) 35*i*.
and Li M_A centers in KCl, (4) 155*d*.
metaphosphate, P (11) 382*h*.
metaphosphate, reaction with ferric oxide, (8) 297*e*.
migration in SiN films, (10) 361*g*.
molybdate-MoO_3 mixtures, at 970°K, calorimetric study, (11) 383*e*.
montmorillonite, electron microscopy, (10) 352*j*.
mordenite, in pebble form, hydrothermal synthesis, (8) 293*g*.
natroalunite, in Upper Cretaceous sedimentary rocks, north central Texas, (6) 229*e*.
nitrate, crystalline, Raman spectrum, (5) 199*i*.
thermodynamics of λ transition in, (5) 202*c*.
ultrasonic and infrared studies of lambda transition in, (6) 239*d*.
nitrite, ferroelectric, charge distribution of NO_2^- radical in, (5) 192*d*.
perchlorate, *M*, solubility and dissolution kinetics of precipitated amorphous SiO_2 in, at 25°C, (8) 297*i*.
phosphate, binary, surface tensions and molar volumes, (4) 158*g*.
phosphates, vitreous, thermal conductivity, (4) 97*f*.
and potassium, determination after separation from each other and from other ions by ammonium phosphomolybdate and other ion exchangers, (7) 259*j*.
-potassium niobate-tantalate, single crystal and polycrystalline, P (4) 116*a*.
potassium-, ratios in aqueous solutions and coexisting silicate melts, (5) 198*f*.
rare-earth tungstates, energy transfer mechanisms involving trivalent Er and Tb or Tm in, (4) 144*a*.
energy transfer mechanisms involving trivalent Tb and Nd in, (4) 144*a*.
quenching interactions involving first excited states of Gd, Yb, Er, Tm, and Ho in, (10) 359*e*.
scandium titanate, and its isomorphs, crystal chemistry, (11) 383*j*.
self-diffusion, in montmorillonite suspension at equilibrium, (4) 154*e*.
in sodium aluminosilicate glasses, (9) 307*c*.
in sodium silicate liquids, (1) 36*j*.
sesquicarbonate, and carbonate, producing from trona, P (10) 349*d*.
silicate, amorphous, with inherent binding properties, P (9) 317*c*.
delayed gelling, and use for, P (7) 262*g*.
hydrolysis: ultracentrifugation in chloride solutions, (1) 30*h*.
silicate hydrates: III, crystal structure of Na_2O·SiO_2·$6H_2O$, and isostructural Na_2O·GeO·$6H_2O$, (7) 268*d*.
in SiO_2 films, studies by neutron activation and radiotracer techniques, (4) 157*a*.
Na^+, diffusion in Na_2O·$2SiO_2$ glass containing NaCl and $NaSO_4$, (9) 306*j*.
mobility in silicogermanate, aluminogermanate, and aluminosilicate melts, electrical conductance study, (2) 76*j*.
self-diffusion in its molten fluoride, (8) 297*d*.
^{23}Na in $NaBrO_3$, nuclear quadrupole frequency, pressure and temperature dependence, (10) 359*a*.
$NaAlO_2$, high-pressure, α-$NaFeO_2$ isotype, (11) 385*e*.
Na_3Sb and Na_3As powders, NMR study, (6) 235*j*.
$NaH_3(SeO_3)_2$ and $NaD_3(SeO_3)_2$ ferroelectric crystals, growth, (4) 137*i*.
NaH_2PO_4, Na_2HPO_4, and Na_3PO_4, heats of formation, (8) 298*i*.
Na_3FeF_6, crystallography, (7) 264*j*.
$Na(Sc,Fe)TiO_4$ isomorphous series, magnetic,

Sodium *(continued)*
ESR, optical, and structural studies, (11) 385*g*.
$Na_2Si_2O_7$, new type of silicate sheet, crystal structure, (4) 130*j*.
systems. See *Systems*.
tin germanium oxide hydroxide, ordered, crystal structure, (4) 130*a*.
triphosphates, pyrophosphates, sodium trimetaphosphate and tetrametaphosphate, heats of formation, (9) 330*e*.
tripolyphosphate, P (6) 230*c*.
Soils, cohesive, permeability coefficient, determination, (5) 190*a*.
cohesive, preconditioning for stabilization with cement, (4) 92*c*.
dry, thermal conductivity, (9) 315*d*.
plastic limit, rapid technique for determination, (8) 285*c*.
stabilized, strength, (5) 190*c*.
Solar batteries or **Solar cells.** See *Cells, photovoltaic*.
Solar furnaces. See *Furnaces*.
Solarization, of soda-potash crystal glass by sunshine, and stabilization, (8) 276*g*.
Solder, braze compositions, for pyrolytic graphite, (8) 279*c*.
mounds, on substrates, P (11) 377*a*.
for rendering noble metal conductive composition nonwettable, P (1) 18*d*.
Soldering. See also *Seals and sealing*.
active, use in making vacuum-tight aluminate glass-to-metal seals, (4) 97*j*.
brazing, P (4) 94*f*; P (5) 178*c*.
carbonaceous materials, and with metal, and brazing material, P (7) 252*e*.
silicon nitride material, alloys for, P (6) 217*f*.
metals and ceramics with grossly different coefficients of thermal expansion, P (5) 172*b*.
vacuum-tight, of metal to ceramic, problems, (5) 181*e*.
Solid solutions. See *Solutions, solid*.
Solid state, chemistry, principles, B (11) 390*f*.
device, with reduced leakage current at *np* junctions over which electrodes pass, P (5) 185*b*.
devices, fabricating by ion implantation, P (6) 221*j*.
element, comprising semiconductive glass composition exhibiting negative incremental resistance, P (9) 314*c*.
element, nonrectifying, P (10) 339*d*.
Fe_3C particles coarsening in, (9) 326*d*.
laser device, using Gd_2O_3 as host material, P (5) 185*b*.
matrix, for display system, P (11) 379*a*.
reactions, between iodides of Ag, K, and Rb, kinetics, (4) 142*f*.
in lithium ferrite, (6) 220*f*.
of MgO and enstatite, for formation of forsterite, (4) 142*j*.
MgO-FeO and MgO-Al_2O_3, electron microscopic observation, (1) 28*h*.
between MgO and Fe_2O_3, kinetics, (4) 142*e*.
in pyrophyllite-nickel (cobalt) oxide systems, (9) 329*i*.
selection of mineralizers for, (4) 154*c*.
of $SrCO_3$ + TiO_2, (9) 329*j*.
between ZnO and Fe_2O_3, (9) 311*j*.
source, continuous 0.532-μm, using $Ba_2NaNb_5O_{15}$, (4) 129*g*.
storage device, P (11) 379*a*.
studies, of oxygen-deficient Ta_2O_5, (11) 387*d*.
of potassium molybdenum bronzes, (11) 387*e*.
of ternary fluorides; synthesis, identification, relationships, and miscibility, (1) 37*g*.
Solidification, of binary eutectic system, heat transfer analysis, (4) 138*i*.
of Bi_2Te_3 and its solid solutions with Bi_2Se_3 and Sb_2Te_3 under influence of ultrasonic agitation, (4) 155*e*.
kinetics, effect of impurities measured by thermal wave technique, (4) 132*j*.
Solids, comminuted and compacted, surface chemical study, (4) 157*j*.
crystalline, point defects in, (4) 150*c*.
dielectric behavior and proton conduction in: I, borax, (4) 131*a*.
finely divided, standard length sample, surface area measurement of, P (11) 381*b*.
finely divided, variable length sample, surface area measurement of, P (4) 122*b*.
-fluid interfaces, free energy of adhesion and equilibrium of contact reactions at: I, perfect solid and fluid, (1) 30*d*.
gas bubbles in, (2) 77*a*.
-gas reaction, quantitative DTA applied to, (8) 297*g*.
gas-, reactions in industrial fluidized beds, (2) 67*h*.
inorganic, energy transfer between trivalent rare-earth ions in, (4) 135*h*.
ionic, dielectric constant, and change with hydrostatic pressure, (1) 27*h*.
/liquid interface, morphology during melting, (4) 145*c*.
/liquid interface temperatures, investigation via isenthalpic solidification, (6) 234*a*.
mixtures of, dry separation, P (8) 287*i*.
molecular, imperfections in, (8) 293*i*.
nonmetallic, indentation deformation, effect of adsorption, (4) 133*b*.
-phase reactions with participation of "carriers" in transfer of volatile compounds of starting compounds, (8) 297*g*.
Solids *(continued)*
porous, structures, effects on diffusion of gases in transition region, (4) 133*g*.
refractory, lubrication at high temperature, (1) 32*b*.
separation, vortical, method and apparatus, P (4) 124*f*.
shock-induced preferred disorder in, (10) 360*g*.
stress distribution in, effect of inclusions on, (8) 291*c*.
surface areas, comparison using adsorption from solution, (2) 70*j*.
surface chemistry, (6) 238*d*.
thermal decomposition, two-stage: II, effects of inert materials, (5) 170*i*.
thermal fatigue in liquid metal, apparatus for measuring, (2) 68*e*.
tunneling phenomena in, B (11) 390*d*,
Sols. See *Colloids*.
Solubility, of Al, in cryolite melts, (1) 37*h*.
of Al in presence of hydroxide, fluoride, and sulfate, (9) 329*j*.
of Sb(III) in chlorapatite, (10) 360*a*.
aqueous, high temperature and pressure data, bearing on stability of silicates, (4) 138*g*.
of calcium sulfate dihydrate in hydrochloric acid solutions, (9) 329*a*.
of carbon in cobalt and nickel, (4) 155*f*.
chromium, in wustite at 1000°C: changes in oxygen activity and lattice parameter, (4) 128*g*.
dependence of Ru volatilization from glass, (10) 338*h*.
hydrothermal, of lithium metagallate in NaOH solutions, (4) 139*b*.
limit, of C in Mo, (1) 37*i*.
of Nb_2O_5 in melts of fluoride salts of Li, Na, and K, (7) 269*b*.
of Ru in silicate and phosphate glasses, (10) 338*i*.
solid, of $FePO_4$ and $CrPO_4$ in $AlPO_4$, (1) 37*e*.
solid, relationships, in NaCl-type uranium compounds, (1) 37*f*.
of solid phases at high pressure, and stability of silica modifications, (1) 37*a*.
studies, aqueous, of high-Al_2O_3 and clay minerals, (8) 288*j*.
of sulfur in alpha iron, (4) 155*f*.
of U in UO_2, (5) 199*j*.
Solutions, crystalline, of monticellite and forsterite, (7) 267*e*.
dis-, of Al_2O_3 in carbon-saturated liquid Fe, (10) 340*h*.
anodic, of copper(I) sulfide and direct recovery of Cu and elemental sulfur from white metal, (4) 126*f*.
of calcined ferric oxides, (4) 132*b*.
of α-$CaSO_4 \cdot \frac{1}{2}H_2O$ in water, (2) 83*b*; (7) 245*d*.
rate of Al_2O_3, in molten iron oxide, (4) 152*i*.
SiO_2, in glass, (10) 338*g*.
of silica particles, spherical, in molten sodium disilicate, (8) 276*d*.
of UC particles in U during post-irradiation annealing, (10) 340*i*.
of zircon in molten glasses, (11) 372*i*.
growth, of AlP, (2) 83*e*.
growth, of II-VI compounds, using tin as a solvent, (8) 298*a*.
molten, chemistry: III, preparation of crystalline tungstates $M^{2+}WO_4$, (6) 231*a*.
theory, conformal, of certain molten salts, (4) 129*e*.
Solutions, solid. See also *Equilibrium studies*.
of alkali halides, (5) 199*g*.
$BaTiO_3$-based, thermal conductivity in phase transformation region, effect of constant electric field on, (4) 132*j*.
of Bi_2Te_3 with Bi_2Se_3 and Sb_2Te_3 under influence of ultrasonic agitation, (4) 155*e*.
carbide-graphite compositions, P (4) 106*j*.
α-chromia-alumina, ESR, (8) 291*h*.
$CuFe_2O_4$-Fe_3O_4 spinel, including $CuFe_2O_4$, eutectoid decomposition, (9) 321*a*.
decay, and structural vacancies in ferrospinels, (10) 361*c*.
ferroelectric perovskite-type, temperature dependence of velocity and absorption of ultrasonic waves in, (4) 159*d*.
formation of lepidocrocite-boehmite, and occurrence in soil, (7) 268*f*.
of hafnium and zirconium monoclinic oxides, optical energy gaps in, (1) 33*h*.
high-quartz phases, from thermally crystallized (Li_2O,MgO)-Al_2O_3-$nSiO_2$ glasses, (1) 7*f*.
homogeneous, in system TlBr-TlCl, change in lattice period and microhardness of, (7) 264*c*.
interstitial, of Zr–O system, ordered arrangement of O in, (2) 81*g*.
iron-bearing, certification of formation, and precise determination of $BaAl_2O_4$ cell, (1) 35*f*.
of lithium oxide in nickel oxide, lattice parameter, variations in, (9) 332*j*.
MgO, optical reflectance spectra of Cr^{3+} in, (11) 370*b*.
MgO-$MgCr_2O_4$ and Al_2O_3-Cr_2O_3, thermal conductivity, temperature and concentration dependence of, (6) 238*h*.
MnSe-MnS, slip behavior and hardness indentations in, (9) 329*i*.
metastable crystalline, with quartz structure in oxide system Li_2O-MgO-ZnO-Al_2O_3-SiO_2, (9) 306*f*.
Solutions, solid *(continued)*
metastable quartz, in MgO-Al_2O_3-SiO_2 glasses, crystal growth, (7) 264*h*.
olivine, X-ray diffraction study, (10) 363*e*.
oxide, activity/composition relations in, (5) 200*c*.
oxide, thermal expansion anisotropy, (9) 332*c*.
periclase, containing Li^+ and R^{3+} ions, (9) 326*d*.
periclase-chromite, lattice spacings, (4) 142*h*.
KCl-RbCl, mobility of cation vacancies in, (9) 325*f*.
KCl-NaCl, anomalies in structure, as revealed by enthalpies of crystallization, (10) 350*c*.
pyrite, of type $Fe_xCo_{1-x}S_2$, $Co_xNi_{1-x}S_2$, and $Cu_xNi_{1-x}S_2$, preparation, (7) 268*d*.
of rare earth oxides, behavior in binary systems during crystallization by verneuil method, (9) 318*g*.
refractory oxide, possessing fluorite, pyrochlore, and perovskite structures, anionic conduction in, (10) 349*h*.
safflorite-loellingite, series, (10) 359*i*.
Na-Li niobate, ceramics, with small Li concentration, properties, (1) 17*j*.
β-spodumene, synthetic, and β-spodumene—silica, thermal expansion, (1) 9*e*.
$SrTiO_3$ containing La_2O_3, dielectric relaxation in, (9) 320*a*.
of system CaO-"FeO"-SiO_2 in contact with metallic iron at 1080°C, activity-composition relations in, (1) 24*i*.
in system $2CaO \cdot SiO_2$-$Na_2O \cdot CaO \cdot SiO_2$, (10) 360*j*.
in system $CaSiO_3$-$CaGeO_3$, (7) 269*a*.
in system (Na-Ag)Cl and (Na-Ag)Br, heats of formation, (1) 30*d*.
synthetic diopside-hedenbergite, unit-cell parameters, (10) 363*d*.
(Th,U)C, electrical properties, (10) 341*e*.
ThO_2-CaO, creep, (2) 75*f*.
ThP-UP, preparation and properties, (4) 150*h*.
of SnTe and PbTe, (2) 83*d*.
TiO_2-Nb_2O_5, microhardness, (11) 386*b*.
of transition metal nitrides and oxynitrides, and preparation, P (4) 107*j*.
of tricalcium silicate, chemical and structural studies, (2) 43*j*.
between tricalcium silicate and tricalcium germanate, (8) 297*g*.
WO_3-ReO_3, preparation and properties, (4) 150*d*.
of uranium oxide, thermodynamic study: I, uranium oxide-thorium oxide; II, uranium oxide-yttrium oxide, (4) 161*b*.
Y_2O_3-ZrO_2, defect structure, (6) 231*d*.
ZnSe-ZnTe, growth in Te_2 atmosphere, (10) 354*d*.
ZrO_2-CaO, electrical conductivity at elevated temperatures, (6) 232*j*.
ZrO_2-CaO and ZrO_2-Y_2O_3, cubic, lattice constants, (6) 234*f*.
Sonics, method and apparatus for grinding rock material to powder, P (6) 230*d*.
ultra-, cleaning, (2) 67*d*.
devices, glass bonding medium for, P (4) 98*h*.
devices, isostatically hot-pressed sodium-potassium niobate transducer material for, (1) 17*d*.
disaggregations of sandstones and siltstones, (8) 286*b*.
effects on diffusion, (4) 157*f*.
measurement of degree of dispersion of suspended particles, (2) 71*h*.
method for producing phase transitions in materials at high pressures, P (5) 186*f*.
properties in solids at high temperatures, gold-indium bond for measurement of, (7) 260*e*.
pulse echo method and apparatus for detecting flaws in materials, P (10) 348*a*.
studies on alkali-borosilicate melt—spectrum of relaxation times and fluctuation theory, (4) 97*e*.
test results, correlation and anlysis, in evaluating reinforced resin laminates, (11) 380*b*.
use in determining optimum steam-curing period for concrete, (8) 274*d*.
Sorel cement. See *Cement, magnesium oxychloride*.
Sorption. See also *Absorption; Adsorption*.
of α-amino acids by copper montmorillonite, (7) 269*e*.
of benzene on SiO_2 gel, (10) 360*f*.
of ethylamine, on silica and silica xerogel, (1) 37*d*.
fission induced, of krypton in UC, (9) 321*e*.
isotherm, of water vapor by montmorillonite surface, applicability of BET equation, (7) 267*e*.
in organo-clays, (1) 37*f*.
properties, of aluminosilica gels, (1) 37*h*.
of water, by porous glass, role of surface boron as adsorption center for, (4) 97*e*.
water, studies on rutile surfaces, bare and silica-coated, (1) 30*d*.
Sound, second, in nonmetallic crystals, (2) 84*f*.
ultra-, effect on mechanism of formation of coagulation structures in aqueous dispersions of tremolite and hydromica, (7) 267*b*.
Spacecraft, coatings to control temperature and/or reflectivity of, P (6) 208*b*.
rocket combustion chamber, P (11) 375*c*.
rocket insulation, elastomeric composition containing chromic oxide for use as, P (5) 178*f*.

Spacecraft *(continued)*
rocket motor throat insert, tungsten oxide coated, P (4) 108*a*.
rocket nozzle, P (6) 218*e*.
rocket nozzle, noneroding, P (7) 252*j*.
Spalling. See *Refractories*.
Spark plugs, with annular heat dam recess in insulator nose, P (8) 280*e*.
and seal for, P (2) 66*h*.
Specific gravity. See *Density*.
Specific heat. See *Heat, capacity*.
Specific surface. See *Surface*.
Specifications, and test methods in refractories industry, (6) 216*j*.
Spectra, absolute reflective, of barium titanate, (1) 16*b*.
absorption, of CdTe, effect of high electric field, (5) 193*h*.
of Co^{2+}-doped NaF, (6) 230*f*.
of Co^{2+} and Ni^{2+} in MgO, (2) 80*h*.
of first row transition metal ions in phosphate glasses, (4) 94*g*.
and fluorescence, of trivalent Mo in aluminoborophosphate glasses, (8) 275*i*.
of Np^{4+} in single-crystal ThO_2, (11) 383*b*.
of Ni^{2+} ions in spinel, (11) 383*b*.
of NiO, fine structures in, (1) 29*g*.
of KMnF$_3$ and RbMnF$_3$, fine structure in, (4) 136*h*.
acoustic paramagnetic resonance, of chromous ions in MgO, (1) 24*h*.
cathodoluminescence, and coordination of Mn^{2+}, Fe^{2+}, and Cr^{3+} in β-LiAlSiO$_4$, (10) 350*c*.
crystal, 80°K, of $Ca_5(CrO_4,PO_4)Cl$, (8) 290*b*.
electron absorption, of irradiated silicate glasses, (8) 277*a*.
EMR, of MnCl$_2$-LiCl-KCl eutectic mixtures, (10) 352*i*.
EPR, of Cu^{2+}-CaO, at 1.2°K, small tunneling effect in, (5) 199*g*.
of doped ferroelectric Rochelle salt, effect of applied electric field on, (4) 132*h*.
of Fe^{3+} in synthetic brown quartz, (11) 384*j*.
of radicals formed when NO_2 is adsorbed on MgO, (5) 194*e*.
ESR, of Er^{3+} and Yb^{3+} in SrCl$_2$ single crystals, (6) 232*c*.
of gamma-ray-irradiated phosphate glasses and compounds—oxygen vacancies, (1) 7*a*.
of sodium borate glass irradiated by ultraviolet light, (1) 7*b*.
ESR absorption, of AsO_2^{2-} molecule-ion in γ-irradiated single-crystal calcite, (10) 353*a*.
of CO_3^- molecule-ions in single crystal calcite, motional effects in, (2) 80*f*.
of Mn^{2+} in single-crystal calcite, superhyperfine interaction due to ^{13}C in, (8) 299*c*.
of Y^{3+}-stabilized Co_3^{3-} molecule-ion in single-crystal calcite, (5) 194*d*.
electronic, of diatomic molecules, magnetic hyperfine interactions in: I, rotational structure of absorption bands of gaseous BiO; II, in Hund's case (c) and spectrum of BiO, (1) 32*e*.
electronic absorption, of Ni^{2+} in CaO, (8) 291*j*.
emission, of impurity activated (Zn,Cd)(S,Se,Te) phosphors: II, silver activated phosphors, (1) 29*f*; III, self-activated phosphors, (4) 135*g*.
emission, of Ti, TiO_2, and Mn, μ-atomic Lyman and Balmer series in, (4) 145*e*.
energy, of densified silica glass, (7) 247*j*.
far-infrared, of Al_2O_3:V^{4+}, (8) 292*f*.
far infrared absorption, of plagioclase feldspars, (9) 321*c*.
infrared, of aryloxysilanes, investigation of Si-O bond, (5) 195*h*.
of borohydride ions in alkali halide single crystals, (4) 140*g*.
of clay minerals and adsorbed substances, (7) 259*g*.
of foreign molecules in beryl, (4) 140*h*.
of Indian bentonites, (10) 355*g*.
of $FeBO_3$, (2) 83*g*.
of powders by means of internal reflection spectroscopy, P (6) 227*h*.
of rubidium borates of varying compositions, (4) 140*h*.
of SeO_2, (2) 79*c*.
of SiO_2-GeO_2 glass, (8) 276*c*.
of SiN deposited on GaAs, (4) 110*j*.
of tetrachlorides and tetrabromides of Se and Te, (11) 385*h*.
infrared absorption of CdTe, (4) 140*g*.
of important oxides, (4) 140*e*.
of stannic oxide and TiO_2 powders, (10) 355*i*.
for study of structure of strontium silicate glasses, (7) 247*d*.
infrared reflection, of molten fluoride solutions—hydrolysis of Ta(V) in potassium fluoride-lithium fluoride, (2) 79*e*.
infrared transmission, of perovskite fluorides, (4) 140*j*.
luminescence, of crystalline phosphors, for determination of rare earths in Y_2O_3, (2) 75*e*.
luminescence, of rare earth ions in SrTiO$_3$, BaTiO$_3$, and other perovskites, vibronic structure in, (2) 84*e*.
Mn$K\beta_5$, and MnK absorption edges of manganese oxides in various valence states, (9) 325*h*.
microwave, of cyclic $H_2B_2O_3$, (4) 144*f*.
microwave, of RbOH and RbOD, (10) 361*d*.
Moessbauer, of ^{57}Fe in oxidic spinels containing Cu and Fe, (10) 357*h*.
Moessbauer, of natural minerals, (4) 145*e*.
Spectra *(continued)*
Moessbauer hyperfine, of Fe^{3+} in corundum—magnetic- and crystal-field effects, (2) 80*e*.
NMR, of pair-powders, least-squares analysis, (8) 294*d*.
optical, of Cr^{3+} impurity ions in ferroelectric LiNbO$_3$ and LiTaO$_3$, (11) 386*a*.
of Cr^{3+} ions in spinels, (6) 235*b*.
of Mn-doped Sr_2VO_4Cl, (4) 158*f*.
of Pu in CaF_2, (4) 147*c*.
of 3*d* transition metal ions in MgO·3.5Al$_2$O$_3$ spinel, (8) 295*g*.
of Yb in CdF_2, (4) 147*e*.
optical absorption, of coupled Nd^{3+} ions in NdCl$_3$ and NdBr$_3$, (4) 147*g*.
of crystal-field transitions in MnO, (11) 386*a*.
and optical Zeeman effect in $CaWO_4$:Yb^{3+}, (4) 147*g*.
optical reflectance, of Cr^{3+} in MgO solid solutions, (11) 370*b*.
pair, in BP, (2) 81*h*.
paramagnetic ESR, of higher vanadium oxides, (6) 235*d*.
paramagnetic resonance, of O^- trapped in alkali iodide crystals, (8) 296*b*.
polarized, of Eu^{3+} in YPO_4, (9) 327*i*.
polarized optical absorption, of tourmaline, cordierite, chloritoid, and vivianite—ferrous-ferric electronic interaction as source of pleochroism, (9) 327*g*.
properties, of rare earth phosphates, (10) 358*f*.
Raman, of BaClF, BaBrF, and SrClF, (8) 297*c*.
of crystalline NaNO$_3$, (5) 199*i*.
of fused In and Bi chlorides, (9) 328*b*.
of α-quartz at high pressures, (10) 359*g*.
of SrTiO$_3$, (4) 152*d*.
of SrTiO$_3$, temperature dependence of, (4) 159*f*
of SrTiO$_3$ and KTaO$_3$, temperature dependence of, (4) 159*c*.
of rare earth vanadates, (10) 360*i*.
reflectance, of tungsten bronzes, (9) 328*i*.
reflectivity, of $Cd_{1-x}Zn_xS$ single crystals, (4) 153*g*.
of relaxation times in GeO_2 glass, (1) 9*b*.
of relaxation times and fluctuation theory—ultrasonic studies on alkali-borosilicate melt, (4) 97*e*.
spin echo, of manganese ferrite at liquid helium temperature, (8) 298*e*.
of SrF_2:Sm^{2+} and $SrCl_2$:Sm^{2+}, optically pumped, (8) 298*d*.
ultraviolet, of nitrate ion in molten mixtures of alkali metal nitrates, (5) 202*c*.
ultraviolet absorption, of SnBr and SnI, (9) 332*f*.
vibrational, of fused SiO_2, interpretation, (4) 140*i*.
of glasses of alkali metal nitrates with group IIA and IIB metal nitrates and with $ZnCl_2$ and water, (5) 174*a*.
of ionic liquids: II, pure alkali metal nitrates, (5) 203*c*.
of molten salts: V, infrared and Raman spectra of molten sulfates, (10) 363*i*.
of silacyclohexane derivatives and Si-C stretching frequencies of various-membered silacycloalkanes, (5) 203*b*.
of zinc halides, (6) 239*e*.
visible and ultraviolet emission and absorption, of MgAl$_2$O$_4$:Cr, (5) 203*c*.
X-ray emission, fine structure, in microvolumes of Ti and Ti oxides, effect of chemical bonds on, (4) 132*i*.
X-ray K emission, of Cr in various Cr compounds, (10) 363*f*.
X-ray fluorescence, of Al$_2$O$_3$, MgO, SiC, and SiO_2, relative intensities of $K\alpha$ satellites, and chemical bond, (4) 153*h*.
Zeeman, and stress in Bi-doped and undoped CaO, (7) 269*a*.
Spectrochemical analysis. See *Analysis*.
Spectrography, analysis, of impurities in (U-Pu)-O$_2$, (8) 285*e*.
X-ray, sample holder containing adjustably mounted internal reference standard, P (11) 381*f*.
Spectrometer, mass, for analysis of distribution of gaseous impurities in materials by laser beams, (4) 118*j*.
mass: II, mass-analyzer systems; detectors, (8) 285*j*.
monochromator system, with selective diffraction grating system, P (4) 122*b*.
multichannel emission, for rock analysis, (1) 20*i*.
wavelength programed monochromator device, P (11) 381*e*.
X-ray fluorescence, specimen changer for, P (4) 122*a*.
Spectrometry, analysis, of powdered samples using dc arc fusion technique, (4) 121*i*.
atomic absorption, for determination of arsenic, with electrodeless discharge lamp as source of radiation, (10) 347*e*.
atomic absorption, Mg spinel interferences in air-acetylene vs nitrous oxide-acetylene flames in, (8) 285*h*.
determination of Cu(II) ion by N-8-quinolyl-p-toluenesulfonamide, (8) 285*e*.
mass, analysis, spark source, preparation of powder samples for, (10) 347*g*.
determination of dissociation energy of molecule BO, (9) 324*i*.
evidence for molecules UC and CeC and predicted stability of diatomic carbides of transition metals, (11) 385*j*.
Spectrometry, mass *(continued)*
of evaporaion of UO$_2$ and UC, (1) 32*j*.
high-temperature, study of system neodymium-carbon, (1) 195*e*.
at high temperatures: XI, sublimation pressure of NdF$_3$ and stabilities of gaseous NdF$_3$ and NdF, (2) 80*i*; XII, stabilities of Dy, Ho, and Er subfluorides, (4) 143*d*; XIII, stabilities of Sm, Eu, and Gd mono- and difluorides, (5) 196*e*; XIV, vapor pressure and dissociation energy of AgF, (6) 234*i*; XV, sublimation pressures of Cr, Mn, and Fe trifluorides and heat of dissociation of Fe_2F_6(*g*), (7) 267*a*; XVI, sublimation pressures for TiF$_3$ and stabilities of TiF_3(*g*) and TiF(*g*), (8) 294*f*; XXII, stabilities of Ta pentafluoride and Ta oxytrifluoride, (9) 324*i*; XXIV, thermodynamics of vaporization of SnF$_2$ and PbF$_2$ and dissociation energies of SnF and PbF, (10) 356*j*.
investigation of hydrogen reaction with graphite at 1900°-2400°K, (11) 386*a*.
studies of laser-induced vaporization: I, selenium; II, bismuth-selenium system, (5) 196*f*.
study of rhenium-oxygen system, (10) 356*j*.
of vaporization of refractory compounds, (5) 196*f*.
of zirconium diboride, (1) 32*a*.
α-ray, for study of cation diffusion in UO_{2+x} and ThO_2, (8) 298*f*.
X-ray, determination of K_2O and CaO in mineral standards by decomposition method, (6) 227*f*.
Spectrophotometers. See also *Photometers*.
for rapid analysis with deflection means to prevent vortex formation, P (4) 122*a*.
three-crystal, for X-ray total reflection studies of Ge, Au, and glass, (4) 121*c*.
Spectrophotometry. See also *Photometry*.
of Al$_2$O$_3$, (4) 120*b*.
atomic absorption, analysis by, application to study of silicates, (5) 186*i*.
for analysis of ferrosilicon, feldspars, and iron ores and slags, (9) 314*j*.
for analysis of inorganic siliceous materials: IV, of cements, clinkers, raw mixes, and siliceous limestones, (8) 284*i*.
for cement analysis, (7) 259*g*.
in ceramic analysis, evaluation of commercial spectrophotometers, B (4) 165*b*.
for determination of vanadium in silicate materials, (7) 259*j*.
for determination of vapor pressures of metallic elements, (1) 20*i*.
and hydrofluoric acid decomposition technique for analysis of inorganic siliceous materials: I, analysis of silicate rocks, (5) 186*j*.
determination, of Ba and Sr by means of dimethylsulfonazo-III and related compounds, (5) 188*g*.
of coordination ratios in Mg_2TeO_6 and Mg_2InSbO_6 crystal lattices, (9) 329*f*.
of Cu in alkali metals and hydroxides with 4,4′-dihydroxy-2,2′-biquinoline, (8) 285*e*.
of Hf as reduced molybdosulfatohafnic acid, (10) 347*h*.
of Fe in high purity Y_2O_3 with 1-(2-pyridylazo)-2-naphthol, (10) 347*g*.
of Fe with 2-pyridyl-2′-hydroxymethane sulfonic acid, (10) 347*h*.
direct, determination of Cu with thiothenoyltrifluoroacetone, (8) 285*b*.
reaction rate method for determination of Bi using dimeric heteropolymolybdate, (8) 285*f*.
stopped-flow, for differential kinetic analysis of alkaline-earth ions, (8) 284*j*.
studies, on high iron content soda-lime-silica glasses, (1) 8*j*.
Titan Yellow, for determination of Mg in silicate and carbonate rocks, (1) 21*c*.
ultraviolet, for determination of fluoride with Ce(III)- or La(III)- alizarin fluorine in presence of dimethylsulfoxide, (1) 22*g*.
Spectroscopy, analyzing sample by detecting radiation field change as function of radiation power density in sample, P (7) 261*b*.
applied, reviews: Vol. I, B (4) 165*b*.
atomic absorption, atomization of solid samples for, (2) 70*i*.
for determination of trace amounts of Co in Al$_2$O$_3$, (6) 226*a*.
gas burner for, P (6) 227*h*.
to study kinetics of reaction between MgO and SiO_2, (2) 71*a*.
constants, for O_2^- ions in alkali halide crystals, (8) 298*c*.
determination of trace impurities in yttria-alumina garnets, (2) 70*j*.
electromagnetic radiation method for use in, P (9) 315*h*.
infrared, of crystalline silicates, (11) 380*g*.
and selective deuteration, for study of hydroxyl groups in kaolin minerals, (7) 269*e*.
for study of crystallization of lead-silicate glass of 2PbO·SiO$_2$ composition, (7) 269*c*.
for study of metal oxide coatings on glass, (1) 9*d*.
in surface chemistry, B (9) 334*i*.
infrared absorption, and simultaneous thermogravimetric analysis, of gas phases—manganese(II) carbonate thermolysis, (5) 202*f*.
IR-, method, for determination of P and Si in high-P glasses, (2) 69*i*.

Spectroscopy *(continued)*
internal reflection, infrared spectra of powders by means of, P (6) 227*h*.
LEED and Auger emission, for observation of Ag growth on KCl, (8) 281*i*.
microwave, and potentialities for chemical analysis, (4) 120*d*.
molecular, with neutrons, B (10) 364*j*.
NMR, annual review, Vol. I, B (4) 165*j*.
photoelectron, (4) 120*c*.
properties, of uranium oxide fluorides, and structural relation to U oxides, (10) 356*i*.
optical, of CrO_4^{3-} in chlorospodiosite, Ca_2PO_4Cl, (4) 135*j*.
quantitative emission, for determination of minor constituents in limestone and dolomite using high-frequency plasma jet, (9) 315*b*.
study, of Mo^{3+} in bisulfate melt and glass, (6) 211*f*.
uniaxial stress, study of symmetry properties of defects, (8) 299*f*.
visible and infrared absorption, for characterization of beryl and emerald, (8) 289*e*.
X-ray, for determination of valence of Ti and coordination number of Al in glasses, (2) 52*g*.
of spinel-type ferrites and garnets of different compositions and in different states, (4) 164*f*.
ultralongwave, for investigation of B and BN energy structure, (4) 141*c*.
X-ray fluorescence, for supervision of raw materials and finished products in glass industry, (9) 307*g*.

Sphalerite, stoichiometry of, application of density determinations to, (10) 347*c*.

Spheres, micro-, metal oxide, preparation, P (5) 179*e*.
micro-, metal oxide, preparation by ion exchange method, P (7) 262*i*.
sol-gel oxide, preparation, coating, evaluation, and irradiation testing, (4) 150*g*.
$(U,Pu)O_2$, alpha autoradiography, (10) 347*b*.
SiO_2, monodisperse, controlled growth in micron size range, (1) 26*c*.
transient heating or cooling, by thermal radiation at bounding surface, (2) 84*b*.

Spinel. See also *Refractories*.
chalcogenide, cation-anion distances in, (7) 264*b*.
chromium, P (7) 256*i*.
compositions, with type 1/1 cation ordering on tetrahedral sites, (1) 33*c*.
$CuCr_2Se_{4-x}Br_x$, pressure sintering, (1) 17*h*.
$Cu_{0.5}Fe_{2.5}O_4$, formation from $CuFe_2O_4$ and α-Fe_2O_3, (8) 292*j*.
$Cu_{0.8}Mn_xFe_{2.2-x}O_{4+\gamma}$, compensated tetragonal deformation and oxygen nonstoichiometry in, (7) 264*j*.
copper-containing sulfides and selenides, magnetic and electrical properties, (4) 143*e*.
crystals, synthetic, study with scanning electron microscope, (8) 298*j*.
ferrimagnetic, temperature dependence of cation distribution in, (11) 387*j*.
ferro-, structural vacancies and solid solution decay in, (10) 361*c*.
ferrothio-, hydrothermal synthesis, (10) 355*f*.
lattice, ferromagnetic exchange coupling in, (4) 136*d*.
lattice, magnetization process in, (2) 80*g*.
LiV_2O_4, hydrothermal crystal growth and electrical conductivity, (4) 139*d*.
Mg, interferences in air-acetylene vs nitrous oxide-acetylene flames in atomic absorption spectrometry, (8) 285*h*.
magnesium aluminate, plastic deformation in, (8) 296*h*.
microwave phonon attenuation in, (4) 144*d*.
single crystal growth by traveling isotherm technique, (5) 188*d*.
sintered, (1) 13*e*.
$MgGa_{2-x}Mn_xO_4$ and $MgCr_{2-x}Mn_xO_4$, X-ray and neutron diffraction study of Jahn-Teller type of tetragonal deformation in, (10) 363*g*.
MgO-Al_2O_3-, sintering characteristics of oxide-ceramic materials based on, (1) 36*e*.
MgO-Al_2O_3, whiskers, P (10) 343*c*.
MgO-3.5Al_2O_3, optical spectra of 3*d* transition metal ions in, (8) 295*g*.
β-$MnsGeO_4$, modified, stability and crystal structure, (11) 386*e*.
-mullite mixtures, firing, phase transformations in, and charges of cordierite and sapphirine, (6) 238*f*.
Ni^{2+} ions in, absorption spectrum, (11) 383*b*.
olivine-, stability relation, structural basis, (10) 361*b*.
oxide, lattice vibration, effect of crystal deformation, (1) 27*f*.
oxidic, containing Cu and Fe, Moessbauer resonance of ^{57}Fe in, (10) 357*h*.
oxidic, ligand field effect and structure: I, spinel phases containing Ge^{4+}, (10) 356*g*.
single-crystal semiconducting ferromagnetic, magnetoabsorption in, (2) 80*h*.
single crystals, defect structure and mechanical properties, (2) 75*j*.
epitaxial growth of Ge on, (4) 135*c*.
properties of epitaxial silicon layers on, (5) 199*e*.
stoichiometric, heteroepitaxy of Si on, (10) 354*e*.
sulfo-, pressure-temperature study, (1) 35*i*.
in system MgO-Al_2O_3-Al_2O_3, crystals grown by flame fusion, (9) 319*e*.

Spinel *(continued)*
tetragonal, ($MgMn_2O_4$), cation migration in, (10) 350*e*.
titanate, high-pressure decomposition, (4) 138*j*.
Ti-Al, containing Co^{2+} and Ni^{2+} ions, research, (1) 36*e*.
Ti-Cr, containing Co^{2+} and Ni^{2+} ions, formation and color development, (1) 30*b*.
2,6-, light absorption of Ni^{2+} and Co^{2+} in, (7) 267*j*.
ulvo-, $TiFe_2O_4$, Moessbauer study, (2) 80*e*.
variable stoichiometry, growth and characterization, (9) 322*c*.
zinc aluminate, formation, effect of particle size on reaction rate constants in, (4) 133*d*.
Spodiosite, analogs, new, Ca_5VO_4Cl and Ca_5AsO_4Cl, (11) 386*i*.
Spodumene, β-, crystal structure, stereographic projection, (6) 237*j*.
β-, synthetic, and β-spodumene–silica solutions, thermal expansion, (1) 9*e*.
Spraying. See also *Automization*.
of borides and nitrides with plasma torch, (2) 58*a*.
ceramic stock semifinished products, particularly crockery, with varnish, P (5) 180*b*.
composite carbide flame spray material, P (4) 93*j*.
dried bodies of vitrified ceramic tiles, comparison, (6) 219*c*.
electrostatic. See *Electrostatic processes*.
electrostatic device, P (5) 186*f*.
flame, with glass, P (10) 337*b*.
metalizing, P (11) 379*f*.
Mo wire, and process, P (10) 337*c*.
for producing carbide containing materials, P (10) 337*b*.
gun, airless, self-cleaning tip for, P (4) 118*i*.
gun, powder type flame, nozzle and gas mixing arrangement for, P (10) 337*d*.
method, and apparatus to lubricate punch surfaces of tableting machines, P (11) 379*h*.
molybdenum powder for use in, P (2) 46*e*.
nozzle, for dry process enamels, P (1) 5*f*.
plasma, of borides and nitrides, (4) 93*f*.
plasma, ceramics, speciality of new plant, (2) 46*a*.
plasma-gun of borides and nitrides: II, properties of resulting products, (5) 177*j*.
powder, adapter for converting torch to, P (7) 246*d*.
torch, for applying powdered material, P (2) 46*b*.
powder, with explosion-proof hopper construction, P (4) 94*a*.
powder spray, P (7) 246*h*.
powder supply construction for, P (4) 94*a*.
Sputtering, apparatus, stabilized low pressure triode, P (7) 258*a*.
cathode, apparatus for producing plural coatings in confined high frequency generated discharge, P (5) 182*h*.
electrostatic control of electron movement in, P (4) 112*j*.
for forming films of compounds with at least two anions, P (4) 114*f*.
of stoichiometric ZnO films, P (5) 182*i*.
cathodic, from cathodically biased target electrode with rf potential superimposed on cathodic bias, P (11) 376*h*.
for depositing $Cd_xHg_{1-x}Te$ films, (4) 128*e*.
making ferrimagnetic films by, P (7) 257*e*.
for production of cooling module for microelectronic circuits, P (7) 257*i*.
for depositing nickel-iron-manganese ferromagnetic films, P (1) 19*a*.
for depositing thin films of controlled thickness, P (1) 19*b*.
for fabrication of uniform rare earth iron garnet, P (7) 257*c*.
glow discharge cathode, for forming high purity niobium films, P (6) 221*f*.
low power density, on semiconductors, P (6) 221*j*.
of oxide films in plasma anodization of Al, (4) 111*a*.
for preparation of garnet films, (6) 220*j*.
protection, for Ta cathodes in plasma devices, P (9) 314*d*.
reactive, for depositing SiN films, (4) 111*j*.
reverse, selected electrically exposed areas of cathodically biased workpiece, method and apparatus, P (4) 114*g*.
rf, processes, (4) 153*e*.
rf, rate of SiO_2, effect of oxygen, (4) 133*c*.
superimposed rf and dc, for depositing of Ta and Ta_2O_5 (4) 131*c*.
Stability, of acmite in presence of water, (9) 329*i*.
of Al_2SiO_5 polymorphs, (1) 37*j*.
chemical, of glasses in system Li_2O-SiO_2-Li_2O-Al_2O_3-$4SiO_2$, electron-microscope study, (2) 48*g*.
of chloritoid and staurolite, analysis, and equilibria in system FeO-Al_2O_3-SiO_2-H_2O-O_2, (6) 230*h*.
electrical, of metal-nitride-oxide-silicon structures, (6) 236*h*.
field, of cobalt garnet ($Co_3Al_2Si_3O_{12}$), (6) 233*h*.
high pressure, of acmite, (9) 322*f*.
of hydrated aluminum silicates, (9) 329*j*.
of hydrosol of arsenic trisulfide in light of Derjaguin-Landau-Verwey-Overbeek theory, (4) 155*j*.
of $FeBO_3$, (2) 83*g*.

Stability *(continued)*
meta, of high cristobalite in vitreous silica, (8) 295*b*.
of metal tritides-yttrium tritide, (4) 156*a*.
of metamorphic amphiboles—tremolite-ferroactinolite series, (4) 156*a*.
morphological, (10) 357*b*.
of olivine and pyroxene in Ni-Mg-Si-O system, (7) 269*f*.
range, of disthene (cyanite), experimental determination, (6) 232*f*.
of spinel, β-Mn_2GeO_4, (11) 386*e*.
staurolite, in part of system Fe-Al-Si-O-H, (4) 156*a*.
of surface phases, (9) 330*b*.
thermal, of chlorine oxysalts in solid state: I, kinetic study of disproportionation and explosion of chlorites; II, kinetic and derivatographic study of thermal decomposition of metal chlorates, (5) 201*j*.
of chloritoid at high pressure and relatively high oxygen fugacity, (4) 161*b*.
influence of phase composition of ZrO_2 on, (8) 293*a*.
programed tests, of brittle materials, apparatus for, (2) 68*e*.
of Ti-andradite, (9) 331*j*.
of U_2C_3, (9) 330*d*.
volume, of baddeleyite-corundum refractories, (6) 217*c*.
Stabilization, of sheet glass, internal friction studies, (4) 96*h*.
of SiC, cubic, P (2) 59*g*.
of ZrO_2, problems, (4) 105*f*.
Staining, artificial, for precipitational environment and correlation of calcite cements, (11) 380*e*.
glass, and compositions, P (5) 175*i*.
glasses with rare earth elements, (6) 211*h*.
and inclusions, effect on electrical properties of mica, (5) 190*d*.
Stains. See *Color; Pigments*.
Standards, ASTM, on cement; lime; gypsum, B (9) 333*h*.
ASTM, on chemical-resistant materials; clay, concrete, asbestos-cement stone products; mortars, B (6) 240*e*.
on electrical insulating materials, B (6) 240*f*.
on refractories, glass, and ceramic materials; manufactured carbon and graphite products, B (6) 240*g*.
new, for pH scale, (6) 227*f*.
Stannic oxide. See *Tin, oxide*.
Statistical analysis. See *Analysis*.
Steam. See *Moisture; Water*.
Stearic acid, monolayers, thermal desorption from mica and silver, (1) 39*b*.
and octadecylamine, adsorbed, desorption and exchange on steel and glass, (1) 27*c*.
Steatite. See also *Talc*.
irradiation influence on, (2) 60*f*.
Steels. See also *Enameling metals; Iron*.
continuous casting, P (4) 93*j*.
corrosion, in lightweight concrete specimens, (4) 91*d*.
decarburized, testing methods of strength after enamel firing, (1) 5*c*.
desorption and exchange of adsorbed octadecylamine and stearic acid on, (1) 27*c*.
effect of alkaline cleaner composition on removal of drawing and stamping compounds from, (8) 274*j*.
glassed, for breweries, (2) 45*h*.
heat-resistant, problems with, especially in porcelain industry, (10) 337*b*.
improved, for direct-white enameling applications, (1) 4*d*.
liquid 18% Cr-8% Ni stainless, equilibrium between Al and N in, (6) 232*c*.
molten, effect of fireclay and Al in, on dissociation of Zr, (4) 103*i*.
new appliance, for direct-on porcelain enamel, (11) 368*i*.
sheet, cold-rolled low-carbon, degree of development for white direct-on enameling, (5) 171*d*.
Ni pretreatment, (10) 336*i*.
preparation for enameling, PEI Bulletin P-307, (1) 5*f*.
preparation for enameling, survey, (1) 5*d*.
pretreated, for porcelain enameling, (7) 246*g*.
surfaces, effect of gases on, (10) 336*i*.
for sheets, to be enameled by single-coat method, production, P (4) 94*e*.
sheet ware, for enameled utensils, evolution, (6) 207*g*.
strength problem, (8) 275*e*.
strip, descaling in aqueous organic chelating bath using alternating current, P (5) 172*b*.
strip, pickling, and regeneration of contact acid, P (8) 275*h*.
vacuum degassing process for, and refractories used, (7) 252*a*.
viterous enameling, and method of making, P (2) 46*d*.
Stereography, projection, for monoclinic ZrO_2, (7) 269*i*.
projection, of β-spodumene crystal structures, (6) 237*j*.
Stoichiometry, effect on lattice deformation of CoO scales, (9) 320*b*.
effect on yield stress of TiC and TiO_2, (2) 76*e*.
influence on lattice parameter in Fe_3O_4, NiO, and Ni-Fe ferrite, (10) 344*g*.
of Li metaniobate single crystals, (9) 330*i*.
of luminescent apatites, (4) 156*b*.

Stoichiometry *(continued)*
melt, Curie temperature, birefringence, and phase-matching temperature variations in $LiNbO_3$ as function of, (1) 26*e*.
non-, in CdS crystals grown by different methods, (10) 357*g*.
oxygen, in spinels $Cu_{0.5}Mn_xFe_{2.5-x}O_{4+\gamma}$, (7) 264*j*.
in oxygen-rich UO_2, at high temperatures dependence of flow stress on, (4) 131*c*.
in rare-earth aluminum borates, (4) 146*h*.
in ternary oxides with fluorite structure, (5) 197*g*.
of TiO_2, (5) 194*j*.
sphalerite, application of density determinations to, (10) 347*c*.
Stones. See also *Rocks*.
crushed, resources of Devonian and Silurian carbonate rocks of Indiana, (9) 316*h*.
ornamental, apparatus for cutting, grinding, and polishing, P (9) 314*g*.
Stoneware, ceramics, pressed, Rovenskie basalts as raw materials for, (6) 219*d*.
earthenware, and porcelain, (6) 219*e*.
salt-glazed, from Muehlendyck pottery center, (7) 244*b*.
Strains, analysis, at fracture of brittle solids with high densities of microcracks, (10) 349*h*.
in ceramic articles, influence of firing, (7) 253*i*.
in diamond surfaces, abraded, (1) 38*a*.
elastic, measurement in interior of crystalline materials by X-ray diffraction, (9) 315*e*.
gage, molded polyester resin, for measuring strain of hardening cement mortar, by electrical method, (1) 3*e*.
measurements, in system $MgO-Al_2O_3-Cr_2O_3$, (6) 234*d*.
permanent, produced by experimentally induced "natural" intragranular flow in quartz and quartzite, (6) 232*f*.
polarizability constant, measure of ion overlap in crystals of NaCl structure, (6) 237*j*.
residual, in sapphire rods and boules, (2) 82*d*.
in TaC due to composition gradients, X-ray measurement, (6) 239*g*.
in VC, measurement and its significance, (5) 177*f*.
Stratifiers. See *Concentrators; Separators*.
Strength, of autoclave-hardened bodies, effect of slaked lime, siliceous materials, and blast-furnace slag mixtures, (4) 92*i*.
bend, of HfB_2 and ZrB_2, (4) 156*c*.
bending, of humus-containing clays, increasing by adding calcium hydroxide, (11) 382*c*.
of ceramic-glass materials, two-phase, (4) 97*h*.
compressive, of calcareous cements, (4) 92*h*.
of concrete, relation with effective cement-water ratio calculated from hydration rate of cement, (7) 245*a*.
of TiO_2, (5) 194*j*.
criterion for sands, (5) 190*a*.
of decarburized steel, testing methods, (1) 5*c*.
and deformation characteristics of anisotropically consolidated kaolinite clay, (5) 190*a*.
dielectric, of porcelain, effect of active admixtures, (7) 253*f*.
dry, by methylene blue adsorption, (1) 15*d*.
dry, of porcelain bodies, influence of drying degree, (2) 60*e*.
of E-glass fibers, effect of environment and temperature, (4) 95*c*.
of enameled glass, (1) 9*c*.
of glass, increasing by ion exchange and etching, (8) 276*a*.
of glass-crystal composites, (6) 211*i*.
of glass fibers, statistical theory, (4) 97*g*.
of glass foil, (2) 51*h*.
high, of chalk-aggregate concrete, observations, (2) 44*j*.
hot bending, of basic bricks, (4) 104*b*.
impact, of sheet glass strengthened by etching, (2) 49*e*.
of insulator porcelain, effect of glaze, (2) 60*b*.
of $Mg(OH)_2$ and MgO highly dispersed fine-pore structures, effect of $MgSO_4$, (6) 232*f*.
material, nondestructive measurement, P (1) 22*g*.
mechanical, of hydrated barium aluminate at elevated temperature, (5) 170*h*.
of porcelain insulators, increase, (2) 60*d*.
of porous disperse bodies, change in, as function of water content, (5) 192*i*.
ring-tensile, of concrete, comparison with compressive, flexural, and splitting-tensile strengths, (5) 187*b*.
of rocks, determination, (4) 123*j*.
shear, interlaminar, correlation with void content in glass-filament-wound composites, (1) 8*a*.
of montmorillonite, physicochemical interpretation, (5) 198*e*.
parameters for saturated clays, (4) 153*d*.
of reinforced concrete beam, prediction by analysis of existing data, (2) 68*j*.
of tidal marsh sediments, (8) 285*d*.
of soils, stabilized, (5) 190*c*.
of steel, problem, (8) 275*e*.
tensile, of brittle ceramics, Griffith flaws and effect of porosity, (10) 354*h*.
of concrete, effect of size and shape of test specimens, (1) 21*g*.
of fiber glass, relation with temperature of glass from which fiber is drawn and fiber diameter, (6) 209*f*.
Strength, tensile *(continued)*
of granular materials, (4) 159*h*; (10) 362*f*.
of moist agglomerates, (7) 260*d*.
of sapphire, effect of heat treatment, (2) 76*a*.
of sapphire whiskers at elevated temperatures, (10) 362*g*.
splitting, of concrete, effects of curing and drying environments, (1) 2*j*.
testing device, P (11) 381*c*.
of wet granular materials, (7) 270*d*.
testing, high temperature cross bending, of ceramic materials, (6) 226*j*.
of Ti diboride and Zr diboride, effect of porosity and grain size, (2) 55*f*.
torsional, of basic bricks, (4) 105*g*.
of whiteware bodies, (2) 60*f*.
yield, of low carbon enameling steels after firing, (8) 275*g*.
Strengthening, accelerated, of extruded ceramic bodies, (5) 176*f*.
glass, by ion exchange, (5) 173*d*.
glass, by multiple alkali ion exchange, P (6) 213*f*.
glass sheets, by ion exchange, P (4) 101*b*.
of silicate glasses by ion exchange, (4) 97*a*.
sitalls, possibilities, (2) 50*b*.
Stresses, analysis, of stopper brick screw parts by photoelasticity, (7) 251*h*.
analysis and temperature stresses of WC-Co cermets, (7) 270*g*.
analyzed using ceramic coatings, (6) 225*h*.
dependence of tensile creep rate in carbons and graphites, (8) 298*a*.
distribution, around holes in concrete, (1) 3*c*.
distribution, in solids, effect of inclusions on, (8) 291*c*.
effect on superconductive transition temperature of $SrTiO_3$, (4) 133*b*.
effect on thermal emf of Pt-Pt13Rh thermocouples, (6) 228*f*.
in enamels for thick plate steel, (10) 336*i*.
flow, dependence, on nonstoichiometry in oxygen-rich UO_2 at high temperatures, (4) 131*c*.
in glass caused by ultraviolet radiation: VIII, kinetics, (6) 211*i*.
in glass-to-metal seals, (1) 5*i*.
influence on disintegration of $MoSi_2$ by oxidation at intermediate temperatures, (1) 31*b*.
inspection apparatus, with sine wave modulation of the photomultiplier tube output, P (7) 261*b*.
measurement, on earthenware tiles set on reinforced concrete slabs, (4) 108*d*.
in pyrocarbon- and silicon carbide-coated fuel particles, mathematical model for calculating, (10) 341*a*.
residual, in cylindrical grinding, controlling, (4) 89*g*.
/strain behavior of refractory materials at high temperatures, (10) 342*g*.
strain relations, for clays, (1) 38*b*.
thermal, measuring by nuclear resonance, apparatus and method, P (1) 22*i*.
micromechanical, and thermal stress resistance of porous brittle ceramics, (6) 235*e*.
problems in glass, (1) 9*f*.
resistance, of HfB_2 and ZrB_2, (4) 157*c*.
uniaxial, effect on glass resistivity, (8) 276*f*.
and Zeeman spectra in Bi-doped and undoped CaO, (7) 269*a*.
Strontium, carbonate, solid state reactions with TiO_2, (9) 329*j*.
chloride, single crystals, ESR spectra of Er^{3+} and Yb^{3+} in, (6) 232*c*.
chromatographic separation from barites for mass spectrometric analysis, (9) 315*a*.
contents of natural peralkaline silicic glasses and petrogenetic significance, (10) 348*i*.
diffusion in irradiated basalt, (7) 265*c*.
iodide, thermographic investigation, (7) 270*b*.
ions, isothermal diffusion in pure NaCl crystals and reconsiderations of Soret effect, (10) 356*e*.
ions, thermal diffusion in NaCl crystals, (4) 160*e*.
isotope studies related to petrogenesis in Caledonian basic igneous province of NE. Scotland, (7) 262*b*.
molybdate(IV), magnetic susceptibility in range 2°–300°K, (11) 385*h*.
molybdate, segregation coefficients of rare earth niobates in, (1) 36*j*.
oxide, computed ground state properties in molecular orbital approximation, (8) 289*d*.
defect structure, (9) 330*d*.
irradiated, surface centers and fast irreversible oxygen adsorption on, (4) 128*d*.
X-irradiated polycrystalline, thermoluminescent study, (9) 332*a*.
separation, quantitative, (1) 21*g*.
spectrophotometric determination, by means of dimethylsulfonazo-III and related compounds, (5) 188*g*.
spodiosites, vanadate and arsenate, synthesis, and interpretation of optical spectra of Mn-doped Sr_2VO_4Cl, (4) 158*f*.
Sr^{2+}, coprecipitation with aragonite between 16° and 96°C, (6) 231*f*.
$Sr_{1-x}Ba_xNb_2O_6$, tungsten bronze ferroelectric, single crystals, growth and properties, (6) 233*c*.
SrClF, Raman spectra, (8) 297*c*.
$SrF_2:Sm^{2+}$ and $SrCl_2:Sm^{2+}$, optically pumped, spectra, (8) 298*d*.
$Sr_3(FeMo)O_8$, neutron diffraction study, (2) 80*i*.
Strontium *(continued)*
α-$Sr_2P_2O_7$, ESR of Mn^{2+} in, (9) 321*i*.
$Sr_4P_2O_9$ formation, influence of water vapor, in system $SrO-P_2O_5$, (11) 386*e*.
systems. See *Systems*.
titanate, chemical preparation, (7) 264*f*.
insulating and semiconducting magnetic, susceptibility, (1) 32*f*.
photoconduction, (5) 198*j*.
photoconductivity in, anomalous temperature dependence of, (2) 74*j*.
photo-Hall effect in, (2) 81*g*.
photomagnetoresistance, (2) 81*h*.
Raman spectrum, (4) 152*d*.
Raman spectrum, temperature dependence of, (4) 159*c,f*.
single crystals, ESR of Fe^{3+} in, with reference to 110°K phase transition, (1) 29*a*.
single crystals, growth from silica flux, (7) 266*b*.
single crystals, hydrogen and deuterium in, (9) 322*h*.
solid solutions containing La_2O_3, dielectric relaxation in, (9) 320*a*.
superconducting, magnetization and critical fields, (2) 80*g*.
superconductive transition temperature, effect of stress, (4) 133*b*.
vibronic structure in luminescence spectra of rare earth ions in, (2) 84*e*.
tungstate, Bi-doped, phototropy (4) 149*j*.
yttrate, luminescent materials, rare earth activated, P (9) 314*d*.
Structural clay products. See also *Brick; Pipe; Tile*.
black coring in, combating with chemically combined water, (1) 11*g*.
hollow ceramic building units, drying, (2) 54*d*.
low density rigid shapes, production, P (5) 176*g*.
setting machinery, modern, (6) 214*d*.
technology: Vol. 2, fundamentals of drying; Vol. 4, firing and furnace design fundamentals; Vol. 5, firing systems, B (8) 302*c*.
vitrified, P (7) 250*a*.
Structural clay products industry, Dickey Clay, develops new uses for polyurethanes, (8) 278*f*.
European, (6) 213*j*.
in Germany, exports to 40 countries, (4) 101*g*.
leads nation in panels, (4) 102*h*.
palletizing and drying, fully automatic, in, (7) 250*a*.
Structural materials. See also *Aggregates; Brick; Building materials; Cement; Concrete; Enameled ware; Glass; Insulation, thermal; Masonry; Structural clay products*.
honeycomb, P (8) 280*e*.
scanning electron micrographs of, (6) 227*i*.
Structure, of alkali polyaluminates, (4) 156*e*.
of alkali silicate glasses and melts, indication from bonding of OH groups (6) 209*h*.
of alumina-silicon cermets, reaction-formed, (4) 156*c*.
of aluminum hydroxide gel, (2) 83*i*.
of amorphous silicoaluminas: III, hydrated and transition aluminas, (4) 156*a*.
atomic, of amorpohus ZrO_2, (1) 25*i*.
band, of TiC, (1) 33*i*.
and bonding, B (6) 242*b*.
of boroxol skeleton, vibrational assignment and valence force field, (1) 9*i*.
of cadmium iodide films, vacuum-deposited, (2) 83*j*.
cage, for polyborate ions, (4) 127*g*.
of carbon fibers, high modulus, (4) 156*g*.
change, of hydrated barium aluminate at elevated temperature, (5) 170*h*.
changes, in high-melting-point metals, at high temperatures, electron optics method and apparatus for investigating, (6) 227*j*.
of clay minerals, (4) 128*h*.
of compounds of formula, $MFeF_3$ (M=Na,K,Rb,Cs,NH_4,Tl), (10) 361*i*.
crystalline, of $Bi_2O_3{\cdot}2MoO_3$, new data, (4) 146*b*.
of crystals. See *Crystals*.
defect, of Cu_2O films on (111) face of Cu, (8) 298*b*.
of α-Nb_2O_5, (5) 193*b*.
role in growth of NiO films, (5) 181*j*.
of rutile, (4) 146*i*.
of silicon surfaces after thermal oxidation, (2) 75*b*.
of spinel single crystals, (2) 75*j*.
of SrO, (9) 330*d*.
of Y_2O_3-ZrO_2 solid solutions, (6) 231*d*.
determination of inorganic compounds, use of magnetism in, (1) 22*h*.
dispersed, physicochemical mechanics, B (9) 334*j*.
effect on electric properties of ceramics, (4) 110*b*.
electronic, of alkali halides: III, NaCl, (2) 84*e*.
of lanthanum hydrides, (4) 143*g*.
of Nb_6Cl_{12} cluster, (4) 136*d*.
fine, in diamond direct absorption edge, (2) 77*e*.
fine, of polycrystalline MgO, behavior during sintering, (7) 263*f*.
floc, theoretical model, (1) 39*h*.
free-electron molecular-orbital calculations for inorganic systems: II, tetrahedra, square octahedral, trigonal prismatic, hexagonal cubic, Archimedean antiprismatic, and icosahedral free-electron networks, (4) 136*d*.
of glass, (11) 370*e*.

Structure *(continued)*
grain, of Mn-Zn ferrite, relation with magnetic properties, (4) 110*h*.
high temperature, of plutonium dicarbide, (9) 322*g*.
high temperature, in ZrO_2-Y_2O_3-Ta_2O_5 system, (5) 195*g*.
high temperature resistant, production, P (6) 218*d*.
interstratification, formed from preheated mica by acid treatments, (8) 293*h*.
of ionic liquids: II, pure alkali metal nitrates, (5) 203*c*.
of kyanite, two refinements, comparison, (1) 26*h*.
in limestone, obscure, fluorescent dye penetrant technique for displaying, (1) 21*j*.
magnetic, of $MnWO_4$ at 4.2°K, (4) 143*h*.
magnetic, of terbium chromite, neutron diffraction study, (10) 357*f*.
metal-nitride-oxide-silicon, radiation effects and electrical stability, (6) 236*h*.
micro-, in CdS:Cu single crystals, effects of growth conditions on, (2) 76*g*.
of carbon fibers, high strength, high modulus, (4) 144*c*.
ceramic, B (8) 301*g*.
of ceramic materials: V, aluminosilicate refractories, (7) 251*a*.
changes during sintering of pure Al_2O_3, (5) 177*g*.
and composition, effect on deformation in bend of periclase-silicate mixtures at high temperatures, (6) 215*b*.
control in nickel ferrous ferrite, (5) 181*j*.
of corundum ceramics, (10) 341*d*.
development during liquid-phase sintering of two-phase alloys in NbC-Co system, (8) 295*d*.
influence on dielectric properties of $BaTiO_3$, (10) 344*f*.
of Indian magnesites calcined up to 2000°, (2) 73*h*.
of lead ferrite, (8) 281*a*.
of mist zone on glass fracture surfaces, (1) 7*i*.
new of inorganic materials, (2) 50*f*.
surface, of crystals grown from molten salts, (4) 158*c*.
molecular, of $Al(BH_4)_3$, (8) 295*i*.
of B_2O_3, (5) 197*g*.
of cyclic $H_3B_3O_3$, (4) 144*f*.
of P_4O_{10} and P_4O_9, (4) 145*a*.
of MO_2-$nM'O_2$ compounds (M = Si, Ge, Ti; M' = Zr, Hf, Ce, Th), comparison, (9) 318*c*.
MOS, effect of heating under bias on photoelectric threshold in, (2) 76*b*.
Au-doped, properties, (4) 151*g*.
instabilities, (9) 323*c*.
monomeric, evidence in polygermanatosilicate melts, (7) 265*f*.
ordered, of $TiO_{1.25}$, (2) 81*h*.
of organic matter, and influence on use of raw materials in area of mineralogy and metallurgy, B (11) 389*b*.
of $OsOF_5$ orthorhombic phase, (5) 200*j*.
of phosphate-vanadates, of Y, Gd, Lu, and La, (4) 156*h*.
polarization, of interfacial amorphous films, (6) 220*i*.
of porcelain, hard, development by use of mineralizers, (11) 375*h*.
properties, of cermet films of Cr-SiO, (4) 110*e*.
of $Pb(Sc_{1/2}Nb_{1/2})_{1-x}Ti_xO_3$ system, (1) 16*g*.
of Na-Li niobate solid solution ceramics with small Li concentrations, (1) 17*j*.
of pyrographite, low-temperature, (1) 38*i*.
relation with ionic mobility in solid MAg_4I_5 [M = K,Rb,NH_4], (5) 199*b*.
rock-salt- and zinc-blende-type, low-temperature electric dipole vibronic transitions in, (1) 31*j*.
of $RbNiF_3$, effect of pressure, (7) 265*j*.
of SeO_3, (2) 79*c*.
of semiconductor compounds, (4) 128*b*.
shock induced planar deformation, in quartz from Ries Crater, Germany, (9) 329*e*.
significant, search for, (6) 237*b*.
significant-, theory, applied to molten salts, (6) 237*e*.
of sintered materials of Me-MeO system, detection by ionic bombardment, (7) 265*a*.
spin-polarized energy-band, of antiferromagnetic MnO, (9) 329*g*.
stabilization of Sm_2O_3, Gd_2O_3, and Nb_2O_5 with WO_3, (8) 298*c*.
and structural chemistry of synthetic Mg-Al hydroxycarbonates and related minerals and compounds, (9) 325*b*.
structural classification of fluorine compounds with Fe and monovalent cations and relation to magnetic properties, (6) 237*j*.
structural compacting, observed in lead glasses at different temperatures, (4) 97*b*.
study, of double oxide of Mn and Ca, orthorhombic $CaMn_3O_6$, (1) 38*d*.
of isomorphous series $Na(Sc,Fe)TiO_4$, (11) 385*g*.
of system HfO_2-Y_2O_3, (1) 38*d*.
on three modifications of $FeMoO_4$ (11) 385*h*.
of Ti_2Te_3, (5) 200*h*.
substrate, effect on deposition of evaporated carbon, (4) 110*c*.
sub-, picosecond pulse, measurement using compression techniques, (10) 357*a*.
surface of silica gel, (8) 299*d*.
of thin dielectric films prepared by cathodic sputtering of single-phase and multiphase materials, (2) 63*g*.
of thorium hydrolysis products, (8) 298*e*.
of TiC, defect concentration, X-rays to study, (1) 40*c*.
two-liquid phase, of photoconducting oxide glasses, (2) 52*d*.
two-phase, development in glasses in system $BaOSiO_2$, (1) 6*f*.
of uranium carbide, sintered, effects of Ni, (4) 133*h*.
vacancies, and solid solution decay in ferrospinels, (10) 361*c*.
of V_6C_5 ordered compound, (4) 156*j*.
vibronic, in luminescence spectra of rare earth ions in $SrTiO_3$, $BaTiO_3$, and other perovskites, (2) 84*e*.

Sublimation, rate, of Mg_3N_2 from effusion cells and from free surfaces in vacuo and in argon and nitrogen gases, (5) 199*i*.

Substrates, amorphous, nucleation and growth of thin Pb films on, (2) 63*j*.
epitaxial deposition on one side, simultaneous with vapor etching on opposite side, P (6) 223*h*.
insulating, single-crystal GaAs on, (1) 17*d*.
laminate, for use in making integrated circuits, (8) 281*j*.
metal salt impregnated silica-coated, art of producing, P (7) 248*a*.
movable, method of vaporizing and depositing electrode material layers on, P (9) 313*h*.
plastic, for thin film electronic devices, (8) 281*d*.
NaCl, doped, epitaxy of Ag and Au on, (2) 62*j*.
spinel-type lattice, epitaxial precipitation of semiconductor material on, P (5) 183*b*.
steel, ferrous metal, and ferrous alloy, protective coating for, P (4) 94*d*.

Sulfates, molten, infrared and Raman spectra, (10) 363*i*.
reaction with tobermorite gel, (4) 152*i*.
thermodynamic aspects of melting and fining with, (1) 9*g*.

Sulfides, capacities of basic slags containing CaF_2, (7) 245*b*.
higher, of lanthanides and actinides, study, (1) 38*e*.
metal, of groups II and III, growing single crystals of, P (4) 115*h*.
ores, single phase polycrystalline, annealing, (8) 288*i*.
research contributions from Mineral Sciences Div., Mines Branch, Dept. of Energy, Mines, and Resources, Canada, (9) 316*j*.
of transition elements and zinc, free energy of formation, (1) 37*j*.
of transition metals, thermal expansion, (1) 39*d*.

Sulfur, dioxide, bubbles, behavior in soda-lime glass, (4) 94*g*.
dioxide, collection from flue gases by limestone-dolomite processes, (1) 20*c*.
in flue gas, and desulfurization by compounds of alkaline-earth metals, (7) 261*c*.
kinetics of interaction with clean and oxidized metal films of Fe, Ni and Pb, (9) 324*b*.
reactivity of selected limestones and dolomites with, (1) 20*h*.
elemental, and Cu, recovery from white metal, (4) 126*f*.
hexafluoride, reaction with ceramic oxides at high temperatures, (1) 11*i*.
in molybdenite concentrates and minerals, determination by rapid methods, (1) 21*j*.
oxide, capacity of limestones, (10) 336*b*.
polymorphic transformations, linear rate, (4) 142*i*.
and selenium chains, rotational isomeric state models of: III, large rings in liquid sulfur and nature of S_π, (9) 329*b*.
solubility and permeability in alpha iron, (4) 155*f*.
sulfating in lime with Mg and Al sulfates, (8) 287*c*.
sulfation, of lead sulfide, (1) 38*g*.
systems. See *Systems*.

Sulfuric acid, cement-, process at British Columbia, (7) 244*h*.

Superconductors, anisotropic, P (2) 64*d*.
containing flux traps, P (6) 222*j*.
marcasite-type, $CuSe_2$, (9) 318*j*.
materials and devices involving lanthanum chalcogenides, P (1) 19*c*.
in modern materials, B (4) 166*h*.
Nb(Cb)-Ti-O, aging in, (6) 230*f*.
NbSn doped with ZrO_2 particles, diffusion-processed, performance, (4) 157*h*.
superconducting compounds, intermetallic, of Nb and Ga, production, P (5) 184*c*.
superconductivity, occurrence in yttrium dicarbide, (5) 197*j*.
superconductivity, practical developments, (2) 62*f*.
type II, theory of vortices in, (9) 331*b*.

Surface, activity, of clay minerals, (4) 128*h*.
area determination, of fine particles, rapid method, (6) 227*e*.
area estimations of grains used in glass durability testing, (7) 248*d*.
area measurement, of standard length sample of finely divided solids, P (11) 381*b*.
area measurement, of variable length sample of finely divided solids, P (4) 122*b*.
areas, and *c* values for chemically etched and thermally oxidized silicon single-crystal surfaces by krypton absorption, (1) 38*i*.
of mixed hydroxides and oxides of Mg and Fe, (1) 38*g*.
of silicate minerals by BET method using adsorption of Xenon at −78°, (5) 200*e*.
of solids, new method for comparison using adsorption from solution, (2) 70*j*.
studies in pretreated SiO_2 gels, (10) 361*h*.
chemical study, of comminuted and compacted solids, (4) 157*j*.
chemistry, of solids, (6) 238*d*.
effects, on thermal diffuse scattering of X-rays or electrons from crystal lattices, (2) 84*e*.
flaws and dislocations on glass, (9) 305*a*.
forces, normal and retarded van der Waals, direct measurement, (4) 157*j*.
fracture-exposed, of single crystals and polycrystalline ceramics, characteristics, (1) 25*g*.
homogeneous, immersion heat relations for, (1) 30*i*.
ice and silicate, interface between, (1) 31*e*.
and interfaces: Vol. I, chemical and physical characteristics; Vol. II, physical and mechanical properties, B (10) 366*d*.
interphase transfer, (1) 31*h*.
layers, of calcium silicates in aqueous electrolyte solutions, (6) 230*j*.
low-work-function, for negative-electron-affinity photoemitters, (11) 385*e*.
monolayers, thermodynamics and phase transitions in, (1) 39*f*.
nonoptical, surface topography by projected interference fringes, (4) 121*j*.
phenomena, role in kinetics of chemical reactions, sintering, and collective recrystallization of refractory oxides (7) 268*h*.
planar, cylindrical, and spherical, numerical solutions to finite, diffusion-controlled two-phase moving-interface problem with, (6) 235*a*.
porous, thin-walled, transpiration-cooled, transient temperature response of, (4) 162*c*.
preparation processes, systematic approach and selection, (8) 284*g*.
properties, of calcined chromium oxide gel, (4) 158*d*.
properties, of ferric oxalate, (1) 39*b*.
reduction, of lead glass tubes, (10) 338*a*.
of silica melts, (1) 38*i*.
specific, area, determination by low-temperature krypton adsorption, (1) 27*f*.
area of solids, determination by Ar adsorption, (2) 71*j*.
computation, coefficients expressing influence of grain shape and surface texture in, (1) 26*f*.
of heavy clays, measuring methods and significance, (11) 380*i*.
measurement of silicate materials, (10) 347*h*.
by methylene blue adsorption, (1) 15*d*.
of powders, determination from ratio of flow rates measured under different conditions of gas flow in porous medium, (2) 69*a*.
of technical powdered glasses, dependence on chemical composition, (9) 305*g*.
states, on small crystals, unified model of oxide cathode give prominence to role of, (4) 111*h*.
tensions, of binary phosphates of Na, Li, Ca, and Zn, (4) 158*g*.
of glass. See *Glass*.
of liquid $CdCl_2$-alkali chloride systems, (5) 200*g*.

Suspensions. See also *Slips*.
Al_2O_3, sedimentation activity of organic acids in, (4) 140*j*.
aqueous asbestos, filtration properties, effect of polyacrylamide, (1) 23*e*.
clay. See *Clays*.
congulative structure formation in: II, effect of Na and Ca chlorides on structure formation of lime-clay suspensions; III, influence of pressure-vessel treatment on structural-mechanical properties of, (7) 253*j*.
colloidal, of chrysotile asbestos: specific anion effects, (4) 128*i*.
colloidal, of chrysotile asbestos: surface charge enhancement, (5) 193*a*.
kaolinite, rheological characteristics and deposition, (9) 329*a*.
laboratory aerosol device, P (5) 188*g*.
montmorillonite, tactoid rearrangement and optical density during Na-Ca exchange reaction, (5) 200*j*.
rheological and technological properties, dependence on alumina pretreatment, (4) 123*i*.
self-diffusion in, (4) 154*e*.
silica and gold, determination of particle-diameter distributions in, (5) 193*b*.

Swelling. See *Expansion*.

Switches, device, adjustable variable voltage responsive two-terminal semiconductor, P (8) 282*a*.
four-layer semiconductor, in integrated circuitry, P (9) 312*a*.
miniature single pole-double throw ceramic-metal structure, P (2) 66*b*.
reed, adjusting contacts in, P (6) 212*j*.
saturable solid state nonrectifying, P (4) 116*i*.
sealed reed, with adjustable reed, P (5) 185*f*.
semiconductor, P (4) 116*j*.
high-speed, P (1) 18*h*.
low voltage, P (5) 185*j*.

Symmetry, of crystals. See *Crystals*.
-entropy-volume relations in polymorphs, (1) 39*a*.

Symposiums, on fundamental phenomena in materials sciences, proceedings of 4th, B (1) 41*d*.
on heat-resistant coatings, 1966, B (5) 204*d*.
on hybrid microelectronics, 1967, B (6) 242*f*.
on mass transport in oxides, 1967, B (5) 204*a*.
on surface of glass and modern, treatment, 1967, B (5) 204*h*.
on thick-film, 1967, B (5) 204*d*.
on thorium fuel cycle, 1966, B (6) 242*a*.
Synthesis, of albites at 250°–700°C, (9) 331*h*.
of AlP, (2) 83*e*.
of aluminosilica gels, (1) 39*b*.
of $4BaO{\cdot}Nb_2O_5$ in solid phase, (10) 362*b*.
of Cd_4SiS_6 and Cd_4SiSe_6, (4) 109*i*.
of ceramic pigments in $Ra^{2+}Rb^{2+}(PO_4)_4$ system, (6) 219*g*.
of cerite, (1) 39*a*.
of Cr garnet-type pigments, (6) 210*f*.
of CuS large crystals, (9) 331*i*.
of diamond, P (1) 20*f*.
of dolomite, (4) 158*b*.
and epitaxial growth of GaP by fused salt electrolysis, (10) 362*a*.
of finely divided oxide powders, P (9) 317*g*.
of glass in system P_2O_5-ZnO-UO_3, (4) 97*e*.
of grossularite-spessartite series, (8) 299*f*.
of grunerite and other phases in system SiO_2-NaOH-Fe-H_2O, (4) 158*c*.
high-pressure, of cobalt garnet ($Co_3Al_2Si_3O_{12}$), (6) 233*h*.
of new perovskite, $PbSnO_3$, (7) 266*d*.
of perovskite-type $Pb(Zn_{1/3}Nb_{2/3})O_3$, (11) 385*f*.
of stoichiometric compound FeO, (4) 138*a*.
of yttrium sesquicarbide, (10) 354*j*.
hydrothermal, of calcium silicate hydrate, influence of pore space, (11) 368*c*.
of quartz grown in RbOH and other alkali hydroxides, (7) 267*a*.
of silicates and germanates with garnet-type structure, (7) 267*b*.
of single domain $LiNbO_3$ crystals by transport reactions, (10) 355*g*.
of sodium mordenite in pebble form, (8) 293*g*.
of YIG, conditions of, (7) 264*b*.
of lead silicates—larsenite, barysilite, and related phases, (4) 158*j*.
low pressure, of electrically conductive platinum cobalt oxide from platinum halide and oxide containing cobalt, P (4) 113*j*.
low-temperature, of Mn-activated zinc silicate of superior crystallinity, (4) 143*d*.
of Mg_2PtO_4 and Zn_2PtO_4, (10) 362*a*.
of mullite, by sintering process, (2) 58*f*.
of mullite, in system kaolinite-aluminum fluoride, mechanism, (4) 105*d*.
of optical quality proustite and pyrargyrite, (8) 299*g*.
of orthosilicates of Ni and Co, (4) 158*e*.
of oxidation resistant metal diboride composites, (1) 13*h*.
parameters, effect on magnetic properties of manganese zinc ferrites, (6) 220*e*.
of perovskites containing In and Tl, (11) 387*i*.
of porous ceramic [silicate] materials for filtration and aeration, (11) 374*b*.
of pyrite-type modification of SiP_2, (4) 158*e*.
of rare-earth iron borates, and crystallographic data, (11) 387*i*.
of Sc analog of beryl, (8) 295*h*; errata, (10) 362*c*.
of smithite-rhombohedral FeS_4, (9) 331*i*.
and study of yttrialite, (10) 362*c*.
of ternary fluorides, (1) 37*g*.
of Ti-andradite, (9) 331*j*.
of titanium diboride by carbon reduction, (1) 39*c*.
of (U,Pu)C nuclear fuel pellets from U-Pu alloy, (10) 342*j*.
of vanadate and arsenate spodiosites, (4) 158*f*.
of wollastonite from calcium hydrosilicates, (11) 387*j*.
Systems. See also *Equilibrium studies; Phase diagrams.*
alkali strontium-barium-lead, with tungsten bronze structure, crystallographic properties and Curie points, (7) 254*e*.
Al_2O_3-B_2O_3, thermodynamics of vaporization in, (4) 162*d*.
Al_2O_3-H_2O, phase diagram, considering transformation mechanism of polymorphs appearing in, (1) 27*b*.
Al_2O_3-SiO_2, (7) 269*d*.
Al_2O_3-SiO_2, devolpment of electric potentials in, (10) 352*a*.
Al_2O_3-$Y_3Al_5O_{12}$, eutectic point in, (10) 356*a*.
Al_2O_3-ZrO_2-SiO_2, phase equilibria in, (6) 235*j*.
Al-fluoride-SiO_2, kinetics of mullite formation in, (5) 196*h*.
Al-O, *P-T-x* diagram, (1) 39*c*.
Al-S-O, from 850° to 1050°K, thermodynamics, (4) 162*c*.
Sb-Tl-Te, phase relations and transport properties in Te-rich region, (4) 153*h*.
$SbCl_3$-$AsCl_3$, (4) 159*e*.
barium-oxygen, vapor species, (2) 84*e*.
$Ba_{1-x}Sr_xRuO_3$, pressure-induced structural changes in, (2) 82*e*.
BaO-Al_2O_3-SiO_2, studies: I, polymorphism of celsian, (6) 238*d*; II, binary system celsian-silica, (9) 331*a*.
BaO-Fe_2O_3-Fe_2O_3, phase investigations, (11) 376*b*.
Systems *(continued)*
BaO-MgO-P_2O_5, luminescence of divalent Eu in, (10) 356*d*.
BaO-P_2O_5, phase relationships in portion of, (6) 236*b*.
BaO-Pt, in air, (11) 383*c*.
BaO-TiO_2 in region of barium polytitanates, (8) 299*j*.
$BaSO_4$-$SrSO_4$-$PbSO_4$, subsolidus phase relations and lattice constants in, (10) 361*e*.
Be-B, structure of zeta phase in, (7) 269*b*.
Be_3N_2-Si_3N_4: III, preparation and properties of $BeSiN_2$; IV, crystal structure of $BeSiN_2$, (8) 299*b*.
BeO-Al_2O_3-MgO at subsolidus temperatures, (11) 387*b*.
BeO-B_2O_3, thermodynamics of vaporization in, (2) 84*i*.
BeO-Li_2O, tentative phase diagram, (4) 159*h*.
binary alkaline earth orthosilicate, fluorescence of Eu^{2+}-activated phases in, (10) 353*f*.
binary, of fusible salts of type Me_3AlF_6, volumetric relations in, (4) 163*i*.
binary eutectic, with time-dependent surface temperature, unidimensional solidification of, (4) 163*a*.
binary salt, NbCl5-MeCl (Me=Na,K,Rb,Cs), physicochemical study, (8) 296*h*.
bismuth-selenium vaporization, laser-induced, mass spectrometric studies, (5) 196*f*.
Bi_2O_3-MoO_3, dilatometry, (8) 290*i*.
Bi_2O_3-WO_3, X-ray investigation, (8) 301*a*.
of bromides and iodides of Na and Pb, inverse reciprocal, (9) 323*f*.
of bromides of lithium, calcium, and lead, properties, (9) 329*c*.
Cd-Se, phase equilibria in, (4) 149*d*.
$CdCl_2$-alkali choride, liquid, surface tension, (5) 200*g*.
$CaCO_3$-$MgCO_3$, *P-T-X* relations in, at high temperatures and pressures, (9) 328*j*.
$CaCO_3$-$MgCO_3$-$FeCO_3$, subsolidus relations between 350° and 550°C, (4) 157*e*.
$CaCO_3$-SiO_2, carbon formation at high pressures and temperatures, (4) 127*e*.
$CaFeSi_2O_6$-$FeSiO_3$, subsolidus reactions in, (10) 361*f*.
$CaMoO_4$/$LnVO_4$, luminescent properties, (1) 32*c*.
$Ca_3(PO_4)_2$-$CaNaPO_4$, (4) 127*d*.
$Ca_3(PO_4)_2$-$Zn_3(PO_4)_2$, phase equilibria in, (4) 149*e*.
CaO-Al_2O_3-TiO_2, phase equilibria in, (6) 235*h*.
CaO-CO_2-H_2O, liquidus phase relations in, to 40 kbars pressure, (10) 356*j*.
CaO-"FeO"-MnO, in contact with metallic iron, solid-liquid equilibria in, (6) 237*g*.
CaO-"FeO"-SiO_2, solid solutions, in contact with metallic iron at 1080°C, activity-composition relations in, (1) 24*i*.
CaO-MgO-Al_2O_3-SiO_2, diopside + spinel equilibria, anorthite and forsterite reaction relations in silica-poor liquids in, and bearing on genesis of melilites and nephelinites, (11) 383*g*.
CaO-MgO-CaF_2, (4) 127*c*.
CaO-MgO-SiO_2, densities of silicates in, (10) 351*h*.
CaO-NiO-SiO_2, (8) 299*c*.
CaO-SiO_2-Al_2O_3, thermodynamics of carbide formation and graphite solubility in, (4) 161*h*.
CaO-SiO_2-CaF_2, new compound $(3CaO{\cdot}SiO_2)_3{\cdot}CaF_2$ in, (4) 127*h*.
CaO-SiO_2-CO_2-H_2O: III, second critical end point on melting curve, (11) 387*c*.
CaO-SiO_2-H_2O-CO_2, effect of carbonic binder on properties of hydrothermally hardened silica-lime compositions in, (11) 372*j*.
CaO-SiO_2, Na_2O-SiO_2, and Na_2O-CaO-SiO_2, binary and ternary, phase composition, (9) 326*i*.
CaO–SrO, formation of mixed crystals in, (2) 77*g*.
CaO-Ta_2O_5-SiO_2, phase relations in, (10) 358*d*.
CaO-V_2O_5-Na_2O, melts, effect of lime on quantity of water-soluble V_2O_5 in, (8) 291*g*.
CaO–ZrO_2–SiO_2, phase analysis of compounds in, (2) 70*b*.
CaO-ZrO_2-SiO_2, phase equilibria in, (4) 149*g*.
$2CaO{\cdot}SiO_2$-$3CaO{\cdot}P_2O_5$, subsolidus relations in, (8) 299*a*.
$2CaO{\cdot}SiO_2$-$Na_2O{\cdot}CaO{\cdot}SiO_2$, solid solutions in, (10) 360*j*.
$CaSiO_3$-$CaGeO_3$, solid solutions in, (7) 269*a*.
$CaSO_4$-H_2O, stability relations in, at high temperatures and pressures, (10) 360*i*.
C-Si-Be, triangulation, (1) 40*b*.
carbonate-quartz, Gatesburg formation (late Cambrian), Pennsylvania, petrography-porosity relations in, (9) 326*g*.
CeO_2-Ce_2O_3, thermodynamic analysis of equilibrium in, (4) 161*g*.
CeO_2-Tb_2O_3, mixed, tensimetric studies in, (5) 200*d*.
Cs,Pb‖Cl,Br, (9) 331*e*.
Cs_2O-SiO_2, (7) 269*h*.
of chlorides of Na, K, Ca, and Ba, (4) 158*j*.
of chlorides and fluorides of Na, K, and Ca, (4) 158*i*.
Cr-SiC, (9) 331*b*.
Cr-SiO, phase composition of thin layers in, (9) 311*e*.
clay-water. See *Clays.*
$Co_{1-x}Fe_xS_2$, Moessbauer effect in, (11) 386*f*.
Cu-Fe-O, phase relations, (1) 34*i*.
Cu-Mn-O, phase equilibria in, (6) 235*j*.
Systems *(continued)*
Cu-Nb-S, vapor growth of new single-crystalline phases in, (9) 332*i*.
CuO-P_2O_5 and Cu_2O-P_2O_5, phase-equilibrium relations in, (5) 198*i*.
CuO-SiO_2 and Cu_2O-SiO_2, X-ray study, (7) 270*g*.
$Cu(PO_3)_2$-$TlPO_3$ and $Cu(PO_3)_2$-$RbPO_3$—crystallographic data for $CuTl(PO_3)_3$ and $CuRb(PO_3)_3$, (9) 331*f*.
Cu_2S-Ag_2S, phase transformations in, (5) 198*j*.
diopside-akermanite-nepheline-$CaTiAl_2O_6$, role of Ti in alkaline basalts in light of, (10) 353*j*.
ErCl3-KCl, (8) 299*c*.
formed by Al_2O_3 and oxides of trivalent and tetravalent metals, especially TiO_2, contribution to study of, (5) 193*f*.
formed by oxides of rare earths and chromium, phase correlation, (1) 34*g*.
forsterite-diopside-silica with and without water at high pressures, (9) 331*c*.
Ga-Al-P, phase and thermodynamic properties, -solution epitaxy of $Ga_xAl_{1-x}P$ and AlP, (9) 327*j*.
gallium and arsenic, with group IB elements, ternary condensed phase, (4) 159*i*.
Ga–As–Si ternary phase, (2) 77*a*.
Ga-As-Te, ternary condensed phase diagram, (4) 159*i*.
Ga-As-Zn ternary phase, arsenic-rich region of, modification of ternary diagram, (1) 25*h*.
Ga-P-Te, (4) 137*b*.
Ga-S, *P-T-x* phase diagram, (1) 35*c*.
$GaCl_3$-$SeCl_4$ and $GaCl_3$-$TeCl_4$, (8) 299*h*.
GaP-GaAs, thermal expansion coefficients and lattice parameters between 10° and 65°C in, (4) 160*e*.
GeS_2-In_2S_3, coprecipitation in, (7) 264*d*.
Ge-GaAs, pseudobinary, (1) 35*d*.
HfO_2-Gd_2O_3, binary, (7) 263*i*.
HfO_2-Y_2O_3, structural study, (1) 38*d*.
H_2O-Na_2O-SiO_2, at 200°, 250°, and 300°, (11) 387*e*.
InSb-InTe, pseudobinary, (1) 35*c*.
InI_3-HgI_2, (8) 299*d*.
InIs with iodide and oxyiodide of bismuth, (8) 299*i*.
In_2O_3-H_2O-Na_2O and In_2O_3-D_2O-Na_2O, hydrothermal investigation, crystal structure of rhombohedral In_2O_3 and $In(OH)_3$, (4) 139*i*.
Fe-Al-Si-O-H, staurolite stability in part of, (4) 156*a*.
Fe-O-SiO_2, *P-T-f*-$_{O_2}$ relations in, (10) 359*d*.
iron-sulfur: I, growth rate of ferrous sulfide on iron and diffusivities of iron in ferrous sulfide; II, rate of reaction of hydrogen sulfide with ferrous sulfide, (4) 141*g*.
Fe-S-O, portion, between 900° and 1080°C and application to sulfide ore magmas, (11) 386*g*.
$FeCl_2$-$MgCl_2$, (4) 158*j*.
"FeO," "FeO"-SiO_2, and "FeO"-CaO, thermoelectric power, (4) 162*e*.
FeO-Al_2O_3-SiO_2-H_2O-O_2, equilibria in, and analysis of stabilities of chloritoid and staurolite, (6) 230*h*.
FeO-Fe_2O_3-Al_2O_3 and FeO-Fe_2O_3-Cr_2O_3, equilibrium relations up to 1750°C in air, (4) 135*f*.
FeO-MgO-SiO_2, *P-T-f*$_{O_2}$ relations in, (6) 236*e*.
(Fe,Mn)O, phase diagram at 1260°K, (4) 149*a*.
FeSiO3-MgSiO3 orthopyroxene, magnetic behavior, from NGR in ^{57}Fe, (9) 324*h*.
jadeite-diopside, melting relations in, at 30 and 40 kbars, (9) 324*d*.
$(La,Gd)_2CoMnO_6$, magnetic interactions in, (2) 80*b*.
$(La,Gd)_2CoMnO_6$, magnetic interactions and crystal structure in, (10) 356*g*.
La_2O_3-Ta_2O_5, phase composition, (10) 361*c*.
Pb-Sb and Pb-Bi, metastable phases in, (4) 144*g*.
Pb-PbO-As_2O_3, slag-metal equilibria in, (1) 37*a*.
PbF_2-AlF_3 and CaF_2-AlF_3, (4) 159*a*.
$Pb_2MgNb_2O_9$-$Pb_2NiNb_2O_9$, dielectric and mechanical loss in, (5) 180*g*.
$PbNb_2O_6$, and its bearing on growth of single crystals of ferroelectric polymorph, (2) 83*j*.
PbO-B_2O_3 binary liquid, thermochemistry at 800°, (4) 161*e*.
PbO-chromium oxide, in air, (1) 39*d*.
PbO-Fe_2O_3-SiO_2, ternary phase relations in, new data on kentrolite and melanotekite, (4) 146*b*.
PbO-SiO_2, silica transformations in, (1) 36*b*.
$Pb(Sc_{1/2}Nb_{1/2})_{1-x}Ti_xO_3$, ferroelectric and structural properties, (1) 16*g*.
PbS-Na_2S-CuS, (8) 299*g*.
PbTe-PbI_2, (9) 331*e*.
Li,Ca,Ba‖Cl, (8) 299*d*.
Li^+,Ca^+,Sc^{3+}‖F^-, (4) 159*a*.
Li,Ca,Sr‖Cl, (8) 299*e*.
Li^+,Ca^+,Y^{3+}‖F^-, (4) 159*a*.
lithium-cobalt-oxide, cation vacancy density in phase transition from monoxide to spinel in, (10) 360*b*.
lithium-manganese-arsenic, ternary, phases, magnetochemical studies, (5) 181*h*.
Li,KBa‖F,Cl, quaternary reciprocal, cross sections, (8) 298*b*.
Li,K,Cs‖Br and Li,K,Rb‖Br, (9) 331*g*.
Li^+,K^+,Sr^{2+}‖Cl^-, (4) 159*b*.

Systems *(continued)*
- Li,Na,Cs‖Br and Na,K,Rb‖Br, (9) 331*g*.
- Li,Na,K‖Cl, (7) 269*j*.
- LiBr-KBr, electrolytic conductance of melts in, (9) 321*h*.
- Li_2O-B_2O_3-B_2O_3-NiO, phase relations in, (11) 386*e*.
- Li_2O-MgO-ZnO-Al_2O_3-SiO_2, metastable crystalline solid solutions with quartz structure in, (9) 306*f*.
- Mg^{2+}-Fe^{2+}-CO_3^{2-}-Cl_2^{2-}-H_2O, formation of magnesite and siderite deposits in, (10) 353*h*.
- $MgAl_2O_4$-$LiAl_5O_8$, $MgAl_2O_4$-$NiCr_2O_4$, $MgAl_2O_4$-$NiAl_2O_4$, and $NiAl_2O_4$-$ZnAl_2O_4$, (10) 358*e*.
- MgO-Al_2O_3-Al_2O_3, crystal growth of spinels in, by flame fusion, (9) 319*c*.
- MgO-Al_2O_3-Cr_2O_3, kinetics of precipitation and measurements of strain in, (6) 234*d*.
- MgO-Al_2O_3-Ga_2O_3, Mn-activated luminescence in, (4) 143*c*.
- MgO-Al_2O_3-SiO_2-H_2O, high pressure phases in, (10) 354*j*.
- MgO-Al_2O_3-SiO_2-H_2O and K_2O-MgO-Al_2O_3-SiO_2-H_2O, compatibility relations of aluminum silicate in, at high pressure, (7) 264*h*.
- MgO-CaO-Cr_2O_3-SiO_2, investigation with high temperature microscope, (4) 141*j*.
- MgO-GeO_2-MgF_2, subsolidus equilibria in, discussion and reply, (6) 231*g*.
- MgO-FeO-Fe_2O_3, phase equilibria in, (9) 327*c*.
- MgO-FeO-Fe_2O_3-SiO_2, element distribution among coexisting phases in, as function of temperature and oxygen fugacity, (4) 135*c*.
- MgO-"FeO"-SiO_2, equilibrium phase compositions and thermodynamic properties of olivines and pyroxenes in, (4) 135*d*.
- MgO-FeO-SiO_2, partitioning of cations between single and multisite phase in orthopyroxene-clinopyroxene and orthopyroxene-olivine joins, (6) 235*e*.
- MgO-iron oxide-TiO_2, phase equilibria in air, (10) 358*j*.
- MgO-SiO_2, (8) 299*e*.
- MgO-SiO_2-Fe-O, gel preparation of starting materials in, (10) 354*g*.
- MgO-SiO_2-TiO_2 and bearing on distribution of TiO_2 in basalts, (11) 387*d*.
- MgO-V_2O_5, phase diagram, (9) 326*j*.
- MgO-Ve_2O_5, solubility limits in, as determined by diffusion, (10) 360*j*.
- Mn–Ga, η phase in, magnetic and crystallographic properties, (2) 79*h*.
- $MnCl_2$-LiCl-KCl, eutectic mixtures, EMR spectra, (10) 352*i*.
- $MnCl_2$-NiCl, phase diagram, (9) 327*a*.
- MnO-Al_2O_3, (corundum), diagram of phase equilibria, (4) 131*j*.
- MnS-CdS, phase studies in, (4) 149*j*.
- metal-oxide, mechanical tension in: IV, anodic oxidation of Ta, (10) 357*b*.
- Me-MeO, structure of sintered materials of, detection by ionic bombardment, (7) 265*a*.
- MeF-MnF_2 (Me = Li,Na,K,Rb,Cs), (7) 269*j*.
- Mo-Fe-B, isothermal section (1) 31*c*.
- MoO_3CaMoO4, MoO_3-PbMoO4, MoO_3-ZnMoO4, (7) 270*a*.
- multiconstituent, multiphase, chemical reacting, calculating equilibrium compositions of, (9) 318*h*.
- neodymium-carbon, high-temperature mass spectrometric study, (5) 195*e*.
- Nb-Mo-C alloy, constitution, (1) 26*j*.
- Nb-O, Nb-Hf-O, Nb-Mo-O, and Nb-W-O, phase equilibria, (4) 155*e*.
- Nb-W-B, X-ray diffraction study, (7) 270*f*.
- NbC-Co, microstructural development during liquid-phase sintering of two-phase alloys in, (8) 295*d*.
- $NbCl_5$-Rb (Cs)Cl, (4) 159*a*.
- $NbCl_5$-Na (K)Cl, phase diagrams, (8) 296*e*.
- $NbCl_5$-NaCl and $NbCl_5$-KCl, (4) 159*j*.
- Nd_2O_3-Cr_2O_3, (7) 270*b*.
- Ni-Mg-Si-O, stability of olivine and pyroxene in, (7) 269*f*.
- NiO-CaO, (11) 387*e*.
- NiO-Cr_2O_3-O_2, MgO-Cr_2O_3-O_2 and CdO-Cr_2O_3-O_2, phase equilibria at high oxygen pressures, (1) 34*i*.
- NiO–H_2O, hydrothermal studies, (2) 78*c*.
- nonisothermal, condensation-enchanced vaporization rates in, (6) 231*f*.
- oxide, application of high-temperature solution calorimetry to, (5) 192*e*.
  - electron or laser-beam decomposition, for production of electrically conductive tracks, (8) 281*e*.
  - nonstoichiometric, thermodynamics, (5) 201*i*.
  - partially liquid, thermodynamic relationships in, (5) 201*e*.
- oxygen-niobium, adsorption, absorption, and degassing in, at very low pressure, (4) 126*e*.
- phosphite, binding properties, (7) 245*c*.
- PuO_2-ThO_2-BeO, pseudoternary, phase diagrams, (1) 35*d*.
- K,Cs,Pb‖Br, (7) 269*i*.
- $KAlSi_3O_8$-SiO_2-H_2O, melting reactions in, to 18.5 kbars, (10) 357*d*.
- potassium carbonate-magnesium carbonate, (4) 159*e*.
- KCl-$MgCl_2$, electrical conductivity in, (7) 265*b*.
- KF-YF3, phase diagram, (8) 296*d*.
- K_2O-GeO_2, phase equilibria in, (1) 38*a*.
- KTaCl4-KMgCl3-KCl-NaCl and KNbCl4-KMgCl3-KCl-NaCl, (8) 299*j*.
- $KTaO_3$-$KNbO_3$, subsolidus stability relations in, (1) 38*f*.

Systems *(continued)*
- PrO_{2-x}-O_2, phase transformations in, high-temperature X-ray diffraction studies, (10) 358*d*.
- pyrophyllite-nickel (cobalt) oxide, solid reactions in, (9) 329*i*.
- quartz-water-dodecane, contact angles and adsorption modified by dodecyl ammonium chloride, (1) 26*a*.
- rare-earth-carbon, thermodynamics: I, cerium-carbon, (11) 388*d*.
- rare-earth oxides–tellurium dioxide, compound formation in, (9) 318*f*.
- Re-Cr-C, (1) 36*f*.
- rhenium-oxygen, mass spectrometric study, (10) 356*j*.
- RbI-AgI, KI-AgI, and NH_4I-AgI, high conducing solid, thermodynamics studies in, (5) 201*g*.
- Rb_2O-B_2O_3, liquid, vapor pressure measurements and structural interpretation in, (4) 163*f*.
- Ru-Ir-O_2, phase relations in, in air, (9) 327*d*.
- samarium-nitrogen-oxygen, ternary, and question of lower oxides of Sm, (11) 388*d*.
- Sc_2O_3-Fe_2O_3-MnO_x, investigation of region of Sc_2O_3 solid solutions in, by statistical method of averaging, (4) 141*h*.
- Se-Cl, conductance and equilibrium studies, (7) 264*c*.
- silicate, with unipolar conductivity, evaluation of diffusion potential in, (2) 48*j*.
- silicon-carbon-nitrogen, (4) 159*f*.
- Si-SiO_2, nitriding reactions, (4) 146*d*.
- Si-SiO_2, properties, effect of gold, (4) 132*h*.
- Si-Te, partial pressures of Te2 and SiTe and thermodynamic properties from optical density of vapor phase, (8) 297*f*.
- SiC-B4C-C, SiC phase in, (10) 360*h*.
- SiO_2-Al_2O_3, study by cooling curve method, (5) 200*d*.
- SiO_2-NaOH-Fe-H_2O, synthesis of grunerite and other phases in, (4) 158*c*.
- Ag_2S–As_2S_3, and growth of crystals of proustite, smithite, and pyrargyrite, (2) 83*i*.
- Ag_2Te-In_2Te_3 pseudobinary, phase diagram, and semiconducting properties of $AgIn_5Te_{14}$, (4) 149*b*.
- Na,Cs,Ba‖Cl, (8) 299*f*.
- Na,Cs,Cd‖Br, (8) 299*g*.
- Na, Cs, Cd‖I, (7) 270*b*.
- Na^+, K^+, Ca^{2+}‖F^-, (9) 331*d*.
- Na^+,K^+,Cs^+‖I^-, (4) 159*c*.
- Na^+,K^+‖PO_3^-,F^-, (4) 159*c*.
- Na,K,Rb‖I, (4) 159*c*.
- Na^+,K^+,Y^{3+}‖F^-, (4) 159*d*.
- (Na-Ag) Cl and (Na-Ag)Br, solid solutions in, heats of formation, (1) 30*d*.
- Na_3AlF_6 and Na_3AlF_6-Al_2O_3 with MgF_2,Li_3AlF_6, and K_3AlF_6, liquidus curves, (1) 31*h*.
- Na_3AlF_6-CaF2, phase diagram, and constitution of melt in, (9) 327*a*.
- $NaAlSi_2O_6$-SiO_2 and $KAlSi_2O_6$ to 20 kbars and relation between H_2O content, P_{H_2O} and P_{total} in granitic magnas, (11) 387*g*.
- $NaAlSi_2O_6$-NaF-H_2O, melting relations to 4 kbars pressure, (4) 144*d*.
- NaCl-KCl, analysis of two-phase region halite-sylvite in, (10) 349*h*.
- NaCl-ZnCl, vaporization equilibria in, (10) 363*h*.
- Na_2O-Al_2O_3-CaO-SiO_2-H_2O, reaction at 280°, (1) 35*i*.
- Na_2O-Al_2O_3-SiO_2-H_2O, quaternary, interactions in, at 280°C, (7) 267*f*.
- Na_2O-B_2O_3-Ln_2O_3, rare earth borates in, (6) 236*i*.
- $NaNbO_3$-$BaNb_2O_6$, phase equilibria in, (10) 358*i*.
- $NaPO_3$-NaF and KPO_3-KF, phase diagrams, (4) 149*c*.
- sodium titanium phosphate, crystalline phase in, (9) 319*h*.
- Sr-Ti-O, 1375°C isotherm, phase equilibria in, (11) 386*e*.
- $Sr_{2-x}Mg_xP_2O_7$, crystallographic character, (10) 351*f*.
- SrO-GeO_2, (2) 84*a*.
- SrO-P_2O_5, phase relations in, and influence of water vapor on formation of $Sr_4P_2O_9$, (11) 386*e*.
- TaCl5-NbCl5-KCl-$MgCl_2$, (7) 270*c*.
- TaCl5-$WOCl_4$, (9) 331*f*.
- terbium oxide-oxygen and mixed cerium terbium oxide-oxygen, high-temperature X-ray diffraction studies, (10) 355*d*.
- terbia and praseodymia, and mixed proseodymia-terbia, tensimetric study, (5) 201*b*.
- ternary of bromides and iodides of thallium and cesium, fusibility diagram, (7) 266*e*.
- ternary, of fluorides of alkali metals and manganese, (7) 270*d*.
- of tetrachlorides of Zr and Hf with $AlCl_3$ phase relations in, (8) 296*f*.
- TlBr-TlCl, change in lattice period and microhardness of homogeneous solid solutions in, (7) 264*e*.
- Tl-Pb, phase boundaries in, calculation from activity data, (1) 25*c*.
- Th-C, electrical resistivity and phase relations for, (4) 134*e*.
- Th-ThC, miscibility gap in, from high-temperature X-ray data, (4) 144*h*.
- Th-U-N, ternary, phase relations in, at 1000°C, (9) 327*f*.
- Th-ThAs, phase equilibria, (5) 202*g*.

Systems *(continued)*
- SnTe-Bi_2Te_3 and PbTe-Sb_2Te_3, phase relations and thermoelectric properties, (4) 149*i*.
- SnTe-PbTe, solid solutions in, (2) 83*d*.
- SnTe–SnSe, phase relations, (2) 81*c*.
- Ti-C-N, investigation, (5) 195*h*.
- Ti-O, magnetism, (8) 294*a*.
- Ti-O, thermodynamics, and dissociation energy of molecule TiO (*g*), (11) 383*i*.
- Ti-P, crystal structures and phase relations, (4) 156*g*.
- TiO_2-SnO_2, modulated structures in, (5) 197*e*.
- W-LaB_6, alloys, preparation and physical properties, (7) 268*d*.
- tungsten-oxygen, thermodynamics, (5) 202*d*.
- tungsten-oxygen-iodine: I, tungsten dioxide (*s*) + iodine (*g*) = tungsten dioxide diiodide (*g*) equilibrium; II, preparation and properties of tungsten dioxide iodide; III, thermal behavior of tungsten dioxide diiodide, (5) 202*b*.
- U-C-O, contribution to study of, (5) 193*d*.
- U-C-O-N, phase relations in low-nitrogen region at 1700°C, (1) 35*e*.
- U-H, study at high pressures, (4) 157*d*.
- U-M-C, ternary carbides in, (10) 362*j*.
- U-Zr-C, phases, (9) 327*b*.
- UO_2-H_2O, formation, thermal decomposition, and structure: III, thermal decomposition of β-UO_3·$2H_2O$ produced from γ-UO_3, (5) 194*j*.
- UO_2-SiO_2, with varying UO_2 concentrations at 100°C, thermal diffusivity, (10) 342*j*.
- UO_2-SiO_2, thermal conductivity at 100°–800°C, (9) 331*e*.
- uranium hexafluoride-plutonium hexafluoride, melting-point diagram for, (11) 386*b*.
- UN-C, thermochemical and technological investigation, (5) 201*j*.
- UP-US, melting point studies, (8) 295*b*.
- V-B-N, (8) 300*c*.
- V-Si-O, chemical transport reactions in, and ternary phase diagram, (5) 192*f*.
- VCl_3-CsCl, (7) 270*c*.
- ytterbium-gallium and yttrium-calcium silicate, growth of mixed cation iron garnets in, (10) 354*i*.
- Y-C, phase diagram, (4) 164*b*.
- Y_2O_3-Al_2O_3: I, formation of compounds; II, liquidus curve measurement, (4) 159*g*,*i*.
- Zn-In-S, new phases, (9) 325*f*.
- Zn-Te, phase equilibria in, (4) 149*i*.
- zinc-tellurium, *P-T-x* phase diagram, (1) 35*e*.
- ZnO-B_2O_3, lamellar glass-crystal structures in, (7) 247*f*.
- ZnO-In_2O_3, light absorption of semiconductive phase in, (10) 356*h*.
- ZnO-TiO_2, ceramics in, influence of oxides of different valence on properties, (2) 62*i*.
- ZnV_2O_4-LiV_2O_4, relation between V-V bond distances, infrared spectra, and electronic properties in, (6) 237*h*.
- Zr-H, phase studies at high hydrogen concentrations, (9) 327*h*.
- Zr–O, interstitial solid solution, ordered arrangement of O in, (2) 81*g*.
- Zr-ZrC, phase diagram, (7) 267*i*.
- $ZrCl_4$-$AlCl_3$, (8) 299*h*.
- ZrO_2-CaO, fundamental research with solar furnace, (5) 194*j*.
- ZrO_2-CeO2, solid binary, physicochemical properties, (9) 327*e*.
- ZrO_2-FeO3, ZrO_2-SnO_2, and ZrO_2-Cr_2O_3, lattice parameter variations in mixed oxides with monoclinic ZrO_2 structure, (5) 196*j*.
- ZrO_2-MoSi2 and ZrO_2-SiC, sintering of mixtures in, and properties, (1) 36*h*.
- ZrO_2-neodymium oxide, electrochemical properties at high temperatures, (1) 28*d*.
- ZrO_2-SrO, reactions in, (6) 237*f*.
- ZrO_2-TiO_2: III, change of mineral composition by heat treatment, (4) 164*e*.
- ZrO_2-Y_2O_3-Ta_2O_5, high-temperature structure and electrical conductivity in, (5) 195*g*.

Tableware, Soviet, state and future development, (6) 206*c*.

Talc. See also *Steatite*.
- and anthrophyllite deposits in Tallapoosa and Chambers counties, Alabama, (2) 73*h*.
- beneficiation, P (4) 126*a*; P (11) 383*a*.
- deposit, new, in St. Lawrence County, N. Y., (8) 286*h*.
- structural changes during heating, (2) 63*f*.
- thermodynamic properties, new data, (4) 146*e*.

Tanks. See also *Furnaces, glass*.
- pickle, protective linings for, (8) 275*d*.

Tantalum, anodic oxidation, (10) 357*b*.
- carbide, diffusion of C in, (8) 290*h*.
  - phase, abnormal structure in WC-TaC-Co alloys, (4) 102*i*.
  - powders, changes in properties during pressing, (6) 230*i*.
  - and Ta-alloy carbide filaments, production, P (4) 107*b*.
  - X-ray measurement of strain in, due to composition gradients, (6) 239*g*.
- diboride, borothermic preparation, (8) 288*j*.
- monocarbide, CO isotope exchange with, (10) 350*b*.
- monocarbide, thermal properties, (5) 201*f*.
- mononitride-Zr diboride, densification and wear resistance, (8) 278*j*.
- nitride, finely divided nonpyrophoric, preparation, P (6) 218*a*.
- nitride, powder, P (5) 179*f*.
- oxidation, high-temperature, rate-controlling processes in, (4) 152*g*.

Tantalum *(continued)*
oxide and dioxide, gaseous, enthalpies of formation, (2) 76*h*.
oxides, structure, (10) 361*g*.
oxide fluorides, pentavalent, studies, and thermal decomposition of TaO_2F, (4) 156*j*.
pentafluoride and Ta oxytrifluoride, stabilities, mass spectrometric studies at high temperatures, (9) 324*i*.
pentoxide, free energy of formation, (8) 292*b*.
oxygen-deficient, solid state studies, (11) 387*d*.
purification, P (7) 263*c*.
in silicates, simultaneous determination with Hf by neutron activation analysis, (1) 22*b*.
solubility of N_2 in, (8) 298*a*.
systems. See *Systems*.
Ta(V), hydrolysis, in potassium fluoride-lithium fluoride, (2) 79*c*.
and Ta_2O_5, deposition by superimposed rf and dc sputtering, (4) 131*e*.
$TaTe_4$, high-pressure induced transformations in, (10) 354*h*.
Tar, saturation, effect on performance of high-silica nozzle, (2) 55*h*.
Television screens. See *Screens*.
Television tubes. See *Tubes*.
Tellurides, metal, of groups II and III, growing single crystals of, P (4) 115*h*.
Tellurium, dioxide, *a*-, structure, refinement, (9) 328*g*.
hexafluoride, removal from gaseous systems by solid reagents, (4) 153*c*.
telluric anhydride, interactions with sulfides of Zn, Cd, and Hg, (7) 267*f*.
tetrachloride and tetrabromide, infrared spectra, (11) 385*h*.
thermal expansion, comparison with Se, (4) 129*e*.
Temperature, arc, in electrodes, use of CN bands for determining in presence of silicates containing higher amounts of Fe, (2) 71*e*.
bombardment, effect on trapping of xenon in oxides and halides, (11) 384*d*.
characteristic, of refractory Th compounds, (4) 128*i*.
compensating unit, for piezoelectric crystals, P (4) 117*c*.
control. See also *Controls*.
control, of large oil-fired container glass tanks, (9) 307*g*.
Curie, and phase-matching temperature variations in $LiNbO_3$, as function of melt stoichiometry, (1) 26*c*.
Curie points, of alkali strontium-barium-lead niobate systems with tungsten bronze structure, (7) 254*e*.
Curie point, of ferroelectric $LiNbO_3$, determination, (2) 62*d*.
cycling, effect in structure of basic bricks in oxidizing and reducing atmospheres, (6) 215*f*.
Debye, characteristic, of halides and oxides of heavier salts, (2) 79*a*.
dependence, of absorption edge in ferroelectric $KNbO_3$ crystals, (1) 39*d*.
of adsorption of krypton and xenon by crystals of zeolite LiX and NaX, (4) 131*c*.
anomalous, of photoconductivity in $SrTiO_3$, (2) 74*j*.
of cation distribution in ferrimagnetic spinels, (11) 387*j*.
of ε and $tg\delta$ of sitalls containing compounds of Ce, Bi, and Pb, (2) 77*i*.
of *F* band in MgO, (1) 39*d*.
of *F*-center absorption in KBr and NaBr, (9) 331*j*.
of *F*-center production in KCl, (4) 159*a*.
of far-infrared reflectivity of magnesium stannide, (2) 84*b*.
of heat-pulse propagation in sapphire, (2) 84*c*.
of internal friction and of modulus of elasticity of basic refractories, (2) 78*j*.
of low-frequency transverse optic lattice vibration of $BaTiO_3$, (1) 39*e*.
of microwave dielectric constant of GaAs lattice, (4) 159*b*.
of Mie scattering and absorption cross sections for Al_2O_3, (1) 39*f*.
of nuclear quadrupole frequency of ^{23}Na in $NaBrO_3$, (10) 359*a*.
of nuclear quadrupole, resonance frequency of ^{79}Br in $NaBrO_3$ and $KBrO_3$, (8) 299*j*.
of nuclear quadrupole resonance in cuprous oxide, (4) 159*b*.
of paramagnetic relaxation of Mo^{5+} in TiO_2, (4) 159*c*.
of Raman spectrum of $SrTiO_3$, (4) 159*f*.
of Raman spectrum of $SrTiO_3$ and $KTaO_3$, (4) 159*c*.
of serpentine dehydroxylation, (4) 142*g*.
of SiC oxidation, (4) 159*h*.
of surface potential of Si(III) surfaces with silicon nitride layer, (1) 39*g*.
of ultrasonic paramagnetic resonance in $MgO:Fe^{2+}$, (4) 159*d*.
of velocity and absorption of ultrasonic waves in perovskite-type ferroelectric solid solutions, (4) 159*d*.
distribution, in end-fired melter, (1) 9*e*.
distribution, in pulled crystals, analysis, (7) 263*i*.
effect on Si stain films growth, (9) 320*b*.
field, of cooling casting with different thermophysical characteristics in mold and external insulation, calculation, (2) 47*a*.
glass transition, of Se, (4) 137*h*.
Temperature *(continued)*
gradient, linear, radiation transfer across spherical pore in, (10) 359*f*.
gradient, nonuniform, formation and behavior of gas bubbles in, (8) 292*h*.
grinding, relation to cement quality, (4) 92*d*.
high, behavior of carbonaceous materials at, (1) 25*a*.
chemistry, advances in: Vol. I, B (4) 165*a*.
materials and technology, B (1) 41*h*.
probe, P (10) 347*j*.
processes, accompanied by changes in weight, apparatus for kinetic studies in, (2) 68*j*.
properties, of basic refractories, equipment for determining, (6) 215*i*.
quenchable effects, on cubic monoxide of Ti, (2) 82*h*.
resistant structures, P (6) 218*d*.
studies, to 1900°C on calcium orthosilicate and tricalcium silicate, (7) 266*e*.
maximum, indicated by ceramic film, P (4) 122*a*.
measurement, apparatus and method, P (5) 188*e*.
circuit arrangement for, P (1) 22*a*.
optical, in glass works, (7) 260*i*.
precise, and calibration, (7) 260*j*.
system, P (6) 228*c*.
Néel, of Cr_2O_3, pressure dependence, (9) 328*d*.
Néel in FeO and CoO, effect of hydrostatic pressure, (1) 27*j*.
and pressure dependences of isotropic elastic moduli of polycrystalline Al_2O_3 (7) 268*e*.
pressure-, study of sulfospinels, (1) 35*i*.
pressure-, studies of anatase, brookite, rutile, and TiO_2-II, (10) 359*b*.
programer, automatic fatigue test, P (2) 71*i*.
radiant self-stabilization, (1) 35*f*.
regulation, of laboratory furnace to 800°C with accuracy of ±0.02°C, (1) 22*j*.
response, transient, of thin-walled, transpiration-cooled porous surface, (4) 162*c*.
second-harmonic phase-matching, in $LiNbO_3$ crystals, dependence on melt composition, (1) 26*j*.
sensor probe, P (9) 316*a*.
setting-, measurement simultaneously with thermal expansion and Young's modulus of vitreous enamel in form of thin layer, (10) 336*g*.
softening, of chalcogenide glasses, (8) 276*f*.
of specimens in electron microscope, (2) 69*b*.
spin flip, shift, of α-Fe_2O_3 fine particles, (2) 82*j*.
superconductive transition, of $SrTiO_3$, effect of stress, (4) 133*b*.
transition, of lithium hexafluoroaluminate, solid, (9) 322*c*.
Temperature measuring instruments, for change, P (10) 348*b*.
dc-, in evaporated CaF_2 films, (8) 281*b*.
high, (1) 20*j*.
low, (1) 20*j*.
monitor, high speed, P (11) 381*e*.
for monitoring, in grade used for drying and calcining shapes, P (1) 22*a*.
pyrometer, and control of manufacturing processes with, P (5) 188*g*.
for determining spectral reflectance of opaque materials at high temperatures, P (7) 261*a*.
electronic radiant energy, P (4) 121*g*.
measures gas temperatures to 2500°C, (11) 380*a*.
polarization, P (11) 381*a*.
radiation, for glass temperature measurement, (7) 260*i,j*.
simple indicator, (7) 260*e*.
with sonic wave guide, P (1) 22*e*.
thermocouple, P (1) 22*h*.
assembly, or insulated electrical conductor with membrane gastight seal, P (4) 121*i*.
cements to nuclear rocket engine nozzles, (10) 342*a*.
for control systems, (1) 22*g*.
head, P (11) 381*d*.
high, P (1) 22*c*.
high temperature ZrO_2 coated, P (11) 381*f*.
junction, high-temperature stress-free, P (7) 260*i*.
metal, protected by boron carbonitride electric insulation tube, (6) 215*g*.
Ni alloy, P (10) 348*a*.
noble metal, with base metal compensating leads, P (9) 315*j*.
platinum, errors in continuous operation, (10) 348*b*.
Pt–Pt13Rh, effect of stress on thermal emf of, (6) 228*f*.
probe assembly, and temperature sensing circuits comprising, P (4) 122*b*.
with reducing atmosphere producing sheath, P (9) 316*a*.
swing mounted assembly, P (11) 381*b*.
welding, P (5) 188*i*.
thermometer, high-sensitivity quartz, (9) 315*a*.
mercury glass clinical, with maximum temperature recording trap, P (11) 371*d*.
piezoresistive, P (2) 66*e*.
printing and baking scales on, P (10) 339*d*.
problem of moving, (5) 187*f*.
thermoprobe assembly, P (4) 122*c*.
using semiconductor junction, P (5) 188*h*.
Tempering, of glass. See *Glass*.
Tension, of liquid films and contact angles between film and bulk liquid, (10) 362*i*.
surface, critical, of UO_2 (5) 193*g*.
of glass melts, effects of atmosphere and
Tension, surface *(continued)*
minor constituents, (4) 95*e*.
of molten polyphosphate mixtures, (9) 330*j*.
verification of empirical equations in computing by sessile-drop method, (1) 40*b*.
of zinc metaphosphate, (8) 299*d*.
tensile test, theory, (1) 22*f*.
test method for high-modulus, high-strength filaments, (11) 381*a*.
testing of Al_2O_3 whiskers, (5) 188*h*.
Terbium, chromite, magnetic structure, neutron diffraction study, (10) 357*f*.
oxide, activation of glasses in system Na_2O-B_2O_3 by, (2) 51*d*.
Terminology. See *Nomenclature*.
Testing. See also *Analysis* and specific types.
aggregate size, apparatus and process, P (7) 262*d*.
of brittle materials, and structural ceramics, B (11) 390*i*.
catalytic mufflers, with single cylinder engine, use of alumina-coated filaments in, (7) 260*e*.
ceramic materials and products, increased applicability of mercury porosimeter for, (7) 260*f*.
of foundry sand, P (11) 381*c*.
in-pile, facilities for, of cirene fuel rods, (7) 260*d*.
laboratory, of fusion sealed glazing units, (1) 7*d*.
methods, for chemical resistance of silicate glasses, (6) 210*c*.
properties, of tamping materials, P (11) 381*b*.
of refractories for construction and repair work as seen from literature, (6) 217*b*.
of refractory materials by high temperature cross bending and compressive strengths, (4) 104*d*.
and service performance, B (10) 366*a*.
tester, material, P (6) 227*i*.
tester, nondestructive, P (6) 228*a*.
transparent materials for lattice imperfections, P (4) 100*a*.
Tests, cylinder flow, for controlling viterous bonds, (4) 89*h*.
field, for common mineral elements, (2) 69*f*.
fusion flow, for frits, for calculation of viscosity, (6) 225*i*.
for grinding wheels, (7) 243*f*.
impression and scratching, for hardness anisotropy of crystals, (2) 70*a*.
methods and specifications in refractory industry, (6) 216*j*.
Palmqvist, for toughness testing of cemented carbides, influence of sample preparation on, (10) 347*h*.
potassium flame, improving, (8) 285*e*.
T-bend, for prefinished metal, (2) 71*b*.
torsion, for determination of adherence of porcelain enamels to steel, (2) 71*g*.
Texture, interrelation with mineralogy within Ordovician Lexington limestone section in central Kentucky, (1) 23*g*.
of pyrolytic silicon carbide, (4) 160*a*.
of refractories, study with scanning electron microscope, (4) 105*b*.
surface, coefficients expressing influence in computation of specific surface, (1) 26*e*.
Thallium, in alkali halide single crystals, fluorometric microdetermination: I, determination in sodium iodide, (6) 226*h*.
cation, distribution in thallium silicate glasses, (8) 275*j*.
monofluoride, enthalpy of formation and dissociation energy, (2) 76*i*.
selenide, semiconducting properties, (1) 17*c*.
systems. See *Systems*.
ternary chalcogenides, with Ga and In, (6) 238*j*.
thallous chloride, ionic conduction and thermal disorder in, (5) 195*j*.
thallous flouride, vaporization and gaseous dimerization, (2) 84*i*.
thallous nitrate, transport processes in, (8) 300*a*.
Thermal analysis, apparatus for, (7) 259*h*.
of carbonatation of $Ca(OH)_2$, (8) 289*b*.
of chlorite structures, synthesized, (4) 160*h*.
differential, of adsorbed water of porous glass and silica gel at room temperature up to −90°C, (4) 95*i*.
apparatus with interchangeable measuring heads, (7) 260*a*.
applications in cement chemistry, B (10) 364*b*.
application in investigation on calcium silicate bricks, (9) 303*i*.
of $BaTiO_3$ ceramics containing clay and dolomite, (4) 109*i*.
dehydration of clay minerals under N_2 reduced pressure by, (7) 264*j*.
for determination of dolomitic limestone, (1) 22*c*.
for determination of metallic Ni in catalysts and ceramic materials, (8) 284*i*.
effect, effect of thermoelement adjustment on magnitude, (4) 119*e*.
of Israeli clays and associated materials, (4) 132*d*.
methods and apparatus, P (4) 122*b*.
of mixture of gypsum and EDTA, (4) 119*d*.
peak, relationship with maximum reaction rate, (5) 199*b*.
of powdered materials, effect of particle size characteristics, (1) 21*f*.
for quantitative analysis of gypsum, (4) 120*j*.
quantitative method, application to forma-

Thermal analysis, differential *(continued)*
tion enthalpies of U_3P_4 and UP, (10) 350*g*.
quantitative, realization: II, solid-gas reaction, (8) 297*g*.
use in spontaneous combustion of coal, (4) 122*f*.
Thermal conductivity. See *Conductivity.*
Thermal decomposition. See *Decomposition.*
Thermal expansion. See *Expansion.*
Thermal properties, of $A^{III}B^{V}$ compounds: I, high-temperature heat contents and heats of fusion of InSb, GaSb, and AlSb; II, of InAs and GaAs, (10) 362*g*.
of actinide compounds, (10) 352*h*.
of alkali halide crystals with CsCl-type structure, (4) 160*g*.
of calcium tungstate, low-temperature, (9) 324*g*.
of ceramics, B (11) 389*h*.
convection, in horizontal crystal growth, (6) 239*a*.
high temperature, of mullite bricks, (4) 104*g*.
of silica at low temperatures, (4) 160*i*.
of sodium halides, (5) 201*i*.
of TaC and WC, (5) 201*f*.
Thermal shock resistance. See *Shock resistance, thermal.*
Thermistors. See *Resistors, electrical.*
Thermochemistry. See *Thermodynamics.*
Thermocouples. See *Temperature measuring instruments.*
Thermodynamics, adsorption of, interaction of water and silica powders, (4) 126*g*.
of adsorption at rutile-solution interface, (5) 191*i*.
analysis, of equilibrium in CeO_2-Ce_2O_3 system, (4) 161*g*.
of beryllium compounds, (1) 39*f*.
of carbide formation and graphite solubility in CaO-SiO_2-Al_2O_3 system, (4) 161*h*.
data of UN_x (x=1.5–1.75), (5) 201*b*.
of disordering process in albite, (6) 239*h*.
in ferroelectric and antiferroelectric Pb(Zr, Ti)O_3 compounds, (1) 16*c*.
functions, partial, of NaBr and KBr in respective bromide-chloride mixtures, (8) 290*e*.
of glassy state, (4) 97*h*.
of heterovalent cation exchange reactions in montmorillonite clay, (9) 332*e*.
of higher oxides: I, heats of formation and lattice energies of superoxides of K, Rb, and Cs, (1) 39*f*.
investigation of disorder in hydrates of disodium hydrogen phosphate, (5) 201*e*; in in hydrates of Na_2CO_3, (9) 332*h*.
of jadeite, (9) 332*d*.
of kyanite-sillimanite equilibrium, (7) 270*a*.
of λ transition in sodium nitrate, (5) 202*c*.
of liquid system PbO-B_2O_3 at 800°, (4) 161*e*.
of melting and fining with sulfate, (1) 9*g*.
of molten LiF-BeF_2 solutions, (11) 386*b*.
of nonstoichiometric oxide systems, (5) 201*i*.
and phase transitions in monolayers, (1) 39*f*.
of phosphorus halide-boron halide complexes, (4) 161*f*.
properties, of adsorbed water molecules, (1) 39*e*.
of alkali halides with CsCl structure, (2) 7*b*.
of aluminum hydride, (4) 161*j*.
of aluminum silicates, (4) 161*j*.
of beryllium compounds, (4) 161*h*; (5) 201*d*.
of bismuth trifluoride, (10) 362*i*.
of chromium carbides, (1) 38*c*.
of Cr_2O_3 and $FeCr_2O_4$ at high temperatures, (8) 300*h*.
and frequency shifts of molecular adducts of antimony pentachloride and molecules containing carbonyl group, (7) 270*b*.
high temperature, of binary alkali silicate glasses, measurement, (1) 7*d*.
high-temperature, of oxygen-deficient uranias, (10) 355*c*.
of minerals and related substances at 298.15°K (25.0°C) and 1 atm (1.013 bars) pressure and at higher temperatures, B (8) 302*h*.
of NiCl$_2$ molten mixtures with alkali halides, (10) 362*j*.
of oxides of Fe, Ni, Pb, Cu, and Mn by emf measurements, (10) 362*j*.
of PuO_2, (10) 354*e*.
of silicates, determination from locations of conjugation lines in ternary systems, (4) 131*i*.
of stoichiometric and nonstoichiometric NiO, (4) 161*f*.
of talc, new data, (4) 146*c*.
of uranium monosulfide from 1.5° to 350°K, (2) 84*d*.
of rare-earth-carbon systems: I, cerium-carbon system, (11) 388*d*.
of reacting materials, (8) 300*g*.
of reactions in Li_2O-SiO_2 mixtures, (4) 161*j*.
of reactions used for preparation of borides of groups II-VI metals, (1) 13*a*.
relations in partially liquid oxide systems, (5) 201*e*.
of solid solutions of uranium oxide: I, uranium oxide-thorium oxide; II, uranium oxide-yttrium oxide, (4) 161*b*.
of solution of oxygen and nitrogen in UC, (5) 202*b*.
stabilities, of $H_4B_4O_4(g)$ and $H_4B_6O_7(g)$, (4) 161*j*.
Thermodynamics *(continued)*
statistical method, for calculating composition dependence of chemical potentials in nonstoichiometric ZrC, (8) 292*d*.
studies, of dilute solutions of defects in rutile structure TiO_{2-x}, NbO_{2-x}, and $Ti_{0.8}Nb_{0.8}O_{2+x}$, (5) 201*g*.
in high-conducting solid systems RbI-AgI, KI-AgI, and NH_4I-AgI, (5) 201*g*.
of sublimation of SeO, (9) 332*i*.
of thermal decomposition of Al sulfate, (4) 162*b*; Al-S-O system from 850° to 1050°K, (4) 162*c*.
of titanium oxides, (1) 39*g*; (11) 383*i*.
of tungsten-oxygen system, (5) 202*d*.
of UOS; on attainment of equilibrium in Knudsen cells, (10) 362*i*.
values, for PuN, consistent set, (1) 26*i*.
of vaporization in Al_2O_3-B_2O_3 system, (4) 162*d*.
of vaporization of SnF_2 and PbF_2, (10) 356*j*.
of vaporization behavior of substoichiometric PuO_2 phase, (4) 161*e*.
of zinc halides, (6) 239*e*.
Thermoelastic properties, of fibrous composites, theories predicting, (2) 47*g*.
Thermoelectric materials, device, comprising oxide base thermoelectric element, P (11) 379*c*.
lead telluride base compositions, and devices using, P (11) 379*c*.
zirconia-based, P (9) 314*d*.
Thermoelectric properties, of $Bi_2Te_3Sb_2Te_3$-Sb_2Se_3 pseudoternary alloys, effects of growth rate, (5) 194*b*.
Thermoelectricity, body, including pyrolyzed reaction product of pyromellitonitrile and alkanol and with comminuted metal, P (1) 19*f*.
compositions, of Te, Mn, and Pb and/or Sn, P (1) 19*f*.
device, with graphite elements, P (9) 314*b*.
device, with graphite member between thermoelement and refractory hot strap, P (8) 284*a*.
elements, P (1) 19*d*.
bonding to nonmagnetic refractory metal electrodes, P (9) 312*c*.
Mn_4Si_7, process and product, P (2) 66*h*.
force, of Ag halides, effect of fusion on, (6) 232*d*.
power, anomalous, of $FeCr_2S_4$ near Curie temperature, (2) 74*i*.
power, in semiconductive TiO_2, (8) 292*g*.
Thermography, heat transfer measurement, (2) 63*j*.
of strontium iodide, (7) 170*b*.
Thermogravimetry, for analysis of gypsum plasters and minerals, (8) 284*h*.
analysis, and simultaneous infrared absorption spectroscopy of gas phases—manganese(II) carbonate thermolysis, (5) 202*f*.
application in investigation on calcium silicate bricks, (9) 303*i*.
of cobaltous oxide, single crystalline, (10) 352*f*.
for quantitative determination of binder and lubricant in ceramic materials, (5) 187*j*.
Thermoluminescence. See *Luminescence.*
Thermometers. See *Temperature measuring instruments.*
Thermophysical properties. See *Physical properties.*
Thickness, ablation shield, measuring, P (7) 261*a*.
coating, determination by means of measuring blackbody radiation resultant from infrared irradiation, P (4) 121*e*.
coating, tested by beta-ray scatter techniques, (8) 284*j*.
of films, monitoring apparatus, P (1) 22*b*.
gage, magnetic, with shielded magnet, P (7) 260*j*.
layer, of polymer adsorbed on TiO_2, viscometric technique for determining, (5) 188*c*.
measurement, of hot glass ribbons in flat glass industry, (9) 307*h*.
meter, electronic, with direct readout of coating thickness, P (7) 260*h*.
thickening, continuous, of flocculated silica slurry, (2) 67*e*.
of thin films grown on rough surfaces, measuring technique, (4) 120*g*.
of thin section, technique for estimating, (6) 227*e*; discussion, (10) 347*f*.
Thin sections. See *Microscopy.*
Thixotropy, control of porcelain bodies with higher Al_2O_3 content, (10) 343*f*.
Thoria. See *Thorium, oxide.*
Thorium, borides, electrical properties, (6) 232*b*.
carbides, nitrides, and carbonitrides, magnetic susceptibility, (4) 143*a*.
dioxide, cation diffusion in, study using α-ray spectrometry, (8) 298*f*.
and ThO_2-UO_2 solid solution, lattice and grain-boundary diffusions of protactinium in, (5) 196*i*.
and ThO_2-UO_2 solid solutions, lattice and grain boundary diffusion of U in, (8) 294*c*.
-1.3 wt% UO_2, annealing of irradiation-induced thermal conductivity changes in, (6) 208*e*.
Eu^{3+} activated, alkali metal vanadates, luminescence, (10) 356*d*.
fuel cycle, proceedings of second international symposium, 1966, B (6) 242*a*.
hydrides, activation energies for hydrogen diffusion in, (4) 126*d*.
hydrolysis products, structure, (8) 298*e*.
Thorium *(continued)*
in Mn nodules, (4) 124*d*.
nitrides, vapor pressure measurements, (4) 163*g*.
oxide, arc-melted, precipitates in, (1) 35*d*.
colloidal, small angle X-ray scattering study, (2) 83*d*.
single-crystal, absorption spectrum of Np^{4+} in, (11) 383*b*.
solid stabilized, with layer of Ta_2O_5 and TiO, P (1) 19*a*.
target elements, aluminum-clad, dissolving, P (2) 59*a*.
and ThO_2-CaO solid solutions, creep, (2) 75*f*.
oxychalcogenides, (9) 328*c*.
refractory compounds, characteristic temperatures and entropies, (4) 128*i*.
silicate, ground-state splitting of trivalent Gd and Cm in, determined by ESR, (11) 385*c*.
strength, effect of carbon, (4) 132*h*.
systems. See *Systems.*
Th(IV), compounds of Schiff's bases with, (4) 129*j*.
Th(IV) ion, hydrolysis in 3*M* (Na)Cl medium, (10) 361*i*.
ThP and ThP-UP solid solutions, preparation and properties, (4) 150*h*.
(Th,U)C_2-particles, coated, preparation by reaction sintering and coating in fluidized bed, (9) 308*i*.
Thortveitite, ESR, (4) 135*b*.
Thulium, orthoferrite, crystal structure, (5) 193*j*.
Tm^{2+} crystalline electric field parameters, Moessbauer effect determination in Tm-doped soda-silica glasses, (6) 210*i*.
Tile. See also *Pipe.*
assemblies, pregrouted ceramic, P (8) 280*d*.
and brick, cutting method for manufacture, P (11) 372*g*.
British ceramic, (4) 108*d*.
ceramic, influence of design in, (6) 206*d*.
decorative, P (1) 11*h*.
drain, shrink foil packaging, (10) 340*d*.
structure, P (4) 102*e*.
wrapping and palletizing, P (7) 250*b*.
earthenware, set on reinforced concrete slabs, measurement of stresses on, (4) 108*d*.
enameled ceramic, Italian, quantitative control of chromatic behavior of, (9) 309*j*.
floor, composition and process, P (4) 109*b*.
frost-resistant glazed, P (6) 220*c*.
glazed structural facing, used in school, (4) 102*g*.
hollow, fully automatic palletizing and drying, (7) 250*a*.
hollow, thermal shock resistance, measurement and calculation, (1) 15*j*.
manufacture from siliceous materials, P (1) 11*g*.
production, conveyor system for, (2) 59*j*.
roof, rain penetration, (6) 213*j*.
roofs, P (6) 214*g*.
setter loading device, P (4) 109*c*.
-setting frame apparatus, P (7) 254*b*.
sheets, devices for continuous manufacture, P (7) 254*a*.
vitrified ceramic, comparison of spraying dried bodies of, (6) 219*c*.
wall, developing production parameters for, once-fired in roller kilns, (6) 219*d*.
and floor, drying, (1) 15*c*.
packing methods, (4) 108*e*.
Tin, bromide and iodide, ultraviolet absorption spectra, (9) 332*f*.
galvanoluminescence, (8) 281*h*.
-lead-tin layer arrangement to improve adherence of photoresist and substrate, P (9) 314*b*.
oxides, chemical shift of the $K\alpha_1$ X ray in, (4) 128*d*.
crystals, electrical and optical properties, (10) 352*g*.
resistances, P (1) 19*d*.
sintering: I, influence of bismuth oxide addition, (4) 154*g*.
SnO_2, (4) 162*j*.
as solvent in solution growth of II-VI compounds, (8) 298*a*.
stannic oxide, powders, infrared absorption spectra, (10) 355*i*.
stannic oxide, single crystals, weak-field magnetoresistance in, (10) 363*i*.
stannic oxide, Zn-doped polycrystalline, electrical conductivity, effect of chemisorbed oxygen, (9) 320*g*.
stannous fluoride, vaporization thermodynamics, and SnF_2 dissociation energies, (10) 356*j*.
telluride, absorption edge, Burnstein shift of, (4) 127*g*.
tetrachloride, vibrational relaxation in, (5) 203*b*.
SnI_4 structure, theoretical morphology of crystals, (7) 270*h*.
Sn_4P_3, crystal structure, (4) 130*d*.
Titanates. See also *Dielectrics* and specific types.
-Al_2O_3 ceramics, dielectric properties, (8) 281*b*.
of bivalent metals, solid phase reactions, (7) 268*h*.
crystallization, under hydrothermal conditions, (8) 290*f*.
lead to other electronic ceramics, (2) 63*b*.
Titania. See *Titanium, dioxide.*
Titanium, -andradite, synthesis and stability, (9) 331*j*.
carbide. See also *Cermets.*
atomic scattering factors and defect concen-

Titanium, carbide *(continued)*
tration of structure, X-rays to study, (1) 40*c*.
boron-doped, nature of precipitates in, (1) 33*g*.
coatings, on iron, chemical vapor deposition, (4) 93*c*.
and dioxide, yield stress, effect of stoichiometry, (2) 76*e*.
formation by reaction of TiO_2 and carbon powder, (5) 178*g*.
free carbon determination in, (2) 69*h*.
hard alloy, sintered, P (9) 309*e*.
optical properties and band structure, (1) 33*i*.
X-ray study of electron density distribution in, (6) 240*b*.
for coating articles, and article produced, P (8) 280*f*.
cubic monoxide, quenchable effects of high pressures and temperatures on, (2) 82*h*.
diborides, borothermic preparation, (5) 192*g*.
hot-pressed, (2) 56*c*.
strength, effect of porosity and grain size, (2) 55*f*.
synthesis by carbon reduction, (1) 39*c*.
dioxide. See also *Rutile*.
P (4) 124*d*; P (10) 349*d*.
concentrate, P (8) 288*d*.
concentrate, production from massive ilmenite ores, P (10) 349*d*.
contribution to firebrick manufacture, (10) 340*i*.
fine particle size, process and apparatus for manufacture by reacting $TiCl_4$ with oxygen, P (4) 125*g*.
granules, P (2) 74*g*.
granules, use in molten glass batch, P (6) 213*g*.
high pressure electrical resistance, compressive strength, and nonstoichiometry, (5) 194*j*.
hot-pressing, P (11) 371*a*.
Mg surface for cooling, P (8) 287*i*.
making using CO containing inorganic ashes, P (7) 263*e*.
microporous, pore volume uncertainties, (4) 150*e*.
photon trapping in, (4) 149*h*.
pigmentary, P (6) 230*a*; 230*b*.
pigmentary, recovering from nonpigmentary waste TiO_2, P (11) 382*i*.
pigmentary size, P (6) 230*b*.
pigments. See *Pigments*.
polycrystalline, VRH and elastic moduli, (5) 203*d*.
polymorphic behavior under dynamic loading, (10) 358*h*.
powders, infrared absorption spectra, (10) 355*i*.
powders and single crystals, reduction, (11) 387*b*.
producing product high in, P (6) 230*e*.
production by chromium removal from beneficiated titaniferous ore, P (5) 191*g*.
pseudomorphs, pure, conversion of alkali metal titanates to, P (5) 191*e*.
raw pigmentary, treating, P (8) 288*b*.
semiconductive, Hall effect and thermoelectric power in, (8) 292*g*.
single crystals, growth by chemical transport with $TeCl_4$, (5) 194*c*.
sintered, polycrystalline structure, influence of thermal treatment, (10) 355*f*.
solid state reactions with $SrCO_3$, (9) 329*j*.
temperature dependence of paramagnetic relaxation of Mo^{3+} in, (4) 159*c*.
thermal stability, (4) 163*f*.
-II, anatase, brookite, rutile, pressure-temperature studies, (10) 359*b*.
graphitization of furfuryl alcohol coke by, catalysis of, (1) 11*j*.
and iron, simultaneous determination by polarographic methods, (5) 188*c*.
monoxide, compatibility of MgO with, (8) 289*a*.
(*g*), dissociation energy, and high-temperature vaporization and thermodynamics of titanium oxides, (11) 383*j*.
(*g*) molecule, dissociation energy, and thermodynamics of system titanium-oxygen, (11) 383*i*.
Nb-, binary alloys, silicided, oxidation behavior, (7) 246*d*.
nitride, production in direct current plasma, (11) 373*d*.
nitride refractory articles, ultrapure, P (9) 309*d*.
nitride, single crystal, oxidation kinetics by optical measurements, (11) 386*a*.
ores, treating with hydrochloric acid to produce titanium tetrachloride, P (2) 74*g*.
oxide, compounds, P (4) 126*b*.
crystallization under hydrothermal conditions, (8) 290*f*.
high-temperature vaporization and thermodynamics: III, vaporization characteristics of liquid phase, (1) 30*g*.
Madelung potentials and ordering energy in, (10) 356*e*.
pigment materials, colored, with spinel structure, and preparation, P (5) 190*h*.
role in alkaline basalts in light of system diopside-akermanite-nepheline-$CaTiAl_2O_6$, (10) 353*j*.
sesquioxide, antiferromagnetism in, (2) 74*j*.
silicide—Ti_5Si_4, (6) 235*h*.

Titanium *(continued)*
sulfate and TiO_2 concentrate, producing from titaniferous ore, P (4) 125*b*.
systems. See *Systems*.
tetrachloride, interaction with gallium chloride, (8) 293*e*.
reacting with oxygen or gases containing oxygen for manufacture of rutile pigment, P (10) 349*f*.
removal from gases, P (11) 382*e*.
vibrational relaxation in, (5) 203*b*.
Ti^{4+} coordination in glasses in RO–TiO_2 systems, (4) 97*j*.
Ti(IV) oxide (anatase), reaction with barium carbonate, measurements at high temperatures, (6) 235*a*.
$TiFe_2O_4$, ulvospinel, Moessbauer study, (2) 80*e*.
$TiO_{1.25}$, ordered structure, (2) 81*h*.
and TiO_2, μ-atomic Lyman and Balmer series in, (4) 145*e*.
Ti_2O_3 effective mass, (2) 84*a*.
Ti_2O_5, polymorphism, (10) 358*j*.
Ti_2Te_3, structural study, (5) 200*h*.
and Ti oxides, microvolumes, effect of chemical bonds on fine structure of X-ray emission spectra in, (4) 132*i*.
$(Ti_{1-x}V_x)O_2$, preparation and structural data, (8) 296*b*.
titaniferous ores, chlorinating, P (4) 125*i*.
titaniferous ore, producing titanium sulfate solution and TiO_2 concentrate from, P (4) 125*b*.
trichloride, crystalline, P (11) 382*j*.
trichloride, delta form crystalline, preparation, P (9) 317*b*.
trifluoride, sublimation pressures for, and stabilities of $TiF_3(g)$ and $TiF(g)$, by mass spectrometry at high temperatures, (8) 294*f*.
Tobermorite, 14 A, of Crestmore, and dehydration products, structure of silicate anions of, (5) 192*d*.
Tohdite, $5Al_2O_3{\cdot}H_2O$, formation conditions, (1) 30*b*.
Tooling, furnace, design for heavy loading, (8) 275*b*.
Tools. See also *Drills*.
abrasive cutting, contoured, P (7) 243*i*.
cleaving device, for use in ultrahigh vacuum, (4) 119*b*.
cutters, diamond milling or planer, P (1) 1*h*.
cutting. See also *Abrasives*.
diamond abrasive saw blade, P (8) 273*f*.
diamond saw, P (7) 243*h*.
for making slab cuts in resistor films, P (4) 112*b*.
diamond, P (7) 243*i*.
grinding. See *Grinding apparatus*.
program-controlled machine, for production of ceramic whitewares, (2) 60*a*.
Topography, micro-, studies of first order prism faces of synthetic quartz, (9) 324*f*.
surface, of nonoptical surfaces by projected interference fringes, (4) 121*j*.
surface, of quartz grown in RbOH and other alkali hydroxides, (7) 267*a*.
X-ray diffraction, B (1) 40*h*.
X-ray diffraction, for analysis of epitaxic growth layers of SiC, (10) 349*j*.
X-ray moire, of lattice defects in quartz, (9) 333*b*.
X-ray observations, of dislocations in mica, (1) 39*g*.
Tourmalines, synthetic, containing elements of first transition series, (5) 200*i*.
Trace elements. See *Elements*.
Tracers. See *Radioactive tracers*.
Transducers, P (10) 345*d*.
assembly, base mounted piezoelectric, with intermediate stress absorbing member, P (7) 255*f*.
electromechanical, material, P (9) 312*f*.
epoxy bonding to delay lines, P (2) 64*e*.
electromechanical, for routine measurement of static moduli of elasticity of ceramic and building materials, (6) 227*g*.
ferrimagnetic pressure, P (6) 221*a*.
field-effect electroacoustic, P (7) 256*h*.
material, isostatically hot-pressed sodium-potassium niobate, for ultrasonic devices, (1) 17*d*.
miniature pressure, P (7) 257*e*.
monocrystalline directional sonic, P (5) 184*i*.
multilayer piezoelectric thin-film, *c* axis flipping for, (4) 109*h*.
piezoelectric, P (7) 257*f*.
piezoelectric, for determination of metals at micromolar level, (8) 285*i*.
piezoelectric pressure, P (5) 184*h*; P (11) 378*e*.
quartz crystal temperature, P (5) 185*e*.
segments, connecting together plurality of, P (10) 345*e*.
semiconductive electromechanical, P (6) 223*c*.
semiconductive pressure, P (4) 116*b*.
semiconductor, mechanical to electrical, P (11) 377*e*.
surface-barrier diode, using high dielectric semiconductor material, P (8) 283*i*.
ultrasonic, P (10) 346*a*.
using electrically polarizable material, P (9) 314*c*.
Transfers. See *Decoration*.
Transformations, α, β-quartz, effect on diffusion of ^{22}Na in SiO_2 glass, (6) 208*i*.
of anhydrite, finely divided soluble, into orthorhombic anhydrite, (1) 39*i*.
aragonite-calcite, and vaterite-aragonite, catalysis and inhibition in, (6) 230*g*.

Transformations *(continued)*
behavior of Al_2O_3-SiO_2 minerals, (11) 388*e*.
of CaO to CaS at 1400° to 1650°C, (4) 162*a*.
dihydrate-hemihydrate, in gypsum, (9) 303*i*.
of finely divided cubic to trigonal iron(III) oxide, (4) 162*b*.
GeO_2, role of catalysts, (6) 237*a*.
high pressure, in zinc germanates and silicates, (4) 138*b*.
high-pressure phase, of oxides, coordination and volume changes accompanying, (10) 351*e*.
irreversible, of hexagonal BN by shock compression, (2) 79*i*.
low temperature hydrothermal, of kaolinite, (8) 289*i*.
magnetic and structural, in $RbFeF_3$, (4) 143*h*.
mechanism, of γ-Fe_2O_3 to α-Fe_2O_3, (6) 235*b*.
order-disorder, for binary, ternary, and quaternary alloys of type AuCu and $AuCu_3$ (2) 81*f*.
order-disorder, in potassium graphite, (9) 326*g*.
orthorhombic-cubic, in lead zirconate, pressure dependence of, (2) 82*e*.
phase, in complex processing of red mud, (6) 216*j*.
crystallographic, in ferric fluoride, (9) 319*j*.
in enamels, TiO_2-opacified: I, theory; II, comparison of theory with experiment, (4) 93*d*.
in firing of spinel-mullite mixtures and charges of cordierite and sapphirine, (6) 238*f*.
in $RbFeF_3$, (7) 267*j*.
thermally induced in iron carbides, (4) 161*d*.
Pm3m-Fm3m, of alkali halides and Born-Mayer model—CsCl and its solid solutions with RbCl, KCl, and CsBr, (4) 150*b*.
polymorphic, of sulfur, linear rate, (4) 142*i*.
polymorphic, of WB_2, (9) 327*j*.
silica, in system PbO–SiO_2, (1) 36*b*.
temperature, of sodium borosilicate glasses, phase-separated, (8) 277*b*.
thermal, of iodides of Co and Ni, (7) 270*h*.
thermal, of rhodium trichloride, (8) 289*j*.
Transformers, including BN insulation, P (6) 224*a*.
solid state, P (8) 283*h*.
Transistors, P (5) 185*h*.
Al_2O_3-silicon insulated gate field effect, (1) 25*c*.
avalanche, with reduced width in depletion region adjacent gate surface, P (8) 282*c*.
beam-of-light, utilizing *pn* junctions, P (5) 182*f*.
body, enclosing submerged integrated resistor, P (2) 67*a*.
chip, joining to printed circuit, by vibratory process, P (2) 67*a*.
constant gain power, P (11) 376*b*.
devices, hermetically sealed, method and apparatus for testing, P (4) 114*h*.
diffused junction germanium, low resistance contact to, P (2) 65*i*.
drivers, MOS field-effect, for laminated-ferrite memories, (8) 281*b*.
electrooptical, switching device, P (4) 112*i*.
epitaxial, with inverted structure, P (7) 257*h*.
field effect, P (5) 183*f*; P (7) 256*i*.
with ferroelectric control gate layer, P (5) 182*b*.
gate cooling structure for, P (10) 344*j*.
with insulated gates, P (10) 344*j*.
in integrated circuit with embedded grid, P (6) 221*a*.
with interdigitated source and drain and overlying insulated gate, P (4) 113*c*.
low capacitance, P (8) 282*b*.
making by diffusion, coating with oxide, and placing metal layer on oxide, P (9) 312*j*.
MOS, Hall effect devices, P (9) 313*g*.
remote-cutoff, P (1) 66*j*.
four-pole parameters, measurement, (4) 110*f*.
high frequency field effect, P (4) 113*j*; P (7) 256*a*.
high frequency, with sloping emitter junction, P (6) 221*e*.
high-voltage, with controlled base and collector doping and geometry, P (9) 312*b*.
with isolated region having *pn* junction from isolation wall to surface, P (4) 117*a*.
insulated-gate field-effect, P (4) 114*c*; P (6) 221*h*; P (10) 345*g*.
with controlled operating characteristics, P (8) 282*g*.
with critical bulk characteristics for use as oscillator component, P (7) 256*d*.
exhibiting maximum source-drain conductance at critical gate bias voltage, P (2) 65*d*.
with improved characteristics, P (4) 115*g*.
with interdigital source and drain and gate with limited overlap, P (9) 312*b*.
using lead salt, P (2) 65*d*.
with nonplanar gate electrode structure for optimizing transconductance, P (9) 312*c*.
with piezoelectric substrates, P (11) 377*a*.
with plural overlapped gates, P (7) 256*d*.
structure, with reduced current leakage, P (7) 256*d*.
with widening current path between source and drain, P (7) 256*c*.
integrated complementary MOS-type, structure, and method, P (7) 256*e*; P (8) 282*a*.
lateral, with improved injection efficiency, P (5) 183*g*.
Lh junction lateral, P (8) 282*b*.
mesa, with asymmetrical U-shape base electrode, P (9) 312*g*.
metal base, P (5) 185*c*.

Transistors *(continued)*
MOS field-effect, with 1 μm vertical channel, P (4) 115*a*.
MOSFET, self-registered molybdenum-gate, (5) 182*b*.
multiple emitter, with improved frequency and power characteristics, P (10) 345*b*.
narrow base, epitaxial growth method of making, P (10) 345*f*.
narrow emitter lateral, P (8) 283*f*.
n-p-n planar silicon power, experimental, (4) 110*g*.
pn junction, P (7) 257*g*.
polycrystalline CdS thin film field effect, fabrication, stability, and temperature dependence, (2) 63*a*.
power, method of assembly, P (4) 114*i*.
remote cutoff junction gate field-effect, P (9) 313*f*.
selection tree, 64-output MOS, development, (8) 281*a*.
semiconductor, high voltage, P (5) 183*f*.
semiconductor material type of, tester for determining, P (11) 379*b*.
silicon planar, P (5) 185*b*.
single diffused surface, P (8) 283*g*.
structure, complementary, P (4) 115*a*.
high frequency, P (11) 377*d*.
high frequency, with two-conductivity emitters, P (5) 183*d*.
integrated complementary, with equivalent performance characteristics, P (5) 183*f*.
superhigh-frequency, P (11) 377*e*.
surface treatment, P (4) 115*i*.
tapered insulated gate field-effect, P (7) 258*b*.
three-region complementary, monolithic structure with, P (4) 115*j*.
three-region or field effect complementary, monolithic structure with, P (4) 115*j*.
unijunction, with improved efficiency and heat transfer characteristics, P (5) 185*i*.
unipolar, P (10) 346*b*.
with very thin diffused base and epitaxially grown emitter, P (2) 65*h*.
Transitions, crystal-field, in MnO, optical absorption spectra, (11) 386*a*.
crystal field, total intensities, in MnO and MnS related to antiferromagnetism, (9) 332*b*.
ferromagnetic, of uranium monosulfide, (2) 84*d*.
interband optical, in extremely anistropic semiconductors: I, bound and unbound exciton absorption; II, coexistence of exciton and Landau levels, (5) 195*e*.
lambda, in $NaNO_3$, ultrasonic and infrared studies, (6) 239*d*.
laser, of GaAs in lightly doped limit, (9) 324*d*.
low-temperature electric dipole vibronic, in rock-salt- and zinc-blende-type structures, (1) 31*j*.
phase. See *Phase*.
pseudo-polymorphic, amphibole→pyroxene reaction, (9) 328*h*.
of surface phases, (9) 330*b*.
vibronic, in ruby and $MgO:V^{3+}$, (1) 40*c*.
Transmission, of infrared materials: III, spectra from 2μ: IV, bibliography, (1) 36*b*.
patterns, scanning-electron-beam anomalous, (8) 297*a*.
ultraviolet, of optical materials between 1050 and 3000 Å, effects of simulated high-energy space environment, (1) 28*i*.
Transmittance, of optically neutral glass filters, calculation, (6) 211*e*.
Transport, electrical, processes in BeO, (9) 321*e*.
energy, mechanisms, in ruby, (11) 386*a*.
ion, mechanism, in UO_2, (8) 291*c*.
ionic, in amorphous oxide glasses, (4) 96*j*.
in CsI, effect of alkaline earth impurities, (4) 133*e*.
and high-temperature internal friction in sodium silicate glasses, (1) 7*g*.
mass, in oxides, B (5) 204*a*.
mechanism of U in iodide process, (8) 300*a*.
in molten salts under pressure: I, glass-forming nitrate melts, (10) 338*c*.
phenomena in fluorite-type, cubic phases related to ZrO_2, (5) 202*j*.
processes, in low melting salts—thallous nitrate, (8) 300*a*.
physical chemistry, (10) 358*h*.
in refractories, (2) 58*g*.
in thermal oxidation of silicon, (1) 40*a*; (4) 129*c*.
properties, of stoichiometric and nonstoichiometric NiO, (4) 161*f*.
reactions of transition metal niobates, (6) 239*c*.
system, sample, for wet chemical analyzers, P (4) 122*a*.
thermal balance for measuring, during vapor phase crystal growth, (5) 188*j*.
vapor, reactions, for production of refractory crystals, (9) 328*f*.
Tricalcium. See *Calcium*.
Travertine, geochemical investigations, (9) 322*a*.
Tridymite, lattice constants and space groups, at 20°C, (6) 234*j*.
solution and diffusion of He and Ne in, (5) 200*a*.
Triodes, compound channel insulated gate, P (7) 256*b*.
device, space-charge-limited current, P (2) 66*h*.
p-channel enhancement MOS, development, (8) 280*j*.
Tritium, diffusional release, from irradiated BeO, (4) 131*f*.
Trituration. See *Crushing; Grinding*.
Tubes, arc, P (5) 182*f*.

Tubes *(continued)*
arc, ceramic, and closure member construction, P (5) 182*i*.
arc discharge, with electrode which contains light-emitting metal, P (2) 52*j*.
automatic recording settling, University of Southern California, calibration, (11) 379*i*.
camera, target plate for use in, P (10) 345*j*.
cathode ray, P (7) 249*h*.
apparatus for applying bonding material between implosion band and glass for, P (2) 52*i*.
color, screening, P (6) 223*j*.
display device, with hemispherical display area, P (2) 64*g*.
envelopes, P (2) 52*c*.
envelopes, glass parts for forming, P (1) 10*e*.
evacuation, P (11) 371*b*.
glass envelopes, treating, P (4) 100*j*.
high voltage connection for, P (6) 221*f*.
magnetic shielding means for, P (8) 282*d*.
mesa type combined direct viewing storage target and fluorescent screen for, P (1) 18*a*.
with nondiscoloring X-ray absorptive display window, P (5) 182*h*.
and other vacuumized, resistant to violent devacuation, P (2) 52*c*.
cathode ray oscilloscope, development, (4) 109*h*.
cathode-ray storage, mica membrane mounting structure for, P (8) 283*j*.
closed, apparatus, for deposition of silicon oxide, (1) 20*j*.
closure with refractory oxide material, P (6) 221*a*.
color, with mask interior peripheral shield of treated steel foil for improved heat radiation, P (2) 64*i*.
color picture, containing red-emitting Eu-activated yttrium oxysulfide phosphor, P (5) 182*j*.
color TV, display, with ferromagnetic screening member, P (5) 182*a*.
color TV, structure, P (2) 64*i*.
discharge, P (5) 182*e*.
gas-filled, and electrical energy generators using, P (11) 376*h*.
glow-, containing radioactive primer, P (11) 376*h*.
satisfactorily low in radio-interfering noise, P (5) 182*f*.
electric discharge, nonevaporative getter for, P (2) 53*j*.
glass, helically shaped, apparatus for forming, P (5) 174*g*.
union for, P (5) 175*a*.
work holder for aligning and sealing beaded wire element into, P (4) 101*e*.
hot drawing, P (1) 10*i*.
image orthicon, faceplate, glass composition for use as, P (4) 98*i*.
krypton-xenon flash, for pumping ruby laser, P (7) 256*g*.
lead glass, surface reduction, (10) 338*a*.
mercury vapor, with special discharge chamber means separating mercury electrodes, P (2) 53*e*.
pulsed CdS laser cathode-ray, experimental, (8) 281*g*.
radioactive radiation counter, with improved high temperature properties, P (8) 283*a*.
recording settling, inexpensive, for analysis of sands, (11) 380*f*.
sealer, microhematocrit, P (4) 100*d*.
TV picture, metallic members for, P (4) 99*b*.
three-electrode cold-cathode gas laser, P (1) 19*g*.
video, method and apparatus for making implosionproof, P (11) 371*d*.
Tungstates, alkaline earth, Bi-doped, phototropy, (4) 149*j*.
crystalline, $M^{2+}WO_4$, (6) 231*a*.
dipole-dipole interactions in, (6) 231*g*.
ortho-, condensation, in fused equimolar $NaNO_3$-KNO_3 solvent, (4) 157*a*.
Tungsten, alloyed with lanthanide oxides, thermoemission, (9) 332*j*.
bronze-type crystal structures, ferroelectric: I, barium strontium niobate, (5) 194*f*.
-bronze structure, alkali-rare earth niobates with, (8) 288*f*.
carbide, cobalt-bonded, P (10) 335*h*.
-cobalt hard metal, thin foils of, (9) 332*a*.
preparation by electrodeposition, (8) 286*i*.
-10% (Ni-Fe) alloys, properties, (4) 151*j*.
sintered materials, wear properties, (1) 13*e*.
dioxide, reaction with liquid sodium, (1) 35*i*.
dioxide diiodide, thermal behavior (5) 202*b*.
dioxide iodide, preparation and properties, (5) 202*b*.
disulfide, crystallization from molten slags, P (1) 13*h*.
disulfide, rhombohedral crystalline, preparing, P (1) 14*i*.
hexafluoride, vibrational analysis, (4) 163*f*.
high-temperature, kinetics of attack by atomic oxygen, (4) 141*i*.
monocarbide, thermal properties, (5) 201*f*.
oxide, reduced, P (2) 74*e*.
oxide tetrafluoride, crystal structure, (5) 194*i*.
oxygenated, and thoriated surfaces, formation of positive and negative ions on, (8) 292*i*.
powder bodies, infiltrated with Zr, production, P (9) 309*h*.
selenide, preparation and electrical properties, (11) 376*d*.
systems. See *Systems*.

Tungsten *(continued)*
ternary peritectics with molybdenum and UC, (4) 159*i*.
trioxide, single crystals, vapor growth, (8) 300*a*.
WB_2, polymorphic transformation, (9) 327*j*.
Twinning, of crystals. See *Crystals*.

Ultrasonics. See *Sonics*.
Underwater vehicles, glass for, (2) 47*j*.
structural evaluation, (1) 9*h*.
Urania. See *Uranium, oxide*.
Uranium, -activated compounds with rock salt lattice, fluorescence, (10) 353*g*.
carbide, fission induced sorption of krypton in, (9) 321*e*.
heat of formation, (4) 138*h*.
molecules, mass-spectrometric evidence for, and predicted stability of diatomic carbides of electropositive transition metals, (11) 385*j*.
particles, dissolution in U during post-irradiation annealing, (10) 340*i*.
ratio of grain boundary to surface energy for, (6) 236*j*.
self-diffusion measurements, and application to related activated processes, (4) 143*e*.
sintered, structure, effects of Ni, (4) 133*h*.
and sulfide, enthalpies, high-temperature adiabatic drop calorimeter for measurement between 330° and 1700°K, (5) 195*b*.
carbides, compatibility relationship with alloys of iron, nickel, and chromium, (4) 129*f*.
carbides and nitrides, entropy measurements, (5) 200*j*.
compounds, nitrogen determination in, (4) 120*h*.
separation of trace contaminants in, through carbonates, (10) 347*e*.
variation of solid fission product and gas swelling in, with thermal neutron dose rate, (8) 300*g*.
detection, means and method, P (1) 22*d*.
diffusion in UC, (10) 352*e*.
dioxide, and carbide, evaporation, mass spectrometric study, (1) 32*j*.
and carbide, irradiated at low temperatures, density measurements, (8) 290*a*.
-cladding gap, under irradiation, (2) 54*h*.
columnar grain growth in, (4) 128*j*.
critical surface tension, (5) 193*g*.
crystalline, preparation by thermal decomposition of $UOCl_2$ dissolved in molten UCl_4, (10) 359*e*.
crystals, grown by solar furnace, (7) 270*e*.
dissolution in nitric acid, effect of crystallographic orientation, (5) 193*g*.
electrolysis and ion transport mechanism in, (8) 291*c*.
as fuel for atomic reactors, (2) 58*h*.
fuel pellets, irradiated, transmission electron microscopy, (8) 300*j*.
grain growth in: III, factors influencing equiaxed grain growth, (4) 137*b*.
graphite-, reaction, from 1400° to 1756°C, kinetics, (7) 267*i*.
heat content, from 1200°-3100°K, (5) 194*h*.
high density, particles and compositions, preparation, P (8) 280*a*.
hydrothermal precipitation, from uranyl nitrate solution, (2) 73*f*.
isothermal elastic modulus, (1) 12*j*.
low-energy electron diffraction studies, (6) 234*e*.
melting point determination, (1) 27*e*.
migration of krypton bubbles in, (4) 144*f*.
oxygen-rich, nonstoichiometry at high temperatures, dependence of flow stress on, (4) 131*c*.
particles, irradiated, fission product segregation at surface of, (6) 232*g*.
pellets, fluorination by F_2, kinetics, (5) 196*c*.
polycrystalline, yield and flow, (10) 363*g*.
powders, crystallinity, evaluation by streaming potential studies, (2) 55*h*.
powders, sintering, role of crystallinity in, (2) 57*d*.
powders, storage behavior, (8) 298*i*.
reaction with liquid sodium, (1) 35*i*.
single-crystal, relaxation processes in, (8) 297*j*.
single crystals, yield and flow, (9) 333*a*.
sintered, high-temperature thermal conductivity, (2) 56*b*.
for sintered nuclear fuel pellets, P (2) 59*c*.
sintering, development of high density and controlled microstructure in sintered UO_2 pellets, (11) 374*e*.
sintering, initial phase, Dorn method in study of, comment and reply, (1) 26*g*.
steam oxidation kinetics and oxygen diffusion in, at high temperatures, (10) 361*b*.
surface-diffusion studies, (6) 238*f*.
surface diffusivity, tracer study, (7) 270*d*.
surface self-diffusion, (4) 158*f*.
temperature-dependent shear modulus, calculation, (4) 127*b*.
thermal conductivity, effect of porosity, (4) 133*e*.
thermal conductivity at very high temperature gradients, comments, (8) 289*a*.
ThO_2-1.3 wt%, annealing of irradiation-induced thermal conductivity changes in, (6) 208*e*.
fluoride, obtainment, P (2) 59*d*.
inclusions, dihedral angles, in hypostoichiometric UC, (8) 290*h*.

Uranium *(continued)*
lattice and grain boundary diffusion, in ThO_2 and ThO_2-UO_2 solid solutions, (8) 294*c*.
monocarbide, of controlled composition, preparation by carbothermic reduction of oxides in vacuum, (4) 150*h*.
and dicarbide, free energies of formation, (4) 157*h*.
dissociation behavior, (8) 290*j*.
extruding method, P (6) 217*g*.
ternary peritectics with tungsten and Mo, (4) 159*i*.
thermodynamics of solution of oxygen and nitrogen in, (5) 202*b*.
monocarboxides, deficient in metalloid—composition and lattice parameters, (5) 202*d*.
mononitride, hydrolysis, (4) 139*a*.
nitrogen and oxygen determination in, (6) 226*i*.
phosphide, and sulfide, preparation and fabrication, (4) 150*a*.
monophosphide, solid state preparation, (8) 279*d*.
monosulfide, ferromagnetic transition, heat capacity and thermodynamic properties from 1.5° to 350°K, (2) 84*d*.
nitride, mixed crystal formation with nitrides, (9) 324*i*.
oxidation and deformation studies by electron microscopy, (1) 33*j*.
spherical particles, with porous interior, preparation, P (4) 106*j*.
thermal conductivity, low-temperature, (11) 385*e*.
UC, and $(U,Pu)C_{1-x}O_x$, reaction of oxygen and water vapor on, (1) 12*i*.
oxide, fluorination with bromine pentafluoride, engineering-scale studies, (5) 177*h*.
high-temperature hemispherical spectral emittance at 0.65 and 0.70 μm, (6) 233*a*.
oxygen-deficient, high-temperature thermodynamic properties, (10) 355*c*.
pycnometer, dry-pressing, (1) 12*a*.
solid solutions, thermodynamic study: I, uranium oxide-thorium oxide; II, uranium oxide-yttrium oxide, (4) 161*b*.
oxide fluorides, magnetic and spectroscopic properties, and structural relation to U oxides, (10) 356*i*.
oxychalcogenides, (9) 328*c*.
-Pu alloy, synthesis and fabrication of (U,Pu)C nuclear fuel pellets from, (10) 342*j*.
and plutonium, mixed oxides, thermal conductivity study, (8) 300*c*.
sesquinitride, two varieties, phase relations between, (10) 358*b*.
-silicon alloys, δ-peritectoid reaction, effect of carbon, (8) 291*c*.
NaCl-type compounds, solid-solubility relationships and atomic size in, (1) 37*f*.
solubility in UO_2, (5) 199*j*.
sulfide, single crystals, electron microscope studies: I, slip behavior; II, precipitation phenomena, (1) 28*f*.
systems. See *Systems*.
tetrafluoride, P (4) 107*f*.
-transition metal silicides of UM_2Si_2 composition, (5) 202*e*.
transport mechanism, in iodide process, (8) 300*a*.
trifluoride, magnetic susceptibility in range 2°–300°K, (4) 143*b*.
trioxide, α-, quantitative X-ray phase analysis of mixtures of, with amorphous modification of UO_3, (4) 151*h*.
trioxide, aquasol process, P (10) 349*f*.
trioxide dihydrate, properties, (5) 199*f*.
U(IV), compounds of Schiff's bases with, (4) 129*j*.
U(IV) and uranyl(VI) formates, thermal decomposition, (5) 201*d*.
^{233}U, diffusion in UO_2, (11) 383*f*.
-UAs phase diagram, (4) 163*b*.
UC_2, neutron diffraction study of 300°–5°K, (4) 146*a*.
U_2C_3, stability, (9) 330*d*.
U C phases, existence domains, influence of oxygen, (10) 355*e*.
UO_2^{2+} ion, infrared absorption intensity of ν_3 vibration, in nitrate and thiocyanate media, (9) 323*j*.
UO_{2+x}, cation diffusion in, study using α-ray spectrometry, (8) 298*f*.
UO_{2+x}, statistical model of partially ordered defects in, (9) 330*f*.
UN_x (x=1.5–1.75), thermodynamic data, (5) 201*b*.
UOS, thermochemistry; evaporation of US-UO_2 mixtures; on attainment of equilibrium in Knudsen cells, (10) 362*i*.
U_3P_4 and UP_2, formation enthalpies determination, application of quantitative method of differential thermal analysis to, (10) 350*g*.
(U-Pu)O_2, spectrographic analysis of impurities in, (8) 285*e*.
β-US_2, single crystals, preparation and electrical resistance, (4) 150*j*.
(U,Th)C_2-particles, coated, preparation by reaction sintering and coating in fluidized bed, (9) 308*i*.
uranyl ion, hydrolysis in $Mg(NO_3)_2$ medium, (10) 361*i*.
uranyl(VI) oxalate, thermal decomposition, (5) 201*e*.

Vacuum, high, technology, materials of: Vol. 2, silicates; Vol. 3 auxiliary materials, B (2) 85*f*.
influence on pore texture of firebrick during heating, (2) 56*i*.
to intensify fining process of glass, (2) 50*e*.
tightness of forsterite ceramics, (6) 219*f*.
ultrahigh, cleavage device for use in, (4) 119*b*.
ultrahigh, universal motion device for use in, (2) 71*j*.
Vanadium, in $CaWO_4$, spin-resonance properties, (4) 155*i*.
carbide, orthorhombic β′ phases, (9) 326*h*.
powders, changes in properties during pressing, (6) 230*i*.
strain measurement in, and significance, (5) 177*f*.
carbonitride solutions, twin-crucible studies, formation of active carbon in, (7) 265*j*.
carbonitrides, crystallizing in cubic δ-V(C-N) system, preparation, (8) 296*d*.
chalcogenides and NiAs structure, (9) 332*h*.
and Cr, in ZrO_2, crystal field studies, (4) 130*c*.
diboride, borothermic preparation, (8) 288*j*.
dioxide, high frequency conductivity, (8) 292*j*.
infrared optical properties, above and below transition temperature, (2) 79*b*.
phase transition in, (8) 296*f*.
tetragonal phase, thermal expansion, (2) 84*g*.
single-crystal growth, by isothermal flux-evaporation, (9) 329*f*.
single crystals, epitaxial growth, and anisotropic properties in electrical resistivities, (10) 353*c*.
in fuel oil, causes discoloration of glass, (4) 95*j*.
graphitization of furfuryl alcohol coke by, catalysis of, (1) 11*j*.
interference in titrimetric determination of iron by tin(II) chloride-mercury(II) chloride-dichromate method, (9) 315*i*.
oxide, single crystals, epitaxial growth and electrical properties, (2) 76*i*.
oxides, higher, paramagnetic ESR spectra, (6) 235*d*.
pentoxide, for chemical polishing of α-corundum surfaces, (4) 150*f*.
single crystals, optical properties, (5) 198*a*.
water-soluble, quantity in melts of CaO-V_2O_5-Na_2O system, effect of lime, (8) 291*g*.
quadrupole coupling tensor in KVO_3, (4) 163*d*.
in silicate materials, determination by atomic absorption spectrophotometry, (7) 259*j*.
systems. See *Systems*.
trioxide, P (4) 125*f*.
$^{51}V^{2+}$ spin, Hamiltonian, in MgO, as derived from electron nuclear double resonance, (9) 329*g*.
VC_2 ordered compound, structure, (4) 156*j*.
VO^{2+}, EPR, in sphene and apophyllite, (1) 28*i*.
VO^{2+} in KNO_3 and $CsNO_3$ single crystals, EPR studies, (8) 291*g*.
VOF_5^{3-} ion, ESR study, (10) 353*g*.
V_2O_3, metallic single crystals, magnetic susceptibilities, (4) 143*i*.
V_3Si-type superconducting compounds, anomalous properties, (2) 74*i*.
Vapor pressure, of B_2F_2, (4) 163*f*.
of boron oxide over range 1946°–2419°K, (4) 163*d*.
of calcium nitride, (8) 300*c*.
of cerium (III) fluoride, (4) 163*f*.
dependence of serpentine dehydroxylation, (4) 142*g*.
measurements, on thorium nitrides, (4) 163*g*.
of metallic elements, atomic absorption spectrophotometry as technique in determination, (1) 20*i*.
of praseodynium trifluoride, (10) 363*g*.
of refractory metals at high temperatures, determination by shock-tube method, (5) 188*c*.
of Rb_2O-B_2O_3 liquid system, (4) 163*f*.
of silicon, (1) 34*d*.
of AgF, (6) 234*i*.
studies on thermal decomposition of NbO_2F, (4) 163*i*.
in tetrachlorides of Zr and Hf, (8) 300*f*.
and vapor dimerization of AlF_3 using entrainment method, (5) 202*i*.
Vaporization, of alkaline-earth and rare-earth metal dicarbides, (5) 202*i*.
in Al_2O_3-B_2O_3 system, thermodynamics of, (4) 162*d*.
in BeO-B_2O_3 system, thermodynamics, (2) 84*h*.
characteristics, of zinc chloride, bromide, and iodide, (10) 363*h*.
characteristics, of $ZrTe_5O_8$, (1) 30*e*.
of chrome ore at high temperatures, (7) 252*a*.
high-temperature, of titanium oxides: III, vaporization characteristics of liquid phase, (1) 30*g*; (11) 383*j*.
laser-induced, mass spectrometric studies: I, selenium: II, bismuth-selenium system, (5) 196*f*.
rates, condensation-enhanced, in nonistothermal systems, (6) 231*f*.
of refractory compounds, mass spectrometric studies, (5) 196*f*.
of SmC_2, Knudsen cell studies of, (6) 234*e*.
of sintered oxide ceramics, (4) 163*i*.
of NaCl single crystals, effect of dislocations on rate, (2) 75*j*.
of thallous fluoride and its gaseous dimerization, (2) 84*i*.
of ytterbium dicarbide, (5) 203*a*.

Vapors, adsorbed, surface flow, (1) 38*i*.
coating, employing degassing of coating metal, P (2) 67*a*.
composition, effects on growth rates of faceted GaAs hole deposits, (10) 352*j*.
phase, growth of aluminum phosphide, (10) 363*g*.
preparation of mixed compounds, apparatus for, (1) 20*j*.
process for conversion of metal halides into oxides, P (4) 126*b*.
plating apparatus, including rotatable substrate support, P (2) 67*a*.
Vermiculite, cation-exchanged, X-ray studies, (7) 270*g*.
clay particles, morphology, as affected by genesis, (II) 386*f*.
crystals, hydrated, restricted anisotropic diffusion and anisotropic nuclear spin relaxation of protons in, (5) 199*c*.
paper, P (6) 218*g*.
single crystal, proton magnetic resonance in, (6) 236*b*.
Vibration, lattice, analysis, of perovskite fluorides, (4) 140*j*.
lattice, optically active, in wurtzite-type crystals of ZnO and CdS, (4) 147*d*.
lattice, in tetragonal $BaTiO_3$, X-ray studies, (5) 203*b*.
low-frequency, of water molecules in beryl, (6) 234*c*.
low-frequency transverse optic lattice, of $BaTiO_3$, temperature dependence of, (1) 39*e*.
for mixing, (5) 186*c*.
modes, localized, due to U centers in NaCl and KCl, influence of additional cation impurities on, (2) 78*g*.
molecular, in crystals, (8) 290*i*.
pseudolocalized, of M^{2+}-vacancy complex of alkali halides, (4) 151*d*.
thermal, amplitudes, of carbon atoms in graphite lattice parallel to c axis, (4) 161*c*.
three-dimensional, for pelletizing on flat surface, (8) 284*f*.
Viscometers, canal, analysis for Bingham plastic surface flow in, (1) 20*i*.
high-pressure, high-temperature, (9) 315*f*.
industrial, for glasses in high viscosity range, (5) 172*i*.
for measuring viscosities of molten silicates, (2) 70*a*.
quartz-crystal, change in resonant frequency with pressure to 8000 atm of, (9) 305*e*.
rotational, for powders and granules, (4) 121*e*.
Viscometry, oscillating plate: I, theoretical principles, (9) 315*b*.
technique for determining layer thickness of polymer adsorbed on TiO_2, (5) 188*c*.
Viscosity, of B_2O_3, pressure dependence, (1) 8*d*.
of B_2O_3 glass, inadequacies of theories, (4) 96*e*.
calculation by means of fusion flow test for frits, (6) 225*i*.
of fused salt, effect of internal coulomb field, (11) 384*f*.
glass, change, forehearth addition process for, P (8) 277*j*.
Czechoslovak technical, (1) 9*j*.
float, electrical control, method and apparatus, P (8) 277*g*.
silicate and chalcogenide, new type of temperature function of, (2) 50*g*.
simultaneous measurement with electrical resistivity in melting and working range, (5) 173*b*.
sodium borosilicate, phase-separated, (8) 277*b*.
low, providing for aged siliceous slurries, P (1) 24*e*.
low-temperature, in copper-red glasses, (10) 338*d*.
low-temperature, measurements for glass plant composition control, (10) 338*a*.
measurement apparatus, for glasses in range 10^4–$10^{2.5}$ P, (1) 8*i*.
in molten BeF_2-LiF solutions, (10) 338*d*.
of molten salts, (7) 262*f*; B (10) 365*f*.
polymer-melt, and glass transition—evaluation of Adam-Gibbs and free-volume models, (4) 97*b*.
properties, of blast furnace slags, (5) 178*f*.
reduction, of alumina hydrate filter cake, P (2) 74*h*.
of spinellite melts up to 2500°, (8) 290*f*.
-temperature curve, of glass, calculation from fixed points, (4) 94*h*.
and temperature dependence in molten BeF_2, (1) 10*a*.
of titania one-coat enamels, (6) 207*h*.
of vitreous silica in transformation range, (8) 300*h*.
Voids, content, in glass-filament-wound composites, quantitative measurement, and correlation of interlaminar shear strength with, (1) 8*a*.
distribution according to volume, (5) 190*c*.
micro-, in glass-resin composites, (1) 7*j*.
shaped, structures containing, P (6) 218*b*.
Voight-Reuss-Hill, approximation, of polycrystalline ZnO, TiO_2, and α-Al_2O_3, (5) 203*d*.
Volatilization, oxide, effect on oxidation kinetics of Cr and Fe-Cr alloys, (1) 28*b*.
Voltammetry, potential sweep, of Na_2O-SiO_2 glass melt by stationary platinum electrodes, (1) 8*b*.
Volume, apparent molal, and expansibilities of

Volume *(continued)*
electrolytes in dilute aqueous solution, (8) 288*i*.
apparent and partial molal, of Na-kaolin and NaCl in kaolin suspensions, (8) 288*j*.
change zone, in clay layer, measurements in situ, (5) 190*f*.
isothermal, change of Se, (4) 137*h*.
molar, of binary phosphates of Na, Li, Ca, and Zn, (4) 158*g*.
-symmetry-entropy relations, in polymorphs, (1) 39*a*.
thixotropic and sedimentary, of kaolins and clays, (4) 124*b*.

Wallboard, gypsum, P (4) 92*h*; P (11) 368*e*.
Wastes, disposal, cost factor for glass container industry and manufacturers of other packing materials, (9) 306*c*.
industrial, municipalities' handling, (1) 4*i*.
plating, treatment, (1) 20*g*.
radioactive, processing, Pt for high temperature crucibles used in, (5) 178*a*.
water and slimes, handling methods, (10) 363*j*.
Water. See also *Humidity; Moisture; Steam.*
adsorbed, by partially dehydrated K Cr alum, dielectric behavior, (9) 319*i*.
of porous glass and silica gel, DTA at room temperature to -90°C, (4) 95*i*.
on silica, infrared study, (1) 31*d*.
on NaCl, effect of prior exposure to HCl, CO_2, and water vapor, (4) 126*h*.
attack, on lithia glasses in relation to phase separation phenomena, (2) 52*f*.
and CO_2 adsorption on MgO, infrared study, (8) 293*c*.
chemically combined, for combating black coring in structural clay products, (1) 11*g*.
clay-, relations in stiff clays, (5) 192*i*.
content, effect on phase separation in soda-silica glasses, (11) 369*f*.
effect on refraction and densities of glasses of various compositions, (6) 209*i*.
effect on strength of porous disperse bodies, (5) 192*i*.
desorption, from rutile surface, kinetics, (1) 31*d*.
diffusion, into fused quartz lamps, calculation, (7) 246*j*.
diffusion, in soda-lime glass within and near transformation range, (7) 247*b*.
effect on crushed quantity and grain size of raw material during crushing process, (10) 341*d*.
extraction, of decomposition products of modified ilmenite treated with sulfuric acid, (7) 262*c*.
industrial, usage, measuring, methods and installation, (10) 363*j*.
interaction of montmorillonite surface with: III, applicability of BET equation on sorption isotherm of water vapor by montmorillonite, (7) 267*e*.
interaction with silica powders, adsorption thermodynamics of, (4) 126*g*.
ionization equilibria in, at 25°C, effect of pressure, (11) 384*a*.
pollutants, from porcelain enameling operations, (5) 171*b*.
role in electron transfer reactions, (6) 237*a*.
silica-, interface, (1) 36*b*.
Si absorptiometric determination in, (7) 259*g*.
silicon content of, determination, (6) 225*j*.
solubility, in liquid CaO-SiO_2 with Al_2O_3, TiO_2, and FeO at 1550°C, (11) 374*g*.
solubility, of porcelain enameled ware, (10) 337*c*.
systems. See *Systems.*
toughening effect on MgO crystals, (4) 148*a*.
vapor, adsorption by inorganic oxides, (1) 24*j*.
effect on length change characteristics of $Ca(OH)_2$ compacts, (8) 286*j*.
effect on photoconductivity of ZnO, (9) 320*b*.
effect on sintering of BeO, (5) 177*f*.
effect on sintering of glass powder compacts, (4) 117*g*.
in furnace atmsophere, effect on one-coat white porcelain enamel, (8) 274*i*.
influence on formation of $Sr_4P_2O_9$ in system SrO-P_2O_5, (11) 386*c*.
and oxygen, reaction on UN, UC, and (UPu)$C_{1-x}O_x$, (1) 12*i*.
role in formation of α-alumina from transient alumina, (1) 36*g*.
Water glass. See *Sodium, silicate.*
Waves, dynamic mode surface, on magnetized YIG and ferrite rods, (9) 310*i*.
elastic-plastic, in glass, (1) 7*a*.
elastic surface, in quartz, attenuation at frequencies of 316 MHz and 1047 MHz, (7) 263*e*.
light, modes of propagating in thin deposited semiconductor films, (10) 344*h*.
longitudinal magnetoelastic, in YIG rods, (6) 232*e*.
micro-, device for heating material, P (8) 287*d*.
micro-, frequency acoustic surface, propagation losses in $LiNbO_3$, (9) 311*a*.
shear, generation at microwave frequencies by epitaxial YIG films on YAG, (4) 111*i*.
shock, pressure, caused by electric discharge, used for forming ceramics, (2) 67*f*.
surface elastic, excitation by transient surface heating, (1) 29*d*.
ultrasonic, parametric amplification, in CdS, (6) 235*e*.

Waves *(continued)*
ultrasonic, velocity and absorption in perovskite-type ferroelectric solid solutions, temperature dependence of, (4) 159*d*.
Wear, abrasive, materials for protection of surfaces against, (1) 1*g*.
behavior, and friction of ceramics-cemented carbide couples, (5) 177*j*.
of magnesia-chrome bricks in sintering zone of rotary cement kilns, (1) 13*d*.
properties, of tungsten carbide and aluminum oxide sintered materials, (1) 13*e*.
resistance, effect of cold-welding between metals and sintered alumina on, (4) 89*h*.
resistance, of TaN-ZrB_2, (8) 278*j*.
of ruby single crystals along plane close to basal plane, (6) 239*e*.
Weathering. See *Frost resistance.*
Weighing. See also *Balances; Thermogravimetry.*
continuous, of powdered or granular materials with weight regulation of flow, apparatus for, P (2) 67*e*.
hydrostatic, for powder density measurement, (8) 285*i*.
weigher, automatic, with rapping means to aid discharge of materials, P (1) 20*c*.
Welding, arc, with ac power and cored electrode, P (6) 207*j*.
cold-, between metals and sintered alumina, effect on wear resistance, (4) 89*h*.
composition, and electrode, P (10) 337*d*.
composition low silica, P (5) 172*a*.
devices, for semiconductors, P (11) 378*i*.
electric arc, core wire for, P (2) 46*d*.
electric arc, process, and coated electrode, P (5) 171*j*.
electrodes. See *Electrodes.*
friction, ceramic to metal, P (4) 118*d*.
with metal back members, and method of forming welded joints in metallic members or between metallic members, P (6) 208*c*.
thermocouples, P (5) 188*i*.
ultrasonic, method and apparatus, P (10) 340*b*.
Wettability, of refractories by molten slag and molten glass, (5) 174*c*.
Wetting, of Al_2O_3, by molten Al and other metals, (10) 363*b*.
apparatus for mixing argillaceous products, P (1) 20*f*.
of binary aluminum alloys in contact with Be, B_4C, and graphite, (6) 207*i*.
of borides and carbides of transition metals, interpretation by electron theory, (7) 267*h*.
of sapphire, by liquid Cu-O alloys, (1) 31*g*.
of SiC surfaces, (5) 203*e*.
silicon nitride, P (1) 18*e*.
Whiskers. See also *Crystals.*
α-Al_2O_3, room and elevated temperature strength, and structural characteristics, (6) 216*c*.
and β-SiC, growing, P (2) 59*c*.
X-ray microtopographs, (7) 270*f*.
Al_2O_3, tension testing, (5) 188*h*.
α-Fe_2O_3, on iron, crystal morphology and growth mechanisms, (4) 130*e*.
α-Fe_2O_3, and twinned platelets, growth, dislocation and grain boundary diffusion in, peculiar to gaseous oxidation, (9) 320*f*.
2H-SiC growth, influence of oxygen, (4) 140*d*,
2H-SiC, growth by screw dislocation process, (9) 308*i*.
MgO-Al_2O_3 spinel, P (10) 343*c*.
$PdCl_2$, preparation and properties, (4) 148*d*.
sapphire, tensile strength at elevated temperatures, (10) 362*g*.
β-SiC, structure, comments, (4) 129*c*.
SiN, vapor deposition preparation, P (4) 107*b*.
Whiteware. See also *Art and Artware; Bodies, ceramic; Bone china; Dielectrics; Dinnerware; Heating elements; Insulators, electrical; Porcelain; Pottery; Tile.*
armor, lightweight, with laminated base member resistant to delamination, P (8) 280*f*.
armor plate, curved, P (8) 280*c*.
bodies, colored, engobes, and glazes, review, (4) 108*d*.
green and fired, and ceramic raw materials, phase composition, quantitative determination, (8) 280*c*.
strength, (2) 60*f*.
closed-cell ceramic article, P (5) 180*a*,
dishwashers, behavior of decorated tableware in, (1) 15*a*.
behavior of porcelain decoration in, (1) 15*c*.
domestic, (1) 15*h*.
industrial and domestic, wear of porcelain decoration in, (1) 15*h*.
industry, Carborundum-Latrobe, (5) 179*h*.
clay preparation plant in, (1) 15*e*.
J. & G. Meakin boosts output, (10) 343*f*.
shrink foil packaging in, (10) 343*f*.
lightweight, P (4) 109*d*.
low density ceramic material for packing fractional distillation columns, (9) 309*i*.
production, program-controlled machine tools for, (2) 60*a*.
Windows. See *Glass.*
Windshields. See *Glass.*
Wire, beader, P (11) 379*c*.
coated with boron nitride and boron, P (9) 304*j*.
core, for electric arc welding, P (2) 46*d*.
filament, for use in cathode of thermionic valve, P (4) 113*d*.
gold, bonded to semiconductor devices, apparatus to sever, P (9) 312*b*.
magnet, high-temperature, P (8) 275*d*.
magnet, high-temperature, and apparatus and

Wire *(continued)*
enamel composition for insulation of, P (8) 275*d*.
metallic, coating with glass, P (9) 304*i*.
micro-, (9) 306*h*.
niobium, niobium stannide coated, P (2) 65*h*.
sintering, by surface diffusion, (1) 39*h*.
terminal, lamp lead, P (5) 175*c*.
Wollastonite, from calcium hydrosilicates, synthesis, (11) 387*j*.
Writing, for professional and technical journals, B (1) 43*a*; B (2) 86*b*.
para-, crystal structure, (6) 231*i*.
Wustite, chromium solubility in, at 1000°C: changes in oxygen activity and lattice parameter, (4) 128*g*.
defect structure model for, (4) 130*h*.
Mn-bearing sintered, nature: II, semiconductive and thermomagnetic properties, (4) 145*g*.

Xenon, trapping, in oxides and halides, effect of bombardment temperature on, (11) 384*d*.
X rays, absorption, for grain size determination, (2) 69*i*.
absorption analysis, for determining particle size, apparatus and process, P (9) 315*h*.
absorption edge measurements, for determination of valence state of Cu in cubic $CuMn_2O_4$, (9) 319*f*.
analysis, advances: Vol. 10, B (1) 40*h*; Vol. 11, B (9) 333*e*,
of glass, (10) 338*e*.
of Indian magnesites, (2) 73*j*.
of Indian magnesites on sintering, (2) 73*i*.
new crystal (clinochlore) for region 5–27 Å, (8) 284*j*.
anomalous diffusion, in semiconductors of blende type, (9) 318*d*.
collimating device wherein plurality of adjustable overlapping leaves define collimating cone, P (9) 316*b*.
data, on fractionated regularly interstratified clay, (8) 300*j*.
determination, of grain size between 10^4 and 10^6 Å, (2) 71*e*.
determination, of thermal expansion of $AgNO_3$, (4) 121*a*.
diffraction, apparatus, and diffraction camera, (2) 70*i*.
apparatus for investigation isothermal transformation kinetics, (6) 225*g*.
contrast of inversion twin boundaries in BeO crystals, (10) 363*d*.
crystal, cryogenic refrigeration for, P (4) 121*f*.
in crystals, apparatus and process for eliminating preferred orientation in, P (4) 121*d*.
for elastic strain measurement in interior of crystalline materials, (9) 315*e*.
for evaluation of quartz in airborne dust, (7) 260*b*.
for expansion measurement at high temperature, (11) 380*g*.
fine-structure, as mineralogical-analytical method, (2) 71*f*.
identification system, computerized, (1) 21*a*.
intensities calculated for random network of vitreous silica, (4) 126*d*.
line intensities, revised for SiC polytypes, (10) 347*d*.
low-angle maximum, due to textural periodicity in heated gibbsite, (8) 294*h*.
method for location of atomic planes relative to piezoelectric crystal surface, P (9) 313*c*.
method for quantitative determination of crystallization in glass, (6) 208*g*.
for showing vitreous nature of new inorganic glasses, (9) 307*i*.
diffraction analysis, of carbonatation of $Ca(OH)_2$, (8) 289*b*.
for determining percentage of compounds in cement clinker, P (6) 206*c*.
of melts, high-temperature furnace for, (2) 69*i*.
quantitative, using clay mineral standards extracted from samples to be analyzed, (7) 260*a*.
diffraction study, of aqueous alkali-metal halide solutions, (4) 164*d*.
of disorder in $MgFe_2O_4$ and $Mg(Cr,Al)O_4$, (5) 203*h*.
of $Ca_3Al_2(O_4D_4)_3$, garnetoid, (5) 197*b*.
on ferrite $Mn_xZn_{1-x}Fe_2O_4$, (9) 333*b*.
high-temperature, of phase transformations in system PrO_x-O_2, (10) 358*d*.
high-temperature, of terbium oxide-oxygen and mixed cerium terbium oxide-oxygen systems, (10) 355*d*.
high-temperature, of zircon-containing glaze frits, (10) 343*d*.
of Jahn-Teller type of tetragonal deformation in spinels $MgGa_{2-x}Mn_xO_4$ and $MgCr_{2-x}$-Mn_xO_4, (10) 363*g*.
multiple, of $Y_3Fe_5O_{12}$, (11) 388*d*.
of olivine solid solution series, (10) 363*e*.
of structure of vapor deposited Ni films on quartz glass, (8) 281*j*.
of system Nb-W-B, (7) 270*f*.
of tetragonal hydrogen bronze H_xWO_3, (4) 164*e*.
diffractometry, for quantitative determination of uncombined MgO in portland cement, (9) 304*b*.
dynamical diffraction effects, of oxide films on Si substrates, (4) 111*i*.

X rays *(continued)*
emission, anomalous, from electrical insulators, (10) 350*e*.
emission analysis, flux-fusion improved technique for, (10) 347*g*.
emission band, Si$K\beta$, for silicates, structural and chemical effects on, (4) 156*d*.
emission band, Al$K\beta$, among Al containing silicates and Al oxides, structural and chemical effects, (11) 387*g*.
emission lines, of elements for common analyzing crystals, angular position of, (9) 318*b*.
fluorescence, for determination of Ar content of sputtered SiO_2 films, (8) 280*i*.
for on-stream analysis, (4) 121*b*.
for quantitative analysis in ceramic industry, (11) 380*e*.
fluorescence analysis, (2) 71*g*.
application of coherent diffusion of Cr$K\alpha$ radiation by light elements to problems of, (7) 259*i*.
application to determination of Ca and Fe, (2) 68*f*.
continuous, of solid component of slurry, P (8) 286*b*.
modern methods, (2) 70*h*.
of powders, preparation of emitters for, (6) 227*a*.
of silica-based materials, comparison with spectrography and chemistry results, (5) 188*d*.
fluorescence apparatus, portable, uses, (11) 380*b*.
fluorescence contact radiographic method, for studying diffusion phenomena in glass, (2) 46*g*.
fluorescence silicate rock analysis, calibration of intensity data for, (8) 289*a*.
investigation, of green mica in khondalite from Auranga Koel Valley, Palamau, Bihar, India, (5) 203*a*.
^{55}Fe K, on LiF for obtaining Debye-Scherrer powder photographs, (5) 193*a*.
$K\alpha_1$, of tin, chemical shift in its oxides, (4) 128*d*.
Kratky small-angle camera, high-temperature sample cell for, (9) 315*g*.
microfluorescence, for analysis of inclusions in glass, (5) 172*e*.
and microstructural study of phase relations during formation of barium-cobalt hexagonal ferrite, $BaCo_2Fe_{16}O_{27}$, (9) 333*a*.
microtopographs, of α-Al_2O_3 whiskers, (7) 270*f*.
moire topography of lattice defects in quartz, (9) 333*b*.
and optical study of alkali feldspar, (6) 239*g*.
phase analysis, for study of initial stages of lithia-alumina-silica glasses crystallization, (1) 9*a*.
photography. See *Photography*.
for quantitative determination of crystalline phases, (6) 226*e*.
roentgenography of double oxide $La_2O_3{\cdot}5Nb_2O_5$, (8) 297*a*.
rotating table, measurements of quartz maxima on, (6) 226*d*.
scattering, Compton, variation with changes in structure of quartz, (4) 163*j*.
scattering study, small angle, of colloidal thorium oxide, (2) 83*d*.
spectrometer. See *Spectrometers*.
stress analysis, of WC-Co cermets: I, procedures; II, temperature stresses, (7) 270*g*.
source and measuring means for backscatter analysis of samples, P (9) 316*a*.
study, of $A_2Sn_2O_7$ stannates, (2) 82*f*.
of atomic scattering factors of TiC components and defect concentration of structure, (1) 40*c*.
of cation-exchanged vermiculite, (7) 270*g*.
of covalent bonding in diamond and silicon, (5) 203*b*.
of electron density distribution in TiC, (6) 240*b*.
of systems CuO-SiO_2 and Cu_2O-SiO_2, (7) 270*g*.
for use in investigation of macrostructure of ceramic antiquities, (6) 206*d*.
window, Be, vacuum seal for, P (4) 122*c*.

Young's modulus. See *Elasticity*.
Ytterbium, dicarbide, vaporization, (5) 203*a*.
optical spectra, in CdF_2, (4) 147*c*.
valences in compounds, (10) 363*c*.
Yb^{3+}, ESR spectra, in $SrCl_2$ single crystals, (6) 232*c*.
spectrum, in $CaWO_4$, by microwave-optical double resonance using circularly polarized light, (5) 197*d*.
in II-VI compounds, EPR, host crystal effects on, (4) 138*i*.
Yttria. See *Yttrium, oxide*.
Yttrium, aluminate, crystals, P (4) 125*a*.
dicarbide, occurrence of superconductivity in, (5) 197*j*.
germanates, influence on polymorphism of ZrO_2, (7) 267*b*.
hydroxide, preparation, and thermal decomposition in nitrogen stream, (8) 296*c*.
iron garnet, single crystal, effect of pressure on homogeneous distribution of Ga in, (11) 384*j*.
oxide, high purity, spectrophotometric determination of Fe in, with 1-(2-pyridylazo)-2-naphthol, (10) 347*g*.
hydrothermal crystal growth, (9) 322*i*.

Yttrium, oxide *(continued)*
polycrystalline, cation self-diffusion in, (4) 128*d*.
polycrystalline, elastic properties, high-temperature measurements, (11) 384*h*.
polycrystalline, elastic properties, room temperature measurements, (10) 352*a*.
rare earths in, determination on basis of luminescence spectra of crystalline phosphors, (2) 75*e*.
retention of additives in, (5) 199*e*.
and vanadate, relaxation processes of Eu^{3+} in, using pulsed cathode-ray excitation, (8) 297*i*.
-Zr dispersions, structure and properties, (10) 361*e*.
oxychalcogenide phosphors, rare earth activated, P (4) 116*e*.
phosphate, polarized spectra and crystal-field parameters of Eu^{3+} in, (9) 327*i*.
phosphate-vanadate, structure and luminescence, (4) 156*h*.
separating from rare earths by ion exchange, P (10) 349*e*.
sesquicarbide, high-pressure synthesis and superconducting properties, (10) 354*j*.
systems. See *Systems*.
tritide-metal tritides, stability, (4) 156*a*.
vanadate, Bi^{3+} and Eu^{3+} activated, energy transfer and fluorescence processes in, (4) 135*i*.
and phosphate, zero-field resonance of Gd^{3+} in, (8) 301*a*.
and yttrium europium vanadate phosphors, bismuth in, (4) 109*f*.
Y^{3+}, as color center in irradiated CaF_2, (11) 388*e*.
$Y_3Al_5O_{12}$, single crystals, strain-free, growth, (7) 266*a*.
$YCrO_3$, weak ferromagnetism, (4) 163*j*.
$Y_3Fe_5O_{12}$, X-ray multiple diffraction study, (11) 388*d*.
$Y_3Mn_{0.1}Fe_{4.9}O_{12}$, magnetic anisotropy and magnetostriction at 300°K, (10) 356*f*.
$Y_{0.85}TaO_3$, lattice parameters, determination, (8) 290*c*.
YVO_4 and YPO_4, determination of parameters for Gd^{3+} in, from variable-frequency EPR, (8) 290*j*.

Zeeman effect, optical, and optical absorption spectrum in $CdWO_4$:Yb^{3+}, (4) 147*g*.
Zeolites, calcined divalent cation faujasite-type, X-ray evidence for residual water in, (5) 203*a*.
contact masses containing, P (9) 317*e*.
crystalline, P (6) 229*f*.
catalyst composite, preparation, P (1) 24*a*; P (6) 230*b*.
containing singly charged nickel cations, P (4) 124*j*.
ion exchange, P (1) 23*j*.
with faujasite-type framework, positions of cations and molecules in: I, dehydrated Ca-exchanged faujasite, (2) 81*i*; II, dehydrated La-exchanged faujasite; III, hydrated Ca-exchanged faujasite, (8) 296*a*; dehydrated La-exchanged faujasite at 420°C, (10) 359*c*.
high purity metal, and product, P (2) 74*e*.
LiX and NaX crystals, adsorption of krypton and xenon, dependence on temperature and pressure, (4) 131*c*.
materials, P (4) 126*b*.
metal-cation-deficient, P (11) 382*g*.
mordenite, hydrogen form, synthetic, preparation, dealuminizing, and ion-exchange properties, (7) 266*a*.
N, P (4) 126*b*.
review, (6) 229*a*.
selective exchange of cation sites in, observed by ESR of Mn(II) ions, (9) 329*d*.
stabilized, P (9) 317*g*.
synthetic, P (2) 61*b*.
X and B factors affecting formation, (5) 192*g*.
Y, krypton as probe of electrostatic fields in, (10) 348*g*.
Zinc, chloride, bromide, and iodide, vaporization characteristics, (10) 363*h*.
chloride-KCl mixtures, molten, coordination states of Ni(II) in, (4) 154*i*.
ferrite, formation by hydrothermal method, (4) 136*c*.
formation kinetics and mechanism, (4) 142*c*.
formation at low temperatures, (7) 266*c*.
germanates and silicates, high pressure transformations in, (4) 138*b*.
in glasses, determination by atomic absorption, (2) 48*e*.
halides, vibrational spectra and thermodynamics, (6) 239*e*.
metaphosphate, surface tension, (8) 299*d*.
-nickel manganites, electrical and magnetic properties, (9) 321*b*.
niobate and tantalate, coordination situation in, (9) 318*i*.
oxide, P (6) 230*e*.
-copper crystals, photoconductive effect, (9) 327*e*.
crystals, maximum efficiency transverse wave, P (7) 258*e*.
crystals, morphology and polarity, (8) 295*j*.
crystals, optical absorption and conduction due to Co^{2+} in, (2) 81*d*.
crystals, photoconductivity decay in oxygen, (4) 149*f*.
crystals, semiconductor, magnetic susceptibility, **(4) 143*j*.**

Zinc, oxide *(continued)*
crystals, structure of paramagnetic lithium center in, (9) 330*c*.
crystals, wurtzite-type, optically active lattice vibrations in, (4) 147*d*.
electrophotographic layers, effect of electric field on space charge density of, (5) 180*i*.
and hydroxide, P (10) 349*d*.
multiphonon infrared absorption in, (4) 145*e*.
optical properties of free electrons in, (4) 147*b*.
photoconductivity, effect of water vapor, (9) 320*b*.
polycrystalline dielectrics, (4) 111*a*.
polycrystalline, VRH approximation and elastic moduli, (5) 203*d*.
production, P (4) 125*f*.
semiconducting, field dependence of ultrasonic attenuation in, (4) 136*f*.
single crystals, growth by vapor phase reaction method, (10) 354*c*.
single crystals, Li-doped, electronic drift mobilities and space-charge-limited currents in, (9) 321*i*.
single crystals, Mn(II)-doped, paramagnetic resonance, (9) 326*a*.
single crystals, vapor phase growth, (6) 239*d*.
solid-state reaction with Fe_2O_3, (9) 311*j*.
and sulfide, crystals, hexagonal, spontaneous polarization, (8) 292*c*.
and sulfide, refractive indices, (10) 359*h*.
and Zn-CdO phosphors, (5) 203*g*.
phosphate, binary, surface tensions and molar volumes, (4) 158*g*.
reproducible diffusion into GaAs, (2) 82*d*.
selenide, crystals, growth and properties, by chemical transport, (9) 322*a*.
infrared transmitting optical elements, P (10) 339*a*.
powder, pure stable, P (10) 349*c*.
single crystals, cathodoluminescence in, scanning electron microscope studies, (5) 199*e*.
-zinc tellurite solid solutions, growth in Te_2 atmosphere, (10) 354*d*.
silicate, Mn-activated, of superior crystallinity, low-temperature synthesis, (4) 143*d*.
sulfide, α-, (sphalerite), nonlinear piezooptic behavior, **(4) 146*g*.**
CdS, and HgS, epitaxial growth on CdS and ZnS, (7) 265*e*.
catalyzed oxidation under acid pressure leaching conditions, (4) 127*g*.
coherent fluorescence from, excited by two-photon absorption, (2) 75*c*.
crystals, cubic, molten flux growth, (10) 357*a*.
crystals, dendritic growth, (6) 231*e*.
crystals, grown from vapor, distribution of stacking faults in, (11) 383*j*.
cubic, growth from molten lead chloride, (2) 77*f*.
cubic, optical absorption of tetrahedral Fe^{2+}($3d^6$) in, (4) 147*h*.
hexagonal, transformation, role of Cu in, (4) 153*g*.
iron-containing, iron-iron interaction in, (1) 31*b*.
hydrothermal crystal growth, (9) 322*i*.
interaction with telluric anhydride, (7) 267*f*.
particle size and morphology: I, influence of precipitating conditions, (4) 148*f*.
selenide, and telluride crystals, synthesis and growth in Ga and In melts, (6) 238*g*.
single crystals, growth from melt at 1850° under Ar pressure of 50 atm, (6) 233*e*.
twist boundaries and rotational slip in, (9) 332*e*.
systems. See *Systems*.
telluride, ion-implanted, type conversion and pn junction formation in, (9) 311*h*.
telluride, single crystals, growth in Zn atmosphere, (7) 266*c*.
Zn(II) hydrolyzed species, absorption-coagulation reactions at ZnO-water interface, (1) 24*i*.
$ZnNH_4PO_4$, two varieties, crystallographic data, (2) 75*i*.
Zn_2PtO_4, synthesis and crystal structure, (10) 362*a*.
ZnSe(Cu,In), effects of ion pair concentration and firing temperature on photoluminescence in, (1) 28*h*.
ZnS_xSe_{1-x} mixed crystals, optical phonons in, (4) 147*j*.
ZnTe and $ZnTe_{1-x}Se_x$, single crystals, growth by temperature gradient solution zoning, (2) 77*h*.
α-$Zn_3(VO_4)_2$, crystal field studies of CO^{2+} in, (1) 26*d*.
Zn_2Y, planar ferrite, magnon analysis of ferromagnetic resonance in, (8) 294*d*.
Zn_2Y, hexagonal ferrite, two-magnon ferrimagnetic resonance line width, (2) 84*d*.
Zircon. See also *Refractories; Zirconium, silicate*.
behavior in contact with molten iron, (11) 372*h*.
dissociation, effect of fireclay and Al in molten steel on, (4) 103*i*.
dissociation, influence of heating temperature and grain size on, (7) 250*e*.
dissolution in molten glasses, (11) 372*i*.
formation, effects of CuO, (8) 291*j*.

Zircon, formation *(continued)*
effects of low melting point impurities, (9) 320*c*.
effects of NH_4VO_3 and NaF, (5) 177*g*.
natural, origin of luminescence in, (4) 147*j*.
as pigment base, (5) 180*b*.
sand, from Kerala beach, mineralogy, metamictization, and suitability as raw material for glaze opacification, (10) 348*j*.
Zirconates, crystallization, under hydrothermal conditions, (8) 290*f*.
of rare-earth elements formed by complex thermoanalysis, (1) 35*b*.
Zirconia. See *Zirconium, oxide.*
Zirconium, behavior, in artificial magmas under diverse *P-T* conditions, (4) 127*e*.
boride, bodies, dense refractory, P (6) 217*j*.
carbide, free carbon determination in, (2) 69*h*.
high-temperature oxidation, (4) 138*e*.
-Ni mixture, hot-pressing, (2) 56*e*.; (6) 215*e*.
nonstoichiometric, statistical thermodynamic method for calculating composition dependence of chemical potentials in, (8) 292*d*.
compounds, thermal decomposition in presence of Al hydroxides, (6) 239*c*.
diboride, borothermic preparation, (5) 192*g*.
crystals, structure and orientation of second phase in, (5) 200*i*.
high-temperature oxidation, (2) 78*g*.
hot-pressed, (2) 56*c*.
mass spectrometry, (1) 32*a*.
sintered, creep at high temperatures, (5) 176*j*.
strength, effect of porosity and grain size, (2) 55*f*.
strength, fracture mode, and thermal stress resistance, (4) 156*c*.
tantalum mononitride-, densification and wear resistance, (8) 278*j*.
dibromide, single crystal, growth and characterization, (9) 322*b*.
dioxide, amorphous, atomic structure, (1) 25*i*.
-base thermoelectric materials, P (9) 314*d*.
and $CaCO_3$ mixture, complex study of processes during heating of, (7) 264*a*.
freezing point measurement with solar furnace, (7) 266*d*.
hypostoichiometric, oxygen-ion diffusivity in, (8) 295*i*.
Zirconium, dioxide *(continued)*
monoclinic, stereographic projection for, (7) 269*i*.
new modifications produced under high pressures, (4) 146*g*.
phase composition, influence on thermal stability, (8) 293*a*.
polymorphism, (1) 35*b*.
polymorphism, influence of additions of GeO_2 and Y and Nd germanates, (7) 267*b*.
radiation damage in, (8) 297*b*.
reaction with Cr_2O_3 in argon plasma, (6) 237*e*.
stabilizing and sintering problems, (4) 105*f*.
structure, monoclinic, lattice parameter variations in mixed oxides with systems ZrO_2-Fe_2O_3, ZrO_2-SnO_2, and ZrO_2-Cr_2O_3, (5) 196*j*.
translucent, preparation at high pressures, (4) 162*d*.
transparent composition, and process, P (6) 218*h*.
hydride, thermal diffusion flux equation for, at high hydrogen contents, (2) 84*g*.
hydrides, containing 4 at.% U, specific heats, thermal diffusivities, and thermal conductivities, (10) 360*h*.
hydroxides, aging, (5) 192*a*.
in mineral rutile, determination with Alizarin Red S, (6) 226*c*.
monoclinic oxides, and solid solutions, optical energy gaps in, (1) 33*h*.
-2.7 wt% Nb alloy, oxidation properties in temperature range 300°–500°C, (4) 148*h*.
nitride, film-thickness determination of N_2 diffusion in, (5) 194*g*.
finely divided nonpyrophoric, preparation, (6) 218*a*.
powders, changes in properties during pressing, (6) 230*i*.
oxidation, in dry oxygen, (4) 136*i*.
influence of thin noble metal films on, (5) 195*c*.
low-pressure, (4) 143*b*.
oxide, crystallization under hydrothermal conditions, (8) 290*f*.
electric fusion crystallization, P (4) 106*d*.
fluorite-type, cubic phases related to, transport phenomena in, (5) 202*j*.
hot-pressing method, P (1) 14*c*.
hypostoichiometric, oxygen diffusion in, in temperature range 875°–1050°C, (4) 148*j*.
Zirconium, oxide *(continued)*
interaction with iron oxide at high temperatures, (9) 323*c*.
monoclinic, oxygen diffusion in, (5) 198*d*.
oxygen-deficient, oxidation, and relation to oxidation of Zr, (1) 34*b*.
porous lightweight bodies, making, P (5) 179*b*.
sintered materials: I, grain growth and phase transition of ZrO_2, (4) 154*a*.
solid stabilized, with layer of Ta_2O_5 and TiO, P (1) 19*a*.
stabilized, tool for metallurgists, (9) 311*c*.
stabilized electrolyte in fuel batteries, (6) 217*j*.
substitution, effect on durability of ZrO_2 soda-silica glass, (10) 337*i*.
thermal expansion, and formation reaction of stabilized ZrO_2, (8) 300*f*.
thermoluminescence, (11) 388*e*.
-oxygen alloy single crystals, plastic deformation in range 77°–950°K, (4) 149*i*.
-O and Zr-Si alloys, kinetics and evaporation mechanisms during electron beam melting of, (9) 309*c*.
oxygen-saturated, oxidation, (2) 83*j*.
phosphates, crystalline, P (4) 124*a*.
phosphate, membranes for intermediate temperature fuel cells, (4) 164*c*.
powder, oxidation kinetics at high temperatures in O_2 and CO_2 atmospheres, (10) 358*f*.
pyrophosphate fluorescent material, (6) 240*a*.
silicate, ground-state splitting of trivalent Gd and Cm in, determined by ESR, (11) 385*c*.
silicate, of particular particle size, dentifrice compositions comprising, P (10) 335*h*.
systems. See *Systems.*
tetrachloride, vapor pressure and heat of sublimation, (8) 300*f*.
values, recovery from ores, P (4) 125*d*.
and Zircaloy-2, preirradiated, oxide growth and capacitance on, (4) 148*i*.
Zn(IV), compounds of Schiff's bases with, (4) 129*j*.
$ZrTe_5O_8$, fusion and vaporization characteristics, (1) 30*e*.
Zone melting, P (6) 228*a*.
of alkaline and rare-earth metal hexaboride rods, (8) 301*a*.
of earth mantel material, in evolution of ocean, (8) 292*d*.
methods and apparatus, P (6) 227*j*.

STANDING COMMITTEES FOR 1969–1970

The American Ceramic Society

Executive

ARTHUR J. BLUME, *chairman (ex officio)*
American Olean Tile Co., Lewisport, Ky. 42351
LORAN S. O'BANNON, Battelle Memorial Institute
JAMES S. OWENS, Champion Spark Plug Co.
J. EARL FRAZIER, Frazier-Simplex, Inc.
W. J. SMOTHERS, Bethlehem Steel Corp., Homer Research Labs.

Trustees Nominating

ARTHUR J. BLUME, *chairman (ex officio)*
American Olean Tile Co., Lewisport, Ky. 42351
LORAN S. O'BANNON, Battelle Memorial Institute
JAMES S. OWENS, Champion Spark Plug Co.

Rules

JOHN S. NORDYKE, *chairman*, 440 Sulgrave Rd.
Pittsburgh, Pa. 15211 (Hammond Lead Products, Inc.)
KENNETH C. LYON, Ball Brothers Corp.
GEORGE H. SPENCER-STRONG, Pemco Ceramics Group
Glidden-Durkee Div., SCM Corp.

Classification, Nomenclature and Standards

WALTER H. GITZEN, *chairman*, One Wesley Dr.
Belleville, Ill. 62223
(Assisted by the chairman of the Classification and Nomenclature Committee of each Division.)

Publications

W. J. SMOTHERS, *chairman*, Bethlehem Steel Corp.
Homer Research Labs., Bethlehem, Pa. 18016
ELBURT F. OSBORN, Pennsylvania State University
SEYMOUR L. BLUM, IIT Research Institute
JAMES P. POOLE, Brockway Glass Co., Inc.
FLOYD A. HUMMEL *(ex officio)* Pennsylvania State University
HERBERT INSLEY *(ex officio)* American Ceramic Society
F. P. REID *(ex officio)* American Ceramic Society

Finance

W. J. SMOTHERS, *chairman*, Bethlehem Steel Corp.
Homer Research Labs., Bethlehem, Pa. 18016
J. EARL FRAZIER, Frazier-Simplex, Inc.
EUGENE E. BRYANT, Ferro Corp.

Classes and Divisions

GILBERT C. ROBINSON, *chairman*, Box 91
Clemson, S. C. 29631 (Clemson University)
(With the presiding officer of each Class and the chairman of each Division.)

Sections

BASIL G. STAPLES, *chairman*, Pfaudler Co.
Div. of Sybron Corp., 1000 West Ave., Rochester, N. Y. 14603
(With the counselor of each active Section.)

Student Branches

JAMES C. WALDAL, *chairman*, 4229 Stalwart Dr.
Palos Verdes Peninsula, Calif. 90274
(Monolithic Dielectrics, Inc.)
RAYMOND J. BROWN
JAMES R. FLOYD, United States Graphite-Engineered Materials

Ross Coffin Purdy Award

WILLIS E. MOODY, *chairman*, Georgia Institute of Technology
School of Ceramic Engineering, Atlanta, Ga. 30332 (1970)
FLOYD A. HUMMEL, Pennsylvania State University (1971)
MERLE D. RIGTERINK, Bell Telephone Labs., Inc. (1972)
ARTHUR L. FRIEDBERG, University of Illinois (1973)
NEILL M. BRANDT, American Optical Corp. (1974)

Orton Memorial Lecture

ROBERT H. INSLEY, *chairman*, Champion Spark Plug Co.
Ceramic Div., 20000 Conner Ave., Detroit, Mich. 48234 (1970)
ALFRED W. ALLEN, University of Illinois (1971)
RICHARD M. FULRATH, University of California (1972)

Honorary Members

PAUL V. JOHNSON, *chairman*, 100 Chestnut Rd.
Severna Park, Md. 21146 (1970)
ELBURT F. OSBORN, Pennsylvania State University (1971)
HOWARD P. BONEBRAKE, (1972)
GEORGE J. BAIR, Corning Glass Works (1973)
JAMES S. OWENS, Champion Spark Plug Co. (1974)

Programs and Meetings

STEPHEN D. STODDARD, *chairman*, 203 Chamisa Ave.
Los Alamos, N. M. 87544 (Los Alamos Scientific Lab.)
WILLIAM R. PRINDLE, Ferro Corp.
WILLIAM B. CAMPBELL, Ohio State University
H. HOWARD LUND, Pomona Pipe Products Co.
F. P. REID *(ex officio)* American Ceramic Society

John Jeppson Award

KENNETH A. BAAB, *chairman*, Bethlehem Steel Corp.
Homer Research Labs., Bethlehem, Pa. 18016 (1970)
WILLARD E. HAUTH, JR., AC Spark Plug Div., General Motors Corp. (1970)
JOHN B. WACHTMAN, JR., National Bureau of Standards (1970)
SAMUEL W. BRADSTREET, Consultant (1971)
PAUL D. MARTINO, Can-Tex Industries (1971)
JAMES P. POOLE, Brockway Glass Co., Inc. (1971)
WILLIAM K. BURRISS, Lavino Div. of International Minerals & Chemical Corp. (1972)
WILLIAM R. JACOBY, Westinghouse Electric Corp. (1972)
WALTER W. PERKINS, Norton Chemical Process (1972)

Membership

CHARLES A. MCFADDEN, *chairman*, Bickley Furnaces, Inc.
550 State Rd., Philadelphia, Pa. 19114
FORREST A. NELSON, A. O. Smith Corp.
JAMES R. FLOYD, United States Graphite-Engineered Materials
JULES J. DUGA, Battelle Memorial Institute

Building Finance

LYLE A. HOLMES, *chairman*, 805 Hutchison Rd.
Flossmoor, Ill. 60422 (International Minerals & Chemical Corp., Industrial Minerals Div.)
EUGENE E. BRYANT, Ferro Corp.
WENDELL P. KEITH, W. P. Keith Co., Inc.
HARRY W. THIEMECKE, Homer Laughlin China Co.